Learning Bidding Strategies for Karma Economies in Realistic Traffic Settings with Multi-Agent Reinforcement Learning

Anastasia Psarou[1,3]   ANASTASIA.PSAROU@UJ.EDU.PL
Kevin Riehl[2]   KEVIN.RIEHL@ETHZ.CH
Matej Jusup[4]   MATEJ.JUSUP@GMAIL.COM
Anastasios Kouvelas[2]   KOUVELAS@ETHZ.CH
Michail A. Makridis[2]   MMAKRIDIS@ETHZ.CH
Rafał Kucharski[1]   RAFAL.KUCHARSKI@UJ.EDU.PL

[1] *Jagiellonian University, Krakow, Poland* [2] *ETH Zürich, Institute for Transport Planning and Systems (IVT), Switzerland* [3] *Doctoral School of Exact and Natural Sciences, Jagiellonian University, Krakow, Poland* [4] *Independent researcher, Zurich, Switzerland*

Abstract

Karma is a non-monetary resource-allocation mechanism that prioritizes users' needs rather than their financial power. Monetary pricing can effectively reduce congestion by imposing charges on specific road segments, but it may be unfair by favoring higher-income individuals. Prior work has shown that in this context, Karma can achieve similar efficiency while yielding fairer outcomes; however, it has been demonstrated only in a deterministic setting. Demonstrating Karma's applicability under more realistic traffic conditions is therefore important for real-world implementation. Additionally, experimental evidence suggests that humans may struggle to execute optimal bidding strategies in Karma economies. In this paper, we demonstrate the use of Multi-Agent Reinforcement Learning (MARL) to train automated bidding agents for travelers. In a microscopic traffic simulation case study, we show that MARL agents learn effective bidding strategies that yield fairer travel outcomes for drivers than those achieved under monetary pricing schemes[1].

Keywords: Karma, fairness, monetary segment pricing, multi-agent systems, multi-agent reinforcement learning, traffic simulation.

1. Introduction

Traffic congestion is a major issue in urban road networks, resulting in substantial travel time losses. To reduce congestion and incentivize travelers to choose alternative routes cities often price specific road segments [6]. While such a mechanism can improve traffic efficiency, it may raise significant equity concerns in societies with uneven income and wealth distributions, as it tends to favor those who can afford to pay while disadvantaging others, thereby exacerbating social inequality. As a result, the implementation of monetary segment pricing is often impeded by public opposition and lower user acceptance [9].

Karma is a resource allocation mechanism that uses an artificial, non-tradable currency and allocates resources based on users' needs rather than their financial means. Originally introduced in the context of file-sharing networks, Karma has since been studied in a wide range of domains [14].

---

1. Code and resources are available at: https://github.com/AnastasiaPsarou/Karma-bidding-agents-workshop.

In transport pricing, prior work has demonstrated that Karma can serve as a fairer alternative to monetary pricing [13]. However, this work assumed deterministic travel times and decision-making at the beginning of the day, whereas real-world travel conditions require more complex constraints, such as variations in departure times [2] and stochastic travel-time variability [4].

In this work, we model daily commuting under non-deterministic, i.e., microscopic, traffic dynamics as a repeated congestion game [10], where individuals travel from their homes (origins) to their workplaces (destinations) at different times over many days. Our experiments are conducted leveraging a complex, microscopic traffic simulation tool (SUMO [12]) that captures the real-world complexity of road transportation. We consider a setting with 300 vehicles and a network in which the fastest route between the origin and destination has limited capacity and becomes congested when about one-third of the vehicles use it. Within this urban framework, our aim is to evaluate the implementation of monetary and Karma pricing mechanisms, assessing their relative efficacy in achieving system-optimal travel times and their respective impacts on fairness in the population travel times.

To find optimal solutions in Karma games, prior works have used optimization methods, including fixed-point computation, the momentum method [3], and evolutionary dynamics-inspired algorithms [13]. The choice of method is important because Karma games can involve large state spaces, and this is further amplified in our setting by microscopic traffic dynamics. In addition, learning optimal bidding strategies in Karma economies can be challenging for human users. Experimental evidence indicates that, although a population of human bidders achieves aggregate outcomes superior to random allocation, they still do not reach the theoretical Nash equilibrium solution [8]. This suggests that users may need AI-aided bidding agents to make decisions on their behalf, much as navigation applications help travelers select routes. These considerations motivate the use of MARL for learning bidding strategies in repeated, microscopic environments where multiple agents compete for limited resources. MARL has already been applied to study vehicles' routing decisions [1, 18] and to learn bidding strategies in auction settings [11].

In this work, MARL agents represent simulated commuters who repeatedly travel in a microscopic traffic environment. Under the Karma mechanism, agents learn a policy that maps their observed state to a bid. In a city employing a Karma scheme, the learned policy can be interpreted as a decision rule that mobility providers could deploy, for example, through a navigation app, to suggest bids to real commuters.

The main research contributions of this work are as follows.

- We demonstrate that multi-agent reinforcement learning (MARL) can effectively be used to learn efficient bidding strategies in Karma economies for road segment pricing.

- We show that MARL agents trained under both Karma and monetary road-pricing schemes equally well mitigate traffic congestion.

- We show that Karma pricing yields fairer outcomes than monetary pricing across four measures that reflect different notions of fairness.

2. Methodology

We consider a sequential decision-making process in which individuals commute once per day from home to work in a city operating under either a monetary or a Karma pricing scheme, making

decisions in order of their departure times. We model this problem as an Agent Environment Cycle (AEC) game [16]. We use the terms agents, individuals, and commuters interchangeably for the simulated commuter entities. Each agent is assigned an income value, a day-specific urgency, and departure time.

At their own departure time, agents receive an observation from the environment and select an action. They then travel through the SUMO traffic network, and their experienced travel times are recorded, which are part of their reward (cost) that their policy aims to maximize. Our RL environment is based on the RouteRL framework [1], which models vehicle routing decisions using MARL. We extend it by modifying agents' reward functions and introducing bidding and auction mechanisms.

We model the Karma route allocation to be determined through a Stackelberg auction, where the city acts as the leader and travelers as followers. The city first computes route prices that induce a system-optimal allocation among the routes, i.e., an assignment that minimizes total travel time [13]. Travelers then submit bids before their departure in response to these centrally defined prices [19]. This mechanism, unlike first- or second-price auctions used in previous works [13], allows individuals to bid just before departure rather than requiring all bids to be submitted at the beginning of the day. Therefore, an agent is assigned to the fastest route if their bid exceeds the centrally defined price for that route. Otherwise, the assignment proceeds to the next-best route by comparing the submitted bid with the corresponding threshold, and this process continues iteratively until a route is allocated. The minimum bids (prices) to get access to the preferred routes are assumed to remain fixed over time.

In both pricing schemes, agents make bidding decisions after receiving an observation from the environment (o_i^d). The observations (see Equation 1) include the historical travel times ($h_{i,d}$) over the previous μ days, and agent-specific information, such as the income (β_i), departure time $dt_{i,d}$, urgency ($u_{i,d}$) and Karma balance ($k_{i,d}$) of a commuter i on a day d.

$$o_i^d = \left[\underbrace{(h_{i,d})}_{\text{historical travel times}} \mid \underbrace{u_{i,d}, \ \beta_i, \ dt_{i,d}, \ k_{i,d}}_{\text{agent-specific information}} \right] \tag{1}$$

They then submit bids for each route x subject to their available Karma balance, with all agents starting on day one with the same initial endowment of Karma points. Once an agent is assigned to route x, the bid submitted for that route is deducted from their Karma balance and, at the end of the day, equally redistributed to all the users in the city.

Before the next round (day), agents evaluate outcomes of their choices by observing their rewards, representing their total experienced costs:

$$r_{i,d}(x) = -c(x) - \beta_i \times u_{i,d} \times \tilde{t}_{i,d}(x), \tag{2}$$

comprising their monetary costs $c(x)$, and the realized (experienced) travel time $\tilde{t}_{i,d}(x)$. Travel time is weighted with its value, being a product of their current urgency $u_{i,d}$ and the income β_i. In both the monetary and Karma pricing scenarios, agents aim to maximize their reward. Under the monetary pricing scheme, $c(x)$ is fixed, and β_i reflects the income distribution within the population. Under Karma pricing scheme, $c(x)$ is always zero. Therefore in the monetary pricing wealthy agents may buy priority with their high monetary budgets, whereas in Karma agents have equal power to supply their urgency, independent of monetary budgets.

MARL. We train our agents using the Independent Proximal Policy Optimization (IPPO) algorithm, which has shown strong benchmark performance in a variety of tasks [7]. Since our setting involves 300 agents, scalability is important. Parameter sharing, where agents update a single shared neural network, can improve scalability [5] but can hinder convergence in complex environments and limit the ability to capture heterogeneity across agents. We therefore use hypernetworks, which generate agent-specific weights while decoupling observation-driven and agent-conditioned gradients, and train agents with IPPO with hypernetworks [17]. The algorithm's hyperparameters are listed in Appendix C.

Fairness. We compare and evaluate the monetary, Karma pricing, SO, and UE solutions using several notions of quantitative fairness [15]. These fairness measures are computed with respect to a quantity X, which may correspond to different formulations of an agent's travel time, or reward. Specifically:

- **Harsanyian fairness**, evaluates fairness by the average welfare across individuals. It is given by:

$$F_{\text{hars}} = \frac{1}{R} \sum_{r=1}^{R} \left[\frac{1}{N} \sum_{i=1}^{N} \left(\frac{1}{K^{(r)}} \sum_{d=1}^{K^{(r)}} \left(X_{i,d}^{(r)} \right) \right) \right], \tag{3}$$

   where R is the number of replications, N is the number of agents, $K^{(r)}$ is the number of days in replication r, $X_{i,d}^{(r)}$ is the travel time or reward of an agent i on a day (training iteration) d.

- **Utilitarian fairness** favors decisions that maximize aggregate welfare at the population level, even if some individuals are disadvantaged. It is given by:

$$F_{\text{util}} = \frac{1}{R} \sum_{r=1}^{R} \left(\frac{1}{K^{(r)}} \sum_{d=1}^{K^{(r)}} \sum_{i=1}^{N} X_{i,d}^{(r)} \right). \tag{4}$$

- **Rawlsian fairness**, evaluates fairness by the welfare of the least advantaged individual. In our setting, we quantify it using the maximum delay experienced in the system, given by:

$$F_{\text{rawls}} = \frac{1}{R} \sum_{r=1}^{R} \max_{i \in \{1,...,N\}} \left[\max_{d \in \{1,...,K^{(r)}\}} \left(X_{i,d}^{(r)} \right) \right]. \tag{5}$$

- **Egalitarian fairness**, emphasizes equality of outcomes across individuals. We evaluate it with the standard deviation of agents' average travel times and the Gini coefficient of travel times below:

$$F_{\text{egal(std)}} = \frac{1}{R} \sum_{r=1}^{R} \sqrt{\frac{1}{N-1} \sum_{i=1}^{N} \left(\bar{X}_i^{(r)} - \bar{X}^{(r)} \right)^2}, \tag{6}$$

   where $\bar{X}_i^{(r)}$ is the average travel time of an agent i among K days and $\bar{X}^{(r)}$ is the overall average travel time across agents in replication r.

$$F_{\text{egal(gini)}} = \frac{1}{R} \sum_{r=1}^{R} \frac{\sum_{i=1}^{N} \sum_{b=1}^{N} \left| \bar{X}_i^{(r)} - \bar{X}_b^{(r)} \right|}{2N^2 \left(\frac{1}{N} \sum_{i=1}^{N} \bar{X}_i^{(r)} \right)}. \tag{7}$$

Table 1: Reward parameterization of agent attributes under monetary and karma pricing schemes.

Agent attributes	Monetary pricing (without urgency)	Monetary pricing (with urgency)	Karma pricing
Income (β_i)	Heterogeneous	Heterogeneous	Uniform (0.1 for all)
Urgency ($u_{i,d}$)	Uniform (one for all)	Heterogeneous	Heterogeneous
Resource cost ($c(x)$)	Fixed	Fixed	Zero

We model two variants of the monetary pricing setting, which differ in whether commuter urgency is incorporated into the reward formulation. In the first (*monetary pricing without urgency*), the commuters' urgency is not taken into account and is set to 1 for all individuals. In the second (*monetary pricing with urgency*), urgency is derived from the population distribution, as in the Karma pricing setting (see Table 1). The purpose of considering these two variants is to examine whether incorporating urgency into monetary pricing improves equity outcomes, and whether the non-monetary Karma mechanism can deliver fairness benefits beyond those achieved by urgency-aware monetary pricing.

The traffic network used to study this problem is depicted in Appendix 3. It has one origin-destination pair connected by three alternative routes. In addition, each experiment is repeated 5 times, with different random seeds. Following that, when the monetary fee or the minimum bid to get assigned to a route is properly tuned, the system travel times can approach the system-optimal solution [13], we have tuned the prices on Routes 1 and 2 to reach the system-optimal route allocation for all the scenarios discussed in Table 1. For Karma, we apply a price of $c(1) = 4$ to Route 1 and $c(2) = 3$ to Route 2. For *monetary pricing with urgency* $c(1) = 1.5$ and $c(2) = 0.8$, and *monetary pricing without urgency* $c(1) = 0.9$ and $c(2) = 0.65$.

We model each MARL episode as lasting 30 days, after which all agents' Karma balances are reinitialized (to 5 Karma points). This prevents excessive concentration of Karma points among a small subset of agents. It is also motivated by an analogy to a monthly budget cycle, in which individuals periodically reassess how they have used their available resources. Historic travel times are computed over the last 10 days ($\mu = 10$) and defined for each agent as the average travel time on each route observed among individuals departing within a 20-simulation-step window before that agent. The income of the agents is drawn from the European income distribution reported in the World Inequality Report[2], and the urgency is drawn from a geometric distribution with parameter $p = 0.6$ following [13]. The population distributions of hourly salary, urgency, and value of time are depicted in Appendix B. We consider two baseline scenarios: the approximated System-Optimal and User-Equilibrium solutions. In the latter, the agents choose the fastest route based on historical travel times.

---

2. Derived from https://wir2022.wid.world/methodology.

Figure 1: **Learning outcomes of congestion pricing.** a) Monetary and Karma pricing achieve similar average system travel times that are substantially lower than in the User Equilibrium (UE) case and close to the approximated System Optimum (SO) solution. Circles denote individual replications, rhombus the mean travel time across replications, and orange lines the median travel time. b) During training, the average agent reward increases and then stabilizes, suggesting that the MARL agents reached a stable solution. U denotes *monetary pricing with urgency* and WU *monetary pricing without urgency* (see Table 1).

3. Results and discussion

Both monetary and Karma pricing reduce congestion, achieving average system travel times close to the SO solution, shown in Figure 1a. In Figure 1b, the average system rewards increase during training and then stabilize, suggesting that the MARL algorithms reached to stable policies. Figure 2a shows that *monetary pricing without urgency* can be unfair, as it favors individuals with higher Value of Time (VoT), who experience lower travel times. This decreasing trend in travel time across VoT bins is less evident under *monetary pricing with urgency*, suggesting that incorporating urgency mitigates some of the inequity associated with VoT-based monetary pricing. Under Karma, however, travel times remain nearly constant across VoT bins. Figure 2b shows that agents with higher urgency experience lower average travel times under the Karma pricing mechanism.

Table 2 compares Karma and monetary pricing schemes across the fairness ideologies, discussed in Section 2. Statistical significance of these values is presented in D. We evaluate fairness in different quantities, including agent travel time, travel time weighted by urgency, and travel time weighted by VoT. The Harsanyian and Rawlsian fairness measures are quantified using the agent's experienced average delay, defined as the difference between the agent's experienced travel time and the free-flow travel time for the Route they travel. The results show that, under the travel-time and urgency-weighted quantities, Karma yields lower fairness measures than monetary pricing, indicating fairer outcomes. *Monetary pricing with urgency* also appears to improve fairness relative to *monetary pricing without urgency*, as reflected by lower fairness-measure values. Under the VoT-weighted quantity, monetary pricing yields higher fairness values than Karma, since VoT depends on

agents' income. Overall, these findings indicate Karma's potential as an efficient and fair congestion management mechanism.

Figure 2: **Average travel times by urgency and Value-of-Time quintile.** (a) Under *monetary pricing (without urgency)*, average travel times drops as the VoT quantile increases, whereas under Karma and *monetary pricing (urgency)*, they remain nearly constant across quantiles. (b) Under both Karma and *monetary pricing (urgency)*, average travel times decrease as urgency increases; however, this pattern is more pronounced under Karma pricing. Shaded areas represent the standard deviation across replications.

Table 2: Fairness measures across scenarios.

	Fairness Measures	System optimum	Monetary Pricing (without urgency)	Monetary Pricing (urgency)	Karma Pricing	User equilibrium
Travel time	Egalitarian (std)	-	1.55 (0.32)	1.31 (0.05)	**1.21 (0.07)**	1.41 (0.06)
	Egalitarian (gini)	-	0.030 (0.006)	0.026 (0.001)	**0.024 (0.001)**	0.026 (0.001)
	Utilitarian	8374.00 (36.02)	8660.79 (209.44)	8577.05 (121.43)	**8536.88 (86.72)**	9072.49 (52.09)
Delay	Rawlsian	-	29.51 (1.00)	28.89 (0.73)	**28.40 (0.60)**	31.19 (0.60)
	Harsanyian	-	25.33 (0.75)	25.17 (0.50)	**25.07 (0.36)**	27.33 (0.18)
Travel time × Urgency	Egalitarian (std)	-	0.47 (0.06)	0.44 (0.05)	**0.43 (0.07)**	1.05 (0.09)
	Egalitarian (gini)	-	0.055 (0.005)	0.053 (0.004)	**0.051 (0.005)**	0.060 (0.002)
	Utilitarian	-	1433.64 (94.57)	1418.74 (70.47)	**1415.95 (97.64)**	2922.44 (165.07)
	Rawlsian	-	6.27 (0.63)	6.09 (0.49)	**6.04 (0.60)**	13.28 (0.93)
	Harsanyian	-	4.78 (0.32)	4.73 (0.23)	**4.72 (0.33)**	9.74 (0.55)
Travel time × VoT	Egalitarian (std)	-	**59.24 (7.10)**	59.49 (5.51)	60.73 (7.92)	124.77 (14.16)
	Egalitarian (gini)	-	**0.436 (0.016)**	0.438 (0.016)	0.444 (0.017)	0.442 (0.019)
	Utilitarian	-	19486.74 (1487.36)	**19358.60 (1111.51)**	19382.59 (1578.18)	40022.68 (2620.85)
	Rawlsian	-	**388.91 (42.33)**	396.42 (38.86)	410.85 (39.07)	844.73 (86.76)
	Harsanyian	-	64.96 (4.96)	**64.53 (3.71)**	64.61 (5.26)	133.41 (8.74)

References

[1] Ahmet Onur Akman, Anastasia Psarou, Łukasz Gorczyca, Zoltán György Varga, Grzegorz Jamróz, and Rafał Kucharski. Routerl: Multi-agent reinforcement learning framework for urban route choice with autonomous vehicles. *SoftwareX*, 31:102279, 2025. ISSN 2352-7110. doi: 10.1016/j.softx.2025.102279.

[2] Chandra R. Bhat and Frank S. Koppelman. *Activity-Based Modeling of Travel Demand*, pages 35–61. Springer US, Boston, MA, 1999. ISBN 978-1-4615-5203-1. doi: 10.1007/978-1-4615-5203-1_3.

[3] Andrea Censi, Saverio Bolognani, Julian G. Zilly, Shima Sadat Mousavi, and Emilio Frazzoli. Today me, tomorrow thee: Efficient resource allocation in competitive settings using karma games. In *2019 IEEE Intelligent Transportation Systems Conference (ITSC)*, pages 686–693, 2019. doi: 10.1109/ITSC.2019.8916911.

[4] Peng Chen, Rui Tong, Guangquan Lu, and Yunpeng Wang. Exploring travel time distribution and variability patterns using probe vehicle data: case study in beijing. *Journal of Advanced Transportation*, 2018(1), 2018. doi: 10.1155/2018/3747632.

[5] Filippos Christianos, Georgios Papoudakis, Arrasy Rahman, and Stefano V. Albrecht. Scaling multi-agent reinforcement learning with selective parameter sharing. In *International Conference on Machine Learning (ICML)*, 2021.

[6] André de Palma and Robin Lindsey. Traffic congestion pricing methodologies and technologies. *Transportation Research Part C: Emerging Technologies*, 19(6):1377–1399, 2011. ISSN 0968-090X. doi: 10.1016/j.trc.2011.02.010.

[7] Christian Schröder de Witt, Tarun Gupta, Denys Makoviichuk, Viktor Makoviychuk, Philip H. S. Torr, Mingfei Sun, and Shimon Whiteson. Is independent learning all you need in the starcraft multi-agent challenge? *CoRR*, abs/2011.09533, 2020.

[8] Ezzat Elokda, Saverio Bolognani, Florian Dörfler, and Heinrich H. Nax. Dynamic resource allocation with karma: An experimental study. *arXiv preprint arXiv:2404.02687*, 2026. doi: 10.48550/arXiv.2404.02687.

[9] Ziyuan Gu, Zhiyuan Liu, Qixiu Cheng, and Meead Saberi. Congestion pricing practices and public acceptance: A review of evidence. *Case Studies on Transport Policy*, 6(1):94–101, 2018. ISSN 2213-624X. doi: 10.1016/j.cstp.2018.01.004.

[10] Ron Holzman and Nissan Law-Yone. Strong equilibrium in congestion games. *Games and Economic Behavior*, 21(1):85–101, 1997. ISSN 0899-8256. doi: 10.1006/game.1997.0592.

[11] Yudong Hu, Congying Han, Tiande Guo, and Hao Xiao. Applying opponent modeling for automatic bidding in online repeated auctions. In *Proceedings of the 23rd International Conference on Autonomous Agents and Multiagent Systems*, AAMAS '24, page 843–851, 2024. ISBN 9798400704864. doi: 10.5555/3635637.3662938.

[12] Pablo Alvarez Lopez, Michael Behrisch, Laura Bieker-Walz, Jakob Erdmann, Yun-Pang Flötteröd, Robert Hilbrich, Leonhard Lücken, Johannes Rummel, Peter Wagner, and Evamarie Wießner. Microscopic traffic simulation using SUMO. In *The 21st IEEE International Conference on Intelligent Transportation Systems*. IEEE, 2018. doi: 10.1109/ITSC.2018.8569938.

[13] Kevin Riehl, Anastasios Kouvelas, and Michail A. Makridis. Karma economies for sustainable urban mobility – a fair approach to public good value pricing. *npj Sustainable Mobility and Transport*, 1:14, 2024. doi: 10.1038/s44333-024-00014-4.

[14] Kevin Riehl, Anastasios Kouvelas, and Michail A. Makridis. Resource allocation with karma mechanisms—a review. *Economies*, 12(8), 2024. ISSN 2227-7099. doi: 10.3390/economies12080211.

[15] Kevin Riehl, Anastasios Kouvelas, and Michail A. Makridis. Quantitative fairness—a framework for the design of equitable cybernetic societies. *Computers in Human Behavior: Artificial Humans*, 6:100236, 2025. ISSN 2949-8821. doi: 10.1016/j.chbah.2025.100236.

[16] J. K. Terry, Benjamin Black, Nathaniel Grammel, Mario Jayakumar, Ananth Hari, Ryan Sullivan, Luis Santos, Rodrigo Perez, Caroline Horsch, Clemens Dieffendahl, Niall L. Williams, Yashas Lokesh, and Praveen Ravi. Pettingzoo: Gym for multi-agent reinforcement learning, 2021.

[17] Kale-ab Abebe Tessera, Arrasy Rahman, Amos Storkey, and Stefano V Albrecht. Hypermarl: Adaptive hypernetworks for multi-agent rl. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025. doi: 10.48550/arXiv.2412.04233.

[18] Luiz A. Thomasini, Lucas N. Alegre, Gabriel O. Ramos, and Ana L. C. Bazzan. Route-choiceenv: a route choice library for multiagent reinforcement learning. In *Adaptive and Learning Agents Workshop at AAMAS*, 2023.

[19] Heinrich von Stackelberg. *Market Structure and Equilibrium*. Number 978-3-642-12586-7 in Springer Books. Springer, none edition, January 2011. doi: 10.1007/978-3-642-12586-7.

Appendix A. Case study network

Figure 3: **Case study network.** Left: Traffic network. Right: Mean travel time at the final simulation timestep for different numbers of vehicles.

Appendix B. Population-level distributions of hourly salary, urgency, and value of time

Figure 4: **Population-level distributions of simulated commuter attributes.** Panels (a)–(c) show the distributions of hourly income, urgency, and value of time among the simulated agents. The dashed line represents the median of each distribution. Panel (d) shows the monthly income distribution per adult from which commuter incomes are sampled. The income distribution contains 800 entries and is expressed in euros at purchasing power parity (PPP) on a logarithmic scale. The PPP adjustment accounts for differences in living costs across countries, converting incomes into a common unit that better reflects real purchasing power.

Appendix C. MARL algorithm hyperparameters

Table 3: Hyperparameters used in the experiments for both the karma and monetary pricing scenarios.

Parameter	Value
PPO-specific parameters	
Discount factor (γ)	0.99
GAE parameter (λ)	0.95
PPO clipping parameter (ϵ)	0.20
Entropy coefficient	0.001
Value loss coefficient	0.50
Learning parameters	
Learning rate	8×10^{-4}
Optimizer	Adam
Epochs	4
Minibatch size	4096
Maximum gradient norm	0.5
Hypernetwork architecture	
Embedding dimension	32
Hypernetwork hidden dimensions	$(64, 64)$
Target activation	tanh
Target network architecture	
Actor layers	$(64, 64)$
Critic layers	$(64, 64)$
Entropy scheduling	
Entropy schedule	linear
Initial entropy coefficient	0.01
Final entropy coefficient	0.00

Appendix D. Statistical Significance of Fairness Differences

Table 4: Pairwise t-test p-values comparing Karma pricing with monetary pricing scenarios. Bold values indicate statistical significance at the 5% level.

	Fairness Measures	Karma vs. Monetary Pricing (without urgency)	Karma vs. Monetary Pricing (urgency)
Travel time	Egalitarian (std)	**0.020**	**0.038**
	Egalitarian (gini)	**0.028**	**0.040**
	Utilitarian	0.169	0.502
Delay	Rawlsian	**0.030**	0.218
	Harsanyian	0.424	0.701
Travel time × Urgency	Egalitarian (std)	0.364	0.755
	Egalitarian (gini)	0.214	0.574
	Utilitarian	0.756	0.957
	Rawlsian	0.523	0.879
	Harsanyian	0.756	0.957
Travel time × VoT	Egalitarian (std)	0.742	0.770
	Egalitarian (gini)	0.427	0.587
	Utilitarian	0.909	0.977
	Rawlsian	0.365	0.533
	Harsanyian	0.909	0.977