🏠 ProcTHOR: Large-Scale Embodied AI Using Procedural Generation

Abstract

Massive datasets and high-capacity models have driven many recent advancements
in computer vision and natural language understanding. This work presents a plat-
form to enable similar success stories in Embodied AI. We propose PROCTHOR, a
framework for procedural generation of Embodied AI environments. PROCTHOR
enables us to sample arbitrarily large datasets of diverse, interactive, customizable,
and performant virtual environments to train and evaluate embodied agents across
navigation, interaction, and manipulation tasks. We demonstrate the power and
potential of PROCTHOR via a sample of 10,000 generated houses and a simple
neural model. Models trained using only RGB images on PROCTHOR, with no
explicit mapping and no human task supervision produce state-of-the-art results
across 6 embodied AI benchmarks for navigation, rearrangement, and arm manipu-
lation, including the presently running Habitat 2022, AI2-THOR Rearrangement
2022, and RoboTHOR challenges[1]. We also demonstrate strong 0-shot results
on these benchmarks, via pre-training on PROCTHOR with no fine-tuning on the
downstream benchmark, often beating previous state-of-the-art systems that access
the downstream training data.

1   Introduction

Computer vision and natural language processing models have become increasingly powerful through
the use of large-scale training data. Recent models such as CLIP [35], DALL-E [37], GPT-3 [5], and
Flamingo [4] use massive amounts of task agnostic data to pre-train large neural architectures that
perform remarkably well at downstream tasks, including in zero and few-shot settings. In comparison,
the Embodied AI (E-AI) research community predominantly trains agents in simulators with far
fewer scenes [36, 24, 13]. Due to the complexity of tasks and the need for long planning horizons, the
best performing E-AI models continue to overfit on the limited training scenes and thus generalize
poorly to unseen environments.

In recent years, E-AI simulators have become increasingly more powerful with support for physics,
manipulators, object states, deformable objects, fluids, and real-sim counterparts [24, 40, 41, 18, 51],
but scaling them up to tens of thousands of scenes has remained challenging. Existing E-AI
environments are either designed manually [24, 18] or obtained via 3D scans of real structures
[40, 36]. The former approach requires 3D artists to spend a significant amount of time designing 3D
assets, arranging them in sensible configurations within large spaces, and carefully configuring the
right textures and lighting in these environments. The latter involves moving specialized cameras

---

[1]Based on publicly viewable results on May 19 '22 05:00 PM UTC – 3 hours prior to NeurIPS deadline

Figure 1: We propose PROCTHOR, a framework to procedurally generate a large variety of diverse, interactable, and customizable houses.

through many real-world environments and then stitching the resulting images together to form 3D reconstructions of the scenes. These approaches are not scalable, and expanding existing scene repositories multiple orders of magnitude is not practical.

We present PROCTHOR, a framework built off of AI2-THOR [24], to procedurally generate fully-interactive, physics-enabled environments for E-AI research. Given a room specification (e.g., a house with 3 bedrooms, 3 baths, and 1 kitchen), PROCTHOR can produce a large and diverse set of floorplans that meet these requirements (Fig. 1). A large asset library of 108 object types and 1633 fully interactable instances is used to automatically populate each floorplan, ensuring that object placements are physically plausible, natural, and realistic. One can also vary the intensity and color of lighting elements (both artificial lighting and simulated skyboxes) in each scene, to simulate variations in indoor lighting and the time of the day. Assets (such as furniture and fruit) and larger structures such as walls and doors can be assigned a variety of colors and textures, sampled from sets of plausible colors and materials for each asset category. Together, the diversity of layouts, assets, placements, and lighting leads to an arbitrarily large set of environments – allowing PROCTHOR to scale orders of magnitude beyond the number of scenes currently supported by present-day simulators. In addition, PROCTHOR supports dynamic material randomizations, whereby colors and materials of individual assets can be randomized each time an environment is loaded into memory for training. Importantly, in contrast to environments produced using 3D scans, scenes produced by PROCTHOR contain objects that both support a variety of different object states (*e.g.* open, closed, broken, *etc.*) and are fully interactive so that they can be physically manipulated by agents with robotic arms. We also present ARCHITECTHOR, a 3D artist-designed set of 10 high quality fully interactable houses, meant to be used as a test-only environment for research within household environments. In contrast to AI2-iTHOR (single rooms) and RoboTHOR (lesser visual diversity) environments, ARCHITECTHOR contains larger, diverse, and realistic houses.

We demonstrate the ease and effectiveness of PROCTHOR by sampling an environment of 10,000 houses (named PROCTHOR-10K), composed of diverse layouts ranging from small 1-room houses to larger 10-room houses. We train agents with very simple neural architectures (CNN+RNN) – *without* a depth sensor, and instead only employing RGB channels, with no explicit mapping and no human task supervision – on PROCTHOR-10K and produce state-of-the-art (SoTA) models on several navigation and interaction benchmarks including (1) **RoboTHOR ObjectNav Challenge** [3] – Our 0-shot performance is superior to the previous best model which uses RoboTHOR training scenes, and fine-tuning improves this more; (2) **Habitat ObjectNav Challenge 2022** [1] – Top of the leaderboard, as of the submission deadline with 6% Success improvement over the next best submission; (3) **1-phase Rearrangement Challenge 2022** [2] – Top of the leaderboard, as of the submission deadline with Prop Fixed Strict improving from 0.19 to 0.245; (4) **AI2-iTHOR ObjectNav** – Our 0-shot numbers already outperform a previous model that trains on AI2-iTHOR with fine-tuning achieving Success up to 77.5%; (5) **ArmPointNav** [17] – Our 0-shot numbers beat previous SoTA results when using RGB; and (6) **ArchitecTHOR ObjectNav** – A large Success improvement from 18.5% to 31.4%. Finally, an ablation analysis clearly shows the advantages of scaling up from 10 to 100 to 1K and finally to 10K scenes and indicates that further improvements can be obtained by invoking PROCTHOR to produce even larger environments.

In summary, our contributions are (1) PROCTHOR, a framework that allows for the performant procedural generation of an unbounded number of diverse, fully-interactive, simulated environments, (2) ARCHITECTHOR, a new, 3D artist-designed set of houses for E-AI evaluation, and (3) SoTA results across six E-AI benchmarks covering manipulation and navigation tasks, including strong 0-shot results. PROCTHOR will be open-sourced and the code used in this work will be released.

2 Related Work

Embodied AI platforms. Various Embodied AI platforms have been developed over the past several years [24, 40, 41, 51, 18, 49]. These platforms target different design goals. AI2-THOR [24] and its variants (ManipulaTHOR [17] and RoboTHOR [13]) are built in the Unity game engine and focus on agent-object interactions, object state changes, and accurate physics simulation. Unlike AI2-THOR, Habitat [40] provides scenes constructed from 3D scans of houses, however, objects and scenes are not interactable. A more recent version, Habitat 2.0 [43], introduces object interactions at the expense of being limited to one floorplan and synthetic scenes. iGibson [41] includes photo-realistic scenes, but with limited interactions such as pushing. iGibson 2.0 [26] extends iGibson by focusing on household tasks and object state changes in synthetic scenes and includes a virtual reality interface. ThreeDWorld [18] targets high-fidelity physics simulation such as liquid and deformable object simulation. VirtualHome [34] is designed for simulating human activities via programs. RLBench [20], RoboSuite [55] and Sapien [51] target fine-grained manipulation. The main advantage of PROCTHOR is that we can generate a diverse set of *interactive* scenes procedurally, enabling studies of data augmentation and large-scale training in the context of Embodied AI.

Large-scale datasets. Large-scale datasets have resulted in major breakthroughs in different domains such as image classification [14, 25], vision and language [11, 44], 3D understanding [8, 52], autonomous driving [6, 42], and robotic object manipulation [33, 30]. However, there are not many interactive large-scale datasets for Embodied AI research. PROCTHOR includes interactive houses generated procedurally. Hence, there are an arbitrarily large number of scenes in the framework. The closest works to ours are [36, 32, 28]. HM3D [36] is a recent framework that includes 1,000 scenes generated using 3D scans of real environments. PROCTHOR has a number of key distinctions: (1) unlike HM3D which includes static scenes, the scenes in PROCTHOR are interactive i.e., objects can move and change state, the lighting and texture of objects can change, and a physics engine determines the future states of the scenes; (2) it is challenging to scale up HM3D as it requires scanning a house and cleaning up the data, while we can procedurally generate more houses; (3) HM3D can be used only for navigation tasks (as there is no physics simulation and object interaction), while PROCTHOR can be used for tasks other than navigation. OpenRooms [28] is similar to HM3D in terms of the source of the data (3D scans) and dataset size. However, OpenRooms is interactive. OpenRooms is also confined to the set of scanned houses, and it takes a significant amount of time to annotate a new scene (e.g., labeling materials for one object takes 1 minute), while PROCTHOR does not suffer from these issues. Megaverse [32] is another large-scale Embodied AI platform that includes procedurally generated environments. Although it is impressive in terms of simulation speed, it includes only game-like environments with a simplified appearance. In contrast, PROCTHOR mimics real-world houses in terms of the complexity of appearance, physics, and object interactions.

Scene generation. Indoor scene synthesis has been studied extensively in computer vision and graphics communities. [9, 10, 7] address generating 3D scenes from text descriptions. [48, 19, 31] learn to generate house floorplans. [38, 53, 12, 45, 21, 27] use generative models for indoor scene generation. [54, 39] propose potential objects for a query location in an indoor scene. Others have used procedural generation [22, 16] and unsupervised learning [15] to synthesize grid-world environments for AI. PROCTHOR is specifically designed for Embodied AI research in the sense that (1) all scenes are interactive and physics-enabled, and the placement of objects respects the physics of the world (e.g., there are no two objects that clip through each other), (2) there are various forms of scene augmentation such as randomization of object placements while following certain commonsense rules, variation in the appearance of objects and structures, and variation in lighting.

3 PROCTHOR

PROCTHOR is a framework to procedurally generate E-AI environments. It extends AI2-THOR and, thereby, inherits AI2-THOR's large asset library, robotic agents, and accurate physics simulation. Just as in scenes painstakingly created by designers in AI2-THOR, environments in PROCTHOR are fully interactive and support navigation, object manipulation, and multi-agent interaction.

Figure 2: Procedurally generating a house using PROCTHOR.

Fig. 2 shows a high-level schematic of the procedure used by PROCTHOR to generate a scene. Given a room specification (*e.g.* house with 1 bedroom + 1 bathroom), PROCTHOR uses multi-stage conditional sampling to, iteratively, generate a floor plan, create an external wall structure, sample lighting, and doors, then sample assets including large, small and wall objects, pick colors and textures, and determine appropriate placements for assets within the scene. We refer the reader to the appendix for details regarding our procedural generation and sampling mechanism, but highlight five key characteristics of PROCTHOR: **Diversity**, **Interactivity**, **Customizability**, **Scale**, and **Efficiency**.

Diversity. PROCTHOR enables the creation of rich and diverse environments. Mirroring the success of pre-training models with diverse data in the vision and NLP domains, we demonstrate the utility of this diversity on several E-AI tasks. Scenes in PROCTHOR exhibit diversity across several facets:

Diversity of floor plans. Given a room specification, we first employ iterative boundary cutting to obtain an external scene layout (that can range from a simple rectangle to a complex polygon). The recursive layout generation algorithm by Lopes *et al.* [29] is then used to divide the scene into the desired rooms. Finally, we determine connectivity between rooms using a set of user-defined constraints. These procedures result in natural room layouts (e.g., bedrooms are often connected to adjoining bathrooms via a door, bathrooms more often have a single entrance, etc). As exemplified in Fig. 3, PROCTHOR generates hugely diverse floor plans using this procedure.

Figure 3: **Floorplan diversity.** Examples showing the diversity of the generated floorplans. Rooms in the house are colored by ▪ Bedroom, ▪ Bathroom, ▪ Kitchen, and ▪ Living Room.

Diversity of assets. PROCTHOR populates scenes with small and large assets from its database of 1633 household assets across 108 categories (examples in Fig. 4). While many assets are inherited from AI2-THOR, we also introduce new assets such as windows, doors, and countertops, hand-designed by 3D graphic designers. Asset instances are split into train/val/test subsets and are

interactable, i.e. objects can be picked and placed within the scenes, some objects have multiple states (*e.g.* a light can be on or off) and several objects consists of parts with rigid body motions (*e.g.* door on a microwave).

Figure 4: **Object diversity.** A subset of instances for four object categories.

Diversity of materials. Walls can have two kinds of materials – one of 40 solid (and popular) colors or one of 122 wall textures such as brick and tile. We also provide 55 floor materials. The ceiling material for the entire house is sampled from the set of wall materials. PROCTHOR also provides the ability to randomize materials of objects. Materials are only randomized within categories, which ensures objects still look and behave like the class they represent.

Figure 5: **Material augmentation**. Different materials for objects (left two columns) and structural elements like walls and floors (right two columns).

Diversity of object placements. Asset categories have several soft annotations that help place them realistically within a house. These include room assignments (*e.g.* couch in a living room but not a bathroom) and location assignments (*e.g.* fridge along a wall, TV not on the floor). We also develop the notion of a Semantic Asset Group (SAG) – groups of assets that typically co-occur (*e.g.* dining table with four chairs) and thus must be sampled and placed using dependent sampling. Given a layout, individual assets and SAGs that lie on the floor are sampled and placed iteratively, ensuring that rooms continue to have adequate floor space for agents to navigate and manipulate objects. Then wall objects such as windows and paintings get placed, and finally, surface objects (ones found on top of other assets) are placed (*e.g.* cups on the kitchen counter). This sampling allows for a large and diverse set of object choices and placements within any layout. Fig. 6 shows such variations.

Figure 6: **Object placement.** Four examples of object placement within the same room layout.

Diversity of lighting. PROCTHOR supports a single directional light (analogous to the sun) and several point lights (analogous to lightbulbs). Varying the color, intensity, and placement of these

sources allows us to simulate different artificial lighting, typically observed in houses, and also at different times of the day. Lighting has a significant effect on the rendered images as seen in Fig. 7.

Figure 7: **Lighting variation**. Morning, dusk, and night lighting for an example scene.

Interactivity. A key property of PROCTHOR is the ability to interact with objects to change their location or state (Fig. 8). This capability is fundamental to many Embodied AI tasks. Datasets like HM3D [36] that are created from static 3D scans do not possess this capability. PROCTHOR supports agents with arms capable of manipulating objects and interacting with each other.

Figure 8: **Interactivity.** Object states can change (e.g., the laptop or the lamp in the left panel), and the agents can interact with objects and other agents (middle and right panels).

Customizability. PROCTHOR supports many room, asset, material, and lighting specifications. With a few simple lines of specification, one can easily generate customized environments of interest. Fig. 9 shows examples of such varied scenes (classroom, library, and office).

Figure 9: **Customizability.** PROCTHOR can be used to construct custom scene types such as classrooms, libraries, and offices.

Scale and Efficiency. PROCTHOR currently uses 16 different scene specifications to seed the scene generation process. These can result in over 100 billion layouts. PROCTHOR uses 18 different Semantic Asset groups and 1633 assets. These can result in roughly 20 million unique asset groups. Each of these assets can be placed in numerous locations. In addition, each house gets scaled and uses a variety of lighting. This diversity of layouts, assets, materials, placements, and lighting enables the generation of *arbitrarily large* sets of houses – either statically generated and stored as a dataset or dynamically generated at each iteration of training. Scenes are efficiently represented in a JSON specification and are loaded into AI2-THOR at runtime, making the memory overhead of storing houses incredibly efficient. Moreover, the scene generation process is fully automatic and fast and PROCTHOR provides high framerates for training E-AI models (see Sec. 4 for details).

4 PROCTHOR-10K

We demonstrate the power and potential of PROCTHOR using a sampled set of 10,000 fully interactive houses obtained by the procedural generation process described in Section 3 – which we label PROCTHOR-10K. An additional set of 1,000 validation and 1,000 testing houses are available

Figure 10: **PROCTHOR-10K statistics.** *Left:* distribution of the number of objects in each room; *Middle:* distribution of the area of each house, bucketed into small, medium, and large houses; *Right:* bar plot showing the distribution over the number of rooms that make up each house.

for evaluation. Asset splits across train/val/test are detailed in the Appendix. All houses are fully navigable, allowing an agent to traverse through each room without any interaction. In terms of scale, PROCTHOR-10K is one of the largest sets of interactive home environments for Embodied AI – as a comparison, AI2-iTHOR [24] includes 120 scenes, RoboTHOR [13] has 89 scenes, iGibson [41] has 15 scenes, Habitat Matterport 3D [36] has 1,000 static (non-interactive) scenes, and Habitat 2.0 [43] has 105 scene layouts. Scaling beyond 10K houses is straightforward and inexpensive. This set of 10K houses was generated in 1 hour on a local workstation with 4 NVIDIA RTX A5000 GPUs. Fig. 11 shows examples of ego-centric and top-down views of houses present in PROCTHOR-10K.

Scene statistics. Houses in PROCTHOR-10K are generated using 16 different room specifications. An example room spec is: *A house with 1 bedroom connected to 1 bathroom, 1 kitchen, and 1 living room* and is visualized in Fig. 2. Houses in this dataset have as few as 1 room and as many as 10. Fig. 10 shows the distribution of areas (middle) and the number of rooms (right) of these generated houses. Our use of room specifications enables us to change the distribution of the size and complexity of houses fairly easily. PROCTHOR-10K encompasses a wider spectrum of scenes than AI2-iTHOR [24] and ROBOTHOR [13] (biased towards room-sized scenes) and Gibson [50] and HM3D [36] (biased towards large houses).

Rooms in each of these houses contain objects from 95 different categories including common household objects such as fridges, countertops, beds, toilets, and house plants, and structure objects such as doorways and windows. Fig. 10 (left) shows the distribution of the number of objects per room per house, which shows that houses in PROCTHOR-10K are well populated. They also contain objects sampled via 18 different Semantic Asset groups. Examples of Semantic asset groups (SAG) are a *Dining Table with 4 Chairs* or *Bed with 2 Pillows*. Given our large asset library and SAGs, we can create 19.3 million combinations of group instantiations.

Figure 11: **Example scenes** in PROCTHOR-10K with top-down and an egocentric view.

Compute	Navigation FPS		Isolated Interaction FPS		Environment Query FPS	
	Small	Large	Small	Large	Small	Large
8 GPUs	$8{,}599{\pm}359$	$3208{\pm}127$	$6{,}488{\pm}250$	$2861{\pm}107$	$480{,}205{\pm}19{,}684$	$433{,}587{\pm}18{,}729$
1 GPU	$1{,}427{\pm}74$	$6280{\pm}40$	$1{,}265{\pm}71$	$597{\pm}37$	$160{,}622{\pm}2{,}846$	$157{,}567{\pm}2{,}689$
1 Process	$240{\pm}69$	$115{\pm}19$	$180{\pm}42$	$93{\pm}15$	$14{,}825{\pm}199$	$14{,}916{\pm}186$

Table 1: **Rendering speed.** Benchmarking FPS for navigation (*e.g.* moving/rotating), interaction (*e.g.* pushing an object), and querying the environment for data (*e.g.* checking the dimensions of the agent). We report FPS for Small and Large houses. See Appendix for details.

Rendering speed. A crucial requirement for large-scale training is high rendering speed since the training algorithms require millions of iterations to converge. Table 1 shows these statistics. Experiments were run on a server with 8 NVIDIA Quadro RTX 8000 GPUs. For the 1 GPU experiments, we use 15 processes and for the 8 GPU experiments, we use 120 processes, evenly distributed across the GPUs. PROCTHOR provides framerates comparable to iTHOR and RoboTHOR environments in spite of having larger houses (See Appendix for details), rendering it fast enough for training large models for hundreds of millions of steps in a reasonable amount of time.

5 Experiments

Tasks. We now present results for models pre-trained on PROCTHOR-10K on several navigation and manipulation benchmarks to demonstrate the benefits of large-scale training. We consider ObjectNav (navigation towards a specific object category) in PROCTHOR, ARCHITECTHOR, RoboTHOR [13], HM3D [36], and AI2-iTHOR [24]. We also consider two manipulation-based tasks: ArmPointNav [17] and 1-phase Room Rearrangement [46]. In ArmPointNav, the agent moves an object using a robotic arm from a source location to a destination location specified in the 3D coordinate frame. In Room Rearrangement, the goal is to move objects or change their state to reach a target scene state.

Models. Our models for all tasks consist of a CNN to encode visual information and a GRU to capture temporal information. We deliberately use a simple architecture across all tasks to show the benefits of large-scale training. Our ObjectNav and Rearrangement models use the CLIP-based architectures of [23]. Our ArmPointNav model uses a simpler visual encoder with 3 convolutional layers; we found this more effective than the CLIP encoder. All models are trained with the AllenAct [47] framework, see the Appendix for training details.

Results. We present results in two settings: zero-shot and after fine-tuning on the training scenes provided by the downstream benchmark. Zero-shot experiments show us how well models trained on PROCTHOR generalize to new environments, whereas fine-tuning experiments tell us if representations learned from PROCTHOR can serve as a good initialization for quick tuning. For all experiments, we use only RGB images (no depth and other modalities is used).

Zero-shot is particularly challenging since other environments have different appearance statistics, layouts, and object distributions compared to PROCTHOR. ARCHITECTHOR and AI2-iTHOR [24] are high-fidelity artist-designed scenes with high-quality shadows and lighting. HM3D is constructed from 3D scans of houses which can differ quite a bit from synthetic environments. RoboTHOR [13] houses use wall panels and floors with very specific textures.

Zero-shot transfer results. Models trained only on PROCTHOR and evaluated zero-shot outperform previous SoTA models on 3 benchmarks (refer to *zero-shot* rows of Table 2). These are very strong results since the models generalize to not only unseen objects and scenes, but also different appearance and layout statistics.

Fine-tuning results. Further fine-tuning of the model using each benchmark's training data, achieves state-of-the-art results on all benchmarks (refer to *fine-tune* rows of Table 2). Notably, our model is ranked first on three public leaderboards at the time of submission: Habitat 2022 ObjectNav challenge, AI2-THOR Rearrangement 2022 challenge, and RoboTHOR ObjectNav challenge. It should be noted that our model achieves these results using a very simple architecture and only RGB images.

Other techniques typically use more complex architectures that include mapping or visual odometry modules and use additional perception sensors such as depth images.

Scale ablation. To evaluate the effect of scale we train the models on 10, 100, 1,000, and 10,000 houses. For this experiment, we do not use any material augmentations. As shown in Table 3, the performance improves as we use more houses for training, demonstrating the benefits of large-scale data for Embodied AI tasks.

Task	Benchmark	Method	Metrics	
			Success	SPL
ObjectNav	RoboTHOR Challenge	EmbCLIP [23][a]	47.0%	0.200
		ProcTHOR 0-shot	55.0%	0.237
		ProcTHOR + fine-tune	**65.2**%	**0.288**
			Success	SPL
ObjectNav	Habitat Challenge (2022) *HM3D-Semantic*	MLNLC[c]	39.0%	0.200
		Alstar (m7_4m16_580)[c]	47.0%	0.250
		ProcTHOR 0-shot	9.00%	0.055
		ProcTHOR + fine-tune	**53.0**%	**0.270**
			Success	SPL
ObjectNav	AI2-iTHOR	EmbCLIP [23][b]	68.4%	0.516
		ProcTHOR 0-shot	75.7%	**0.644**
		ProcTHOR + fine-tune	**77.5**%	0.621
			Success	SPL
ObjectNav	ARCHITECTHOR	EmbCLIP [23][b]	18.5%	0.118
		ProcTHOR	**31.4**%	**0.195**
			Success	% Fixed Strict
Rearrangement	AI2-THOR Challenge *1-phase* (2022)	EmbCLIP [23]	7.10%	0.190
		ProcTHOR 0-shot	3.80%	0.156
		ProcTHOR + fine-tune	**7.40**%	**0.245**
			Success	% PickUp SR
ArmPointNav	ManipulaTHOR	iTHOR-SimpleConv [17][d]	29.2%	73.4
		ProcTHOR 0-shot	**37.9**%	**74.8**

Table 2: Results for models trained on ProcTHOR and evaluated 0-shot and with fine-tuning on several E-AI benchmarks. For each benchmark we also compare to the relevant baselines (previous SoTA or leaderboard submissions where applicable). [a]EmbCLIP [23] trained on ROBOTHOR, [b]EmbCLIP [23] trained on AI2-iTHOR, [c]submission on the Habitat 2022 ObjectNav leaderboard [1]. [d]uses the model from [17] but retrains on the complete iTHOR data with RGB inputs. ▨ 0-shot results, whereby models are pre-trained on PROCTHOR-10K and do not use any training data from the benchmark that they are evaluated on.

	ARCHITECTHOR Test		ROBOTHOR Test (0-Shot)		HM3D Valid (0-Shot)		AI2-iTHOR Test (0-Shot)	
# HOUSES	SPL	SR	SPL	SR	SPL	SR	SPL	SR
10 Houses	0.077	11.3%	0.040	8.53%	0.007	1.60%	0.249	28.7%
100 Houses	0.102	18.6%	0.076	20.9%	0.050	**10.4**%	0.352	42.0%
1,000 Houses	0.122	17.2%	0.157	33.1%	0.027	4.65%	0.456	53.0%
10,000 Houses	**0.185**	**27.0**%	**0.210**	**44.5**%	**0.060**	9.70%	**0.554**	**64.9**%

Table 3: Ablation study to evaluate the effect of the number of training houses. Each model is trained to 80% success during training. Test performance increases with the number of training houses.

6 Conclusion

We propose PROCTHOR, a framework to procedurally generate *arbitrarily large* sets of interactive, physics-enabled houses for Embodied AI research. We pre-train simple models on 10,000 generated houses and show state-of-the-art results across 6 embodied navigation and manipulation benchmarks with strong 0-shot results, even outperforming prior state-of-the-art on 3 of these benchmarks.

References

[1] Habitat ObjectNav Challenge 2022. https://aihabitat.org/challenge/2022. 2, 9

[2] Rearrangement Challenge 2022. https://leaderboard.allenai.org/ithor_rearrangement_1phase_2022. 2

[3] RoboTHOR ObjectNav Challenge. https://github.com/allenai/robothor-challenge. 2

[4] Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katie Millican, Malcolm Reynolds, Roman Ring, Eliza Rutherford, Serkan Cabi, Tengda Han, Zhitao Gong, Sina Samangooei, Marianne Monteiro, Jacob Menick, Sebastian Borgeaud, Andrew Brock, Aida Nematzadeh, Sahand Sharifzadeh, Mikolaj Binkowski, Ricardo Barreira, Oriol Vinyals, Andrew Zisserman, and Karen Simonyan. Flamingo: a visual language model for few-shot learning. *arXiv*, 2022. 1

[5] Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, T. J. Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeff Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In *NeurIPS*, 2020. 1

[6] Holger Caesar, Varun Bankiti, Alex H. Lang, Sourabh Vora, Venice Erin Liong, Qiang Xu, Anush Krishnan, Yu Pan, Giancarlo Baldan, and Oscar Beijbom. nuscenes: A multimodal dataset for autonomous driving. In *CVPR*, 2020. 3

[7] Angel Chang, Manolis Savva, and Christopher D Manning. Interactive learning of spatial knowledge for text to 3d scene generation. In *ACL Workshop on Interactive Language Learning, Visualization, and Interfaces*, 2014. 3

[8] Angel X. Chang, Thomas Funkhouser, Leonidas Guibas, Pat Hanrahan, Qixing Huang, Zimo Li, Silvio Savarese, Manolis Savva, Shuran Song, Hao Su, Jianxiong Xiao, Li Yi, and Fisher Yu. ShapeNet: An Information-Rich 3D Model Repository. *arXiv*, 2015. 3

[9] Angel X. Chang, Will Monroe, Manolis Savva, Christopher Potts, and Christopher D. Manning. Text to 3d scene generation with rich lexical grounding. In *ACL*, 2015. 3

[10] Angel X. Chang, Manolis Savva, and Christopher D. Manning. Learning spatial knowledge for text to 3d scene generation. In *EMNLP*, 2014. 3

[11] Soravit Changpinyo, Piyush Kumar Sharma, Nan Ding, and Radu Soricut. Conceptual 12m: Pushing web-scale image-text pre-training to recognize long-tail visual concepts. In *CVPR*, 2021. 3

[12] Siddhartha Chaudhuri, Daniel Ritchie, Kai Xu, and Hao Zhang. Learning generative models of 3d structures. In *Eurographics*, 2019. 3

[13] Matt Deitke, Winson Han, Alvaro Herrasti, Aniruddha Kembhavi, Eric Kolve, Roozbeh Mottaghi, Jordi Salvador, Dustin Schwenk, Eli VanderBilt, Matthew Wallingford, Luca Weihs, Mark Yatskar, and Ali Farhadi. Robothor: An open simulation-to-real embodied ai platform. In *CVPR*, 2020. 1, 3, 7, 8

[14] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *CVPR*, 2009. 3

[15] Michael Dennis, Natasha Jaques, Eugene Vinitsky, Alexandre Bayen, Stuart Russell, Andrew Critch, and Sergey Levine. Emergent complexity and zero-shot transfer via unsupervised environment design. In *NeurIPS*, 2020. 3

[16] Sam Earle, Maria Edwards, Ahmed Khalifa, Philip Bontrager, and Julian Togelius. Learning controllable content generators. In *CoG*, 2021. 3

[17] Kiana Ehsani, Winson Han, Alvaro Herrasti, Eli VanderBilt, Luca Weihs, Eric Kolve, Aniruddha Kembhavi, and Roozbeh Mottaghi. ManipulaTHOR: A Framework for Visual Object Manipulation. In *CVPR*, 2021. 2, 3, 8, 9

[18] Chuang Gan, Jeremy Schwartz, Seth Alter, Martin Schrimpf, James Traer, Julian De Freitas, Jonas Kubilius, Abhishek Bhandwaldar, Nick Haber, Megumi Sano, Kuno Kim, Elias Wang, Damian Mrowca, Michael Lingelbach, Aidan Curtis, Kevin T. Feigelis, Daniel Bear, Dan Gutfreund, David Cox, James J. DiCarlo, Josh H. McDermott, Joshua B. Tenenbaum, and Daniel L. K. Yamins. Threedworld: A platform for interactive multi-modal physical simulation. In *NeurIPS (dataset track)*, 2021. 1, 3

[19] Ruizhen Hu, Zeyu Huang, Yuhan Tang, Oliver Matias van Kaick, Hao Zhang, and Hui Huang. Graph2plan: Learning floorplan generation from layout graphs. *ACM Trans. on Graphics*, 2020. 3

[20] Stephen James, Zicong Ma, David Rovick Arrojo, and Andrew J Davison. Rlbench: The robot learning benchmark & learning environment. *IEEE Robotics and Automation Letters*, 2020. 3

[21] Mohammad Keshavarzi, Aakash Parikh, Xiyu Zhai, Melody Mao, Luisa Caldas, and Allen Y Yang. Scenegen: Generative contextual scene augmentation using scene graph priors. *arXiv*, 2020. 3

[22] Ahmed Khalifa, Philip Bontrager, Sam Earle, and Julian Togelius. Pcgrl: Procedural content generation via reinforcement learning. In *AIIDE*, 2020. 3

[23] Apoorv Khandelwal, Luca Weihs, Roozbeh Mottaghi, and Aniruddha Kembhavi. Simple but effective: Clip embeddings for embodied ai. In *CVPR*, 2021. 8, 9

[24] Eric Kolve, Roozbeh Mottaghi, Winson Han, Eli VanderBilt, Luca Weihs, Alvaro Herrasti, Daniel Gordon, Yuke Zhu, Abhinav Gupta, and Ali Farhadi. Ai2-thor: An interactive 3d environment for visual ai. *arXiv*, 2017. 1, 2, 3, 7, 8

[25] Alina Kuznetsova, Hassan Rom, Neil Gordon Alldrin, Jasper R. R. Uijlings, Ivan Krasin, Jordi Pont-Tuset, Shahab Kamali, Stefan Popov, Matteo Malloci, Alexander Kolesnikov, Tom Duerig, and Vittorio Ferrari. The open images dataset v4. *IJCV*, 2020. 3

[26] Chengshu Li, Fei Xia, Roberto Mart'in-Mart'in, Michael Lingelbach, Sanjana Srivastava, Bokui Shen, Kent Vainio, Cem Gokmen, Gokul Dharan, Tanish Jain, Andrey Kurenkov, Karen Liu, Hyowon Gweon, Jiajun Wu, Li Fei-Fei, and Silvio Savarese. igibson 2.0: Object-centric simulation for robot learning of everyday household tasks. In *CoRL*, 2021. 3

[27] Manyi Li, Akshay Gadi Patil, Kai Xu, Siddhartha Chaudhuri, Owais Khan, Ariel Shamir, Changhe Tu, Baoquan Chen, Daniel Cohen-Or, and Hao Zhang. Grains: Generative recursive autoencoders for indoor scenes. *ACM Trans. on Graphics*, 2019. 3

[28] Zhengqin Li, Ting Yu, Shen Sang, Sarah Wang, Mengcheng Song, Yuhan Liu, Yu-Ying Yeh, Rui Zhu, Nitesh B. Gundavarapu, Jia Shi, Sai Bi, Hong-Xing Yu, Zexiang Xu, Kalyan Sunkavalli, Milos Hasan, Ravi Ramamoorthi, and Manmohan Chandraker. Openrooms: An open framework for photorealistic indoor scene datasets. In *CVPR*, 2021. 3

[29] Ricardo Lopes, Tim Tutenel, Ruben M Smelik, Klaas Jan De Kraker, and Rafael Bidarra. A constrained growth method for procedural floor plan generation. In *International Conference on Intelligent Games and Simulation*, 2010. 4

[30] Tongzhou Mu, Zhan Ling, Fanbo Xiang, Derek Yang, Xuanlin Li, Stone Tao, Zhiao Huang, Zhiwei Jia, and Hao Su. ManiSkill: Generalizable Manipulation Skill Benchmark with Large-Scale Demonstrations. In *NeurIPS (dataset track)*, 2021. 3

[31] Nelson Nauata, Sepidehsadat Hosseini, Kai-Hung Chang, Hang Chu, Chin-Yi Cheng, and Yasutaka Furukawa. House-gan++: Generative adversarial layout refinement network towards intelligent computational agent for professional architects. In *CVPR*, 2021. 3

[32] Aleksei Petrenko, Erik Wijmans, Brennan Shacklett, and Vladlen Koltun. Megaverse: Simulating embodied agents at one million experiences per second. In *ICML*, 2021. 3

[33] Lerrel Pinto and Abhinav Gupta. Supersizing self-supervision: Learning to grasp from 50k tries and 700 robot hours. In *ICRA*, 2016. 3

[34] Xavier Puig, Kevin Kyunghwan Ra, Marko Boben, Jiaman Li, Tingwu Wang, Sanja Fidler, and Antonio Torralba. Virtualhome: Simulating household activities via programs. In *CVPR*, 2018. 3

[35] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. In *ICML*, 2021. 1

[36] Santhosh K. Ramakrishnan, Aaron Gokaslan, Erik Wijmans, Oleksandr Maksymets, Alexander Clegg, John Turner, Eric Undersander, Wojciech Galuba, Andrew Westbury, Angel Xuan Chang, Manolis Savva, Yili Zhao, and Dhruv Batra. Habitat-matterport 3d dataset (hm3d): 1000 large-scale 3d environments for embodied ai. *arXiv*, 2021. 1, 3, 6, 7, 8

[37] Aditya Ramesh, Mikhail Pavlov, Gabriel Goh, Scott Gray, Chelsea Voss, Alec Radford, Mark Chen, and Ilya Sutskever. Zero-shot text-to-image generation. In *ICML*, 2021. 1

[38] Daniel Ritchie, Kai Wang, and Yu-An Lin. Fast and flexible indoor scene synthesis via deep convolutional generative models. In *CVPR*, 2019. 3

[39] Manolis Savva, Angel X. Chang, and Maneesh Agrawala. Scenesuggest: Context-driven 3d scene design. *arXiv*, 2017. 3

[40] Manolis Savva, Abhishek Kadian, Oleksandr Maksymets, Yili Zhao, Erik Wijmans, Bhavana Jain, Julian Straub, Jia Liu, Vladlen Koltun, Jitendra Malik, et al. Habitat: A platform for embodied ai research. In *ICCV*, 2019. 1, 3

[41] Bokui Shen, Fei Xia, Chengshu Li, Roberto Mart'in-Mart'in, Linxi (Jim) Fan, Guanzhi Wang, S. Buch, Claudia. Pérez D'Arpino, Sanjana Srivastava, Lyne P. Tchapmi, Micael Edmond Tchapmi, Kent Vainio, Li Fei-Fei, and Silvio Savarese. igibson, a simulation environment for interactive tasks in large realistic scenes. In *IROS*, 2021. 1, 3, 7

[42] Pei Sun, Henrik Kretzschmar, Xerxes Dotiwalla, Aurelien Chouard, Vijaysai Patnaik, Paul Tsui, James Guo, Yin Zhou, Yuning Chai, Benjamin Caine, et al. Scalability in perception for autonomous driving: Waymo open dataset. In *CVPR*, 2020. 3

[43] Andrew Szot, Alexander Clegg, Eric Undersander, Erik Wijmans, Yili Zhao, John Turner, Noah Maestre, Mustafa Mukadam, Devendra Singh Chaplot, Oleksandr Maksymets, Aaron Gokaslan, Vladimir Vondrus, Sameer Dharur, Franziska Meier, Wojciech Galuba, Angel Xuan Chang, Zsolt Kira, Vladlen Koltun, Jitendra Malik, Manolis Savva, and Dhruv Batra. Habitat 2.0: Training home assistants to rearrange their habitat. In *NeurIPS*, 2021. 3, 7

[44] Bart Thomee, David A. Shamma, Gerald Friedland, Benjamin Elizalde, Karl S. Ni, Douglas N. Poland, Damian Borth, and Li-Jia Li. Yfcc100m: the new data in multimedia research. *Comm. of the ACM*, 2016. 3

[45] Xinpeng Wang, Chandan Yeshwanth, and Matthias Nießner. Sceneformer: Indoor scene generation with transformers. In *3DV*, 2021. 3

[46] Luca Weihs, Matt Deitke, Aniruddha Kembhavi, and Roozbeh Mottaghi. Visual room rearrangement. In *CVPR*, 2021. 8

[47] Luca Weihs, Jordi Salvador, Klemen Kotar, Unnat Jain, Kuo-Hao Zeng, Roozbeh Mottaghi, and Aniruddha Kembhavi. AllenAct: A framework for embodied AI research. *arXiv*, 2020. 8

[48] Wenming Wu, Xiao-Ming Fu, Rui Tang, Yuhan Wang, Yu-Hao Qi, and Ligang Liu. Data-driven interior plan generation for residential buildings. *ACM Trans. on Graphics*, 2019. 3

[49] Yi Wu, Yuxin Wu, Georgia Gkioxari, and Yuandong Tian. Building generalizable agents with a realistic and rich 3d environment. *arXiv*, 2018. 3

[50] Fei Xia, Amir R Zamir, Zhiyang He, Alexander Sax, Jitendra Malik, and Silvio Savarese. Gibson env: Real-world perception for embodied agents. In *CVPR*, 2018. 7

[51] Fanbo Xiang, Yuzhe Qin, Kaichun Mo, Yikuan Xia, Hao Zhu, Fangchen Liu, Minghua Liu, Hanxiao Jiang, Yifu Yuan, He Wang, Li Yi, Angel X.Chang, Leonidas Guibas, and Hao Su. SAPIEN: A SimulAted Part-based Interactive ENvironment. In *CVPR*, 2020. 1, 3

[52] Yu Xiang, Wonhui Kim, Wei Chen, Jingwei Ji, Christopher Bongsoo Choy, Hao Su, Roozbeh Mottaghi, Leonidas J. Guibas, and Silvio Savarese. Objectnet3d: A large scale database for 3d object recognition. In *ECCV*, 2016. 3

[53] Zaiwei Zhang, Zhenpei Yang, Chongyang Ma, Linjie Luo, Alexander G. Huth, Etienne Vouga, and Qixing Huang. Deep generative modeling for scene synthesis via hybrid representations. *ACM Trans. on Graphics*, 2020. 3

[54] Yang Zhou, Zachary While, and Evangelos Kalogerakis. Scenegraphnet: Neural message passing for 3d indoor scene augmentation. In *ICCV*, 2019. 3

[55] Yuke Zhu, Josiah Wong, Ajay Mandlekar, and Roberto Martín-Martín. robosuite: A modular simulation framework and benchmark for robot learning. *arXiv*, 2020. 3