Learning C to x86 Translation: An Experiment in Neural Compilation

Abstract

Deep learning has had a significant impact on many fields. Recently, code-to-code neural models have been used in code translation, code refinement and decompilation. However, the question of whether these models can automate compilation has yet to be investigated. In this work, we explore neural compilation, building and evaluating Transformer models that learn how to produce x86 assembler from C code. Although preliminary results are relatively weak, we make our data, models and code publicly available to encourage further research in this area.

1 Introduction

Machine learning based compilation has been explored for over a decade [Wang and O'Boyle, 2018]. Early work focused on learning profitability heuristics while more recently, deep learning models have been used to build code-to-code models, for translating or decompiling code. However, to the best of our knowledge, there has been no prior work on using machine learning to entirely automate compilation i.e given a high level source code program generate the equivalent assembler code. Compilers are large, complex objects [Lattner and Adve, 2004] and automating their behavior represents a significant reseacrh challenge.

In this paper, we investigate whether it is possible to learn an end-to-end machine compiler using neural machine translation. In particular, we focus on the translation of small C functions to x86 assembler We use an existing function-level C corpus, Anghabench [da Silva et al., 2021], to build a parallel C-x86 assembler corpus. Then, we model the compilation task as a sequence-to-sequence task (akin to machine translation) with the Transformer architecture [Vaswani et al., 2017]. We study the effect of modifying different settings by varying training data size, model size, number of epochs, and other hyperparameters. While we can successfully generate syntactically correct assembler over 80% of the time and obtain high BLEU scores c. 90%, generating semantically correct assembler is more challenging .

The best model can only compile correctly about 33% of the functions in a benchmark built from an existing program synthesis evaluation set [Collie et al., 2020]; it specially struggles to compile functions with numerous arguments and arrays.

The article is structured as follows. In Section 2, we briefly summarise related work in NLP and machine learning for code. In Section 3, we formalize the task of machine compilation and propose how to effectively build neural compilers and fairly evaluate them. Then, in Section 4 we establish our experimental framework and report results. Finally, we discuss our approach and conclude, in Section 5.

2 Related Work

Natural Language Processing and Machine Translation   In Natural Language Processing (NLP), the current state-of-the-art typically involves using some variant the Transformer architecture [Vaswani et al., 2017] together with some form of subword tokenization [Sennrich et al., 2015]. In this work, we omit the prolific literature in unsupervised NLP (most famously, BERT [Devlin et al., 2018]) and machine translation because we focus on a supervised setting.

Deep Learning for Code and Symbolic Data   Recent works have proposed to use the encoder-decoder Transformer architecture out of the box for symbolic mathematics [Saxton et al., 2019, Lample and Charton, 2019], or even for automated symbolic proving with decoder-only Transformers [Polu and Sutskever, 2020]. The state-of-art NLP systems for unsupervised pretraining have also been with successfully applied to code, as in CodeBERT [Feng et al., 2020]. However, other research lines explore the use of alternative modeling strategies for code instead of flat sequences, such as trees to leverage the grammar [Chen et al., 2018] or other kinds of graphs for data flow analysis [Cummins et al., 2020a].

Machine Learning for Compilers   Many works have proposed the use of machine learning for improving code optimization [Leather and Cummins, 2020] and the field is gaining momentum with recent works such as the CompilerGym [Cummins et al., 2020b], a reinforcement learning environment for compilers optimization. However, the common approach is to use machine learning for decision-making, not to directly generate assembler with a machine learning decoder.

Code Translation and Code-to-Code models   Code-to-code models have been applied in tasks such as 1. programming language translation Drissi et al. [2018], even in unsupervised settings Lachaux et al. [2020], 2. code refinement Tufano et al. [2018], or 3. decompilation Katz et al. [2019]. The latter is the inverse task of the one we are posing. and is restricted to a highly restricted subset of C with a maximum of 5 statements.

To the best of our knowledge, no previous work has addressed the task of machine compilation. One specific additional challenge we note, is that the target sequences are considerably longer (being assembler) instead of a similar size (as usual in machine translation) or considerably shorter (as usual in summarization or decompilation).

3 Methods

We pose machine compilation as a sequence-to-sequence task. Akin to machine translation, machine compilation is the task of translating code into assembler language. More formally, given a dataset $\mathbf{D}$ with N pairs $(\mathbf{x_i}, \mathbf{y_i})$, where $\mathbf{x_i}$ is an input program and $\mathbf{y_i}$ is the corresponding assembler code, the system is trained with max likelihood estimation: $\ell(\boldsymbol{\theta}, \mathbf{D}) = \sum_{(\mathbf{x_i}, \mathbf{y_i} \in \mathbf{D})} ln p(\mathbf{y_i}|\mathbf{x_i}, \boldsymbol{\theta})$. Posing the task as a sequence-to-sequence task conditions both the data generation and the model building.

3.1 Training data

Regarding the granularity, as a first approach we decided to consider functions, following Lachaux et al. [2020]. Functions, unlike statements, are standalone units of meaning that can be translated, but at the same they are shorter and easier to test (unit tests) than a whole program (integration tests). Since we investigate a supervised setting, we need pairs (C functions, x86 assembler). However, C functions cannot be directly compiled; they typically need additional context (inclusion of headers, type definitions, constant definitions). Thus, even if we have pre-exiting C compilers, generating these data pairs is not trivial.

For this work, we base our dataset on Anghabench [da Silva et al., 2021], a benchmark of around 1 million C functions coupled with the required minimal C code to compile them. Anghabench is built by crawling C code from Github repositories. The authors extracted individual functions, and applied type-inference to reconstruct the missing definitions required to compile them (e.g., declarations of auxiliary functions, type definitions, etc). However, while these reconstructions makes the functions compilable, they are not executable. Apart from not necessarily having a main function

and input/output calls, the declared auxiliary functions are not defined. This, among other issues, prevents execution.

It is not practical to directly use this dataset for neural compilation. The inclusion of headers and type definitions while necessary for compilation, adds noise to the translation task. We refer to Appendix A for the description of our preprocessing pipeline together with data statistics (Appendix B). After filtering for length, we kept as many as 500k programs (Angha-Par500k) and a subset (250k) of those for an ablation study (Angha-Par250k).

3.2 Evaluation

BLEU Machine translation is usually evaluated with BLEU score [Papineni et al., 2002], based on n-gram overlaps between the generated sequence and the ground truth one (in our case, the GCC assembler). This metric does not take into account syntactical or semantic correctness. However, it is easy to compute for all cases, so we report it for both Angha-Par's test and Synthesis-Bench.

Syntactic accuracy We use GCC to check if the assembler generated is syntactically correct, by asking it to generate object code from the assembler. This metric is more relevant and even easier to compute, so we report it for both Angha-Par's test and Synthesis-Bench as well.

IO accuracy We evaluate semantic correctness using *observational equivalence* or *IO accuracy* between the reference GCC assembler and the one output by the model, following recent works on program translation [Lachaux et al., 2020]. That is, we check whether for a given set of inputs, the assembler predicted by the models have the same output as the reference GCC compilation (in other words, we evaluated whether the assembler functions generated by the models pass the available unit tests). While this is no proof that the two programs are formally equivalent, in practice it is a high indicator that it is. This is the most relevant metric and the one we use for selecting the best model and assessing its real performance.

3.3 Model

Following previous work on machine translation and deep learning for symbolic mathematics and source code modeling, we use a Transformer model (encoder-decoder) in different settings. We implement all models with Fairseq [Ott et al., 2019], a PyTorch [Paszke et al., 2019] sequence modeling library. As usual in sequence-to-sequence models, we train with teacher forcing and use a special token to denote the end of the sequence, which is also predicted by the model.

4 Experiments

We experiment with 4 Transformer sizes (Trans-Small, Trans-Med-Trans-Big, Trans-Big+). With Trans-Big we further experiment with different vocabulary and data sizes, and number of epochs. See Table 1 for the parameter count of each of the models, and Appendix C for more details on the models. We train all models with the same data (except from the ones that have a different vocabulary, which use a different tokenizer, and the one that uses half of data) and the same number of epochs, 5 (except for the model additionally trained for 5 more epochs). Regarding other hyperparameters, all models are trained with the Adam optimizer [Kingma and Ba, 2017]. We refer to Fairseq and our source code for additional details. We do not conduct any hyperparameter search, aside from the different configurations reported in Table 1. We then evaluate as described in Section 3.2, always with beam search ($k = 5$) and taking the best hypothesis among the top 5.

Table 1 shows the results summary of each model, together with their respective size. The best model, as per the most relevant metric (IO evaluation, that is, observational equivalence) is the Transformer-Big trained for 10 epochs.

5 Discussion and Conclusion

Transformer-Big+1/2x epochs is the best model in terms of the most relevant metric, IO accuracy (observational equivalence). It is the best model in terms of syntactical accuracy in Synthesis-Bench

MODEL	PARAMS	SYNTHESIS			ANGHA-PAR	
		IO	SYNTAX	BLEU	SYNTAX	BLEU
Trans-Small	30.9M	0/64	0/64	32.68	**98.50**	47.53
Trans-Med	142.7M	18/64	35/64	77.99	81.60	89.52
Trans-Big	193.1M	19/64	**37/64**	78.03	82.70	89.20
- 50% data	193.1M	13/64	34/64	76.81	88.16	83.80
- 1/2x vocab	184.7M	19/64	36/64	78.07	75.60	88.63
+ 1/2x vocab	209.8M	20/64	36/64	**79.48**	79.30	89.21
+ 1e2x w.-decay	193.1M	18/64	34/64	77.73	82.00	89.55
+ 1/2x epochs	193.1M	**21/64**	**37/64**	78.10	82.50	**90.19**
Trans-Big+	251.9M	19/64	34/64	78.19	82.50	89.76

Table 1: Results summary.

and BLEU score in the Angha-Par test. The smallest model clearly underfits the task of machine compilation, while all reasonably sized models achieve similar enough results (except the model trained with half of the data, which performs considerably worse).

The smallest model variant, Transformer-Small obtains has a surprisingly high syntactic accuracy in Angha-Par, as shown in Table 1, given that that its outputs are abnormally long (see Table 7. On inspection the outputs do not correlate with the inputsInstead, the model behaves as a unconditional assembler language model. Furthermore, we observe repeated outputs with different inputs. This phenomenon is reminiscent of the *hallucinations* described in other Sequence-to-Sequence models [Raunak et al., 2021] and the *mode collapse* of some generative models [Thanh-Tung et al., 2018].

Focusing on the outputs of the best model, we observe that 1. if a model has one correct IO example for a given function, then it is highly likely that other IO examples are correct 2. many syntactical errors occur because of a premature end of the hypothesis, 3. IO accuracy does not correlate with cyclomatic complexity, but with the number of function arguments and pointer variables in the function (as shown in Table 6), 4. models fail and succeed in the same functions, 5. correct model outputs look very similar to the GCC ones although not necessarily identical, 6. there are some trivial errors, such as `true` and `false` being confused with variable names instead of boolean values. For a more complete error analysis, we refer to Appendix E, and for samples of the model, to Appendix F. In Appendix D, we break down the results for each of the functions in Synthesis-Bench, include the average length of the outputs of the different models, and report the most frequent syntactical errors and error intersections between statistics between the different models.

There is no compelling reason to believe that neural networks would not scale with data, model size, and compute in a similar way to other domains [Kaplan et al., 2020]. Indeed, we have found that models generally perform better the more data, compute, and parameters can one afford, even though the largest model we trained was not the best one. Although the biggest model is not the best one, we hypothesize that is the case due to not having enough data to train it or a sub-optimal training procedure (e.g., not enough training updates). However, unlike other domains, code is usually evaluated in a binary fashion (that is, it is either correct or it is not). This, together with the fact that complexity in a given benchmark is not linear (e.g., going from a IO accuracy of 70% to a IO accuracy of 71% might be more difficult than going from 10% to 20%) causes sharp jumps.

Our best model can correctly compile less than half of the examples in the IO evaluation. Thus, it is far from being usable in practice as a compiler. Moreover, we have no control over the output space, and we operate on small functions instead of entire programs. In this work, apart from using code tokenizers and IO evaluation, we have not included any domain knowledge.

We conclude that our neural compilation approach shows that sequence-to-sequence deep learning models can, indeed, learn to compile end-to-end. Nevertheless, the performance is far from ideal and the restrictions make it still far from being usable in practice. The task presents many challenges, such as output length or hard syntactic and correctness constraints, that were not explicitly tackled in this work. As future work, we suggest 1. scaling up our approach, in terms of data, compute, and model parameters, 2. investigating how to incorporate domain knowledge in form of inductive biases or alternative data representations and inputs, and 3. researching unsupervised techniques to leverage unlabelled (i.e., not parallel) code or assembler.

References

Zheng Wang and Michael O'Boyle. Machine learning in compiler optimization. *Proceedings of the IEEE*, 106(11):1879–1901, 2018.

Chris Lattner and Vikram Adve. Llvm: A compilation framework for lifelong program analysis and transformation. In *Proceedings of the International Symposium on Code Generation and Optimization: Feedback-Directed and Runtime Optimization*, CGO '04, page 75, USA, 2004. IEEE Computer Society. ISBN 0769521029.

A. F. da Silva, B. C. Kind, J. W. de Souza Magalhães, J. N. Rocha, B. C. Ferreira Guimarães, and F. M. Quinão Pereira. Anghabench: A suite with one million compilable c benchmarks for code-size reduction. In *2021 IEEE/ACM International Symposium on Code Generation and Optimization (CGO)*, pages 378–390, 2021. doi: 10.1109/CGO51591.2021.9370322.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. *CoRR*, abs/1706.03762, 2017. URL http://arxiv.org/abs/1706.03762.

Bruce Collie, Jackson Woodruff, and Michael F. P. O'Boyle. Modeling black-box components with probabilistic synthesis. *CoRR*, abs/2010.04811, 2020. URL https://arxiv.org/abs/2010.04811.

Rico Sennrich, Barry Haddow, and Alexandra Birch. Neural machine translation of rare words with subword units. *CoRR*, abs/1508.07909, 2015. URL http://arxiv.org/abs/1508.07909.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. *CoRR*, abs/1810.04805, 2018. URL http://arxiv.org/abs/1810.04805.

David Saxton, Edward Grefenstette, Felix Hill, and Pushmeet Kohli. Analysing mathematical reasoning abilities of neural models. *CoRR*, abs/1904.01557, 2019. URL http://arxiv.org/abs/1904.01557.

Guillaume Lample and François Charton. Deep learning for symbolic mathematics. *CoRR*, abs/1912.01412, 2019. URL http://arxiv.org/abs/1912.01412.

Stanislas Polu and Ilya Sutskever. Generative language modeling for automated theorem proving. *CoRR*, abs/2009.03393, 2020. URL https://arxiv.org/abs/2009.03393.

Zhangyin Feng, Daya Guo, Duyu Tang, Nan Duan, Xiaocheng Feng, Ming Gong, Linjun Shou, Bing Qin, Ting Liu, Daxin Jiang, and Ming Zhou. Codebert: A pre-trained model for programming and natural languages, 2020.

Xinyun Chen, Chang Liu, and Dawn Song. Tree-to-tree neural networks for program translation. *CoRR*, abs/1802.03691, 2018. URL http://arxiv.org/abs/1802.03691.

Chris Cummins, Zacharias V. Fisches, Tal Ben-Nun, Torsten Hoefler, and Hugh Leather. Programl: Graph-based deep learning for program optimization and analysis, 2020a.

Hugh Leather and Chris Cummins. Machine learning in compilers: Past, present and future. In *2020 Forum for Specification and Design Languages (FDL)*, pages 1–8, 2020. doi: 10.1109/FDL50818.2020.9232934.

Chris Cummins, Hugh Leather, Benoit Steiner, Horace He, and Soumith Chintala. CompilerGym: A reinforcement learning toolkit for compilers. https://github.com/facebookresearch/CompilerGym/, 2020b.

Mehdi Drissi, Olivia Watkins, Aditya Khant, Vivaswat Ojha, Pedro Sandoval, Rakia Segev, Eric Weiner, and Robert Keller. Program language translation using a grammar-driven tree-to-tree model, 2018.

Marie-Anne Lachaux, Baptiste Roziere, Lowik Chanussot, and Guillaume Lample. Unsupervised translation of programming languages, 2020.

Michele Tufano, Cody Watson, Gabriele Bavota, Massimiliano Di Penta, Martin White, and Denys Poshyvanyk. An empirical study on learning bug-fixing patches in the wild via neural machine translation. *CoRR*, abs/1812.08693, 2018. URL `http://arxiv.org/abs/1812.08693`.

Omer Katz, Yuval Olshaker, Yoav Goldberg, and Eran Yahav. Towards neural decompilation. *CoRR*, abs/1905.08325, 2019. URL `http://arxiv.org/abs/1905.08325`.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: A method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting on Association for Computational Linguistics*, ACL '02, page 311–318, USA, 2002. Association for Computational Linguistics. doi: 10.3115/1073083.1073135. URL `https://doi.org/10.3115/1073083.1073135`.

Myle Ott, Sergey Edunov, Alexei Baevski, Angela Fan, Sam Gross, Nathan Ng, David Grangier, and Michael Auli. fairseq: A fast, extensible toolkit for sequence modeling. In *Proceedings of NAACL-HLT 2019: Demonstrations*, 2019.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems 32*, pages 8024–8035. Curran Associates, Inc., 2019. URL `http://papers.neurips.cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf`.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization, 2017.

Vikas Raunak, Arul Menezes, and Marcin Junczys-Dowmunt. The curious case of hallucinations in neural machine translation, 2021.

Hoang Thanh-Tung, Truyen Tran, and Svetha Venkatesh. On catastrophic forgetting and mode collapse in generative adversarial networks. *CoRR*, abs/1807.04015, 2018. URL `http://arxiv.org/abs/1807.04015`.

Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B. Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. Scaling laws for neural language models. *CoRR*, abs/2001.08361, 2020. URL `https://arxiv.org/abs/2001.08361`.

A Preprocessing pipeline

Our preprocessing pipeline is composed of the following steps:

1. Compilation: We use the GCC compiler to compile the C code into x86 assembler. We do not apply any optimizations (-O0).

2. Boilerplate removal: We remove the headers and type and constant definitions. Likewise, we remove the header and footer of the assembler. In both cases, we believe those inject noise and make sequences longer than need be.

3. Pre-tokenization: We use the GCC C and x86 assembler (GAS) tokenizers with the Pygments[1] library. In C, new lines are meaningless and just used to make code more human readable, but in GAS end of lines delimits the end of each instruction. Thus, in the latter we replace end of lines by a special token `<newline>`.

4. Length filtering: Due to computational restrictions and potentially easing the task, we discard the (C, assembler) pairs such that when summing the length of tokens of the C code and assembler we get more than 314 tokens.

5. Train-valid-test split: We randomly split the pairs into training, validation, and test sets, with 2k programs for validation and test and the rest for training.

6. Subword tokenization: We use subword encoding to automatically split tokens into further tokens based on n-gram frequencies in the train set. Specifically, `subword-nmt` [Sennrich et al., 2015] .[2] This has the benefit of decreasing the vocabulary size while making out-of-vocabulary tokens virtually impossible (since unknown tokens can be reconstructed from ASCII characters or other subwords present in the vocabulary).

7. Formatting: We write each C and assembler programs in plain text files, such that we have one program for each line.

B Data

DATASET	# PROGRAMS	Filter	# KEPT PROGRAMS	IO
Angha-Par500k	1.044M	Max. length	500k	✗
Angha-Par250k	1.044M	Max. length + random	250k	✗
Synthesis-Bench	112	Manual (difficulty)	64	✓

Table 2: Used datasets, original number of programs, filter criteria, number of kept programs after filtering, and whether they have input/output examples (which only Synthesis-Bench does). The AnghaPar corpus was filtered with a maximum combined (C + assembler) length of 314 tokens. The 250k subset was further subsampled randomly. Finally, the Synthesis-Bench was built from a manual selection of 64 functions from the original benchmark, based on implementation difficulty.

SPLIT	PROGRAMS	TOKENS C (AVG)	TOKENS ASM (AVG)
Angha-Par500k Train	500,439	22,653,480 (45.27)	65,910,582 (131.71)
Angha-Par250k Train	250,000	11,281,616 (45.12)	32,992,914 (131.97)
Angha-Par Valid	1,000	45,737 (45.74)	132,424 (132.42)
Angha-Par Test	1,000	44,643 (44.64)	132,446 (132.37)

Table 3: Dataset splits. assembler code has almost 3x tokens than its corresponding C code.

---

[1] https://pygments.org/
[2] https://github.com/rsennrich/subword-nmt

VOCAB	SUBW/TOK C (AVG LEN)	SUBW/TOKEN ASM (AVG LEN)	COVERAGE
4k	1.55 (69.85)	1.14 (149.85)	100%
8k	1.42 (64.22)	1.10 (144.99)	100%
16k	1.33 (59.96)	1.08 (143.12)	100%

Table 4: Subwords per token. All vocabularies have a coverage of 100% (i.e., no unknowns) since they include all ASCII characters. C code length is more sensitive to the vocabulary size, since it has a larger vocabulary (e.g., identifiers, except procedure names, are translated as memory positions or registers). There is a clear trade-off between sequence length and vocabulary size.

C   Experiments

We experiment with the following models:

- Transformer-Small: The *small* model follows the `transformer_iwslt_de_en` configuration in Fairseq, that is, 6 encoder layers and 6 decoder layers, an embedding size of 512 and 4 attention heads.

- Transformer-Big (base): The *big* model follows the `transformer_wmt_en_de_big_t2t` configuration in Fairseq, with 6 encoder layers and 6 decoder layers, an embedding size of 1024 and 16 attention heads

  - -50% data: Transformer-Big trained with Angha-Par250k instead of Angha-Par500k.
  - -1/2x vocab: Transformer-Big trained with a vocabulary of 4k tokens (instead of 8k tokens).
  - +1/2x vocab: Transformer-Big trained with a vocabulary of 16k tokens (instead of 8k tokens).
  - +1e2x weight-decay: Transformer-Big further regularized (a weight decay of 0.01 instead of 0.0001)
  - +1/2 epochs: Transformer-Big trained for a total of 10 epochs (instead of 5).

- Transformer-Med: The medium-size model roughly follows the Transformer-Big configuration, but with 8 attention heads (instead of 16) and a Feed-Forward hidden size of 2048 (instead of 4096).

- Transformer-Big+: This model has the same configuration as Transformer-Big, but with 2 additional layers for both the encoder and the decoder.

D   Expanded results

We report the fine-grained IO evaluation for the best model in Table 5, together with other metrics to ease the analysis of the results. Specifically, apart from the aforementioned syntactic accuracy and BLEU scores, we also report: 1. *LOC*: Lines of Code, the number of lines of the C implementation. 2. Tokens: The number of tokens of the C implementation. 3. *Cyclo*: The *cyclomatic complexity*: Cyclomatic complexity $= E - N + 2 \times P$ where E is the number of edges in the flow graph, N is the number of nodes in the flow graph, and P is the number of nodes that have exit points. 4. Params: The number of parameters of the C function. 5. Pointers: The number of pointer parameters (typically arrays) of the C function.

Finally, Tables 6, 7, 8, 9 show the correlations between IO errors and other metrics, the mean output length of each model, the most frequent syntactical errors, and the most frequent IO errors, respectively.

FUNC	IO	SYNTAX	BLEU	LOC	TOKENS	CYCLO	PARAMS	POIN
add	✗	✓	85.23	6	39	2	3	1
array_inc	✗	✓	87.6	5	34	2	2	1
array_prod	✓	✓	97.96	7	42	2	2	1
array_sum	✓	✓	97.8	7	42	2	2	1
binary_digits	✓	✓	97.27	8	31	2	1	0
binary_mul_sum	✗	✗	50.59	8	66	2	3	2
clamp	✗	✓	96.77	7	45	3	2	1
collatz	✓	✓	98.2	12	54	3	1	0
count_odds	✓	✓	87.58	9	52	3	2	1
cube_in_place	✗	✗	65.55	5	47	2	2	1
digit_prod	✗	✗	59.63	9	38	2	1	0
digits	✓	✓	82.32	8	31	2	1	0
diveq	✗	✓	75.31	5	41	2	3	2
diveq_sca	✗	✓	82.79	5	37	2	3	1
dot	✗	✓	97.5	7	51	2	3	2
elementwise_ _sum_of_ _negated_sum_ _and_max	✗	✗	3.25	15	122	4	4	3
eq	✗	✗	81.47	9	57	3	3	2
fact	✓	✓	96.94	8	31	2	1	0
fact_fact	✓	✓	96.94	8	31	2	1	0
fib_n	✓	✓	97.42	10	46	2	1	0
fourth_in_place	✗	✗	45.37	6	57	2	2	1
int_sqrt	✓	✓	86.34	9	43	2	1	0
last_elem	✓	✓	97.8	7	42	2	2	1
last_zero_idx	✓	✓	98.04	9	50	3	2	1
length	✗	✗	41.35	1	14	1	2	1
max	✗	✗	79.59	11	63	3	2	1
max_elt	✗	✗	87.36	9	53	3	2	1
min	✗	✗	80.04	11	63	3	2	1
min_elt	✗	✗	88.04	9	53	3	2	1
min_so_far_ _subtracted	✗	✓	0.0	18	157	6	4	3
mirror_image	✗	✗	77.16	9	61	3	3	2
muleq	✗	✓	73.78	5	41	2	3	2
muleq_sca	✗	✓	85.0	5	37	2	3	1
negate	✗	✓	87.71	5	38	2	2	1
pluseq	✗	✗	76.4	5	41	2	3	2
prod_elts	✓	✓	97.96	7	42	2	2	1
prod_n_squared	✓	✓	97.66	8	39	2	1	0
prod_sq_elts	✗	✗	85.46	8	49	2	2	1
replace_first	✗	✗	79.77	9	62	3	2	1
replace_last	✗	✗	79.89	9	62	3	2	1
reverse	✗	✗	55.01	7	62	2	2	1
reverse_int	✗	✗	61.04	9	37	2	1	0
search	✓	✓	95.23	9	59	4	3	1
sort	✗	✗	33.63	9	84	4	2	1
subeq	✗	✗	74.26	5	41	2	3	2
subeq_sca	✗	✓	89.73	5	37	2	3	1
subtract_of_ _min_reverse	✗	✗	46.71	8	82	3	4	3
sum_abs	✗	✗	59.81	7	57	3	2	1
sum_elts	✓	✓	97.8	7	42	2	2	1
sum_n	✓	✓	96.74	8	30	2	1	0
sum_n_squared	✓	✓	92.65	8	32	2	1	0
sum_of_lists_ _multiplied_ _after_dividing_ _by_three	✗	✗	18.44	13	105	4	3	2
sum_of_positives	✗	✗	44.02	10	91	4	4	3
sum_of_squares	✓	✓	98.27	7	47	2	2	1
triangle_prod	✓	✓	97.95	9	51	3	1	0

triangle_sum	✓	✓	97.86	9	51	3	1	0
vadd	✗	✗	73.97	5	50	2	4	3
vcopy	✗	✓	84.61	5	41	2	3	2
vfill	✗	✓	96.03	5	37	2	3	1
vmul	✗	✗	72.34	5	50	2	4	3
vneg	✗	✓	87.71	5	38	2	2	1
voffset	✗	✓	85.23	5	37	2	3	1
vscal	✗	✓	85.0	5	37	2	3	1
vsub	✗	✗	71.26	5	50	2	4	3

Table 5: Best model in Synthesis-Bench: IO and syntactic accuracy and BLEU of the model output, and cyclomatic complexity, n. of parameters and pointer parameters of the C function.

METRIC	CORRELATION (P-VALUE)
Syntax	**0.597 (1.92E-07)**
BLEU	**0.536 (4.96E-06)**
LOC	0.174 (1.69E-01)
Tokens	**-0.269 (3.13E-02)**
Cyclo	-0.106 (4.04E-01)
Params	**-0.607 (1.04E-07)**
Pointers	**-0.573 (7.56E-07)**

Table 6: Pearson correlations between different metrics (syntactical accuracy, BLEU score, lines of code and number of tokens in the C implementation, cyclomatic complexity of the C implementation, number of parameters in the C function, and number of pointer parameters in the C function) and IO accuracy. Bold values are statistically significant.

E   Expanded error analysis

Focusing on the outputs of the best model, we observe:

- When the model has one correct IO test in a given function, it is likely that the others will be also correct, as shown in Table 9. The probability of generating a program that only passes one unit test by chance is, indeed, very low.

- After manually inspecting the most frequent syntactical errors (Table 8), we find that most of these occur because the output finishes prematurely. For instance, it is common to find outputs with operators with unbalanced parentheses as the last instruction, not because the model has not learned the syntax, but because the decoding terminated in the middle of the program. This occurs when outputs are long and the model predicts the end of the program special token prematurely.

- In our experiments, IO accuracy does not correlate with cyclomatic complexity, a well-known code complexity measure, as shown in Table 6. We see two potential reasons for that, namely, 1. in Synthesis-Bench there are not enough functions to observe sufficient variability in cyclomatic complexity

MODEL	AVG OUTPUT LENGTH
Transformer-Small	**162.29**
Transformer-Med	124.94
Transformer-Big	124.61
- 50% data	125.00
- 1/2x vocab	127.22
+ 1/2x vocab	124.13
+ 1e2x weight-decay	124.74
+ 1/2x epochs	124.59
Transformer-Big+	124.99
Ground truth	132.37

Table 7: Average length of the output of the different models in the Angha-Par test, vs. the ground truth (GCC) one.

ERROR
open CFI at the end of file; missing .cfi_endproc directive
expecting operand after ','; got nothing
unbalanced brackets in operand 1.
number of operands mismatch for 'mov'
number of operands mismatch for 'add'
unbalanced brackets in operand 2.
bad or irreducible absolute expression
CFI instruction used without previous .cfi_startproc
junk at end of line, first unrecognised character is '%'
symbol '.L3' is already defined
number of operands mismatch for 'cmp'
symbol '.L5' is already defined
number of operands mismatch for 'movq'
number of operands mismatch for 'lea'
.cfi_endproc without corresponding .cfi_startproc
symbol '.L4' is already defined
operand type mismatch for 'sar'
number of operands mismatch for 'pop'
number of operands mismatch for 'sal'
number of operands mismatch for 'pxor'
number of operands mismatch for 'movslq'
.size expression for sum_n does not evaluate to a constant

Table 8: Frequent syntactical errors (sorted by frequency).

ERROR	
Syntax error	27
Compiled but 0 tests passed	15
Compiled but only 1 test passed	1
Compiled but more than 1 test passed	0

Table 9: IO error typology for the best model.

MODEL	INTERSECTIONS
Transformer-Small	0/0
Transformer-Med	18/19
Transformer-Big	19/19
- 50% data	13/13
- 1/2x vocab	19/19
+ 1/2x vocab	20/20
+ 1e2x weight-decay	18/18
+ 1/2x epochs	21/21
Transformer-Big+	19/19

Table 10: Intersections between the correct outputs of each model and the correct outputs of the best one (Transformer-Big + 1/2x epochs).

to observe the expected correlation, or 2. the sources of the errors are more simple (e.g., the mere presence of an array) than the complexity captured by cyclomatic complexity.. In fact, the number of function parameters and the number of points seems to be indeed negatively correlated with the IO accuracy. Thus, we conclude that the more function parameters and more pointers, the more difficult is for neural models to correctly interpret C and generate the corresponding assembler. Finally, with no surprise, syntactical accuracy and BLEU score positively correlate with IO accuracy, since correct solutions are clearly syntactically correct and, with a lesser degree, lexically similar to the GCC solution. However, the correlation is not strong enough for these metrics to be used as reliable proxies of the IO accuracy in case unit tests are not available.

- All models fail in the same functions: Table 10 shows that the intersection of IO errors between the different models is almost full, meaning that errors are related to some intrinsic difficulty of these functions (at least to neural compilers) and not to randomness in the training process.

- Model outputs do appear like GCC outputs, but with some artifacts such as unnecessary nop operations in some cases (see supplementary material).

- We observe some trivial errors. For instance, `true` and `false` (boolean values from `stdbool`) are confused with variable names. If they are manually replaced with 1 and 0, the models usually generate a correct output.

F   Output samples

We include some model output samples, together with the reference GCC output and the original C, selected as follows:

- All outputs belong to the best model, specifically they are one of the top 5 hypothesis.

- All outputs belong to Synthesis-Bench.

- They have not been randomly sampled, or cherry-picked to show the best outputs only, but manually curated to try to provide representative outputs of different cases, which may not appear proportionally.

Listing 1: C input

```
int triangle_sum(int n) {
  int r = 0;
  for (int i = 1; i < n;
        ++i) {
    for (int m = 1; m < i;
          ++m) {
      r += m;
    }
  }
  return r;
}
```

Listing 2: Model assembler

```
triangle_sum:
.LFB0:
 .cfi_startproc
 pushq %rbp
 .cfi_def_cfa_offset 16
 .cfi_offset 6, -16
 movq %rsp, %rbp
 .cfi_def_cfa_register 6
 movl %edi, -20(%rbp)
 movl $0, -12(%rbp)
 movl $1, -8(%rbp)
 jmp .L2
 .L5:
 movl $1, -4(%rbp)
 jmp .L3
 .L4:
 movl -4(%rbp), %eax
 addl %eax, -12(%rbp)
 addl $1, -4(%rbp)
 .L3:
 movl -4(%rbp), %eax
 cmpl -8(%rbp), %eax
 jl .L4
 addl $1, -8(%rbp)
 .L2:
 movl -8(%rbp), %eax
 cmpl -20(%rbp), %eax
 jl .L5
 movl -12(%rbp), %eax
 popq %rbp
 .cfi_def_cfa 7, 8
 ret
 .cfi_endproc
```

Listing 3: GCC assembler

```
triangle_sum:
.LFB0:
 .cfi_startproc
 endbr64
 pushq %rbp
 .cfi_def_cfa_offset 16
 .cfi_offset 6, -16
 movq %rsp, %rbp
 .cfi_def_cfa_register 6
 movl %edi, -20(%rbp)
 movl $0, -12(%rbp)
 movl $1, -8(%rbp)
 jmp .L2
.L5:
 movl $1, -4(%rbp)
 jmp .L3
.L4:
 movl -4(%rbp), %eax
 addl %eax, -12(%rbp)
 addl $1, -4(%rbp)
.L3:
 movl -4(%rbp), %eax
 cmpl -8(%rbp), %eax
 jl .L4
 addl $1, -8(%rbp)
.L2:
 movl -8(%rbp), %eax
 cmpl -20(%rbp), %eax
 jl .L5
 movl -12(%rbp), %eax
 popq %rbp
 .cfi_def_cfa 7, 8
 ret
 .cfi_endproc
```

Figure 1: Correct output sample in which the system output is almost identical to the GCC one. The only difference is the inclusion of the new instruction `endbr64`, which is used for security reasons and is executed as a `NOPs` in targets that do not support it.

Listing 4: C input

```c
int fib_n(int n) {
    int i = 1;
    int r = 1;
    while (n > 1) {
        i = r - i;
        r = i + r;
        n = n - 1;
    }
    return r;
}
```

Listing 5: Model assembler

```
fib_n:
.LFB0:
    .cfi_startproc
    pushq %rbp
    .cfi_def_cfa_offset 16
    .cfi_offset 6 , -16
    movq %rsp , %rbp
    .cfi_def_cfa_register 6
    movl %edi , -20 ( %rbp )
    movl $1 , -8 ( %rbp )
    movl $1 , -4 ( %rbp )
    jmp .L2
.L3:
    movl -4 ( %rbp ), %eax
    subl -8 ( %rbp ), %eax
    movl %eax , -8 ( %rbp )
    movl -8 ( %rbp ), %edx
    movl -4 ( %rbp ), %eax
    addl %edx , %eax
    movl %eax , -4 ( %rbp )
    subl $1 , -20 ( %rbp )
.L2:
    cmpl $1 , -20 ( %rbp )
    jg .L3
    movl -4 ( %rbp ), %eax
    popq %rbp
    .cfi_def_cfa 7 , 8
    ret
    .cfi_endproc
```

Listing 6: GCC assembler

```
fib_n:
.LFB0:
    .cfi_startproc
    endbr64
    pushq %rbp
    .cfi_def_cfa_offset 16
    .cfi_offset 6, -16
    movq %rsp , %rbp
    .cfi_def_cfa_register 6
    movl %edi , -20(%rbp)
    movl $1, -8(%rbp)
    movl $1, -4(%rbp)
    jmp .L2
.L3:
    movl -4(%rbp), %eax
    subl -8(%rbp), %eax
    movl %eax , -8(%rbp)
    movl -8(%rbp), %eax
    addl %eax , -4(%rbp)
    subl $1, -20(%rbp)
.L2:
    cmpl $1, -20(%rbp)
    jg .L3
    movl -4(%rbp), %eax
    popq %rbp
    .cfi_def_cfa 7, 8
    ret
    .cfi_endproc
```

Figure 2: Correct compilation of an iterative Fibonacci implementation, in which the system output subtly differs from the GCC one.

Listing 7: C input

```
int search(int *arr,
           int v,
           int n) {
  int idx = -1;
  for (int i = 0; i < n;
       ++i) {
    if (idx == -1 &&
        arr[i] == v) {
      idx = i;
    }
  }
  return idx;
}
```

Listing 8: Model assembler

```
search:
.LFB0:
  .cfi_startproc
  pushq %rbp
  .cfi_def_cfa_offset 16
  .cfi_offset 6, -16
  movq %rsp, %rbp
  .cfi_def_cfa_register 6
  movq %rdi, -24(%rbp)
  movl %esi, -28(%rbp)
  movl %edx, -32(%rbp)
  movl $-1, -8(%rbp)
  movl $0, -4(%rbp)
  jmp .L2
.L4:
  cmpl $-1, -8(%rbp)
  jne .L3
  movl -4(%rbp), %eax
  movslq %eax, %rdx
  movq -24(%rbp), %rax
  addq %rdx, %rax
  movl (%rax), %eax
  cmpl -28(%rbp), %eax
  jne .L3
  movl -4(%rbp), %eax
  movl %eax, -8(%rbp)
.L3:
  addl $1, -4(%rbp)
.L2:
  movl -4(%rbp), %eax
  cmpl -32(%rbp), %eax
  jl .L4
  movl -8(%rbp), %eax
  popq %rbp
  .cfi_def_cfa 7, 8
  ret
  .cfi_endproc
```

Listing 9: GCC assembler

```
search:
.LFB0:
  .cfi_startproc
  endbr64
  pushq %rbp
  .cfi_def_cfa_offset 16
  .cfi_offset 6, -16
  movq %rsp, %rbp
  .cfi_def_cfa_register 6
  movq %rdi, -24(%rbp)
  movl %esi, -28(%rbp)
  movl %edx, -32(%rbp)
  movl $-1, -8(%rbp)
  movl $0, -4(%rbp)
  jmp .L2
.L4:
  cmpl $-1, -8(%rbp)
  jne .L3
  movl -4(%rbp), %eax
  cltq
  leaq 0(,%rax,4), %rdx
  movq -24(%rbp), %rax
  addq %rdx, %rax
  movl (%rax), %eax
  cmpl %eax, -28(%rbp)
  jne .L3
  movl -4(%rbp), %eax
  movl %eax, -8(%rbp)
.L3:
  addl $1, -4(%rbp)
.L2:
  movl -4(%rbp), %eax
  cmpl -32(%rbp), %eax
  jl .L4
  movl -8(%rbp), %eax
  popq %rbp
  .cfi_def_cfa 7, 8
  ret
  .cfi_endproc
```

Figure 3: Incorrect output sample (top 3 hypothesis of the best model in the search function) that passes only some (5/9) of the IO examples. This is relatively uncommon, since usually either it passes all tests or none, and when one hypothesis in the top 5 ones obtains better than half of the examples right, it is likely that some other hypothesis will pass all tests, as happened in this case (top 1 and 2 hypothesis were correct).

Listing 10: C input

```c
void min_so_far_subtracted
(int *arr, int *arr2,
int *result, int n) {
  int min_so_far_array[n];
  int min_so_far = 1;

  for (int i = 0; i < n;
  i++) {
    min_so_far =
      (min_so_far < arr[i])
      ? min_so_far : 1;
    min_so_far_array[i] =
      min_so_far;
  }
  int max_of_min_so_far
    _and_other_array[n];
  for (int i = 0; i < n;
  i++) {
    int m1 = min_so_far
      _array[i];
      int m2 = arr2[i];
      int max = (m1 > m2
        ? m1 : m2);
    max_of_min_so_far
      _and_other_array[i]
      = max;
  }
  for (int i = 0; i < n;
      i++) {
        result[i] =
          min_so_far
          _array[i] -
          max_of_min_so
          _far_and_
          other_array
          [i];
  }
}
```

Listing 11: Model assembler

```
min_so_far_subtracted:
.LFB0:
 .cfi_startproc
 pushq %rbp
 .cfi_def_cfa_offset 16
 .cfi_offset 6, -16
 movq %rsp, %rbp
 .cfi_def_cfa_register 6
 movq %rdi, -8(%rbp)
 movq %rsi, -16(%rbp)
 movq %rdx, -24(%rbp)
 movl %ecx, -28(%rbp)
 movl %r8d, -32(%rbp)
 nop
 popq %rbp
 .cfi_def_cfa 7, 8
 ret
 .cfi_endproc
```

Listing 12: GCC assembler

```
min_so_far_subtracted:
.LFB0:
 .cfi_startproc
 endbr64
 pushq %rbp
 .cfi_def_cfa_offset 16
 .cfi_offset 6, -16
 movq %rsp, %rbp
 .cfi_def_cfa_register 6
 pushq %r15
 pushq %r14
 pushq %r13
 pushq %r12
 subq $112, %rsp
 .cfi_offset 15, -24
 .cfi_offset 14, -32
 .cfi_offset 13, -40
 .cfi_offset 12, -48
 movq %rdi, -120(%rbp)
 movq %rsi, -128(%rbp)
 movq %rdx, -136(%rbp)
 movl %ecx, -140(%rbp)
 movq %fs:40, %rax
 movq %rax, -40(%rbp)
 xorl %eax, %eax
 movq %rsp, %rax
 movq %rax, %rdi
 movl -140(%rbp), %eax
 movslq %eax, %rdx
 subq $1, %rdx
 movq %rdx, -72(%rbp)
 movslq %eax, %rdx
 movq %rdx, %r14
 movl $0, %r15d
 movslq %eax, %rdx
 movq %rdx, %r8
 movl $0, %r9d
 cltq
 leaq 0(,%rax,4), %rdx
 movl $16, %eax
 subq $1, %rax
 addq %rdx, %rax
 movl $16, %esi
 movl $0, %edx
 divq %rsi
 imulq $16, %rax, %rax
 movq %rax, %rdx
 andq $-4096, %rdx
 movq %rsp, %rsi
 subq %rdx, %rsi
 movq %rsi, %rdx
.L2:
 cmpq %rdx, %rsp
 # CONTINUES FOR 168
 # INSTRUCTIONS MORE...
 .cfi_endproc
```

Figure 4: Syntactically correct, yet meaningless output. This case follows a common pattern we have observed: when the input C is too complex for the model, the model just outputs a short, syntactically correct assembler that semantically has almost nothing to do with the input C. The model seems to behave like an unconditional assembler language model.

Listing 13: C input	Listing 14: Model assembler	Listing 15: GCC assembler

```
void norm(float *vec,
          float *o,
          int n) {
  float sum = 0.0f;
  for (int i = 0; i < n;
       ++i) {
    sum += vec[i];
  }

  for (int i = 0; i < n;
       ++i) {
    o[i] /= sum;
  }
}
```

```
subeq:
.LFB0:
  .cfi_startproc
  pushq %rbp
  .cfi_def_cfa_offset 16
  .cfi_offset 6, -16
  movq %rsp, %rbp
  .cfi_def_cfa_register 6
  movq %rdi, -24(%rbp)
  movq %rsi, -32(%rbp)
  movl %edx, -36(%rbp)
  movl $0, -4(%rbp)
  jmp .L2
.L3:
  movl -4(%rbp),%eax
  cltq
  leaq 0(,%rax,4), %rdx
  movq -24(%rbp), %rax
  addq %rdx, %rax
  movl -4(%rbp), %edx
  movslq %edx, %rdx
  leaq 0(,%rdx, 4), %rcx
  movq -24(%rbp), %rdx
  addq %rcx, %rdx
  movl (%rdx), %edx
  movl %edx, %ecx
  movl -4(%rbp), %edx
  movslq %edx, %rdx
  leaq 0(, %rdx, 4), %rsi
  movq -32(%rbp), %rdx
  addq %rsi, %rdx
  movl (%rdx), %edx
  subl %edx, %ecx
  movl %ecx, %edx
  movl %edx, (%rax)
  addl $1, -4(%rbp
```

```
norm:
.LFB0:
  .cfi_startproc
  endbr64
  pushq %rbp
  .cfi_def_cfa_offset 16
  .cfi_offset 6, -16
  movq %rsp, %rbp
  .cfi_def_cfa_register 6
  movq %rdi, -24(%rbp)
  movq %rsi, -32(%rbp)
  movl %edx, -36(%rbp)
  pxor %xmm0, %xmm0
  movss %xmm0, -12(%rbp)
  movl $0, -8(%rbp)
  jmp .L2
.L3:
  movl -8(%rbp), %eax
  cltq
  leaq 0(,%rax,4), %rdx
  movq -24(%rbp), %rax
  addq %rdx, %rax
  movss (%rax), %xmm0
  movss -12(%rbp), %xmm1
  addss %xmm1, %xmm0
  movss %xmm0, -12(%rbp)
  addl $1, -8(%rbp)
.L2:
  movl -8(%rbp), %eax
  cmpl -36(%rbp), %eax
  jl .L3
  movl $0, -4(%rbp)
  jmp .L4
.L5:
  movl -4(%rbp), %eax
  cltq
  leaq 0(,%rax,4), %rdx
  movq -32(%rbp), %rax
  addq %rdx, %rax
  movss (%rax), %xmm0
  movl -4(%rbp), %eax
  cltq
  leaq 0(,%rax,4), %rdx
  movq -32(%rbp), %rax
  addq %rdx, %rax
  divss -12(%rbp), %xmm0
  movss %xmm0, (%rax)
  addl $1, -4(%rbp)
.L4:
  movl -4(%rbp), %eax
  cmpl -36(%rbp), %eax
  jl .L5
  nop
  nop
  popq %rbp
  .cfi_def_cfa 7, 8
  ret
  .cfi_endproc
```

Figure 5: Syntactically incorrect output (unbalanced parentheses in the last `addl` instruction) that actually is caused by the hypothesis terminating before it should have, like most detected syntax errors.

G Code and Data Availability

We plan to release[3] the code and data used in this work with an open license.

---

[3]For the camera-ready version.