I-LLM: Efficient Integer-Only Inference for Fully-Quantized Low-Bit Large Language Model

Abstract

Post-training quantization (PTQ) serves as a potent technique to accelerate the inference of large language models (LLMs). Nonetheless, existing works still necessitate a considerable number of floating-point (FP) operations during inference, including additional quantization and de-quantization, as well as non-linear operators such as RMSNorm and Softmax. This limitation hinders the deployment of LLMs on the edge and cloud devices. In this paper, we identify the primary obstacle to integer-only quantization for LLMs lies in the large fluctuation of activations across channels and tokens in both linear and non-linear operations. To address this issue, we propose I-LLM, a novel integer-only fully-quantized PTQ framework tailored for LLMs. Specifically, (1) we develop Fully-Smooth Block-Reconstruction (FSBR) to aggressively smooth inter-channel variations of all activations and weights. (2) to alleviate degradation caused by inter-token variations, we introduce a novel approach called Dynamic Integer-only MatMul (DI-MatMul). This method enables dynamic quantization in full-integer matrix multiplication by dynamically quantizing the input and outputs with integer-only operations. (3) we design DI-ClippedSoftmax, DI-Exp, and DI-Normalization, which utilize bit shift to execute non-linear operators efficiently while maintaining accuracy. The experiment shows that our I-LLM achieves comparable accuracy to the FP baseline and outperforms non-integer quantization methods. For example, I-LLM can operate at W4A4 with negligible loss of accuracy. To our knowledge, we are the first to bridge the gap between integer-only quantization and LLMs. We've published our code on anonymous.4open.science, aiming to contribute to the advancement of this field.

1 Introduction

Large Language Models (LLMs) have paved the way for general artificial intelligence with their remarkable performance across a wide range of tasks. However, the rising number of parameters and computing power requirements of LLMs pose significant challenges when it comes to deployment.

Post-training quantization (PTQ) is a powerful technique employed to accelerate the inference process of LLMs. Previous PTQ methods for LLMs have primarily relied on simulated quantization (aka. fake quantization) (Xiao et al., 2022; Shao et al., 2023; Wei et al., 2022b; Yuan et al., 2023a), where integer values are typically used for inputs/outputs and compute-intensive operations are performed using dequantized floating-point (FP) values (as shown in Fig1). Although this scheme offers benefits in scenarios where data transmission bandwidth is limited, it does not effectively reduce computational costs and thus has little effect on compute-bound situations. Besides, non-linear operations (e.g., Softmax and RMSNorm) often involve complex operations, including transcendental functions such as exponential functions and square root functions. These functions are typically performed on dedicated FP units and may require multiple iterations for accurate computation.

In contrast, integer-only quantization (Jacob et al., 2018; Wu et al., 2020; Qin et al., 2022; Li & Gu, 2023; Lin et al., 2022) utilizes low-precision integer arithmetic for all operations, including linear operations (e.g., matrix multiplication) and non-linear operations. It enables quantized models to take full advantage of fast and efficient integer arithmetic units, resulting in promising speedup effects and reduction of latency and power consumption. Additionally, integer-only quantization facilitates

Figure 1: Typical LLM quantization vs. I-LLM. The former requires dequantization and involves FP arithmetic, while the latter performs the entire inference using integer-only arithmetic.

Figure 2: PPL↓ of different PTQ methods on LLaMA family using W8A8. Notably, due to the exceptionally high PPL of I-Bert, a dedicated y-axis has been allocated for its representation.

deployment on popular edge processors specifically designed for embedded, mobile, or IoT devices, which often lack dedicated floating point units. Examples of such edge processors include ARM Cortex-M (WIKIPEDIA, 2024), GreenWaves GAP-9 (Flamand et al., 2018), and Google's Edge TPU (Google, 2024). Note that Turing Tensor Cores in GPU server-class devices also have introduced support for integer logical units, offering notably lower latency compared to FP arithmetic.

However, the aforementioned integer-only methods are designed specifically for CNNs or small Transformer networks (e.g., Bert Kim et al. (2021) and ViT Dosovitskiy et al. (2020)), which renders them inadequate for LLMs. First, they are incapable of straightforwardly supporting the non-linear operators inherent in LLMs, such as SwiGLU and RMSNorm. Furthermore, their accuracy on LLMs deteriorates significantly (as depicted in Figure 2), even when those non-supported operators are executed in full-precision mode. This is because as the model size increasing, the presence of activation outliers in both linear and non-linear layers becomes prominent. As illustrated in Fig 3, Llama2-7B exhibits substantial variations in activation magnitude at both the token and channel levels, making previous approaches ineffective. Last but not least, these methods are limited to 8-bit quantization, whereas LLMs would benefit from lower bit-width quantization (e.g., 4-bit) to address the extensive computational requirements and storage demands. **Consequently, how to accurately perform LLMs with efficient integer-only arithmetic remains an unresolved issue that requires further investigation.**

In this paper, we identify the primary obstacle to integer-only quantization for LLMs lies in the large fluctuation of activations across channels and tokens in both linear and non-linear operators. To address this issue, we introduce I-LLM, a novel integer-only PTQ framework tailored for LLMs: (1) We propose Fully-Smooth Block-Reconstruction (FSBR) to harmonize the variance in activation across channels. While Omniquant Shao et al. (2023) and Smoothquant Xiao et al. (2022) share some similarities, they primarily focus on smoothing the activation in serial norm-linear and parallel linear-linear operations. We argue that mitigating the disparities of all suitable activation-activation and activation-weight pairs of LLMs (see Fig.5) significantly enhances accuracy. For instance, the input of SwiGLU encounters numerous disparities on both token-wise and channel-wise dimensions, as depicted in Fig.4-a. To achieve smoothing on such a non-linear operator, we decom-

The performance of different quantization methods on six zero-shot datasets using the LLaMA-30B under W4A4 setting.

pose SiLU into $x \cdot \sigma(x)$ to apply FSBR, and as a result the input becomes more consistent and amenable to quantization, as shown in Fig.4-b. (2) To alleviate the degradation resulting from inter-token variations, we present a novel approach called Dynamic Integer-only MatMul (DI-MatMul). DI-MatMul facilitates quantization on full-integer matrix multiplication by employing integer-only operations to quantize the input and outputs dynamically. Traditional static quantization methods, which are characterized by their lack of robustness and adaptability, often falter when encountering input beyond the calibration set. In contrast, DI-MatMul is designed to proactively recognize and

Figure 3: Differences in activations of the non-linear operator in LLaMA2 7b model across the channel/token dimensions.

Figure 4: The input activation distribution of the SwiGLU before FSBR (a) and after FSBR (b).

adapt to the diverse range of input data, thereby reducing quantization errors and enhancing overall model performance. (3) For non-linear operators, we design DI-ClippedSoftmax, DI-Exp, and DI-Norm, which leverage the efficiency of bit shifting to replace complex math calculations while maintaining accuracy. Our contributions are summarized as:

1. We identify the primary obstacle to integer-only quantization for LLMs lies in the large fluctuation of activations across channels and tokens in both linear and non-linear operators. To address inter-channel variations, we propose FSBR to effectively reduces disparities among all suitable activation-activation and activation-weight pairs, thereby markedly improving accuracy.

2. We attribute the failure of previous integer-only quantization methods on LLMs to various range in activation tokens. To tackle this problem, we introduce DI-MatMul, which enables dynamic quantization on input and output through full-integer matrix multiplication. DI-MatMul proactively adapts to the range of input, minimizing quantization errors and improving overall performance.

3. We introduce DI-Exp, DI-ClippedSoftmax, and DI-Norm, innovative integer-only operators that harness the power of bit shifting to replace complex mathematical computations within the non-linear functions of LLMs, without compromising on accuracy.

4. To the best of our knowledge, this work represents the first attempt to utilize integer-only quantization for LLMs, enabling their deployment on edge devices that lack floating-point capabilities. Experiments demonstrate remarkable accuracy when compared to SOTA non-integer quantization techniques; for instance, I-LLM on LLAMA-13b achieves an approximate 20% reduction in perplexity. Additionally, our integer-only algorithm achieves a 2x improvement in computational performance and a 3.5x reduction in memory usage compared to the full-precision model.

2 RELATED WORK

LLMs Quantization. LLMs quantization can be broadly categorized into weight-only and weight-activation quantization. To alleviate the computational burdens, some works (Liu et al., 2023b; Frantar et al., 2022; Chee et al., 2023; Lin et al., 2023; Lee et al., 2023; Shang et al., 2023; Kim et al., 2023; Dettmers et al., 2023) make efforts in weight-only quantization. GPTQ (Frantar et al., 2022) and QuIP (Chee et al., 2023) achieve high compression rates by optimizing matrix multiplications operation. AWQ (Lin et al., 2023) and OWQ (Lee et al., 2023) demonstrate performance improvements by accounting for the impact of activation outliers on weight quantization. Moreover, works such as QLORA (Dettmers et al., 2024), QA-lora (Xu et al., 2023) and LoftQ (Li et al., 2023b) leverage Parameter Efficient Fine-Tuning (PEFT) techniques to achieve weight compression with fine-tuning tasks. Different with weight-only quantization methods, towards to accelerate the LLMs inference, the weight-activation quantization methods (Wei et al., 2022b; Yuan et al., 2023a; Wei et al., 2023; Li et al., 2023a; Yuan et al., 2023b; Yue et al., 2024) quantize both the weights and activations, including the KV cache. The primary challenge in quantizing activations lies in

outliers, leading to significant quantization errors. To tackle this issue, ZeroQuant (Yao et al., 2022) proposes a fine-grained hardware-friendly quantization scheme for both weight and activations. SmoothQuant (Xiao et al., 2022) migrates the quantization difficulty from activations to weights with a mathematically equivalent transformation (i.e., per-channel scaling). OmniQuant (Shao et al., 2023) further enhances performance by training the quantization parameters. While these methods have mitigated the quantization error, their inference pipelines still involve partially FP operations on non-linear operators such as Softmax, Normalization, and SiLU. In this study, our focus on achieving Integer-only inference for LLMs model using advanced PTQ (Li et al., 2021; Wei et al., 2022a; Liu et al., 2023a; Zhou et al., 2024) techniques.

Integer-only Quantization. Current quantization methods for LLMs often involve dequantized FP operations during inference, limiting the utilization of efficient low-precision arithmetic units. Integer-only quantization, eliminating dequantization, enables complete inference using Integer-only arithmetic, promising enhanced model acceleration. Previous approaches (Jacob et al., 2018; Yao et al., 2021) leverage dyadic arithmetic for Integer-only pipeline on CNNs, but these are tailored for linear operations and are unsuitable for non-linear operations in ViTs. Applying INT arithmetic solely to linear operations while retaining FP arithmetic for non-linear ones maybe a straightforward solution, but this demands custom hardware and introduces computational overheads. Advancements include Fully-8bit (Lin et al., 2021) and I-BERT (Kim et al., 2021), which address non-linear operations through employs L1 LayerNorm and INT polynomial approximations for the non-linear operations. However, these methods face inefficiencies or fail to fully exploit hardware advantages. Based on I-BERT (Kim et al., 2021), FQ-ViT (Lin et al., 2022) extends INT arithmetic to part of the operations but overlooks significant non-linear operations like GELU. While some methods (Stevens et al., 2021; Zhu et al., 2020) retain FP arithmetic during approximation, they cannot meet the requirement for Integer-only arithmetic. Recently, I-ViT (Li & Gu, 2023) introduces Integer-only quantization for ViTs, yet its suitability for LLMs is questionable due to differing data distributions, and its computational graph includes partially INT32 precision operations. In this paper, we focus on Integer-only inference for LLMs, maintaining the entire computational graph at INT8 precision or lower bit (e.g., 6/4-bit), enhancing LLMs' inference efficiency on edge processors.

3 METHOD

Challenges of Integer-Only Quantization for Large Language Models. Presently, integer-only LLMs encounter two primary hurdles: (1) quantizing the activation of LLMs, especially those originating from non-linear operators, poses a formidable challenge. As evidenced in Fig 3, the divergence in these non-linear activations often surpasses that of linear operators, particularly pronounced in models such as LLaMA (Touvron et al., 2023a). Previous methods have failed to address these non-linear activations, and straightforwardly quantizing non-linear layers may lead to substantial accuracy degradation. (2) prior integer-only quantization techniques have overlooked the distinctive traits of LLMs, including divergent activation scales and the substantial overhead of loading large-scale weights. Even the W8A8 method introduced in I-BERT can lead to catastrophic outcomes, as shown in Fig 2, let alone more aggressive quantization methods like W6A6 or W4A4.

In this section, we introduce a novel integer-only quantization framework termed I-LLM. As illustrated in Fig 5, this framework incorporates a differentiable approach within the Post-Training Quantization (PTQ) paradigm, termed Fully-Smooth Block Reconstruction. This method is designed to effectively balance all feasible parameter pairs, as elaborated in Section 3.2. Furthermore, we advance the develop of dynamic quantization within the integer-only context by introducing DI-MatMul, a dynamic integer-only matrix multiplication method, which is elucidated in Section 3.3. Additionally, we detail integer-only non-linear approximations, including DI-ClippedSoftmax, DI-exp, and DI-Norm, that are built upon DI-MatMul and are presented in Section 3.4. These operators facilitate 8-bit input activations while minimizing accuracy loss.

3.1 BASIC MATHEMATICAL NOTATIONS

Matrices are denoted by bold uppercase letters such as X, vectors by bold lowercase letters such as x. Floating-point and integer numbers are distinguished using the superscript I, for example, x^I for integers and x for floating-point numbers. The notation $\mathcal{Q}$ means the quant function, $\lfloor \cdot \rfloor$ represents the floor function, and $\lfloor \cdot \rceil$ denotes rounding to the nearest integer. The symbol $\otimes$ indicates

Figure 5: Details of I-LLM in a transformer block. The left side of the figure illustrates various paradigms for channel-wise smoothing during the FSBR process. The right side depicts the integer-only execution pipeline for both linear operators, such as matrix multiplication (MatMul), and non-linear operators.

element-wise multiplication, while $\oslash$ denotes element-wise division. Other mathematical symbols follow their standard definitions.

3.2 FULLY-SMOOTH BLOCK-RECONSTRUCTION (FSBR)

As mention above, to mitigate the issue of non-linear layer activations in LLMs being affected by channel and token differences (Fig 3 and 4), we propose Fully-Smooth Block-Reconstruction (FSBR). An intuitive method is to train a smoothing coefficient for all activations and weights to aid in restoring the model's quantization accuracy, especially the quantization accuracy of non-linear operators. Therefore, we consider the activations of all non-linear layers and learn the smoothing coefficients for all possible equivalent smoothing transformations at the channel level. On the left side of Fig 5, four paradigms for achieving inter-channel smoothing during block reconstruction are shown: Parallel Linear-Linear, Serial Linear-Norm, Serial Linear-Linear, and NonLinear Act-Smooth. The first three smoothing methods are indeed linear, making them easier to implement.

However, when addressing non-linear operators (NonLinear Act-Smooth) in LLMs, such as the gated activation function (SwiGLU), it becomes challenging to apply any linear transformations to them. For convenience, we can represent SwiGLU using the following formula:

$$\begin{aligned}
\mathrm{SwiGLU}(\boldsymbol{x}, \boldsymbol{W}, \boldsymbol{V}, \boldsymbol{b}, \boldsymbol{c}) &= \mathrm{SiLU}(\boldsymbol{x}\boldsymbol{W} + \boldsymbol{b}) \otimes (\boldsymbol{x}\boldsymbol{V} + \boldsymbol{c}) \\
&= \boldsymbol{x1} \otimes \boldsymbol{x2} \otimes \sigma(\boldsymbol{x1})
\end{aligned} \tag{1}$$

Where $x \in \mathbb{R}^{ic}$ is a vector, $\boldsymbol{W}, \boldsymbol{V} \in \mathbb{R}^{ic \times oc}$ are weight matrices, and $\boldsymbol{b}, \boldsymbol{c} \in \mathbb{R}^{oc}$ represent biases. $\boldsymbol{x1} = \boldsymbol{x}\boldsymbol{W} + \boldsymbol{b}$, $\boldsymbol{x2} = \boldsymbol{x}\boldsymbol{V} + \boldsymbol{c}$. SiLU stands for Sigmoid-Weighted Linear Unit. σ represents the sigmoid activation function. In order to jointly balance the activation and weight quantization difficulties of $\boldsymbol{x1}$ and $\boldsymbol{x2}$, we introduce a smoothing factor $\boldsymbol{s}$, expressed in the formula as follows:

$$\begin{aligned}
\mathrm{SwiGLU}(\boldsymbol{x}, \boldsymbol{W}, \boldsymbol{V}, \boldsymbol{b}, \boldsymbol{c}) &= (\boldsymbol{x1} \otimes \boldsymbol{s}) \otimes (\boldsymbol{x2} \oslash \boldsymbol{s}) \otimes \sigma'(\boldsymbol{x1}) \\
&= \boldsymbol{x1'} \otimes \boldsymbol{x2'} \otimes \sigma'(\boldsymbol{x1'})
\end{aligned} \tag{2}$$

Where $\boldsymbol{W'} = \boldsymbol{W} \otimes \boldsymbol{s}, \quad \boldsymbol{b'} = \boldsymbol{b} \otimes \boldsymbol{s}, \quad \boldsymbol{V'} = \boldsymbol{V} \oslash \boldsymbol{s}, \quad \boldsymbol{c'} = \boldsymbol{c} \oslash \boldsymbol{s}, \boldsymbol{x1'} = \boldsymbol{x}\boldsymbol{W'} + \boldsymbol{b'}, \quad \boldsymbol{x2'} = \boldsymbol{x}\boldsymbol{V'} + \boldsymbol{c'}, \quad \sigma'(\boldsymbol{x1'}) = \sigma(\boldsymbol{x1'} \oslash \boldsymbol{s})$. As shown by the red dashed box in Fig 5, during reconstruction, we first incorporate $\boldsymbol{s}$ into the weights. After calculating $\boldsymbol{x1'}$ and $\boldsymbol{x2'}$, we quantize them before proceeding with the computation. The forward inference process of SwiGLU can be expressed as: $\mathrm{SwiGLU}(\boldsymbol{x}) = \mathcal{Q}(\mathcal{Q}(\boldsymbol{x})\mathcal{Q}(\boldsymbol{W'}) + \boldsymbol{b'}) \otimes \mathcal{Q}(\mathcal{Q}(\boldsymbol{x})\mathcal{Q}(\boldsymbol{V'}) + \boldsymbol{c'}) \otimes \sigma'(\mathcal{Q}(\mathcal{Q}(\boldsymbol{x})\mathcal{Q}(\boldsymbol{W'}) + \boldsymbol{b'}))$. After block reconstruction, it is natural to incorporate the smoothing factor $\boldsymbol{s}$ into the weights. The only difference lies in replacing the original activation function σ with σ', which incurs negligible overhead. Fig 4 presents the output activation distribution of the gated unit in SwiGLU before and after the FSBR. It can be observed that the significant imbalance between channels and tokens, as depicted in Fig 4-a, is effectively alleviated after FSBR (Fig 4-b).

It is worth noting that SmoothQuantXiao et al. (2022) and OmniQuantShao et al. (2023) are subsets of FSBR. FSBR encompasses various previous equivalent quantization algorithms, providing more possibilities for optimizing the distribution of weights and activations. Through mutual optimization across channels, the network demonstrates improved robustness to quantization, as shown in Table 5.

3.3 DYNAMIC INTERGER-ONLY MATMUL (DI-MATMUL)

The dynadic arithmetic pipeline is an efficient approach that implements floating-point operations using integer bit-shifts, allowing linear operations to be performed solely through integer arithmetic. Initially developed for convolutional neural networks Jacob et al. (2018), this technique has been extended to Vision Transformers by I-ViT Li & Gu (2023). However, these methods primarily focus on static quantization, where the quantization parameters of the model's activation are fixed during runtime. In the context of LLMs, even after applying inter-channel smoothing, there still exists considerable variation in activation on a token-wise basis, as shown in Fig. 6 in Appendix A. Employing static quantization can result in significant quantization errors and subsequent degradation in accuracy, as depicted in the Fig. 2. Therefore, implementing dynamic quantization for inputs and outputs while adhering to Integer-only constraints poses a significant challenge.

We propose a novel DI-MatMul approach, where the matrix multiplication is formulated as $\boldsymbol{Y^I}, s_y, zp^I = \mathcal{M}(s_1, zp_1^I, \boldsymbol{X_1}, s_2, zp_2^I, \boldsymbol{X_2})$. Herein, s_1, s_2, and s_y are floating-point scalars representing the quantization steps for the inputs and outputs respectively; while zp_1^I and zp_2^I denote zero-points. To avoid floating-point operations in our method, we represent quantization step s using a dyadic number (DN), i.e., $\frac{m^I}{2^{k^I}}$ where both m^I and k^I are 8-bit integers. Consequently, the entire matrix multiplication can be expressed as:

$$\boldsymbol{Y^I}, m_y^I, k_y^I, zp^I = \mathcal{M}(m_1^I, k_1^I, zp_1^I, \boldsymbol{X_1}, m_2^I, k_2^I, zp_2^I, \boldsymbol{X_2}) \tag{3}$$

For a single matrix multiplication operation:

$$\boldsymbol{P^I} = (\boldsymbol{X_1^I} - zp_1^I)(\boldsymbol{X_2^I} - zp_2^I), \quad \boldsymbol{Y} = \boldsymbol{P^I} \frac{m_1^I m_2^I}{2^{k_1^I + k_2^I}} \tag{4}$$

The intermediate result of the matrix multiplication is denoted as $\boldsymbol{P^I}$. By applying Eq 14 in Appendix and preliminary Eq 3, we obtain the following approximation:

$$\frac{m_y^I}{2^{k_y^I}} \approx s_y = \frac{(p_{\max}^I - p_{\min}^I) \cdot m_1^I \cdot m_2^I}{(2^{n^I} - 1) \cdot 2^{k_1^I + k_2^I}} \tag{5}$$

where $p_{\max}^I$ and $p_{\min}^I$ denote the maximum and minimum values in $\boldsymbol{P^I}$. To obtain the quantization scale of the output:

$$\arg \min_{m_y^I, k_y^I} \left\| \frac{(p_{\max}^I - p_{\min}^I) \cdot m_1^I \cdot m_2^I}{(2^{n^I} - 1) \cdot 2^{k_1^I + k_2^I}} - \frac{m_y^I}{2^{k_y^I}} \right\|_1 \quad \text{s.t.} \quad m_y^I, k_y^I \in 0, 1, 2, \dots, 255 \tag{6}$$

Obtaining the optimal values for m_y^I and k_y^I may require multiple iterations. However, by induction, it is known that if an optimal value of k_0^I is achieved for k_y^I, then increasing it to $k_0^I + 1$ will not result in a worse outcome. Therefore, we set $m_y^I = 256$ to determine the value of k_y^I, and subsequently solve for the remaining variables as follows:

$$k_y^I = \left\lfloor \log_2 \left(\frac{256 \cdot (2^{n^I} - 1) \cdot 2^{k_1^I + k_2^I}}{p_{\max}^I - p_{\min}^I} \right) \right\rfloor = \left\lfloor \log_2 \left(\frac{(2^{n^I} - 1) \cdot 2^{k_1^I + k_2^I + 8}}{p_{\max}^I - p_{\min}^I} \right) \right\rfloor \tag{7}$$

$$m_y^I = \left\lfloor \frac{(p_{\max}^I - p_{\min}^I) \cdot m_{x1}^I \cdot m_{x2}^I}{n^I} \gg (k_1^I + k_2^I - k_y^I) \right\rfloor \tag{8}$$

$$z_y^I = \left\lfloor \frac{-p_{\min}^I \cdot (2^{n^I} - 1)}{p_{\max}^I - p_{\min}^I} \right\rceil, \quad \boldsymbol{Y^I} = \left\lfloor \frac{(\boldsymbol{P^I} - p_{\min}^I) \cdot (2^{n^I} - 1)}{p_{\max}^I - p_{\min}^I} \right\rceil \tag{9}$$

The implementation of $\lfloor \log_2(\cdot) \rfloor$ can be achieved using either the Most Significant Bit (MSB) method or by performing iterative right shifts. As shown in Eq equation 7, equation 8, and equation 9, our approach introduces only a few additional integer-only scalar computations during runtime, making

it more efficient than previous methods. For the Dense layers in Large Language Models (LLMs), one can simply replace an input with its corresponding weights. During inference, since the input usually consists of a single token, this allows for per-token dynamic quantization naturally. In the prefill phase, we adjust the required dimensions accordingly; for instance, we define $\boldsymbol{m^I}$ and $\boldsymbol{k^I}$ as vectors in $\mathbb{R}^{\text{token}}$.

3.4 DYNAMIC NON-LINEAR INTEGER-ONLY OPERATIONS

3.4.1 DYNAMIC INTERGER-ONLY CLIPPED SOFTMAX & DYNAMIC INTEGER-ONLY EXPONENT FUNCTION

The Softmax function converts attention scores into a probability distribution. It can be represented as follows:

$$\text{Softmax}(x_i) = \frac{e^{x_i}}{\sum_{j=0}^{i} e^{x_j}} = \frac{e^{x_i - x_{\max}}}{\sum_{j=0}^{i} e^{x_j - x_{\max}}}, \quad \text{where } i = 1, 2, \cdots, d \tag{10}$$

We introduce DI-ClippedSoftmax to avoid quantizing the entire input range. As shown in Fig 3, the activation inputs to the Softmax function in LLMs can exhibit significant outliers, with their magnitudes being proportional to the number of tokens. Fortunately, the DI-MatMul approach proposed in Section 3.3 allows for the differences between tokens to be handled individually. However, simply applying 8-bit quantization to the Softmax inputs would result in substantial precision loss, as demonstrated by the ablation studies in Section 6. Starting from the observation that the value of the exponential function at -20 can be considered to be zero, this implies that, for each token, only the values within the range $(x_{\max} - 20, x_{\max})$ contribute to the result. For a single token, we can constrain the quantization range by limiting $p_{\min}^I$ as defined in Eq 5. Assuming we want to confine the range within $(p_{\max} - c, p_{\max})$, we first represent c as a dyadic number, i.e., $c = \frac{m_c^I}{2^{k_c^I}}$. Combining this with Eq 5, the entire truncation process can be expressed as follows:

$$p_{min}^I = \max(p_{min}^I, p_{max}^I - c^I) \quad, \text{where } c^I = m_c^I \cdot 2^{k_1^I + k_2^I - k_c^I} \tag{11}$$

Therefore, regardless of the dynamic range, the length of our quantization range will never exceed c. In our hyper-parameters tuning experiments (Table 6), we select the optimal value of $c = 15$, ensuring that the maximum quantization error does not exceed 0.047.

We also propose Dynamic Interger-only Exponent function(DI-Exp), an exponential computation method that performs non-linear calculations of the exponential function using only shift operations. For a dynamically quantized input composed of $\boldsymbol{x^I}, m_x^I, k_x^I$, where $\boldsymbol{x^I}$ is already the result after subtracting the maximum value, the computation of the exponential can be expressed as:

$$e^{\boldsymbol{x^I} \cdot \left(m_x^I \gg k_x^I\right)} = 2^{\boldsymbol{x^I} \cdot \left(m_x^I \gg k_x^I\right) \cdot \log_2 e} = 2^{\boldsymbol{x^I} \cdot m_x^I \cdot \left(\log_2 e \gg k_x^I\right)} \tag{12}$$

We let $s = \frac{\log_2 e}{2^{k_x^I}}$ and $s^I = \left\lfloor \frac{2^{k_x^I}}{\log_2 e} \right\rfloor$, then: $e^{\boldsymbol{x^I} \cdot \left(m_x^I \gg k_x^I\right)} \approx 2^{\left(\left\lfloor \frac{\boldsymbol{x^I}}{s^I} \right\rfloor + \left(\boldsymbol{x^I} \% s^I\right) s\right)} \approx 2^{-q^I + r^I \cdot s}$

where $q^I = -\left\lfloor \frac{\boldsymbol{x^I}}{s^I} \right\rfloor$, $r^I = \boldsymbol{x^I} \% s^I$ It is known that $r^I \cdot s \in (-1, 0]$, therefore, we can simply perform linear interpolation within this interval. That is, $2^{r^I \cdot s} \approx 1 - \frac{r^I}{2 \cdot s^I}$ Finally, we obtain:

$$e^{\boldsymbol{x^I} \cdot \left(m_x^I \gg k_x^I\right)} \approx \left(1 - \frac{r^I}{2 \cdot s^I}\right) \gg q^I \tag{13}$$

In DI-Exp, nonlinearity is achieved using only shift operations, which improves computational efficiency compared to complex methods such as quadratic fitting and Taylor series expansion. Only the calculation of s^I and the linear interpolation within a small interval introduce errors, while other computations remain equivalent to the original. Detailed implementation of DI-Exp is in Algorithm1.

3.4.2 DYNAMIC INTERGER-ONLY NORMALIZATION & DYNAMIC INTERGER-ONLY SWIGLU

DI-Norm. LayerNorm and RMSNorm are commonly used normalization methods in LLMs. RMSNorm represents a lightweight improvement over LayerNorm, as it does not necessitate the computation of means and biases, thereby reducing computational complexity. Both RMSNorm and LayerNorm exhibit similar characteristics, with significant fluctuations at the channel level. As

depicted in the Fig 3, RMSNorm often exhibits more pronounced differences between channels due to the absence of a centering step. We propose Dynamic Integer-only Normalization (DI-Norm) to adapt to fluctuations between channels. When conducting FSBR, we perform per-channel quantization on the inputs of LayerNorm and RMSNorm. During inference, while computing the mean is straightforward, calculating the variance requires an appropriate root mean square function. Unlike the Newton's method used in I-BERT, to ensure consistency between inference and training, we employ a bit-wise check method as mentioned in the Algorithm 4 to achieve higher precision.

DI-SwiGLU. During the block reconstruction stage, we decompose the SiLU activation function of SwiGLU into $\text{SiLU}(\boldsymbol{x}) = \boldsymbol{x} \cdot \sigma(\boldsymbol{x})$ to achieve non-linear smoothing. As described in Algorithm 3, we implement the Dynamic Integer-only SwiGLU (DI-SwiGLU), consisting of a single sigmoid nonlinearity and two multiplication operations, where the sigmoid implementation involves multiple invocations of our proposed DI-Exp operator.

4 EXPERIMENTS

Implementation Details. I-LLM ensures that the activation of all non-linear operators remains at 8 bits, while the weights and activations of linear operators are determined by the current quantization configuration, such as W4A8. Consistent with other methods, we employ 128 samples for reconstruction. During the reconstruction phase, we maintain that the input to Softmax is not quantized and ensure that all smoothing coefficients maintain a common learning rate of 5×10^{-3}. After the reconstruction, all operators will be replaced with respective versions supporting dynamic integer-only inference. All experiments are conducted on Nvidia A6000 GPU.

Models & Evaluation Metric. We conduct experiments on several commonly used open-source LLMs, including OPT (Zhang et al., 2022), LLaMA (Touvron et al., 2023a), and LLaMA2 (Touvron et al., 2023b). Additionally, we also evaluated the recently impressive LLaMA3-8B model. For the sake of comparison, we tested the impact of quantization on Perperxity on two of the most commonly used datasets WikiText2 (Merity et al., 2016) and C4 (Raffel et al., 2020). Moreover, accuracy is evaluated in zero-short tasks including PIQA (Bisk et al., 2020), ARC (Boratko et al., 2018), BoolQ (Clark et al., 2019), HellaSwag (Zellers et al., 2019), Winogrande (Sakaguchi et al., 2021).

4.1 QUANTITATIVE RESULTS

Notably, our work is the first to address integer-only quantization for LLMs, whereas all the methods we compare against in our experiments are not integer-only except I-Bert. Although this may seem somewhat unfair for us, I-LLM still demonstrates the superiority through its remarkable performance.

Fig 2 illustrates the efficacy of our 8-bit quantization technique on widely adopted large-scale language models. Despite SmoothQuant's prior success with 8-bit quantization, our approach demonstrates performance for each model that is closer to floating-point precision. This suggests that even with low-bit quantization using integer-only conditions (e.g., 8-bit), we can achieve performance comparable to floating-point representation. These findings strongly validate the effectiveness of our proposed I-LLM, as it enables integer-only operators to yield results highly akin to those obtained through floating-point operations, using simple arithmetic and integer bit-shifting.

Quantization results on OPT and LLaMA. As shown in Table 1 and Table 2, we report the perplexity performance of I-LLM on the C4 and WikiText2 datasets. As depicted in these tables, I-LLM consistently surpasses previous methods across a diverse array of LLM families (OPT 6.7B-30B, LLaMA-1 7B-30B, LLaMA-2 7B-13B, LLaMA-3 8B) and varying levels of precision. Particularly noteworthy is its performance under the W4A4 setting, where our proposed method achieves perplexity values that are consistently 10% to 30% lower than those attained by state-of-the-art methods.

Table 1: Quantitative weight-activation quantization PPL($\downarrow$) results on OPT Family of I-LLM.

#Bits	Method	OPT-6.7B		OPT-13B		OPT-30B	
		WikiText2	C4	WikiText2	C4	WikiText2	C4
FP16	-	10.86	11.74	10.13	11.20	9.56	10.69
W6A6	SmoothQuant	11.34	12.14	10.56	11.40	9.67	10.81
	RPTQ	11.19	12.08	11.00	11.68	10.22	11.73
	OmniQuant	10.96	11.81	10.21	11.27	9.62	10.76
	I-LLM	10.94	11.82	10.17	11.90	9.72	10.83
W4A4	SmoothQuant	1.8e4	1.5e4	7.4e3	5.6e3	1.2e4	8.3e3
	RPTQ	12.00	12.85	12.74	14.71	11.15	13.48
	OmniQuant	12.24	13.56	11.65	13.46	10.60	11.90
	I-LLM	12.20	12.21	11.45	13.41	10.53	11.66

Table 2: Quantitative weight-activation quantization PPL($\downarrow$) results of I-LLM. We report WikiText2 and C4 perplexity of LLaMA Family in this table.

#Bits	Method	LLaMA-7B		LLaMA-13B		LLaMA-30B		LLaMA2-7B		LLaMA2-13B		LLaMA3-8b	
		WikiText2	C4	WikiText2	C4	WikiText2	C4	WikiText2	C4	WikiText2	C4	WikiText2	C4
FP16	-	5.68	7.08	5.09	6.61	4.10	5.98	5.47	6.97	4.88	6.46	6.14	8.88
W6A6	SmoothQuant	6.03	7.47	5.42	6.97	4.55	6.34	6.2	7.76	5.18	6.76	7.08	10.16
	OmniQuant	5.96	7.43	5.28	6.84	4.38	6.22	5.87	7.48	5.14	6.74	6.97	10.08
	I-LLM	5.84	7.32	5.23	6.79	4.32	6.25	5.68	7.27	5.10	6.74	6.61	9.77
W4A4	SmoothQuant	22.25	32.32	40.05	47.18	192.40	122.38	83.12	77.27	35.88	43.19	418.88	312.86
	OmniQuant	11.26	14.51	10.87	13.78	10.33	12.49	14.26	18.02	12.30	14.55	437.88	315.69
	AffineQuant	10.28	13.64	10.32	13.44	9.35	11.58	12.69	15.76	11.45	13.97	-	-
	I-LLM	9.10	12.33	7.99	10.96	7.24	9.85	10.44	12.92	9.76	12.57	21.19	30.9

Table 3: The performance of various methods for 4-bit and 6-bit quantization on the LLaMA family models across six zero-shot datasets.

LLaMA / Acc($\uparrow$)	#Bits	Method	PIQA($\uparrow$)	ARC-e($\uparrow$)	ARC-c($\uparrow$)	BoolQ($\uparrow$)	HellaSwag($\uparrow$)	Winogrande($\uparrow$)	Avg.($\uparrow$)
LLaMA-7B	FP16	-	77.47	52.48	41.46	73.08	73.00	67.07	64.09
	W6A6	SmoothQuant	76.75	51.64	39.88	71.75	71.67	65.03	62.81
	W6A6	OmniQuant	77.09	51.89	40.87	72.53	71.61	65.03	63.17
	W6A6	I-LLM	76.99	52.66	40.78	72.94	71.31	65.67	**63.39**
	W4A4	SmoothQuant	49.80	30.40	25.80	49.10	27.40	48.00	38.41
	W4A4	LLM-QAT	51.50	27.90	23.90	61.30	31.10	51.90	41.27
	W4A4	LLM-QAT+SQ	55.90	35.50	26.40	62.40	47.80	50.60	46.43
	W4A4	OS+	62.73	39.98	30.29	60.21	44.39	52.96	48.43
	W4A4	OmniQuant	66.15	45.20	31.14	63.51	56.44	53.43	52.65
	W4A4	AffineQuant	69.37	42.55	31.91	63.73	57.65	55.33	53.42
	W4A4	I-LLM	67.25	45.58	32.59	63.88	58.89	57.06	**54.21**
LLaMA-13B	FP16	-	79.10	59.89	44.45	68.01	76.21	70.31	66.33
	W6A6	SmoothQuant	77.91	56.60	42.40	64.95	75.36	69.36	64.43
	W6A6	OmniQuant	78.40	57.28	42.91	67.00	75.82	68.27	64.95
	W6A6	I-LLM	77.48	56.94	44.03	64.92	75.24	69.14	**64.63**
	W4A4	SmoothQuant	61.04	39.18	30.80	61.80	52.29	51.06	49.36
	W4A4	OS+	63.00	40.32	30.38	60.34	53.61	51.54	49.86
	W4A4	OmniQuant	69.69	47.39	33.10	62.84	58.96	55.80	54.37
	W4A4	AffineQuant	66.32	43.90	29.61	64.10	56.88	54.70	52.58
	W4A4	I-LLM	67.95	48.15	34.47	62.29	63.13	59.98	**56.00**
LLaMA-30B	FP16	-	80.08	58.92	45.47	68.44	79.21	72.53	67.44
	W6A6	SmoothQuant	77.14	57.61	42.91	65.56	78.07	69.92	65.20
	W6A6	OmniQuant	78.40	57.28	42.91	67.00	75.82	68.27	64.95
	W6A6	I-LLM	79.43	58.88	45.14	73.36	78.51	72.61	**67.99**
	W4A4	SmoothQuant	58.65	35.53	27.73	60.42	35.56	48.06	44.83
	W4A4	OS+	67.63	46.17	34.40	60.70	54.32	52.64	52.62
	W4A4	OmniQuant	71.21	49.45	34.47	65.33	64.65	59.19	56.63
	W4A4	AffineQuant	66.32	43.90	29.61	64.10	56.88	54.70	52.58
	W4A4	I-LLM	71.38	51.81	37.12	65.69	67.79	61.40	**59.20**

Zero-shot results on LLaMA. Table 3 presents our performance on six zero-shot tasks, employing both W4A4 and W6A6 settings. Particularly striking is the performance of the LLaMA-30b model, configured with full quantization at W6A6 precision, which achieves an average accuracy on these tasks surpassing even that of the floating-point model. This achievement underscores the potential of fully quantized integer-only methods in maintaining the generalization capabilities of LLMs to a considerable degree.

Table 4: Performance comparison of LLaMA models using I-LLM and traditional methods. The table presents the comparison between the full-precision (Fp16) and quantized (W4A4) methods, including the proposed I-LLM W4A4 approach. I-LLM W4A4 achieves up to a **2.63x** speedup and a **3.08x** memory saving across different LLaMA model sizes (7B, 13B, 8B). All experiments used a token length of 2048.

Model	Method	Weight Memory	Running Memory	Latency(ms) $\downarrow$	SpeedUp	Memory Saving
LlaMA2-7b	Fp16	12.61G	14.40G	649	-	-
	Traditional W4A4	3.57G	5.36G	314	2.06x	2.69x
	I-LLM W4A4	3.15G	4.73G	260	2.49x	3.04x
LlaMA2-13b	Fp16	24.24G	27.03G	1240	-	-
	W4A4	6.52G	9.31G	592	2.09x	2.90x
	I-LLM W4A4	6.06G	8.76G	493	2.52x	3.08x
LlaMA3-8b	Fp16	14.95G	16.22G	702	-	-
	W4A4	5.21G	7.43G	316	2.22x	2.18
	I-LLM W4A4	3.74G	5.34G	267	2.63x	3.03x

Latency and memory saving on LLaMA. To validate the versatility of I-LLM, we have executed a series of tests to assess its performance enhancement on Nvidia A6000 GPU. In Table 4, we analyze the latency and memory saving of I-LLM across various models. Under W4A4 settings, I-LLM achieves a substantial 2.6x speed boost and a 3x memory saving compared to the fp16 model, surpassesing other W4A4 methods in both speed and memory saving. Specifically, as shown in Table 7, DI-MatMul outperforms conventional quantized GEMM in both weight-activation (1.2x speedup) and activation-activation (2.1x speedup) scenarios, attributed to DI-MatMul's efficient integer arithmetic and its requant-only feature. Additionally, Table 8 shows that DI-ClippedSoftmax is over 5x faster than the fp16 implementation across different input sizes, while DI-Norm also exhibits lower latency. Overall, I-LLM significantly improves both speed and memory saving, outperforming competing methods and demonstrating its superior performance.

4.2 Ablation Study

Contribution of Fully-Smooth Block Reconstruction In Table 5, we meticulously assess the impact of various PTQ methods on model accuracy. To maintain impartiality, this experiment abstains from utilizing integer-only operators; instead, all quantization procedures are substituted with pseudo-quantization. The nodes necessitating quantization align with those delineated in Fig 1. Notably, conventional non-integer-only methodologies often overlook the influence of activation in non-linear layers, leading to compromised model accuracy during integer inference. However, with the integration of FSBR, these activations are thoughtfully considered during PTQ, effectively reinstating the model's accuracy under full quantization.

Table 5: Impact of different PTQ methods and integer-only operators on LLaMA-7B PPL(↓) across WikiText2 and C4 datasets.

LLaMA-7B	W4A4		W6A6	
Method	WikiText2	C4	WikiText2	C4
SmoothQuant	256.58	218.47	6.09	7.6
OmniquantQuant	122.18	183.2	5.99	7.57
FSBR	**9.44**	**12.72**	**5.83**	**7.02**
+DI-CLippedSoftamx	9.44	12.72	5.83	7.02
+DI-Swiglu	9.12	12.38	5.83	7.04
+DI-Norm	9.52	12.63	5.85	7.35

Table 6: Effect of clipped value in DI-ClippedSoftamx.

LLaMA-7B	W4A4		W6A6	
Clipped Value c	WikiText2	C4	WikiText2	C4
–	7360945.00	1998371.38	60335.22	47103.44
20	9.15	12.39	5.86	7.36
17	9.19	12.38	5.86	7.37
15	**9.16**	**12.36**	**5.85**	**7.36**
12	9.19	12.35	5.86	7.36
10	9.23	12.45	5.89	7.42

Impact of Integer-Only Operators. As shown in Table 5, we intricately outline the precise impact of each integer-only operator on the holistic accuracy of the model. Additionally, we ablate the influence of the clipping coefficient c in Eq 11 within DI-ClippedSoftmax on model accuracy, as depicted in Table 6. Notably, owing to residual connections, the quantization of DI-Norm engenders a discernible decrement in performance, a phenomenon meticulously anticipated in our comprehensive analysis. In Table 5, we elaborate on the influence of each integer-only operator on the overall model accuracy. Specifically, Table 6 illustrates the impact of the clipping coefficient c in the Eq 11 from DI-ClippedSoftmax on model accuracy. It is worth noting that the quantization of DI-Norm leads to a performance decline, primarily due to outliers in the residual connections.

5 Conclusion

In this paper, we present I-LLM, a fully-quantized integer-only PTQ framework for LLMs. We address the challenge of fluctuating activations in both linear and non-linear operations by proposing Fully-Smooth Block-Reconstruction (FSBR) to harmonize inter-channel variations and Dynamic Integer-only MatMul (DI-MatMul) to handle inter-token variations. Additionally, we design DI-ClippedSoftmax, DI-Exp, and DI-Norm as lightweight integer-only operators to replace computationally intensive floating-point operations. Experiments demonstrate that I-LLM outperforms simulated quantization methods and achieves comparable accuracy to the floating-point baseline. Notably, I-LLM operates effectively in a low-bit quantization setting with minimal accuracy loss, thereby bridging the gap between low-precision integer-only quantization and full-precision LLMs. Moreover, experiments demonstrate that I-LLM not only outperforms simulated quantization methods but also achieves comparable accuracy to the floating-point baseline. In practical scenarios, I-LLM benefits from the performance gains of low-precision computation, while its consistent operation at low bit-width significantly reduces memory utilization. Consequently, this work not only accelerates LLM inference on server-side deployments but also paves the way for efficient LLM deployment on edge devices without floating-point capabilities.

REFERENCES

Yonatan Bisk, Rowan Zellers, Jianfeng Gao, Yejin Choi, et al. Piqa: Reasoning about physical commonsense in natural language. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pp. 7432–7439, 2020.

Michael Boratko, Harshit Padigela, Divyendra Mikkilineni, Pritish Yuvraj, Rajarshi Das, Andrew McCallum, Maria Chang, Achille Fokoue-Nkoutche, Pavan Kapanipathi, Nicholas Mattei, et al. A systematic classification of knowledge, reasoning, and context within the arc dataset. *arXiv preprint arXiv:1806.00358*, 2018.

Jerry Chee, Yaohui Cai, Volodymyr Kuleshov, and Christopher De Sa. Quip: 2-bit quantization of large language models with guarantees. *arXiv preprint arXiv:2307.13304*, 2023.

Christopher Clark, Kenton Lee, Ming-Wei Chang, Tom Kwiatkowski, Michael Collins, and Kristina Toutanova. Boolq: Exploring the surprising difficulty of natural yes/no questions. *arXiv preprint arXiv:1905.10044*, 2019.

Tim Dettmers, Ruslan Svirschevski, Vage Egiazarian, Denis Kuznedelev, Elias Frantar, Saleh Ashkboos, Alexander Borzunov, Torsten Hoefler, and Dan Alistarh. Spqr: A sparse-quantized representation for near-lossless llm weight compression. *arXiv preprint arXiv:2306.03078*, 2023.

Tim Dettmers, Artidoro Pagnoni, Ari Holtzman, and Luke Zettlemoyer. Qlora: Efficient finetuning of quantized llms. *Advances in Neural Information Processing Systems*, 2024.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

Eric Flamand, Davide Rossi, Francesco Conti, Igor Loi, Antonio Pullini, Florent Rotenberg, and Luca Benini. Gap-8: A risc-v soc for ai at the edge of the iot. In *2018 IEEE 29th International Conference on Application-specific Systems, Architectures and Processors (ASAP)*, pp. 1–4. IEEE, 2018.

Elias Frantar, Saleh Ashkboos, Torsten Hoefler, and Dan Alistarh. Gptq: Accurate post-training quantization for generative pre-trained transformers. *arXiv preprint arXiv:2210.17323*, 2022.

Google. Edge tpu, 2024. URL https://cloud.google.com/edge-tpu.

Benoit Jacob, Skirmantas Kligys, Bo Chen, Menglong Zhu, Matthew Tang, Andrew Howard, Hartwig Adam, and Dmitry Kalenichenko. Quantization and training of neural networks for efficient integer-arithmetic-only inference. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2704–2713, 2018.

Sehoon Kim, Amir Gholami, Zhewei Yao, Michael W Mahoney, and Kurt Keutzer. I-bert: Integer-only bert quantization. In *International conference on machine learning*, pp. 5506–5518. PMLR, 2021.

Sehoon Kim, Coleman Hooper, Amir Gholami, Zhen Dong, Xiuyu Li, Sheng Shen, Michael W Mahoney, and Kurt Keutzer. Squeezellm: Dense-and-sparse quantization. *arXiv preprint arXiv:2306.07629*, 2023.

Changhun Lee, Jungyu Jin, Taesu Kim, Hyungjun Kim, and Eunhyeok Park. Owq: Lessons learned from activation outliers for weight quantization in large language models. *arXiv preprint arXiv:2306.02272*, 2023.

Liang Li, Qingyuan Li, Bo Zhang, and Xiangxiang Chu. Norm tweaking: High-performance low-bit quantization of large language models. *Association for the Advancement of Artificial Intelligence*, 2023a.

Yixiao Li, Yifan Yu, Chen Liang, Pengcheng He, Nikos Karampatziakis, Weizhu Chen, and Tuo Zhao. Loftq: Lora-fine-tuning-aware quantization for large language models. *arXiv preprint arXiv:2310.08659*, 2023b.

Yuhang Li, Ruihao Gong, Xu Tan, Yang Yang, Peng Hu, Qi Zhang, Fengwei Yu, Wei Wang, and Shi Gu. Brecq: Pushing the limit of post-training quantization by block reconstruction. In *International Conference on Learning Representations (ICLR)*, 2021.

Zhikai Li and Qingyi Gu. I-vit: integer-only quantization for efficient vision transformer inference. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 17065–17075, 2023.

Ji Lin, Jiaming Tang, Haotian Tang, Shang Yang, Xingyu Dang, and Song Han. Awq: Activation-aware weight quantization for llm compression and acceleration. *arXiv preprint arXiv:2306.00978*, 2023.

Yang Lin, Tianyu Zhang, Peiqin Sun, Zheng Li, and Shuchang Zhou. Fq-vit: Post-training quantization for fully quantized vision transformer. In *Proceedings of the Thirty-First International Joint Conference on Artificial Intelligence, IJCAI-22*, pp. 1173–1179, 2022.

Ye Lin, Yanyang Li, Tengbo Liu, Tong Xiao, Tongran Liu, and Jingbo Zhu. Towards fully 8-bit integer inference for the transformer model. In *Proceedings of the Twenty-Ninth International Conference on International Joint Conferences on Artificial Intelligence*, pp. 3759–3765, 2021.

Jiawei Liu, Lin Niu, Zhihang Yuan, Dawei Yang, Xinggang Wang, and Wenyu Liu. Pd-quant: Post-training quantization based on prediction difference metric. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 24427–24437, 2023a.

Zechun Liu, Barlas Oguz, Changsheng Zhao, Ernie Chang, Pierre Stock, Yashar Mehdad, Yangyang Shi, Raghuraman Krishnamoorthi, and Vikas Chandra. Llm-qat: Data-free quantization aware training for large language models. *arXiv preprint arXiv:2305.17888*, 2023b.

Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. Pointer sentinel mixture models. *arXiv preprint arXiv:1609.07843*, 2016.

Haotong Qin, Yifu Ding, Mingyuan Zhang, Qinghua Yan, Aishan Liu, Qingqing Dang, Ziwei Liu, and Xianglong Liu. Bibert: Accurate fully binarized bert. *arXiv preprint arXiv:2203.06390*, 2022.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of Machine Learning Research*, 2020.

Keisuke Sakaguchi, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. Winogrande: An adversarial winograd schema challenge at scale. *Communications of the ACM*, 2021.

Yuzhang Shang, Zhihang Yuan, Qiang Wu, and Zhen Dong. Pb-llm: Partially binarized large language models. *International Conference on Learning Representations*, 2023.

Wenqi Shao, Mengzhao Chen, Zhaoyang Zhang, Peng Xu, Lirui Zhao, Zhiqian Li, Kaipeng Zhang, Peng Gao, Yu Qiao, and Ping Luo. Omniquant: Omnidirectionally calibrated quantization for large language models. *CoRR*, abs/2308.13137, 2023.

Jacob R Stevens, Rangharajan Venkatesan, Steve Dai, Brucek Khailany, and Anand Raghunathan. Softermax: Hardware/software co-design of an efficient softmax for transformers. In *2021 58th ACM/IEEE Design Automation Conference (DAC)*, pp. 469–474, 2021.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023a.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023b.

Xiuying Wei, Ruihao Gong, Yuhang Li, Xianglong Liu, and Fengwei Yu. Qdrop: Randomly dropping quantization for extremely low-bit post-training quantization. In *International Conference on Learning Representations (ICLR)*, 2022a.

Xiuying Wei, Yunchen Zhang, Xiangguo Zhang, Ruihao Gong, Shanghang Zhang, Qi Zhang, Fengwei Yu, and Xianglong Liu. Outlier suppression: Pushing the limit of low-bit transformer language models. *Advances in Neural Information Processing Systems*, 2022b.

Xiuying Wei, Yunchen Zhang, Yuhang Li, Xiangguo Zhang, Ruihao Gong, Jinyang Guo, and Xianglong Liu. Outlier suppression+: Accurate quantization of large language models by equivalent and optimal shifting and scaling. *arXiv preprint arXiv:2304.09145*, 2023.

WIKIPEDIA. Arm cortex-m, 2024. URL `https://en.wikipedia.org/wiki/ARM_Cortex-M`.

Hao Wu, Patrick Judd, Xiaojie Zhang, Mikhail Isaev, and Paulius Micikevicius. Integer quantization for deep learning inference: Principles and empirical evaluation. *arXiv preprint arXiv:2004.09602*, 2020.

Guangxuan Xiao, Ji Lin, Mickael Seznec, Julien Demouth, and Song Han. Smoothquant: Accurate and efficient post-training quantization for large language models. *arXiv preprint arXiv:2211.10438*, 2022.

Yuhui Xu, Lingxi Xie, Xiaotao Gu, Xin Chen, Heng Chang, Hengheng Zhang, Zhensu Chen, Xiaopeng Zhang, and Qi Tian. Qa-lora: Quantization-aware low-rank adaptation of large language models. *arXiv preprint arXiv:2309.14717*, 2023.

Zhewei Yao, Zhen Dong, Zhangcheng Zheng, Amir Gholami, Jiali Yu, Eric Tan, Leyuan Wang, Qijing Huang, Yida Wang, Michael Mahoney, et al. Hawq-v3: Dyadic neural network quantization. In *International Conference on Machine Learning*, pp. 11875–11886. PMLR, 2021.

Zhewei Yao, Reza Yazdani Aminabadi, Minjia Zhang, Xiaoxia Wu, Conglong Li, and Yuxiong He. Zeroquant: Efficient and affordable post-training quantization for large-scale transformers. *arXiv preprint arXiv:2206.01861*, 2022.

Zhihang Yuan, Lin Niu, Jiawei Liu, Wenyu Liu, Xinggang Wang, Yuzhang Shang, Guangyu Sun, Qiang Wu, Jiaxiang Wu, and Bingzhe Wu. Rptq: Reorder-based post-training quantization for large language models. *arXiv preprint arXiv:2304.01089*, 2023a.

Zhihang Yuan, Yuzhang Shang, Yue Song, Qiang Wu, Yan Yan, and Guangyu Sun. Asvd: Activation-aware singular value decomposition for compressing large language models. *arXiv preprint arXiv:2312.05821*, 2023b.

Yuxuan Yue, Zhihang Yuan, Haojie Duanmu, Sifan Zhou, Jianlong Wu, and Liqiang Nie. Wkvquant: Quantizing weight and key/value cache for large language models gains more. *arXiv preprint arXiv:2402.12065*, 2024.

Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. Hellaswag: Can a machine really finish your sentence? *arXiv preprint arXiv:1905.07830*, 2019.

Susan Zhang, Stephen Roller, Naman Goyal, Mikel Artetxe, Moya Chen, Shuohui Chen, Christopher Dewan, Mona Diab, Xian Li, Xi Victoria Lin, et al. Opt: Open pre-trained transformer language models. *arXiv preprint arXiv:2205.01068*, 2022.

Sifan Zhou, Liang Li, Xinyu Zhang, Bo Zhang, Shipeng Bai, Miao Sun, Ziyu Zhao, Xiaobo Lu, and Xiangxiang Chu. Lidar-ptq: Post-training quantization for point cloud 3d object detection. *International Conference on Learning Representations*, 2024.

Danyang Zhu, Siyuan Lu, Meiqi Wang, Jun Lin, and Zhongfeng Wang. Efficient precision-adjustable architecture for softmax function in deep learning. *IEEE Transactions on Circuits and Systems II: Express Briefs*, 67(12):3382–3386, 2020.

A APPENDIX

A.1 QUANTIZATION PRELIMINARIES

Quantization & Dequantization. Quantization typically refers to mapping a floating-point number to a discrete interval with integer number. Here, we only consider uniform quantization. The quantization process can be expressed as follows:

$$\boldsymbol{X}^I = \text{clamp}\left(\left\lfloor \frac{\boldsymbol{X}}{s} \right\rceil + zp^I, 0, 2^{n^I} - 1\right) \tag{14}$$

$$s = \frac{x_{\max} - x_{\min}}{2^{n^I} - 1} \tag{15}$$

$$zp^I = \left\lfloor \frac{-x_{\min}}{s} \right\rceil \tag{16}$$

$$\boldsymbol{X}' = (\boldsymbol{X}^I - zp^I) \cdot s \tag{17}$$

where $\boldsymbol{X}$ is the floating-point tensor, $\boldsymbol{X}^I$ is its quantized counterpart and $\boldsymbol{X}'$ is the dequantized resuls of $\boldsymbol{X}^I$. Here, n^I represents the number of bits (e.g., 8). s is the quantization step size, determined by $x_{\min}, x_{\max}$, and n^I. clamp represents truncation function. The choice of s greatly affects the accuracy of the quantized model. We can obtain s from the activations of some samples, which is called static quantization. Alternatively, we can derive it from runtime statistics, known as dynamic quantization. Quantization can also be distinguished by its granularity into per-channel quantization and per-token quantization (Yao et al., 2022).

A.2 DYNAMIC INTERGER-ONLY ALGORITHMS

Algorithm 1 Dynamic Integer-only Exp: DI-Exp

Input: Integer input $\mathbf{x}_{in}^I$, Integer input scale factor m^I and Integer shift factor k^I.
Output: result of I-Exp.
  1: $m_f^I = m^I + (m^I \gg 1) - (m^I \gg 4)$
  2: $s_f = m_f \gg k$
  3: $t = round(-1/(s_f))$
  4: $\mathbf{q}^I = floor(\mathbf{x}_{in}^I/t)$
  5: $\mathbf{r}^I = \mathbf{x}_{in}^I - \mathbf{q}^I \cdot t$
  6: $unshifted\_exp = (\mathbf{r}^I \gg 1) - t$
  7: $result = unshifted\_exp \gg \mathbf{q}^I$
  8: **return** result

Algorithm 2 Dynamic Integer-only Softmax : DI-Softmax

Input: Integer input $\mathbf{x}_{in}^I$, Integer input scale factor m_{in}^I, Integer shift factor k_{in}^I and output bit-precision p_{out}^I.
Output: Integer output $\mathbf{y}_{out}^I$, Integer output scale factor m_{out}^I and Integer shift factor k_{out}^I.
  1: $\mathbf{x}_\Delta^I = \mathbf{x}_{in}^I - max(\mathbf{x}_{in}^I)$
  2: $\mathbf{Exp}_\Delta^I = \text{DI-Exp}(\mathbf{x}_\Delta^I, m_{in}^I, k_{in}^I)$
  3: $\mathbf{y}_{out}^I = IntDiv(\mathbf{Exp}_\Delta^I, \sum \mathbf{Exp}_\Delta^I, p_{out}^I)$
  4: $m_{out}^I = 1$
  5: $k_{out}^I = p_{out}^I - 1$
  6: **return** $\mathbf{y}_{out}^I, m_{out}^I, k_{out}^I$

Algorithm 3 Dynamic Integer-only SwiGLU : DI-SwiGLU

Input: Integer input $\mathbf{x}_{gate}^I, \mathbf{x}_{up}^I$, Integer input scale factor m_{gate}^I, m_{up}^I, Integer shift factor k_{gate}^I, k_{out}^I, smooth factor α_{smooth} and output bit-precision p_{out}^I.
Output: Integer output $\mathbf{y}_{out}^I$, Integer output scale factor m_{out}^I and Integer shift factor k_{out}^I.

1: $\mathbf{x}_{smoothed\_gate}^I = \mathbf{x}_{gate}^I / \alpha_{smooth}$
2: $\mathbf{x}_\Delta^I = \mathbf{x}_{smooth\_gate}^I - max(\mathbf{x}_{smoothed\_gate}^I)$
3: $\mathbf{Exp}_\Delta^I = \text{DI-Exp}(\mathbf{x}_\Delta^I, m_{gate}^I, k_{gate}^I)$
4: $\mathbf{Exp}_{-max}^I = \text{DI-Exp}(-max(\mathbf{x}_{smoothed\_gate}^I), m_{gate}^I, k_{gate}^I)$
5: $\mathbf{y}_{out}^I = \mathbf{x}_{gate}^I \cdot IntDiv(\mathbf{Exp}_\Delta^I, \mathbf{Exp}_\Delta^I + \mathbf{Exp}_{-max}^I, p_{out}^I) \cdot \mathbf{x}_{up}^I$
6: $m_{out}^I = m_{gate}^I \cdot m_{up}^I$
7: $k_{out}^I = k_{gate}^I + k_{up}^I + p_{out}^I - 1$
8: **return** $\mathbf{y}_{out}^I, m_{out}^I, k_{out}^I$

Algorithm 4 Dynamic Integer-only RMSnorm : DI-RMSnorm

Input: Integer input $\mathbf{x}_{in}^I$, input per-channel Integer scale factor $\mathbf{m}_{in}^I$, input per-channel Integer shift factor $\mathbf{k}_{in}$, weights of RMSnorm $\boldsymbol{\gamma}$ and output bit-precision p_{out}^I.
Output: Integer output $\mathbf{y}_{out}^I$, and Output scale factor $\mathbf{S}_{out}$.

1: **function** I-SQRT(I_{in})
2:      $v = 15$
3:      $n = 1$
4:      $b = 0\ x\ 8000$
5:      **while** b **do**
6:          $temp = ((n << 1) + b) << v --$
7:          **if** $I_{in} \geq temp$ **then**
8:              $n+ = b$
9:              $I_{in}- = temp$
10:         **end if**
11:         $b >>= 1$
12:      **end while**
13:      $I_{out} = n$
14:      **return** I_{out}
15: **end function**
16:
17: **function** DI-RMSNORM($\mathbf{x}_{in}^I, \mathbf{m}_{in}^I, \mathbf{k}_{in}^I, \boldsymbol{\gamma}, p_{out}^I$)
18:      $\mathbf{shift}^I = \mathbf{k}_{in}^I - min(\mathbf{k}_{in}^I)$
19:      $\mathbf{m}^I = \mathbf{m}_{in}^I \ll \mathbf{shift}^I$
20:      $m_{min} = min(m)$
21:      $s, n = shape(\mathbf{x}_{in}^I)$
22:      $\boldsymbol{\alpha}^I = round(\mathbf{m}^I \cdot M / m_{min})$
23:      $var^I = (sum(\mathbf{x}_{in}^I * \mathbf{m}^I))^2$
24:      $std^I = \text{I-SQRT}(var^I)$
25:      $dim\_sqrt^I = \text{I-SQRT}(n)$
26:      $\mathbf{y}_{out}^I = IntDiv(\mathbf{x}_{in}^I \cdot N \cdot dim\_sqrt^I, std^I, p_{out}^I)$
27:      $\mathbf{S}_{out} = \mathbf{m}^I \cdot \boldsymbol{\alpha}^I \cdot \boldsymbol{\gamma} / (m_{min} \cdot N)$
28:      **return** $\mathbf{y}_{out}^I, \mathbf{S}_{out}$
29: **end function**

A.3 THE OVERHEAD AND EFFICIENCY OF DI-MATMUL

The DI-MatMul has lower overhead and higher execution efficiency compared to conventional GEMM quantization. As detailed in Section 3.3 of paper, we utilize two 8-bit scalars, m^I and k^I to represent the quantization scale for a batch of activations. This approach incurs no additional storage overhead compared to the previous method using FP16 to store the quantization scale. After obtaining the intermediate results from integer-only matrix operations, I-LLM only requires a small amount of scalar integer operations and one vector-scalar multiplication, as specified in Formulas 6, 7, and 8. The output of DI-Matmul is composed of a low-bit-width integer matrix and three INT8 scalars.

It should be noted that conventional quantization methods still require a large number of floating-point computations during inference. In contrast, all computations in DI-MatMul are integer-based, effectively leveraging efficient integer arithmetic units. To be more specific:

- Weight-only quantization demands an online dequantization step for the quantized weights, involving floating-point multiplication as a precursor to the subsequent floating-point General Matrix Multiply (GEMM) operations.

- The joint quantization of weights and activations often incurs the necessity for online quantization and dequantization procedures specifically for the activations. More importantly, the output of traditional quantization methods is typically rendered in floating-point format (e.g., FP16), while the output of DI-MatMul is in a low-bit-width integer format. This paradigm not only conserves considerable memory and bandwidth but also reduces latency. For instance, compared to FP16 format, employing 4-bit quantization for feature-map and KV-cache results in a substantial reduction of memory and bandwidth usage by 75

- As shown in Table 7, DI-MatMul outperforms conventional quantized GEMM in both weight-activation (1.2x speedup) and activation-activation (2.1x speedup) scenarios, attributed to DI-MatMul's efficient integer arithmetic and its requant-only feature.

Table 7: The latency comparison of Quantized-Gemm(QGemm) and DI-MatMul in both weight-activation and activation-activation scenarios. Both QGemm and DI-MatMul are implemented based on NVIDIA Cutlass.

	Input Size	QGemm(4bit)	DI-MatMul(4bit)	Speedup
	1 x 4096	1.14ms	0.45ms	2.53x
	2048 x 4096	1.71ms	0.69ms	2.48x
Act-Act	1 x 8192	3.73ms	1.54ms	2.42x
	4096 x 8192	5.92ms	2.79ms	2.12x
	8192 x 8192	8.21ms	3.83ms	2.14x
	1 x 8192	0.29ms	0.21ms	1.38x
Act-Weight	4096 x 8192	2.08ms	1.75ms	1.18x
	8192 x 8192	3.91ms	3.07ms	1.27x

A.4 FULL RESULTS

A.4.1 I-LLM IN DIFFERENT QUANTIZATION CONFIGURATIONS

I-LLM is a framework designed for fully integer quantization of large language models. However, FSBR demonstrates significant performance improvements across various quantization configurations. In Table 9, we present the results for different settings, including W4A16 and W4A8. The experimental results clearly demonstrate the effectiveness of FSBR in restoring the quantization accuracy of the model.

A.4.2 MORE COMPARISONS WITH OTHER METHODS

It is important to note that conventional quantization methods (Xiao et al., 2022; Shao et al., 2023),still rely on a significant amount of floating-point computations during inference. Furthermore, while

Table 8: Latency comparison of different Softmax or Norm implementation methods. FP16 represents the native implementation in Torch. I-LLM achieves a twofold speedup for Softmax and accelerates Norm, benefiting from efficient integer computation and reduced memory transfer overhead.

	Input Size	FP Latency	I-LLM Latency	SpeedUp
Softmax	1 x 4096	1.89ms	0.28ms	6.75x
	2048 x 4096	1.91ms	0.33ms	5.79x
	4096 x 4096	1.99ms	0.41ms	4.85x
	131072 x 4096	10.75ms	5.90ms	1.82x
RMSNorm	1 x 4096	0.35ms	0.35ms	1.01x
	2048 x 4096	0.23ms	0.19ms	1.21x
	4096 x 4096	0.36ms	0.23ms	1.54x
	1 x 8192	0.08ms	0.07ms	1.08x
	4096 x 8192	0.67ms	0.40ms	1.68x
	8192 x 8192	3.18ms	2.97ms	1.07x

Table 9: Accuracy performance of the Llama2 model under different quantization configurations using the I-LLM method.

Quantization Setting	Wikitext2 PPL	C4 PPL
W16A16	5.47	6.97
W4A16	5.66	7.24
W6A6	5.68	7.27
W4A8	5.69	7.28
W4A4	9.60	12.71
W3A8	11.29	18.02
W2A8	25.33	35.07

some existing methods have achieved INT4 precision with minimal accuracy loss, such as AWQ (Lin et al., 2023), these approaches primarily focus on weight-only quantization. A crucial distinction is that in weight-only quantization methods, both the input and output activations are typically represented in floating-point format (e.g., FP16). In contrast, I-LLM applies low-bit quantization to the inputs and outputs of all operators throughout the entire dataflow, including GEMM (e.g., FC, Matmul), Norm, Softmax, SiLU, and Add. Therefore, direct comparisons between I-LLM and weight-only quantization methods are not entirely fair, as I-LLM faces significantly greater challenges in the quantization process. Despite this, I-LLM has achieved notable, and in some cases, even superior results compared to these methods, as demonstrated in Tab32 10. In addition to traditional quantization, we also report comparative results with the low-bit floating-point method, LLM-FP4 (Liu et al., 2023b), as shown in Table 11.

Table 10: Comparison of perplexity between I-LLM and AWQ (Lin et al., 2023) methods on WikiText2. Note that AWQ is a weight-only quantizationmethod that only quantizes the weights of linear layers, while I-LLM considers quantization of all weights and activations in the network.

QuantSetting	Method	LLAMA3 8B	LLAMA2 7B	LLAMA2 13B
-	FP16	6.14	5.47	4.95
W4 only	AWQ	7.04	6.02	5.06
W6 only	AWQ	6.21	5.49	4.89
W6A6	AWQ	6.90	5.98	5.19
	I-LLM	6.61	5.68	5.10
W4A4	AWQ	125.74	8248	133.62
	I-LLM	21.19	10.44	9.76

Table 11: Comparison of I-LLM with current state-of-the-art low-bit floating-point quantization methods on six zero-shot tasks.Note that LLM-FP4 only quantizes the weights and activations of linear layer.

		Quant Setting	PIQA	ARC-e	Arc-c	BoolQ	HellaSwag	Winogrande	Avg
llama-7b	FP16	-	77.47	52.48	41.46	73.08	73.00	67.07	64.10
	LLM-FP4	W4A4	71.40	63.80	31.50	62.10	45.70	62.60	56.00
	I-LLM	W4A4	67.00	47.35	32.94	63.88	58.49	58.80	54.74
llama-13b	FP16	-	79.10	59.89	44.45	68.01	76.21	70.31	66.33
	LLM-FP4	W4A4	72.20	69.10	37.30	69.30	50.70	64.10	60.60
	I-LLM	W4A4	67.95	48.15	34.47	62.29	63.13	59.98	56.00

A.5 LIMITATION AND DISCUSSION

We have shown evidence that our I-LLM can replicate float-point performance with an integer-only module with 8-bit or lower bits. A limitation is that we only focused on natural language models, however, it would be interesting to explore how I-LLM performs in computer vision tasks. We leave this for future work.

A.6 VISIBLE RESULTS

Figure 6: The activation distribution of FFN and Attention of LLMs before and after the FSBR.