Alleviating Adversarial Attacks on Variational Autoencoders with MCMC

Abstract

Variational autoencoders (VAEs) are latent variable models that can generate complex objects and provide meaningful latent representations. Moreover, they could be further used in downstream tasks such as classification. As previous work has shown, one can easily fool VAEs to produce unexpected latent representations and reconstructions for a visually slightly modified input. Here, we examine several objective functions for adversarial attacks construction proposed previously and present a solution to alleviate the effect of these attacks. Our method utilizes the Markov Chain Monte Carlo (MCMC) technique in the inference step that we motivate with a theoretical analysis. Thus, we do not incorporate any extra costs during training and the performance on non-attacked inputs is not decreased. We validate our approach on a variety of datasets (MNIST, Fashion MNIST, Color MNIST, CelebA) and VAE configurations (β-VAE, NVAE, β-TCVAE), and show that our approach consistently improves the model robustness to adversarial attacks.

1   Introduction

Variational Autoencoders (VAEs) [22, 27] are deep generative models used in various domains. Recently, it was shown that Variational Autoencoders with a hierarchical structure [26], coupled with skip-connections [25, 28], can generate high-quality images [12, 30]. An interesting trait of VAEs is that they allow learning meaningful latent space induced by the encoder. These latent representations are commonly used in downstream tasks [5, 19]. These motivates us to explore the *robustness* of the resulting latent representations to understand the capabilities and potential vulnerabilities of VAEs better. *Adversarial attacks* constitute one way to assess the robustness of a deep neural network. Robustness to the attacks is a crucial property for VAEs, especially in such applications as anomaly detection [1, 25] or data compression [3, 17].

The main questions on adversarial attacks for VAEs are mainly focused on how they could be formulated and alleviated. In [15] it is proposed to minimize the KL-divergence between an adversarial input and a target input to learn an adversarial attack for the vanilla VAE. Further, in [23] it is shown that a similar strategy can be used to attack hierarchical VAEs. To counteract the adversarial attacks, the authors of [32] suggest using a modified VAE objective, namely, β-TCVAE, that increases VAE robustness, especially when coupled with the hierarchical structure. It was shown in [8] that β-VAEs tend to be more robust to adversarial attacks in terms of the r-metric proposed therein. The authors of [4] presented that the adversarial robustness can be achieved by constraining the Lipschitz constant of the encoder and the decoder. [9, 10] introduce modifications in the VAE framework that allow for better robustness against the adversarial attacks on downstream classification tasks. In our work, we consider β-VAE, β-TCVAE and a hierarchical VAE, and outline a defence strategy that improves robustness to attacks on the encoder and the downstream classification task. The proposed method is applied during inference and, therefore, can be combined with other known techniques to get more robust latent representations.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

An adversarial attack on a VAE is usually formulated as an additive perturbation ε of the real data point $\mathbf{x}^r$ so that the resulting point is perceived by a model as if it is a totally different image (either during reconstruction or in the downstream classification task) [15]. In Figure 1, we depict an example of an attack on the encoder: the reference point $\mathbf{x}^r$ and the adversarial point $\mathbf{x}^a$ are almost indistinguishable, but they are encoded into different regions in the latent space. As a result, their reconstructions also differ significantly.

In this paper, we formulate the following hypothesis: *An adversarial attack maps the input to a latent region with a lower probability mass assigned by the true posterior (proportional to the conditional likelihood times the marginal over latents) and, eventually, we obtain incorrect reconstructions*. Therefore, a potential manner to milden the effect of an attack may rely on running a Markov chain to move the latent representation back to a more probable latent region. Such a defence is reasonable because we do not modify the training procedure or the model itself, we only insert a correction procedure. As a result, we propose to counteract adversarial attacks by enhancing the variational inference with Markov Chain Monte Carlo (MCMC) sampling. The toy experiment depicted in the

Figure 1: Example of an unsupervised encoder attack on VAE with 2D latent space and the proposed defence. Given a single reference point $\mathbf{x}^r$ we learn additive perturbation ε, s.t. perturbed input $\mathbf{x}^a$ has the most different latent code and, therefore, the reconstruction $\widetilde{\mathbf{x}}^a$. We observe that a single reference point can be mapped to extremely different regions of the latent space but using MCMC we are able to move them closer to the initial position so that the reconstruction $\widetilde{\mathbf{x}}^a_{HMC}$ is similar to the initial one $\widetilde{\mathbf{x}}^r$.

Figure 1 shows that the latent code of the adversarial input (red circle) moves closer to the latent code of the reference point (orange circle) after applying the MCMC (purple circle).

The contribution of this work is the following:

- We propose to use an MCMC technique during inference to correct adversarial attacks on VAEs.

- We show theoretically that the application of an MCMC technique could indeed help to counteract adversarial attacks (Theorem 3).

- We indicate empirically that the previously proposed strategies to counteract adversarial attacks do not generalize well across various datasets.

- We show empirically that the proposed approach (i.e., a VAE with an MCMC during inference) outperforms all baselines by a significant margin.

2 Background

2.1 Variational Autoencoders

Let us consider a vector of observable random variables, $\mathbf{x} \in \mathcal{X}^D$ (e.g., $\mathcal{X} = \mathbb{R}$) sampled from the empirical distribution $p_e(\mathbf{x})$, and vectors of latent variables $\mathbf{z}_k \in \mathbb{R}^{M_k}$, $k = 1, 2, \ldots, K$, where M_k is the dimensionality of each latent vector. First, we focus on a model with $K = 1$ and the joint distribution $p_\theta(\mathbf{x}, \mathbf{z}) = p_\theta(\mathbf{x}|\mathbf{z})p(\mathbf{z})$. The marginal likelihood is then equal to $p_\theta(\mathbf{x}) = \int p_\theta(\mathbf{x}, \mathbf{z})\mathrm{d}\mathbf{z}$. VAEs exploit variational inference [20] with a family of variational posteriors $\{q_\phi(\mathbf{z}|\mathbf{x})\}$, also referred to as encoders, that results in a tractable objective function, i.e., the Evidence Lower BOund (ELBO):
$$\mathcal{L}(\phi, \theta) = \mathbb{E}_{p_e(\mathbf{x})}\left(\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})} \ln p_\theta(\mathbf{x}|\mathbf{z}) - D_{\mathrm{KL}}\left[q_\phi(\mathbf{z}|\mathbf{x})\|p(\mathbf{z})\right]\right).$$

β-VAE [18] uses a modified objective by weighting the D_{KL} term by $\beta > 0$. In the case of $K > 1$, we consider a hierarchical latent structure with the generative model of the following form:

Table 1: Different types of attacks on the VAE. We denote $g_\theta(z)$ the deterministic mapping induced by decoder $p_\theta(x|z)$ and as $p_\psi(y|z)$ classification model in the latent space (downstream task). * Only used during VAE training

	REFERENCE	$f(x)$	$\Delta[A, B]$	$\|\cdot\|_p$	TYPE
Latent Space Attack	[4, 15, 32]	$q_\phi(\cdot|x)$	$D_{\mathrm{KL}}[A\|B]$	2	Supervised
Unsupervised Encoder Attack	[23]	$q_\phi(\cdot|x)$	$\mathrm{SKL}[A\|B]$	2	Unsupervised
Targeted Output Attack	[15]	$g_\theta(\tilde{z}), \tilde{z} \sim q_\phi(\cdot|x)$	$\|A - B\|_2^2$	2	Supervised
Maximum Damage Attack	[4, 8]	$g_\theta(\tilde{z}), \tilde{z} \sim q_\phi(\cdot|x)$	$\|A - B\|_2^2$	2	Unsupervised
Projected Gradient Descent Attack*	[10]	$q_\phi(\cdot|x)$	$\mathcal{WD}[A, B]$	inf	Unsupervised
Adversarial Accuracy	[9, 10]	$p_\psi(y|\tilde{z}), \tilde{z} \sim q_\phi(\cdot|x)$	CROSS ENTROPY	inf	Unsupervised

$p_\theta(\mathbf{x}, \mathbf{z}_1, \ldots, \mathbf{z}_K) = p_\theta(\mathbf{x}|\mathbf{z}_1, \ldots, \mathbf{z}_K) \prod_{k=1}^{K} p_\theta(\mathbf{z}_k|\mathbf{z}_{>k})$. There are various possible formulations of the family of variational posteriors. However, here we follow the proposition of [28] with the autoregressive inference model, namely, $q_\phi(\mathbf{z}_1, \ldots, \mathbf{z}_K|\mathbf{x}) = q_\phi(\mathbf{z}_K|\mathbf{x}) \prod_{k=1}^{K-1} q_{\theta,\phi}(\mathbf{z}_k|\mathbf{z}_{>k}, \mathbf{x})$. This formulation was used, among others, in NVAE [30]. Because of the top-down structure, it allows sharing data-dependent information between the inference model and the generative model.

2.2 Adversarial attacks

An *adversarial attack* is a slightly deformed data point that results in an undesired or unpredictable performance of a model [16]. In this work, we focus on the attacks that are constructed as an additive perturbation of the real data point $\mathbf{x}^r$ (which we will refer to as *reference*), namely:

$$\mathbf{x}^a = \mathbf{x}^r + \varepsilon, \text{ where} \tag{1}$$
$$\|\varepsilon\|_p \le \delta, \tag{2}$$

where δ is the radius of the attack. The additive perturbation ε is chosen in such a way that the attacked point does not differ from the reference point too much in a sense of a given similarity measure. It is a solution to an optimization problem solved by the attacker. The optimization problem could be formulated in various manners by optimizing different objectives and by having specific constraints and/or assumptions.

Attack construction Let $f(x)$ be part of the model available to the attacker. In the case of VAEs, this, for example, may be an encoder network or an encoder with the downstream classifier in the latent space. The attacker uses a similarity measure Δ to learn an additive perturbation to a reference point. We consider two settings: *unsupervised* and *supervised*. In the former case, the perturbation is supposed to incur the largest possible change in f:

$$\varepsilon = \arg \max_{\|\varepsilon\|_p \le \delta} \Delta\left[f(\mathbf{x}^r + \varepsilon), f(\mathbf{x}^r)\right]. \tag{3}$$

The latter setting requires a *target point* $\mathbf{x}^t$. The perturbation attempts to match the output for the target and the attacked points, namely:

$$\varepsilon = \arg \min_{\|\varepsilon\|_p \le \delta} \Delta\left[f(\mathbf{x}^r + \varepsilon), f(\mathbf{x}^t)\right]. \tag{4}$$

There are different ways to select f and Δ in the literature. Furthermore, different L_p-norms can be used to restrict the radius of the attack. Table 1 summarizes recent work on the topic.

In this work, we focus on attacking the encoder and the downstream classification task using unsupervised adversarial attacks. In the former, we maximize the symmetric KL-divergence to get the point with the most unexpected latent code and, therefore, the reconstruction. In the latter, the latent code is passed to a classifier. The attack is trained to change the class of the point by maximizing the cross-entropy loss. However, the method we propose in Section 3 is not limited to these setups since it is agnostic to how the attack was trained.

Robustness measures To measure the robustness of the VAE as well as the success of the proposed defence strategy, we focus on two metrics: MSSSIM and Adversarial accuracy.

For latent space attacks we follow [23] in using Multi-Scale Structural Similarity Index Measure (MSSSIM) [31]. We calculate $\text{MSSSIM}[\widetilde{\mathbf{x}}^r, \widetilde{\mathbf{x}}^a]$, i.e., the similarity between reconstructions of $\mathbf{x}^r$ and the corresponding $\mathbf{x}^a$. We do not report the similarity between a reference and the corresponding adversarial input, since this value is the same for all the considered models (for a given attack radius). A successful adversarial attack would have a small value of $\text{MSSSIM}[\widetilde{\mathbf{x}}^r, \widetilde{\mathbf{x}}^a]$.

For the attacks on the downstream classifier, we follow [9, 10] and calculate the adversarial accuracy. For a given trained VAE model, we first train a linear classifier using latent codes as features. Afterwards, the attack is trained to fool the classifier. Adversarial accuracy is the proportion of points for which the attack was unsuccessful. Namely, when the predicted class of the reference and corresponding adversarial point are the same.

3   Preventing adversarial attacks with MCMC

Assumptions and the hypothesis We consider a scenario in which an attacker has access to the VAE encoder and, where relevant, to the downstream classification model. Above, we presented in detail how an attack could be performed. We assume that the defender cannot modify these components, but it is possible to add elements that the attacker has no access to.

We hypothesize that *the adversarial attacks result in incorrect reconstructions because the latent representation of the adversarial input lands in a region with a lower probability mass assigned by the true posterior*. A potential solution to this issue would be to bring the latents "back" to a highly probable region. Since the adversarial attack destroys the input irreversibly, at the first sight it seems impossible to reconstruct the latent representation of the reference point. We aim at showing that this is possible to some degree.

The proposed solution In order to steer the latents towards high probability regions, we propose to utilize an MCMC method during inference time. Since we are not allowed to modify the VAE or its learning procedure, this is a reasonable procedure from the defender's perspective. Another positive outcome of such an approach is that in a case of no attack, the latents given by the MCMC sampling will be closer to the mean of the posterior, thus, the reconstruction should be sharper or, at least, not worse. Note that the variational posterior approximates the true posterior from which the MCMC procedure samples. We propose to sample from $q^{(t)}(\mathbf{z}|\mathbf{x}) = \int Q^{(t)}(\mathbf{z}|\mathbf{z}_0)q_\phi(\mathbf{z}_0|\mathbf{x})d\mathbf{z}_0$, where $Q^{(t)}(\mathbf{z}|\mathbf{z}_0)$ is a transition kernel of MCMC with the target distribution $\pi(\mathbf{z}) = p_\theta(\mathbf{z}|\mathbf{x}) \propto p_\theta(\mathbf{x}|\mathbf{z})p(\mathbf{z})$.

Now, the naturally arising question is whether applying the MCMC could indeed help us in the case of an adversarial attack. To further analyze the proposed approach, we start with showing the following lemma:

Lemma 1 *Consider true posterior distributions of the latent code $\mathbf{z}$ for a data point $\mathbf{x}^r$ and its corrupted version $\mathbf{x}^a$. Assume also that $\ln p_\theta(\mathbf{z}|\mathbf{x})$ is differentiable at the point $\mathbf{x} = \mathbf{x}^r$. Then the KL-divergence between these two posteriors could be expressed using the small o notation in terms of the radius of the attack, namely:*

$$D_{\text{KL}}\left[p_\theta(\mathbf{z}|\mathbf{x}^r) \| p_\theta(\mathbf{z}|\mathbf{x}^a)\right] = o(\|\varepsilon\|). \tag{5}$$

Proof See Appendix A.

According to Lemma 1, the difference (in the sense of the Kullback-Leibler divergence) between the true posteriors for a data point $\mathbf{x}$ and its corrupted version $\mathbf{x}^a$ is proportional to the norm of the noise (attack). This result is rather intuitive because the stronger is the noise, the larger is the difference between the latent representations.

Next, the crucial step to show is whether we can quantify somehow the difference between the distribution over latents for $\mathbf{x}^a$ after applying the MCMC, $q^{(t)}(\mathbf{z}|\mathbf{x}^a)$, and the variational distribution for $\mathbf{x}^r$, $q_\phi(\mathbf{z}|\mathbf{x}^r)$. We provide an important upper-bound for the Total Variation distance (TV)[1] between $q^{(t)}(\mathbf{z}|\mathbf{x}^a)$ and $q_\phi(\mathbf{z}|\mathbf{x}^r)$ in the following lemma:

---

[1]The Total Variation fulfills the triangle inequality and it is a proper distance measure.

Lemma 2 *The Total Variation distance (*TV*) between the variational posterior with MCMC for a given corrupted point $\mathbf{x}^a$, $q^{(t)}(\mathbf{z}|\mathbf{x}^a)$, and the variational posterior for a given data point $\mathbf{x}^r$, $q_\phi(\mathbf{z}|\mathbf{x}^r)$, can be upper bounded by the sum of the following three components:*

$$
\begin{aligned}
\mathrm{TV}\left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), q_\phi(\mathbf{z}|\mathbf{x}^r)\right] \leq\ & \mathrm{TV}\left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), p_\theta(\mathbf{z}|\mathbf{x}^a)\right] \\
& + \sqrt{\tfrac{1}{2} D_{\mathrm{KL}}\left[p_\theta(\mathbf{z}|\mathbf{x}^r)\|p_\theta(\mathbf{z}|\mathbf{x}^a)\right]} \\
& + \sqrt{\tfrac{1}{2} D_{\mathrm{KL}}\left[q_\phi(\mathbf{z}|\mathbf{x}^r)\|p_\theta(\mathbf{z}|\mathbf{x}^r)\right]}.
\end{aligned}
\tag{6}
$$

Proof See Appendix A.

The difference expressed by $\mathrm{TV}\left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), q_\phi(\mathbf{z}|\mathbf{x}^r)\right]$ is thus upper-bounded by the following three components:

- The TV between $q^{(t)}(\mathbf{z}|\mathbf{x}^a)$ and the real posterior for the corrupted image, $p_\theta(\mathbf{z}|\mathbf{x}^a)$. Theoretically, if $t \to \infty$, $q^{(\infty)}(\mathbf{z}|\mathbf{x}^a) = p_\theta(\mathbf{z}|\mathbf{x}^a)$ and, hence, $\mathrm{TV}\left[q^{(\infty)}(\mathbf{z}|\mathbf{x}^a), p_\theta(\mathbf{z}|\mathbf{x}^a)\right] = 0$.

- The second component is the square root of the KL-divergence between the real posteriors for the image and its corrupted counterpart. Lemma 1 gives us information about this quantity.

- The last element, the square root of $D_{\mathrm{KL}}\left[q_\phi(\mathbf{z}|\mathbf{x}^r)\|p_\theta(\mathbf{z}|\mathbf{x}^r)\right]$, quantifies the *approximation gap* [13], i.e., the difference between the best variational posterior from a chosen family, and the true posterior. This quantity has no direct connection with adversarial attacks. However, as we can see, using a rich family of variational posteriors can help us to obtain a tighter upper-bound. In other words, taking flexible variational posteriors allows to counteract attacks. This finding is in line with the papers that propose to use hierarchical VAEs as the means for preventing adversarial attacks [32].

Eventually, by applying Lemma 1 to Lemma 2, we obtain the following result:

Theorem 3 *The upper bound on the total variation distance between samples from MCMC for a given corrupted point $\mathbf{x}^a$, $q^{(t)}(\mathbf{z}|\mathbf{x}^a)$, and the variational posterior for the given real point $\mathbf{x}^r$, $q_\phi(\mathbf{z}|\mathbf{x}^r)$, is the following:*

$$
\begin{aligned}
\mathrm{TV}\left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), q_\phi(\mathbf{z}|\mathbf{x}^r)\right] \leq\ & \mathrm{TV}\left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), p_\theta(\mathbf{z}|\mathbf{x}^a)\right] \\
& + \sqrt{\tfrac{1}{2} D_{\mathrm{KL}}\left[q_\phi(\mathbf{z}|\mathbf{x}^r)\|p_\theta(\mathbf{z}|\mathbf{x}^r)\right]} \\
& + o(\sqrt{\|\varepsilon\|}).
\end{aligned}
\tag{7}
$$

Proof See Appendix A.

As discussed already, the first component gets smaller with more steps of the MCMC. The second component could be treated as a *bias* of the family of variational posteriors. Finally, there is the last element that corresponds to a constant error that is unavoidable. However, this term decays faster than the square root of the attack radius.

Specific implementation of the proposed approach   In this paper, we use a specific MCMC method, namely, the Hamiltonian Monte Carlo (HMC) [6, 14]. Once the VAE is trained, the attacker calculates an adversarial point $\mathbf{x}^a$ using the encoder of the VAE. After the attack, the latent representation of $\mathbf{x}^a$ is calculated, $\mathbf{z}^a$, and used as the initialization of the HMC.

In the HMC, the target (unnormalized) distribution is $p(\mathbf{x}^a|\mathbf{z})p(\mathbf{z})$. The Hamiltonian is then the energy of the joint distribution of $\mathbf{z}$ and the auxilary variable $\mathbf{p}$, that is:

$$
H(\mathbf{z}, \mathbf{p}) = U(\mathbf{z}) + K(\mathbf{p}), \tag{8}
$$
$$
U(\mathbf{z}) = -\ln p_\theta(\mathbf{x}^a|\mathbf{z}) - \ln p(\mathbf{z}), \tag{9}
$$
$$
K(\mathbf{p}) = -\tfrac{1}{2}\mathbf{p}^T\mathbf{p}. \tag{10}
$$

When applying the proposed defence to hierarchical models, we update all the latent variables simultaneously. That is, we have $\mathbf{z} = \{\mathbf{z}_1, \ldots, \mathbf{z}_K\}$ and $U(\mathbf{z}) = -\ln p_\theta(\mathbf{x}^a|\mathbf{z}) - \sum_{k=1}^{K} \ln p_\theta(\mathbf{z}_k|\mathbf{z}_{k+1})$.

Eventually, the resulting latents from the HMC are decoded. The steps of the whole process are presented below:

1. (*Defender*) Train a VAE: $q_\phi(\mathbf{z}|\mathbf{x})$, $p(\mathbf{z})$, $p_\theta(\mathbf{x}|\mathbf{z})$.

2. (*Attacker*) For given $\mathbf{x}^r$, calculate the attack $\mathbf{x}^a$ using the criterion equation 3 or equation 4.

3. (*Defender*) Initialize the latent code $\mathbf{z} := \mathbf{z}_0$, where $\mathbf{z}_0 \sim q_\phi(\mathbf{z}|\mathbf{x}^a)$. Then, run T steps of HMC (Algorithm 1) with the step size η and L *leapfrog* steps.

The resulting latent code $\mathbf{z}$ can be passed to the decoder to get a reconstruction or to the downstream classification task.

Algorithm 1 One Step of HMC.

Input: $\mathbf{z}, \eta, L$
  $\quad \mathbf{p} \sim \mathcal{N}(0, I)$. $\quad \triangleright$ Sample the auxiliary variable
  $\quad \mathbf{z}^{(0)} := \mathbf{z}, \mathbf{p}^{(0)} := \mathbf{p}$.
  $\quad$**for** $l = 1 \dots, L$ **do** $\quad \triangleright$ Make L steps of *leapfrog*.
  $\quad\quad \mathbf{p}^{(l)} = \mathbf{p}^{(l-1)} - \frac{\eta}{2} \nabla_\mathbf{z} U(\mathbf{z}^{(l)})$.
  $\quad\quad \mathbf{z}^{(l)} = \mathbf{z}^{(l)} + \eta \nabla_\mathbf{p} K(\mathbf{p}^{(l)})$.
  $\quad\quad \mathbf{p}^{(l)} = \mathbf{p}^{(l)} - \frac{\eta}{2} \nabla_\mathbf{z} U(\mathbf{z}^{(l)})$.
  $\quad$**end for**
  $\quad\quad\quad\quad\quad\quad \triangleright$ Accept new point with prob. α.
  $\quad \alpha = \min\left(1, \exp\left(-H(\mathbf{z}^{(L)}, \mathbf{p}^{(L)}) + H(\mathbf{z}^{(0)}, \mathbf{p}^{(0)})\right)\right)$
  $\quad \mathbf{z} = \begin{cases} \mathbf{z}^{(L)} \text{ with probability } \alpha, \\ \mathbf{z}^{(0)} \text{ otherwise.} \end{cases}$
Return: $\mathbf{z}$

---

4 Experiments

4.1 VAE, β-VAE and β-TCVAE

Datasets VAEs are trained on the MNIST, Fashion MNIST [33] and Color MNIST datasets. Following [10], we construct the Color MNIST dataset from MNIST by artificially coloring each image with seven colors (all corners of RGB cube except for black).

Models We train vanilla fully convolutional VAEs, as well as β-VAE [18] and β-TCVAE [11, 21]. Both β-VAE and β-TCVAE modify the ELBO objective to encourage disentanglement. β-VAE weighs the KL-term in the ELBO with $\beta > 0$. It is said that the larger values of β encourage disentangling of latent representations [11] and improve the model robustness as observed by [8]. β-TCVAE puts a higher weight on the total correlation (TC) term of the ELBO. Penalization of the total correlation was shown to increase the robustness of VAE adversarial attacks [32].

In Appendix C.1 we provide details of the architecture, optimization, and results on the test dataset for VAE trained with different values of β. We note that the optimal value in terms of the negative log-likelihood (NLL) is always $\beta = 1$. Larger values of β are supposed to improve robust-

(a) $\mathbf{x}^r$	(b) $\widetilde{\mathbf{x}}^r$	(c) $\mathbf{x}^a$	(d) $\widetilde{\mathbf{x}}^a$	(e) $\widetilde{\mathbf{x}}^a_{\mathrm{HMC}}$

Figure 2: Examples of (a) reference points, (b) reconstructions of the reference points, (c) adversarial points, (d) reconstructions of the adversarial points, (e) reconstructions of the adversarial points after the proposed defence (HMC). All the adversarial examples are unsupervised attacks on the encoder.

ness in exchange for the reconstruction quality. When evaluating the robustness of β-VAE and β-TCVAE, we train models with $\beta \in \{2, 5, 10\}$. Then, we select the value of β that provides the most robust model in terms of the used metric. Next, we apply our defence strategy to this model to observe the potential performance improvement.

Attacks on the Encoder In the first setup, we assume that the attacker has access to the encoder of the model $q_\phi(z|x)$ [4, 15, 32]. We use the projected gradient descent (PGD) with 50 steps to maximize

Table 2: Results for unsupervised attack with radius 0.1 (top) and 0.2 (bottom) on MNIST and Fashion MNIST datasets. We attack the encoder (left) and the downstream classification task (right). † Our implementation.

		MSSSIM[$\widetilde{\mathbf{x}}^r, \widetilde{\mathbf{x}}^a$] ↑		ADVERSARIAL ACCURACY ↑			MSE
		0.1	0.2	0.0	0.1	0.2	
MNIST	VAE	0.70 (0.02)	0.36 (0.03)	**0.90** (0.04)	0.08 (0.04)	0.05 (0.03)	**578.7**
	VAE + HMC	**0.88** (0.01)	**0.76** (0.02)	**0.90** (0.04)	**0.25** (0.03)	**0.19** (0.03)	**578.7**
	β-VAE	0.75 (0.01)	0.50 (0.03)	0.90 (0.05)	0.11 (0.04)	0.01 (0.01)	824.2
	β-TCVAE†	0.70 (0.02)	0.46 (0.03)	0.86 (0.05)	0.05 (0.03)	0.03 (0.02)	828.4
FASHION MNIST	VAE	0.59 (0.03)	0.47 (0.03)	0.78 (0.06)	0.00 (0.01)	0.01 (0.01)	**814.2**
	VAE + HMC	**0.66** (0.03)	**0.54** (0.03)	0.78 (0.06)	**0.14** (0.02)	**0.13** (0.02)	**814.2**
	β-VAE	0.52 (0.03)	0.41 (0.03)	0.80 (0.05)	0.00 (0.01)	0.00 (0.01)	1021.1
	β-TCVAE†	0.52 (0.03)	0.42 (0.03)	**0.84** (0.05)	0.00 (0.01)	0.02 (0.02)	980.4

Table 3: Results for unsupervised attack with radius 0.1 (top) and 0.2 (bottom) on ColorMNIST dataset. We attack the encoder (left) and the downstream classification task (right).
† Our implementation.
* Values reported in [9], VAE implementation and evaluation protocol may differ.

	MSSSIM[$\widetilde{\mathbf{x}}^r, \widetilde{\mathbf{x}}^a$] ↑		ADVERSARIAL ACCURACY ↑						MSE	FID
			DIGIT			COLOR				
$\|\varepsilon\|$	0.1	0.2	0.0	0.1	0.2	0.0	0.1	0.2		
VAE	0.36 (0.03)	0.19 (0.02)	1.00 (0.00)	0.04 (0.03)	0.02 (0.02)	1.00 (0.00)	0.06 (0.03)	0.06 (0.03)	**261**	**2.1**
VAE + HMC	**0.96** (0.01)	**0.90** (0.01)	**1.00** (0.00)	0.16 (0.02)	0.11 (0.02)	1.00 (0.00)	0.68 (0.03)	0.62 (0.03)	**261**	**2.1**
β-VAE	0.75 (0.01)	0.5 (0.03)	0.88 (0.04)	0.08 (0.04)	0.05 (0.03)	1.00 (0.00)	0.21 (0.06)	0.18 (0.05)	366	2.4
β-TCVAE†	0.35 (0.02)	0.23 (0.02)	0.94 (0.04)	0.08 (0.04)	0.05 (0.03)	1.00 (0.00)	0.06 (0.03)	0.05 (0.02)	366	3.0
$SE_{0.1}$*	N/A	N/A	0.94 (N/A)	0.89 (N/A)	0.02 (N/A)	1.00 (N/A)	1.00 (N/A)	0.22 (N/A)	1372	13.0
$SE_{0.2}$*	N/A	N/A	0.95 (N/A)	0.92 (N/A)	**0.87** (N/A)	1.00 (N/A)	1.00 (N/A)	**1.00** (N/A)	1375	11.7
AVAE*	N/A	N/A	0.97 (N/A)	0.88 (N/A)	0.55 (N/A)	1.00 (N/A)	1.00 (N/A)	0.88 (N/A)	1372	15.5
$SE_{0.1}$-AVAE*	N/A	N/A	0.97 (N/A)	**0.94** (N/A)	0.25 (N/A)	1.00 (N/A)	1.00 (N/A)	0.60 (N/A)	1373	13.9
$SE_{0.2}$-AVAE*	N/A	N/A	0.98 (N/A)	**0.94** (N/A)	0.80 (N/A)	1.00 (N/A)	1.00 (N/A)	0.83 (N/A)	1374	13.9
AVAE-SS*	N/A	N/A	0.94 (N/A)	0.73 (N/A)	0.21 (N/A)	1.00 (N/A)	1.00 (N/A)	0.57 (N/A)	1379	12.4

the symmetric KL-divergence in the unsupervised setting (equation 3). We train 10 adversarial attacks (with different random initialization) for each of 50 reference points. See Appendix C.2 for the details. We report similarity between the reconstruction of the adversarial and reference point as a measure of the robustness (see Section 2.2).

Attacks on the downstream task   In this setup, we examine how the proposed approach can aleviate the effect of the attack on the downstream tasks in the latent space. For this purpose, we follow the procedure from [9, 10]. Once the VAE is trained, we learn a linear classifier using the mean mappings as features. For the MNIST and Fashion MNIST datasets, we have the 10-class classification problem (digits in the former and pieces of clothing in the latter case). For the ColorMNIST dataset, we consider two classification tasks: the digit classification (10 classes), and the color classification (7 classes). We construct the attack to fool the classifier. See Appendix C.2 for the details.

Results   In Tables 2 and 3, we compare our method (VAE + HMC) with the vanilla VAE with other methods in the literature. We report more results and the extended comparison in the Appendix B.1 where we show that our method combined with β-VAE and β-TCVAE leads to the increased robustness. For MNIST and Fashion MNIST (Table 2), we observe that the vanilla VAE with the HMC is more robust than β-VAE and β-TCVAE. The latter model was shown to be more robust to the latent space attack [32]. Still, in our experiments (on different datasets), we could not observe the consistent improvement over the vanilla VAE, when using it with a single level of latent variables.

In Table 3 we report the result on the ColorMNIST dataset. Here, we additionally compare the adversarial accuracy for our method with the Smooth Encoders (SE) and Autoencoding Variational Autoencoder (AVAE) methods [9, 10]. We notice that these methods provide higher adversarial accuracy. However, we have also observed a large discrepancy in terms of the MSE and FID scores

(a) The reconstruction similarity for MNIST   (b) The reconstruction similarity for CelebA

Figure 3: The robustness improvement for the hierarchical model (NVAE) on (a) MNIST and (b) CelebA for two different attack radii. Higher values correspond to more robust representations.

of the model itself compared to our experiments, which we suspect might be a result of a mistake in [9, 10]. [2]

Lastly, we would like to highlight that our defence strategy can be also combined with all the above VAE modifications. Another advantage of our approach is that it does not require changing the training procedure of a VAE and, as a result, it does not decrease the quality of the generated images. As we observe from the columns **MSE** and **FID**, the quality of the vanilla VAE is always better compared to the models with modified training objectives. We depict several examples of the reconstructions of the attacked point in Figure 2.

4.2 Hierarchical VAE: NVAE

Model and datasets In this section, we explore the robustness of the deep hierarchical VAE (NVAE) [30], a specific implementation of a hierarchical VAE that works well for high-dimensional data. We attack models trained on MNIST and CelebA [24] datasets. We use the weights of the pre-trained model provided in the official NVAE implementation[3].

Attacks construction Following [23] we construct adversarial attacks on the hierarchical VAE by considering higher-level latent variables. That being said, we use latent variables $\{\mathbf{z}_{L-k_A}, \mathbf{z}_{L-k_A+1}, \ldots, \mathbf{z}_L\}$ when constructing an attack (equation 3). Otherwise, we follow the same procedure we used for VAEs with a single level of latent variables. We assume that the attacker has access to the model's encoder and uses the symmetric KL-divergence as the objective. The radius of an attack is measured with the $L_{\inf}$ norm. For optimization, we use the projected gradient descent with the number of iterations limited to 50 per point. Further details are reported in the Appendix C.2.

Results In Figure 3, we present reconstruction similarity of the reference and adversarial points for both datasets. We observe that the proposed method consistently improves the robustness of the model to the adversarial attack. This result is in line with our theoretical considerations where a flexible class of variational posteriors could help to counteract adversarial attacks and, eventually, deacrease the bias of the class of models measured in terms of the KL-divergence. Additionally, applying the MCMC can further help us to counteract the attack. In Figure 2 (the two bottom rows), we show how an adversarial point (c) is reconstructed without any defence (d) and with the proposed defence (e). In the depicted samples, we have used the top 10 latent variables ($k_A = 10$) to construct the attack with a radius of 0.05.

4.3 Ablation Study: What if the attacker knows the defence strategy?

In our experiments, we rely on the assumption that the attacker does not take into account the defence strategy that we use. We believe that it is reasonable, since the defence requires access to the decoder part of the model, $p_\theta(x|z)$, which is not necessarily available to the attacker.

In this ablation study we verify how the robustness results change if we construct the attack with the access to the defence strategy. We train an adversarial attack with the modified objective 3, which takes into account the HMC step. See Appendix B.2 for more details on the experimental setup.

---

[2]We have gotten in touch with the authors, who are kindly working with us to address this issue

[3]The code and model weights were taken from `https://github.com/NVlabs/NVAE`

(a) An attacker does not know the defence strategy

(b) An attacker knows the defence strategy

Figure 4: Robustness to adversarial attack (with HMC defence). We report similarity of the reference and adversarial point (blue) and their reconstructions (orange).

In Figure 4 we show the experiment results for various attack radii between 0 and 1. We observe that constructing an attack with such an objective is much harder (Figure 4 (b)).

5   Discussion

Following the previous works on attacking VAEs [4, 8, 9, 10, 15, 32], we only consider the projected gradient descent as a way to construct the attack. However, more sophisticated adaptive methods [2, 29] were proposed to attack discriminative model and can be potentially applied to VAEs as well. We believe that it is an interesting direction for the future work.

Objective Function   For the unsupervised attack on the encoder, we use the symmetric KL-divergence to measure the dissimilarity. However, other options are possible, e.g., the forward or reverse KL-divergence or even L_2 distance between the means (see Table 1). In our comparative experiments (see Appendix B.5), we observe that no single objective consistently performs better than others.

Attack radius   During the attack construction we seek to obtain a point that will have the most different latent representation or a different predicted class. However, it is also important that the point itself is as similar to the initial reference point as possible. In Appendix B.3, we visualize how the attacks of different radii influence the similarity between the adversarial and reference points. Based on these results, we have chosen the radii which do not allow adversarial points to deviate a lot from the reference (as measured by MSSSIM): $\|\varepsilon\|_{\text{inf}} \leq 0.2$ for the MNIST dataset (which goes in line with the previous works [9, 10]) and $\|\varepsilon\|_{\text{inf}} \leq 0.1$ for the CelebA dataset.

Number of MCMC steps   In our approach, we have to select the number of MCMC steps that the defender performs. This parameter potentially can be critical. Following the theoretical analysis, the more steps in the MCMC procedure is taken, the tighter the bound (7) is. On the other hand, typically we have time- and computational constraints to take into account. In Appendix B.4, we show the method's performance for the number of HMC steps ranging between 0 and 2000. There is a considerable jump in robustness between 0 and 100 steps. At the same time, we do not observe much improvement as we continue to increase the number of steps.

6   Conclusion

In this work, we explore the robustness of VAEs to adversarial attacks. We propose a theoretically justified method that allows alleviating the effect of attacks on the latent representations by improving the reconstructions of the adversarial inputs and the downstream tasks accuracy. We experimentally validate our approach on a variety of datasets: both grey-scale (MNIST, Fashion MNIST) and colored (ColorMNIST, CelebA) data. We show that the proposed method improves the robustness of the vanilla VAE models and its various modifications, i.e., β-VAE, β-TCVAE and NVAE.

References

[1] J. An and S. Cho. Variational autoencoder based anomaly detection using reconstruction probability. *Special Lecture on IE*, 2(1):1–18, 2015.

[2] A. Athalye, N. Carlini, and D. Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. In *International conference on machine learning*, pages 274–283. PMLR, 2018.

[3] J. Ballé, D. Minnen, S. Singh, S. J. Hwang, and N. Johnston. Variational image compression with a scale hyperprior. In *International Conference on Learning Representations*, 2018.

[4] B. Barrett, A. Camuto, M. Willetts, and T. Rainforth. Certifiably robust variational autoencoders. pages 3663–3683, 2022.

[5] Y. Bengio, A. Courville, and P. Vincent. Representation learning: A review and new perspectives. *IEEE transactions on pattern analysis and machine intelligence*, 35(8):1798–1828, 2013.

[6] M. Betancourt. A conceptual introduction to hamiltonian monte carlo. *arXiv preprint arXiv:1701.02434*, 2017.

[7] Y. Burda, R. B. Grosse, and R. Salakhutdinov. Importance weighted autoencoders. In *International Conference on Learning Representations*, 2016.

[8] A. Camuto, M. Willetts, S. Roberts, C. Holmes, and T. Rainforth. Towards a theoretical understanding of the robustness of variational autoencoders. In *International Conference on Artificial Intelligence and Statistics*, pages 3565–3573. PMLR, 2021.

[9] T. Cemgil, S. Ghaisas, K. Dvijotham, S. Gowal, and P. Kohli. The autoencoding variational autoencoder. *Advances in Neural Information Processing Systems*, 33, 2020.

[10] T. Cemgil, S. Ghaisas, K. D. Dvijotham, and P. Kohli. Adversarially robust representations with smooth encoders. In *International Conference on Learning Representations*. openreview.net, 2019.

[11] R. T. Chen, X. Li, R. B. Grosse, and D. K. Duvenaud. Isolating sources of disentanglement in variational autoencoders. *Advances in neural information processing systems*, 31, 2018.

[12] R. Child. Very deep VAEs generalize autoregressive models and can outperform them on images. In *International Conference on Learning Representations*, 2021.

[13] C. Cremer, X. Li, and D. Duvenaud. Inference suboptimality in variational autoencoders. In *International Conference on Machine Learning*, pages 1078–1086. PMLR, 2018.

[14] S. Duane, A. D. Kennedy, B. J. Pendleton, and D. Roweth. Hybrid monte carlo. *Physics letters B*, 195(2):216–222, 1987.

[15] G. Gondim-Ribeiro, P. Tabacof, and E. Valle. Adversarial attacks on variational autoencoders. June 2018.

[16] I. J. Goodfellow, J. Shlens, and C. Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014.

[17] A. Habibian, T. v. Rozendaal, J. M. Tomczak, and T. S. Cohen. Video compression with rate-distortion autoencoders. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 7033–7042, 2019.

[18] I. Higgins, L. Matthey, A. Pal, C. Burgess, X. Glorot, M. Botvinick, S. Mohamed, and A. Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. 2016.

[19] I. Higgins, A. Pal, A. Rusu, L. Matthey, C. Burgess, A. Pritzel, M. Botvinick, C. Blundell, and A. Lerchner. Darla: Improving zero-shot transfer in reinforcement learning. In *International Conference on Machine Learning*, pages 1480–1490. PMLR, 2017.

[20] M. I. Jordan, Z. Ghahramani, T. S. Jaakkola, and L. K. Saul. An introduction to variational methods for graphical models. *Machine learning*, 37(2):183–233, 1999.

[21] H. Kim and A. Mnih. Disentangling by factorising. In *International Conference on Machine Learning*, pages 2649–2658. PMLR, 2018.

[22] D. P. Kingma and M. Welling. Auto-encoding variational bayes. In *International Conference on Learning Representations, ICLR 2014*, 2014.

[23] A. Kuzina, M. Welling, and J. M. Tomczak. Diagnosing vulnerability of variational auto-encoders to adversarial attacks. *ICLR, RobustML workshop*, 2021.

[24] Z. Liu, P. Luo, X. Wang, and X. Tang. Deep learning face attributes in the wild. In *Proceedings of International Conference on Computer Vision (ICCV)*, December 2015.

[25] L. Maaløe, M. Fraccaro, V. Liévin, and O. Winther. BIVA: A very deep hierarchy of latent variables for generative modeling. In *Advances in Neural Information Processing Systems*, Feb. 2019.

[26] R. Ranganath, D. Tran, and D. Blei. Hierarchical variational models. In *Proceedings of The 33rd International Conference on Machine Learning*, volume 48 of *Proceedings of Machine Learning Research*, pages 324–333, New York, New York, USA, 2016. PMLR.

[27] D. J. Rezende, S. Mohamed, and D. Wierstra. Stochastic backpropagation and approximate inference in deep generative models. In *International Conference on Machine Learning*, pages 1278–1286. PMLR, 2014.

[28] C. K. Sønderby, T. Raiko, L. Maaløe, S. R. K. Sønderby, and O. Winther. Ladder variational autoencoders. In *Advances in Neural Information Processing Systems*, volume 29, pages 3738–3746. Curran Associates, Inc., 2016.

[29] F. Tramer, N. Carlini, W. Brendel, and A. Madry. On adaptive attacks to adversarial example defenses. *Advances in Neural Information Processing Systems*, 33:1633–1645, 2020.

[30] A. Vahdat and J. Kautz. NVAE: A deep hierarchical variational autoencoder. In *Neural Information Processing Systems (NeurIPS)*, 2020.

[31] Z. Wang, E. P. Simoncelli, and A. C. Bovik. Multiscale structural similarity for image quality assessment. In *The Thrity-Seventh Asilomar Conference on Signals, Systems & Computers, 2003*, volume 2, pages 1398–1402. Ieee, 2003.

[32] M. Willetts, A. Camuto, T. Rainforth, S. Roberts, and C. Holmes. Improving VAEs' robustness to adversarial attack. In *International Conference on Learning Representations*, 2021.

[33] H. Xiao, K. Rasul, and R. Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms. *arXiv preprint arXiv:1708.07747*, 2017.

 # A   Theory

461 We consider an attack, which has an additive structure:

$$\mathbf{x}^a = \mathbf{x}^r + \varepsilon, \tag{11}$$

$$\text{such that } \|\varepsilon\| \leq \delta, \tag{12}$$

462 where δ is a radius of the attack.

463 In the vanilla VAE setup we will get the latent code by sampling from $q_\phi(\mathbf{z}|\mathbf{x})$. With our approach,
464 instead, we get a sample from the following distribution:

$$q^{(t)}(\mathbf{z}|\mathbf{x}) = \int Q^{(t)}(\mathbf{z}|\mathbf{z}_0)q_\phi(\mathbf{z}_0|\mathbf{x})d\mathbf{z}_0, \tag{13}$$

465 where $Q^{(t)}(\mathbf{z}|\mathbf{z}_0)$ is a transition kernel of MCMC with the target distribution $\pi(\mathbf{z}) = p_\theta(\mathbf{z}|\mathbf{x}) \propto$
466 $p_\theta(\mathbf{x}|\mathbf{z})p(\mathbf{z})$.

467 **Lemma 1**   Consider true posterior distributions of the latent code $\mathbf{z}$ for a data point $\mathbf{x}$ and its
468 corrupted version $\mathbf{x}^a$. Assume also that $\ln p_\theta(\mathbf{z}|\mathbf{x})$ is differentiable at the point $\mathbf{x} = \mathbf{x}^r$. Then the
469 KL-divergence between these two posteriors could be expressed using the small o notation of the
470 radius of the attack, namely:

$$D_{\mathrm{KL}}\left[p_\theta(\mathbf{z}|\mathbf{x}^r)\|p_\theta(\mathbf{z}|\mathbf{x}^a)\right] = o(\|\varepsilon\|). \tag{14}$$

471 *Proof*
472 Let us use definition of the KL-divergence:

$$D_{\mathrm{KL}}\left[p_\theta(\mathbf{z}|\mathbf{x}^r)\|p_\theta(\mathbf{z}|\mathbf{x}^a)\right] = \mathbb{E}_{p_\theta(\mathbf{z}|\mathbf{x}^r)} \ln \frac{p_\theta(\mathbf{z}|\mathbf{x}^r)}{p_\theta(\mathbf{z}|\mathbf{x}^a)} \tag{15}$$

473 Let us introduce $\ln p_\theta(\mathbf{z}|\mathbf{x}) = g(\mathbf{x}, \mathbf{z})$. Assume that this function is differentiable at $\mathbf{x} = \mathbf{x}^r$. Then,
474 we can apply Taylor expansion to $g(\mathbf{x}, \mathbf{z})$ in the point $\mathbf{x}^r$ which yields:

$$g(\mathbf{x}, \mathbf{z}) = g(\mathbf{x}^r, \mathbf{z}) + (\mathbf{x} - \mathbf{x}^r)^T \nabla_{\mathbf{x}} g(\mathbf{x}, \mathbf{z})\Big|_{\mathbf{x}^r} + o(\|\mathbf{x} - \mathbf{x}^r\|). \tag{16}$$

475 Then, the log-ratio of two distributions is the following:

$$\ln \frac{p_\theta(\mathbf{z}|\mathbf{x}^r)}{p_\theta(\mathbf{z}|\mathbf{x}^a)} = g(\mathbf{x}^r, \mathbf{z}) - g(\mathbf{x}^a, \mathbf{z}) \tag{17}$$

$$= g(\mathbf{x}^r, \mathbf{z}) - \left(g(\mathbf{x}^r, \mathbf{z}) + (\mathbf{x}^a - \mathbf{x}^r)^T \nabla_{\mathbf{x}} g(\mathbf{x}, \mathbf{z})\Big|_{\mathbf{x}^r} + o(\|\mathbf{x}^a - \mathbf{x}^r\|)\right). \tag{18}$$

$$= -\varepsilon^T \nabla_{\mathbf{x}} g(\mathbf{x}, \mathbf{z})\Big|_{\mathbf{x}^r} + o(\|\varepsilon\|). \tag{19}$$

476 Notice that $\varepsilon^T \nabla_{\mathbf{x}} g(\mathbf{x}, \mathbf{z})\Big|_{\mathbf{x}^r}$ is the dot product between ε and $\nabla_{\mathbf{x}} g(\mathbf{x}, \mathbf{z})\Big|_{\mathbf{x}^r}$, i.e., $\varepsilon^T \nabla_{\mathbf{x}} g(\mathbf{x}, \mathbf{z})\Big|_{\mathbf{x}^r} =$
477 $\langle \varepsilon, \nabla_{\mathbf{x}} g(\mathbf{x}, \mathbf{z})\Big|_{\mathbf{x}^r}\rangle$.

478 We can now plug this into the KL-divergence definition (15):

$$D_{\mathrm{KL}}\left[p_\theta(\mathbf{z}|\mathbf{x}^r)\|p_\theta(\mathbf{z}|\mathbf{x}^a)\right] = \mathbb{E}_{p_\theta(\mathbf{z}|\mathbf{x}^r)}\left[-\langle \varepsilon, \nabla_{\mathbf{x}} \ln p_\theta(\mathbf{z}|\mathbf{x})\Big|_{\mathbf{x}^r}\rangle + o(\|\varepsilon\|)\right] \tag{20}$$

$$= -\langle \varepsilon, \underbrace{\mathbb{E}_{p_\theta(\mathbf{z}|\mathbf{x}^r)} \nabla_{\mathbf{x}} \ln p_\theta(\mathbf{z}|\mathbf{x})\Big|_{\mathbf{x}^r}}_{\mathrm{A}(\mathbf{x}^r)}\rangle + o(\|\varepsilon\|) \tag{21}$$

479 Let us take a closer to look at the term $\mathrm{A}(\mathbf{x}^r)$ in the equation above:

$$\mathrm{A}(\mathbf{x}^r) = \mathbb{E}_{p_\theta(\mathbf{z}|\mathbf{x}^r)} \nabla_{\mathbf{x}} \ln p_\theta(\mathbf{z}|\mathbf{x}) \Big|_{\mathbf{x}^r} \tag{22}$$

$$= \mathbb{E}_{p_\theta(\mathbf{z}|\mathbf{x}^r)} \nabla_{\mathbf{x}} \ln \frac{p_\theta(\mathbf{x}|\mathbf{z}) p_\theta(\mathbf{z})}{p_\theta(\mathbf{x})} \Big|_{\mathbf{x}^r} \tag{23}$$

$$= \mathbb{E}_{p_\theta(\mathbf{z}|\mathbf{x}^r)} \nabla_{\mathbf{x}} \ln p_\theta(\mathbf{x}|\mathbf{z}) \Big|_{\mathbf{x}^r} - \mathbb{E}_{p_\theta(\mathbf{z}|\mathbf{x}^r)} \nabla_{\mathbf{x}} \ln p_\theta(\mathbf{x}) \Big|_{\mathbf{x}^r} \tag{24}$$

$$= \int p_\theta(\mathbf{z}|\mathbf{x}^r) \frac{\nabla_{\mathbf{x}} p_\theta(\mathbf{x}|\mathbf{z})\big|_{\mathbf{x}^r}}{p_\theta(\mathbf{x}^r|\mathbf{z})} d\mathbf{z} - \int p_\theta(\mathbf{z}|\mathbf{x}^r) \frac{\nabla_{\mathbf{x}} p_\theta(\mathbf{x})\big|_{\mathbf{x}^r}}{p_\theta(\mathbf{x}^r)} d\mathbf{z} \tag{25}$$

$$= \int \frac{p_\theta(\mathbf{z})}{p_\theta(\mathbf{x}^r)} \nabla_{\mathbf{x}} p_\theta(\mathbf{x}|\mathbf{z})\big|_{\mathbf{x}^r} d\mathbf{z} - \frac{\nabla_{\mathbf{x}} p_\theta(\mathbf{x})\big|_{\mathbf{x}^r}}{p_\theta(\mathbf{x}^r)} \underbrace{\int p_\theta(\mathbf{z}|\mathbf{x}^r) d\mathbf{z}}_{=1} \tag{26}$$

$$= \frac{1}{p_\theta(\mathbf{x}^r)} \left[\int p(\mathbf{z}) \nabla_{\mathbf{x}} p_\theta(\mathbf{x}|\mathbf{z})\big|_{\mathbf{x}^r} d\mathbf{z} - \nabla_{\mathbf{x}} p_\theta(\mathbf{x})\big|_{\mathbf{x}^r} \right] \tag{27}$$

$$= \frac{1}{p_\theta(\mathbf{x}^r)} \left[\mathbb{E}_{p(\mathbf{z})} \nabla_{\mathbf{x}} p_\theta(\mathbf{x}|\mathbf{z})\big|_{\mathbf{x}^r} - \nabla_{\mathbf{x}} \mathbb{E}_{p(\mathbf{z})} p_\theta(\mathbf{x}|\mathbf{z})\big|_{\mathbf{x}^r} \right] \tag{28}$$

$$= \frac{1}{p_\theta(\mathbf{x}^r)} \underbrace{\left[\mathbb{E}_{p(\mathbf{z})} \nabla_{\mathbf{x}} p_\theta(\mathbf{x}|\mathbf{z})\big|_{\mathbf{x}^r} - \mathbb{E}_{p(\mathbf{z})} \nabla_{\mathbf{x}} p_\theta(\mathbf{x}|\mathbf{z})\big|_{\mathbf{x}^r} \right]}_{=0} = 0. \tag{29}$$

where we use Bayes rule in 23, 26, log-derivative trick in 25.

We have shown that $\mathrm{A}(\mathbf{x}^r) = 0$, therefore, from equation 21 we have:

$$D_{\mathrm{KL}} \left[p_\theta(\mathbf{z}|\mathbf{x}^r) \| p_\theta(\mathbf{z}|\mathbf{x}^a) \right] = -\langle \varepsilon, \mathrm{A}(\mathbf{x}^r) \rangle + o(\|\varepsilon\|) = o(\|\varepsilon\|). \tag{30}$$

∎

Lemma 2 The Total Variation distance (TV) between the variational posterior with MCMC for a given corrupted point $\mathbf{x}^a$, $q^{(t)}(\mathbf{z}|\mathbf{x}^a)$, and the variational posterior for a given data point $\mathbf{x}^r$, $q_\phi(\mathbf{z}|\mathbf{x}^r)$, can be upper bounded by the sum of the following three components:

$$\mathrm{TV} \left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), q_\phi(\mathbf{z}|\mathbf{x}^r) \right] \leq \mathrm{TV} \left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), p_\theta(\mathbf{z}|\mathbf{x}^a) \right] \tag{31}$$

$$+ \sqrt{\tfrac{1}{2} D_{\mathrm{KL}} \left[p_\theta(\mathbf{z}|\mathbf{x}^r) \| p_\theta(\mathbf{z}|\mathbf{x}^a) \right]} \tag{32}$$

$$+ \sqrt{\tfrac{1}{2} D_{\mathrm{KL}} \left[q_\phi(\mathbf{z}|\mathbf{x}^r) \| p_\theta(\mathbf{z}|\mathbf{x}^r) \right]}. \tag{33}$$

Proof

Total variation is a proper distance, thus, the triangular inequality holds for it. For the proof, we apply the triangular inequality twice. First, we use the triangle inequality for $\mathrm{TV} \left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), q_\phi(\mathbf{z}|\mathbf{x}^r) \right]$, namely:

$$\mathrm{TV} \left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), q_\phi(\mathbf{z}|\mathbf{x}^r) \right] \leq \mathrm{TV} \left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), p_\theta(\mathbf{z}|\mathbf{x}^r) \right] + \mathrm{TV} \left[p_\theta(\mathbf{z}|\mathbf{x}^r), q_\phi(\mathbf{z}|\mathbf{x}^r) \right]. \tag{34}$$

Second, we utilize the triangle inequality for $\mathrm{TV} \left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), p_\theta(\mathbf{z}|\mathbf{x}^r) \right]$, that is:

$$\mathrm{TV} \left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), p_\theta(\mathbf{z}|\mathbf{x}^r) \right] \leq \mathrm{TV} \left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), p_\theta(\mathbf{z}|\mathbf{x}^a) \right] + \mathrm{TV} \left[p_\theta(\mathbf{z}|\mathbf{x}^a), p_\theta(\mathbf{z}|\mathbf{x}^r) \right]. \tag{35}$$

Combining the two gives us the following upper bound on the initial total variation:

$$\mathrm{TV} \left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), q_\phi(\mathbf{z}|\mathbf{x}^r) \right] \leq \mathrm{TV} \left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), p_\theta(\mathbf{z}|\mathbf{x}^a) \right] \tag{36}$$

$$+ \mathrm{TV} \left[p_\theta(\mathbf{z}|\mathbf{x}^a), p_\theta(\mathbf{z}|\mathbf{x}^r) \right] \tag{37}$$

$$+ \mathrm{TV} \left[p_\theta(\mathbf{z}|\mathbf{x}^r), q_\phi(\mathbf{z}|\mathbf{x}^r) \right] \tag{38}$$

Moreover, the Total Variation distance is a lower bound of the KL-divergence (by Pinsker inequality):

$$\text{TV}\left[p(\mathbf{x}), q(\mathbf{x})\right] \leq \sqrt{\tfrac{1}{2} D_{\text{KL}}\left[p(\mathbf{x})\|q(\mathbf{x})\right]}. \tag{39}$$

Applying Pinsker inequality to 37 and 38 yields:

$$\text{TV}\left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), q_\phi(\mathbf{z}|\mathbf{x}^r)\right] \leq \text{TV}\left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), p_\theta(\mathbf{z}|\mathbf{x}^a)\right] \tag{40}$$

$$+ \sqrt{\tfrac{1}{2} D_{\text{KL}}\left[p_\theta(\mathbf{z}|\mathbf{x}^r)\|p_\theta(\mathbf{z}|\mathbf{x}^a)\right]} \tag{41}$$

$$+ \sqrt{\tfrac{1}{2} D_{\text{KL}}\left[q_\phi(\mathbf{z}|\mathbf{x}^r)\|p_\theta(\mathbf{z}|\mathbf{x}^r)\right]}. \tag{42}$$

∎

Theorem 1 The upper bound on the total variation distance between samples from MCMC for a given corrupted point $\mathbf{x}^a$, $q^{(t)}(\mathbf{z}|\mathbf{x}^a)$, and the variational posterior for the given real point $\mathbf{x}$, $q_\phi(\mathbf{z}|\mathbf{x})$, is the following:

$$\text{TV}\left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), q_\phi(\mathbf{z}|\mathbf{x}^r)\right] \leq \text{TV}\left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), p_\theta(\mathbf{z}|\mathbf{x}^a)\right] + \sqrt{\tfrac{1}{2} D_{\text{KL}}\left[q_\phi(\mathbf{z}|\mathbf{x}^r)\|p_\theta(\mathbf{z}|\mathbf{x}^r)\right]} + o(\sqrt{\|\varepsilon\|}). \tag{43}$$

Proof
Combining **Lemma 1** and **2** we get:

$$\text{TV}\left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), q_\phi(\mathbf{z}|\mathbf{x}^r)\right] \underbrace{\leq}_{\text{Lemma 2}} \text{TV}\left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), p_\theta(\mathbf{z}|\mathbf{x}^a)\right] \tag{44}$$

$$+ \sqrt{\tfrac{1}{2} D_{\text{KL}}\left[p_\theta(\mathbf{z}|\mathbf{x}^r)\|p_\theta(\mathbf{z}|\mathbf{x}^a)\right]} \tag{45}$$

$$+ \sqrt{\tfrac{1}{2} D_{\text{KL}}\left[q_\phi(\mathbf{z}|\mathbf{x}^r)\|p_\theta(\mathbf{z}|\mathbf{x}^r)\right]} \tag{46}$$

$$\underbrace{=}_{\text{Lemma 1}} \text{TV}\left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), p_\theta(\mathbf{z}|\mathbf{x}^a)\right] \tag{47}$$

$$+ \sqrt{\tfrac{1}{2} o(\|\varepsilon\|)} \tag{48}$$

$$+ \sqrt{\tfrac{1}{2} D_{\text{KL}}\left[q_\phi(\mathbf{z}|\mathbf{x}^r)\|p_\theta(\mathbf{z}|\mathbf{x}^r)\right]}. \tag{49}$$

Note that $\sqrt{\tfrac{1}{2} o(\|\varepsilon\|)} = o(\sqrt{\|\varepsilon\|})$ that gives us the final expression:

$$\text{TV}\left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), q_\phi(\mathbf{z}|\mathbf{x}^r)\right] \leq \text{TV}\left[q^{(t)}(\mathbf{z}|\mathbf{x}^a), p_\theta(\mathbf{z}|\mathbf{x}^a)\right] + \sqrt{\tfrac{1}{2} D_{\text{KL}}\left[q_\phi(\mathbf{z}|\mathbf{x}^r)\|p_\theta(\mathbf{z}|\mathbf{x}^r)\right]} + o(\sqrt{\|\varepsilon\|}). \tag{50}$$

∎

B Additional results

B.1 Detailed results for β-VAE and β-TCVAE

In this section we report extended results for MNIST, FashionMNIST and ColorMNIST dataset. We

train VAE, β-VAE and β-TCVAE on three datasets: MNIST, FashionMNIST and ColorMNIST. Then,

we compare the robustness to adversarial attack with and without HMC. We present all the result with

the standard error in Table 4. On Figures 5, 6 we show visually how HMC improve the robustness for

each dataset and model.

Table 4: Robustness results on MNIST, Fashion MNIST and Color MNIST datasets. We perform
unsupervised attack with radius 0.1 (top) and 0.2 (bottom). We attack the encoder (left) and the
downstream classification task (right). Higher values correspond to more robust models.

| | | MSSSIM$[\tilde{\mathbf{x}}^r, \tilde{\mathbf{x}}^a]$ ↑ | | | ADVERSARIAL ACCURACY ↑ | | | |
| | | | | | | | COLOR MNIST | |
		MNIST	FASHION MNIST	COLOR MNIST	MNIST	FASHION MNIST	DIGIT	COLOR
$\|\varepsilon\|_{\inf} = 0.1$	VAE	0.70 (0.02)	0.59 (0.03)	0.36 (0.03)	0.08 (0.04)	0.00 (0.01)	0.04 (0.03)	0.06 (0.03)
	+ HMC	**0.88 (0.01)**	**0.66 (0.03)**	**0.96 (0.01)**	0.25 (0.03)	**0.14 (0.02)**	0.16 (0.02)	0.68 (0.03)
	β-VAE	0.75 (0.01)	0.52 (0.03)	0.50 (0.04)	0.11 (0.04)	0.00 (0.02)	0.08 (0.04)	0.21 (0.06)
	+ HMC	0.84 (0.01)	0.64 (0.03)	0.92 (0.03)	**0.30 (0.03)**	0.13 (0.02)	0.14 (0.02)	0.66 (0.04)
	β-TCVAE	0.70 (0.02)	0.52 (0.03)	0.35 (0.03)	0.05 (0.03)	0.01 (0.01)	0.08 (0.04)	0.06 (0.03)
	+ HMC	0.79 (0.02)	**0.66 (0.03)**	**0.96 (0.01)**	0.25 (0.04)	0.13 (0.02)	**0.22 (0.03)**	**0.81 (0.02)**
$\|\varepsilon\|_{\inf} = 0.2$	VAE	0.36 (0.03)	0.47 (0.03)	0.19 (0.02)	0.05 (0.03)	0.01 (0.01)	0.02 (0.02)	0.06 (0.03)
	+ HMC	**0.76 (0.02)**	**0.54 (0.03)**	**0.90 (0.01)**	**0.19 (0.03)**	**0.13 (0.02)**	0.11 (0.02)	0.62 (0.03)
	β-VAE	0.50 (0.03)	0.41 (0.03)	0.38 (0.04)	0.01 (0.01)	0.00 (0.01)	0.05 (0.03)	0.18 (0.05)
	+ HMC	0.69 (0.03)	0.50 (0.03)	0.87 (0.01)	0.16 (0.02)	0.12 (0.02)	**0.15 (0.02)**	0.56 (0.04)
	β-TCVAE	0.45 (0.03)	0.42 (0.03)	0.20 (0.02)	0.03 (0.02)	0.02 (0.02)	0.05 (0.03)	0.05 (0.03)
	+ HMC	0.65 (0.03)	0.52 (0.03)	0.87 (0.01)	0.16 (0.04)	0.11 (0.02)	0.14 (0.02)	**0.72 (0.03)**

(a) $\|\varepsilon\|_{\inf} = 0.1$ (b) $\|\varepsilon\|_{\inf} = 0.2$

Figure 5: Improvement of the Reconstruction Similarity after the proposed defence. We fix the attack
radius to be equal to (a) 0.1 and (b) 0.2. Higher values correspond to a more robust representations.

(a) $\|\varepsilon\|_{\inf} = 0.1$ (b) $\|\varepsilon\|_{\inf} = 0.2$

Figure 6: Improvement of the Adversarial Accuracy after proposed defence. We fix the attack radius
to be equal to (a) 0.1 and (b) 0.2.

B.2 What if the attacker knows the defence strategy?

In our experiments we relied on the assumption that attack does not take into account the defence strategy that we use. We believe that it is reasonable, since defence requires access to the decoder part of the model ($p_\theta(x|z)$), which is not necessarily available to the attacker.

However, one may assume that the defence strategy is known to the attacker. In this case, it is reasonable to verify whether the robustness results change. In the conducted experiment we show that it is vastly more complicated to attack the encoder with taking the MCMC defence into account. We train the unsupervised attack (3). The attack has access to the encoder and MCMC defence:

$$f(x) = q^{(t)}(\mathbf{z}|\mathbf{x}) = \int Q^{(t)}(\mathbf{z}|\mathbf{z}_0) q_\phi(\mathbf{z}_0|\mathbf{x}) d\mathbf{z}_0, \tag{51}$$

Then, given the attack radius δ, we train the attack using the following objective:

$$\varepsilon^* = \arg \max_{\|\varepsilon\|_{\inf} < \delta} \|\widetilde{z}^a - \widetilde{z}^t\|^2, \tag{52}$$

$$\widetilde{z}^a \sim q^{(t)}(\mathbf{z}|\mathbf{x}^r + \varepsilon), \tag{53}$$

$$\widetilde{z}^r \sim q^{(t)}(\mathbf{z}|\mathbf{x}^r). \tag{54}$$

The similarity results of these attacks are plotted in Figure 8. We observe that the reconstructed reference and adversarial points have approximately the same similarity (measured by MSSSIM) as the initial points $\mathbf{x}^r$ and $\mathbf{x}^a$, which indicates that the attacks were unsuccessful.

However, if we use the same objective, but omit the MCMC step (e.g $t = 0$ in eq. 53 and 54), then, as observed in Figure 7, the attack becomes much more successful (Figure 7 (a)), but we can fix it with the proposed defence (Figure 7 (b)).

It is interesting to compare how the attacked points look in both cases, especially as we increase the radius of the attack. In Figure 9, we plot attack on two reference points for radius values in $\{0.1, 0.6, 0.8, 1.0\}$. When the attacker does not use MCMC (left), it just learns to add more and more noise to the image, which eventually makes it meaningless.

When we use MCMC during an attack, the situation is different. The adversarial input is almost indistinguishable from the reference point for a small radius. After each gradient update, the attacker runs a new MCMC, which moves point closer to the region of high posterior probability, but may follow a different trajectory every time. Eventually, it makes it harder to learn an additive perturbation ε. However, as we increase the attack radius, we observe a very interesting effect. Instead of meaningless noise, the attacker learns to change the digit. For instance, we see how 4 is transformed into 0 in the first example and into 9 in the second. This way, the attacker ensures that the MCMC will move the latent far away from the reference latent code, which now has a different posterior distribution.

(a) No defence (b) MCMC defence

Figure 7: Adversarial attack, if attacker **does not use MCMC**. We report similarity of the reference and adversarial point before forward pass (blue) and after forward pass (orange).

(a) No defence (b) MCMC defence

Figure 8: Adversarial attack, if attacker **uses MCMC**. We report similarity of the reference and adversarial point before forward pass (blue) and after forward pass (orange).

Figure 9: Examples of adversarial point and their reconstructions, when attacker does not use MCMC (left) and when attacker uses MCMC(right).

B.3 Which attack radius should be considered?

In out experiments, we use attacks with the radius 0.1 and 0.2 for all the models except for CelebA dataset, where radii 0.05 and 0.1 were considered. Here, we provide additional experiment to justify this choice. In Figure 10 (a) we show the similarity between the reference point and the adversarial point. We observe that for CelebA the similarity drops faster than for the MNIST. Further, if we look at the example plotted in Figure 11, we can clearly notice that with the radius 0.2 CelebA image is already containing a lot of noise. At the same time, we observe (Figure 10 (b)) that reconstruction similarity, which indicates the success of the attack, drops relatively fast when the radius of the attack increases.

(a) Reference and adversarial point similarity (b) Reconstruction similarity

Figure 10: Average images similarity (a) before it is passed to VAE and (b) after image is encoded and decoded back. We consider unsupervised attack on the encoder with the radiuses ranging from 0.01 to 0.5 for MNIST and CelebA datasets.

Figure 11

B.4 How many HMC steps are required for a defence?

One of the main hyperparameters of the proposed approach is number of steps of MCMC that the
defender does. We have conducted experiments with MNIST and Color MNSIT dataset to see how
the robustness metrics change when we increase number of HMC steps from 0 to 200. As we can
see from the Figure 12, there is always a considerable jump between 0 steps (no defence) and 100
steps (lowest number of steps considered). However, as we continue making steps, we do not observe
further improvement of the metrics.

(a) Reconstruction similarity. (b) Adversarial Accuracy (digit classification task).

Figure 12: Example of the reference point (leftmost column) and adversarial points for different
raduises of the attack.

B.5   Comparison of objective functions

This section compares different objective functions that can be used to construct adversarial attacks on VAE. In general, in both supervised and unsupervised setting, we need to measure the difference between variational posterior in the adversarial point $q(\mathbf{z}|\mathbf{x}^a)$ and a point from the dataset (either a target or reference point). We consider a Gaussian encoder, and the simplest way to compare two Gaussian distributions is to measure the distance between their means. To take into account the variances, we can use the KL-divergence. It is a non-symmetric metric. Thus, we have two options: to use the forward or reverse KL. Finally, it is also possible to consider the symmetrical KL divergence that is an average between the two.

(a) Reconstructions similarity: adversarial point and the reference.

(b) Adversarial Accuracy.

Figure 13: Comparison of different objectives function used to train an attack. Arrows represent the direction of the successful attack.

In Figure 13, we measure how successful the attacks are in terms of the proposed metrics. We use arrows in the plot titles to indicate desirable values of the metric for a successful attack. We compare supervised and unsupervised attacks on VAE trained on MNIST and fashion MNIST datasets. We observe that there is no single objective function that consistently outperforms others.

C Details of the experiments

C.1 Training VAE models

Architecture We use the same fully convolutional architecture with latent dimension 64 for MNIST, FashionMNISt and ColorMNIST datasets. In Table 5, we provide detailed scheme of the architecture. We use `Conv(3x3, 1->32)` to denote convolution with kernel size 3x3, 1 input channel and 32 output channels. We denote stride of the convolution with `s`, padding with `p` and dilation with `d`. The same notation applied for the transposed convolutions (`ConvTranspose`). ColorMNIST has 3 input channels, so the first convolutional layer in the encoder and the last of the decoder are slightly different. In this cases values for ColorMNIST are report in parenthesis with the red color.

Table 5: Convolutional architecture for VAE trained on MNIST, Fashion MNIST and ColorMNIST datasets.

Encoder	Decoder
`Conv(3x3, 1(3)->32, s=2, p=1)`	`ConvTranspose(3x3,64->128,s=1,p=0, d=2)`
`ReLU()`	`ReLU()`
`Conv(3x3, 32->64, s=2, p=1)`	`ConvTranspose(3x3,128->96,s=1,p=0)`
`ReLU()`	`ReLU()`
`Conv(3x3, 64->96, s=2, p=1)`	`ConvTranspose(3x3,96->64,s=1,p=1)`
`ReLU()`	`ReLU()`
`Conv(3x3,96->128,s=2,p=1)`	`ConvTranspose(4x4,64->32,s=2,p=1)`
`ReLU()`	`ReLU()`
$\mu_z \leftarrow$ `Conv(3x3,128->64,s=2,p=1)`	`ConvTranspose(4x4,31->1(3),s=2,p=1)`
$\log \sigma_z^2 \leftarrow$ `Conv(3x3,128->64,s=2,p=1)`	$\mu_x \leftarrow$ `Sigmoid() (Identity())`

Optimization We use Adam to perform the optimization. We start from the learning rate $5e-4$ and reduce it by the factor of 2 if the validation loss does not decrease for 10 epochs. We train a model for 300 epochs with the batch size 128. In Table 6, we report the values of the test metrics for VAEs trained on MNIST, Fashion MNIST and Color MNIST.

For calculating the FID score, we use `torchmetrics` library: `https://torchmetrics.readthedocs.io/en/latest/references/modules.html#frechetinceptiondistance`.

Table 6: Test performance of the β-VAE and β-TCVAE with different values of β. Negative loglikelihood is estimated with importance sampling ($k = 1000$) as suggested in [7].

	β	MNIST $-\log p(\mathbf{x})$	MSE	FASHION MNIST $-\log p(\mathbf{x})$	MSE	COLOR MNIST $-\log p(\mathbf{x})$	MSE	FID
	1	**88.3**	578.6	**232.8**	814.3	**54.87**	261.3	2.09
β-VAE	2	89.3	824.2	234.1	1021.1	55.6	365.6	2.4
	5	100.6	1485.1	241.8	1457.8	63.6	586.1	2.5
	10	126.8	2498.9	248.7	1842.3	88.7	936.2	2.4
β-TCVAE	2	89.3	828.4	233.6	980.4	55.8	366.4	3.0
	5	96.7	1325.4	238.2	1024.6	63.0	574.8	2.0
	10	107.2	1686.1	247.5	1570.0	76.5	806.2	2.2

C.2 Adversarial Attacks and Defence Hyperparameters

In Table 7, we report all the hyperparameter values that were used to attack and defend VAE models.

In all the experiments we randomly select reference points from the test dataset. We also ensure that the resulting samples are properly stratified — include an even number of points from each of the classes. For each reference point, we train 10 adversarial inputs with the same objective function but different initialization.

We use projected gradient descent to learn the adversarial attacks. Optimization parameters were the same for all the datasets and models. They are presented in Table 7.

We choose HMC to defend the model against the trained attack. We perform T steps of HMC with the step size η and L leapfrog steps. Where indicated, we adapt the step size after each step of HMC using the following formula:

$$\eta_t = \eta_{t-1} + 0.01 \cdot \frac{\alpha_{t-1} - 0.9}{0.9} \cdot \eta_{t-1}, \tag{55}$$

where α_t is the acceptance rate at step t. This way we increase the step size if the acceptance rate is higher than 90% and decrease it otherwise. When adaptive steps size is used, a value in the table indicates the η_0.

Table 7: Full list of hyperparameters for attack construction and the defence.

| | | VAE | | | NVAE | |
		MNIST	Fashion MNIST	Color MNIST	MNIST	CelebA
	# of reference points	50	50	50	50	20
	# of adversarial points	500	500	500	500	200
	Radius norm ($\|\cdot\|_p$)	inf	inf	inf	inf	inf
	Radius	$\{0.1, 0.2\}$	$\{0.1, 0.2\}$	$\{0.1, 0.2\}$	$\{0.1, 0.2\}$	$\{0.05, 0.1\}$
Optimization (PGD)	Optimizer			SGD		
	Num. steps			50		
	ε initialization			$\mathcal{N}(0, 0.2 \cdot I)$		
	Learning rate (lr)			1		
Defence (HMC)	Num. steps (T)	500	1000	1000	2000	1000
	Step size η	0.1	0.05	0.05	1e-4	1e-4
	Num. Leapfrog steps (L)	20	20	20	20	1
	Adaptive step size	True	True	True	True	False