Symplectic Adjoint Method for Exact Gradient of Neural ODE with Minimal Memory

Abstract

A neural network model of a differential equation, namely, neural ODE, has enabled the learning of continuous-time dynamical systems and probabilistic distributions with high accuracy. The neural ODE uses the same network repeatedly during numerical integration. The memory consumption of the backpropagation algorithm is proportional to the number of uses *times* the network size. This is true even if a checkpointing scheme divides the computational graph into sub-graphs. Otherwise, the adjoint method obtains a gradient by a numerical integration backward in time. Although this method consumes memory only for a single network use, it requires high computational cost to suppress numerical errors. This study proposes the symplectic adjoint method, which is an adjoint method solved by a symplectic integrator. The symplectic adjoint method obtains the exact gradient (up to rounding error) with memory proportional to the number of uses *plus* the network size. The experimental results demonstrate that the symplectic adjoint method consumes much less memory than the naive backpropagation algorithm and checkpointing schemes, performs faster than the adjoint method, and is robust to rounding errors.

1 Introduction

Deep neural networks offer remarkable methods for various tasks, such as image recognition [18] and natural language processing [4]. These methods employ a residual architecture [19, 30], where the output x_{n+1} of the n-th operation is defined as the sum of a subroutine f_n and the input x_n as $x_{n+1} = f_n(x_n) + x_n$. The residual architecture can be regarded as a numerical integration applied to an ordinary differential equation (ODE) [26]. Accordingly, a neural network model of the differential equation $\mathrm{d}x/\mathrm{d}t = f(x)$, namely, neural ODE, was proposed in [2]. Given an input as an initial condition $x(0) = x_0$, the neural ODE solves an initial value problem by numerical integration, obtaining an output $y = x(T)$. The neural ODE can model a continuous-time dynamics, irregularly sampled time series [22], stable dynamical systems [32, 37], and physical phenomena associated with geometric structures [3, 13, 27]. Further, because the neural ODE approximates a diffeomorphism [38], it can model probabilistic distributions of real-world data by a change of variables [12, 21, 23, 40].

For an accurate integration, the neural ODE must employ a small step size and a high-order numerical integrator composed of many internal stages. A neural network f is used at each stage of each time step. Thus, the backpropagation algorithm consumes exorbitant memory to retain the whole computational graph [34, 2, 10, 41]. The neural ODE employs the adjoint method to reduce memory consumption [8, 17, 36, 39]—this method obtains the gradient by backward integration along with the state x, without consuming memory for retaining the computational graph over time. However, this method incurs high computational costs to suppress numerical errors. Several previous works employed a checkpointing scheme [10, 41, 42]. This scheme retains only the state x sparsely as

Table 1: Comparison of the proposed method with existing methods

Methods	Gradient Calculation	Exact	Checkpoints	Memory Consumption		Computational Cost
				checkpoint	backprop.	
NODE [2]	adjoint method	no	x_N	M	L	$(N+2\tilde{N})sLM$
NODE [2]	backpropagation	yes	—	—	$NsLM$	$2NsLM$
ANODE [10]	backpropagation	yes	x_0	M	NsL	$3NsLM$
ACA [41]	backpropagation	yes	$\{x_n\}_{n=0}^{N-1}$	MN	sL	$3NsLM$
MALI [42]*	backpropagation	yes	x_N	M	sL	$4NsLM$
proposed**	symplectic adjoint method	yes	$\{x_n\}_{n=0}^{N-1}, \{X_{n,i}\}_{i=1}^s$	$MN+s$	L	$4NsLM$

*Available only for the asynchronous leapfrog integrator. **Available for any Runge–Kutta methods.

checkpoints and recalculates a computational graph from each checkpoint to obtain the gradient. However, this scheme still consumes significant memory to retain the computational graph between checkpoints.

To address the above limitations, this study proposes the *symplectic adjoint method*. The main advantages of the proposed method are presented as follows.

Exact Gradient and Fast Computation: The adjoint method relies on a quadratic invariant of a partitioned system. A numerical integrator cannot preserve such quantity in general, thereby suffering from numerical errors. The proposed method employs a specially designed integrator, which preserves a quadratic invariant in discrete time, thereby obtaining the exact gradient. The proposed method works with the step size used for forward integration and is thus faster than the adjoint method in practice.

Minimal Memory Consumption: Existing methods (except the adjoint method) apply the backpropagation algorithm to the computational graph of the whole or a subset of numerical integration [10, 41, 42]. Thus, the memory consumption is proportional to the number of steps/stages in the graph *times* network size. Conversely, the proposed method applies the algorithm only to each use of the neural network. The memory consumption is only proportional to the number of steps/stages *plus* network size.

Robust to Rounding Error: The backpropagation algorithm accumulates the gradient from each use of the neural network and tends to suffer from rounding errors [41]. Conversely, the proposed method obtains the gradient from each step as a numerical integration, and is thus more robust to rounding errors.

2 Background and Related Work

2.1 Neural Ordinary Differential Equation and Adjoint Method

We use the following notion.

M: the number of stacked neural ODE components,
L: the number of layers in a neural network,
$N, \tilde{N}$: the number of time steps in the forward and backward integrations, respectively, and
s: the number of uses of a neural network f per step.

s is typically equal to the number of internal stages of the numerical integrator [17]. A numerical integration forward in time requires a computational cost of $O(NsLM)$. It also provides a computational graph over time steps, which is retained with a memory of $O(NsLM)$; the backpropagation algorithm is then applied to obtain the gradient. The total computational cost is $O(2NsLM)$, where we suppose the computational cost of the backpropagation algorithm is equal to that of forward propagation. The memory consumption and computational cost are summarized in Table 1.

To reduce the memory consumption, the original study on neural ODE introduced the adjoint method [2, 8, 17, 36, 39]. This method integrates the pair of the system state x and the adjoint variable λ backward in time. The adjoint variable λ represents the gradient $\frac{\partial \mathcal{L}}{\partial x}$ of some function $\mathcal{L}$, and the backward integration of the adjoint variable λ works as the backpropagation (or more generally the reverse-mode automatic differentiation) in continuous time. The memory consumption

is $O(M)$ to retain the final conditions $x(T)$ of M neural ODE components and $O(L)$ to obtain the gradient of a neural network f used for integrating the adjoint variable λ. The computational cost is at least doubled because of the re-integration of the system state x backward in time. The adjoint method only holds in continuous time [10, 36]. Because of numerical errors, the backward integration of the state is not consistent with the forward integration, and the adjoint variable is not equal to the exact gradient. Moreover, the adjoint variable has the same size as the model parameter, and is thus more likely to suffer from numerical errors. To suppress numerical errors, backward integration often requires a smaller step size than the forward integration (i.e., $\tilde{N} > N$), leading to an increase in computation time. Conversely, the proposed symplectic adjoint method uses a specially designed integrator, which provides the exact gradient with the same step size as the forward integration.

2.2 Checkpointing Scheme

The checkpointing scheme has been investigated to reduce the memory consumption of neural networks [14, 15], where intermediate states are retained sparsely as checkpoints, and a computational graph is recomputed from each checkpoint. For example, Gruslys *et al.* applied this scheme to recurrent neural networks [15]. The ANODE scheme retains the initial value $x(0)$ of each neural ODE component and solves the initial value problem again before applying the backpropagation algorithm [10]. The memory consumption is $O(M)$ to retain the initial conditions of M components and $O(NsL)$ to obtain the gradient of each component; ANODE does not reduce the memory consumption when $M = 1$. The ACA scheme retains all steps $\{x_n\}_{n=0}^{N-1}$ at most as checkpoints with a memory of $O(MN)$ [41]. Form each checkpoint x_n, this scheme recalculates the next step x_{n+1} and obtains the gradient using the backpropagation algorithm with a memory of $O(sL)$. Even with checkpoints, the memory consumption is still proportional to the number of uses s of a neural network f per step, which is not negligible for a high-order integrator, e.g., $s = 6$ for the Dormand–Prince method. In this context, the proposed method is regarded as a checkpointing scheme inside of a numerical integrator.

Instead of a checkpointing scheme, MALI employs an asynchronous leapfrog (ALF) integrator after the state x is paired up with the velocity state v [42]. The ALF integrator is time-reversible, i.e., the backward integration obtains the state x equal to that in the forward integration without checkpoints [17]. However, the ALF integrator is a second-order integrator, implying that it requires a small step size and a high computational cost to suppress numerical errors. Higher-order explicit Runge–Kutta methods are unavailable because they are not time-reversible. The ALF integrator is inapplicable to physical systems without velocity (such as partial differential equation (PDE) systems). Nonetheless, a similar approach named RevNet was proposed in [11]. When regarding ResNet as a forward Euler method [2, 18], RevNet has an architecture regarded as the leapfrog integrator and can recalculate the intermediate activations in the reverse direction.

3 Adjoint Method

Consider a system

$$\frac{\mathrm{d}}{\mathrm{d}t}x = f(x, t, \theta), \tag{1}$$

where x, t, and θ, respectively, denote the system state, an independent variable (e.g., time), and parameters of the function f. Given an initial condition $x(0) = x_0$, the solution $x(t)$ is given by

$$x(t) = x_0 + \int_0^t f(x(\tau), \tau, \theta)\mathrm{d}\tau. \tag{2}$$

The solution $x(t)$ is evaluated at the terminal $t = T$ by a function $\mathcal{L}$ as $\mathcal{L}(x(T))$. Our main interest is in obtaining the gradients of $\mathcal{L}(x(T))$ with respect to the initial condition x_0 and the parameters θ.

Now, we introduce the adjoint method [2, 8, 17, 36, 39]. We first focus on the initial condition x_0 and omit the parameters θ. The adjoint method is based on the *variational variable* $\delta(t)$ and the *adjoint variable* $\lambda(t)$. They follow the variational system and adjoint system as

$$\frac{\mathrm{d}}{\mathrm{d}t}\delta(t) = \frac{\partial f}{\partial x}(x(t), t)\delta(t) \text{ for } \delta(0) = I, \quad \frac{\mathrm{d}}{\mathrm{d}t}\lambda(t) = -\frac{\partial f}{\partial x}(x, t)^\top \lambda(t) \text{ for } \lambda(T) = \lambda_T. \tag{3}$$

The variational variable $\delta(t)$ represents the Jacobian $\frac{\partial x(t)}{\partial x_0}$ of the state $x(t)$ with respect to the initial condition x_0; the detailed derivation is summarized in Appendix A.

Remark 1. *The quantity $\lambda^\top \delta$ is time-invariant, i.e., $\lambda(t)^\top \delta(t) = \lambda(0)^\top \delta(0)$.*

The proofs of most Remarks and Theorems in this paper are summarized in Appendix B.

Remark 2. $\lambda(t)$ *represents the gradient* $(\frac{\partial \mathcal{L}(x(T))}{\partial x(t)})^\top$ *if the final condition λ_T of the adjoint variable λ is set to* $(\frac{\partial \mathcal{L}(x(T))}{\partial x(T)})^\top$.

This is because of the chain rule. Thus, the backward integration of the adjoint variable $\lambda(t)$ works as reverse-mode automatic differentiation. One can then optimize the initial condition x_0 by a gradient-based method. In this way, the adjoint method has been used for data assimilation [8, 17, 36, 39]. For system identification (i.e., parameter adjustment), one can consider the parameters θ as a part of the augmented state $\tilde{x} = [x \ \theta]^\top$ of the system

$$\frac{\mathrm{d}}{\mathrm{d}t}\tilde{x} = \tilde{f}(\tilde{x}, t), \ \tilde{f}(\tilde{x}, t) = \begin{bmatrix} f(x, t, \theta) \\ 0 \end{bmatrix}, \ \tilde{x}(0) = \begin{bmatrix} x_0 \\ \theta \end{bmatrix}. \tag{4}$$

The variational and adjoint variables are augmented in the same way. Hereafter, we let x denote the state or augmented state without loss of generality. See Appendix C for more details.

According to the original implementation of the neural ODE [2], the final condition $x(T)$ of the system state x is retained after forward integration, and the pair of the system state x and the adjoint variable λ is integrated backward in time to obtain the gradients. The right-hand sides of the main system in Eq. (1) and the adjoint system in Eq. (3) are obtained by the forward and backward propagations of the neural network f, respectively. Therefore, the computational cost of the adjoint method is twice that of the ordinary backpropagation algorithm.

After a numerical integrator discretizes the time, Remark 1 does not hold, and thus the adjoint variable $\lambda(t)$ is not equal to the exact gradient [10, 36]. Moreover, the numerical integration backward in time is not consistent with that forward in time. Although a small step size (i.e., a small tolerance) suppresses numerical errors, it leads to a longer computation time and rounding errors. This fact motivates the present study to obtain the exact gradient with a small memory.

4 Symplectic Adjoint Method

4.1 Runge–Kutta Method

We first discretize the main system in Eq. (1). Let t_n, h_n, and x_n denote the n-th time step, step size, and state, respectively, where $h_n = t_{n+1} - t_n$. Most previous studies employed one of the Runge–Kutta methods, generally expressed as

$$\begin{aligned} x_{n+1} &= x_n + h_n \sum_{i=1}^{s} b_i k_{n,i}, \\ k_{n,i} &:= f(X_{n,i}, t_n + c_i h_n), \\ X_{n,i} &:= x_n + h_n \sum_{j=1}^{s} a_{i,j} k_{n,j}. \end{aligned} \tag{5}$$

The coefficients $a_{i,j}$, b_i, and c_i are often summarized as the Butcher tableau [16, 17, 36]. If $a_{i,j} = 0$ for $j \geq i$, the intermediate state $X_{n,i}$ is calculable from $i = 1$ to $i = s$ sequentially; then, the Runge–Kutta method is considered explicit. Runge–Kutta methods are not time-reversible, i.e., the numerical integration backward in time is not consistent with that forward in time.

Remark 3 (Bochev and Scovel [1], Hairer et al. [16])**.** *When the system in Eq.* (1) *is solved by the Runge–Kutta method in Eq.* (5)*, the variational system in Eq.* (3) *is automatically solved by the same Runge–Kutta method.*

Therefore, the variational variable $\delta(t)$ is not necessarily solved separately.

4.2 Symplectic Runge–Kutta Method for Adjoint System

We assume $b_i \neq 0$ for $i = 1, \ldots, s$. We suppose the adjoint system to be solved by another Runge–Kutta method with a step size that is the same as the system state x, expressed as

$$\begin{aligned} \lambda_{n+1} &= \lambda_n + h_n \sum_{i=1}^{s} B_i l_{n,i}, \\ l_{n,i} &:= -\frac{\partial f}{\partial x}(X_{n,i}, t_n + C_i h_n)^\top \Lambda_{n,i}, \\ \Lambda_{n,i} &:= \lambda_n + h_n \sum_{j=1}^{s} A_{i,j} l_{n,j}. \end{aligned} \tag{6}$$

The final condition λ_N is set to $\frac{\partial \mathcal{L}(x_N)}{\partial x_N}$. Because the time evolutions of the variational variable δ and the adjoint variable λ are expressible by two equations, the combined system is considered as a partitioned system. A combination of two Runge–Kutta methods for solving a partitioned system is called a partitioned Runge–Kutta method, where $C_i = c_i$ for $i = 1, \ldots, s$. We introduce the following condition for a partitioned Runge–Kutta method.

Condition 1. $b_i A_{i,j} + B_j a_{j,i} - b_i B_j = 0$ *for* $i, j = 1, \ldots, s$, *and* $B_i = b_i \neq 0$ *and* $C_i = c_i$ *for* $i = 1, \ldots, s$.

Theorem 1 (Sanz-Serna [36])**.** *The partitioned Runge–Kutta method in Eqs.* (5) *and* (6) *conserves a bilinear quantity* $S(\delta, \lambda)$, *if the continuous-time system conserves the quantity* $S(\delta, \lambda)$ *and Condition 1 holds.*

Because the bilinear quantity is conserved, the adjoint system solved by the Runge–Kutta method in Eq. (6) under Condition 1 provides the exact gradient as the adjoint variable $\lambda_n = (\frac{\partial \mathcal{L}(x_N)}{\partial x_n})^\top$. The Dormand–Prince method, one of the most popular Runge–Kutta methods, has $b_2 = 0$ [7]. For such methods, the Runge–Kutta method under Condition 1 in Eq. (6) is generalized as

$$
\begin{aligned}
\lambda_{n+1} &= \lambda_n + h_n \sum_{i=1}^s \tilde{b}_i l_{n,i}, \\
l_{n,i} &:= -\frac{\partial f}{\partial x}(X_{n,i}, t_n + c_i h_n)^\top \Lambda_{n,i}, \\
\Lambda_{n,i} &:= \begin{cases} \lambda_n + h_n \sum_{j=1}^s \tilde{b}_j \left(1 - \frac{a_{j,i}}{b_i}\right) l_{n,j} & \text{if } i \notin I_0 \\ -\sum_{j=1}^s \tilde{b}_j a_{j,i} l_{n,j} & \text{if } i \in I_0, \end{cases}
\end{aligned}
\tag{7}
$$

where

$$
\tilde{b}_i = \begin{cases} b_i & \text{if } i \notin I_0 \\ h_n & \text{if } i \in I_0, \end{cases}, \quad I_0 = \{i | i = 1, \ldots, s, \; b_i = 0\}.
\tag{8}
$$

Note that this numerical integrator is no longer a Runge–Kutta method and is equivalent to the fancy integrator proposed in [36].

Theorem 2. *The combination of the integrators in Eqs.* (5) *and* (7) *conserves a bilinear quantity* $S(\delta, \lambda)$, *if the continuous-time system conserves the quantity* $S(\delta, \lambda)$.

Remark 4. *The Runge–Kutta method in Eq.* (6) *under Condition 1 and the numerical integrator in Eq.* (7) *are explicit backward in time, if the Runge–Kutta method in Eq.* (5) *is explicit forward in time.*

A partitioned Runge–Kutta method that satisfies Condition 1 is symplectic and conserves the symplectic structure of a Hamiltonian system [16, 17]. While the symplecticity is sufficient but not necessary for obtaining the exact gradient, we named this method the *symplectic adjoint method*. The integrators in Eq. (6) and (7) are available only when the main system is solved by one of the Runge–Kutta methods in Eq. (5). If not, one has to design the integrator for the adjoint system so that the pair of integrators is symplectic. For when the main system is solved by a partitioned Runge–Kutta method, see [28].

4.3 Proposed Implementation of Symplectic Adjoint Method

The discrete-time adjoint system in Eqs. (6) and (7) depends on the intermediate system state $X_{n,i}$ and the vector-Jacobian product (VJP) $\lambda^\top \frac{\partial f}{\partial x}$. To obtain $\lambda^\top \frac{\partial f}{\partial x}$, the computational graph from the input $X_{n,i}$ to the output $f(X_{n,i}, t_n + c_i h_n)$ is required. When the whole computational graph in the forward integration is retained, the memory consumption and computational cost are of the same orders as those for the naive backpropagation algorithm. To reduce the memory consumption, we propose the following strategy as summarized in Algorithms 1 and 2.

At the forward integration of a neural ODE component, the pairs of system states x_n and time points t_n at time steps $n = 0, \ldots, N - 1$ are retained with a memory of $O(N)$ as checkpoints, and all computational graphs are discarded, as shown in Algorithm 1. The backward integration is summarized in Algorithm 2. The below steps are repeated from $n = N - 1$ to $n = 0$. From the checkpoint x_n, the intermediate states $X_{n,i}$ for s stages are obtained following the Runge–Kutta method in Eq. (5) and retained as checkpoints with a memory of $O(s)$, while all computational graphs are discarded. Then, the adjoint system is integrated from $n + 1$ to n using Eq. (7). Because the computational graph of the neural network f in line 5 is discarded, the VJP $\lambda^\top \frac{\partial f}{\partial x}$ in line 11 is obtained by the recomputation and backpropagation of $f(X_{n,i}, \ldots)$ with a computational cost of $O(2L)$ and memory of $O(L)$. The total memory consumption is $O(MN + s) + O(L)$ for M neural ODE components.

Algorithm 1 Forward Integration

Input: x_0
Output: x_N ,$\{x_n\}_{n=0}^{N-1}$
 1: **for** $n = 0$ to $N - 1$ **do**
 2:     Retain x_n as a checkpoint
        According to Eq. (5)
 3:     **for** $i = 1$ to s **do**
 4:         Get $X_{n,i}$ using x_n and $k_{n,j}$ for $j < i$
 5:         Get $k_{n,i}$ using $X_{n,i}$
 6:     **end for**
 7:     Get x_{n+1} using x_n and $k_{n,i}$
 8: **end for**

Algorithm 2 Backward Integration

Input: x_N ,$\{x_n\}_{n=0}^{N-1}$
Output: λ_0
 1: **for** $n = N - 1$ to 0 **do**
 2:     Load checkpoint x_n
        According to Eq. (5)
 3:     **for** $i = 1$ to s **do**
 4:         Get $X_{n,i}$ using x_n and $k_{n,j}$ for $j < i$
 5:         Get $k_{n,i}$ using $X_{n,i}$.
 6:         Retain $X_{n,i}$ as a checkpoint
 7:     **end for**
        According to Eq. (7)
 8:     **for** $i = s$ to 1 **do**
 9:         Get $\Lambda_{n,i}$ using λ_{n+1} and $l_{n,j}$ for $j > i$
10:         Load checkpoint $X_{n,i}$
11:         Get $l_{n,i}$ using $\Lambda_{n,i}$ and $X_{n,i}$.
12:         Discard checkpoint $X_{n,i}$
13:     **end for**
14:     Get λ_n using λ_{n+1} and $l_{n,i}$
15:     Discard checkpoint x_n
16: **end for**

We emphasize that the memory consumption is proportional to the number of checkpoints $MN + s$ *plus* neural network size L, whereas that of existing methods is proportional to the number of integration steps/stages between two checkpoints (i.e., Ns for ANODE and s for ACA) *times* neural network size L, in addition to the memory for checkpoints (see Table 1). Due to the recalculation of a discarded computational graph f in line 11, the computational cost of the proposed strategy is $O(4NsLM)$, whereas that of the adjoint method [2] and ACA [41] is $O((N + 2\tilde{N})sLM)$ and $O(3NsLM)$, respectively. However, the increase in the computation time is much less than that expected theoretically, because of other bottlenecks (demonstrated later).

5 Experiments

We evaluated the performance of the proposed symplectic adjoint method and existing methods using PyTorch 1.7.1 [31]. We implemented the proposed symplectic adjoint method by extending the adjoint method implemented in the package torchdiffeq 0.1.1 [2]. We also re-implemented ANODE [10] and ACA [41] because the interfaces of their official implementations are incompatible with torchdiffeq. The source code is available at `https://github.com/******/symplectic-adjoint-method/`.

5.1 Continuous Normalizing Flow

Experimental Settings: We evaluated the proposed symplectic adjoint method on training continuous normalizing flows [2, 12]. A normalizing flow is a neural network that approximates a bijective map g and obtains the exact likelihood of a sample u by the change of variables $\log p(u) = \log p(z) + \log |\det \frac{\partial g(u)}{\partial u}|$, where $z = g(u)$ and $p(z)$ denote the corresponding latent variable and its prior, respectively [5, 6, 33]. A continuous normalizing flow is a normalizing flow whose map g is modeled by stacked neural ODE components, in particular, $u = x(0)$ and $z = x(T)$ for the case with $M = 1$ [2, 12]. The log-determinant of the Jacobian is obtained by a numerical integration together with the system state x as $\log |\det \frac{\partial g(u)}{\partial u}| = -\int_0^T \text{Tr}(\frac{\partial f}{\partial x}(x(t), t)) dt$. The trace operation Tr is approximated by the Hutchinson estimator [20]. We adopted the experimental settings of the continuous normalizing flow FFJORD[1] [12], unless stated otherwise.

We examined five real tabular datasets, namely, MiniBooNE, GAS, POWER, HEPMASS, and BSDS300 datasets [12, 29]. The network architectures were the same as those that achieved the best results in the original experiments; the number of neural ODE components M varied across datasets. We employed the Dormand–Prince integrator, which is a fifth-order Runge–Kutta method with adaptive time-stepping, composed of seven stages [7]. Note that the number of function evaluations per step is $s = 6$ because the last stage is reused as the first stage of the next step. We set the absolute and relative tolerances to atol $= 10^{-8}$ and rtol $= 10^{-6}$, respectively. The neural networks were trained using the Adam optimizer [24] with a learning rate of 10^{-3}. We used a batch-size of 1000

---
[1] `https://github.com/rtqichen/ffjord` (MIT License)

Table 2: Results obtained for continuous normalizing flows.

	MINIBOONE ($M = 1$)			GAS ($M = 5$)			POWER ($M = 5$)		
	NLL	mem.	time	NLL	mem.	time	NLL	mem.	time
adjoint method [2]	10.59±0.17	170	0.74	-10.53±0.25	24	4.82	-0.31±0.01	**8.1**	6.33
backpropagation [2]	10.54±0.18	4436	0.91	-9.53±0.42	4479	12.00	-0.24±0.05	1710.9	10.64
ANODE [10]	10.54±0.18	4457	1.10	-9.53±0.42	1858	5.48	-0.24±0.05	515.2	4.37
ACA [41]	10.57±0.30	306	0.77	-10.65±0.45	73	3.98	-0.31±0.02	29.5	5.08
proposed	10.49±0.11	**95**	0.84	-10.89±0.11	**20**	4.39	-0.31±0.02	9.2	5.73

	HEPMASS ($M = 10$)			BSDS300 ($M = 2$)			MNIST ($M = 6$)		
	NLL	mem.	time	NLL	mem.	time	NLL	mem.	time
adjoint method [2]	16.49±0.25	40	4.19	-152.04±0.09	577	11.70	0.918±0.011	1086	10.12
backpropagation [2]	17.03±0.22	5254	11.82	—	—	—	—	—	—
ANODE [10]	17.03±0.22	1102	4.40	—	—	—	—	—	—
ACA [41]	16.41±0.39	88	3.67	-151.27±0.47	757	6.97	0.919±0.003	4332	7.94
proposed	16.48±0.20	**35**	4.15	-151.17±0.15	**283**	8.07	0.917±0.002	**1079**	9.42

Negative log-likelihoods (NLL), memory consumption [MiB], and computation time per iteration [s/itr]. The differences in the memory consumption and computation time are significant (see Table A2 in Appendix for standard deviations).

for all datasets to put a mini-batch into a single NVIDIA GeForce RTX 2080Ti GPU with 11-GB of memory, while the original experiments employed a batch-size of 10 000 for the latter three datasets on multiple GPUs. When using multiple GPUs, bottlenecks such as transferring data across GPUs may affect the performance, and a fair comparison becomes difficult. Nonetheless, the naive backpropagation algorithm and ANODE consumed the entire memory for the BSDS300 dataset.

We also examined the MNIST dataset [25] using a single NVIDIA RTX A6000 GPU with 48-GB of memory. Following the original study, we employed the multi-scale architecture and set the tolerance to atol = rtol = 10^{-5}. We set the learning rate to 10^{-3}, and then reduced it to 10^{-4} at the 250th epoch. The original experiments employed a batch-size of 900; however, following the official code[1], we set the batch-size to 200. The naive backpropagation algorithm and ANODE consumed the entire memory.

Performance: The medians ± standard deviations of three runs are summarized in Table 2. In many cases, all methods obtained models of negative log-likelihoods (NLLs) with no significant difference because all but the adjoint method provide the exact gradients up to rounding error, and the adjoint method with a small tolerance provides a sufficiently accurate gradient. The naive backpropagation algorithm and ANODE obtained slightly worse results on the GAS, POWER, and HEPMASS datasets. Due to adaptive time-stepping, the numerical integrator sometimes makes the step size much smaller, and the backpropagation algorithm over time steps suffered from rounding errors, as pointed out by Zhuang *et al.* [41]. Conversely, the ACA and the proposed symplectic adjoint method applied the backpropagation algorithm separately to a subset of the integration, thereby becoming robust to rounding errors (see Appendix D.1 for details).

After the training procedure, we obtained the maximum memory consumption during additional training iterations (see mem. [MiB]), from which we subtracted the memory consumption before training (i.e., occupied by the model parameters, loaded data, etc.). The memory consumption still includes the optimizer's states and the intermediate results of the multiply–accumulate operation. The results agree roughly with the theoretical orders shown in Table 1 (see also Table A2 for standard deviations). The symplectic adjoint method consumed much smaller memory than the naive backpropagation algorithm and the checkpointing schemes. Owing to the optimized implementation, the symplectic adjoint method consumed smaller memory than the adjoint method in some cases (see Appendix D.2).

On the other hand, the computation time per iteration (time [s/itr]) at the end of the training procedure does not agree with the theoretical orders. First, the adjoint method was slower in many cases, especially for the BSDS300 and MNIST datasets. For obtaining the gradients, the adjoint

Table 3: Results obtained for GAS dataset with different Runge–Kutta methods.

	Order 2, $s=2$		Order 3, $s=3$		Order 5, $s=6$		Order 8, $s=12$	
	mem.	time	mem.	time	mem.	time	mem.	time
adjoint method [2]	**21**± 0	247.47± 7.52	**22**±0	18.32±0.88	24± 0	5.34±0.31	28± 0	9.77±0.81
backpropagation [2]	—	—	—	—	4433±255	11.85±1.10	—	—
ANODE [10]	—	—	—	—	1858±228	5.82±0.28	4108±576	22.76±3.70
ACA [41]	607±30	232.90±13.81	69±2	17.72±1.38	73± 0	4.15±0.21	138± 0	9.36±0.55
proposed	589±14	262.99± 5.19	43±2	18.59±0.75	**20**± 0	4.78±0.32	**21**± 0	11.41±0.23

Memory consumption [MiB], and computation time per iteration [s/itr].

method integrates the adjoint variable λ, which has the size equal to the sum of the sizes of the parameters θ and the system state s. Accurate backward integration requires a much smaller step size than the forward integration (i.e., $\tilde{N}$ much greater than N), leading to a longer computation time. Second, the naive backpropagation algorithm and ANODE were slower than that expected theoretically, in many cases. A method with high memory consumption may have to wait for a retained computational graph to be loaded or memory to be freed, leading to an additional bottleneck. The symplectic adjoint method is free from the above bottlenecks and performs faster in practice; it was faster than the adjoint method for all but the MiniBooNE dataset.

The symplectic adjoint method is superior (or at least competitive) to the adjoint method, naive backpropagation, and ANODE in terms of both memory consumption and computation time. Between the proposed symplectic adjoint method and ACA, a trade-off exists between memory consumption and computation time.

Robustness to Tolerance: The adjoint method provides gradients with numerical errors. To evaluate the robustness against tolerance, we employed the MiniBooNE dataset and varied the absolute tolerance atol while maintaining the relative tolerance as rtol $= 10^2\times$atol. During the training, we obtained the computation time per iteration, as summarized in the upper panel of Fig. 1. The computation time was shorten as the tolerance increased. After training, we obtained the NLLs with atol $= 10^{-8}$, as summarized in the bottom panel of Fig. 1. The adjoint method performed well only with atol $< 10^{-4}$. With atol $= 10^{-4}$, the numerical error in the backward integration was non-negligible, and the performance degraded. With atol $> 10^{-4}$, the adjoint method destabilized. The symplectic adjoint method performed well

Figure 1: Performance with different tolerances.

even with atol $= 10^{-4}$. Even with $10^{-4} <$ atol $< 10^{-2}$, it performed to a certain level, while the numerical error in the forward integration was non-negligible. Because of the exact gradient, the symplectic adjoint method is robust to a large tolerance compared with the adjoint method, and thus potentially works much faster with an appropriate tolerance.

Different Runge–Kutta Methods: The Runge–Kutta family includes various integrators characterized by the Butcher tableau [16, 17, 36], such as the Heun–Euler method (a.k.a. adaptive Heun), Bogacki-Shampine method (a.k.a. bosh3), fifth-order Dormand–Prince method (a.k.a. dopri5), and eighth-order Dormand–Prince method (a.k.a. dopri8). These methods have the orders of 2, 3, 5, and 8 using $s = 2, 3, 6$, and 12 function evaluations, respectively. We examined these methods using the GAS dataset, and the results are summarized in Table 3. The naive backpropagation algorithm and ANODE consumed the entire memory in some cases, as denoted by dashes. We omit the NLLs because the methods used the same tolerance and achieved the same NLLs.

The advantage of the symplectic adjoint method over ACA in terms of memory consumption is more significant with a higher-order method (i.e., more function evaluations s), as the theory suggests in Table 1. With the Heun–Euler method, all methods were extremely slow, and all but the adjoint method consumed larger memory. A method of a lower order has to set the step size extremely small

Table 4: Results obtained for continuous-time physical systems.

	KdV Equation			Cahn–Hilliard System		
	MSE $(\times 10^{-3})$	mem.	time	MSE $(\times 10^{-6})$	mem.	time
adjoint method [2]	1.61 ± 3.23	93.7 ± 0.0	276 ± 16	5.58 ± 1.67	93.7 ± 0.0	942 ± 24
backpropagation [2]	1.61 ± 3.40	693.9 ± 0.0	105 ± 4	4.68 ± 1.89	3047.1 ± 0.0	425 ± 13
ACA [41]	1.61 ± 3.40	647.8 ± 0.0	137 ± 5	5.82 ± 2.33	648.0 ± 0.0	484 ± 13
proposed	1.61 ± 4.00	$\mathbf{79.8} \pm 0.0$	162 ± 6	5.47 ± 1.46	$\mathbf{80.3} \pm 0.0$	568 ± 22

Mean-squared errors (MSEs) in long-term predictions, memory consumption [MiB], and computation time per iteration [ms/itr].

to satisfy the tolerance, thereby increasing the number of steps N, computation time, and the memory consumed by checkpoints. This result indicates the limitations of methods that depend on lower-order integrators, such as MALI [42]. With the eighth-order Dormand–Prince method, the adjoint method performs relatively faster. This is because the backward integration easily satisfies the tolerance with a higher-order method (i.e., $\tilde{N} \simeq N$). Nonetheless, in terms of computation time, the fifth-order Dormand–Prince method is the best choice, for which the symplectic adjoint method greatly reduces the memory consumption and performs faster than all but ACA.

5.2 Continuous-Time Dynamical System

Experimental Settings: We evaluated the symplectic adjoint method on learning continuous-time dynamical systems [13, 27, 35]. Many physical phenomena can be modeled using the gradient of system energy H as $dx/dt = G\nabla H(x)$, where G is a coefficient matrix that determines the behaviors of the energy [9]. We followed the experimental settings of HNN++, provided in [27][2]. A neural network composed of one convolution layer and two fully connected layers approximated the energy function H and learned the time series by interpolating two successive samples. The deterministic convolution algorithm was enabled (see Appendix D.3 for discussion). We employed two physical systems described by PDEs, namely, the Korteweg–De Vries (KdV) equation and the Cahn–Hilliard system. We used a batch-size of 100 to put a mini-batch into a single NVIDIA TITAN V GPU instead of the original batch-size of 200. Moreover, we used the eighth-order Dormand–Prince method [17], composed of 13 stages, to emphasize the efficiency of the proposed method. We omitted ANODE because of $M = 1$. We evaluated the performance using mean squared errors (MSEs) in the system energy for long-term predictions.

Performance: The medians $\pm$ standard deviations of 15 runs are summarized in Table 4. Due to the accumulated error in the numerical integration, the MSEs had large variances, but all methods obtained similar MSEs. The ACA consumed much more memory than the symplectic adjoint method because of the large number of stages; the symplectic adjoint method is more beneficial for physical simulations, which often require extremely higher-order methods. Due to the severe nonlinearity, the adjoint method had to employ a small step size, and thus performed slower than others (i.e., $\tilde{N} > N$).

6 Conclusion

We proposed the symplectic adjoint method, which solves the adjoint system by a symplectic integrator with appropriate checkpoints. The symplectic adjoint method only applies the backpropagation algorithm to each use of the neural network, and thus consumes much less memory than the backpropagation algorithm and the checkpointing schemes. Its memory consumption is competitive to that of the adjoint method because the memory consumed by checkpoints is negligible for a higher-order method. Because the symplectic adjoint method preserves a bilinear quantity, it provides the exact gradient with the same step size as that used for the forward integration. Therefore, it performs faster than the adjoint method, which requires a small step size to suppress numerical errors.

---

[2]`https://github.com/tksmatsubara/discrete-autograd` (MIT License)

References

[1] Bochev, P. B. and Scovel, C. (1994). On quadratic invariants and symplectic structure. *BIT Numerical Mathematics*, 34(3):337–345.

[2] Chen, T. Q., Rubanova, Y., Bettencourt, J., Duvenaud, D., Chen, R. T. Q., Rubanova, Y., Bettencourt, J., and Duvenaud, D. (2018). Neural Ordinary Differential Equations. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 1–19.

[3] Chen, Z., Zhang, J., Arjovsky, M., and Bottou, L. (2020). Symplectic Recurrent Neural Networks. In *International Conference on Learning Representations (ICLR)*, pages 1–23.

[4] Devlin, J., Chang, M.-W., Lee, K., and Toutanova, K. (2018). BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. *arXiv*, pages 1–15.

[5] Dinh, L., Krueger, D., and Bengio, Y. (2014). NICE: Non-linear Independent Components Estimation. In *Workshop on International Conference on Learning Representations*, volume 1, pages 1–13.

[6] Dinh, L., Sohl-Dickstein, J., and Bengio, S. (2017). Density estimation using Real NVP. In *International Conference on Learning Representations (ICLR)*, pages 1–32.

[7] Dormand, J. R. and Prince, P. J. (1986). A reconsideration of some embedded Runge-Kutta formulae. *Journal of Computational and Applied Mathematics*, 15(2):203–211.

[8] Errico, R. M. (1997). What Is an Adjoint Model? *Bulletin of the American Meteorological Society*, 78(11):2577–2591.

[9] Furihata, D. and Matsuo, T. (2010). *Discrete Variational Derivative Method: A Structure-Preserving Numerical Method for Partial Differential Equations*. Chapman and Hall/CRC.

[10] Gholami, A., Keutzer, K., and Biros, G. (2019). ANODE: Unconditionally accurate memory-efficient gradients for neural ODEs.

[11] Gomez, A. N., Ren, M., Urtasun, R., and Grosse, R. B. (2017). The Reversible Residual Network: Backpropagation Without Storing Activations. In *Advances in Neural Information Processing Systems (NIPS)*, pages 1–14.

[12] Grathwohl, W., Chen, R. T. Q., Bettencourt, J., Sutskever, I., and Duvenaud, D. (2018). FFJORD: Free-form Continuous Dynamics for Scalable Reversible Generative Models. In *International Conference on Learning Representations (ICLR)*, pages 1–13.

[13] Greydanus, S., Dzamba, M., and Yosinski, J. (2019). Hamiltonian Neural Networks. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 1–16.

[14] Griewank, A. and Walther, A. (2000). Algorithm 799: Revolve: An implementation of checkpointing for the reverse or adjoint mode of computational differentiation. *ACM Transactions on Mathematical Software*, 26(1):19–45.

[15] Gruslys, A., Munos, R., Danihelka, I., Lanctot, M., and Graves, A. (2016). Memory-efficient backpropagation through time. *Advances in Neural Information Processing Systems (NIPS)*, pages 4132–4140.

[16] Hairer, E., Lubich, C., and Wanner, G. (2006). *Geometric Numerical Integration: Structure-Preserving Algorithms for Ordinary Differential Equations*, volume 31 of *Springer Series in Computational Mathematics*. Springer-Verlag, Berlin/Heidelberg.

[17] Hairer, E., Nørsett, S. P., and Wanner, G. (1993). *Solving Ordinary Differential Equations I: Nonstiff Problems*, volume 8 of *Springer Series in Computational Mathematics*. Springer Berlin Heidelberg, Berlin, Heidelberg.

[18] He, K., Zhang, X., Ren, S., and Sun, J. (2016). Deep Residual Learning for Image Recognition. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 1–9.

[19] Hochreiter, S. and Schmidhuber, J. (1997). Long Short-Term Memory. *Neural Computation*, 9(8):1735–1780.

[20] Hutchinson, M. (1990). A stochastic estimator of the trace of the influence matrix for laplacian smoothing splines. *Communications in Statistics - Simulation and Computation*, 19(2):433–450.

[21] Jiang, C. M., Huang, J., Tagliasacchi, A., and Guibas, L. (2020). ShapeFlow: Learnable Deformations Among 3D Shapes. In *Advances in Neural Information Processing Systems (NeurIPS)*.

[22] Kidger, P., Morrill, J., Foster, J., and Lyons, T. (2020). Neural Controlled Differential Equations for Irregular Time Series. In *Advances in Neural Information Processing Systems (NeurIPS)*.

[23] Kim, H., Lee, H., Kang, W. H., Cheon, S. J., Choi, B. J., and Kim, N. S. (2020). WaveNODE: A Continuous Normalizing Flow for Speech Synthesis. In *ICML2020 Workshop on Invertible Neural Networks, Normalizing Flows, and Explicit Likelihood Models*, number Icml.

[24] Kingma, D. P. and Ba, J. (2015). Adam: A Method for Stochastic Optimization. In *International Conference on Learning Representations (ICLR)*, pages 1–15.

[25] LeCun, Y., Bottou, L., Bengio, Y., and Haffner, P. (1998). Gradient-based learning applied to document recognition. In *Proceedings of the IEEE*, volume 86, pages 2278–2323.

[26] Lu, Y., Zhong, A., Li, Q., and Dong, B. (2018). Beyond finite layer neural networks: Bridging deep architectures and numerical differential equations. In *International Conference on Machine Learning (ICML)*, volume 7, pages 5181–5190.

[27] Matsubara, T., Ishikawa, A., and Yaguchi, T. (2020). Deep Energy-Based Modeling of Discrete-Time Physics. In *Advances in Neural Information Processing Systems (NeurIPS)*.

[28] Matsuda, T. and Miyatake, Y. (2021). Generalization of partitioned Runge–Kutta methods for adjoint systems. *Journal of Computational and Applied Mathematics*, 388:113308.

[29] Papamakarios, G., Pavlakou, T., and Murray, I. (2017). Masked Autoregressive Flow for Density Estimation. In *Advances in Neural Information Processing Systems (NIPS)*, pages 1–17.

[30] Pascanu, R., Mikolov, T., and Bengio, Y. (2013). On the difficulty of training Recurrent Neural Networks. In *International Conference on Machine Learning (ICML)*, pages 2347–2355.

[31] Paszke, A., Chanan, G., Lin, Z., Gross, S., Yang, E., Antiga, L., and Devito, Z. (2017). Automatic differentiation in PyTorch. In *Autodiff Workshop on Advances in Neural Information Processing Systems*, pages 1–4.

[32] Rana, M. A., Li, A., Fox, D., Boots, B., Ramos, F., and Ratliff, N. (2020). Euclideanizing Flows: Diffeomorphic Reduction for Learning Stable Dynamical Systems. In *Conference on Learning for Dynamics and Control*, volume 120, pages 1–10.

[33] Rezende, D. J. and Mohamed, S. (2015). Variational Inference with Normalizing Flows. In *International Conference on Machine Learning (ICML)*, volume 37, pages 3–6.

[34] Rumelhart, D. E., Hinton, G. E., and Williams, R. J. (1986). Learning representations by back-propagating errors. *Nature*, 323(6088):533–536.

[35] Saemundsson, S., Terenin, A., Hofmann, K., Deisenroth, M. P., Sæmundsson, S., Hofmann, K., Terenin, A., and Deisenroth, M. P. (2020). Variational Integrator Networks for Physically Meaningful Embeddings. In *Artificial Intelligence and Statistics (AISTATS)*, volume 108, pages 1–11.

[36] Sanz-Serna, J. M. (2016). Symplectic Runge-Kutta schemes for adjoint equations, automatic differentiation, optimal control, and more. *SIAM Review*, 58(1):3–33.

[37] Takeishi, N. and Kawahara, Y. (2020). Learning dynamics models with stable invariant sets. In *AAAI Conference on Artificial Intelligence (AAAI)*.

[38] Teshima, T., Tojo, K., Ikeda, M., Ishikawa, I., and Oono, K. (2020). Universal Approximation Property of Neural Ordinary Differential Equations. In *NeurIPS Workshop on Differential Geometry meets Deep Learning (DiffGeo4DL)*.

[39] Wang, Q. (2013). Forward and adjoint sensitivity computation of chaotic dynamical systems. *Journal of Computational Physics*, 235:1–13.

[40] Yang, G., Huang, X., Hao, Z., Liu, M. Y., Belongie, S., and Hariharan, B. (2019). Pointflow: 3D point cloud generation with continuous normalizing flows. *International Conference on Computer Vision (ICCV)*, 2019-Octob:4540–4549.

[41] Zhuang, J., Dvornek, N., Li, X., Tatikonda, S., Papademetris, X., and Duncan, J. (2020). Adaptive Checkpoint Adjoint Method for Gradient Estimation in Neural ODE. In *International Conference on Machine Learning (ICML)*, number 1.

[42] Zhuang, J., Dvornek, N. C., Tatikonda, S., and Duncan, J. S. (2021). MALI: A memory efficient and reverse accurate integrator for Neural ODEs. In *International Conference on Learning Representations (ICLR)*, pages 1–22.