Linking Emergent and Natural Languages via Corpus Transfer

Abstract

The study of language emergence aims to understand how human languages are shaped by perceptual grounding and communicative intent. Computational approaches to emergent communication (EC) predominantly consider referential games in limited domains and analyze the learned protocol within the game framework. As a result, it remains unclear how the emergent languages[1] from these settings connect to natural languages or provide benefits in real-world language processing tasks, where statistical models trained on large text corpora dominate. In this work, we propose a novel way to establish such a link by *corpus transfer*, i.e. pretraining on a corpus of emergent language for downstream natural language tasks, which is in contrast to prior work that directly transfers speaker and listener parameters. Our approach showcases non-trivial transfer benefits for two different tasks – language modeling and image captioning. For example, in a low-resource setup (modeling 2 million natural language tokens), pre-training on an emergent language corpus with just 2 million tokens reduces model perplexity by 24.6% on average across ten natural languages. We also introduce a novel metric to predict the transferability of an emergent language by translating emergent messages to natural language captions grounded on the same images. We find that our translation-based metric highly correlates with the downstream performance on modeling natural languages (for instance $\rho = 0.83$ on Hebrew), while topographic similarity, a popular metric in previous works, shows surprisingly low correlation ($\rho = 0.003$), hinting that simple properties like attribute disentanglement from synthetic domains might not capture the full complexities of natural language. Our findings also indicate potential benefits of moving language emergence forward with natural language resources and models.

1 Introduction

The remarkable recent progress in NLP (Devlin et al., 2018; Radford et al., 2019; Brown et al., 2020) benefits from huge text corpora, on which large, powerful models learn rich statistical patterns *tabula rasa* and adapt to downstream tasks. But in stark contrast, human language acquisition (De Villiers et al., 1978) does not start with passive and complex corpora such as Wikipedia. Instead, children learn language through a cumulative series of interactions with other people (Bruner, 1985; Barton, 1994) grounded in the physical and social world (Harnad, 1990; Vogt, 2002; Alomari et al., 2017). Incorporating such cognitive insights with recent machine learning advances holds great promises towards more functional (Wittgenstein, 1958; Wagner et al., 2003) and generalizable (Lake et al., 2017) language agents.

The study of emergent communication (EC) (Cangelosi & Parisi, 2002; Kirby, 2002; Wagner et al., 2003; Lazaridou & Baroni, 2020) is one promising direction toward this motivation, where a communication protocol is shaped through multi-agent interactions with perceptual grounding. A typical setup is the image referential game (Figure 1(a)), where a speaker generates a discrete sequence of tokens based on an input image, a listener is challenged to select the input out of detractors based on the message, and both networks are optimized jointly via game success signals. By studying these games, researchers are interested in the emergence of desirable properties resembling natural

---

[1] In this work "emergent language" means generated messages from an EC game speaker. The term also refers to children's language development in psychology (Bohlmann & Downer, 2016; Zajicek-Farber, 2010).

Figure 1: Our framework. (a) We train a referential game on natural images, and **use the trained speaker to generate a corpus of emergent messages** (bold box) to pre-train for (b) language modeling and (c) image captioning. We also propose to (d) translate emergent language (yellow) into corresponding natural language (blue) with same perceptual grounding to evaluate their closeness.

language, such as game success generalization (Kharitonov & Baroni, 2020; Lazaridou & Baroni, 2020) and compositionality (Smith et al., 2003; Andreas & Klein, 2017; Kirby et al., 2015; Lazaridou et al., 2018; Li et al., 2020). However, these properties are mostly defined and analyzed within each individual game framework. For example, generalization is usually measured as game success with novel inputs, but it remains unknown how the emergent coding can be useful beyond the particular game (e.g. useful for natural language tasks). Moreover, compositionality is often approximated by attribute-wise disentanglement in simple environments, which could be drastically different from the structural properties of natural language (Dankers et al., 2021). Such gaps pose difficulty in objectively understanding the emergent properties with respect to the full complexities of natural language, and assessing the universality of various claims.

In this work, we aim to address these issues by linking emergent languages with natural languages. Concretely, we investigate if modeling an emergent language provides transferable benefits for downstream natural language tasks - language modeling (Figure 1(b)), image captioning (Figure 1(c)) - through **corpus transfer**, i.e. by pre-training a model on a corpus of emergent messages produced by a trained emergent speaker, and fine-tuning the model on downstream tasks with natural language data. This approach integrates inspirations from prior work like Papadimitriou & Jurafsky (2020), which proposes the transfer scheme from synthetic to natural corpora, and Li et al. (2020), which takes a preliminary step to connect EC to natural language tasks (few-shot translation) by transferring the trained speaker and listener model weights. Through a series of experiments, we find that corpus transfer is helpful when the downstream natural language resource is limited. For example, in a low-resource setup of modeling two million natural language tokens, such a transfer scheme reduces the test perplexity by 24.6% on average versus training from scratch, across ten different downstream languages. We also establish the non-triviality of such a transfer performance by comparing to other synthetic and natural source corpora, as well as multiple ablation studies on the EC and downstream transfer setups. Notably, our method of corpus transfer significantly outperforms directly transferring the trained emergent speaker model (Li et al., 2020), demonstrating that modeling the emergent language could yield greater usefulness than directly transferring the EC agents.

While our transfer experiments demonstrate that emergent languages can be leveraged and understood outside the game and towards real-world tasks, the pre-training and fine-tuning pipeline is computationally expensive as a scalable evaluation scheme for a population of emergent languages. Instead, we are interested in developing a simpler metric to predict the transferability of emergent language, which pertains to properties of natural language and may challenge metrics defined within the game framework (e.g. game accuracy). Therefore, we propose a novel metric for emergent languages based on how easily it can be translated to the corresponding natural language grounded on the same perceptual input (Figure 1(d)). Concretely, we employ the trained speaker to produce emergent messages based on a small set of unseen images with natural language captions, and train a translation model on paired emergent and natural captions. We show that the translation score (such as ROUGE_L (Lin, 2004)) can better predict (e.g. Pearson correlation $\rho = 0.83$ for modeling Hebrew)

the transfer benefits of different emergent languages than two commonly adopted metrics in prior literature – game success with novel inputs ($\rho = 0.74$), and topographic similarity (Brighton & Kirby, 2006; Lazaridou et al., 2018) ($\rho = 0.003$). These results call for a re-thinking of what properties we should evaluate for an emergent language corpus, and how we should evaluate them. For example, game accuracy may be confounded by the listener performance, and topographic similarity, a metric of attribute disentanglement, can be flawed for measuring the compositional structure of real language with stable irregularities (Kirby, 2001).

In summary, our work takes a step toward bridging the gap between emergent and natural languages. We believe that shifting from synthetic setups and in-game evaluations to leveraging downstream natural language tasks and state-of-the-art language models could potentially lead to more general insights and greater practical impact for EC and NLP research.

2 BACKGROUND

2.1 EMERGENT COMMUNICATION (EC) GAME

As shown in Figure 1(a), we consider a typical speaker-listener referential game (Lazaridou et al., 2016; 2018; Li & Bowling, 2019) on a set of N image features $\mathcal{D}_I = \{\mathbf{I}_1, \cdots, \mathbf{I}_N\}$. At each training step, the speaker takes an input image feature $\mathbf{I}_i$ and generates a discrete message $\mathbf{M}_i \in [V]^T$ using the Gumbel-Softmax trick (Jang et al., 2016), where V is the vocabulary size and T is the sequence length limit. For simplicity denote $\mathbf{m} = \mathbf{M}_i$ so that $m_t = M_{i,t}$ denotes the t-th token of the message $\mathbf{M}_i$. Then

$$\mathbf{hs}_0 = I_i, \quad \mathbf{hs}_t = \text{GRU}_{spk}(m_{t-1}, \mathbf{hs}_{t-1}) \ (t > 0),$$
$$m_0 = [\text{CLS}], \quad m_t = \text{Gumbel-Softmax}(\text{MLP}_{spk}(\mathbf{hs}_t)) \ (t > 0). \tag{1}$$

Here $\mathbf{hs}_t$ denotes speaker hidden states. Next, the listener takes the message $\mathbf{m}$, and tries to guess the right image $\mathbf{I}_i$ out of a set of K confounding images $C_i = \{\mathbf{I}_{j_1}, \cdots, \mathbf{I}_{j_K}\} \subset \mathcal{D}_I - \{\mathbf{I}_i\}$. To do so, it uses another GRU layer to decode the message $\mathbf{m}$ into a hidden vector $\mathbf{hl}_T$

$$\mathbf{hl}_0 = \mathbf{0}, \quad \mathbf{hl}_t = \text{GRU}_{lsn}(m_t, \mathbf{hl}_{t-1}) \ (t > 0). \tag{2}$$

Based on $\mathbf{hl}_T$, the listener assigns a score for each candidate image based on inverse square error (Lee et al., 2018), then selects the image by Softmax sampling across the scores. The speaker and listener are jointly optimized by minimizing the cross-entropy loss of image selection:

$$\text{score}(\mathbf{I}) = ||\mathbf{hl}_T - MLP_{lsn}(\mathbf{I})||_2^{-2}, \tag{3}$$
$$p(\text{guess} = \mathbf{I}) = \text{softmax}(\text{score}(\mathbf{I})) \quad (\mathbf{I} \in \{\mathbf{I}_i\} \cup C_i), \tag{4}$$
$$\mathcal{L}_{EC} = -\mathbb{E}_{\mathbf{I}_i, C_i} \mathbb{E}_{\mathbf{M}_i} \log p(\text{guess} = \mathbf{I}_i). \tag{5}$$

After the game is trained, the speaker can be employed to sample a corpus of emergent language $\mathcal{D}_M = \{\mathbf{M}_1, \cdots, \mathbf{M}_N\}$ based on input images.

2.2 EVALUATING EMERGENT LANGUAGE

A central question in emergent communication is how to evaluate the quality of the emergent corpus $\mathcal{D}_M$. Two commonly used metrics in prior work are game accuracy and topographic similarity.

Game Accuracy with Novel Objects The most straightforward metric is the accuracy of playing the referential game $p(\text{guess} = \mathbf{I}_i)$. Prior work (Cogswell et al., 2019; Li & Bowling, 2019) usually considers how well the speaker and listener generalize to novel inputs, and finds that such a generalization ability might not correlate with other properties such as compositionality (Chaabouni et al., 2020; Kharitonov & Baroni, 2020). Note that this metric involves both the speaker and listener, while the emergent language corpus $\mathcal{D}_M$ is generated solely by the speaker.

Topographic Similarity Given a set of objects (images), their meanings (input attributes) and the associated messages (emergent messages), the topographic similarity (Brighton & Kirby, 2006; Lazaridou et al., 2018) measures how messages align with the meaning representations. More concretely, let $CS_{ij} = -\mathbf{I}_i \cdot \mathbf{I}_j / (||\mathbf{I}_i||_2 ||\mathbf{I}_j||_2)$ be the negative cosine similarity of image features $\mathbf{I}_i$ and $\mathbf{I}_j$, and ED_{ij} be the Levenshtein distance (Levenshtein et al., 1966) between messages $\mathbf{M}_i$ and

$\mathbf{M}_j$. The topographic similarity of the emergent language is defined to be the Spearman rank-based correlation of the two distance metrics:

$$r_{ED,CS} = \rho_{R(ED),R(CS)} = \frac{\mathbb{E}_{i,j}\left[(R(ED_{ij}) - \mu_{R(ED)})(R(CS_{ij}) - \mu_{R(CS)})\right]}{\sigma_{R(ED)}\sigma_{R(CS)}} \tag{6}$$

Here $R(\cdot)$ denotes the rank of the element in the list. This metric measures the notion of *disentanglement*: different attributes of the input should be expressed in different token positions, and each token only describes one attribute, so that two objects with only a single different attribute (e.g. "big red cube" and "big blue cube") should also have an edit distance of one in their messages. Such a property has been claimed (Lazaridou et al., 2018; Li & Bowling, 2019) as connected to *compositionality*, a key structural property of natural language. However, this metric is too rigid in its definition of compositionality, ignoring aspects like argument structure, context or morphology which play a key role in determining the combination of word semantics (Goldberg, 2015).

We note that experiments around both these metrics are within the *game framework* – accuracy is based on *game success*, while topographic similarity measures how emergent messages align with *game input representations*. This leaves two questions unsolved: (i) can emergent languages be used outside the game? (ii) if so, would these metrics predict the usefulness of emergent languages for downstream tasks? We tackle these two questions in Sections 3 and 4 respectively.

3 EMERGENT CORPUS TRANSFER FOR NATURAL LANGUAGE TASKS

In this section, we present initial evidence that a *corpus* of emergent language $\mathcal{D}_M$ can benefit two types of downstream tasks involving natural language: language-only task (language modeling, Section 3.1) and vision-language task (image captioning, Section 3.2). Moreover, we show such a benefit is most significant when the natural language resources are limited, which indicates that emergent language is potentially valuable for low-resource languages and tasks. We then analyze what contributes to such a transfer via ablation studies in Section 3.3.

3.1 LANGUAGE MODELING

Inspired by Papadimitriou & Jurafsky (2020), we consider the task of natural language modeling, and explore if pretraining a language model on a corpus of emergent messages can reduce the downstream perplexity in a low-resource setup (Figure 1(b)), and how emergent language compares to other sources of synthetic and even natural language corpora.

Pre-training Corpora We compare three source corpora: (i) a Spanish Wikipedia corpus (**es**) culled to 50,000 vocabulary size using the pre-processing script from Papadimitriou & Jurafsky (2020), (ii) a regular language of well-balanced brackets (**paren-zipf**) with the Zipf unigram distribution as **es**, and (iii) an emergent language corpus (**ec**). **paren-zipf** is the best-performing source corpus from Papadimitriou & Jurafsky (2020) not created by humans (e.g. natural language, music, or code) with the inductive bias of *hierarchical structure*, and **es** should set a upper bound of the transfer performance for both **paren-zipf** and **ec**. We vary the source corpus size from 2, 5, 10, 15 to 30 million tokens to understand how the transfer results change with respect to the pre-training scale.

Fine-tuning Corpora We scrape Wikipedia corpora of 10 languages to test downstream transfer: Danish (**da**, IE-Germanic), Basque (**eu**, Basque), Japanese (**ja**, Japanese), Romanian (**ro**, IE-Romance), Finnish (**fi**, Uralic), Indonesian (**id**, Austronesian), Kazakh (**kk**, Turkic), Hebrew (**he**, Afro-Asiatic), Urdu (**ur**, IE-Indic), and Persian (**fa**, IE-Iranian). They come from diverse linguistic families with different levels of resource richness. Each corpus has 2 million tokens and a vocabulary size of 50,000, and is pre-processed (to remove noise) via the same script to process **es**.

Implementation We train the EC game and generate **ec** based on the Conceptual Captions dataset (Sharma et al., 2018), using more than 2.8 million natural images in the wild. Note that we do not use the natural language captions in the dataset for EC game training. We take the 512-dim pre-trained ResNet-18 (He et al., 2016) features before the classification head as input image features $\mathbf{I}_i$. Other architecture and training details mainly follow Li et al. (2020), and by default $V = 4035$,

Figure 2: Test perplexity for language modeling on ten natural languages, when either pre-trained on a corpus of tokens from EC (**ec**, blue), Spanish (**es**, orange), well-balanced brackets (**paren-zipf**, green) or without any pre-training (**scratch**, red).

$T = 15$, $K = 256$. For language modeling, we adopt a Transformer (Vaswani et al., 2017) with 6 decoder layers and 6 attention heads, and pre-train on each source corpus for 3,000 steps with batch size 32, input length 1,000, and learning rate 5×10^{-4}. For fine-tuning and training from scratch on downstream corpora, the batch size is 8 and learning rate is 10^{-4}. Hyperparameters are chosen after grid search. We report the test perplexity at the best validation loss.

Results   As can be seen from Figure 2, pre-training on **ec** significantly reduces the perplexity compared with training from scratch, with an average reduction of 24.6% with merely 2 million pre-training tokens. This is a positive signal that **a corpus of emergent language could be useful beyond the communication game itself**.

Comparing two synthetic pre-training corpora, **ec** perform better than or comparable to **paren-zipf** throughout different source sizes and downstream languages, with the exception of Basque and Finnish when pre-training size is more than 15 million. Given the strong inductive bias in **paren-zipf** (hierarchical structure and unigram information from real language), and the fact that **ec** is generated by just a single-layer GRU speaker without such explicit bias, such a result hints that **ec** may possess non-trivial structural properties due to the communication signals and perceptual grounding.

On the other hand, the natural language corpus **es** usually achieve a lower perplexity than both **ec** and **paren-zipf** as may be expected. Most surprisingly, when pre-training only on 2M tokens, **ec** consistently beats **es** in terms of transfer performance, and their performances are comparable on most languages using 5 million source tokens. To offer one plausible explanation, **ec** could contain properties closer to everyday conversations – smaller vocabulary, simpler structures (generated by one-layer GRU) and repetitive (all about image references) – easier for language modeling, compared to the complicated structures and statistical patterns of large text corpora like Wikipedia **es**. However, the relative simplicity of **ec** also prevents the transfer from scaling as well as **es** - comparing pretraining on 30 versus 2 million tokens, **ec** only reduces perplexity by 2.4% on average, while **es** reduces 23.8%. Such a mixed finding points to potential in combining the strengths of simpler emergent corpora (easier to acquire and benefit from) and noisy natural language corpora (more structures and complexities) for more efficient language learning. Another important direction would be on how to evolve emergent languages with more complexities and longer dependencies that resemble and transfer to natural language[2].

3.2   IMAGE CAPTIONING

The language modeling transfer experiment leverages the *structural* properties of the source corpus, but has little to do with the *semantics* of the source corpus. For example, a regular language like **paren-zipf** has no real meanings, but still reduces downstream perplexity due to its hierarchical structure. Therefore, we also consider transfer to image captioning, a classical vision-language task

---

[2]Just more powerful architectures would not help - we tried GRU speakers of two or three layers, but the transfer is worse.

Metrics	coco (5k)			coco (50k)			coco (full)		
	base	+ec	+nl	base	+ec	+nl	base	+ec	+nl
BLEU4	14.1	15.3	18.5	26.3	27.2	28.2	35.8	36.2	36.0
ROUGE_L	39.8	41.0	44.4	50.0	50.7	51.5	56.9	57.0	57.1
CIDEr	30.8	35.7	48.0	78.3	82.8	88.8	117.5	118.1	118.5

Table 1: Results on image captioning transfer using three fine-tuning dataset sizes. **base**, **+ec**, **+nl** denote training from scratch and pre-training using EC captions and NL captions, respectively.

where a model has to ground meaning of the words to the images. As shown in Figure 1(c), we pre-train an image captioning model on unlabeled images to generate EC captions, then fine-tune on downstream annotated images to generate natural language captions. We note that such a transfer scheme cannot work for other synthetic corpora such as music, code, or **paren-zipf** as they are not grounded on perceptual stimuli.

Pre-training Data We use the EC speaker trained on Conceptual Captions to generate an EC caption M_i based on each ResNet-18 image feature I_i in the dataset. As image captioning requires fine-grained information beyond a global feature, we extract detection features I'_i for each image via pre-trained Faster R-CNN (Ren et al., 2015) and ResNet-101 (He et al., 2016), and pre-train an image captioning model to generate EC captions based on detection features ($I'_i \mapsto M_i$). To set up an upper bound for transfer performance, we also use the English captions NL_i in the Conceptual Captions dataset for pre-training ($I'_i \mapsto NL_i$).

Fine-tuning Data We use the MS-COCO dataset (Lin et al., 2014) for fine-tuning, which consists of around 500,000 pairs of images and English captions. We use the full training set, or a subset with 5,000 or 50,000 samples to study the transfer benefit when natural language annotation is limited.

Implementation We use a Transformer with 3 encoder layers and 6 decoder layers as the image captioning model, and perform pre-training and fine-tuning in a seq2seq framework (Ott et al., 2019). Notably, we only transfer the encoder weights, and fine-tune the whole network end-to-end with a learning rate of 3×10^{-4}, as we notice transferring the full weights leads to worse performance. We report BLEU4 (Papineni et al., 2002), ROUGE_L (Lin, 2004), and CIDEr (Vedantam et al., 2015) scores for the test split based on best validation loss.

Results As shown in Table 1, when fine-tuning on 5,000 or 50,000 samples, pre-training on either EC or NL captions both significantly improve the image captioning performance. For example, with 50,000 samples, EC pre-training can improve the BLEU-4 score by +0.9 points, while NL pre-training further improves +1.0 points. The fact that EC pre-training can provide half the benefit of NL pre-training is surprising, because the former requires no language annotation - both training the EC games and generating the EC captions can be done on unlabeled images in the wild, while the NL pretraining leverages more than 2.8 million English sentences.

However, when the full MS-COCO dataset is used, even pretraining on 2.8 million English captions is not significantly helpful, possibly because Conceptual Captions collect noisy Internet sentences while MS-COCO annotates captions with less diversity (Wang et al., 2020) so a model trained from scratch on the full dataset can capture most of the output patterns. Other vision-language tasks where natural language annotations are harder or more limited (e.g. instruction following, navigation) would potentially benefit more from EC pre-training, where we can turn abundant unlabeled visual stimuli into annotations in the emergent language.

3.3 WHAT CONTRIBUTES TO SUCCESSFUL CORPUS TRANSFER?

We have shown that emergent languages can provide transfer benefit for natural language tasks, but it is still unknown what properties of emergent languages contribute to such a benefit. Hence we ablate several key aspects of the EC game training and EC corpus generation, and examine the effect via transfer to two example languages, Romanian (**ro**) and Hebrew (**he**). We fix the pre-training size to 15 million tokens and run all experiments for 3 trials.

Method	LM (ro)	LM (he)
EC pretrain	**195**	**357**
from scratch	266	435
random speaker	313 (21)	575 (24)
random input	245 (28)	489 (77)
permuted EC	211 (1)	383 (4)
GRU transfer	618 (8)	1106 (31)

Table 2: Ablations on EC game, corpus, and transfer setups. Standard deviation in parentheses.

Metrics	LM (ro)	LM (he)
Accuracy	0.672	0.737
Topographic	0.030	0.003
Translation	**0.757**	**0.829**

Table 3: Pearson correlations between different metrics (validation accuracy, topographic similarity, emergent to natural language translation ROUGE_L) and downstream language modeling performance (negated perplexity).

Communication and Perceptual Stimuli in EC Game The emergent language stems from two elements in the game that human language acquisition relies on: perceptual grounding (input image features) and communication (referential game). For ablation, we first consider an untrained GRU speaker with randomized parameters (**random speaker**), and use it to sample tokens conditioned on image features according to (1). As Table 2 shows, pre-training on such a corpus leads to even worse performance than training from scratch, because an untrained speaker has highly random generations with no clear structure.

On the other hand, to ablate the effect of visual stimuli, we sample a set of N random vectors from $\mathcal{N}(\mu(\mathcal{D}_I), \sigma(\mathcal{D}_I))$, and replace it for $\mathcal{D}_I$ as inputs of the EC game (**random input**). We then use the trained speaker to generate a EC corpus based on the same random vectors. It turns out only one out of three game trials develop a game accuracy $> 90\%$, and other two trials cannot learn an accuracy beyond 5%. On Hebrew, the "successful" trial achieves a transfer perplexity of 388, which is still worse than EC corpus on visual inputs, while other two trials yield significantly worse perplexities (573, 509). So it turns out communicating visual stimuli instead of random inputs is more robustly successful, and more helpful for transfer even when communication can be successful.

Sentence Structure in EC Corpus To investigate how structured EC sentences are, we independently shuffle each EC sentence in $\mathcal{D}_M$ to form a new-pretraining corpus (**permuted EC**), and find in Table 2 that it indeed leads to a worse performance, though better than training from scratch. This indicates the speaker develops a coding scheme with sentence structures beyond bag-of-words.

Model vs. Corpus Transfer Li et al. (2020) propose to transfer the speaker and listener models for a downstream translation task, whereas we leverage a speaker-generated EC corpus to pre-train models with more powerful architectures. As shown in Table 2, directly fine-tuning the one-layer speaker GRU (**GRU transfer**), a much smaller model than the Transformer we use for corpus transfer, indeed leads to much worse perplexities, demonstrating that our corpus transfer approach better utilizes the emergent communication.

4 EMERGENT-NATURAL LANGUAGE TRANSLATION AS A METRIC

Section 3.3 presents initial evidence that the quality of an emergent language correlates with the transfer performance, by showing ablated emergent languages transfer worse. However, directly using transfer as an evaluation scheme for emergent languages has certain deficiencies. First, the pre-training and fine-tuning optimizations are computationally expensive. Second, transfer performance across different downstream tasks might induce inconsistency. Hence we propose a cheaper and simpler evaluation for emergent languages by measuring how easily it translates to the corresponding natural language grounded on the same input, and show that it better correlates with the transfer performance than existing metrics across different tasks.

More concretely, we use a small set of captioned images, where image $\mathbf{I}_i$ is associated with a natural language caption $\mathbf{NL}_i$. We also use the trained speaker to generate emergent message $\mathbf{M}_i$ based on each $\mathbf{I}_i$, and train a translation model to map emergent sentences to natural sentences $\mathbf{M}_i \mapsto \mathbf{NL}_i$. Intuitively, a higher translation score means the emergent and natural sentences are closer in structure and semantics, similar to how French-English translation might be easier than Chinese-English.

Figure 3: Different metrics and downstream Romanian perplexities (negated) with respect to training steps, averaged over four trials with vocabulary limit 10000 and sequence length limit 15. Our metric better correlates with downstream performance across time steps.

Implementation   To estimate the correlation between metrics and transfer performance requires a population of emergent languages with different speakers. Thus we choose 5 EC game setups with varying vocabulary and sequence length limits ($(V, T) \in \{(4035, 5), (4035, 15), (4035, 25), (1000, 15), (10000, 25)\}$), and for each setup we run 4 trials for 2,000 steps. We consider checkpoints every 200 steps, summing to $5 \times 4 \times 10 = 200$ checkpoints. Due to computational limits, we train EC games on a small subset of 50,000 MS-COCO images, and use another subset of 50,000 MS-COCO image-caption pairs to calculate the translation metric. For translation, we use the same seq2seq Transformer for image captioning, but only train for 2 epochs, so that an emergent language more similar to the natural language can perform better with limited training. We use ROUGE_L[3] (Lin, 2004) as the translation metric. For downstream language modeling, we use ImageNet (Deng et al., 2009) to generate a corpus of 15 million tokens and fine-tune on Romanian (**ro**) and Hebrew (**he**).

Results   We compare with the two existing metrics, validation accuracy and topographic similarity (see Section 2.2). Table 3 shows how different metrics correlate with downstream performance across all checkpoints form all trials[4]. Surprisingly, we find little correlation between topographic similarity and downstream performance, while our translation metric has a better correlation ($\rho_{ro} = 0.757, \rho_{he} = 0.829$) than accuracy ($\rho_{ro} = 0.672, \rho_{he} = 0.737$).

To better understand the results, we take all 4 trials from a specific game setup ($V = 10000, T = 15$) and plot in Figure 3 how the three metrics (accuracy, topographic, translation ROUGE_L) as well as the downstream Romanian performance develop throughout training steps. We observe that our translation metric (Figure 3(c)) aligns with the downstream performance (Figure 3(d)) in that both reach a high level around 300 steps (red dash line) and maintains a similar level afterwards. The validation accuracy ((Figure 3(a))) has a generally similar tendency as these two metrics, with the difference being that it is only around 50% at step 300 and far from convergence, possibly due to the underdevelopment of the listener. A similar observation was made in Li et al. (2020). Such a dependency on the listener renders game success unreliable for the evaluating emergent languages produced by the speaker alone.

On the other hand, the topographic similarity (Figure 3(b)) peaks as early as step 300, after which the degradation fails to explain the downstream performance. To illustrate the misalignment, consider the "best" language with respect to topographic, i.e. a fully disentangled coding scheme (e.g. "red cube", "red sphere", "blue cube", "blue sphere"). Such a corpus would essentially have a maximum possible entropy, pre-training on which should not help with any downstream tasks. Such a finding suggests that **simple measurements of rigid disentanglement fall short of estimating the compositionality of real language**, and we may need to take into account other structural properties of natural language, e.g. stable irregularity (Kirby, 2001), or the role of argument structures, context and morphology (Goldberg, 2015).

---

[3]We find other metrics with similar performance.

[4]For topographic, we exclude 9 checkpoints with the metric undefined due to zero variance of message edit distances.

5   RELATED WORK

Emergent Communication and Evaluation   A large body of prior work qualitatively analyzes the evolved message structures when the EC games are set up with synthetic environments (Mordatch & Abbeel, 2018; Lazaridou et al., 2018) or even with real images (Havrylov & Titov, 2017). Alternative evaluations and examinations include ease of teaching (Li & Bowling, 2019) and symbol usage purity (Lazaridou et al., 2016). While these schemes align the emergent language with game success or different aspects of game input, our work evaluates the emergent language outside the game framework, instead via the corpus transfer performance to natural language tasks and the translation performance to natural language.

Use of Emergent Communication beyond games   There have been efforts to incorporate communication signals to improve on tasks like vision-language navigation (Fried et al., 2018), translation (Lee et al., 2018), and image captioning (Havrylov & Titov, 2017). Different from these setups where the speaker is also grounded on natural language annotations, Li et al. (2020) propose to separate the EC game, where no natural language is involved, and fine-tuning on a downstream translation task with limited natural language data. As discussed in Section 3.3, our work takes a step further and uses the output corpus of EC games to enable transfer to more tasks with better performance.

Linking Synthetic and Natural Language   Papadimitriou & Jurafsky (2020) find that recurrent networks pretrained on non-linguistic corpora (e.g. music, code, regular languages) facilitate natural language modeling. In an opposite direction, Lu et al. (2021) observe that language pre-training improves Transformer's performance with several non-language tasks (logical, vision, protein) even when most weights are frozen, indicating that learning language structure could yield generally useful computational subroutines. Andreas et al. (2017) propose to translate a differentiable communication channel in deep multi-agent policies to natural language by collecting human-human communication in the same games. However, their approach focused on *interpreting* a *continuous* channel, while we focus on *evaluating* emergent messages with *discrete* structures.

6   CONCLUSIONS

We present a new perspective for studying emergent communication by linking the corpora of emergent and natural languages in two ways. First, we leverage a corpus transfer scheme to study the transfer benefit of modeling an emergent language corpus for downstream natural language learning, and discover non-trivial performance boosts where natural language resources are limited. Second, we develop a simple and computationally efficient metric for emergent language, based on translation to natural language grounded on the same perceptual stimuli. Such a metric is found to better predict the transferability of emergent languages to downstream natural language tasks, compared to previous in-game metrics like accuracy and topographic similarity. This calls for a re-thinking of what language properties we should evaluate for emergent languages, and how we should evaluate them. Our methodology and results open up possibilities of establishing a *synergy* between the research of language emergence and natural language processing, where we could potentially better understand and improve emergent communication through the lens of natural language, and in turn improve upon low-resource natural language tasks with the help of emergent languages.

Limitations and Future Directions   Toward building such a synergy between emergent and natural languages, our work indicates that several directions still require further investigation. First, the structure of emergent languages generated from an image referential game is still limited, and using more natural image inputs or more powerful speaker and listener architectures do not seem helpful. Inspirations from research on how natural language evolves its complexity (Mufwene, 2013) could be helpful to this end. For example, harder (Mu & Goodman, 2021) or not fully cooperative (Cao et al., 2018; Noukhovitch et al., 2021) games or a larger populations of agents (Mordatch & Abbeel, 2018) with generational transmissions (Guo et al., 2019; Li & Bowling, 2019) might potentially encourage the emergence of more complex symbolic structure in machine communications. Also, our evaluation for emergent languages in this work is mostly empirical. Better theoretical frameworks that characterize different properties of natural language could be valuable for more fine-grained analysis of emergent languages and more actionable insights.

ETHICS STATEMENT

Our work is a preliminary step toward aligning the language of machines and humans, which has potential positive social impacts in several ways. First, shaping machine communications towards the structure of natural language contributes to human and AI alignment in terms of values and understanding of the world. Second, emergent languages could yield transfer benefits for low-resource languages and tasks, contributing to linguistic diversity and inclusion.

REPRODUCIBILITY STATEMENT

Our research in based on public codebases and datasets, with implementation details described throughout the paper. We have conducted reasonable hyperparameter searches and ablation studies to make sure experiment conclusions are fair. In the Appendix, we further provide links to all used code and data resources, and additional details including hyperparameter search setups and resource requirements for each experiment. We will clean and release the code upon acceptance.

REFERENCES

Muhannad Alomari, Paul Duckworth, David Hogg, and Anthony Cohn. Natural language acquisition and grounding for embodied robotic systems. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 31, 2017.

Jacob Andreas and Dan Klein. Analogs of linguistic structure in deep representations. *arXiv preprint arXiv:1707.08139*, 2017.

Jacob Andreas, Anca Dragan, and Dan Klein. Translating neuralese. *arXiv preprint arXiv:1704.06960*, 2017.

Michelle E Barton. *Input and interaction in language acquisition*. Cambridge University Press, 1994.

Natalie L Bohlmann and Jason T Downer. Self-regulation and task engagement as predictors of emergent language and literacy skills. *Early Education and Development*, 27(1):18–37, 2016.

Henry Brighton and Simon Kirby. Understanding linguistic evolution by visualizing the emergence of topographic mappings. *Artificial life*, 12(2):229–242, 2006.

Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

Jerome Bruner. The role of interaction formats in language acquisition. In *Language and social situations*, pp. 31–46. Springer, 1985.

Angelo Cangelosi and Domenico Parisi. Computer simulation: A new scientific approach to the study of language evolution. In *Simulating the evolution of language*, pp. 3–28. Springer, 2002.

Kris Cao, Angeliki Lazaridou, Marc Lanctot, Joel Z Leibo, Karl Tuyls, and Stephen Clark. Emergent communication through negotiation. *arXiv preprint arXiv:1804.03980*, 2018.

Rahma Chaabouni, Eugene Kharitonov, Diane Bouchacourt, Emmanuel Dupoux, and Marco Baroni. Compositionality and generalization in emergent languages. *arXiv preprint arXiv:2004.09124*, 2020.

Michael Cogswell, Jiasen Lu, Stefan Lee, Devi Parikh, and Dhruv Batra. Emergence of compositional language with deep generational transmission. *arXiv preprint arXiv:1904.09067*, 2019.

Verna Dankers, Elia Bruni, and Dieuwke Hupkes. The paradox of the compositionality of natural language: a neural machine translation case study. *arXiv preprint arXiv:2108.05885*, 2021.

Jill G De Villiers, Jill De Villiers, Peter A De Villiers, and Peter A DeVilliers. *Language acquisition*. Harvard University Press, 1978.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Daniel Fried, Ronghang Hu, Volkan Cirik, Anna Rohrbach, Jacob Andreas, Louis-Philippe Morency, Taylor Berg-Kirkpatrick, Kate Saenko, Dan Klein, and Trevor Darrell. Speaker-follower models for vision-and-language navigation. *arXiv preprint arXiv:1806.02724*, 2018.

Adele E Goldberg. Compositionality. In *The Routledge handbook of semantics*, pp. 435–449. Routledge, 2015.

Shangmin Guo, Yi Ren, Serhii Havrylov, Stella Frank, Ivan Titov, and Kenny Smith. The emergence of compositional languages for numeric concepts through iterated learning in neural agents. *arXiv preprint arXiv:1910.05291*, 2019.

Stevan Harnad. The symbol grounding problem. *Physica D: Nonlinear Phenomena*, 42(1-3):335–346, 1990.

Serhii Havrylov and Ivan Titov. Emergence of language with multi-agent games: Learning to communicate with sequences of symbols. *arXiv preprint arXiv:1705.11192*, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with gumbel-softmax. *arXiv preprint arXiv:1611.01144*, 2016.

Eugene Kharitonov and Marco Baroni. Emergent language generalization and acquisition speed are not tied to compositionality. *arXiv preprint arXiv:2004.03420*, 2020.

Simon Kirby. Spontaneous evolution of linguistic structure-an iterated learning model of the emergence of regularity and irregularity. *IEEE Transactions on Evolutionary Computation*, 5(2): 102–110, 2001.

Simon Kirby. Natural language from artificial life. *Artificial life*, 8(2):185–215, 2002.

Simon Kirby, Monica Tamariz, Hannah Cornish, and Kenny Smith. Compression and communication in the cultural evolution of linguistic structure. *Cognition*, 141:87–102, 2015.

Brenden M Lake, Tomer D Ullman, Joshua B Tenenbaum, and Samuel J Gershman. Building machines that learn and think like people. *Behavioral and brain sciences*, 40, 2017.

Angeliki Lazaridou and Marco Baroni. Emergent multi-agent communication in the deep learning era. *arXiv preprint arXiv:2006.02419*, 2020.

Angeliki Lazaridou, Alexander Peysakhovich, and Marco Baroni. Multi-agent cooperation and the emergence of (natural) language. *arXiv preprint arXiv:1612.07182*, 2016.

Angeliki Lazaridou, Karl Moritz Hermann, Karl Tuyls, and Stephen Clark. Emergence of linguistic communication from referential games with symbolic and pixel input. *arXiv preprint arXiv:1804.03984*, 2018.

Jason Lee, Kyunghyun Cho, Jason Weston, and Douwe Kiela. Emergent translation in multi-agent communication. In *International Conference on Learning Representations*, 2018.

Vladimir I Levenshtein et al. Binary codes capable of correcting deletions, insertions, and reversals. In *Soviet physics doklady*, volume 10, pp. 707–710. Soviet Union, 1966.

Fushan Li and Michael Bowling. Ease-of-teaching and language structure from emergent communication. *arXiv preprint arXiv:1906.02403*, 2019.

Yaoyiran Li, Edoardo Maria Ponti, Ivan Vulić, and Anna Korhonen. Emergent communication pretraining for few-shot machine translation. In *Proceedings of the 28th International Conference on Computational Linguistics*, pp. 4716–4731, 2020.

Chin-Yew Lin. Rouge: A package for automatic evaluation of summaries. In *Text summarization branches out*, pp. 74–81, 2004.

Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *European conference on computer vision*, pp. 740–755. Springer, 2014.

Kevin Lu, Aditya Grover, Pieter Abbeel, and Igor Mordatch. Pretrained transformers as universal computation engines. *arXiv preprint arXiv:2103.05247*, 2021.

Igor Mordatch and Pieter Abbeel. Emergence of grounded compositional language in multi-agent populations. In *Thirty-second AAAI conference on artificial intelligence*, 2018.

Jesse Mu and Noah Goodman. Emergent communication of generalizations. *arXiv preprint arXiv:2106.02668*, 2021.

Salikoko S Mufwene. The emergence of complexity in language: An evolutionary perspective. In *Complexity perspectives on language, communication and society*, pp. 197–218. Springer, 2013.

Michael Noukhovitch, Travis LaCroix, Angeliki Lazaridou, and Aaron Courville. Emergent communication under competition. *arXiv preprint arXiv:2101.10276*, 2021.

Myle Ott, Sergey Edunov, Alexei Baevski, Angela Fan, Sam Gross, Nathan Ng, David Grangier, and Michael Auli. fairseq: A fast, extensible toolkit for sequence modeling. *arXiv preprint arXiv:1904.01038*, 2019.

Isabel Papadimitriou and Dan Jurafsky. Learning music helps you read: Using transfer to study linguistic structure in language models. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 6829–6839, 2020.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th annual meeting of the Association for Computational Linguistics*, pp. 311–318, 2002.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster r-cnn: Towards real-time object detection with region proposal networks. *Advances in neural information processing systems*, 28: 91–99, 2015.

Piyush Sharma, Nan Ding, Sebastian Goodman, and Radu Soricut. Conceptual captions: A cleaned, hypernymed, image alt-text dataset for automatic image captioning. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 2556–2565, 2018.

Kenny Smith, Henry Brighton, and Simon Kirby. Complex systems in language evolution: the cultural emergence of compositional structure. *Advances in complex systems*, 6(04):537–558, 2003.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

Ramakrishna Vedantam, C Lawrence Zitnick, and Devi Parikh. Cider: Consensus-based image description evaluation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4566–4575, 2015.

Paul Vogt. The physical symbol grounding problem. *Cognitive Systems Research*, 3(3):429–457, 2002.

Kyle Wagner, James A Reggia, Juan Uriagereka, and Gerald S Wilkinson. Progress in the simulation of emergent communication and language. *Adaptive Behavior*, 11(1):37–69, 2003.

Zeyu Wang, Berthy Feng, Karthik Narasimhan, and Olga Russakovsky. Towards unique and informative captioning of images. In *Computer Vision–ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part VII 16*, pp. 629–644. Springer, 2020.

Ludwig Wittgenstein. Philosophical investigations. *New York: Macmill an Publish*, 1958.

Michaela L Zajicek-Farber. The contributions of parenting and postnatal depression on emergent language of children in low-income families. *Journal of Child and Family Studies*, 19(3):257–269, 2010.