MCMC Should Mix: Learning Energy-Based Model with Flow-Based Backbone

Abstract

Learning energy-based model (EBM) requires MCMC sampling of the learned model as an inner loop of the learning algorithm. However, MCMC sampling of EBMs in high-dimensional data space is generally not mixing, because the energy function, which is usually parametrized by deep network, is highly multi-modal in the data space. This is a serious handicap for both theory and practice of EBMs. In this paper, we propose to learn EBM with a flow-based model serving as a backbone, so that the EBM is a correction or an exponential tilting of the flow-based model. We show that the model has a particularly simple form in the space of the latent variables of the flow-based model, and MCMC sampling of the EBM in the latent space mixes well and traverses modes in the data space. This enables proper sampling and learning of EBMs. To the best of our knowledge, our work is the first where MCMC sampling with gradient-based methods is mixing for EBM parametrized by modern ConvNet for the modality of images.

1 Introduction

The energy-based model (EBM) (LeCun et al., 2006; Ngiam et al., 2011; Kim & Bengio, 2016; Zhao et al., 2016; Xie et al., 2016; Gao et al., 2018; Kumar et al., 2019b; Nijkamp et al., 2019; Du & Mordatch, 2019; Finn et al., 2016; Atchadé et al., 2017; De Bortoli et al., 2021; Song & Ou, 2018) defines an unnormalized probability density function on the observed data such as images via an energy function, so that the density is proportional to the exponential of the negative energy. Taking advantage of the approximation capacity of modern deep networks such as convolutional networks (ConvNet) (LeCun et al., 1998; Krizhevsky et al., 2012), recent papers (Xie et al., 2016; Gao et al., 2018; Kumar et al., 2019b; Nijkamp et al., 2019; Du & Mordatch, 2019) parametrize the energy function by ConvNet. The ConvNet-EBM is highly expressive and the learned EBM can produce realistic synthesized examples.

The EBM can be learned by maximum likelihood estimation (MLE), which follows an "analysis by synthesis" scheme. In the synthesis step, synthesized examples are generated by sampling from the current model. In the analysis step, the model parameters are updated based on the statistical difference between the synthesized examples and the observed examples. The synthesis step usually requires Markov chain Monte Carlo (MCMC) sampling, and gradient-based sampling such as Langevin dynamics (Langevin, 1908) or Hamiltonian Monte Carlo (HMC) (Neal, 2011) can be conveniently implemented on the current deep learning platforms where gradients can be efficiently and automatically computed by back-propagation.

However, gradient-based MCMC sampling in the data space generally does not mix, which is a fundamental issue from statistical perspective. The data distribution is typically highly multi-modal. To approximate such a distribution, the density function or the energy function of the ConvNet-EBM needs to be highly multi-modal as well. When sampling from such a multi-modal density in the data space, gradient-based MCMC tends to get trapped in local modes with little chance to traverse the modes freely, rendering the MCMC non-mixing. Without being able to generate fair examples from the model, the estimated gradient of the maximum likelihood learning can be highly biased, and the learned model parameters can be far from the unbiased estimator given by MLE. Even if we can learn the model by other means without resorting to MCMC sampling, e.g., by noise contrastive estimation (NCE) (Gutmann & Hyvärinen, 2010; Gao et al., 2019) or by amortized sampling (Grathwohl et al., 2020), it is still necessary to be able to draw fair examples from the

learned model for the purpose of model checking or downstream applications based on the learned model.

Accepting the fact that MCMC sampling is not mixing, contrastive divergence (Tieleman, 2008) initializes finite step MCMC from the observed examples, so that the learned model is admittedly biased from the MLE. Du et al. (2020) improves contrastive divergence by initializing MCMC from augmented samples. Recently, Nijkamp et al. (2019) proposes to initialize short-run MCMC from a fixed noise distribution, and shows that even though the learned EBM is biased, the short-run MCMC can be considered a valid model that can generate realistic examples. This partially explains why EBM learning algorithm can synthesize high quality examples even though the MCMC does not mix. However, the problem of non-mixing MCMC remains unsolved. Without proper MCMC sampling, the theory and practice of learning EBMs is on a very shaky ground. The primary goal of this paper is to address the problem of MCMC mixing, which is crucial for proper learning of EBMs. The quality of synthesis is a secondary issue in our work.

Figure 1: Demonstration of mixing MCMC with neural transport learned from a mixture of eight Gaussians. The Markov chains pulled back into data space x freely traverse the modes of the mixture Gaussian. *Left*: Observed examples (black) and trajectories (blue) of Markov chains (red) in data space x and latent space z. *Right*: Density estimations with exponentially tilted model p_θ of underlying flow q_α.

We propose to learn an EBM with a flow-based model as a backbone model or base measure, so that the EBM is in the form of a correction, or an exponential tilting, of the flow-based model. Flow-based models have gained popularity in generative modeling (Dinh et al., 2014; 2016; Kingma & Dhariwal, 2018; Grathwohl et al., 2018; Behrmann et al., 2018; Kumar et al., 2019a; Tran et al., 2019) and variational inference (Kingma & Welling, 2013; Rezende & Mohamed, 2015; Kingma et al., 2016; Kingma & Welling, 2014; Khemakhem et al., 2019). Similar to the generator model (Kingma & Welling, 2013; Goodfellow et al., 2014), flow-based model is based on a mapping from latent space to the data space. However, unlike the generator model, the mapping in the flow-based model is deterministic and one-one, with closed-form inversion and Jacobian that can be efficiently computed. This leads to an explicit normalized density via *change of variable*. However, to ensure tractable inversion and Jacobian, the mapping in the flow-based model has to be a composition of a sequence of simple transformations of highly constrained forms. In order to approximate a complex distribution, it is necessary to compose a large number of such transformations. In our work, we propose to learn EBM by correcting a relatively simple flow-based model with a relatively simple energy function parametrized by a free-form ConvNet. We show that the resulting EBM has a particularly simple form in the space of the latent variables of the flow-based model. MCMC sampling of the EBM in the latent space, which is a simple special case of neural transport MCMC (Hoffman et al., 2019), mixes well and is able to traverse modes in the data space. This enables proper sampling and learning of EBMs.

Our experiments demonstrate the efficacy of learning EBM with flow-based backbone, and the neural transport sampling of the learned EBM greatly mitigates the non-mixing problem of MCMC.

2 CONTRIBUTIONS AND RELATED WORK

Contributions. This paper tackles the problem of non-mixing MCMC for sampling from an EBM. We propose to learn EBM with a flow-based backbone model. The resulting EBM in the latent space is of a simple form that is much more friendly to MCMC mixing. We demonstrate the mixing of long-run Hamiltonian Monte Carlo Markov chains in several experiments. To the best of our knowledge, our work is the first where MCMC sampling with gradient-based method is mixing for EBM parametrized by modern ConvNet for the modality of images.

The following are research themes in generative modeling and MCMC sampling that are closely related to our work.

Neural transport MCMC. Our work is inspired by neural transport sampling (Hoffman et al., 2019). For an unnormalized target distribution, the neural transport sampler trains a flow-based model as a variational approximation to the target distribution, and then samples the target distribution in the space of latent variables of the flow-based model via change of variable. In the latent space, the target distribution is close to the prior distribution of the latent variables of the flow-based model, which is usually a unimodal Gaussian white noise distribution. Consequently the target distribution in the latent space is close to be unimodal and is much more conducive to mixing and fast convergence of MCMC than sampling in the original space (Mangoubi & Smith, 2017).

Our work is a simplified special case of this idea, where we learn the EBM as a correction of a pre-trained flow-based model, so that we do not need to train a separate flow-based approximation to the EBM. The energy function, which is a correction of the flow-based model, does not need to reproduce the content of the flow-based model, and thus can be kept relatively simple. Moreover, in the latent space, the resulting EBM takes on a very simple form where the inversion and Jacobian in the flow-based model disappear. This may allow for free-form flow-based model where inversion and Jacobian do not need to be in closed form (Grathwohl et al., 2018; Behrmann et al., 2018).

Energy-based corrections. Our model is based on an energy-based correction or an exponential tilting of a more tractable model. This idea has been explored in noise contrastive estimation (NCE) (Gutmann & Hyvärinen, 2010; Gao et al., 2019) and introspective neural networks (INN) (Tu, 2007; Jin et al., 2017; Lazarow et al., 2017), where the correction is obtained by discriminative learning. Earlier works include Rosenfeld et al. (2001); Wang & Ou (2018). Recently Xiao et al. (2020) recruits an EBM to correct a variational autoencoder with MCMC-based learning methods. Correcting or refining a simpler and more tractable backbone model can be much easier than learning an EBM from scratch, because the EBM does not need to reproduce the knowledge learned by the backbone model. It also allows easier sampling of EBM.

Latent space sampling. Non-mixing MCMC sampling of an EBM is a clear call for latent variables to represent multiple modes of the original model distribution via explicit top-down mapping, so that the distribution of the latent variables is less multi-modal. Earlier works in this direction include Bengio et al. (2013); Brock et al. (2018); Kumar et al. (2019b). In this paper, we choose to use flow-based model for its simplicity, because the distribution in the data space can be translated into the distribution in the latent space by a simple change of variable, without requiring integrating out extra dimensions as in the generator model.

3 MODEL AND LEARNING

3.1 FLOW-BASED MODEL

Let x be the input example, such as an image. A flow-based model is of the form

$$z \sim q_0(z), \ x = g_\alpha(z), \tag{1}$$

where z is the latent vector of the same dimensionality as x, and q_0 is a known prior distribution such as Gaussian white noise distribution. g_α is a composition of a sequence of invertible transformations whose inversion and log-determinants of the Jacobians can be obtained in closed form. As a result, these transformations are of highly constrained forms. α denotes the parameters. Let $q_\alpha(x)$ be the probability density at x under the transformation $x = g_\alpha(z)$, then according to the change of variable,

$$q_0(z)dz = q_\alpha(x)dx, \tag{2}$$

where dz and dx are understood as the volumes of the infinitesimal local neighborhoods around z and x respectively under the mapping $x = g_\alpha(z)$. Then for a given x, $z = g_\alpha^{-1}(x)$, and

$$q_\alpha(x) = q_0(z)dz/dx = q_0(g_\alpha^{-1}(x))|\det(\partial g_\alpha^{-1}(x)/\partial x)|, \tag{3}$$

where the ratio between the volumes dz/dx is the absolute value of the determinant of the Jacobian.

Suppose we observe training examples $(x_i, i = 1, ..., n) \sim p_{\text{data}}(x)$, where p_{data} is the data distribution, which is typically highly multi-modal. We can learn α by MLE. For large n, the MLE of α

minimizes the Kullback-Leibler divergence $D_{KL}(p_{\text{data}}\|q_\alpha)$. q_α strives to cover most of the modes in p_{data}, and the learned q_α tends to be more dispersed than p_{data}. In order for q_α to approximate p_{data} closely, it is usually necessary for g to be a composition of a large number of transformations of highly constrained forms with closed-form inversions and Jacobians. The learned mapping $g_\alpha(z)$ transports the unimodal Gaussian white noise distribution to a highly multi-modal distribution q_α in the data space as an approximation to the data distribution p_{data}.

3.2 ENERGY-BASED MODEL

An energy-based model (EBM) is defined as follows:

$$p_\theta(x) = \frac{1}{Z(\theta)} \exp(f_\theta(x))q(x), \tag{4}$$

where $q(x)$ is a reference measure, such as the uniform measure or a Gaussian white noise distribution as in Xie et al. (2016). f_θ is defined by a bottom-up ConvNet whose parameters are denoted by θ. The normalizing constant or the partition function $Z(\theta) = \int \exp(f_\theta(x))q(x)dx = \mathbb{E}_q[\exp(f_\theta(x))]$ is typically analytically intractable.

Suppose we observe training examples $x_i \sim p_{\text{data}}$ for $i = 1, ..., n$. For large n, the sample average over $\{x_i\}$ approximates the expectation with respect to p_{data}. For notational convenience, we treat the sample average and the expectation as the same.

The log-likelihood is

$$L(\theta) = \frac{1}{n} \sum_{i=1}^{n} \log p_\theta(x_i) \doteq \mathbb{E}_{p_{\text{data}}}[\log p_\theta(x)]. \tag{5}$$

The derivative of the log-likelihood is

$$L'(\theta) = \mathbb{E}_{p_{\text{data}}}[\nabla_\theta f_\theta(x)] - \mathbb{E}_{p_\theta}[\nabla_\theta f_\theta(x)] \doteq \frac{1}{n} \sum_{i=1}^{n} \nabla_\theta f_\theta(x_i) - \frac{1}{n} \sum_{i=1}^{n} \nabla_\theta f_\theta(x_i^-), \tag{6}$$

where $x_i^- \sim p_\theta(x)$ for $i = 1, ..., n$ are synthesized examples sampled from the current model $p_\theta(x)$.

The above equation leads to the "analysis by synthesis" learning algorithm. At iteration t, let θ_t be the current model parameters. We generate $x_i^- \sim p_{\theta_t}(x)$ for $i = 1, ..., n$. Then we update $\theta_{t+1} = \theta_t + \eta_t L'(\theta_t)$, where η_t is the learning rate.

To generate synthesized examples from p_θ, we can use gradient-based MCMC sampling such as Langevin dynamics (Langevin, 1908) or Hamiltonian Monte Carlo (HMC) (Neal, 2011), where $\nabla_x f_\theta(x)$ can be automatically computed. Since p_{data} is in general highly multi-modal, the learned p_θ or f_θ tends to be multi-modal as well. As a result, gradient-based MCMC tends to get trapped in the local modes of f_θ with little chance of mixing between the modes.

3.3 ENERGY-BASED MODEL WITH FLOW-BASED BACKBONE

Instead of using uniform or Gaussian white noise distribution for the reference distribution $q(x)$ in the EBM in (4), we can use a relatively simple flow-based model q_α as the reference model. q_α can be pre-trained by MLE, and serves as the backbone of the model, so that the model is of the following form

$$p_\theta(x) = \frac{1}{Z(\theta)} \exp(f_\theta(x))q_\alpha(x), \tag{7}$$

which is almost the same as in (4) except that the reference distribution $q(x)$ is a pre-trained flow-based model $q_\alpha(x)$. The resulting model $p_\theta(x)$ is a correction or refinement of q_α, or an exponential tilting of $q_\alpha(x)$, and $f_\theta(x)$ is a free-form ConvNet to parametrize the correction. The overall negative energy is $f_\theta(x) + \log q_\alpha(x)$.

In the latent space of z, let $p(z)$ be the distribution of z under $p_\theta(x)$, then

$$p(z)dz = p_\theta(x)dx = \frac{1}{Z(\theta)} \exp(f_\theta(x))q_\alpha(x)dx. \tag{8}$$

Recall equation (2), $q_\alpha(x)dx = q_0(z)dz$, we have

$$p(z) = \frac{1}{Z(\theta)} \exp(f_\theta(g_\alpha(z)))q_0(z). \tag{9}$$

$p(z)$ is an exponential tilting of the prior noise distribution $q_0(z)$. It is a very simple form that does not involve the Jacobian or inversion of $g_\alpha(z)$.

We can also apply the above exponential tilting and change of variable scheme to the generator model, i.e., using the generator model as the backbone model. However, for the generator model, $q(x)$ is not in closed form, and after exponential tilting, the marginal $p(z)$ requires integral. See Appendix A.2 for details. In comparison, flow-based model is simpler and more explicit.

3.4   LEARNING BY HAMILTONIAN NEURAL TRANSPORT SAMPLING

Instead of sampling $p_\theta(x)$, we can sample $p(z)$ in (9). While $q_\alpha(x)$ is multi-modal, $q_0(z)$ is unimodal. Since $f_\theta(x)$ is a correction of q_α, $p(z)$ is a correction of $p_0(z)$, and can be much less multi-modal than $p_\theta(x)$ in the data space. After sampling z from $p(z)$, we can generate $x = g_\alpha(z)$.

The above MCMC sampling scheme is a special case of neutral transport MCMC proposed by Hoffman et al. (2019) for sampling from an EBM or the posterior distribution of a generative model. The basic idea is to train a flow-based model as a variational approximation to the target EBM, and sample the EBM in the latent space of the flow-based model. In our case, since p_θ is a correction of q_α, we can simply use q_α directly as the approximate flow-based model in neural transport sampler. The extra benefit is that the distribution $p(z)$ is of an even simpler form than $p_\theta(x)$, because $p(z)$ does not involve the inversion and Jacobian of g_α. As a result, we may use a flow-based backbone model of a more free form such as one based on residual network (Behrmann et al., 2018), and we will leave this issue to future investigation.

We use HMC (Neal, 2011) to sample from $p(z)$. We can then learn θ by MLE according to equation (6). Algorithm 1 describes the detailed learning algorithm.

Algorithm 1: Learning the correction f_θ of flow q_α with Hamiltonian neural transport (NT-EBM).

input : Learning iterations T, learning rate η, batch size m, pre-trained parameters α, initial
 parameters θ_0, initial latent variables $\{z_{i,0}\}_{i=1}^m \sim q_0(z)$, observed examples $\{x_i\}_{i=1}^n$,
 number of MCMC steps K in each learning iteration.
output: Parameters $\{\theta_T\}$.
for $t = 0 : T - 1$ **do**

    1. Update $\{z_{i,t}\}_{i=1}^m$ by HMC with target distribution $p(z)$ in equation (9) for K steps.
    2. Push the z-space samples forward through g_α to obtain synthesized examples $\{x_i^-\}_{i=1}^m$.
    3. Draw observed training examples $\{x_i\}_{i=1}^m$.
    4. Update θ according to (6).

3.5   LEARNING BY NOISE CONTRASTIVE ESTIMATION

We may also learn the correction $f_\theta(x)$ discriminatively, as in noise contrastive estimation (NCE) (Gutmann & Hyvärinen, 2010) or introspective neural networks (INN) (Tu, 2007; Jin et al., 2017; Lazarow et al., 2017). Let x_i^+, $i = 1, ..., n$ be the training examples, which are treated as positive examples, and let x_i^-, $i = 1, ..., n^-$ be the examples generated from $q_\alpha(x)$, which are treated as negative examples. For each batch, let ρ be the proportion of positive examples, and $1 - \rho$ the proportion of negative examples. We have

$$\log \left[\frac{P(+|x)}{P(-|x)} \right] = \log \left[\frac{\rho}{1 - \rho} \right] - \log Z(\theta) + f_\theta(x) = b + f_\theta(x),$$

where $b = \log \left[\frac{\rho}{1-\rho} \right] - \log Z(\theta)$ is treated as a separate bias parameter. Then we can estimate b and θ by fitting a logistic regression on the positive and negative examples. Note, that NCE is the discriminator side of GAN. Similar to GAN, we can also improve the flow-based model based on the value function of GAN. This may further improve the NCE results.

4   EXPERIMENTS

In the subsequent empirical evaluations, we shall address the following questions:

(1) Is the mixing of HMC with neural transport, both qualitatively and quantitatively, apparent?
(2) In the latent space, does smooth interpolation remain feasible?
(3) Does the exponential tilting with correction term $f_\theta(x)$ improve the quality of synthesis?
(4) In terms of ablation, what is the effect of amount of parameters α for flow-based q_α?
(5) Is discriminative learning in the form of NCE an efficient alternative learning method?

The primary concern of our work is the mixing of MCMC, which is addressed in (1) and (2). The questions addressed in (3), (4), and (5) are secondary to this concern. We use Glow (Kingma & Dhariwal, 2018) as the flow-based model q_α. We refer to Appendix A.3 and A.4 for details on the model architectures and training settings, respectively.

4.1   MIXING

In the following, we will recruit several diagnostics to quantitatively and qualitatively address the question of mixing MCMC. We will first evaluate the famous Gelman-Rubin statistic for Markov chains running in latent space and contrast those against chains in data space. Then, we will evaluate auto-correlation of long-run Markov chains as a weaker measure of mixing. Finally, we provide a visual inspection of long-run Markov chains in our model and compare those with a biased model known to not be amenable to mixing.

(a) Latent space.   (b) Data space.   (c) Latent space.   (d) Data space.

Figure 2: Diagnostics for the mixing of MCMC chains with $n = 2,000$ steps, learned from SVHN dataset. (a-b) Histograms of Gelman-Rubin statistic of multiple long-run Markov chains. $\hat{R} < 1.2$ indicates approximative convergence. (c-d) Auto-correlation of a single long-run Markov chain over time lag Δt with mean depicted as line and min/max as bands.

Gelman-Rubin. The Gelman-Rubin statistic (Gelman et al., 1992; Brooks & Gelman, 1998) measures the convergence of Markov chains to the target distribution. It is based on the notion that if multiple chains have converged, by definition, they should appear "similar" to one another, else, one or more chains have failed to converge. Specifically, the diagnostic recruits an analysis of variance to access the difference between the between-chain and within-chain variances. We refer to the Appendix A.6 for details. Figure 2(a-b) depicts the histograms of $\hat{R}$ for $m = 64$ chains over $n = 2,000$ steps with a burn-in time of 400 steps, learned from SVHN dataset. The mean $\hat{R}$ value is 1.13, which we treat as approximative convergence to the target distribution. We contrast this result with HMC sampling in data space with unfavorable diagnostics of mixing.

Auto-Correlation. MCMC sampling leads to autocorrelated samples due to the inherent Markovian dependence structure. The Δt (sample) auto-correlation is the correlation between samples Δt steps apart in time. Figure 2(c-d) shows auto-correlation against increasing time lag Δt, learned from SVHN dataset. While the auto-correlation of HMC chains with neural transport vanishes within $\Delta t = 200$ steps, the over-damped Langevin sampler requires $\Delta t > 1,000$ steps. The single long-run Markov chain behavior is consistent with the Gelman-Rubin statistic assessing multiple chains.

Visual Inspection. Assume a Markov chain is run for a large numbers of steps $n = 2,000$ with a Hamiltonian neural transport. Then, we pull back Markov chains into data space and visualize the long run trajectory in Figures 4 and 10 with p_θ learned on the SVHN ($32 \times 32 \times 3$) (Netzer et al., 2011) dataset and CelebA ($64 \times 64 \times 3$) (Liu et al., 2015) dataset, respectively. Figure 3 contrasts the Markov chain that samples the EBM learned with short-run MCMC (Nijkamp et al., 2019), which does not mix, against our method in which the pulled back Markov chains mix freely. We observe the Markov chain is freely traversing between local modes, which we consider a weak indication

of mixing MCMC. In Appendix A.7 we report the FID scores computed on samples from a single long-run chain, which converge to the FID score computed on samples from multiple chains with a fixed number of sampling steps (Table 1).

Figure 3: Long-run Markov chains for learned models without and with mixing. *Top:* Chains trapped in an over-saturated local mode. Model learned by short-run MCMC (Nijkamp et al., 2019) without mixing. *Bottom:* Chain is freely traversing local modes. Model learned by Hamiltonian neural transport with mixing.

Figure 4: A single long-run Markov Chain with $n = 2,000$ steps depicted in 5 steps intervals sampled by Hamiltonian neural transport on SVHN ($32 \times 32 \times 3$).

4.2 INTERPOLATION

Interpolation allows us to appraise the smoothness of the latent space. In particular, two samples z_1 and z_2 are drawn from the prior distribution q_0. We may spherically interpolate between them in z-space and then push forward into data space to assess q_α.

To evaluate the tilted model $p_\theta(z)$, we run a magnetized form of the over-damped Langevin equation for which we alter negative energy $U(z) = f_\theta(g_\alpha(z)) + \log q_0(z)$ to $U_\gamma(z) = U(z) - \gamma\|z - z^*\|_2$ with magnetization constant γ (Hill et al., 2019). Note, $\frac{d}{dz}\|z\|_2 = z/\|z\|_2$, thus, the magnetization term introduces a vector field pointing with uniform strength γ towards z^*. The resulting Langevin equation is $dz(t) = \left(\Delta U(z(t)) + \gamma\frac{z(t)-z^*}{\|z(t)-z^*\|_2}\right) dt + \sqrt{2}dW(t)$ with Wiener process $W(t)$. To find a low energy path from z_1 towards z_2, we set $z^* = z_2$, $z = z_1$ and perform $n = 1,000$ steps of the discretized, magnetized Langevin equation with small γ.

Figure 5: Low energy path between z_1 and z_2 by magnetized Langevin dynamics over $n = 1,000$ steps on MNIST ($28 \times 28 \times 1$). *Top:* Trajectory in data-space. *Bottom:* Energy profile over time.

Figure 5 depicts the low-energy path in data-space and energy $U(z)$ over time. The qualitatively smooth interpolation and narrow energy spectrum indicate that a Langevin dynamics in latent space (with small magnetization) is able to traverse two arbitrary local modes, thus, substantiating our claim that the underlying geometry is amenable to mixing.

4.3 SYNTHESIS

While the emphasis of our work is on the mixing of Markov chains, we do evaluate the quality of synthesis on four datasets which include MNIST ($28 \times 28 \times 1$) (LeCun et al., 2010), SVHN ($32 \times 32 \times 3$) (Netzer et al., 2011), CelebA ($64 \times 64 \times 3$) (Liu et al., 2015), and, CIFAR-10 ($32 \times 32 \times 3$) (Krizhevsky et al.).

(a) Samples from flow q_α by ancestral sampling.   (b) Samples from p_θ by neural transport.   (c) Samples from flow q_α by ancestral sampling.   (d) Samples from p_θ by neural transport.

Figure 6: Comparison of generated samples by ancestral sampling from flow q_α and neural transport sampling via Hamiltonian Monte Carlo from p_θ learned by NT-EBM. *Left:* SVHN ($32 \times 32 \times 3$). *Right:* CelebA ($64 \times 64 \times 3$).

The qualitative results are depicted in Figure 6 which contrast generated samples from Glow q_α against long-run Markov chains by Hamiltonian neural transport. Table 1 compares the Fréchet Inception Distance (FID) (Heusel et al., 2017) with Inception v3 classifier (Szegedy et al., 2016) on $50,000$ generated examples. Both, qualitatively and quantitatively speaking, we observe a significant improvement in quality of synthesis with exponentially tilting of the reference distribution q_α by the correction f_θ.

Table 1: FID scores for generated examples in comparison to VAE (Kingma & Welling, 2013), ABP (Han et al., 2017), and Glow (Kingma & Dhariwal, 2018).

Method	MNIST	SVHN	CelebA	CIFAR-10
VAE	32.86	49.72	48.27	106.37
ABP	39.12	48.65	51.92	114.13
Glow (MLE)	66.04	94.23	59.35	90.08
NCE-EBM (Ours)	36.52	79.84	51.73	—
NT-EBM (Ours)	**21.32**	**48.01**	**46.38**	**78.12**

Note, the models in Table 1 and 3 have been trained based on the official reference implementations. To ensure a fair comparison of learning Glow by MLE and our methods, we disabled learning of the spatial prior and use additive coupling layers for Glow.

Table 2: FID scores for samples collected from a single long-run chain on SVHN ($32 \times 32 \times 3$).

# Samples	1,000	2,000	3,000	4,000	5,000	6,000	7,000	8,000	9,000	10,000
FID	97.51	76.74	67.67	60.41	60.25	56.45	55.34	53.85	52.32	48.72

In Table 2, we show the FID scores for samples obtained from every 1,000 steps of a single long-run chain for a model learned on SVHN. That is, the first FID score is calculated over the first 1,000 consecutive samples, the second FID score over the first 2,000 consecutive samples, and so forth. The FID score converges to our reported FID score with multiple sampling chains and a fixed number of sampling steps (Table 1), which indicates that one can obtain fair samples of the model by sampling from a single very long-run HMC chain.

4.4 Ablation

We investigate the influence of the number of parameters α of flow-based q_α on the quality of synthesis. In Table 3, we show (1) the threshold of a "large" q_α learned by MLE outperforming NT with a "small" tilted q_α, and, (2) the minimal size of q_α which allows for the learning by our method. Our method with a "medium" sized backbone significantly outperforms the "largest" Glow baseline.

Table 3: FID scores for generated examples for Glow (Kingma & Dhariwal, 2018) q_α with varying sizes of parameters α on SVHN ($32 \times 32 \times 3$). Small: $depth = 4$, $width = 128$, Medium: $depth = 8$, $width = 128$. Large: $depth = 16$, $width = 256$, Largest: $depth = 32$, $width = 512$.

Method	Small	Medium	Large	Largest
Glow (MLE)	110.55	94.34	89.31	86.18
NT-EBM (Ours)	74.77	48.01	43.82	—

4.5 Noise Contrastive Estimation

Noise Contrastive Estimation (NCE) is a computationally efficient alternative learning procedure which avoids MCMC sampling by re-casting the learning problem in the form of a logistic regression. Hence, we wish to learn the correction f_θ with our NCE-EBM algorithm according to (10), while we still sample from the learned model with neural transport MCMC.

Table 1 compares the learned models with both learning methods. The long-run Markov chains in the energy-based models learned by NCE are conducive to mixing and remain of high visual quality. Figure 7 depicts samples from q_α (left) and samples from p_θ learned by our NCE algorithm for which sampling is performed using Hamiltonian neural transport (right) for CelebA.

(a) Samples drawn from q_α by ancestral sampling. (b) Samples drawn from p_θ by neural transport.

Figure 7: Generated samples from a model learned by NCE-EBM on CelebA ($64 \times 64 \times 3$).

Assume a Markov chain is run for a large numbers of steps with a Hamiltonian neural transport. Then, we pull back Markov chain into data space and visualize the long run trajectory in Figure 11 (see Appendix A.7). The Markov chain synthesizes realistic images with high diversity. This finding indicates the efficacy of learning EBM with flow-based backbone by NCE, while, after learning the model, we may draw samples by HMC with neural transport.

5 Conclusion

This paper proposes to learn EBM as a correction or exponential tilting of a flow-based model, so that neural transport MCMC sampling in the latent space of the flow-based model can mix well and traverse the modes in the data space.

From a statistical perspective, the mixing of MCMC is a fundamental problem and, to the best of our knowledge, our work is the first to address this concern for EBMs parameterized by modern ConvNets.

Moreover, we pave the way towards computationally efficient learning by noise contrastive estimation while drawing samples from the learned model by neural transport HMC, which we believe is an important direction to explore in future work.

REFERENCES

Christophe Andrieu and Johannes Thoms. A tutorial on adaptive mcmc. *Statistics and computing*, 18(4):343–373, 2008.

Yves F Atchadé, Gersende Fort, and Eric Moulines. On perturbed proximal gradient algorithms. *The Journal of Machine Learning Research*, 18(1):310–342, 2017.

Jens Behrmann, Will Grathwohl, Ricky TQ Chen, David Duvenaud, and Jörn-Henrik Jacobsen. Invertible residual networks. *arXiv preprint arXiv:1811.00995*, 2018.

Yoshua Bengio, Grégoire Mesnil, Yann Dauphin, and Salah Rifai. Better mixing via deep representations. In *International conference on machine learning*, pp. 552–560, 2013.

Alexandros Beskos, Natesh Pillai, Gareth Roberts, Jesus-Maria Sanz-Serna, Andrew Stuart, et al. Optimal tuning of the hybrid monte carlo algorithm. *Bernoulli*, 19(5A):1501–1534, 2013.

Andrew Brock, Jeff Donahue, and Karen Simonyan. Large scale gan training for high fidelity natural image synthesis. *arXiv preprint arXiv:1809.11096*, 2018.

Stephen P Brooks and Andrew Gelman. General methods for monitoring convergence of iterative simulations. *Journal of computational and graphical statistics*, 7(4):434–455, 1998.

Ricky TQ Chen, Jens Behrmann, and Jörn-Henrik Jacobsen. Residual flows: Unbiased generative modeling with norm-learned i-resnets.

Valentin De Bortoli, Agnès Desolneux, Alain Durmus, Bruno Galerne, and Arthur Leclaire. Maximum entropy methods for texture synthesis: theory and practice. *SIAM Journal on Mathematics of Data Science*, 3(1):52–82, 2021.

Laurent Dinh, David Krueger, and Yoshua Bengio. Nice: Non-linear independent components estimation. *arXiv preprint arXiv:1410.8516*, 2014.

Laurent Dinh, Jascha Sohl-Dickstein, and Samy Bengio. Density estimation using real nvp. *arXiv preprint arXiv:1605.08803*, 2016.

Yilun Du and Igor Mordatch. Implicit generation and generalization in energy-based models. *arXiv preprint arXiv:1903.08689*, 2019.

Yilun Du, Shuang Li, Joshua Tenenbaum, and Igor Mordatch. Improved contrastive divergence training of energy based models. *arXiv preprint arXiv:2012.01316*, 2020.

Chelsea Finn, Paul Christiano, Pieter Abbeel, and Sergey Levine. A connection between generative adversarial networks, inverse reinforcement learning, and energy-based models. *arXiv preprint arXiv:1611.03852*, 2016.

Ruiqi Gao, Yang Lu, Junpei Zhou, Song-Chun Zhu, and Ying Nian Wu. Learning generative convnets via multi-grid modeling and sampling. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 9155–9164, 2018.

Ruiqi Gao, Erik Nijkamp, Diederik P Kingma, Zhen Xu, Andrew M Dai, and Ying Nian Wu. Flow contrastive estimation of energy-based models. *arXiv preprint arXiv:1912.00589*, 2019.

Andrew Gelman, Donald B Rubin, et al. Inference from iterative simulation using multiple sequences. *Statistical science*, 7(4):457–472, 1992.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pp. 249–256, 2010.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pp. 2672–2680, 2014.

Will Grathwohl, Ricky TQ Chen, Jesse Betterncourt, Ilya Sutskever, and David Duvenaud. Ffjord: Free-form continuous dynamics for scalable reversible generative models. *arXiv preprint arXiv:1810.01367*, 2018.

Will Grathwohl, Jacob Kelly, Milad Hashemi, Mohammad Norouzi, Kevin Swersky, and David Duvenaud. No mcmc for me: Amortized sampling for fast and stable training of energy-based models. *arXiv preprint arXiv:2010.04230*, 2020.

Michael Gutmann and Aapo Hyvärinen. Noise-contrastive estimation: A new estimation principle for unnormalized statistical models. In *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, pp. 297–304, 2010.

Tian Han, Yang Lu, Song-Chun Zhu, and Ying Nian Wu. Alternating back-propagation for generator network. In *Proceedings of the Thirty-First AAAI Conference on Artificial Intelligence, February 4-9, 2017, San Francisco, California, USA.*, pp. 1976–1984, 2017. URL http://aaai.org/ocs/index.php/AAAI/AAAI17/paper/view/14784.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In *Advances in Neural Information Processing Systems*, pp. 6626–6637, 2017.

Mitch Hill, Erik Nijkamp, and Song-Chun Zhu. Building a telescope to look into high-dimensional image spaces. *Quarterly of Applied Mathematics*, 77(2):269–321, 2019.

Matthew Hoffman, Pavel Sountsov, Joshua V Dillon, Ian Langmore, Dustin Tran, and Srinivas Vasudevan. Neutra-lizing bad geometry in hamiltonian monte carlo using neural transport. *arXiv preprint arXiv:1903.03704*, 2019.

Long Jin, Justin Lazarow, and Zhuowen Tu. Introspective classification with convolutional nets. In *Advances in Neural Information Processing Systems*, pp. 823–833, 2017.

Ilyes Khemakhem, Diederik P Kingma, and Aapo Hyvärinen. Variational autoencoders and nonlinear ica: A unifying framework. *arXiv preprint arXiv:1907.04809*, 2019.

Taesup Kim and Yoshua Bengio. Deep directed generative models with energy-based probability estimation. *arXiv preprint arXiv:1606.03439*, 2016.

Diederik Kingma and Max Welling. Efficient gradient-based inference through transformations between bayes nets and neural nets. In *International Conference on Machine Learning*, pp. 1782–1790, 2014.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015. URL http://arxiv.org/abs/1412.6980.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Durk P Kingma and Prafulla Dhariwal. Glow: Generative flow with invertible 1x1 convolutions. In *Advances in Neural Information Processing Systems*, pp. 10215–10224, 2018.

Durk P Kingma, Tim Salimans, Rafal Jozefowicz, Xi Chen, Ilya Sutskever, and Max Welling. Improved variational inference with inverse autoregressive flow. In *Advances in neural information processing systems*, pp. 4743–4751, 2016.

Alex Krizhevsky, Vinod Nair, and Geoffrey Hinton. Cifar-10 (canadian institute for advanced research). URL http://www.cs.toronto.edu/~kriz/cifar.html.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pp. 1097–1105, 2012.

Manoj Kumar, Mohammad Babaeizadeh, Dumitru Erhan, Chelsea Finn, Sergey Levine, Laurent Dinh, and Durk Kingma. Videoflow: A flow-based generative model for video. *arXiv preprint arXiv:1903.01434*, 2019a.

Rithesh Kumar, Anirudh Goyal, Aaron Courville, and Yoshua Bengio. Maximum entropy generators for energy-based models. *arXiv preprint arXiv:1901.08508*, 2019b.

Paul Langevin. *On the theory of Brownian motion*. 1908.

Justin Lazarow, Long Jin, and Zhuowen Tu. Introspective neural networks for generative modeling. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 2774–2783, 2017.

Yann LeCun, Léon Bottou, Yoshua Bengio, Patrick Haffner, et al. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Yann LeCun, Sumit Chopra, Raia Hadsell, M Ranzato, and F Huang. A tutorial on energy-based learning. *Predicting structured data*, 1(0), 2006.

Yann LeCun, Corinna Cortes, and CJ Burges. Mnist handwritten digit database. *ATT Labs [Online]. Available: http://yann.lecun.com/exdb/mnist*, 2, 2010.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of International Conference on Computer Vision (ICCV)*, 2015.

Oren Mangoubi and Aaron Smith. Rapid mixing of hamiltonian monte carlo on strongly log-concave distributions. *arXiv preprint arXiv:1708.07114*, 2017.

Radford M Neal. MCMC using hamiltonian dynamics. *Handbook of Markov Chain Monte Carlo*, 2, 2011.

Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Bo Wu, and Andrew Y Ng. Reading digits in natural images with unsupervised feature learning. 2011.

Jiquan Ngiam, Zhenghao Chen, Pang W Koh, and Andrew Y Ng. Learning deep energy models. In *Proceedings of the 28th international conference on machine learning (ICML-11)*, pp. 1105–1112, 2011.

Erik Nijkamp, Song-Chun Zhu, and Ying Nian Wu. On learning non-convergent short-run mcmc toward energy-based model. *arXiv preprint arXiv:1904.09770*, 2019.

Prajit Ramachandran, Barret Zoph, and Quoc V Le. Searching for activation functions. *arXiv preprint arXiv:1710.05941*, 2017.

Danilo Jimenez Rezende and Shakir Mohamed. Variational inference with normalizing flows. *arXiv preprint arXiv:1505.05770*, 2015.

Ronald Rosenfeld, Stanley F Chen, and Xiaojin Zhu. Whole-sentence exponential language models: a vehicle for linguistic-statistical integration. *Computer Speech & Language*, 15(1):55–73, 2001.

Yunfu Song and Zhijian Ou. Learning neural random fields with inclusive auxiliary generators. 2018.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2818–2826, 2016.

Tijmen Tieleman. Training restricted boltzmann machines using approximations to the likelihood gradient. In *Proceedings of the 25th international conference on Machine learning*, pp. 1064–1071, 2008.

Dustin Tran, Keyon Vafa, Kumar Krishna Agrawal, Laurent Dinh, and Ben Poole. Discrete flows: Invertible generative models of discrete data. *arXiv preprint arXiv:1905.10347*, 2019.

Zhuowen Tu. Learning generative models via discriminative approaches. In *2007 IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1–8. IEEE, 2007.

Dootika Vats and Christina Knudson. Revisiting the gelman-rubin diagnostic. *arXiv preprint arXiv:1812.09384*, 2018.

Bin Wang and Zhijian Ou. Learning neural trans-dimensional random field language models with noise-contrastive estimation. In *2018 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 6134–6138. IEEE, 2018.

Zhisheng Xiao, Karsten Kreis, Jan Kautz, and Arash Vahdat. Vaebm: A symbiosis between variational autoencoders and energy-based models. In *International Conference on Learning Representations*, 2020.

Jianwen Xie, Yang Lu, Song-Chun Zhu, and Yingnian Wu. A theory of generative convnet. In *International Conference on Machine Learning*, pp. 2635–2644, 2016.

Junbo Zhao, Michael Mathieu, and Yann LeCun. Energy-based generative adversarial network. *arXiv preprint arXiv:1609.03126*, 2016.

A APPENDIX

A.1 CHANGE OF VARIABLE

Under the invertible transformation $x = g(z)$, let $p(z)$ be the density of z, and $p(x)$ be the density of x. Let D_z be an infinitesimal neighborhood around z, and let D_x be an infinitesimal neighborhood around x, so that g maps z to x, and maps D_z to D_x. Then

$$\Pr(D_z) = \Pr(D_x). \tag{10}$$

$\Pr(D_z) = p(z)|D_z| + o(|D_z|)$, and $\Pr(D_x) = p(x)|D_x| + o(|D_x|)$, where $|D_z|$ and $|D_x|$ are the volumes of D_z and D_x respectively. Thus we have

$$p(z)|D_z| = p(x)|D_x|, \tag{11}$$

where we ignore $o(|D_z|)$ and $o(|D_x|)$ terms. This is the meaning of

$$p(z)dz = p(x)dx, \tag{12}$$

where $|D_x|/|D_z|$ or dx/dz is the determinant of the Jacobian of g.

Equation (12) is a convenient starting point for deriving densities under change of variable.

A.2 ENERGY-BASED CORRECTION AND CHANGE OF VARIABLE FOR GENERATOR MODEL

The generator model is of the form $z \sim \mathrm{N}(0, I_d)$, and $x = g_\alpha(z) + \epsilon$, $\epsilon \sim \mathrm{N}(0, \sigma^2 I_D)$, where D is the dimensionality of x, and $d \ll D$ is the dimensionality of the latent vector. Unlike the flow-based model, the marginal distribution of x involves intractable integral.

We shall study exponential tilting of generator model using the simple equation (12) for change of variable. To that end, we let $\tilde{z} = (z, \epsilon)$, and let $\tilde{x} = (z, x)$. Then

$$\tilde{x} = (z, x) = G_\alpha(\tilde{z}) = G_\alpha(z, \epsilon) = (z, g_\alpha(z) + \epsilon). \tag{13}$$

Let $q_0(\tilde{z})$ be the Gaussian white noise distribution of $\tilde{z}$ under the generator model. Let $q_\alpha(\tilde{x})$ be the distribution of $\tilde{x}$ under the generator model. Consider the change of variable between $\tilde{z}$ and $\tilde{x}$. In parallel to equation (12), we have

$$q_0(\tilde{z})d\tilde{z} = q_\alpha(\tilde{x})d\tilde{x}. \tag{14}$$

The marginal distribution $q_\alpha(x) = \int q_\alpha(\tilde{x})dz = \int q_\alpha(z, x)dz$, which is intractable.

Suppose we exponentially tilt $q_\alpha(\tilde{x})$ to

$$p_\theta(\tilde{x}) = \frac{1}{Z(\theta)} \exp(f_\theta(\tilde{x}))q_\alpha(\tilde{x}). \tag{15}$$

Again this can be translated into the space of $\tilde{z}$ so that under $p_\theta(\tilde{x})$,

$$p(\tilde{z})d\tilde{z} = p_\theta(\tilde{x})d\tilde{x}. \tag{16}$$

Combining equations (14), (15), and (16), we have

$$p(\tilde{z}) = \frac{1}{Z(\theta)} \exp(f_\theta(G_\alpha(\tilde{z}))q_0(\tilde{z}), \tag{17}$$

that is, under the tilted model $p_\theta(\tilde{x})$,

$$p(z, \epsilon) = \frac{1}{Z(\theta)} \exp(f_\theta(z, g_\alpha(z) + \epsilon))q_0(z, \epsilon). \tag{18}$$

For $p(z, \epsilon)$, the marginal distribution $p(z)$ cannot be obtained in closed form, in particular, for gradient-based sampling, we need to compute

$$\nabla_z \log p(z) = \frac{1}{p(z)} \int \nabla_z p(z, \epsilon)d\epsilon \tag{19}$$

$$= \int [\nabla_z \log p(z, \epsilon)] \frac{p(z, \epsilon)}{p(z)} d\epsilon \tag{20}$$

$$= \mathbb{E}_{p(\epsilon|z)}[\nabla_z \log p(z, \epsilon)]. \tag{21}$$

That is, there is an inner loop for approximating $\mathbb{E}_{p(\epsilon|z)}$. This is less convenient than the flow-based model.

A.3 MODEL ARCHITECTURES

For Glow model q_α, we follow the setting of Kingma & Dhariwal (2018) with $n\_bits\_x = 8$, $flow\_permutation = 2$, $flow\_coupling = 0$.

For the EBM model f_θ, we use the following Conv-Net structure.

We use the following notation. Convolutional operation $conv(n)$ with n output feature maps and bias term. We recruit $LipSwish(x) = Swish(x)/1.1$ (Chen et al.) nonlinearity where $Swish(x) = x * sigmoid(x)$ (Ramachandran et al., 2017) as activation function . We set $n_f \in \{32, 64\}$.

Specifically, we set use the following hyper-parameters:

1. **MNIST**: For Glow, $n\_levels = 3$, $depth = 8$, $width = 128$. For EBM, $n_f = 32$.
2. **SVHN**: For Glow, $n\_levels = 3$, $depth = 8$, $width = 128$. For EBM, $n_f = 32$.
3. **CelebA**: For Glow, $n\_levels = 3$, $depth = 16$, $width = 256$. For EBM, $n_f = 32$.
4. **CIFAR-10**: For Glow, $n\_levels = 3$, $depth = 16$, $width = 512$. For EBM, $n_f = 32$.

Energy-based Model ($32 \times 32 \times 3$)		
Layers	In-Out Size	Stride
Input	$32 \times 32 \times 3$	
3×3 conv(n_f), $LipSwish$	$32 \times 32 \times n_f$	1
4×4 conv($2 * n_f$), $LipSwish$	$16 \times 16 \times (2 * n_f)$	2
4×4 conv($4 * n_f$), $LipSwish$	$8 \times 8 \times (4 * n_f)$	2
4×4 conv($4 * n_f$), $LipSwish$	$4 \times 4 \times (4 * n_f)$	2
4×4 conv(1)	$1 \times 1 \times 1$	1

Table 4: Network structures for EBM with data-space ($32 \times 32 \times 3$).

Energy-based Model ($64 \times 64 \times 3$)		
Layers	In-Out Size	Stride
Input	$64 \times 64 \times 3$	
3×3 conv(n_f), $LipSwish$	$64 \times 64 \times n_f$	1
4×4 conv($2 * n_f$), $LipSwish$	$32 \times 32 \times (2 * n_f)$	2
4×4 conv($4 * n_f$), $LipSwish$	$16 \times 16 \times (4 * n_f)$	2
4×4 conv($8 * n_f$), $LipSwish$	$8 \times 8 \times (8 * n_f)$	2
4×4 conv($8 * n_f$), $LipSwish$	$4 \times 4 \times (8 * n_f)$	2
4×4 conv(1)	$1 \times 1 \times 1$	1

Table 5: Network structures for EBM with data-space ($64 \times 64 \times 3$).

A.4 TRAINING

Data. The training image dataset are resized and scaled to $[-1, 1]$. We use 60,000, 70,000, 30,000, 50,000 observed examples for MNIST ($28 \times 28 \times 1$), SVHN ($32 \times 32 \times 3$), CelebA ($64 \times 64 \times 3$), and CIFAR-10 ($32 \times 32 \times 3$), respectively.

Glow. The parameters α of the flow model q_α are pre-trained following the configuration and reference implementation provided in (Kingma & Dhariwal, 2018). Note, for comparability the Glow models have been trained without spatial prior and with additive coupling layers. We refer to Appendix A.3 for a specification of the Glow model configuration.

EBM. The network parameters are initialized with Xavier (Glorot & Bengio, 2010) and optimized using Adam (Kingma & Ba, 2015) with $(\beta_1, \beta_2) = (0.99, 0.999)$. For NT-EBM, the learning rates used are 5e−5, 5e−5, 1e−5, 5e−5 for MNIST, SVHN, CelebA, CIFAR-10, respectively and a batch-size of 64 examples. For NCE-EBM, the learning rates used are 1e−5,1e−5,1e−5 for MNIST, SVHN, and CelebA, respectively, and a batch-size of 128 examples. For NT-EBM, in training the maximum number of parameter θ updates was $40,000$. For NCE-EBM, in training the maximum number of parameter θ updates was $80,000$.

HMC. We run Hamiltonian Monte Carlo (HMC) with persistent chains (Tieleman, 2008) initialized from q_α and 20 steps of MCMC and 3 leapfrog integrator steps per update of parameters of θ. The initial discretization step-size 0.15 with a simple adaptive policy multiplicatively increases or decreasing the step-size of the inner kernel based on the value of the Metropolis-Hastings acceptance rate (Andrieu & Thoms, 2008). The target acceptance-rate is set to 0.651 (Beskos et al., 2013). Figure 8 depicts the MH acceptance-rate and adaptive step-size over time.

Figure 8: Metropolis-Hastings acceptance rate (top) and adaptive step-size (bottom) over time.

FID. The Fréchet Inception Distance (FID) (Heusel et al., 2017) with Inception v3 classifier (Szegedy et al., 2016) was computed on $50,000$ generated examples with $50,000$ observed examples as reference.

A.5 SYNTHESIS

Figure 9 depicts samples from pre-trained flow q_α and samples from p_θ learned by neural transport MCMC for the dataset CIFAR-10 ($32 \times 32 \times 3$).

(a) Samples drawn from flow q_α by ancestral sampling.

(b) Samples drawn from p_θ by Hamiltonian neural transport.

Figure 9: Generated samples from a model learned by NT-EBM on CIFAR-10 ($32 \times 32 \times 3$).

A.6 GELMAN-RUBIN STATISTIC

The Gelman-Rubin statistic (Gelman et al., 1992; Brooks & Gelman, 1998) measures the convergence of Markov chains to the target distribution. It is based on the notion that if multiple chains have converged, by definition, they should appear "similar" to one another, else, one or more chains have failed to converge. Specifically, the diagnostic recruits an analysis of variance to access the difference between the between-chain and within-chain variances.

Let p denote the target distribution with mean $\mu \in \mathcal{R}$ and variance $\sigma^2 < \infty$. Gelman et al. (1992) designs two estimators of σ^2 and compares the square root of their ratio to 1. Let $X = \{X_{ij}, i = 1, \ldots, m, j = 1, \ldots, n\}$ denote m Markov chains of length n. Let $s_w^2 = \frac{1}{m} \sum_{i=1}^{m} \left[\frac{1}{n-1} \sum_{j=1}^{n} (X_{ij} - \bar{X}_{i\cdot})^2 \right]$ be the within-chain variance. The quantity s_w^2 underestimates σ^2 due to positive correlation in the Markov chain. Let $\hat{\sigma}^2 = \frac{n-1}{n} s^2 + \frac{s_b^2}{n}$ be a mixture of within-chain variance s_w^2 and between-chain variance $s_b^2 = \frac{n}{m-1} \sum_{j=1}^{m} (\bar{X}_{i\cdot} - \bar{X}_{\cdot\cdot})^2$. The quantity $\hat{\sigma}^2$ will overestimate σ^2, if an over-dispersed initial distribution for the Markov chains was used (Gelman et al., 1992). That is, s_w^2 underestimates while $\hat{\sigma}^2$ overestimates σ^2. Both estimators are consistent for σ^2 as $n \to \infty$ (Vats & Knudson, 2018). In light of this, the Gelman-Rubin statistic monitors convergence as the ratio $\hat{R} = \sqrt{\frac{\hat{\sigma}^2}{s^2}}$. Hence, $\hat{R}$ measures the degree to which variance (of the means) between chains exceeds what one would expect if the chains were identically distributed.

A.7 VERY LONG MARKOV CHAIN

In Figure 10 with p_θ learned on the CelebA ($64 \times 64 \times 3$) (Liu et al., 2015) dataset.

Figure 10: A single long-run Markov Chain with $n = 2,000$ steps depicted in 5 steps intervals sampled by Hamiltonian neural transport on CelebA ($64 \times 64 \times 3$).

Figure 11: A single long-run Markov Chain with $n = 2,000$ steps depicted in 5 steps intervals sampled by HMC neural transport for a model learned by NCE on SVHN ($32 \times 32 \times 3$).

Notice that NCE is the discriminator side of GAN. Similar to GAN, we can also improve the flow-based model based on the value function of GAN. This may further improve the NCE results. We leave improvements to this method to future investigations.