Applying Second Order Optimization to Deep Transformers with Parameter-Efficient Tuning

Abstract

Despite the theoretical superiority in convergence problem, second-order optimizers are generally not among the top choices for training large-scale neural networks due to their high computational and memory cost. Nevertheless, introduced in recent progress of parameter-efficient tuning is a new paradigm that large-scale pre-trained models (PTMs) can be adapted to specific tasks by optimizing a tiny proportion of parameters, which might hopefully change the game. We associate this new paradigm with the computational tractability of second-order optimizers and succeed in applying them to large PTMs from hundreds of millions of parameters to billions in scale. Beyond verifying their tractability, we further investigate the stability-influencing factors in the optimization process and propose accordingly a Newton-step clipping approach in which we clip the update tensors rather than the gradients. This approach stabilizes the convergence by gating the magnitude of Newton steps along the optimization trajectories through the rugged landscapes of deep transformers. We conduct extensive experiments across different downstream tasks, demonstrating that, when equipped with our Newton-step clipping, second-order optimizers, especially Kronecker-factored curvature approximation (K-FAC), can attain comparable and even superior results and faster convergence to those state-of-the-art bars implemented with AdamW. Furthermore, we scale the model up to 3 billion parameters and validate the tractability and effectiveness of our method. This work is not only the first successful application of second-order optimization on such enormous models but also paves the road towards more advanced design and analysis of optimizers for the downstream adaptation of large-scale PTMs.

1 Introduction

Pre-trained models (Bommasani et al., 2021; Han et al., 2021) (PTMs) based on deep transformers (Vaswani et al., 2017; Devlin et al., 2019; Raffel et al., 2020; Brown et al., 2020) yield remarkable performance on a wide range of tasks thanks to the tremendous capacity brought by numerous parameters. A prevalent paradigm is to firstly pre-train such models on large-scale corpora in a self-supervised manner and then adapt them to specific datasets (typically with supervision). Such adaptations are usually implemented by first-order gradient-based optimization. However, recent applications have witnessed an approaching bottleneck for first-order training – it is neither likely to be faster nor easy to attain higher scores (Pascanu et al., 2013; Goodfellow et al., 2016). On the other hand, second-order optimizers which enjoy better convergence properties might have been an ideal alternative in theory (Nocedal & Wright, 1999; Boyd et al., 2004). They are, nevertheless, almost unattended on the downstream adaptation of PTMs in practice. It is because they require quadratic storage and cubic computation time for each update, which is especially prohibitive given the enormous model scale, even though bunches of their simplified counterparts have been devised (Byrd et al., 1995; Martens & Grosse, 2015; Botev et al., 2017; Anil et al., 2020; Tang et al., 2021).

Hopefully, recent advances in PTMs have brought a slight twist to the situation. Studies show that full-parameter optimization may not be necessary for task-specific adaptations, as updating a small portion (0.05%~1%) of parameters can achieve non-trivial performance in many datasets (Houlsby et al., 2019; Li & Liang, 2021; Lester et al., 2021; Hu et al., 2021). With the new paradigm largely shrinking the trainable parameter space, we find in experiments that second-order optimization is

now tractable on large-scale PTMs with up to billions of parameters. This successful implementation further triggers a sequence of interesting research topics. How tractable are second-order optimizers on deep transformers? Are they capable of converging faster and more steadily and obtaining better results? If not, what auxiliary skills are needed? And also, how does the ratio of trainable parameters influence the relative performance of second-order optimizers?

In this paper, we attempt to answer all the aforementioned questions through theoretical justification and experimental verification. Taking K-FAC as the major example of the second-order optimizer, we first experimentally verify that its memory cost on extremely large PTMs is totally acceptable under control. In addition, we clarify that our newly-proposed Newton-step clipping strategy can stabilize second-order training to a significant extent. We then post comprehensive results to show that with the assistance of Newton-step clipping, second-order optimization outperforms its first-order counterparts in both convergence speed and final test scores. Moreover, we scale the model scale up to 3 billion parameters to evaluate the tractability and effectiveness. Thought-provoking observations of the relation between tunable ratio and convergence speed are also presented subsequently.

2 SECOND-ORDER OPTIMIZERS FOR LARGE-SCALE TRAINING

Following the introductory part, we recap the essential background of second-order optimization. While first-order optimizers such as stochastic gradient descent (SGD) and Adam (Kingma & Ba, 2014) have been more than ubiquitous in deep learning, second-order optimizers remain relatively under-explored in this field. Unlike their first-order counterparts, which take only first-order derivatives into account, second-order optimizers will in addition incorporate the loss function's second-order features, or, in other words, the curvature information.

2.1 NEWTON'S METHOD AND ITS VARIANTS

Newton's method and its variants are perhaps the most typical second-order optimization skills. To be specific, in Newton's method, we approximate the loss function with its Taylor expansion up to order 2:

$$L(\boldsymbol{\theta} + \delta\boldsymbol{\theta}) \approx L(\boldsymbol{\theta}) + \nabla_{\boldsymbol{\theta}} L(\boldsymbol{\theta})^T \delta\boldsymbol{\theta} + \frac{1}{2}\delta\boldsymbol{\theta}^T \nabla_{\boldsymbol{\theta}}^2 L(\boldsymbol{\theta})\delta\boldsymbol{\theta}$$
$$\triangleq L(\boldsymbol{\theta}) + \boldsymbol{g}(\boldsymbol{\theta})^T \delta\boldsymbol{\theta} + \frac{1}{2}\delta\boldsymbol{\theta}^T \boldsymbol{H}(\boldsymbol{\theta})\delta\boldsymbol{\theta}, \tag{1}$$

in which $\boldsymbol{g}(\boldsymbol{\theta})$ and $\boldsymbol{H}(\boldsymbol{\theta})$ are the gradient and Hessian matrix of L at θ respectively. We then hope to move towards the direction in which the quadratic function on the right-hand side of Equation 1 is minimized. This condition implies that the standard Newton's method should proceed as

$$\boldsymbol{\theta}_{t+1} \leftarrow \boldsymbol{\theta}_t - \eta_t \boldsymbol{H}(\boldsymbol{\theta}_t)^{-1}\boldsymbol{g}(\boldsymbol{\theta}_t), \tag{2}$$

where η_t is the learning rate for the t-th step. The quantity $\boldsymbol{u} = \boldsymbol{H}^{-1}\boldsymbol{g}$ is usually called a Newton step.

Despite the theory that fewer steps are required for convergence, the original Newton's method has long been criticized for high computation and storage costs in calculating the Hessian matrix, inverting it, and other additional matrix manipulations (Nocedal & Wright, 1999; Boyd et al., 2004). To remedy this deficiency of speed, amazing increments of Newton's method have been proposed successively in recent centuries. Included are those reducing the cost by using an approximation of the Hessian matrix (Levenberg, 1944; Marquardt, 1963; Botev et al., 2017), and those quasi-Newton optimizers such as BFGS (Broyden, 1970; Fletcher, 1970; Goldfarb, 1970; Shanno, 1970) and its limited-memory version L-BFGS (Byrd et al., 1995) which approximate the inverse of Hessian matrix directly. Those aforementioned methods can partly alleviate the intractability of full Newton's method on deep neural networks.

2.2 NATURAL GRADIENT DESCENT AND K-FAC

In a common situation of supervised learning, a class of parametric conditional distribution $\{p(y \mid x, \boldsymbol{\theta}) \mid \boldsymbol{\theta} \in \Theta\}$ is assigned to the model to fit the underlying distribution $q(y \mid x)$ of the observed data. Kullback-Leibler divergence (Kullback & Leibler, 1951) $L(\boldsymbol{\theta}) = \mathcal{D}_{KL}[q(x,y)\|p(x,y \mid \boldsymbol{\theta})]$ between the two joint distributions, or up to an additive constant, the negative log-likelihood, is

usually selected as the loss function to be minimized. Natural gradient descent suggests an update direction satisfying

$$\boldsymbol{u}(\boldsymbol{\theta}) = \lim_{\varepsilon \to 0^+} \frac{1}{\varepsilon} \underset{\mathcal{D}[p(x,y|\boldsymbol{\theta})\|p(x,y|\boldsymbol{\theta}+\delta\boldsymbol{\theta})]\leq\varepsilon^2}{\arg\min} L(\boldsymbol{\theta}) \qquad (3)$$

$$= -\kappa \boldsymbol{F}(\boldsymbol{\theta})^{-1} \nabla L(\boldsymbol{\theta}), \qquad (4)$$

where κ is a positive constant and

$$\boldsymbol{F}(\boldsymbol{\theta}) = \mathbb{E}_{p(x,y|\boldsymbol{\theta})}[\nabla \log p(x, y \mid \boldsymbol{\theta})^T \nabla \log p(x, y \mid \boldsymbol{\theta})], \qquad (5)$$

is known as the Fisher information matrix (FIM) of $p(x, y \mid \boldsymbol{\theta})$. Since the true FIM is generally not accessible, it is a common practice to evaluate the empirical FIM (Martens, 2020) instead, that is, to evaluate

$$\hat{\boldsymbol{F}}(\boldsymbol{\theta}) \triangleq \mathbb{E}_{\hat{q}(x,y)}[\nabla_{\boldsymbol{\theta}} \log p(x, y \mid \boldsymbol{\theta})^T \nabla_{\boldsymbol{\theta}} \log p(x, y \mid \boldsymbol{\theta})], \qquad (6)$$

in which $\hat{q}$ is the empirical distribution of the observed samples.

Interestingly, when current distribution $p(\cdot \mid \boldsymbol{\theta})$ and target distribution q are close to each other, we have $\nabla_\theta^2 L(\boldsymbol{\theta}) \approx \boldsymbol{F}(\boldsymbol{\theta})$. This relation sheds light on the connection between Newton's method and natural gradient descent, in the sense that natural gradient descent can be conceived as a special Newton's method with approximate Hessian matrices. For this reason, we do not distinguish natural gradient descent from Newton's method in the rest of the paper and also call the update in equation 4 a *Newton step* or *Newton update*.

Vanilla natural gradient descent suffers from the same inefficiency with full Newton's method. Compared to the numerous increments of Newton's method, few improvements for natural gradient descent have ever been devised, among which is the enlightening work of Kronecker-factored approximate curvature (K-FAC) (Martens & Grosse, 2015). K-FAC specializes in optimizing the weights only involved once in linear mapping, including the weights of fully-connected linear projection and convolutional operation (Grosse & Martens, 2016; Martens et al., 2018). The core idea of K-FAC is the approximate evaluation of empirical FIM $\hat{\boldsymbol{F}}(\boldsymbol{\theta})$ taking advantage of the properties of Kronecker products. To be specific, it approximates the expectation of the Kronecker product with the Kronecker product of expectation. In this way, the computation and storage burden is greatly relieved without simplifying the second-order structures too much. K-FAC has been proved a promising optimizer across various deep learning models and tasks (Martens & Grosse, 2015; Grosse & Martens, 2016; Martens et al., 2018; Wu et al., 2017; Osawa et al., 2019), and will be the major second-order optimizer we implement and analyze in this paper. More details about natural gradient descent and K-FAC can be found in appendix A.

3 PARAMETER-EFFICIENT TUNING ENABLES SECOND-ORDER TRAINING

In the foregoing section, we have introduced typical second-order optimizers together with incremental methods which ameliorate their efficiency in large-scale settings. In spite of that amelioration, second-order optimization still requires at least $N^2 \sim N^3$ order of storage space and computing operations and is therefore intractable on extremely large models, especially those foundation language models based on deep transformers. For example, it is unlikely a possible mission to fine-tune a T5$_{\text{XL}}$ with either L-BFGS or K-FAC directly. The sad truth informs us that, beyond making second-order optimizers lighter and faster, more modifications should be made to the way we train. While hardly any further improvements could be made to the optimizers, cutting down the volume of the trainable parameters might be another way out. This straightforward thought coincides with a new paradigm in the spotlight – *parameter-efficient tuning* – including adapter, LoRA, and other useful methods, which we will explain in detail in the following passage.

3.1 BACKGROUND OF PARAMETER-EFFICIENT TUNING

Parameter-efficient tuning aims to adapt PTMs, especially large ones, via optimizing a tiny proportion of parameters. This intuition could also be found in previous works under other scenarios (Tajbakhsh et al., 2016; Guo et al., 2020; 2019). The most practical advantage of such a paradigm is that we do not need to update all the parameters and produce separate fine-tuned instances for every downstream task.

Table 1: Peak memory consumption of different models with first- and second-order optimization. #P denotes the number of total parameters, and #T denotes trainable parameters. All the numbers are measured on the RTE dataset with LoRA with a single NVIDIA A100 GPU, batch size = 16.

Model	#P	#T	Optim.	Mem.
BERT	336M	0.75M	1st	4.22 GB
			2nd	4.99 GB
RoBERTa	355M	0.75M	1st	4.32 GB
			2nd	5.08 GB
T5$_{base}$	220M	0.56M	1st	2.05 GB
			2nd	2.49 GB
T5$_L$	770M	1.50M	1st	6.00 GB
			2nd	7.53 GB
T5$_{XL}$	3B	3.75M	1st	20.94 GB
			2nd	34.00 GB

Figure 2: An example of GPU memory variation during training on the STS-B dataset with adapters. The used model is RoBERTa$_{large}$ and the batch size is 128. Both experiments are run on a single NVIDIA A100 GPU.

By training such lightweight parameters, we are able to flesh out the abstract ability of large-scale models to solve specific problems. Houlsby et al. (2019) injects small neural modules to each layer of the Transformer model and only optimizes the adapters in training. Subsequently, a series of variants of adapters have emerged (Pfeiffer et al., 2020; Sung et al., 2021; Mahabadi et al., 2021; Sung et al., 2022). Prefix and prompt tuning (Li & Liang, 2021; Lester et al., 2021) prepends tunable parameters to the input layers. LoRA (Hu et al., 2021) injects low-rank trainable decomposition matrices to the weights and is successfully applied to GPT-3 (Brown et al., 2020) with 175 billion parameters. Apart from introducing additional parameters, experiments show that optimizing a designated proportion of the inherent parameters produce a similar effect (Zhao et al., 2020; Zaken et al., 2021; Guo et al., 2021). This line of work implies that after massive pre-training, the adaptation of large-scale PTMs may be a "simple" process and is worth further exploring (He et al., 2022; Ding et al., 2022).

Adapter. The adapter (Houlsby et al., 2019) method inserts lightweight neural modules (adapter layer) to each layer of the Transformer model. Given the input hidden state $\boldsymbol{h}_{in} \in \mathbb{R}^d$, each adapter layer comprises a down-projection $\boldsymbol{D} \in \mathbb{R}^{d \times r}$, a non-linear activation function $\sigma(\cdot)$, and an up-projection $\boldsymbol{U} \in \mathbb{R}^{r \times d}$. There is also a residual connection from the input to the output of an adapter layer.

$$\boldsymbol{h}_{out} \leftarrow \sigma(\boldsymbol{h}_{in}\boldsymbol{D})\boldsymbol{U} + \boldsymbol{h}_{in}. \tag{7}$$

The position of adapter layers is optional. Houlsby et al. (2019) add them after the multi-head attention layer and the feed-forward layer of each Transformer block. There are also variants that add adapter modules to other positions like the LayerNorm layer (Pfeiffer et al., 2020). Depending on the size of the bottleneck dimension r, the tunable parameters of the adapter approach account for roughly 0.5%~8% of the total number of parameters.

LoRA. The LoRA method (Hu et al., 2021) assumes that the change of each weight matrix is intrinsically low-rank, thus it injects tunable low-rank decomposition matrices $\boldsymbol{D} \in \mathbb{R}^{d \times r}, \boldsymbol{U} \in \mathbb{R}^{r \times d}$ to estimate the weight changes $\Delta \boldsymbol{W} = \boldsymbol{DU}$. Hence, the output hidden state is

$$\boldsymbol{h}_{out} \leftarrow \boldsymbol{h}_{in}(\boldsymbol{W} + \boldsymbol{D})\boldsymbol{U}, \tag{8}$$

where $\boldsymbol{W}$ is the initial weight matrix. Depending on the intrinsic rank r, the optimizable parameters of LoRA are normally less than 1% of the total parameters.

3.2 PARAMETER-EFFICIENT TUNING ENABLES SECOND-ORDER TRAINING

Having introduced the background in second-order optimization and parameter-efficient tuning and clarified our motivation for integrating them, we move on to verify through experiments that parameter-efficient tuning can indeed enable second-order optimization on large-scale PTMs. As shown in Table 1, PTMs with different architectures and scales could be tractably adapted with a single NVIDIA

A100 GPU. It is worth noting that the excess memory consumption resulting from second-order optimization is relatively low compared to the whole memory consumption. As the model scales, the absolute amount of parameters to be fine-tuned increases, and the memory footprint of the second-order optimization increases considerably. For example, in T5$_{XL}$, the second-order optimization takes up 13.06 GB more video memory than the first-order optimization. However, this is still acceptable in practice. We report an example of the GPU memory variation in Figure 2, which has a jagged shape over the training time. At low points, all the data is sent to the CPU for processing, leaving only the parameters of the model itself and the states in the optimizer in GPU. The gap between the first- and second-order optimization's memory usage at the low point reflects the volume difference in states of optimizers.

4 NEWTON-STEP CLIPPING STABILIZES SECOND-ORDER TRAINING

The mere combination of second-order optimization and parameter-efficient tuning is still far from training smoothly. We reveal both in theory and by experiments that one new auxiliary skill, which we call Newton-step clipping, has to be implemented to achieve satisfactory results. In this section, we first introduce a more traditional stabilizing strategy named gradient clipping. We will afterward clarify the divergence between gradient clipping and Newton-step clipping and justify our initiative of devising and applying this new approach.

4.1 GRADIENT CLIPPING

One crucial point for a smoother training experience is to manage your step-sizes (norms of update tensors) wisely. However, unlike the cases in toy tasks, it is of low efficiency to apply delicate step-size schedules, such as line search with Wolfe (Wolfe, 1969) and Armijo-Goldstein (Armijo, 1966) conditions, to large models like a deep-transformer-based PTM. Such low efficiency is partially ascribed to high computational cost, and, more substantially, to the nonconvex landscape that invalidates the theoretical benefit of taking those schedules. Mostly adopted in deep learning is to set up a fixed learning rate schedule for all layers at the beginning of a training process. But, this solution may not be flexible enough and may result in gradient explosion problem since the optimal step-sizes for different layers can typically be different.

Two strategies – adaptive gradient and gradient clipping – have been devised in previous works to tackle this issue. AdaGrad (Hinton et al., 2011), RMSProp (Duchi et al., 2012), Adam (Kingma & Ba, 2014), and other optimizers adopting the adaptive gradient strategy divide the first-order term by the square root of the second-order term to ensure that the magnitude of each layer's step-size automatically remains in a rather stable range highly irrelevant to the gradient norm. Compared to the adaptive gradient methods, gradient-clipping (Pascanu et al., 2013; Goodfellow et al., 2016) is a more straightforward approach to set off the influence of extremely rugged landscapes. In this approach, a gradient vector is clipped whenever its norm exceeds a fixed threshold, that is,

$$\boldsymbol{g}^{clp} \leftarrow \min\left\{1, \frac{\tau}{||\boldsymbol{g}||}\right\}\boldsymbol{g}. \tag{9}$$

This approach is designed mostly by intuition to conquer the high-curvature landscape in deep learning, especially indispensable for some NLP-specialized models (Pascanu et al., 2013). Apart from the stabilizing effect, more of its advantages are subsequently explored and proved, such as faster convergence (Zhang et al., 2019) and prevention of convergence to stationary points (Chen et al., 2020).

4.2 NEWTON-STEP CLIPPING

In fact, the term "gradient clipping" can be misleading. We claim that the underlying purpose of performing "gradient clipping" is to restrict the scale of the update tensor, NOT the gradient as is literally suggested. It is noteworthy that gradient clipping is usually applied to first-order methods, especially SGD and its variants. For these optimizers, the stepsize is proportional to the gradient norm, and hence clipping the gradient is equivalent to restricting the scales of updates. Nevertheless, for second-order optimizers, this rule may not hold. For instance, in likelihood maximization with natural gradient descent, the gradient $\boldsymbol{g} = -\mathbb{E}_{\hat{q}}[\nabla \log p(\cdot \mid \boldsymbol{\theta})]$ is further preconditioned by the empirical FIM which reads

$$\hat{\boldsymbol{F}} = \mathbb{E}_{\hat{q}(x,y)}[\nabla_{\boldsymbol{\theta}} \log p(x, y \mid \boldsymbol{\theta})^T \nabla_{\boldsymbol{\theta}} \log p(x, y \mid \boldsymbol{\theta})]. \tag{10}$$

Figure 4: Training loss curve of K-FAC optimizer on RoBERTa$_{\text{large}}$ + Adapter with and without our Newton-step clipping approach. All settings and hyperparameters are the same except for whether or not to use Newton-step clipping.

In reality, every updating step is conducted within a mini-batch $\{(x_i, y_i) \mid i = 1, ..., B\}$ from which a gradient tensor

$$\boldsymbol{G} = [-\nabla \log p(x_1, y_1 \mid \boldsymbol{\theta}), \cdots, -\nabla \log p(x_1, y_1 \mid \boldsymbol{\theta})] \triangleq [\boldsymbol{g}_1, \cdots, \boldsymbol{g}_B] \tag{11}$$

is first figured out. Gradient and empirical FIM are subsequently obtained by

$$\boldsymbol{g} = \frac{1}{B} \boldsymbol{G} \mathbf{1}_B, \quad \hat{\boldsymbol{F}} = \frac{1}{B} \boldsymbol{G} \boldsymbol{G}^T. \tag{12}$$

We can now conclude that the magnitude of Newton update $\boldsymbol{u}$ in this case is reciprocal to the gradient norm:

$$||\boldsymbol{u}|| = ||\hat{\boldsymbol{F}}^{-1}\boldsymbol{g}|| = \mathcal{O}(||\boldsymbol{g}||^{-1}). \tag{13}$$

Consequently, it is problematic to associate large gradient norm with large step size in natural gradient descent. A similar problem persists among general second-order optimizers due to the precondition of gradients by either Hessian matrices or FIMs. Hence, gradient clipping, though intuitively correct, may fails to improve the stability in second-order optimization. To address this issue, we propose Newton-step-clipping in which we clip the Newton update $\boldsymbol{u} = \boldsymbol{H}^{-1}\boldsymbol{g}$ (or $\boldsymbol{u} = \hat{\boldsymbol{F}}^{-1}\boldsymbol{g}$) rather than the original gradient $\boldsymbol{g}$, that is,

$$\boldsymbol{u}^{clp} \leftarrow \min\left\{1, \frac{\tau}{||\boldsymbol{u}||}\right\} \boldsymbol{u}. \tag{14}$$

Figure 3: An illustration of the Newton-step clipping strategy.

τ, standing for the maximum update norm, is a hyperparameter to be tuned. We conduct experiments with different τ and discover that $\tau = 0.1$ and $\tau = 1.0$ can work well in a wide range of settings. Series of experimental results shown in Figure 4 verify that for large-scale second-order optimization, the strategy of Newton-step clipping significantly stabilizes the training process and outperforms its non-clipping counterpart.

4.3 GENERALIZATIONS: PRE-CLIPPING AND POST-CLIPPING

We can generalize our approach as follows. In derivative-based optimization, gradient plays a major role. However, the weight (or parameter) is seldom updated directly by its corresponding gradient; most optimizers will further transform the gradient into a final update tensor. Newton's method makes a case in point. It left-multiplies the gradient with the inverse of Hessian to yield a final Newton step. Then a divergence emerges in the question that when is the appropriate time for clipping. The vanilla gradient clipping strategy clips the gradients as soon as the gradients are figured out. This sounds reasonable for SGD, feasible for Adam, but problematic for K-FAC. A different measure is not to clip anything until the final updates have been transformed from the original gradients. According to their time of clipping, we name the two aforementioned approaches pre-clipping and post-clipping by convenience. Procedures of pre-clipping and post-clipping are summarized in algorithm 1. In a word,

---

Algorithm 1: Generalized procedures of pre-clipping and post-clipping

---

Data: Total iteration T, current iteration t, current batch $|\mathcal{B}_t|$, current learning rate η_t;

while $t \leq T$ **do**

    Compute and store gradient $\boldsymbol{g}_t \leftarrow \frac{1}{\mathcal{B}_t} \sum_{x \in \mathcal{B}_t} \nabla_{\boldsymbol{\theta}} L(x, \theta)$ and other required quantities $\boldsymbol{h}_t$;

    if *pre-clipping* **then**

        $\boldsymbol{g}_t \leftarrow \min\left\{1, \frac{\tau}{||\boldsymbol{g}_t||}\right\} \boldsymbol{g}_t$;

    Compute other required quantities $\boldsymbol{r}_t$;

    Transform the gradient to the final update: $\boldsymbol{u}_t \leftarrow \mathcal{T}(\boldsymbol{g}_t, \boldsymbol{h}_t, \boldsymbol{r}_t)$;

    if *post-clipping* **then**

        $\boldsymbol{u}_t \leftarrow \min\left\{1, \frac{\tau}{||\boldsymbol{u}_t||}\right\} \boldsymbol{u}_t$;

    Update the parameter $\boldsymbol{\theta} \leftarrow \boldsymbol{\theta} - \eta_t \boldsymbol{u}_t$.

---

we have explained in the above passage that the choices of when to clip and what to clip can lead to entirely different training results. Although second-order optimizers favor later clipping upon the Newton step, for most of the rest of the optimizers that have ever been proposed, the choices between pre-clipping and post-clipping remain a mystery to be explored in the future.

5 EVALUATION OF EFFECTIVENESS

In this section, we evaluate and analyze our approach with corresponding baselines across widely used natural language understanding (NLU) tasks and different backbone PLMs.

5.1 EXPERIMENTAL SETTINGS

Datasets. The evaluated benchmarks in our experiments include SST-2 (Socher et al., 2013) for sentiment analysis, MRPC (Dolan & Brockett, 2005) for paragraph detection, CoLA (Warstadt et al., 2019) for inference acceptability, RTE (Dagan et al., 2005) for inference, QNLI (Rajpurkar et al., 2016) for inference, STS-B (Cer et al., 2017) for textual similarity, Choice of Plausible Alternatives (COPA) (Gordon et al., 2012) for commonsense causal reasoning, CommitmentBank (CB) (Marneffe et al., 2019) for inference, and Winograd Schema Challenge (WSC) (Levesque, 2011) for commonsense reasoning.

Setup. We adopt RoBERTa_large (Liu et al., 2019) with 350 million parameters for QNLI, SST-2, RTE, COLA, MRPC, and STS-B; and T5-3b (Raffel et al., 2020) with 3 billion parameters for COPA, CB, RTE, and WSC. The project and second-order optimizers are implemented by PyTorch (Paszke et al., 2019), and the used models are loaded from the Huggingface Transformers (Wolf et al., 2019) library. We use NVIDIA Tesla A100 with 40GB memory for all experiments.

Evaluation. Most datasets use accuracy as evaluation metrics, except for MRPC, CoLA, and STS-B. MRPC uses F1 scores. CoLA uses Matthew correlation coefficient (Matthews, 1975). Spearman correlation and Pearson correlation scores are reported on STS-B.

5.2 EXPERIMENTAL RESULTS

Experimental results of natural language understanding are reported in Table 2. We mainly compare our approach with AdamW (Loshchilov & Hutter, 2017), which is broadly considered as the most powerful optimization method for deep transformers. Most of the parameter-efficient adaptations achieve on-par performances to full parameter fine-tuning. With both the adapter and LoRA approaches, second-order optimization with our Newton-step clipping considerably outperforms the AdamW counterparts. Specifically, in direct comparisons, with the adapter method, the average performance in six tasks of NewtwonClip outperforms AdamW by 1.06%. And with the LoRA method, the absolute improvement is 1.25%. We also observe that the performance gap is mainly reflected in RTE, COLA, and MRPC datasets, which are also generally considered to be the more difficult natural language understanding task than the other three tasks.

Table 2: Results on NLU tasks. † indicates the results are from previously published work, and a, b, and c indicate different amounts of trainable parameters. Blue and orange represent the best and second best performances of each column.

Method	#Trainable params	QNLI	SST-2	RTE	COLA	MRPC	STS-B	Avg.
RoBERTa$_{base}$	125M (100%)	92.8	94.8	78.7	63.6	90.2	91.2	85.22
RoBERTa$_{large}$	355M (100%)	94.7	96.4	86.6	68.0	90.9	92.4	88.17
RoBERTa$_{large}$ + Adapter								
AdamW^{†a}	6.0M (1.69%)	$94.7_{\pm0.2}$	$96.2_{\pm0.3}$	$83.4_{\pm1.1}$	$66.5_{\pm4.4}$	$88.7_{\pm2.9}$	$91.0_{\pm1.7}$	86.75
AdamW^{†b}	3.0M (0.84%)	$94.8_{\pm0.2}$	$96.1_{\pm0.3}$	$83.8_{\pm2.9}$	$68.3_{\pm1.0}$	$90.2_{\pm0.7}$	$91.5_{\pm1.5}$	87.45
AdamW^{†c}	0.8M (0.23%)	$94.7_{\pm0.2}$	$96.3_{\pm0.5}$	$72.9_{\pm2.9}$	$66.3_{\pm2.0}$	$87.7_{\pm1.7}$	$91.5_{\pm0.5}$	84.90
AdamW	2.4M (0.67%)	$94.5_{\pm0.3}$	$95.6_{\pm0.2}$	$84.6_{\pm2.2}$	$64.9_{\pm8.2}$	$91.8_{\pm1.2}$	$91.9_{\pm0.5}$	87.22
NewtonClip	2.4M (0.67%)	$94.3_{\pm0.4}$	$96.3_{\pm0.4}$	$86.8_{\pm1.5}$	$68.4_{\pm1.3}$	$92.3_{\pm1.9}$	$91.6_{\pm0.3}$	**88.28**
RoBERTa$_{large}$ + LoRA								
AdamW†	0.8M (0.23%)	$94.8_{\pm0.3}$	$96.2_{\pm0.5}$	$85.2_{\pm1.1}$	$68.2_{\pm1.9}$	$90.2_{\pm1.0}$	$92.3_{\pm0.5}$	87.82
AdamW	0.8M (0.23%)	$94.1_{\pm0.6}$	$95.4_{\pm0.7}$	$82.5_{\pm0.9}$	$69.1_{\pm2.7}$	$91.1_{\pm0.2}$	$91.6_{\pm0.7}$	87.30
NewtonClip	0.8M (0.23%)	$94.4_{\pm0.1}$	$96.2_{\pm0.3}$	$85.7_{\pm1.7}$	$70.4_{\pm1.8}$	$92.7_{\pm0.3}$	$91.9_{\pm0.3}$	**88.55**

As illustrated in Figure 5, equipped with Newton-step clipping, K-FAC demonstrates faster and more stable convergence than the first-order optimizer AdamW. Despite the effectiveness, the hyperparameter tuning of K-FAC is slightly more costly than that of AdamW since the second-order optimizer itself is more sensitive to the learning rate and also involves more hyperparameters such as the scale of clipping. We will investigate adaptive techniques for Newton-step clipping in future work to better deploy second-order optimization to PTM adaptations.

Figure 5: Training loss curve of RoBERTa$_{large}$ + Adapter on NLU tasks with AdamW optimizer and K-FAC optimizer equipped with our Newton-step clipping strategy.

5.3 IMPACT OF THE NUMBER OF TRAINABLE PARAMETERS

To explore the impact of trainable parameters to our method, we train a RoBERTa$_{large}$ + LoRA with different LoRA intrinsic ranks (i.e., the bottleneck dimension r of D, U in equation 8) on the MRPC dataset. When linearly choosing r in $\{8, 12, 16, 20, 24, 28, 32\}$, the amount of trainable parameters becomes $\{0.8M, 1.1M, 1.5M, 1.9M, 2.3M, 2.6M, 3.0M, 3, 4M\}$, respectively (we conduct 3 runs with different random seeds for each LoRA rank). However, as illustrated in Figure 6 and Figure 7, the convergence speed is observably inversely proportional to the number of trainable parameters, i.e., the smaller the number of trainable parameters, the faster the convergence speed. Meanwhile, we observe that the test performance does not change significantly as the number of trainable parameters changes. For a PTM and a specific task, the adaptation process is "simple" that it can be

accomplished with very few parameter optimizations, but it is difficult to make a leap in adaptation performance by changing the number of training parameters. In other words, the pre-training, model structure, and scale of the model itself seem to determine the upper limit of practical adaptations. The fact that using fewer parameters leads to faster convergence is also a testament to the effectiveness of our Newton-step clipping approach.

Figure 6: Training loss curve of models with different LoRA ranks. Experiments are conducted on MRPC with RoBERTa$_{large}$ and batch size is 128.

Figure 7: The change of test metrics (F1) and number of trainable parameters with different LoRA ranks. Experiments are conducted on MRPC with RoBERTa$_{large}$, batch size is 128.

5.4 SCALING TO 3 BILLION PARAMETERS

We scale our experimentation to T5$_{XL}$, a sequence-to-sequence model with 3 billion parameters. Evaluated datasets in this part are relatively small due to high training costs. As shown in Table 3, K-FAC with the proposed Newton-step clipping can achieve comparable performance with AdamW. For some datasets like RTE and WSC, our method even outperforms its first-order counterpart by a considerable margin.

Table 3: Results on COPA, CB, WiC, and WSC datasets of T5$_{XL}$ + Adapter.

Method	COPA	CB	RTE	WSC	Avg.
AdamW	82.00	89.29	79.86	67.31	79.62
NewtonClip	80.00	89.29	82.01	69.23	**80.13**

We also empirically find that larger models tend to favor larger maximum norms for Newton-step clipping due to the vast capacity. The success of K-FAC on T5$_{XL}$ further demonstrates its tractability under parameter-efficient tuning paradigm, and its potential in efficiently steering large pre-trained models.

6 DISCUSSION

Theoretical analysis and experimental results are presented in this paper, illustrating that the parameter-efficient paradigm can vivify second-order optimization on extremely large-scale PTMs with the assistance of the Newton-step clipping strategy. Although the application of second-order optimization on enormous PTMs is promising, the exploration is yet far from closed in the sense that pieces of dark clouds are still hanging over this topic. (1) To begin with, as we have observed in our experiments, second-order optimizers exhibit higher sensitivity to the choices of hyper-parameters compared to their first-order counterparts. While second-order optimizers tend to introduce more hyper-parameters, many of these newly-added hyper-parameters are more obscured in mathematical meaning and their experimental influence is more elusive. It remains unclear whether there are theories and methods to make the hyper-parameter tuning of second-order optimization no longer a sort of dark art. (2) Another uncertainty lies in the question that whether the design of architecture-specified optimizers is feasible. We notice in current work that both adapter and LoRA add to the original model fully-connected feed-forward branches which coincide with K-FAC's strength. But, for the other parameter-efficient methods like modifications of each head of attention output in Prefix Tuning, no similar conclusion has yet been drawn. (3) Moreover, it appears promising to study the combination of first-order or second-order optimization instead of sticking merely to one. Observed in our experiments is the rule of thumb that first-order optimizers, though with slower loss descent and lower test scores, enjoy better numerical and convergence stability. It is a natural deduction to run first-order steps as the warm-up period for second-order optimization. Seemingly trivial at first glance, the design of first and second-order compounds is bound to be an arduous journey of in-detail technical implementation.

REFERENCES

Rohan Anil, Vineet Gupta, Tomer Koren, Kevin Regan, and Yoram Singer. Scalable second order optimization for deep learning. *arXiv preprint arXiv:2002.09018*, 2020.

Larry Armijo. Minimization of functions having lipschitz continuous first partial derivatives. *Pacific Journal of mathematics*, 16(1):1–3, 1966.

Rishi Bommasani, Drew A Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, et al. On the opportunities and risks of foundation models. *arXiv preprint arXiv:2108.07258*, 2021.

Aleksandar Botev, Hippolyt Ritter, and David Barber. Practical gauss-newton optimisation for deep learning. In *International Conference on Machine Learning*, pp. 557–565. PMLR, 2017.

Stephen Boyd, Stephen P Boyd, and Lieven Vandenberghe. *Convex optimization*. Cambridge university press, 2004.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

Charles George Broyden. The convergence of a class of double-rank minimization algorithms 1. general considerations. *IMA Journal of Applied Mathematics*, 6(1):76–90, 1970.

Richard H Byrd, Peihuang Lu, Jorge Nocedal, and Ciyou Zhu. A limited memory algorithm for bound constrained optimization. *SIAM Journal on scientific computing*, 16(5):1190–1208, 1995.

Daniel Cer, Mona Diab, Eneko Agirre, Iñigo Lopez-Gazpio, and Lucia Specia. SemEval-2017 task 1: Semantic textual similarity multilingual and crosslingual focused evaluation. In *Proceedings of SemEval-2017*, pp. 1–14, August 2017.

Xiangyi Chen, Steven Z Wu, and Mingyi Hong. Understanding gradient clipping in private sgd: A geometric perspective. *Advances in Neural Information Processing Systems*, 33:13773–13782, 2020.

Ido Dagan, Oren Glickman, and Bernardo Magnini. The pascal recognising textual entailment challenge. In *Machine Learning Challenges Workshop*, pp. 177–190. Springer, 2005.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of NAACL*, June 2019.

Ning Ding, Yujia Qin, Guang Yang, Fuchao Wei, Zonghan Yang, Yusheng Su, Shengding Hu, Yulin Chen, Chi-Min Chan, Weize Chen, et al. Delta tuning: A comprehensive study of parameter efficient methods for pre-trained language models. *arXiv preprint arXiv:2203.06904*, 2022.

William B. Dolan and Chris Brockett. Automatically constructing a corpus of sentential paraphrases. In *Proceedings of IWP Workshop*, 2005.

John Duchi, Nikhil Elad Srivastava, and Kelvin Swersky. Lecture 6d - a separate, adaptive learning rate for each connection. *Slides of Lecture Neural Networks for Machine Learning*, 2012.

Roger Fletcher. A new approach to variable metric algorithms. *The computer journal*, 13(3):317–322, 1970.

Donald Goldfarb. A family of variable-metric methods derived by variational means. *Mathematics of computation*, 24(109):23–26, 1970.

Ian Goodfellow, Yoshua Bengio, Aaron Courville, and Yoshua Bengio. *Deep learning*, volume 1. MIT Press, 2016.

Andrew Gordon, Zornitsa Kozareva, and Melissa Roemmele. SemEval-2012 task 7: Choice of plausible alternatives: An evaluation of commonsense causal reasoning. In **SEM 2012: The First Joint Conference on Lexical and Computational Semantics – Volume 1: Proceedings of the main conference and the shared task, and Volume 2: Proceedings of the Sixth International Workshop on Semantic Evaluation (SemEval 2012)*, pp. 394–398, 2012.

Roger Grosse and James Martens. A kronecker-factored approximate fisher matrix for convolution layers. In *Proceedings of ICML*, pp. 573–582. PMLR, 2016.

Demi Guo, Alexander Rush, and Yoon Kim. Parameter-efficient transfer learning with diff pruning. In *Proceedings of the ACL*, pp. 4884–4896, Online, 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.acl-long.378.

Yunhui Guo, Honghui Shi, Abhishek Kumar, Kristen Grauman, Tajana Rosing, and Rogerio Feris. Spottune: transfer learning through adaptive fine-tuning. In *Proceedings of CVPR*, pp. 4805–4814, 2019.

Yunhui Guo, Yandong Li, Liqiang Wang, and Tajana Rosing. Adafilter: Adaptive filter fine-tuning for deep transfer learning. In *Proceedings of the AAAI*, volume 34, pp. 4060–4066, 2020.

Xu Han, Zhengyan Zhang, Ning Ding, Yuxian Gu, Xiao Liu, Yuqi Huo, Jiezhong Qiu, Yuan Yao, Ao Zhang, Liang Zhang, et al. Pre-trained models: Past, present and future. *AI Open*, 2:225–250, 2021.

Junxian He, Chunting Zhou, Xuezhe Ma, Taylor Berg-Kirkpatrick, and Graham Neubig. Towards a unified view of parameter-efficient transfer learning. In *Proceedings of ICLR*, 2022.

Geoffrey Hinton, Elad Hazan, and Yoram Singer. Adaptive subgradient methods for online learning and stochastic optimization. *Journal of machine learning research*, 12(7), 2011.

Neil Houlsby, Andrei Giurgiu, Stanislaw Jastrzebski, Bruna Morrone, Quentin de Laroussilhe, Andrea Gesmundo, Mona Attariyan, and Sylvain Gelly. Parameter-efficient transfer learning for NLP. In *Proceedings of ICML*, 2019.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. In *Proceedings of ICLR*, 2021.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Solomon Kullback and Richard A Leibler. On information and sufficiency. *The annals of mathematical statistics*, 22(1):79–86, 1951.

Brian Lester, Rami Al-Rfou, and Noah Constant. The power of scale for parameter-efficient prompt tuning. In *Proceedings of EMNLP*, 2021.

Kenneth Levenberg. A method for the solution of certain non-linear problems in least squares. *Quarterly of applied mathematics*, 2(2):164–168, 1944.

Hector J. Levesque. The winograd schema challenge. In *Logical Formalizations of Commonsense Reasoning, Papers from the 2011 AAAI Spring Symposium, Technical Report SS-11-06, Stanford, California, USA, March 21-23, 2011*, 2011.

Quentin Lhoest, Albert Villanova del Moral, Yacine Jernite, Abhishek Thakur, Patrick von Platen, Suraj Patil, Julien Chaumond, Mariama Drame, Julien Plu, Lewis Tunstall, et al. Datasets: A community library for natural language processing. *arXiv preprint arXiv:2109.02846*, 2021.

Xiang Lisa Li and Percy Liang. Prefix-tuning: Optimizing continuous prompts for generation. In *Proceedings of ACL*, pp. 4582–4597, Online, 2021. Association for Computational Linguistics.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *Proceedings of ICLR*, 2017.

Rabeeh Karimi Mahabadi, James Henderson, and Sebastian Ruder. Compacter: Efficient low-rank hypercomplex adapter layers. *ArXiv preprint*, abs/2106.04647, 2021.

Marie-Catherine de Marneffe, Mandy Simons, and Judith Tonhauser. The commitmentbank: Investigating projection in naturally occurring discourse. In *Proceedings of Sinn und Bedeutung 23*, 2019.

Donald W Marquardt. An algorithm for least-squares estimation of nonlinear parameters. *Journal of the society for Industrial and Applied Mathematics*, 11(2):431–441, 1963.

James Martens. New insights and perspectives on the natural gradient method. *The Journal of Machine Learning Research*, 21(1):5776–5851, 2020.

James Martens and Roger Grosse. Optimizing neural networks with kronecker-factored approximate curvature. In *International conference on machine learning*, pp. 2408–2417. PMLR, 2015.

James Martens, Jimmy Ba, and Matt Johnson. Kronecker-factored curvature approximations for recurrent neural networks. In *Proceedings of ICLR*, 2018.

B.W. Matthews. Comparison of the predicted and observed secondary structure of t4 phage lysozyme. *Biochimica et Biophysica Acta (BBA) - Protein Structure*, 405(2):442–451, 1975.

Jorge Nocedal and Stephen J Wright. *Numerical optimization*. Springer, 1999.

Kazuki Osawa, Yohei Tsuji, Yuichiro Ueno, Akira Naruse, Rio Yokota, and Satoshi Matsuoka. Large-scale distributed second-order optimization using kronecker-factored approximate curvature for deep convolutional neural networks. In *Proceedings CVPR*, pp. 12359–12367, 2019.

Razvan Pascanu, Tomas Mikolov, and Yoshua Bengio. On the difficulty of training recurrent neural networks. In *International conference on machine learning*, pp. 1310–1318. PMLR, 2013.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32, 2019.

Jonas Pfeiffer, Aishwarya Kamath, Andreas Rücklé, Kyunghyun Cho, and Iryna Gurevych. Adapterfusion: Non-destructive task composition for transfer learning. *arXiv preprint arXiv:2005.00247*, 2020.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of Machine Learning Research*, 21:1–67, 2020.

Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. SQuAD: 100,000+ questions for machine comprehension of text. In *Proceedings of EMNLP*, pp. 2383–2392, Austin, Texas, 2016. Association for Computational Linguistics. doi: 10.18653/v1/D16-1264.

David F Shanno. Conditioning of quasi-newton methods for function minimization. *Mathematics of computation*, 24(111):647–656, 1970.

Richard Socher, Alex Perelygin, Jean Wu, Jason Chuang, Christopher D. Manning, Andrew Ng, and Christopher Potts. Recursive deep models for semantic compositionality over a sentiment treebank. In *Proceedings of EMNLP*, pp. 1631–1642, 2013.

Yi-Lin Sung, Jaemin Cho, and Mohit Bansal. Vl-adapter: Parameter-efficient transfer learning for vision-and-language tasks. *arXiv preprint arXiv:2112.06825*, 2021.

Yi-Lin Sung, Jaemin Cho, and Mohit Bansal. Lst: Ladder side-tuning for parameter and memory efficient transfer learning. *arXiv preprint arXiv:2206.06522*, 2022.

Nima Tajbakhsh, Jae Y Shin, Suryakanth R Gurudu, R Todd Hurst, Christopher B Kendall, Michael B Gotway, and Jianming Liang. Convolutional neural networks for medical image analysis: Full training or fine tuning? *IEEE transactions on medical imaging*, 35(5):1299–1312, 2016.

Zedong Tang, Fenlong Jiang, Maoguo Gong, Hao Li, Yue Wu, Fan Yu, Zidong Wang, and Min Wang. Skfac: Training neural networks with faster kronecker-factored approximate curvature. In *Proceedings of CVPR*, pp. 13479–13487, 2021.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Alex Warstadt, Amanpreet Singh, and Samuel R. Bowman. Neural network acceptability judgments. *Transactions of the Association for Computational Linguistics*, 7:625–641, 2019. doi: 10.1162/tacl_a_00290.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, et al. Huggingface's transformers: State-of-the-art natural language processing. *arXiv preprint arXiv:1910.03771*, 2019.

Philip Wolfe. Convergence conditions for ascent methods. *SIAM review*, 11(2):226–235, 1969.

Yuhuai Wu, Elman Mansimov, Roger B Grosse, Shun Liao, and Jimmy Ba. Scalable trust-region method for deep reinforcement learning using kronecker-factored approximation. *Advances in neural information processing systems*, 30, 2017.

Elad Ben Zaken, Shauli Ravfogel, and Yoav Goldberg. Bitfit: Simple parameter-efficient fine-tuning for transformer-based masked language-models. *ArXiv preprint*, abs/2106.10199, 2021.

Jingzhao Zhang, Tianxing He, Suvrit Sra, and Ali Jadbabaie. Why gradient clipping accelerates training: A theoretical justification for adaptivity. *arXiv preprint arXiv:1905.11881*, 2019.

Mengjie Zhao, Tao Lin, Fei Mi, Martin Jaggi, and Hinrich Schütze. Masking as an efficient alternative to finetuning for pretrained language models. *arXiv preprint arXiv:2004.12406*, 2020.

A MORE ABOUT NATURAL GRADIENT DESCENT AND K-FAC

A.1 CONNECTIONS BETWEEN NEWTON'S METHOD AND NATURAL GRADIENT DESCENT

The Hessian matrix of the Kullback-Leibler divergence (the loss function mentioned in section 2.2) reads

$$\nabla_{\boldsymbol{\theta}}^2 L(\boldsymbol{\theta}) = \nabla_{\boldsymbol{\theta}}^2 \mathcal{D}_{KL}[q(x,y)\|p(x,y\mid\boldsymbol{\theta})] \tag{15}$$

$$= -\mathbb{E}_{q(x,y)}[\nabla_\theta^2 \log p(x,y\mid\boldsymbol{\theta})] \tag{16}$$

$$= \mathbb{E}_{q(x,y)}[\nabla_\theta \log q(x,y)^T \nabla_\theta \log p(x,y\mid\boldsymbol{\theta})] \tag{17}$$

In case that the current density $p(\cdot\mid\boldsymbol{\theta})$ is close to the target density q, we could see that $\nabla_{\boldsymbol{\theta}}^2 L \approx \boldsymbol{F}$.

A.2 UPDATE RULES OF K-FAC

In accordance with the symbols adopted in Martens & Grosse (2015), a layer of linear mapping can be written as

$$\boldsymbol{s}_i = \boldsymbol{W}_i \overline{\boldsymbol{a}}_{i-1}. \tag{18}$$

Define $\boldsymbol{g}_i = \frac{\partial L}{\partial \boldsymbol{s}_i}$, then the $\boldsymbol{W}_i$-related sub-block of FIM can be expressed as

$$\hat{\boldsymbol{F}}_{i,i} = \mathbb{E}_{\hat{q}}[\text{vec}(\nabla_{\boldsymbol{W}_i}L)\text{vec}(\nabla_{\boldsymbol{W}_i}L)^T]$$

$$= \mathbb{E}_{\hat{q}}[(\overline{\boldsymbol{a}}_{i-1}\boldsymbol{g}_i)\otimes(\overline{\boldsymbol{a}}_{i-1}\boldsymbol{g}_i)^T]$$

$$= \mathbb{E}_{\hat{q}}[\overline{\boldsymbol{a}}_{i-1}\overline{\boldsymbol{a}}_{i-1}^T \otimes \boldsymbol{g}_i\boldsymbol{g}_i^T] \tag{19}$$

The core idea of K-FAC is to approximate the expectation of Kronecker product in equation 19 with the Kronecker product of expectation, that is,

$$\hat{\boldsymbol{F}}_{i,i} \approx \mathbb{E}_{\hat{q}}[\overline{\boldsymbol{a}}_{i-1}\overline{\boldsymbol{a}}_{i-1}^T]\otimes\mathbb{E}_{\hat{q}}[\boldsymbol{g}_i\boldsymbol{g}_i^T] \triangleq \boldsymbol{A}_{i-1}\otimes\boldsymbol{G}_i. \tag{20}$$

Furthermore, in light of the properties that $(\boldsymbol{B}\otimes\boldsymbol{C})^{-1} = \boldsymbol{B}^{-1}\otimes\boldsymbol{C}^{-1}$ and that $(\boldsymbol{B}\otimes\boldsymbol{C})\text{vec}(\boldsymbol{V}) = \text{vec}(\boldsymbol{C}\boldsymbol{V}\boldsymbol{B}^T)$, the natural gradient updatein K-FAC can be formulated in tensors as

$$\boldsymbol{W}_i \leftarrow \boldsymbol{W}_i - \eta\cdot\boldsymbol{G}_i^{-1}(\nabla_{\boldsymbol{W}_i}L)\boldsymbol{A}_{i-1}^{-1}. \tag{21}$$

B ADDITIONAL EXPERIMENTAL DETAILS

For experiments in Table 2, we perform hyper-parameter search for both AdamW and K-FAC optimizers to select better-performing models. For AdamW, the search space for learning rate is $\{1e-2, 1e-3, 1e-4, 5e-3\}$ and for maximum gradient norm clipping scale is $\{0.1, 1.0, 10\}$. For K-FAC, in addition to the learning rate and the Newton-step clipping scale (τ), we also set the damping factor to stabilize the matrix inverting operation (Levenberg, 1944; Marquardt, 1963). The search space for learning rate, Newton-step clipping scale, and damping factor are $1e-2 \sim 0.5$, $0.1 \sim 2.0$ and $1e-2 \sim 1e-6$, respectively. The reported results in Table 2 and Table 3 use the following hyper-parameter settings in Table 3 and Table 4. All datasets are loaded with huggingface datasets (Lhoest et al., 2021). For results in Figure 4, we adopt K-FAC as the optimizer and set the learning rate as 0.01, and set the damping factor as $1e-4$ for both experiments.

When dealing with MRPC, RTE, and STS-B datasets, some works use the best model checkpoint on the MNLI dataset for initialization to boost the performance. In our empirical study, we do NOT use this strategy, and we use usual initializations for all the models. In our experimentation, the main parameters of PTMs are frozen, and we only optimize the trainable modules.

The GPU memory statistics in Table 1 and Figure 2 come from PyTorch API and NVIDIA respectively, so there might be small inconsistency caused by NVIDIA's extra calculation of cache memory.

Model	Dataset	Method	Learning Rate	Max. Norm	Damping Factor
RoBERTa$_{large}$	QNLI	Adapter	0.1	1.0	1e-4
		LoRA	0.05	1.0	1e-3
	SST-2	Adapter	0.1	1.0	1e-3
		LoRA	0.1	1.0	1e-4
	RTE	Adapter	0.05	1.5	1e-3
		LoRA	0.1	1.5	1e-5
	CoLA	Adapter	1e-2	1.0	1e-2
		LoRA	0.01	1.0	1e-2
	MRPC	Adapter	0.5	0.1	1e-2
		LoRA	0.05	1.0	1e-3
	STS-B	Adapter	0.1	1.0	1e-2
		LoRA	0.1	1.0	1e-6
T5$_{XL}$	COPA	Adapter	0.1	10.0	1e-2
	CB	Adapter	0.1	10.0	1e-2
	WSC	Adapter	0.1	10.0	1e-3
	WSC	Adapter	0.1	10.0	1e-2

Table 3: The training hyper-parameters for K-FAC with the Newton-step clipping strategy.

Model	Dataset	Method	Learning Rate	Max. Norm
RoBERTa$_{large}$	QNLI	Adapter	1e-4	0.1
		LoRA	1e-3	0.1
	SST-2	Adapter	1e-4	0.1
		LoRA	1e-3	0.1
	RTE	Adapter	1e-4	0.1
		LoRA	1e-3	0.1
	CoLA	Adapter	1e-3	0.1
		LoRA	1e-4	1.0
	MRPC	Adapter	1e-4	1.0
		LoRA	1e-3	0.1
	STS-B	Adapter	1e-4	0.1
		LoRA	1e-4	0.1
T5$_{XL}$	COPA	Adapter	1e-4	0.1
	CB	Adapter	1e-4	0.1
	WSC	Adapter	1e-4	0.1
	RTE	Adapter	1e-4	0.1

Table 4: The training hyper-parameters for AdamW.