# Distributionally Robust Imitation Learning

## Abstract

We consider the imitation learning problem of learning a policy in a Markov Decision Process (MDP) setting where the reward function is not given, but demonstrations from experts are available. Although the goal in imitation learning is to learn a policy that produces behaviors nearly as good as the experts' for a desired task, assumptions of consistent optimality for demonstrated behaviors are violated in practice. Distributional robustness based on an adversarial construction has played a prominent role in inverse reinforcement learning methods that solve this problem by robustly estimating the unknown reward function. This paper studies Distributionally Robust Imitation Learning (DRIL) and develops a close connection between DRIL and Maximum Entropy Inverse Reinforcement Learning. We develop a novel approach to transform the objective function into a convex optimization problem over a polynomial number of variables. Our approach lets us optimize both stationary and non-stationary policies. Moreover, unlike prevalent previous methods, it does not require repeatedly solving an inner reinforcement learning problem, which provides a substantial improvement in training time. We experimentally show the significant benefits of DRIL using new optimization method on synthetic data and a highway driving environment.

## 1 Introduction

We consider the imitation learning setting of learning to perform a task based only on demonstrations that are provided by experts. There are two main approaches often considered for this learning problem: *Behavioral Cloning* [19] and *Inverse Reinforcement Learning* [18, 1, 24, 14]. In behavioral cloning, the learner attempts to learn a policy in a supervised learning manner, in which a direct mapping from states to actions is estimated from the demonstrated trajectories. Behavioral cloning, while simple, often generalize poorly when attempting to predict goal-directed sequential decisions due to compounding errors caused by covariate shift and only tends to succeed when given large amounts of data [22, 23]. Alternatively, inverse reinforcement learning (IRL) rationalizes demonstrated trajectories by estimating a reward function that makes the expert's policy optimal. The problem of determining the reward function is inherently ill-posed, since a single policy can be optimal for multiple reward functions.

To obtain a unique solution in IRL, multiple methods have been proposed, with the maximum entropy principle [30, 31] and margin maximization [20] being two widely employed methods among researchers. Maximum (causal) entropy IRL [31], in particular, seeks an entropy-maximizing distribution over sequences that matches expected feature counts [1] with those observed from demonstrations. For imitation learning in very high dimensional and continuous spaces, where function approximations such as deep neural networks are often used, IRL methods have generally been less efficient than behavioral cloning methods [13] since they require reinforcement learning as an inner loop. Recent adversarial IRL methods [10, 9], however, seem more likely to be effective.

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

A common assumption in imitation learning is that all expert behaviors have the same level of trustworthiness and are optimal/near-optimal [29]. However, it is common for noisy expert behaviors to violate this optimality assumption in practice. Thus, relying heavily on the optimality of the expert's behavior may degrade an imitation learner and make the learning algorithm prone to failure in such cases [29]. In [15] the authors have proposed to inject noise into the expert's policy demonstrations, to obtain a more robust policy. Alternatively, [11] trained a discriminator that distinguishes between expert trajectory and generated trajectories that learns reward functions that are robust to changes in dynamics.

An alternative approach to obtain a robust policy, also adopted in this work, is to search for a policy that is distributionally robust given the training data. For this purpose, the learner's policy is obtained by solving a game between a learner and an adversary [5], where the learner tries to choose a policy that minimizes a loss defined between them and the adversary tries to maximize this loss subject to a set of constraints that match some statistics from the training data. This approach leverages two uncertainty sets as opposed to typical Distributionally Robust Optimization (DRO) methods [4, 6] where the uncertainty set is only defined over the adversary (demonstrator-estimator) and the learner's policy is assumed to have a specific parametric form. Authors in [5] proposed a method to solve imitation learning under an adversarial framework. They proposed a Double Oracle method [17] to solve the corresponding optimization. However, their method may take up to exponential time in the size of the space of policies.

In this paper, we first develop a connection between Distributionally Robust Imitation Learning (DRIL) and Maximum Entropy Inverse Reinforcement Learning and show that MaxEnt is a special case of DRIL when a certain loss function and policy description is used. We also show that DRIL can be seen as a framework of maximizing a *general* entropy function that is defined based on a particular loss of interest. We then cast DRIL's objective function into a convex optimization problem over a polynomial number of variables, which is simpler to understand and implement and also significantly improves the training time. We also extend the formulation to stationary policies, which enables us to experimentally show the benefits of learning a robust policy in a highway driving simulation.

## 2 Preliminaries

We model sequential decision making problems using discrete Markov Decision Processes (MDPs). An MDP $\mathcal{M}$, is a tuple $(\mathcal{S}, \mathcal{A}, \Gamma, \mathcal{R}, \gamma)$ in which $\mathcal{S}$ and $\mathcal{A}$ are state and action (control input) spaces, respectively. $\Gamma$ represents the transition probabilities $P(s'|a, s)$, which specifies the state distribution upon taking action $a$ in state $s$; $\mathcal{R} : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ is a reward function; and $\gamma \in (0, 1]$ is a discount factor.

We assume there is some feature vectors $\phi : \mathcal{S} \times \mathcal{A} \to [0, 1]^d$ over state-action pairs that capture the most salient properties distinguishing preferred and nonpreferred trajectories where $\mathcal{R}$ can be written as a (linear) function of these feature vectors given a reward vector $\mathbf{w}$: $\mathcal{R}(s, a) = \mathbf{w} \cdot \phi(s, a)$.

A policy $\pi \in \Pi$ is the probability of taking action $a$ in state $s$, $\pi(a, s) = P(a|s)$ and $\Pi$ represents the set of all possible stochastic policies. Demonstrations by an expert are given as a set of trajectories $\mathcal{D} = \{\tau^1, \cdots, \tau^m\}$. A trajectory is a sequence of state-action pairs $\tau = (s_0, a_0, \cdots, s_T, a_T)$ over horizon $T$. From an optimization perspective, *Imitation Learning with a General Loss*, finds a policy $\hat{\pi}$ that minimizes the distance difference behaviors of learner and expert $\pi_E$:

$$\hat{\pi} \in \operatorname*{argmin}_{\pi} \mathcal{L}(\pi, \pi_E),\,^1$$

where $\mathcal{L}$ measures the dissimilarity between two policies' behaviors.

Having access to only sample demonstrations of a policy as training samples, it is essential to quantify the behavior of a policy. Commonly used in behavioral cloning, one approach is to measure the marginal distribution of states and actions, $P(s, a)$ induced by a policy. Note that in the case of infinite-horizon MDPs, expected (discounted) number of visits to state-action pairs is used.

An alternative measure that is more desirable for long horizon, is the expectation of trajectory features [1]. This approach is often used in inverse reinforcement learning, where a reward function of the features is learned. The expected (discounted if $\gamma \in (0, 1)$) feature of a policy $\pi$ similar to [1] is

---

[1]We overload $\mathcal{L}$ for any type of loss in different context e.g. loss between two deterministic policies or states.

defined as:

$$\mu(\pi) = \mathbb{E}\left[\sum_{t=0}^{T} \gamma^t \phi(s_t, a_t) \big| \pi, \Gamma\right] \in \mathbb{R}^k.$$

# 3  Robust Imitation Learning and Maximum Entropy

Foundational work [26, 12] has developed a close relationship between robust Bayes decisions, maximum entropy, and minimizing worst-case expected loss also known as adversarial learning. Several works have followed this framework of robustness for different supervised learning problems, such as cost-sensitive classification [2], multivariate loss prediction [28], ordinal regression [7], and graphical models [8].

For the imitation learning setting, [5] has applied the adversarial learning framework on inverse reinforcement learning problem and proposed a double oracle algorithm [17] to solve the corresponding optimization problem. In the adversarial framework, the policy that robustly minimizes an imitative loss is defined as following:

**Definition 1.** *Given an imitative loss function $\mathcal{L}$ that measures the distance of two policies' behavior,* **Distributionally Robust Imitation Learning (DRIL)** *is defined as a two-player zero-sum game between the learner and the demonstrator, in which players choose a stochastic control policy, $\hat{\pi}$ or $\check{\pi} \in \tilde{\Xi}$ simultaneously, and receive a payoff of $\mathcal{L}(\hat{\pi}, \check{\pi})$. The minimax strategy for the learner is given by:*

$$\min_{\hat{\pi}} \max_{\check{\pi} \in \tilde{\Xi}} \mathbb{E}[\mathcal{L}(\hat{\pi}, \check{\pi})], \tag{1}$$

*where $\tilde{\Xi}$ represents a convex set of constraints measured from characteristics of demonstrated data.*

Generally, $\tilde{\Xi}$ can be in the form of moment matching in 2 that is commonly used in inverse reinforcement learning: $\check{\pi} \in \tilde{\Xi} \leftrightarrow \mathbb{E}\left[\sum_{t=0}^{T} \gamma^t \phi(s_t, a_t) \big| \check{\pi}, \Gamma\right] = \tilde{\mu} \triangleq \mathbb{E}\left[\sum_{t=0}^{T} \gamma^t \phi(s_t, a_t) \big| \pi_E, \Gamma\right]$, where $\pi_E$ represents the policy that demonstrated trajectories are generated from.

This formulation assumes that except for certain properties of the limited samples of available demonstrated behavior, the demonstrator's policy is the worst-case possible for the learner. This approach avoids generalizing from available demonstrations in an optimistic manner that may be unrealistic and lead to a policy that does not work well in practice, especially in situations where there is noise in the demonstrated behaviors.

The minimax formulation in definition 1 is closely related to the principle of maximum entropy, which is used in Maximum Entropy Inverse Reinforcement Learning (MaxEnt) [30]. MaxEnt provides a probabilistic approach under the constraint of matching the reward value of demonstrated behavior to resolve the ambiguity in choosing a distribution over decisions. Under this model, trajectories with equivalent rewards have equal probabilities, and trajectories with higher rewards are exponentially more preferred according to the following:

$$P(\zeta_i | \mathbf{w}) = \frac{1}{Z(\mathbf{w})} e^{\mathbf{w}^\top \phi_{\zeta_i}}, \tag{2}$$

where $\zeta_i$ and $\phi_{\zeta_i}$ represent a trajectory and its corresponding sum of empirical features.

To show the connection between DRIL and MaxEnt, we employ a tool from the general theory of exponential families [3] that shows for certain classes of two-player zero-sum games, there exists a parametric distribution for the minimax strategy, as shown in lemma 1.

**Lemma 1** (Barndorff-Nielsen [3]). *Let $p \in \Xi$ be a probability distribution over space $X$, where $\Xi$ describes a mean-value constraint $\Xi = \{p : \mathbb{E}_p(\mathcal{T}(X)) = C\}$. Let also $q$ be the set of all mass probability functions. For the maximum entropy distribution, $\max_{q \in \tilde{\Xi}} \min_p \mathbb{E}[-\log q(X)]$, $p^* = q^*$ exists and is given by $p^* = \exp\{\alpha_0 + \alpha^\top \mathcal{T}(X)\}$.*

Equipped with Lemma 1, we develop a connection between DRIL and MaxEnt in Theorem 1.

**Theorem 1.** *The stochastic policy $P(\zeta_i | \mathbf{w})$ obtained from Maximum Entropy IRL in eq. (2) is obtained from DRIL minimax strategy in definition 1 when the logarithmic loss is used.*

*Proof.* We construct a stochastic policy in definition 1 as a probability distribution over all possible trajectories $\{\zeta_1, ..., \zeta_M\}$. Let $\hat{\pi} = P(\zeta)$ and $\check{\pi} = Q(\zeta)$ be the probability distributions of the learner and the demonstrator, respectively. The expected feature of demonstrator now can be written as $\mu_{\check{\pi}} = \sum_i Q(\zeta_i)\phi_{\zeta_i}$, which resembles the mean value constraint in lemma 1, therefore, for logarithmic loss, $P^*(\zeta_i) = Q^*(\zeta_i) = \exp\{\mathbf{w}_0 + \mathbf{w}^\top \phi_{\zeta_i}\}$. $\qquad\square$

Although Theorem 1 shows that DRIL provides the maximum entropy policy only when a logarithmic loss is used, we can generalize it to other losses of interest by using Generalized Entropy functions, $H(P) := \inf_Q \mathbb{E}[\mathcal{L}(P, Q)]$. Proposition 1 describes the relation between DRIL and generalized maximum entropy.

**Proposition 1.** *For any policy descriptions and loss functions that DRIL in Definition 1 has Nash equilibrium, $\hat{\pi}$ is a robust action and $\check{\pi}$ is the maximizer of **Generalized** entropy function.*

Proposition 1 provides a general approach to resolve the ambiguity of matching constraints—where many policies lead to the same feature counts—by choosing either a policy $\check{\pi}$ that does not exhibit any additional preferences beyond matching feature expectations with respect to a loss of interest $\mathcal{L}$ (maximum generalized entropy) or a policy $\hat{\pi}$ that minimizes the worst-case expected loss. This can be seen as the Maximum General Entropy Inverse Reinforcement Learning, where the choice of loss function is not restricted to logarithmic loss function.

We extend the following lemma that describes a class of loss functions and policies for which the solution of the game defined in 1 exists, thus Proposition 1 can be applied.

**Lemma 2.** *For the game in definition 1, where learner $\hat{\pi}$ and demonstrator $\check{\pi}$ simultaneously choose a stochastic policy, if the payoff can be written as a bilinear function: $\sum_{i=1}^n \sum_{j=1}^m l_{ij}\hat{\pi}_i \check{\pi}_j$, the game has a solution and minimax (maximin) strategy produces the solution as long as $m$ and $n$ are finite.*

*Proof.* In his generalized minmax theorem, for arbitrary nonempty convex sets of actions that are closed and bounded, Von Neumann [27] shows that bilinear games have saddle points as long as $m$ and $n$ are finite. Assuming the demonstrated data are generated from a policy (optimality not necessary) the convex moment matching constrained in definition 1 keeps $\tilde{\Xi}$ closed, bounded, and non-empty. $\qquad\square$

**Example 1.** *One illustrating example is to let each player's pure strategy to be a deterministic policy $\delta$. Therefore, a mixed strategy now represents a stochastic policy $\pi$, which is a probability distribution over the set of all deterministic policies. Now eq. (1) can be written as a bilinear game with payoff $\sum_{i=1}^n \sum_{j=1}^m l_{ij}P(\hat{\delta}_i)P(\check{\delta}_j)$ where $l_{ij}$ is $\mathcal{L}(\hat{\delta}_i\check{\delta}_j)$.*

# 4 Learning and Inference

To solve the optimization problem in eq. (1), one needs to specify the policy description $\pi$, and the distance measure between two policies' behaviors $\mathcal{L}$. The choice of $\pi$ and $\mathcal{L}$ can result in different algorithmic approaches.

## 4.1 Double Oracle

In [5], the authors construct the learner and the demonstrator stochastic policies as mixtures of deterministic non-stationary policies. Concretely, let $\Upsilon = \{\delta_1, \delta_2, ...\}$, be the set of all possible non-stationary deterministic policies, then $\hat{\pi}_\Delta := P(\{\hat{\delta} \in \Upsilon\})$ and $\check{\pi}_\Delta = P(\{\check{\delta} \in \Upsilon\})$. Note that $|\Upsilon| \in \mathcal{O}(|\mathcal{A}|^{|\mathcal{S}|T})$ which is exponential in size of action space $\mathcal{A}$. Assuming the loss function is additive over state-action pairs, [5] shows

|  | $\check{\delta}_1$ | $\check{\delta}_2$ | $\cdots$ | $\check{\delta}_j$ |
|---|---|---|---|---|
| $\hat{\delta}_1$ | $\mathcal{L}(\hat{\delta}_1, \check{\delta}_1) + \psi(\check{\delta}_1)$ | $\mathcal{L}(\hat{\delta}_1, \check{\delta}_2) + \psi(\check{\delta}_2)$ | $\cdots$ | $\mathcal{L}(\hat{\delta}_1, \check{\delta}_j) + \psi(\check{\delta}_j)$ |
| $\hat{\delta}_2$ | $\mathcal{L}(\hat{\delta}_2, \check{\delta}_1) + \psi(\check{\delta}_1)$ | $\mathcal{L}(\hat{\delta}_2, \check{\delta}_2) + \psi(\check{\delta}_2)$ | $\cdots$ | $\mathcal{L}(\hat{\delta}_2, \check{\delta}_j) + \psi(\check{\delta}_j)$ |
| $\vdots$ | $\vdots$ | $\vdots$ | $\ddots$ | $\vdots$ |
| $\hat{\delta}_i$ | $\mathcal{L}(\hat{\delta}_i, \check{\delta}_1) + \psi(\check{\delta}_1)$ | $\mathcal{L}(\hat{\delta}_i, \check{\delta}_2) \psi(\check{\delta}_2)$ | $\cdots$ | $\mathcal{L}(\hat{\delta}_i, \check{\delta}_j) \psi(\check{\delta}_j)$ |

Table 1: The payoff matrix of $G(\hat{\pi}_\Delta, \check{\pi}_\Delta | \mathbf{w})$ with loss function $\mathcal{L}$, deterministic policies $\delta$ and Lagrangian potentials $\psi$.

that eq. (1) can be written as bilinear game:

$$\min_{\mathbf{w}} \min_{\hat{\pi}_\Delta} \max_{\check{\pi}_\Delta} \overbrace{\sum_i \sum_j p(\delta_i)p(\delta_j)\mathcal{L}(\hat{\delta}_i, \check{\delta}_j) + \sum_j p(\delta_j) \underbrace{\mathbf{w} \cdot \mathbb{E}[\phi|\check{\delta}_j]}_{\psi(\check{\delta}_j)}}^{G(\hat{\pi}_\Delta, \check{\pi}_\Delta|\mathbf{w})} - w \cdot \tilde{\boldsymbol{\mu}}.$$

This will result in a matrix game with exponential size in number of actions $\mathcal{A}$ as shown in Table 1. To obtain the Lagrange variables $\mathbf{w}$, this matrix game needs to be repeatedly solved to compute the gradient with respect to $\mathbf{w}$. This requires solving a linear program with $\mathcal{O}(|\mathcal{A}|^{|\mathcal{S}|T})$ variables with a simplex constraint, which is impractical for even modestly sized problems. To mitigate this problem, they employed the double oracle method [17] in an attempt to construct a smaller sub-portion of the matrix by gradually adding pure actions through solving a time-varying control problem. However, there is no guarantee that the support set of Nash-equilibrium of the defined game is small and the algorithm may need to solve up to an exponential number of time-varying optimal control problems.

## 4.2 State-Action Distribution

We propose an alternative way to transform the optimization in eq. (1) into a convex problem. Our approach is based on using state-action marginals to construct the stochastic policies of learner and the demonstrator, where the number of required variables is linear in $|\mathcal{S}|$ and $|\mathcal{A}|$, and it can also be extended to stationary policies. In the following, we first look at the non-stationary case and then extend our method to stationary policies.

A policy $\pi$ induces a probability distribution $P_t(s)$ over the states of an MDP $\mathcal{M}$ at each time step. State-action marginals are similarly defined as $P_t(s, a) = P_t(s)\pi_t(a|s)$. A *valid state-action marginal* is a set of simplices corresponding to each time-step that satisfy the Bellman flow constraints for a given MDP $\mathcal{M}$. Let $P_t(s, a) \in \Delta$ be the probability of state-action pairs $(a, b)$ at time $t$; a valid marginal distribution $\mathbf{P} \in \Omega$ satisfies the following affine constraints: For all $s'$, $\sum_{s,a} P_t(s, a)P(s'|s, a) = \sum_a P_{t+1}(s', a)$, where $P(s'|s, a) \in \Gamma$ and $\Omega$ represents the set of all valid marginal distribution for a given MDP $\mathcal{M}$.

Employing state-action marginals allows us to write the objective function in Equation (1) as a convex problem of $\mathcal{O}(|\mathcal{A}||\mathcal{S}|T)$ variables as shown in Theorem 2 in a vectorized form.

**Theorem 2.** *For an additive loss function over state and actions $\mathcal{L}$, Solving DRIL optimization in eq. (1) is equivalent to solving the following convex minimax problem over **marginal state-action probabilities** of the learner $\mathbf{P} = (\mathbf{p}_1, ..., \mathbf{p}_T)$ and demonstrator $\mathbf{Q} = (\mathbf{q}_1, ..., \mathbf{q}_T)$ parameterized with Lagrange multipliers $\mathbf{w}$:*

$$\min_{\mathbf{w}} \max_{\mathbf{Q} \in \Omega} \min_{\mathbf{P} \in \Omega} \left[ \sum_{t=0}^{T} \mathbf{p}_t^\top \mathcal{L} \mathbf{q}_t + \mathbf{w}^\top \Phi^\top \mathbf{q}_t \right] - \mathbf{w}^\top \tilde{\boldsymbol{\mu}}, \tag{3}$$

where $\mathbf{p}_t$ (similarly $\mathbf{q}_t$) is a vector with the size of $|\mathcal{A}||\mathcal{S}|$ storing marginal probability of state-action pairs at time $t$: $P_t(s, a)$; $\mathcal{L}$ is the general loss function that is defined over state-action pairs $\mathcal{L} : |\mathcal{A}||\mathcal{S}| \times |\mathcal{A}||\mathcal{S}|$. $\phi$ is a $d \times |\mathcal{A}||\mathcal{S}|$ matrix storing the feature function for each state-action pair. We denote system dynamics with $\Gamma$, which is a matrix with size $|\mathcal{A}||\mathcal{S}| \times |\mathcal{S}|$ storing transition probabilities $P(s'|s, a)$.

Intuitively, each player in the above formulation searches over a *valid* state-action distribution to reach to an equilibrium. One of the benefits of construing a policy using marginals is that the feature expectation can be written as an inner product of the state-action distribution and the state-action feature vector. Thus, the demonstrator's expected feature is $\mu(\mathbf{Q}) = \sum_{t=0}^{T} \Phi \mathbf{q}_t$, and the feature matching constraint is realized by minimizing $\mathbf{w}^\top (\sum_{t=0}^{T} \Phi \mathbf{q}_t - \tilde{\boldsymbol{\mu}})$ over dual variables $\mathbf{w}$. Writing the objective function in eq. (1) in terms of state-action marginal probabilities reduces the number of variables needed to represent the equilibrium from $\mathcal{O}(|\mathcal{A}|^{|\mathcal{S}|T})$ to $\mathcal{O}(|\mathcal{A}||\mathcal{S}|T)$. The unconstrained optimization over dual variables $\mathbf{w}$ can be solved using any gradient descent methods where the gradient is given by $\sum_{t=0}^{T} \Phi \mathbf{q}_t^* - \tilde{\boldsymbol{\mu}}$ where $\mathbf{Q}^*$ is the solution of the following game for current $\mathbf{w}_t$:

$$G(\mathbf{w}_t) = \max_{\mathbf{Q} \in \Omega} \min_{\mathbf{P} \in \Omega} \left[ \sum_{t=0}^{T} \mathbf{p}_t^\top \mathcal{L} \mathbf{q}_t + \mathbf{w}_t^\top \Phi^\top \mathbf{q}_t \right] \tag{4}$$

### 4.3 Stationary Policy

Our approach can be also extended with some modifications to the stationary policy setting. Stationary policies are desirable because they are simpler to describe, and are more natural and intuitive in terms of the behavior that they prescribe. Similar to state-action marginals, we utilize an *occupancy measure* $\rho_\pi : \mathcal{S} \times \mathcal{A} \to \mathbb{R}^+ \cup 0$ to characterize a stationary policy $\pi$. It is defined as the expected (discounted) number of visits to state-action pair $(s, a)$, when following policy $\pi$ and can be written as a feasible set of affine constraints:

$$\mathcal{G} = \{\rho : \rho \ge 0 \mid \sum_a \rho(s', a) = p_0(s) + \sum_{s,a} \gamma P(s'|s,a)\rho(s,a) \; \forall s \in \mathcal{S}\}, \tag{5}$$

where $P(s'|s,a) \in \Gamma$ and $p_0$ is the distribution of starting states.

For a given additive loss $\mathcal{L}$, with the use of an occupancy measure, we write the expected loss $\mathbb{E}[\mathcal{L}(\pi_1, \pi_2)]$ as $\rho_{\pi_1}^\top \mathcal{L}\rho_{\pi_2}$ and the expected discounted feature as $\mu_\pi = \Phi^\top \rho_\pi$. Theorem 3 shows how we can write eq. (1) as a convex optimization using occupancy measure:

**Theorem 3.** *For an additive loss function over state and actions $\mathcal{L}$, Solving DRIL optimization in eq. (1) is equivalent to solving the following convex minimax problem over **occupancy measure** of the learner $\mathcal{P}$ and demonstrator $\mathcal{Q}$:*

$$\min_{\mathbf{w}} \; \max_{\mathcal{Q} \in \mathcal{G}} \min_{\mathcal{P} \in \mathcal{G}} \mathcal{P}^\top \mathcal{L}\mathcal{Q} + \mathbf{w}^\top(\Phi^\top \mathcal{Q} - \tilde{\boldsymbol{\mu}}). \tag{6}$$

The convex optimization in eq. (6) can also be solved using any gradient-based method where the gradient is obtained by solving a constrained game with $\mathcal{O}(|\mathcal{A}||\mathcal{S}|)$ variables.

### 4.4 Inferred Policy

In the non-stationary case, after obtaining $\mathbf{w}^*$, one can use either $\mathbf{Q}^*$ or $\mathbf{P}^*$ as the produced non-stationary Markovian stochastic policy by computing $\pi^*(a|s_t) = p_t(a|s) = \frac{p_t(a,s)}{\sum_a p_t(a,s)}$. $\mathbf{Q}$ corresponds to the policy that maximizes the generalized entropy and $\mathbf{P}$ corresponds to the policy that has minimized the worst-case expected loss.

For the stationary case, [25] has proved that there is a one-to-one mapping between $\mathcal{G}$ and $\Pi$, in a sense that for an occupancy measure $\mathcal{P} \in \mathcal{G}$, $\pi(a|s) \triangleq \frac{\mathcal{P}(a,s)}{\sum_a \mathcal{P}(a,s)}$ is the only policy that results in $\mathcal{P}_\pi$. Therefore, one can similarly use $\mathcal{P}$ or $\mathcal{Q}$ as the produced stationary stochastic policy.

For either case, assuming the reward function can be written as $\mathcal{R}(s,a) = \mathbf{w} \cdot \phi(s,a)$. Then, $\mathbf{w}^*$ plays the role of the reward weight vector that rationalizes the demonstrated behaviors. Consequently, we can use $\mathbf{w}^{*\top}\Phi$ to obtain the optimal reward function $\mathcal{R}^*$ and using an MDP solver to obtain the (deterministic) corresponding policy.

## 5  Optimization

In both stationary and non-stationary cases, any gradient descent method can be used to optimize over dual variables $\mathbf{w}$. To compute the gradient, one needs to compute $\mathbf{Q}^*$ for non-stationary and $\mathcal{Q}^*$. However, since $\mathbf{w}$ is unconstrained, by adding a norm of $\mathbf{w}$ with hyperparameter $\lambda$, one can directly solve $\mathbf{w}$ and replace it in the objective. Since the optimization algorithms are similar in both cases, we only mention the non-stationary case:

$$\min_{\mathbf{w}} \max_{\mathbf{Q} \in \Omega} \min_{\mathbf{P} \in \Omega} \big[ \sum_{t=0}^{T} \mathbf{p}_t^\top \mathcal{L}\mathbf{q}_t + \mathbf{w}^\top \Phi^\top \mathbf{q}_t \big] - \mathbf{w}^\top \tilde{\boldsymbol{\mu}} + \frac{\lambda}{2}\|\mathbf{w}\|^2, \tag{7}$$

and setting: $\mathbf{w} = \tilde{\boldsymbol{\mu}} - \Phi \sum_{t=0}^{T} \mathbf{q}_t$ we have:

$$\max_{\mathbf{Q} \in \Omega} -\frac{1}{2\lambda}\|\tilde{\boldsymbol{\mu}} - \Phi \sum_{t=0}^{T} \mathbf{q}_t\|^2 + \min_{\mathbf{P} \in \Omega} \sum_{t=0}^{T} \mathbf{p}_t^\top \mathcal{L}\mathbf{q}_t, \tag{8}$$

which is a constrained quadratic optimization in $\mathbf{Q}$. Using Danskin's theorem, the gradient of $\mathbf{q}_t$ is given by $\frac{1}{\lambda}(\Phi^\top \tilde{\boldsymbol{\mu}} - \Phi^\top \Phi \sum_{t=0}^{1} T\mathbf{q}_t) - \mathcal{L}\mathbf{p}_t^*$, where $\mathbf{p}^*$ can be found using linear programming (linear objective with affine constraints) efficiently using standard linear programming toolbox. An alternative approach is to solve the dual of optimization over $\mathbf{p}_t$ and maximize it along with $\mathbf{Q}$.

**Algorithm 1** Distributionally Robust Imitation Learning (DRIL)

---

**Input:** $\mathcal{D} = \{\tau^1, \tau^2, \cdots, \tau^m\}, \Gamma, p_0$
Initialize $\mathbf{Q}^0$, compute $\tilde{\boldsymbol{\mu}}$ using $\mathcal{D}$, and set $i = 0$
**repeat**
    Compute $\nabla_i f(\mathbf{Q}^i)$ in Equation (8)
    $i = i + 1$
    Using $\nabla_i f(\mathbf{Q}^i)$ calculate with $\bar{\mathbf{Q}}^{i+1}$
    **if** $\bar{\mathbf{Q}}^{i+1} \in \Omega$ **then**
        $\mathbf{Q}^{i+1} = \bar{\mathbf{Q}}^{i+1}$
    **else**
        $\mathbf{Q}^{i+1} =$ project $(\bar{\mathbf{Q}}^{i+1})$ where projection function is defined in Equation (9)
    **end if**
**until** convergence

---

### Projection Step

At each iteration of the algorithm, we need to project $\mathbf{Q}$ to a convex domain to maintain a valid state-action distribution given $\Gamma$ and the initial state distribution. Essentially,

$$\min_{\mathbf{Q}} \frac{1}{2} \sum_{t=0}^{T} \|\mathbf{q}_t^* - \mathbf{q}_t\|^2 \quad \text{s.t. } \mathbf{Q} \in \Omega, \tag{9}$$

from which, by using a Lagrangian method and strong duality, we obtain:

$$\max_{\mathbf{V}} \min_{\mathbf{Q} \in \Delta} \sum_{t=0}^{T} \frac{1}{2} \|\mathbf{q}_t^* - \mathbf{q}_t\|^2 + (\mathbf{q}_{t-1}^\top \Gamma - \mathbf{q}_t^\top \mathbf{Z}) \mathbf{v}_t, \tag{10}$$

where $\mathbf{Z}$ operator computes the state distribution: $\mathbf{q}_t^\top \mathbf{Z} = \sum_a q_t(s, a)$. To compute the gradient $\mathbf{V}$, a quadratic program over $\mathbf{Q}$ with probability simplex constraints needs to be solved. This can be analytically determined by sorting each $\mathbf{q}_t$, which takes $\mathcal{O}(|\mathcal{S}||\mathcal{A}| \log(|\mathcal{S}||\mathcal{A}|))$ time.

## 6 Experimental Results

In our experiments, we compare DRIL with prior methods on several imitation learning task. We investigate: 1) How our convex optimization improves the training time compared to the double oracle method; 2) How the choice of loss function affects the performance of DRIL; and 3) How accurately DRIL predicts actions compared to other prior IRL methods. We repeat each experiment $8$ times.

### 6.1 Training Time

To compare the training time of our proposed convex optimization with the double oracle approach [5], we adopt their experimental setup in Grid-World. In this experiment, trajectories are collected from simulated navigation across a discrete 2D grid where the agent starts from a random starting point, and navigates through the grid to reach a specified target location. Taking a step in the grid has a cost and the agent's goal is to reach the target location while minimizing the accumulated navigation cost (maximizing the reward).

| Size | DRIL Time | DRIL Cost | DO Time | Do Cost |
|------|-----------|-----------|---------|---------|
| 128  | 1.6       | $-7.39$   | 30.1    | $-7.39$ |
| 432  | 1.8       | $-21.61$  | 42.1    | $-21.74$ |
| 1024 | 6.0       | $-20.0$   | 141.1   | $-20.0$ |
| 2000 | 98.6      | $-30.1$   | 608.1   | $-30.1$ |
| 3500 | 496       | $-39.2$   | 2020    | $-39.1$ |
| 5500 | 881       | $-58.7$   | 4970    | $-58.9$ |

Table 2: Elapsed time in second until convergence with $10^{-3}$ tolerance.

This problem can be formulated as an optimal sequential decision-making problem in a finite Markov decision process where the optimal policy is non-stationary. We consider linear cost function $C(s) = \mathbf{w}^{*\top} \phi(s) + \epsilon(s)$, where feature function $\phi(s, a)$ and weight vector $\mathbf{w}^*$ are drawn from $U(0, 1)^d$, and $\epsilon \sim U(0, 1)$. Transition function is non-deterministic with parameter $p_m \in (0, 1]$ which navigates the agent to randomly choose neighbors with probability $(1 - p_m)$.

286 The loss function for this experiment is set
287 to $\mathbb{E}\left[\sum_{t=0}^{T}\sqrt{(\hat{\mathbf{X}}_t - \check{\mathbf{X}}_t)^2 + (\hat{\mathbf{Y}}_t - \check{\mathbf{Y}}_t)^2}\right]$ where $(X, Y)$
288 represents the grid position of the agent. We generate
289 trajectories from the optimal policy that is obtained by
290 solving the true reward function and train DRIL and
291 DO until convergence. Along with expected loss, we
292 report the elapsed time that it takes to converge for our
293 proposed method and double oracle (DO) in Table 2.
294 We run the both algorithms until convergences, As Ta-
295 ble 2 shows, our proposed method needs significantly
296 less training time for the same performance and scales
297 very well with the size of state space.

Figure 1: Performance of DRIL when different loss functions are used.

## 6.2 Loss Function Effect

299 For the second question, we show that different choices
300 in loss function result in different performances of the
301 learned policy in the imitation learning setting. There-
302 fore, the choice of loss function provides an extra tool
303 to incorporate certain domain knowledge, and design
304 a problem-specific loss that potentially results in better
305 produced policy. For the purpose of comparison of
306 different losses, we revisit the GridWord environment,
307 however, we train several stationary policies with different losses. We consider $0 - 1$ loss, which
308 equally penalizes any mismatch between state-action pairs; action-loss, which incurs loss only when
309 an action differs from another pair in the same state; random loss, which is drawn from a uniform
310 distribution; and finally Euclidean distance between two positions in the grid. It is clear from Figure 1
311 that the policy produced from Euclidean loss outperform other policies from other losses, which
312 shows the benefit of using a task-specific loss function.

## 6.3 Highway Driving

314 To evaluate DRIL in a complex environment with more realistic behavior, we compared
315 it with several other IRL methods in a highway driving simulator with non-linear reward
316 function: MMP [20], the projection algorithm of Abbeel and Ng [1], and LEARCH [21].
317

318 Following the setting
319 in Levine et al. [16],
320 the task is to drive a
321 car on a three-lane
322 highway in which
323 the agent can switch
324 lanes and drive at
325 up to four times the
326 speed of traffic while
327 all other vehicles
328 move at a constant
329 speed. The set of
330 features includes
331 the distance to the
332 nearest vehicle in
333 each lane (in front
334 and behind), current
335 speed, and current
336 lane. We also evalu-
337 ate each method on

Figure 2: Expected value differences for 64-car-length highways with varying example counts. Lower values are better.

338 the original environment and on 4 additional random environments, denoted as "transfer". We set a
339 uniformly random loss for DRIL and train all methods using examples sampled from the stochastic

MaxEnt policy which can intuitively be viewed as noisy samples of an underlying optimal policy. To evaluate the performance of each method, we use the misprediction rate, which is defined as the ratio of incorrect actions compared to the optimal policy, and the expected value difference, which measures the suboptimality of the learned policy under the true reward. Since DRIL is able to produce stochastic policy, with the same argument from [16], we could evaluate the optimal stochastic policies. However, this would unfairly penalize other methods. Therefor, we first obtain the reward weight vector and find the optimal deterministic policy the corresponding reward function. Then, we measure its expected sum of discounted rewards under the true reward function, and subtract this quantity from the expected sum of discounted rewards of the optimal policy.

As shown in Figure 2 and Figure 3, DRIL performs very well in terms of the obtained reward and the accuracy of the produced policy in both the original and transfer environments. In contrast, we find that MMP and Abbeel & Ng's approach degrade as the number of examples increase. This matches theory since the suboptimality of the demonstrations becomes more apparent as the number of examples in-

Figure 3: Misprediction rate results for 64-car-length highways with varying example counts. Lower values are better.

creases. This indicates that under noisy demonstrations (samples from a stochastic policy), a robust approach has the potential to outperform alternative approaches.

# 7  Discussion & Conclusion

We demonstrated a connection between DRIL, which accepts any loss of interest, and Maximum Entropy Inverse Reinforcement Learning—one of the widely used IRL approaches—which robustly minimizes logarithmic loss. We showed that MaxEnt is a special case of DRIL framework when logarithmic loss function is used and showed that DRIL can be seen as the maximizer of a generalized concept of entropy. We provided a novel approach to cast DRIL's objective into a convex optimization over a polynomial number of variables and experimentally showed our proposed algorithm provides faster training time. DRIL is naturally designed to perform robustly against noisy demonstrations. Our experiment in the highway driving task showed that when demonstrations are noisy, it robustly learns an appropriate policy.

Improvements in imitation learning have the potential for both societal benefits and harms. For example, better imitating top surgeons could scale their abilities to a broader populations that are medically under-served. Enabling robots that better imitate effective soldiers could cause great harm if used inappropriately. Like all general purpose tools, avoiding intentional harms while still providing benefits is an unsolved challenge. We take the position that providing methods that are more robust to noise will help to avoid *unintentional* harms—the application of methods in a well-intentioned manner that fail to maximize their benefits and may instead produce harms through their fragility.

Our presented experiments are restricted to discrete/low-dimensional decision processes. For future work, we are interested in finding a connection between DRIL and the Generalized Exponential family and applying DRIL on very high dimensional state and action spaces that need function approximators such as deep neural networks.

# References

[1] Pieter Abbeel and Andrew Y Ng. Apprenticeship learning via inverse reinforcement learning. In *Proceedings of the twenty-first international conference on Machine learning*, page 1. ACM, 2004.

[2] Kaiser Asif, Wei Xing, Sima Behpour, and Brian D. Ziebart. Adversarial cost-sensitive classification. In *Proceedings of the Conference on Uncertainty in Artificial Intelligence*, 2015.

[3] Ole E Barndorff-Nielsen. Information and exponential families. 1978.

[4] Aharon Ben-Tal, Dick Den Hertog, Anja De Waegenaere, Bertrand Melenberg, and Gijs Rennen. Robust solutions of optimization problems affected by uncertain probabilities. *Management Science*, 59(2):341–357, 2013.

[5] Xiangli Chen, Mathew Monfort, Brian D Ziebart, and Peter Carr. Adversarial inverse optimal control for general imitation learning losses and embodiment transfer. In *UAI*, 2016.

[6] Erick Delage and Yinyu Ye. Distributionally robust optimization under moment uncertainty with application to data-driven problems. *Operations research*, 58(3):595–612, 2010.

[7] Rizal Fathony, Mohammad Ali Bashiri, and Brian Ziebart. Adversarial surrogate losses for ordinal regression. In *Advances in Neural Information Processing Systems*, pages 563–573, 2017.

[8] Rizal Fathony, Ashkan Rezaei, Mohammad Ali Bashiri, Xinhua Zhang, and Brian Ziebart. Distributionally robust graphical models. In *Advances in Neural Information Processing Systems*, pages 8344–8355, 2018.

[9] Chelsea Finn, Paul Christiano, Pieter Abbeel, and Sergey Levine. A connection between generative adversarial networks, inverse reinforcement learning, and energy-based models. *arXiv preprint arXiv:1611.03852*, 2016.

[10] Chelsea Finn, Sergey Levine, and Pieter Abbeel. Guided cost learning: Deep inverse optimal control via policy optimization. In *International conference on machine learning*, pages 49–58, 2016.

[11] Justin Fu, Katie Luo, and Sergey Levine. Learning robust rewards with adversarial inverse reinforcement learning. *arXiv preprint arXiv:1710.11248*, 2017.

[12] Peter D. Grünwald and A. Phillip Dawid. Game theory, maximum entropy, minimum discrepancy, and robust Bayesian decision theory. *Annals of Statistics*, 32:1367–1433, 2004.

[13] Jonathan Ho and Stefano Ermon. Generative adversarial imitation learning. In *Advances in neural information processing systems*, pages 4565–4573, 2016.

[14] Rust John. Maximum likelihood estimation of discrete control processes. *SIAM journal on control and optimization*, 26(5):1006–1024, 1988.

[15] Michael Laskey, Jonathan Lee, Roy Fox, Anca Dragan, and Ken Goldberg. Dart: Noise injection for robust imitation learning. *arXiv preprint arXiv:1703.09327*, 2017.

[16] Sergey Levine, Zoran Popovic, and Vladlen Koltun. Nonlinear inverse reinforcement learning with gaussian processes. *Advances in neural information processing systems*, 24:19–27, 2011.

[17] H Brendan McMahan, Geoffrey J Gordon, and Avrim Blum. Planning in the presence of cost functions controlled by an adversary. In *Proceedings of the 20th International Conference on Machine Learning (ICML-03)*, pages 536–543, 2003.

[18] Andrew Y Ng and Stuart J Russell. Algorithms for inverse reinforcement learning. In *Icml*, volume 1, page 2, 2000.

[19] Dean A Pomerleau. Alvinn: An autonomous land vehicle in a neural network. In *Advances in neural information processing systems*, pages 305–313, 1989.

[20] Nathan D Ratliff, J Andrew Bagnell, and Martin A Zinkevich. Maximum margin planning. In *Proceedings of the 23rd international conference on Machine learning*, pages 729–736, 2006.

[21] Nathan D Ratliff, David Silver, and J Andrew Bagnell. Learning to search: Functional gradient techniques for imitation learning. *Autonomous Robots*, 27(1):25–53, 2009.

[22] Stéphane Ross and Drew Bagnell. Efficient reductions for imitation learning. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pages 661–668, 2010.

[23] Stéphane Ross, Geoffrey Gordon, and Drew Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pages 627–635, 2011.

[24] Stuart J Russell. Learning agents for uncertain environments. In *COLT*, volume 98, pages 101–103, 1998.

[25] Umar Syed, Michael Bowling, and Robert E Schapire. Apprenticeship learning using linear programming. In *Proceedings of the 25th international conference on Machine learning*, pages 1032–1039, 2008.

[26] Flemming Topsøe. Information theoretical optimization techniques. *Kybernetika*, 15(1):8–27, 1979.

[27] John Von Neumann. Uber ein okonomsiches gleichungssystem und eine verallgemeinering des browerschen fixpunktsatzes. In *Erge. Math. Kolloq.*, volume 8, pages 73–83, 1937.

[28] Hong Wang, Wei Xing, Kaiser Asif, and Brian Ziebart. Adversarial prediction games for multivariate losses. In *Advances in Neural Information Processing Systems*, pages 2710–2718, 2015.

[29] Jiangchuan Zheng, Siyuan Liu, and Lionel M Ni. Robust bayesian inverse reinforcement learning with sparse behavior noise. In *Twenty-Eighth AAAI Conference on Artificial Intelligence*, 2014.

[30] Brian D Ziebart, Andrew L Maas, J Andrew Bagnell, and Anind K Dey. Maximum entropy inverse reinforcement learning. 2008.

[31] Brian D Ziebart, J Andrew Bagnell, and Anind K Dey. Modeling interaction via the principle of maximum causal entropy. 2010.