Backpropagation-free training of neural PDE solvers for time-dependent problems

Abstract

Approximating solutions to time-dependent Partial Differential Equations (PDEs) is one of the most important problems in computational science. Neural PDE solvers have shown promise recently because they are mesh-free and easy to implement. However, backpropagation-based training often leads to poor approximation accuracy and long training time. In particular, capturing high-frequency temporal dynamics and solving over long time spans pose significant challenges. To address these, we present an approach to training neural PDE solvers without backpropagation by integrating two key ideas: separation of space and time variables and random sampling of weights and biases of the hidden layers. We reformulate the PDE as an Ordinary Differential Equation (ODE) using a neural network ansatz, construct neural basis functions only in the spatial domain, and solve the ODE leveraging classical ODE solvers from scientific computing. We demonstrate that our backpropagation-free algorithm outperforms the iterative, gradient-based optimization of physics-informed neural networks with respect to training time and accuracy, often by 1 to 5 orders of magnitude using different complicated PDEs characterized by high-frequency temporal dynamics, long time span, complex spatial domain, non-linearities, shocks, and high dimensionality.

1 Introduction

Approximating solutions of partial differential equations (PDEs) is vital in computational science and engineering. Traditional mesh-based numerical methods like finite differences, finite volumes, finite elements, or mesh-free methods based on global basis functions like spectral methods have been developed for decades. These methods often approximate PDE solutions with high accuracy and are grounded in theory. However, mesh-based methods are often difficult to implement on complicated domains due to the meshing difficulties and can be prohibitively expensive for high-dimensional problems owing to the curse of dimensionality. Traditional spectral methods often struggle with complicated domains and locally sharp gradients in the PDE solution (Boyd, 2001).

Deep neural networks have recently shown significant promise for approximating solutions of PDEs because of the mesh-free construction of basis functions, high expressivity of neural networks (Rudi & Rosasco, 2021), their ability to represent functions in high dimensions (E, 2020; Wu & Long, 2022), powerful software for automatic differentiation (e.g., Pytorch (Paszke et al., 2017), TensorFlow (Abadi et al., 2015), and specialized software like DeepXDE (Lu et al., 2021b)). Earlier work on solving PDEs using neural networks (Dissanayake & Phan-Thien, 1994; Lagaris et al., 1998) was recently popularized in the form of Physics-informed neural networks (PINNs) and neural operators by Raissi et al. (2019); Lu et al. (2021a); Li et al. (2020); Raonic et al. (2024); Han et al. (2018), and Sirignano & Spiliopoulos (2018). However, numerous challenges are becoming apparent. Next, we outline some of the key drawbacks of existing neural PDE solvers based on gradient-based iterative optimization that motivate our work: training difficulties, capturing high-frequency temporal dynamics, as well as long training time and low accuracy.

Training difficulties: Neural PDE solvers that rely on backpropagation-through-time require computing gradients of the loss function with respect to the network parameters along trajectories (Um et al., 2020). This usually leads to challenges posed by exploding and vanishing gradients during the iterative, gradient-based training procedure Pascanu et al. (2013); Schmidt et al. (2019). Physics-informed neural networks and their variants are not iterative in the same way, but require minimizing

a loss function involving the PDE residual, boundary conditions, and initial conditions. Rathore et al. (2024) demonstrate that the PDE residual loss primarily causes ill-conditioning of the PINN loss. It has been shown that even in simple settings, the PINN loss is very challenging to minimize using backpropagation (Krishnapriyan et al., 2021; Wang et al., 2021; 2022). Though various approaches such as balancing different loss terms (Yao et al., 2023), regularization (Lu et al., 2021c; Yu et al., 2022), and different optimizers (Müller & Zeinhofer, 2023; Liu et al., 2024) were introduced to alleviate some of the problems, it is still quite difficult to optimize PINNs with backpropagation.

Capturing high-frequency temporal dynamics and solving PDEs over a long time span: The temporal structure of initial value PDEs is local, as each subsequent step depends solely on the values of the preceding spatial slice — a property that typical physics-informed-machine-learning-based approaches, which treat time similar to an extra spatial dimension, fail to consider. We show that by using neural basis functions only in space and classical ODE solvers in time, one can capture high-frequency temporal dynamics and solve PDEs over long time spans.

Long training time and low accuracy: Approximation errors tend to be significant because of the gradient-based iterative optimization of network parameters and the challenges associated with handling time as an additional spatial dimension. This often leads to longer training times and much lower accuracy than classical mesh-based methods, especially for problems involving complex temporal dynamics or long time spans.

Figure 1: Solving a time-dependent PDE with a neural network ansatz: We sample hidden layer parameters w, b and fix the neural spatial basis functions (left) $\phi_i = \sigma(w_i x + b_i)$. The PDE to be solved is reformulated as an ODE in terms of the time-dependent output layer coefficients $c_i(t)$ (right), obtained by solving the ODE and computing the solution $\hat{u}(x,t)$.

To address these limitations, we propose an approach to training neural PDE solvers without backpropagation by integrating two key ideas: separation of variables (space and time) and random sampling of hidden layer weights and biases. For the latter, we employ Extreme Learning Machines (ELMs, cf. Huang et al. (2006)) and Sampling Where It Matters (SWIM, cf. Bolager et al. (2023)). Figure 1 illustrates the key components of our approach. Our key contributions are listed below.

- We propose two approaches to solving time-dependent PDEs with neural networks without backpropagation that synergistically combine data-driven (SWIM-ODE) or data-agnostic (ELM-ODE) sampling algorithms for computing hidden layer parameters with classical ODE solvers from scientific computing (See Section 3.2, Section 3.3).

- We propose novel techniques to satisfy boundary conditions for solving time-dependent PDEs with a neural network ansatz (See Section 3.4).

- We demonstrate the strengths of our backpropagation-free training algorithm for neural PDE solvers—high accuracy, reduced training time, spectral convergence, and mesh-free basis functions—by solving complex PDEs involving high-frequency temporal dynamics, long-time simulations, complicated domains, non-linearities, and shocks (See Section 4).

Our approach outperforms PINNs trained with backpropagation by 1-5 orders of magnitude in accuracy and up to 4 orders of magnitude in training time. Our approach is mesh-free, very easy to implement on complicated geometries, and significantly closes the accuracy gap with mesh-based methods like FEM.

2 RELATED WORK

Randomized neural networks for solving PDEs have been studied, mostly combining Extreme Learning Machines (ELMs) with the self-supervised setting of PINNs (Chen et al., 2024; Wang & Dong, 2024; Shang & Wang, 2024; Sun et al., 2024). Dwivedi & Srinivasan (2020) propose a physics-informed extreme learning machine (PIELM) to efficiently solve linear PDEs, while Calabrò et al. (2021); Galaris et al. (2022) employ ELMs to learn invariant manifolds as well as PDE from data. Dong & Yang (2022) establish that given a fixed computational budget, ELMs achieve substantially higher accuracy compared to classical second-order FEM and slightly higher accuracy compared to higher-order FEM. For static, nonlinear PDEs, ELMs can be used together with nonlinear optimization schemes (Fabiani et al., 2021). On larger spatiotemporal domains, Dong & Li (2021) and Dwivedi et al. (2021) propose using multiple distributed ELMs on multiple subdomains. These approaches treat time similarly to an extra dimension in space, and neural basis functions are used to span (a part of) the entire spatiotemporal domain, unlike our approach.

Neural Galerkin schemes (cf. work from Finzi et al. (2023); Aghili et al. (2024); Berman et al. (2024); Bruna et al. (2024)) offer an alternative to the full spatiotemporal approach of the randomized neural networks and PINNs. In these approaches, all network parameters, not just the parameters of the last layer, are considered time-dependent. This leads to a much larger system of ODEs compared to our approach. Chen et al. (2023); Yin et al. (2023) also use neural network basis functions to represent the space component but are based on backpropagation.

Physics-informed neural networks (PINNs) are widely used to solve PDEs with neural networks. For high-frequency temporal variations, Krishnapriyan et al. (2021) propose curriculum learning with gradually increasing advection coefficients. Our approach is much easier to implement, much more computationally efficient, and accurate, as we demonstrate in Section 4.1. Subramanian et al. (2023) propose using adaptive self-supervision of PINNs for sampling collocation points using the gradient of the loss function. We instead use the solution gradient to capture locally sharp features in the solution (cf. Section 4.4). Many specialized approaches based on PINNs (cf Cho et al. (2024), Meng et al. (2020)), Sharma & Shankar (2022), and Chiu et al. (2022)), methods based on hash-encoding (cf. Huang & Alkhalifah (2024), Wang et al. (2024a)) and transfer learning (cf. Kapoor et al. (2024b))) have been proposed, but are still based on backpropagation, unlike ours.

Classical numerical methods to solve PDEs: Finite elements, finite volumes, and finite differences have been used to solve PDEs for decades. They often have a rich theoretical grounding and high accuracy. Isogeometric analysis (IGA) is such a method in which spline-based basis functions are defined over a structured grid (cf. Hughes et al. (2005); Cottrell et al. (2009; 2006)). Mesh-based methods often entail a time-consuming setup phase, especially when mesh generation is challenging. In this work, we benchmark our results against IGA and finite-element-based methods.

For an extended review of related work, please refer to Appendix A.

3 APPROXIMATION OF PDE SOLUTIONS USING NEURAL NETWORKS

We discuss solution methods for PDEs on domains $\Omega \in \mathbb{R}^d$ with boundary $\partial\Omega$. We address linear and nonlinear time-dependent PDEs with solutions $u : \Omega \times \mathbb{R} \to \mathbb{R}$. These PDEs are defined by linear operators $\mathcal{L}$ and $\mathcal{B}$ that only involve derivative operators in space, and functions $f : \Omega \to \mathbb{R}$, $g : \partial\Omega \to \mathbb{R}$, and $u_0 : \Omega \to \mathbb{R}$ that define forcing, boundary condition, and initial condition, respectively. For nonlinear PDEs, we denote the nonlinear operator by $\mathcal{N}$, and its scaling $\gamma \geq 0$ is either zero (for linear PDEs) or positive (for nonlinear PDEs). Then,

$$u_t(x,t) + \mathcal{L}u(x,t) + \gamma\mathcal{N}(u)(x,t) = f(x), \ x \in \Omega, \ t \in [0,T], \tag{1}$$

$$\mathcal{B}u(x,t) = g(x), \ x \in \partial\Omega, \quad u(x,0) = u_0(x), \ x \in \Omega, \tag{2}$$

where we denote by u_t the first derivative of u by time.

We first describe the neural network ansatz in Section 3.1, and then describe how to construct the spatial basis functions of the ansatz in Section 3.2. For time-dependent PDEs, we propose solving an ordinary differential equation associated with our construction of the spatial basis using classical ODE solvers in Section 3.3 by evolving the last layer coefficients in time. In Section 3.4, we explain different approaches for satisfying boundary conditions by adding a linear layer. Lastly, in Section 3.5, we summarize the algorithm for backpropagation-free training of neural PDE solvers.

3.1 NEURAL NETWORK ANSATZ

We parameterize the approximation of a solution with a neural network with one hidden layer, activation function $\sigma = \tanh$, M neurons, so that

$$\hat{u}(x,t) = C(t)[\Phi(x), \mathbb{1}] = c(t)\sigma(Wx^\top + b) + c_0(t). \tag{3}$$

Here, $c(t) \in \mathbb{R}^{1 \times M}$ and $c_0(t) \in \mathbb{R}$ are time-dependent parameters, $W \in \mathbb{R}^{M \times d}$ and $b \in \mathbb{R}^{M \times 1}$ are time-independent parameters, and $C := [c, c_0] \in \mathbb{R}^{1 \times (M+1)}$. The activation functions are stacked in $\Phi = [\phi_1, \ldots, \phi_M]$, where $\phi_m(x) = \sigma(w_m x^\top + b_m)$. We will distinguish between two approaches with different weight spaces for the hidden layer. For the extreme learning machine (ELM) framework, the weight and bias space is the full space $\mathbb{R}^{M \times d} \times [-\eta, \eta]$, where η is sufficiently large. The second approach, the sampling where it matters (SWIM) framework, follows Bolager et al. (2023) and restricts the weight space to $\Omega \times \Omega$. We construct each weight and bias pair w_m, b_m by taking two points $x^{(1)}, x^{(2)} \in \Omega$ and construct the weight and bias as $w_m = s_1 \frac{x^{(2)} - x^{(1)}}{\|x^{(2)} - x^{(1)}\|^2}$, $b_m = -\langle w_m, x^{(1)}\rangle + s_2$, where s_1, s_2 are constants dependent on the activation function. We distinguish between the two approaches by referring to neural networks constructed by SWIM or ELM.

3.2 COMPUTING HIDDEN LAYER PARAMETERS WITHOUT GRADIENT-BASED OPTIMIZATION

To sample the coefficients of the first hidden layer, we propose two approaches: ELM and SWIM.

ELM (Data-agnostic): In ELM, the weights are sampled from a Gaussian distribution, and biases are sampled from a uniform distribution in $[-\eta, \eta]$ for each hidden layer, where η is a hyper-parameter.

SWIM (Data-dependent): The SWIM algorithm samples weights and biases using a data-dependent distribution. The weight and bias of each neuron in the hidden layer are sampled using one pair of spatial collocation points $(x^{(1)}, x^{(2)})$. In the unsupervised setting, one can choose pairs of collocation points from a uniform distribution over all possible pairs of collocation points, which is the default setting in this paper, as we do not know the solution of the PDE beforehand. In the supervised setting, the data points are selected based on the density $\frac{\|f(x^{(2)}) - f(x^{(1)})\|}{\|x^{(2)} - x^{(1)}\|}$, with f being the true function in a supervised setting. The weights and bias of each neuron with a $\tanh$ activation function are chosen such that the neuron's output is -0.5 for the input $x^{(1)}$ and $+0.5$ for the input $x^{(2)}$. This ensures that the centers of the activation functions are always placed in the spatial domain—unlike ELM, where the centers of the functions could be randomly placed outside the spatial domain. It also ensures that the activation functions are oriented in the direction from point $x^{(1)}$ to point $x^{(2)}$.

The key benefits of randomly sampling basis functions include much shorter training times and improved accuracy compared to PINNs (both from one to five orders of magnitude), nearly matching the numerical state-of-the-art solvers. Moreover, the advantages compared to the classical numerical solvers such as finite elements, finite differences, or finite volume approaches include spectral convergence (i.e., requiring much fewer basis functions) without requiring a mesh, making it much easier to implement on complex geometries.

The suitability of each of the proposed approaches depends on the true PDE solution's gradient distribution. We empirically observe that ELM performs better in approximating solutions with shallow gradients (cf. Section 4.1, cf. Section 4.2), while SWIM (by sampling weights from close data points) performs better in approximating solutions with steep gradients (cf. Section 4.4). In Figure 2, we illustrate the difference between the basis functions sampled with ELM and SWIM.

3.3 SOLVING TIME-DEPENDENT PDES BY SEPARATION OF VARIABLES

For both linear and nonlinear time-dependent PDEs, we plug the ansatz (see Equation (3)) into the PDE Equation (1) to re-formulate it as an ODE for the time-dependent coefficients $c(t)$. We first assemble N_c spatial collocation points in $\mathbb{R}^{1 \times d}$ in the columns of a matrix $X \in \mathbb{R}^{N_c \times d}$. We next sample weights and biases of M neurons and evaluate $\Phi(X)$. We then reformulate the PDE described in Equation (1) as an ODE,

$$C_t(t) = R(X, C(t))[\Phi(X), \mathbb{1}]^+, \quad \text{where}$$

$$R(X, C(t)) = -C(t)\mathcal{L}[\Phi(X), \mathbb{1}] - \gamma\mathcal{N}(C(t)[\Phi(X), \mathbb{1}]) + [f(X)]^\top, \tag{4}$$

Figure 2: SWIM sampling (left) is data-dependent and allows placement of basis functions near steep gradients. ELM sampling (right) is data-agnostic because the parameters of the basis functions are sampled from a Gaussian distribution.

where we denote the pseudo-inverse as $\cdot^+$, $[\Phi(X), \mathbb{1}] \in \mathbb{R}^{(M+1) \times N_c}$. The initial condition for this ODE is given through $C(0) = u(X, 0)^\top [\Phi(X), \mathbb{1}]^+$. We use classical solvers with step-size control like the Runge-Kutta-45 method (cf. Dormand & Prince (1980)) and implicit ODE solvers like LSODA (cf. Petzold (1983)). We then interpolate the predicted solution $C(t)$ at test points. The ansatz (see Equation (3)) does not explicitly take boundary conditions into consideration. In the next section, we discuss how to address this.

3.4 APPROACHES FOR SATISFYING BOUNDARY CONDITIONS

To satisfy certain boundary conditions, we propose adding a linear transformation $A \in \mathbb{R}^{M_b \times M_s}$, where $M_s := M$. We call this a "boundary-compliant layer" (See Figure 3). With this linear transformation, we now rewrite Equation (4) to

$$C_t(t) = R(X, C(t))\Phi_A(X)^+, \quad \text{where}$$
$$R(X, C(t)) = -C(t)\mathcal{L}\Phi_A(X) - \gamma\mathcal{N}(C(t)\Phi_A(X)) + [f(X)]^\top, \tag{5}$$

and $\Phi_A := [A\Phi, \mathbb{1}]$ and $C(t) \in \mathbb{R}^{1 \times (M_b+1)}$. The boundary conditions are dictated by $\mathcal{B}$ and g, which alters how we construct A. We now discuss how to compute A for different boundary conditions.

Periodic boundary condition: If each basis function satisfies the periodic boundary condition, then the ansatz, a linear combination of these functions, will also satisfy it. Thus, we find A so that $A\Phi(x_l) = A\Phi(x_r)$, where x_l, x_r are the left and right boundary points of the spatial domain. In this paper, if required for a given PDE, for $x \in \Omega$ and $k = 1, 2, \ldots, M_s$, we approximate $[A\Phi]_k(x) = \sin(kx)$ (for k even) and $[A\Phi]_k(x) = \cos(kx)$ (for k odd) and set $c_0(t) = 1$ for all t. This can be useful for PDEs where the basis functions are not known explicitly but only through boundary conditions, which we can then incorporate by constructing useful outer basis functions.

Dirichlet boundary conditions: For zero Dirichlet boundary condition $u(x) = 0$, we can use the technique described above by choosing basis functions so that $A\phi(x) = 0$ for $x \in \partial\Omega$.

For non-zero Dirichlet boundary condition, where $u(x) = g(x)$, we augment the ODE (Equation (5)) with an additional equation, $\hat{u}_t(x) = -\kappa(\hat{u}(x) - g(x))$ for $x \in \partial\Omega$, and solve the augmented ODE

$$C_t(t) = \underbrace{[R(X, C(t)), -\kappa(C(t)\Phi_A(X_b) - g(X_b)^\top)]}_{\in \mathbb{R}^{1 \times (N_c + N_b)}} \underbrace{\Phi_A([X, X_b])^+}_{\in \mathbb{R}^{(N_c + N_b) \times (M_b+1)}},$$

where $\kappa > 0$ is a fixed parameter, X are the N_c collocation points and $X_b \in \mathbb{R}^{N_b \times d}$ is a collection of N_b points on the boundary $\partial\Omega$. The intuition behind the augmented ODE for the boundary points is that the approximate solution is forced towards the true solution on the boundary with a rate proportional to the difference $(\hat{u}(x, t) - g(x))$ at any time step. We choose a default value of $\kappa = 100$. This technique with the augmented ODE allows setting A to the identity matrix (not using the linear layer at all) to enforce the Dirichlet boundary conditions.

Other types of boundary conditions: We use similar ideas to deal with time-dependent Dirichlet and Neumann boundary conditions (See Appendix B.1.1).

3.5 SVD LAYER AND SUMMARY OF THE BACKPROPAGATION-FREE ALGORITHM

As the last step in the construction of our architecture, we add a linear layer to improve the condition number of the associated ODE in Equation (5) and to reduce the size of the ODE system. To achieve this, we propose orthogonalizing the basis functions using an "SVD layer".

SVD layer: We compute a truncated singular value decomposition of $A\Phi(X) \in \mathbb{R}^{M_b \times N_c}$ to obtain matrices $V_r, \Sigma_r,$ and U_r with $r \leq M_b$ such that $V_r\Sigma_r U_r^\top = A\Phi(X) + O(\Sigma_{r+1})$. We then define $A_r := V_r^\top A$ and use it instead of the matrix A and $C(t) \in \mathbb{R}^{1 \times (r+1)}$. This ensures $A_r\Phi(X)$ are orthogonal functions on the data X, and the matrix $A_r\Phi(X)$ has a bounded condition number.

This completes the full procedure and we summarize it in Algorithm 1, where the hyper-parameter ϵ_{SVD} is a ratio of the largest to smallest singular value that governs how many singular values should be retained (width of the SVD-layer). In addition, Figure 3 visualizes the complete model $\hat{u}$. Finally, for the PDEs considered in this paper, we discuss how to reformulate those using neural network ansatz into corresponding ODEs in detail in Appendix B.1.2.

Algorithm 1 Backpropagation-free training algorithm to solve a given PDE

Input: PDE (Equation (1)) with boundary and initial conditions (Equation (2)), test grid points $X_{\text{test}} \times T_{\text{test}}$
Output: Solution of the PDE evaluated on the test grid points $\hat{u}(X_{\text{test}}, T_{\text{test}})$
Parameters: $N_c, M_s, M_b, \epsilon_{SVD}$

1: Sample N_c collocation points in a d-dimensional space and store it as a matrix $X \in \mathbb{R}^{N_c \times d}$
2: Construct hidden layer parameters $\{w_m, b_m\}_{m=1}^{M_s}$ using SWIM or ELM   ▷ Section 3.2
3: Compute the output of the hidden layer $\Phi(X) \in \mathbb{R}^{M_s \times N_c}$
4: Construct parameters of the linear hidden layer and evaluate $A\Phi(X) \in \mathbb{R}^{M_b \times N_c}$ ▷ Section 3.4
5: Compute truncated SVD with ϵ_{SVD}: $V_r\Sigma_r U_r^\top = A\Phi(X)$ and compute $V_r^\top A\Phi(X) = A_r\Phi(X)$
6: Compute the spatial basis functions $\Phi_{A_r}(X) := (A_r\Phi(X), 1)^\top \in \mathbb{R}^{(r+1) \times N_c}$
7: Compute the initial condition for the last layer parameters: $C(0) = u(X, 0)^\top \Phi_{A_r}(X)^+$
8: Compute $C(t) \in \mathbb{R}^{1 \times (r+1)}$ by solving the ODE using basis functions Φ_{A_r} ▷ Equation (5)
9: Compute $\hat{u}(X_{\text{test}}, T_{\text{test}}) = C(T_{\text{test}})\Phi_{A_r}(X_{\text{test}})$ ▷ Equation (3)

Figure 3: Architecture of our neural-PDE solver trained with backpropagation-free training algorithm.

4 COMPUTATIONAL EXPERIMENTS

We now demonstrate how our approach of separation of variables can be used to solve several time-dependent PDEs, each involving a different challenge. We compare our approach with physics-informed neural networks (PINNs), both classical Raissi et al. (2019) and causality-respecting (causal PINNs) Wang et al. (2024b). In contrast to the trend of comparing neural PDE-solvers only with other neural PDE-solvers, leading to overly optimistic views of neural solvers and neglecting numerical methods (cf. McGreivy & Hakim (2024)), we also benchmark our method against the state-of-the-art, mesh-based IGA-FEM method Hughes et al. (2005); Cottrell et al. (2009; 2006) or classical

FEM. We use the root mean squared error (RMSE) and the relative L^2 error to quantify errors in all experiments (cf. Appendix B for the definitions). We compute the test error on a uniform grid for all time-dependent PDEs with 256 points in space and 100 points in time. We perform all experiments with three seeds and report the mean and standard deviation in all numerical examples. We use the method `solve_ivp` in the Python package SciPy (cf. Virtanen et al. (2020)) to solve ODEs in Equation (5). The software and hardware environments used to perform the experiments are listed in Appendix B. Table 1 lists all PDEs we solve, together with forcing and boundary terms.

Table 1: Summary of PDEs we solve in this paper. T denotes the final time, functions f, g are forcing and boundary terms, and the parameters β, ν are described in their subsections.

Sec.	PDE		Boundary	Domain
4.1	Advection	$u_t + \beta u_x = 0$	$u(0,t) = u(2\pi, t)$	$[0, 2\pi] \times [0, T]$
4.2	Euler-Bernoulli	$u_{tt} + u_{xxxx} = f(x,t)$	$(u, u_{xx}) = 0$	$[0, \pi] \times [0, 1]$
4.3	Nonlinear diffusion	$u_t - u\Delta u = f(x,t)$	$g(x,t)$	$[0.65, 0.9]^2 \times [0, 1]$
4.4	Burgers'	$u_t + u u_x - \nu\Delta u = 0$	0	$[-1, 1] \times [0, 1]$
4.5	(n-dim) Diffusion	$u_t - \Delta u = f(x,t)$	$g(x,t)$	$[-1, 1]^n \times [0, 1]$

4.1 HIGH ADVECTION SPEEDS AND LONG-TIME SIMULATION

We consider the linear advection equation $u_t + \beta u_x = 0$ (also see Appendix C.1) with the initial condition $u(x, 0) = \sin(x)$ and periodic boundary conditions. The analytical solution is given by $u(x, t) = \sin(x - \beta t)$.

High advection speeds: We solve the advection equation using different neural PDE solvers and IGA-FEM for increasing flow velocities β over the domain $\Omega \times T = [0, 2\pi] \times [0, 1]$. The details on hyper-parameters and the setup of this experiment are listed in Appendix C.1. Figure 4 shows that approaches using basis functions in the entire spatiotemporal domain, such as PINNs, ELM, and SWIM, fail as the flow velocity β increases beyond 40. In contrast, ELM-ODE, SWIM-ODE, and IGA-FEM can accurately solve the PDE, even for high values of β. Figure 5 shows that for $\beta = 40$, L^2_{relative} decays exponentially with the number of basis functions for ELM-ODE, SWIM-ODE, and IGA-FEM. In contrast to IGA-FEM, which uses local basis functions, ELM-ODE and SWIM-ODE require fewer basis functions for a fixed L^2_{relative} because they use global basis functions. In this example, PINNs yield high errors. Note that compared to the curriculum learning approach proposed by Krishnapriyan et al. (2021), ELM-ODE and SWIM-ODE produce errors that are 4-5 orders of magnitude lower for the advection coefficient $\beta = 40$, are extremely fast. Our approach even works for convection coefficients as high as 10^4, where traditional neural PDE solvers completely fail.

Long-time simulation: We attempt to solve the PDE with $\beta = 1$ for $T = [0, 1000]$, with the true solution shown in Figure 6a. Simulating long-time dynamics is a longstanding challenge for traditional neural PDE solvers (Lippe et al., 2024; Kapoor et al., 2024a), and all solvers using neural network basis functions extending over both space and time, such as PINN, fail at approximating functions on long time intervals. Figure 6b shows that with ELM-ODE and SWIM-ODE, we can solve over 1000 seconds with L^2_{relative} of less than 0.001%, requiring only 0.94 seconds of runtime.

Figure 4: Growth of test error with varying flow velocities β for different PDE solvers (14 basis functions) and IGA-FEM (15 basis functions).

Figure 5: Fast exponential decay of test error with the number of neurons in the hidden layer (number of basis functions) for $\beta = 40$.

(a) Analytical solution $u(x,t) = \sin(x - \beta t)$ at $\beta = 1$.   (b) Slow error growth with time

Figure 6: Advection equation: Long time simulation at $\beta = 1$.

4.2 HIGHER-ORDER DERIVATIVES IN SPACE AND TIME

In this example, the beam equation ($u_{tt} + u_{xxxx} = f$, also see Appendix C.2) with fourth- and second-order derivatives in space and time, respectively, is solved with initial data $u(x,0) = \sin(x)$ on the spatial domain $\Omega = [0, \pi]$. The force function and the analytical solution are taken from Kapoor et al. (2023). The details of the PDE, the absolute error plots, and the comparison of approaches can be found in Appendix C.2. Table 2 shows that ELM-ODE is more than five orders of magnitude faster and more accurate than PINNs.

4.3 NON-LINEARITY AND COMPLICATED DOMAIN GEOMETRY

In this example, we demonstrate the efficiency and superior accuracy (by 4 orders of magnitude) of SWIM-ODE in solving a non-linear diffusion equation on a complicated spatial domain compared to PINNs (see Figure 12 for the geometry and Table 2 for results). SWIM-ODE with less than 500 basis functions is three orders of magnitude more accurate than the mesh-based FEM with 2000 finite elements (cf Table 10). We keep the grid points used to generate a mesh in the FEM the same as the data points used to solve the re-formulated ODE with our approach. Please refer to Appendix C.3 for further details on the PDE, the problem setup, and a comparison of our approaches to FEM and PINNs and Appendix B.1.1 for details on satisfying time-dependent Dirichlet boundary conditions.

4.4 NON-LINEARITY AND SHOCKS

We demonstrate how sampling weights and biases from a data-dependant distribution can be exploited to handle locally steep gradients in the solution of the non-linear viscous Burgers' equation. In Figure 8, we compare the SWIM-ODE solution to the numerical solution provided by Raissi et al. (2019). Table 16 indicates that ELM-ODE cannot accurately represent the sharp gradient in the domain's center due to the exponentially small probability of having large norms of internal weights. Sampling ELM-ODE weights from a broader uniform distribution increases the probability of having steeper basis functions, as Calabrò et al. (2021) discuss for linear PDEs. However, given enough collocation points in the domain's center, SWIM-ODE can create numerous basic functions with steep gradients, accurately placing them in the domain's center by factoring in the data. To concentrate collocation points near the shock in the domain's center, we resample them two times after a set number of time steps, guided by a probability distribution that leverages the gradient of the approximated solution. At the resampling time $t_r \in [0, T]$, we approximate the probability density $p(x) \sim |\nabla \hat{u}(x, t_r)|$, which we then use to re-sample collocation points at random. While PINNs provide a reasonable error, SWIM-ODE is more accurate by order of magnitude, almost twice as fast as regular PINN, and over ten times faster than causal PINN (See Table 2, Table 16). We demonstrate with a snapshot of the Burgers' solution that SWIM basis functions exhibit a rapid exponential decay of error with increasing network width, where Fourier and Chebyshev basis functions used in classical spectral methods suffer from the Gibbs phenomenon Gottlieb & Shu (1997) (See Appendix C.4.1).

4.5 HIGH-DIMENSIONALITY

The goal of this example is to highlight our algorithm's ability to solve high-dimensional PDEs efficiently, unlike the vanilla FEM and spectral methods, which suffer from exponential growth in grid points and basis functions as the dimension increases. We demonstrate in Figure 7 that ELM-ODE can solve the heat equation accurately in 3, 5, 7, and 10 dimensions, with a relative L^2

Table 2: Summary of the results of the computational experiments (a detailed comparison with more neural PDE solvers in Appendix C). We outperform PINNs trained with backpropagation by 1-5 orders of magnitude in accuracy and up to 4 orders of magnitude in training time. The results are even comparable to the state-of-the-art mesh-based solvers (shown in italics) while retaining all the advantages of mesh-free methods. Note that the number of basis functions differs for all methods and was chosen to optimize the individual results. For SWIM-ODE, the number of basis functions is always much lower than the finite elements used in the mesh-based methods.

PDE	Method	Training time (s)	Relative L^2 error
Advection ($\beta = 40$)	PINN	30.5	6.92e-1 $\pm$ 2.96e-2
	ELM-ODE (our)	2.7	3.84e-6 $\pm$ 5.2e-7
	Mesh-based method (IGA)	0.07	1.17e-10
Euler-Bernoulli	PINN	2303.71	4.21e-3 $\pm$ 9.56e-4
	ELM-ODE (our)	0.06	3.50e-8 $\pm$ 7.79e-9
	Mesh-based method (IGA)	0.94	4.21e-7
Burgers	PINN	275.2	3.88e-3 $\pm$ 2.61e-3
	SWIM-ODE (our)	141.5	3.33e-4 $\pm$ 4.63e-4
	Mesh-based method (IGA)	13.61	2.20e-4
Nonlinear diffusion	PINN	143.3	1.22e-2 $\pm$ 2.38e-4
	SWIM-ODE (our)	423	2.00e-6 $\pm$ 1.99e-6
	ELM-ODE (our)	4.8	7.34e-3 $\pm$ 1.8e-3
	Mesh-based method (FEM)	2.71	2.68e-3
10-d heat equation	PINN	189.6	6.06e-4 $\pm$ 1.00e-4
	ELM-ODE-fast (our)	0.65	7.18e-4 $\pm$ 3e-4
	ELM-ODE-accurate (our)	210.6	2.28e-5 $\pm$ 2.1e-5

error of around 6.4×10^{-8} to 2.2×10^{-5}. For the 3-dimensional heat equation, ELM-ODE is around 10000 times more accurate and 100 times faster than PINNs. For the 10-dimensional heat equation, ELM-ODE-fast has a lower width of 500 and matches the accuracy of PINNs but is 300 times faster to train, whereas ELM-ODE-accurate, with a higher width of 4000, is 25 times more accurate than PINNs. Note that if we consider 10 grid points per dimension for the FEM, one would need 10 billion grid points, whereas our approach requires around 3000 basis functions for the 10-dimensional heat equation. We also observe in Figure 7 that the error decays rapidly (roughly exponentially until dimension 5) for ELM-ODE until it plateaus at a certain network width. Moreover, the error is uniformly low in different parts of the domain. Due to the smoothness and lack of steep gradients in the solution of the PDE, ELM-ODE is clearly more suitable for approximating the solution of the chosen PDE and is one to three orders of magnitude more accurate than vanilla SWIM-ODE. We summarize the utility of our algorithm compared to the classical general-purpose methods in Table 3.

Figure 7: High-dimensional heat equation: (Left) Comparison of test errors for varying dimensions of the PDE, (Middle): Fast decay of test error with the number of neurons in the hidden layer (S: SWIM-ODE), (E: ELM-ODE), (Right): Pointwise test errors of ELM-ODE evaluated at 100 test points each in different 2-dimensional slices (all other dimensions set as the center values of the spatial domain) and time $t = 0.5$.

Table 3: Comparison of our algorithm with classical mesh-based FEM in different problem settings presented in this paper. Our algorithm (SWIM-ODE \ ELM-ODE) is fast, accurate, easy to implement, and robust to the different PDE settings (shocks, complicated geometries, high-dimensional PDEs). We use the acronym (CoD) for the Curse of Dimensionality in the following.

PDE setting	FEM	PINNs	SWIM-ODE \ ELM-ODE
Solutions with shocks	✓	✓	✓ (SWIM-ODE)
Complex domains	Difficult to mesh	Easy	Easy
High dimensionality	✗ (CoD)	✓	✓
Accuracy	High	Low	High
Speed	Fast	Training (slow)	Fast

Figure 8: Comparison of SWIM-ODE solution to Burgers' equation and ground truth. Black dashed lines indicate the times at which the solution is compared on the right. Gray dotted lines indicate the times at which the collocation points are re-sampled.

5 CONCLUSION

To address the fundamental difficulties stemming from the gradient-based iterative optimization of neural network parameters, we propose a backpropagation-free algorithm for training neural PDE solvers by combining ideas of separation of variables and random sampling of hidden layer parameters.

Benefits of our method: Firstly, we demonstrate that our backpropagation-free algorithm for training neural PDE solvers is 2 to $30,000$ times faster and, at the same time, 10 to $100,000$ times more accurate than the physics-informed neural networks trained with backpropagation for the PDEs considered in this paper. Secondly, by leveraging classical ODE solvers with adaptive time-stepping, we demonstrate that our neural PDE solver can capture high-frequency temporal dynamics and can solve over long time spans, where traditional state-of-the-art neural-PDE solvers fail. Thirdly, our approach reduces the accuracy gap with mesh-based solvers while retaining advantages like mesh-free basis functions, ease of implementation, ability to handle complex domains, and spectral convergence for PDEs with smooth solutions. Finally, we show that our approach can solve high-dimensional PDEs efficiently and accurately, as illustrated by the ten-dimensional heat equation considered in this paper.

Limitations and future work: Our approach requires knowledge of the entire PDE, so grey-box settings and inverse problems, where parts of the PDE must be estimated, are challenging. However, the much faster time-to-solution of our approach should prove very useful for this inverse problem setting. Compared to neural PDE solvers trained with backpropagation, our networks may require more neurons for the same accuracy, leading to higher inference times. A possible improvement for this is to use our approach to solve the PDE and then construct a smaller neural network to approximate the new solution. High-dimensional PDEs with complicated solutions remains an interesting avenue to explore further where traditional numerical methods have many difficulties due to the curse of dimensionality. We hope that our approach can open doors for neural PDE solvers to deal with real-world applications in science and engineering, especially applications where limited accuracy and long training times have been the main reasons for the lack of success.

Reproducibility Statement: The code to reproduce the experiments from the paper and an up-to-date code base can be found in the supplemental material and will be published as an open-source repository upon acceptance. We also run with different seeds to compute mean and standard deviations of the results, and store all seeds in the repository to enforce reproducibility. The dataset describing the complicated geometry used in Section 4.3 is included in the supplemental material, and the details to reproduce all experiments can be found in Appendix C.

Ethics Statement: Ethical considerations are important for any new machine learning approach because neural networks are generally dual-use. Our approach is based on classical methods from scientific computing, which are well understood. This connection now allows researchers to better understand our neural solvers' behavior, failure modes, and robustness. We believe that the benefits of our approach far outweigh the potential downsides of misuse because a system that is understood better can also be controlled more straightforwardly.

REFERENCES

Martín Abadi, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S. Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Ian Goodfellow, Andrew Harp, Geoffrey Irving, Michael Isard, Yangqing Jia, Rafal Jozefowicz, Lukasz Kaiser, Manjunath Kudlur, Josh Levenberg, Dandelion Mané, Rajat Monga, Sherry Moore, Derek Murray, Chris Olah, Mike Schuster, Jonathon Shlens, Benoit Steiner, Ilya Sutskever, Kunal Talwar, Paul Tucker, Vincent Vanhoucke, Vijay Vasudevan, Fernanda Viégas, Oriol Vinyals, Pete Warden, Martin Wattenberg, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. TensorFlow: Large-scale machine learning on heterogeneous systems, 2015. Software available from tensorflow.org.

Joubine Aghili, Joy Zialesi Atokple, Marie Billaud-Friess, Guillaume Garnier, Olga Mula, and Norbert Tognon. A Dynamical Neural Galerkin Scheme for Filtering Problems, January 2024.

Igor A. Baratta, Joseph P. Dean, Jørgen S. Dokken, Michal Habera, Jack S. Hale, Chris N. Richardson, Marie E. Rognes, Matthew W. Scroggs, Nathan Sime, and Garth N. Wells. DOLFINx: the next generation FEniCS problem solving environment. preprint, 2023.

Jules Berman and Benjamin Peherstorfer. Randomized sparse neural galerkin schemes for solving evolution equations with deep networks. *Advances in Neural Information Processing Systems*, 36, 2024.

Jules Berman, Paul Schwerdtner, and Benjamin Peherstorfer. Neural Galerkin schemes for sequential-in-time solving of partial differential equations with deep networks. In *Handbook of Numerical Analysis*, volume 25, pp. 389–418. Elsevier, 2024. ISBN 978-0-443-23984-7. doi: 10.1016/bs.hna.2024.05.006.

Erik L Bolager, Iryna Burak, Chinmay Datar, Qing Sun, and Felix Dietrich. Sampling weights of deep neural networks. In *Advances in Neural Information Processing Systems*, volume 36, pp. 63075–63116. Curran Associates, Inc., 2023.

John P Boyd. *Chebyshev and Fourier spectral methods*. Courier Corporation, 2001.

Joan Bruna, Benjamin Peherstorfer, and Eric Vanden-Eijnden. Neural Galerkin schemes with active learning for high-dimensional evolution equations. *Journal of Computational Physics*, 496:112588, January 2024. ISSN 00219991. doi: 10.1016/j.jcp.2023.112588.

Francesco Calabrò, Gianluca Fabiani, and Constantinos Siettos. Extreme learning machine collocation for the numerical solution of elliptic PDEs with sharp gradients. *Computer Methods in Applied Mechanics and Engineering*, 387:114188, December 2021. ISSN 00457825. doi: 10.1016/j.cma.2021.114188.

Jingrun Chen, Weinan E, and Yifei Sun. Optimization of random feature method in the high-precision regime. *Communications on Applied Mathematics and Computation*, pp. 1–28, 2024.

Peter Yichen Chen, Jinxu Xiang, Dong Heon Cho, Yue Chang, G A Pershing, Henrique Teles Maia, Maurizio M Chiaramonte, Kevin Thomas Carlberg, and Eitan Grinspun. CROM: Continuous reduced-order modeling of PDEs using implicit neural representations. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=FUORz1tG8Og.

Wen Chen, Zhuo-Jia Fu, and C.S. Chen. *Recent Advances in Radial Basis Function Collocation Methods*. Springer Berlin Heidelberg, 2014. ISBN 9783642395727. doi: 10.1007/978-3-642-39572-7.

Pao-Hsiung Chiu, Jian Cheng Wong, Chinchun Ooi, My Ha Dao, and Yew-Soon Ong. Can-pinn: A fast physics-informed neural network based on coupled-automatic–numerical differentiation method. *Computer Methods in Applied Mechanics and Engineering*, 395:114909, 2022.

Junwoo Cho, Seungtae Nam, Hyunmo Yang, Seok-Bae Yun, Youngjoon Hong, and Eunbyung Park. Separable physics-informed neural networks. *Advances in Neural Information Processing Systems*, 36, 2024.

J. Austin Cottrell, Thomas J. R. Hughes, and Yuri Bazilevs. *Isogeometric Analysis: Toward Integration of CAD and FEA*. Wiley Publishing, 1st edition, 2009. ISBN 0470748737.

J.A. Cottrell, A. Reali, Y. Bazilevs, and T.J.R. Hughes. Isogeometric analysis of structural vibrations. *Computer Methods in Applied Mechanics and Engineering*, 195(41):5257–5296, 2006. ISSN 0045-7825. doi: https://doi.org/10.1016/j.cma.2005.09.027. John H. Argyris Memorial Issue. Part II.

M. G. COX. The Numerical Evaluation of B-Splines*. *IMA Journal of Applied Mathematics*, 10(2): 134–149, 10 1972. ISSN 0272-4960. doi: 10.1093/imamat/10.2.134.

Carl de Boor. On calculating with b-splines. *Journal of Approximation Theory*, 6(1):50–62, 1972. ISSN 0021-9045. doi: https://doi.org/10.1016/0021-9045(72)90080-9.

MWMG Dissanayake and Nhan Phan-Thien. Neural-network-based approximations for solving partial differential equations. *communications in Numerical Methods in Engineering*, 10(3): 195–201, 1994.

Suchuan Dong and Zongwei Li. Local extreme learning machines and domain decomposition for solving linear and nonlinear partial differential equations. *Computer Methods in Applied Mechanics and Engineering*, 387:114129, 2021.

Suchuan Dong and Jielin Yang. On computing the hyperparameter of extreme learning machines: Algorithm and application to computational pdes, and comparison with classical and high-order finite elements. *Journal of Computational Physics*, 463:111290, 2022.

John R Dormand and Peter J Prince. A family of embedded runge-kutta formulae. *Journal of computational and applied mathematics*, 6(1):19–26, 1980.

Gideon Dresdner, Dmitrii Kochkov, Peter Christian Norgaard, Leonardo Zepeda-Nunez, Jamie Smith, Michael Brenner, and Stephan Hoyer. Learning to correct spectral methods for simulating turbulent flows. *Transactions on Machine Learning Research*, 2022.

Yifan Du and Tamer A Zaki. Evolutional deep neural network. *Physical Review E*, 104(4):045303, 2021.

Yiheng Du, Nithin Chalapathi, and Aditi Krishnapriyan. Neural spectral methods: Self-supervised learning in the spectral domain. *arXiv preprint arXiv:2312.05225*, 2023.

Vikas Dwivedi and Balaji Srinivasan. Physics informed extreme learning machine (pielm)–a rapid method for the numerical solution of partial differential equations. *Neurocomputing*, 391:96–118, 2020.

Vikas Dwivedi, Nishant Parashar, and Balaji Srinivasan. Distributed learning machines for solving forward and inverse problems in partial differential equations. *Neurocomputing*, 420:299–316, 2021.

Weinan E. Towards a Mathematical Understanding of Neural Network-Based Machine Learning: What We Know and What We Don't. *CSIAM Transactions on Applied Mathematics*, 1(4):561–615, June 2020. ISSN 2708-0560, 2708-0579. doi: 10.4208/csiam-am.SO-2020-0002.

Gianluca Fabiani, Francesco Calabrò, Lucia Russo, and Constantinos Siettos. Numerical solution and bifurcation analysis of nonlinear partial differential equations with extreme learning machines. *Journal of Scientific Computing*, 89(2):44, November 2021. ISSN 0885-7474, 1573-7691. doi: 10.1007/s10915-021-01650-5.

Marc Finzi, Andres Potapczynski, Matthew Choptuik, and Andrew Gordon Wilson. A stable and scalable method for solving initial value pdes with neural networks. *arXiv preprint arXiv:2304.14994*, 2023.

Evangelos Galaris, Gianluca Fabiani, Ioannis Gallos, Ioannis Kevrekidis, and Constantinos Siettos. Numerical Bifurcation Analysis of PDEs From Lattice Boltzmann Model Simulations: A Parsimonious Machine Learning Approach. *Journal of Scientific Computing*, 92(2):34, August 2022. ISSN 0885-7474, 1573-7691. doi: 10.1007/s10915-022-01883-y.

Christophe Geuzaine and Jean-François Remacle. Gmsh: A 3-d finite element mesh generator with built-in pre- and post-processing facilities. *International Journal for Numerical Methods in Engineering*, 79:1309 – 1331, 09 2009. doi: 10.1002/nme.2579.

R. A. Gingold and J. J. Monaghan. Smoothed particle hydrodynamics: theory and application to non-spherical stars. *Monthly Notices of the Royal Astronomical Society*, 181(3):375–389, 12 1977. ISSN 0035-8711. doi: 10.1093/mnras/181.3.375.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pp. 249–256. JMLR Workshop and Conference Proceedings, 2010.

David Gottlieb and Chi-Wang Shu. On the gibbs phenomenon and its resolution. *SIAM review*, 39(4): 644–668, 1997.

Jiequn Han, Arnulf Jentzen, and Weinan E. Solving high-dimensional partial differential equations using deep learning. *Proceedings of the National Academy of Sciences*, 115(34):8505–8510, 2018.

Guang-Bin Huang, Qin-Yu Zhu, and Chee-Kheong Siew. Extreme learning machine: theory and applications. *Neurocomputing*, 70(1-3):489–501, 2006.

Xinquan Huang and Tariq Alkhalifah. Efficient physics-informed neural networks using hash encoding. *Journal of Computational Physics*, 501:112760, 2024.

T.J.R. Hughes, J.A. Cottrell, and Y. Bazilevs. Isogeometric analysis: Cad, finite elements, nurbs, exact geometry and mesh refinement. *Computer Methods in Applied Mechanics and Engineering*, 194(39):4135–4195, 2005.

Tanveer ul Islam and Prasanna S Gandhi. Viscous fingering in multiport hele shaw cell for controlled shaping of fluids. *Scientific reports*, 7(1):16602, 2017.

Taniya Kapoor, Hongrui Wang, Alfredo Núñez, and Rolf Dollevoet. Physics-informed neural networks for solving forward and inverse problems in complex beam systems. *IEEE Transactions on Neural Networks and Learning Systems*, 2023.

Taniya Kapoor, Abhishek Chandra, Daniel M Tartakovsky, Hongrui Wang, Alfredo Nunez, and Rolf Dollevoet. Neural oscillators for generalization of physics-informed machine learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pp. 13059–13067, 2024a.

Taniya Kapoor, Hongrui Wang, Alfredo Núñez, and Rolf Dollevoet. Transfer learning for improved generalizability in causal physics-informed neural networks for beam simulations. *Engineering Applications of Artificial Intelligence*, 133:108085, 2024b.

Mariella Kast and Jan S Hesthaven. Positional embeddings for solving pdes with evolutional deep neural networks. *Journal of Computational Physics*, 508:112986, 2024.

Nikola B. Kovachki, Zongyi Li, Burigede Liu, Kamyar Azizzadenesheli, Kaushik Bhattacharya, Andrew M. Stuart, and Anima Anandkumar. Neural operator: Learning maps between function spaces. *CoRR*, abs/2108.08481, 2021.

Aditi Krishnapriyan, Amir Gholami, Shandian Zhe, Robert Kirby, and Michael W Mahoney. Characterizing possible failure modes in physics-informed neural networks. *Advances in neural information processing systems*, 34:26548–26560, 2021.

Isaac E Lagaris, Aristidis Likas, and Dimitrios I Fotiadis. Artificial neural networks for solving ordinary and partial differential equations. *IEEE transactions on neural networks*, 9(5):987–1000, 1998.

Peter Lancaster and Kestutis Salkauskas. Surfaces generated by moving least squares methods. *Mathematics of Computation*, 37:141–158, 1981.

Henning Lange, Steven L Brunton, and J Nathan Kutz. From fourier to koopman: Spectral methods for long-term time series prediction. *Journal of Machine Learning Research*, 22(41):1–38, 2021.

Zongyi Li, Nikola Borislavov Kovachki, Kamyar Azizzadenesheli, Kaushik Bhattacharya, Andrew Stuart, Anima Anandkumar, et al. Fourier neural operator for parametric partial differential equations. In *International Conference on Learning Representations*, 2020.

Phillip Lippe, Bas Veeling, Paris Perdikaris, Richard Turner, and Johannes Brandstetter. Pde-refiner: Achieving accurate long rollouts with neural pde solvers. *Advances in Neural Information Processing Systems*, 36, 2024.

Qiang Liu, Mengyu Chu, and Nils Thuerey. Config: Towards conflict-free training of physics informed neural networks. *arXiv preprint arXiv:2408.11104*, 2024.

Lu Lu, Pengzhan Jin, Guofei Pang, Zhongqiang Zhang, and George Em Karniadakis. Learning nonlinear operators via deeponet based on the universal approximation theorem of operators. *Nature machine intelligence*, 3(3):218–229, 2021a.

Lu Lu, Xuhui Meng, Zhiping Mao, and George Em Karniadakis. DeepXDE: A deep learning library for solving differential equations. *SIAM Review*, 63(1):208–228, 2021b. doi: 10.1137/19M1274067.

Lu Lu, Raphael Pestourie, Wenjie Yao, Zhicheng Wang, Francesc Verdugo, and Steven G Johnson. Physics-informed neural networks with hard constraints for inverse design. *SIAM Journal on Scientific Computing*, 43(6):B1105–B1132, 2021c.

L. B. Lucy. A numerical approach to the testing of the fission hypothesis. *The Astronomical Journal*, 82:1013–1024, December 1977. doi: 10.1086/112164.

Nick McGreivy and Ammar Hakim. Weak baselines and reporting biases lead to overoptimism in machine learning for fluid-related partial differential equations. *arXiv preprint arXiv:2407.07218*, 2024.

Xuhui Meng, Zhen Li, Dongkun Zhang, and George Em Karniadakis. Ppinn: Parareal physics-informed neural network for time-dependent pdes. *Computer Methods in Applied Mechanics and Engineering*, 370:113250, 2020.

Brek Meuris, Saad Qadeer, and Panos Stinis. Machine-learning-based spectral methods for partial differential equations. *Scientific Reports*, 13(1):1739, 2023.

Johannes Müller and Marius Zeinhofer. Achieving high accuracy with pinns via energy natural gradient descent. In *International Conference on Machine Learning*, pp. 25471–25485. PMLR, 2023.

Razvan Pascanu, Tomas Mikolov, and Yoshua Bengio. On the difficulty of training recurrent neural networks. In *International conference on machine learning*, pp. 1310–1318. Pmlr, 2013.

Adam Paszke, Sam Gross, Soumith Chintala, Gregory Chanan, Edward Yang, Zachary DeVito, Zeming Lin, Alban Desmaison, Luca Antiga, and Adam Lerer. Automatic differentiation in PyTorch, 2017.

Benjamin Peherstorfer. Breaking the kolmogorov barrier with nonlinear model reduction. *Notices of the American Mathematical Society*, 69(5):725–733, 2022.

Linda Petzold. Automatic selection of methods for solving stiff and nonstiff systems of ordinary differential equations. *SIAM journal on scientific and statistical computing*, 4(1):136–148, 1983.

Tobias Pfaff, Meire Fortunato, Alvaro Sanchez-Gonzalez, and Peter Battaglia. Learning mesh-based simulation with graph networks. In *International Conference on Learning Representations*, 2021.

Les Piegl and Wayne Tiller. *The NURBS book (2nd ed.)*. Springer-Verlag, Berlin, Heidelberg, 1997. ISBN 3540615458.

M J D Powell. The Theory of Radial Basis Function Approximation in 1990. In *Advances in Numerical Analysis: Wavelets, Subdivision Algorithms, and Radial Basis Functions*. Oxford University Press, 04 1992. ISBN 9780198534396. doi: 10.1093/oso/9780198534396.003.0003.

Serge Prudhomme, Frédéric Pascal, J.Tinsley Oden, and Albert Romkes. A priori error estimate for the baumann–oden version of the discontinuous galerkin method. *Comptes Rendus de l'Académie des Sciences - Series I - Mathematics*, 332(9):851–856, 2001. ISSN 0764-4442. doi: https://doi.org/10.1016/S0764-4442(01)01936-X.

Maziar Raissi, Paris Perdikaris, and George E Karniadakis. Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational physics*, 378:686–707, 2019.

Bogdan Raonic, Roberto Molinaro, Tim De Ryck, Tobias Rohner, Francesca Bartolucci, Rima Alaifari, Siddhartha Mishra, and Emmanuel de Bézenac. Convolutional neural operators for robust and accurate learning of pdes. *Advances in Neural Information Processing Systems*, 36, 2024.

Pratik Rathore, Weimu Lei, Zachary Frangella, Lu Lu, and Madeleine Udell. Challenges in training pinns: A loss landscape perspective. *arXiv preprint arXiv:2402.01868*, 2024.

Alessandro Rudi and Lorenzo Rosasco. Generalization Properties of Learning with Random Features, April 2021.

Dominik Schmidt, Georgia Koppe, Zahra Monfared, Max Beutelspacher, and Daniel Durstewitz. Identifying nonlinear dynamical systems with multiple time scales and long-range dependencies. *arXiv preprint arXiv:1910.03471*, 2019.

M.S. Shadloo, G. Oger, and D. Le Touzé. Smoothed particle hydrodynamics method for fluid flows, towards industrial applications: Motivations, current state, and challenges. *Computers & Fluids*, 136:11–34, 2016. ISSN 0045-7930. doi: https://doi.org/10.1016/j.compfluid.2016.05.029.

Yong Shang and Fei Wang. Randomized Neural Networks with Petrov–Galerkin Methods for Solving Linear Elasticity and Navier–Stokes Equations. *Journal of Engineering Mechanics*, 150 (4):04024010, April 2024. ISSN 0733-9399, 1943-7889. doi: 10.1061/JENMDT.EMENG-7463.

Ramansh Sharma and Varun Shankar. Accelerated training of physics-informed neural networks (pinns) using meshless discretizations. *Advances in Neural Information Processing Systems*, 35:1034–1046, 2022.

Donald Shepard. A two-dimensional interpolation function for irregularly-spaced data. In *Proceedings of the 1968 23rd ACM National Conference*, ACM '68, pp. 517–524, New York, NY, USA, 1968. Association for Computing Machinery. ISBN 9781450374866. doi: 10.1145/800186.810616.

Justin Sirignano and Konstantinos Spiliopoulos. Dgm: A deep learning algorithm for solving partial differential equations. *Journal of computational physics*, 375:1339–1364, 2018.

Shashank Subramanian, Robert M Kirby, Michael W Mahoney, and Amir Gholami. Adaptive self-supervision algorithms for physics-informed neural networks. In *ECAI 2023*, pp. 2234–2241. IOS Press, 2023.

Jingbo Sun, Suchuan Dong, and Fei Wang. Local randomized neural networks with discontinuous Galerkin methods for partial differential equations. *Journal of Computational and Applied Mathematics*, 445:115830, August 2024. ISSN 03770427. doi: 10.1016/j.cam.2024.115830.

Kiwon Um, Robert Brand, Yun Raymond Fei, Philipp Holl, and Nils Thuerey. Solver-in-the-loop: Learning from differentiable physics to interact with iterative pde-solvers. *Advances in Neural Information Processing Systems*, 33:6111–6122, 2020.

Pauli Virtanen, Ralf Gommers, Travis E. Oliphant, Matt Haberland, Tyler Reddy, David Cournapeau, Evgeni Burovski, Pearu Peterson, Warren Weckesser, Jonathan Bright, Stéfan J. van der Walt, Matthew Brett, Joshua Wilson, K. Jarrod Millman, Nikolay Mayorov, Andrew R. J. Nelson, Eric Jones, Robert Kern, Eric Larson, C J Carey, İlhan Polat, Yu Feng, Eric W. Moore, Jake VanderPlas, Denis Laxalde, Josef Perktold, Robert Cimrman, Ian Henriksen, E. A. Quintero, Charles R. Harris, Anne M. Archibald, Antônio H. Ribeiro, Fabian Pedregosa, Paul van Mulbregt, and SciPy 1.0 Contributors. SciPy 1.0: Fundamental Algorithms for Scientific Computing in Python. *Nature Methods*, 17:261–272, 2020. doi: 10.1038/s41592-019-0686-2.

Haoxiang Wang, Tao Yu, Tianwei Yang, Hui Qiao, and Qionghai Dai. Neural physical simulation with multi-resolution hash grid encoding. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pp. 5410–5418, 2024a.

Sifan Wang, Yujun Teng, and Paris Perdikaris. Understanding and mitigating gradient flow pathologies in physics-informed neural networks. *SIAM Journal on Scientific Computing*, 43(5):A3055–A3081, 2021.

Sifan Wang, Xinling Yu, and Paris Perdikaris. When and why pinns fail to train: A neural tangent kernel perspective. *Journal of Computational Physics*, 449:110768, 2022.

Sifan Wang, Shyam Sankaran, and Paris Perdikaris. Respecting causality for training physics-informed neural networks. *Computer Methods in Applied Mechanics and Engineering*, 421: 116813, 2024b.

Yiran Wang and Suchuan Dong. An extreme learning machine-based method for computational pdes in higher dimensions. *Computer Methods in Applied Mechanics and Engineering*, 418:116578, 2024.

Lei Wu and Jihao Long. A Spectral-Based Analysis of the Separation between Two-Layer Neural Networks and Linear Methods. *Journal of Machine Learning Research*, 23(1), January 2022. ISSN 1532-4435.

Mingtao Xia, Lucas Böttcher, and Tom Chou. Spectrally adapted physics-informed neural networks for solving unbounded domain problems. *Machine Learning: Science and Technology*, 4(2): 025024, 2023.

Jiachen Yao, Chang Su, Zhongkai Hao, Songming Liu, Hang Su, and Jun Zhu. Multiadam: Parameter-wise scale-invariant optimizer for multiscale training of physics-informed neural networks. In *International Conference on Machine Learning*, pp. 39702–39721. PMLR, 2023.

Yuan Yin, Matthieu Kirchmeyer, Jean-Yves Franceschi, Alain Rakotomamonjy, and Patrick Gallinari. Continuous pde dynamics forecasting with implicit neural representations. In *International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=B73niNjbPs.

Jeremy Yu, Lu Lu, Xuhui Meng, and George Em Karniadakis. Gradient-enhanced physics-informed neural networks for forward and inverse pde problems. *Computer Methods in Applied Mechanics and Engineering*, 393:114823, 2022.

APPENDIX

CONTENTS

A EXTENDED REVIEW OF RELATED WORK

Spectral methods for solving PDEs promise fast convergence with much fewer basis functions. Meuris et al. (2023) present a method to extract hierarchical spatial basis functions from a trained DeepONet and employ it in a spectral method to solve the given PDE. Xia et al. (2023) integrate adaptive techniques into PINN-based PDE solvers to obtain numerical solutions of unbounded domain problems that standard PINNs cannot efficiently approximate. Lange et al. (2021) propose spectral methods that fit linear and nonlinear oscillators to data and facilitate long-term forecasting of temporal signals. Dresdner et al. (2022) demonstrate spectral solvers that provide sub-grid corrections to classical spectral methods to improve their accuracy. Du et al. (2023) use fixed orthogonal bases to learn PDE solutions as a map between spectral coefficients and introduce a training strategy based on spectral loss. These methods differ from ours in problem setting, architecture, and training.

Neural operator frameworks (cf. Lu et al. (2021a); Kovachki et al. (2021); Li et al. (2020); Pfaff et al. (2021)) are promising but are typically trained with PDE solutions with different initial conditions, spatial domains (geometries), or parameter settings. Instead, in our setting here, we solve the PDE using given coefficients, domain, and initial conditions without relying on any training data. The ease of implementation, rapid training, and high accuracy of our backpropagation-free approach can be leveraged to generate PDE solution data for training operator networks.

Mesh-free methods are typically based on radial basis functions (RBFs, cf. Powell (1992); Chen et al. (2014)) or moving least squares (MLS, cf. Shepard (1968); Lancaster & Salkauskas (1981)). These often do not have user-friendly software or are only applicable in specialized settings (e.g., smoothed particle hydrodynamics, cf. Lucy (1977); Gingold & Monaghan (1977); Shadloo et al. (2016)). Moreover, despite the ease of dealing with complicated geometries, these methods typically suffer from many challenges, such as the choice of kernel, imposing boundary conditions, and convergence issues. These methods are not the focus of this work.

B METHODS

B.1 SWIM-ODE AND ELM-ODE

B.1.1 HANDLING BOUNDARY CONDITIONS

Our approaches to satisfying the Dirichlet and periodic boundary conditions are already explained in the main text. Here, we explain how we handle time-dependent Dirichlet boundary conditions and Neumann boundary conditions.

Time-dependent Dirichlet boundary conditions: For handling time-dependent Dirichlet boundary conditions ($u(x,t) = g(x,t)$ for $x \in \partial\Omega$), we set A to the identity map and augment the ODE (Equation (4)) with an additional equation,

$$\hat{u}_t(x,t) = g_t(x,t) \text{ for } x \in \partial\Omega \implies C_t(t) = \underbrace{[R(X,C(t)), g_t(X_b,t)]}_{\in \mathbb{R}^{1\times(N_c+N_b)}} \underbrace{\Phi_A([X,X_b])^+}_{\in \mathbb{R}^{(N_c+N_b)\times(M_b+1)}},$$

In the example in Section 4.3, we know the solution on the boundary at all time points, which is continuously differentiable. If the solution on the boundary points is not available at all time points, one can interpolate and approximate the derivative of the solution on the boundary.

Neumann boundary conditions: For simple spatial domains, one can choose appropriate outer basis functions as described in Appendix B.1.1 that inherently satisfy the Neumann boundary conditions. For instance, for zero Neumann boundary conditions on a one-dimensional domain, one can choose outer basis functions consisting of cosines of different frequencies scaled to the domain (function value is 1 at the boundaries) so that their spatial derivatives, which are the sine functions, are zero on the boundary points.

On complicated domain geometries, to satisfy Neumann boundary conditions ($\nabla u(x,t) \cdot \hat{n}(x) = 0$ for $x \in \partial\Omega$), we set A to the identity map and augment the ODE (Equation (4)) with an additional equation for the boundary points and solve

$$C_t(t) = \underbrace{[R(X,C(t)), 0]}_{\in \mathbb{R}^{1\times(N_c+N_b)}} \underbrace{[\Phi_A(X), \nabla\Phi_A(X_b)[\hat{n}(X_b)]^\top]^+}_{\in \mathbb{R}^{(N_c+N_b)\times(M_b+1)}}.$$

B.1.2 DERIVATION OF SPECIFIC FORM OF ODES

We use the notation described in Section 3 of the manuscript. We first discuss how to compute different spatial and temporal derivative terms appearing in the PDEs described in this manuscript using the neural network ansatz. We then use these expressions to reformulate the PDEs described in this manuscript as corresponding ODEs. We consider neural networks in the most general setting by considering the outer basis functions and the SVD layer (cf Algorithm 1).

Computing spatial and temporal derivatives of the neural network solution

Computing spatial derivatives: We compute the first-order spatial derivative as

$$\hat{u}_x(x,t) = C(t)[\Phi_{A_r}]_x(x)$$
$$= C(t)[A_r W \odot \tilde{\sigma}_x(x), 0] \in \mathbb{R}^{1 \times d}, \tag{6}$$

where $\odot$ is the Hadamard product,

$$\tilde{\sigma}_x(x) := [\sigma_z(z)|_{z=Wx^\top+b}, \sigma_z(z)|_{z=Wx^\top+b}, \ldots, \sigma_z(z)|_{z=Wx^\top+b}] \in \mathbb{R}^{M_s \times d}, \tag{7}$$

with $\sigma_z(z) \in \mathbb{R}^{M_s}$ and σ_z is the first derivative of the $tanh$ activation function.

Similarly, we compute the second- and fourth-order spatial derivatives as:

$$\hat{u}_{xx}(x,t) = C(t)[\Phi_{A_r}]_{xx}(x)$$
$$= C(t)[A_r W \odot W \odot \tilde{\sigma}_{xx}(x), 0] \in \mathbb{R}^{1 \times d}, \tag{8}$$

where $\tilde{\sigma}_{xx}(x)$ is defined equivalently as $\tilde{\sigma}_x(x)$ but with σ_{xx} being the second-order spatial derivative of the $tanh$ activation function.

$$\Delta\hat{u}(x,t) = C(t)[\Phi_{A_r}]_{xx}(x)\mathbb{1}, \quad \text{where, } \mathbb{1} \in \mathbb{R}^{d \times 1}$$
$$= C(t)[A_r W \odot W \odot \tilde{\sigma}_{xx}(x), 0]\mathbb{1} \in \mathbb{R}^{1 \times 1}, \tag{9}$$

Finally,

$$\hat{u}_{xxxx}(x,t) = C(t)[\Phi_{A_r}]_{xxxx}(x)$$
$$= C(t)[A_r W \odot W \odot W \odot W \odot \tilde{\sigma}_{xxxx}(x), 0] \in \mathbb{R}^{1 \times d}, \tag{10}$$

where σ_{zzzz} is the fourth-order spatial derivative of the $tanh$ activation function.

Computing time derivatives:

We compute the first-order time derivative as

$$\hat{u}_t(x,t) = C_t(t)[\Phi_{A_r}](x). \tag{11}$$

Similarly, we compute the second-order time derivative as

$$\hat{u}_{tt}(x,t) = C_{tt}(t)[\Phi_{A_r}](x). \tag{12}$$

Reformulating PDEs as ODEs We now reformulate the PDEs as ODEs using the space and time derivatives derived in Appendix B.1.2. We denote the pseudo-inverse by $\cdot^+$.

Advection equation: The one-dimensional advection equation is

$$u_t(x,t) + \beta u_x(x,t) = 0,$$

where β is a scalar. Approximating the solution with neural network ansatz (Equation (3)) and substituting Equation (11) and Equation (6) in the advection equation, we get,

$$C_t(t)[\Phi_{A_r}(X)] = -\beta C(t)[\Phi_{A_r}(X)]_x$$
$$C_t(t) = -\beta C(t)[\Phi_{A_r}(X)]_x[\Phi_{A_r}(X)]^+.$$

The initial condition is given by

$$C(0) = u(X,0)^\top[\Phi_{A_r}(X)]^+.$$

Burgers' equation: The one-dimensional Burgers' PDE we consider is

$$u_t + uu_x - \alpha u_{xx} = 0,$$

where α is a scalar. Approximating the solution with neural network ansatz (Equation (3)) and substituting Equation (11), Equation (6) and Equation (8) in the Burgers equation, we get,

$$C_t(t)\Phi_{A_r}(X) = -(C(t)\Phi_{A_r}(X) \odot C(t)[\Phi_{A_r}]_x(X)) + \alpha(C(t)[\Phi_{A_r}]_{xx}(X))$$

$$C_t(t) = -(C(t)\Phi_{A_r}(X) \odot C(t)[\Phi_{A_r}]_x(X) + \alpha(C(t)[\Phi_{A_r}]_{xx}(X)))[\Phi_{A_r}(X)]^+$$

Note that the non-linearity is transferred to the right-hand side of the ODE. The initial condition is given by

$$C(0) = u(X,0)^\top \Phi(X)^+.$$

Euler-Bernoulli equation: The Euler-Bernoulli PDE considered in this manuscript is

$$u_{tt} + u_{xxxx} = f(x,t).$$

Approximating the solution with neural network ansatz (Equation (3)) and substituting Equation (10) and Equation (12) in the Euler-Bernoulli equation, we get,

$$C_{tt}(t)\Phi(X) = f(X,t)^\top - C(t)\Phi_{xxxx}(X)$$

We re-write this second-order ODE as a combination of first-order ODEs given by

$$C_t(t) = D(t),$$

$$D_t(t)\Phi(X) = f(X,t)^\top - C(t)\Phi_{xxxx}(X).$$

We then reformulate the ODEs as

$$(C_t(t) \quad D_t(t)) = (C(t) \quad D(t)) \begin{pmatrix} 0 & -\Phi(X)_{xxxx}\Phi(X)^+ \\ \mathbb{1} & 0 \end{pmatrix} + (0 \quad \mathbb{1})[f(X,t)]^\top \Phi(X)^+.$$

The initial condition is given by

$$C(0) = u(X,0)^\top \Phi(X)^+,$$

$$D(0) = u_t(X,0)^\top \Phi(X)^+.$$

Nonlinear diffusion equation: The two-dimensional nonlinear diffusion equation we consider is

$$u_t - u\Delta u = f(x,t), \quad x \in \Omega \subset \mathbb{R}^2, \quad t \in [0,1]. \tag{13}$$

Approximating the solution with neural network ansatz (Equation (3)), substituting Equation (11), and Equation (8) in the nonlinear diffusion equation, we get,

$$C_t(t)\Phi(X) = (C(t)\Phi(X) \odot [C(t)\Phi_{xx}(X)]\mathbb{1}) + [f(X,t)]^\top$$

$$C_t(t) = (C(t)\Phi(X) \odot [C(t)\Phi_{xx}(X)]\mathbb{1} + [f(X,t)]^\top)\Phi(X)^+$$

Note that the non-linearity is transferred to the right-hand side of the ODE. The initial condition is given by

$$C(0) = u(X,0)^\top \Phi(X)^+$$

High-dimensional diffusion equation: The d-dimensional diffusion equation we consider is

$$u_t - \Delta u = f(x,t), \quad x \in \Omega \subset \mathbb{R}^d, \quad t \in [0,1]. \tag{14}$$

Approximating the solution with neural network ansatz (Equation (3)), substituting Equation (11), and Equation (8) in the diffusion equation, we get,

$$C_t(t)\Phi(X) = [C(t)\Phi_{xx}(X)]\mathbb{1} + [f(X,t)]^\top$$

$$C_t(t) = ([C(t)\Phi_{xx}(X)]\mathbb{1} + [f(X,t)]^\top)\Phi(X)^+$$

The initial condition is given by

$$C(0) = u(X,0)^\top \Phi(X)^+$$

Note on ODE solvers and interpolation in time: We use the `solve_ivp` routine of the SciPy package Virtanen et al. (2020). One can pass test points in time as an argument to the method `solve_ivp`. One can optionally set the parameter `dense_output` to true, which means that the output of the ODE is a function handle that can be evaluated by interpolation at any time point $t \in \Omega$. The method specified dictates the interpolation order. RK23 uses a cubic Hermite polynomial, while DOPRI85 uses a seventh-order polynomial.

B.1.3 EXTENDED DISCUSSION OF OUR METHOD

Kolmogorov n-width barrier: Without resampling the internal network parameters, our method faces the Kolmogorov n-width barrier Peherstorfer (2022); Du & Zaki (2021); Berman & Peherstorfer (2024); Kast & Hesthaven (2024) because our basis functions are not time-dependent. However, resampling basis functions at certain time points of the SWIM-ODE (as done in the Burgers' equation in 4.4) results in a solution- and time-dependent basis approximation of the solution manifold and, thus, in theory, can break the barrier.

PINNs can theoretically break the Kolmogorov n-width barrier as time is treated as an extra spatial dimension and internal network parameters are time-dependent, the optimization issues pose much more severe challenges even on very simple PDEs and in low dimensions [2, 3, 4, 5, among others]. Thus, we argue that though our vanilla SWIM-ODE/ELM-ODE approach (without periodically resampling hidden layer weights) faces the Kolmogorov n-width barrier, we outperform PINNs, typically by several orders of accuracy and time in practice.

Influence of random sampling on the method: Similar to the question of how PINNs trained with Adam/SGD perform based on their random network initialization, understanding the influence of weights on the output is a challenge. There are two main differences between (stochastic) gradient optimization and our setting. First, after fixing the internal weights, we use regularized least-squares (not a stochastic method) to fit the initial condition. Second, we do not use a stochastic method to solve over time. Therefore, even though PINNs can adapt their random initialization over the gradient-based optimization, precisely that optimization also adds stochasticity. If the number of neurons for the model increases, the randomness in our case decreases because the regularized least-squares fit to the initial condition (which converges to a single solution in the limit of many neurons), while stochastic gradient descent will only converge to a distribution (because of mini-batch optimization). This has been observed for the supervised learning problems Bolager et al. (2023), particularly in the transfer learning experiments. In Table 2, we observe that our model's performance is often orders of magnitude better, and the variance is on the same scale as the magnitude.

B.2 PHYSICS-INFORMED NEURAL NETWORKS

This work employs two prominent variants of physics-informed machine learning to compare the results obtained by the proposed methods. In particular, physics-informed neural network (PINN) Raissi et al. (2019) and causality-respecting physics-informed neural network (causal PINN) Wang et al. (2024b) are utilized to compare the obtained approximations.

Vanilla PINNs are feedforward deep neural networks designed to simulate PDEs by incorporating physical laws into the learning process. The architecture of a vanilla PINN includes a deep neural network that maps inputs (e.g., space and time coordinates) to outputs (e.g., physical quantities of interest) and is trained to minimize a loss function that combines both data and physics-based errors. The data term ensures that the neural network fits the provided data points, while the physics term enforces the PDE constraints with automatic differentiation. Hence, the loss function for PINN could be defined by

$$L(\mu) = \lambda_1 L_{\text{PDE}}(\mu) + \lambda_2 L_{\text{Data}}(\mu). \tag{15}$$

Here, μ represents the trainable network parameters. Considering the generic nonlinear PDE defined by equation 1 with well-posed boundary and initial conditions equation 2, the individual loss terms weighted by the hyperparameters λ_i, $i = 1, 2$, are defined by

$$L_{\text{PDE}}(\mu) = \frac{1}{N_{\text{int}}} \sum_{n=1}^{N_{\text{int}}} ||u_t^*(x^{(n)}, t^{(n)}) + Lu(x^{(n)}, t^{(n)}) + \lambda N(u^*)(x^{(n)}, t^{(n)}) - f(x^{(n)})||^p. \tag{16}$$

The data loss term considering the initial and boundary conditions is defined by

$$L_{\text{Data}}(\mu) = \frac{1}{N_{\text{i}}} \sum_{n=1}^{N_{\text{i}}} ||Bu^*(x^{(n)}, t^{(n)}) - g(x^{(n)})||^p. \tag{17}$$

Here, N is the total number of training points, which is the sum of interior training points (N_{int}) and initial or boundary training points (N). The neural network predicted solution of u at a point in computational domain, $(x^{(n)}, t^{(n)})$ is denoted by $u^*(x^{(n)}, t^{(n)})$. The experiments are trained with

L^2-norm, implying $p = 2$. The main goal is to minimize equation 15 and determine the optimal parameters (μ). These parameters, once optimized, are employed to predict the solution of the PDE within the computational domain.

The second physics-informed method employed is Causal PINNs, which modifies the PINN loss function to explicitly adhere to the temporal causality inherent in time-dependent PDEs. In vanilla PINNs, the loss function does not prioritize resolving the solution at lower times before higher times, leading to inaccuracies, especially in time-dependent problems. Causal PINNs address this by introducing a weighting factor for the loss at each time step, which depends on the accumulated loss from previous time steps. The resulting loss function ensures that the network prioritizes learning the solution accurately at earlier times before focusing on later times, thus maintaining the causal structure of the physical problem being solved. The causal PDE loss term is defined by

$$L_{\text{PDE}}(\mu) = \sum_{i=1}^{N_t} w_i L_{\text{PDE}}(t_i, \mu),$$

$$w_1 = 1, \quad w_i = e^{-\epsilon \sum_{k=1}^{i-1} L_{\text{PDE}}(t_k, \mu)}, \quad i = 2, 3, \ldots N_t. \tag{18}$$

N_t represents the number of time steps into which the computational domain is divided. The causality hyperparameter ϵ regulates the steepness of the weights and is incorporated in the loss function similar to Kapoor et al. (2024b). This modification introduces a weighting factor, w_i, for the loss at each time level t_i, with w_i being dependent on the cumulative PDE loss up to time t_i. The network prioritizes a fully resolved solution at earlier time levels by exponentiating the negative of this accumulated loss. Consequently, the modified loss function for causal PINN is expressed as

$$L_{\text{PDE}}(\mu) = \frac{1}{N_t} \left[w_1 L_{\text{PDE}}(t_1, \mu) + \sum_{i=2}^{N_t} e^{-\epsilon \sum_{k=1}^{i-1} L_{\text{PDE}}(t_k, \mu)} L_{\text{PDE}}(t_i, \mu) \right]. \tag{19}$$

B.3 IGA-FEM

First introduced in Hughes et al. (2005), Isogeometric analysis (IGA) is a numerical method developed to unify the fields of computer-aided design (CAD) and finite element analysis (FEA). The key idea is to represent the solution space for the numerical analysis using the same functions that define the geometry in CAD (cf. Cottrell et al. (2009)), which include the B-Splines and Non-Uniform Rational B-Splines (NURBS) (cf. Piegl & Tiller (1997)).

In this paper, we use B-Splines as the basis functions. The B-Splines are defined using the Cox-de Boor recursion formula (cf. COX (1972); de Boor (1972)), i.e.,

$$N_{i,0}(\xi) = \begin{cases} 1 & \xi_i \leq \xi < \xi_{i+1} \\ 0 & \text{otherwise,} \end{cases}$$

$$N_{i,p}(\xi) = \frac{\xi - \xi_i}{\xi_{i+p} - \xi_i} N_{i,p-1}(\xi) + \frac{\xi_{i+p+1} - \xi}{\xi_{i+p+1} - \xi_{i+1}} N_{i+1,p-1}(\xi),$$

where ξ_i is the ith knot, and p is the polynomial degree. The vector $\Xi = [\xi_1, \xi_2, \ldots, \xi_{n+p+1}]$ is the knot vector, where n is the number of B-Splines. By specifing the knot vector, we define the basis functions we use to solve the PDEs. We use an uniform open knot vector, where the first and last knots have multiplicity $p + 1$, the inner knots have no multiplicity, and all knots that have different values are uniformly distributed. We refer to the knots with different values as "nodes". The intervals between two successive nodes are knot spans, which can be viewed as "elements". The elements form a "patch". A domain can be partitioned into subdomains and each is represented by a patch. In our work, we use a single patch to represent the entire 1D domain. Figure 9a shows an example of such a patch, where the B-Splines are C^p-continuous within the knot spans and C^{p-1} continuous at the inner knots. In order to address the boundary conditions, we adapt the B-Splines as shown in Figure 9b Figure 9c, so that the boundary conditions are directly built into the solution space.

In the following, we refer to the adapted B-Splines as basis functions $\phi_k(x)$. Thus, the solutions of PDEs are approximated by

$$u(x, t) = \sum_{k=1}^{K} c_k(t) \phi_k(x).$$

(a) Number of basis func-
tions $= 7$.

(b) Number of basis func-
tions $= 5$.

(c) Number of basis func-
tions $= 5$.

Figure 9: Examples of B-Splines representing the 1D domain $[0, 1]$. Number of nodes $= 6$ and degree of polynomials $= 2$. **Left:** The original B-Splines. **Middle:** Adapted B-Splines to satisfy the Dirichlet boundary condition. **Right:** Adapted B-Splines to satisfy the periodic boundary condition. Note that the first (blue) spline is identical to the second last (brown) one, and the second (orange) spline is identical to the last (pink) one, as they share the same coefficient. The gray dashed lines indicate where the domain starts and ends.

We solve the PDEs in the weak formulation. For the linear advection equation equation 21, the weak form of the equation is

$$\sum_{k=1}^{K} c_k'(t) \int_X \phi_k(x)v(x)dx + \beta \sum_{k=1}^{K} c_k(t) \int_X \phi_k'(x)v(x)dx = 0, \qquad (20)$$

where $v(x)$ are the test functions. The test functions are chosen to be the same as the basis functions. The integral of the functions is computed using Gaussian quadrature. Then we solve the linear Ordinary differential equation (ODE)

$$\mathbf{M\dot{c} + Kc = 0},$$

where matrix $\mathbf{M}$ and matrix $\mathbf{K}$ contain the integral of the B-Splines and their derivatives, and the coefficient β, which are given. We solve the Euler-Bernoulli equation equation 23 and the Burgers' equation equation 27 in a similar way. The boundary condition for the Euler-Bernoulli equation is in addition weakly imposed, as is done in Prudhomme et al. (2001).

B.3.1 DOLFINₓ

DOLFINx (cf. Baratta et al. (2023)), which is part of the FEniCS project, is a C++ and Python library used for solving PDEs with the finite element method (FEM). It provides tools for defining complex geometries, formulating variational problems, and solving them efficiently on distributed architectures. In this paper, we use `DOLFINx` 0.8.0 to solve the nonlinear diffusion equation equation 24. The programming language is Python. The runtime of the FEM experiment in Table 13 was measured on a Lenovo ThinkPad T14s laptop equipped with 12th Gen Intel® Core™ i7-1255U (12 cores) and 16GB of RAM. In addition, the software Gmsh (cf. Geuzaine & Remacle (2009)) is used to generate mesh for the complex geometry for this experiment, as shown in Figure 12a.

C Numerical Experiments

Code repository: The code to reproduce the experiments from the paper and an up-to-date code base can be found (with MIT Licence) in the supplemental material (open-source and publicly available after acceptance).

Hardware details: The computational experiments were performed with: `Ubuntu` 20.04.6 LTS, `NVIDIA` driver 515.105.01 and i7 CPU.

Metrics for computing errors: Let d be the dimension of space and $\Omega \times [0, T] \subset \mathbb{R}^d \times \mathbb{R}$ be the spatio-temporal domain. Given N points in a test set X_{test}, the error metrics we use to compare numerical results are Root Mean Squared Error (RMSE) and relative L^2 error given by

$$\text{RMSE} := \sqrt{\frac{\sum_{x \in X}(u_{true}(x) - u_{pred}(x))^2}{N}}, \text{ and } L^2_{\text{relative}} := \frac{\sqrt{\sum_{x \in X}(u_{true}(x) - u_{pred}(x))^2}}{\sqrt{\sum_{x \in X}(u_{true}(x))^2}}.$$

C.1 LINEAR ADVECTION EQUATION

The advection equation models the propagation of a quantity at a speed β without altering the shape. We solve the linear advection equation with periodic boundary conditions described by

$$u_t(x,t) + \beta u_x(x,t) = 0, \quad \text{for} \quad x \in [0, 2\pi], t \in [0,1], \tag{21}$$

$$u(x,0) = \sin(x). \tag{22}$$

We describe additional details in solving the advection equation with various neural PDE solvers in Table 4. In addition, hyperparameter optimization for PINN for the case of $\beta = 10$ was carried out, varying the number of neurons and interior points. The results for the hyperparameter optimization are detailed in Table 5, Table 6. For SWIM and ELM, we use 1000 interior points for $\beta \in \{10^{-2}, 10^{-1}, 1, 10\}$, and we use 8000 interior points for $\beta \in \{40, 100\}$. The hidden layer weights for ELM and ELM-ODE are sampled from the Gaussian distribution and biases from a uniform distribution in $[-4, 4]$.

Figure 10 shows the absolute errors obtained with the SWIM-ODE, ELM-ODE, PINN, Causal PINN and IGA methods.

Figure 10: Advection equation: absolute error plots and ground truth

C.2 EULER-BERNOULLI PDE

This is a time-dependent PDE, given by

$$u_{\text{tt}} + u_{\text{xxxx}} = f(x,t) \quad x \in [0, \pi], t \in [0,1] \tag{23}$$

where $f(x,t) = (1 - 16\pi^2) \sin(x) \cos(4\pi t)$, with initial and boundary conditions

$$u(x,0) = \sin(x), \quad u_t(x,0) = 0$$

$$u(0,t) = u(\pi,t) = u_{\text{xx}}(0,t) = u_{\text{xx}}(\pi,t) = 0.$$

It models a simply supported beam with varying transverse force. We describe additional details in solving the Euler-Bernoulli with various neural PDE solvers in Table 8. The hidden layer weights for ELM-ODE are sampled from the Gaussian distribution and biases from a uniform distribution in $[-2, 2]$.

Figure 11 shows the absolute errors obtained with the SWIM-ODE, ELM-ODE, PINN, and IGA methods, and Table 9 shows the summary of results for Euler Bernoulli beam equation for different methods.

Table 4: Network hyperparameters used for the linear advection equation for $\beta \in \{10^{-2}, 10^{-1}, 1, 10, 40, 100\}$ (optimal hyper-parameters in bold)

	Parameter	Value
SWIM-ODE, ELM-ODE	Number of hidden layers	2
	Hidden layer width	$[140, \mathbf{380}, 560]$
	Activation	tanh
	L^2-regularization	$[10^{-8}, \mathbf{10^{-10}}, 10^{-12}]$
	Loss	mean-squared error
SWIM, ELM	Number of hidden layers	2
	SVD cutoff	10^{-12}
	Hidden layer width	$[140, \mathbf{380}, 560]$
	Activation	tanh
	L^2-regularization	$[10^{-8}, \mathbf{10^{-10}}, 10^{-12}]$
	Loss	mean-squared error
	# Initial and boundary points	400
	# Interior points	$[\mathbf{1000}, \mathbf{8000}]$
IGA	Number of nodes	16
	Degree of polynomials	8
	Number of basis functions	15
PINN	Number of hidden layers	4
	Layer width	$[10, 20, \mathbf{30}, 40]$
	Activation	tanh
	Optimizer	LBFGS
	Epochs	5000
	Loss	mean-squared error
	Learning rate	0.1
	Batch size	200
	Parameter initialization	Xavier (Glorot & Bengio, 2010)
	Loss weights, λ_1, λ_2	1, 1
	# Interior points	$[500, 1000, 1500, \mathbf{2000}]$
	# Initial and boundary points	600
Causal PINN	Number of hidden layers	4
	Layer width	30
	Activation	tanh
	Optimizer	ADAM followed by LBFGS
	ADAM Epochs	2000
	LBFGS Epochs	5000
	Loss	mean-squared error
	Learning rate	0.1
	Batch size	2000
	Parameter initialization	Xavier (Glorot & Bengio, 2010)
	Loss weights, λ_1, λ_2	1, 1
	# Interior points	40000
	# Initial and boundary points	6000
	Causality parameter, ϵ	10

Table 5: Advection equation equation 21: hyperparameter optimization for PINN varying layer width for $\beta = 10$.

Layer width	Training time (s)	RMSE	Relative L^2 error
10	$\mathbf{24.47 \pm 0.19}$	1.24e-3 $\pm$ 2.38e-4	1.76e-3 $\pm$ 3.37e-4
20	27.46 ± 0.08	6.52e-4 $\pm$ 2.59e-4	9.22e-4 $\pm$ 3.66e-4
30	30.43 ± 0.50	$\mathbf{3.69e\text{-}4 \pm 4.33e\text{-}5}$	$\mathbf{5.23e\text{-}4 \pm 6.13e\text{-}5}$
40	33.64 ± 0.41	3.86e-4 $\pm$ 9.37e-5	5.46e-4 $\pm$ 1.32e-4

Table 6: Advection equation equation 21: hyperparameter optimization for PINN varying interior points for $\beta = 10$.

Interior points	Training time (s)	RMSE	Relative L^2 error
500	**25.76 $\pm$ 0.29**	4.10e-4 $\pm$ 7.20e-5	5.80e-4 $\pm$ 1.01e-4
1000	27.44 $\pm$ 0.25	3.72e-4 $\pm$ 4.06e-5	5.27e-4 $\pm$ 5.74e-5
1500	29.61 $\pm$ 0.16	5.68e-4 $\pm$ 1.97e-4	8.03e-4 $\pm$ 2.79e-4
2000	30.43 $\pm$ 0.50	**3.69e-4 $\pm$ 4.33e-5**	**5.23e-4 $\pm$ 6.13e-5**

Table 7: Summary of results for the advection equation for $\beta = 40$.

Method	Training time (s)	RMSE	Relative L^2 error	architecture
SWIM	66.30	6.81 $\pm$ 0.26	9.63 $\pm$ 0.38	(2, 4000, 1)
ELM	59.05	3.78 $\pm$ 0.21	5.35 $\pm$ 0.29	(2, 4000, 1)
Causal PINN	357.63 $\pm$ 3.11	2.07 $\pm$ 0.87	2.92 $\pm$ 1.23	(2, 4 $\times$ 30, 1)
PINN	30.56 $\pm$ 0.27	4.89e-1 $\pm$ 2.09e-2	6.92e-1 $\pm$ 2.96e-2	(2, 4 $\times$ 30, 1)
SWIM-ODE (our)	2.72	5.04 e-6 $\pm$ 1.45e-6	7.13e-6 $\pm$ 2.05 e-6	(1, 350, 15, 1)
ELM-ODE (our)	**2.71**	**2.73e-6 $\pm$ 3.68e-7**	**3.84e-6 $\pm$ 5.2e-7**	(1, 350, 15, 1)
IGA-FEM	0.07	8.24e-11	1.17e-10	15

(a) SWIM-ODE   (b) ELM-ODE   (c) PINN

(d) IGA   (e) Ground truth

Figure 11: Euler-Bernoulli equation: absolute error plots and ground truth

C.3 NONLINEAR DIFFUSION EQUATION

We solve a two-dimensional nonlinear diffusion equation

$$u_t - u\Delta u = f(x, y, t), \quad (x, y) \in \Omega, \quad t \in [0, 1], \tag{24}$$

$$f(x, y, t) = 5e^{-t}\sin(\pi x)y^{-3}\left(-1 + e^{-t}\sin(\pi x)y^{-5}\left(-12 + \pi^2 y^2\right)\right) \tag{25}$$

on a complicated geometry inspired by a tree-like pattern occurring during the controlled shaping of fluids (Islam & Gandhi, 2017). The initial condition and time-dependent Dirichlet boundary conditions are obtained from the constructed solution of the PDE

$$u(x, y, t) = 5e^{-t}\sin(\pi x)y^{-3}, \quad (x.y) \in \Omega, \quad t \in [0, 1]. \tag{26}$$

Table 8: Network hyperparameters used for the Euler-Bernoulli equation.

	Parameter	Value
SWIM-ODE and ELM-ODE	Number of hidden layers	2
	Hidden layer width	200
	Outer layer width	10
	Activation	tanh
	L^2-regularization	10^{-12}
	Loss	mean-squared error
IGA	Number of nodes	27
	Degree of polynomials	9
	Number of basis functions	33
PINN	Number of hidden layers	4
	Layer width	20
	Activation	tanh
	Optimizer	LBFGS
	Epochs	15000
	Loss	mean-squared error
	Learning rate	0.1
	Batch size	2000
	Parameter initialization	Xavier (Glorot & Bengio, 2010)
	Loss weights, λ_1, λ_2	0.1, 1
	# Interior points	10000
	# Initial and boundary points	6000

Table 9: Summary of results for the Euler-Bernoulli beam equation.

Method	Training time (s)	RMSE	Relative L^2 error	architecture
PINN	2303.71 ± 278.68	$2.11\text{e-}3 \pm 4.79\text{e-}4$	$4.21\text{e-}3 \pm 9.56\text{e-}4$	$(2, 4\times 20, 1)$
SWIM-ODE (our)	**0.05**	$6.06\text{e-}8 \pm 2.96\text{e-}8$	$1.20\text{e-}7 \pm 5.91\text{e-}8$	$(1, 200, 10, 1)$
ELM-ODE (our)	0.06	$\mathbf{1.75\text{e-}8 \pm 3.91\text{e-}9}$	$\mathbf{3.50\text{e-}8 \pm 7.79\text{e-}9}$	$(1, 200, 10, 1)$
IGA-FEM	0.94	2.11e-7	4.21e-7	33

The training is performed on 1500 data points in the interior and on the boundary. We test the neural-PDE solvers with 5000 data points in the interior and boundary. The exact architectures and comparison of training times and errors are presented in Table 10 and Table 13. For PINN the results for hyperparameter optimization are detailed in Table 11, Table 12. With ELM and SWIM, we compute the SVD of the feature matrix and keep singular values with a cut-off ratio of 10^{-14}. The weights of the hidden layer for the ELM-ODE are sampled from the Gaussian distribution and biases from a uniform distribution in $[-1, 1]$. For our approach to handling time-dependent Dirichlet boundary conditions, please refer to Appendix B.1.1. Figure 13 shows the errors with all approaches and the ground truth.

C.4 BURGERS

The inviscid Burgers' equation is a non-linear PDE, which can form shock waves. We solve Burgers' equation on $\Omega = [-1, 1]$ for time $t \in (0, 1]$, so that

$$u_t + uu_x - (0.01/\pi)u_{xx} = 0, \quad x \in \Omega, \quad t \in [0, 1], \tag{27}$$
$$u(0, x) = -\sin(\pi x), \tag{28}$$
$$u(1, -1) = u(t, 1) = 0. \tag{29}$$

We describe additional details in solving the Burgers' equation with various neural PDE solvers in Table 14 and Table 15. Figure 14 shows the absolute errors obtained with the PINN, Causal PINN, and IGA methods.

(a) Generated Mesh: FEM

(b) Sampled collocation points: Neural PDE solvers

Figure 12: For mesh-based methods, a complicated mesh must be constructed (a), while for our method, one can easily sample arbitrary points on the domain (b).

Table 10: Network hyperparameters used for the non-linear diffusion equation.

	Parameter	Value
SWIM-ODE	Number of hidden layers	2 (nonlinear and SVD layer)
	Hidden layer width	500
	Activation	tanh
	L^2-regularization	10^{-15}
	SVD cutoff	10^{-15}
	ODE solver tolerance	10^{-6}
	Loss	mean-squared error
ELM-ODE	Number of hidden layers	2 (nonlinear and SVD layer)
	Hidden layer width	200
	Activation	tanh
	L^2-regularization	10^{-15}
	SVD cutoff	10^{-15}
	ODE solver tolerance	10^{-6}
	Loss	mean-squared error
FEM	Number of entities	154
	Number of nodes	1193
	Number of elements	2070
	Type of elements	Lagrange
	Shape of elements	triangle
	Degree of polynomials	1
	Number of basis functions	1193
	Solver	Newton solver
	Timestep size	0.001
PINN	Number of hidden layers	4
	Layer width	$[10, 20, \mathbf{30}, 40]$
	Activation	tanh
	Optimizer	LBFGS
	Epochs	10000
	Loss	mean-squared error
	Learning rate	0.01
	Batch size	1000
	Parameter initialization	Xavier (Glorot & Bengio, 2010)
	Loss weights, λ_1, λ_2	0.01, 1
	# Interior points	$[8790, 1760, \mathbf{880}, 440]$
	# Initial and boundary points	$[3140, 630, \mathbf{320}, 160]$

(a) Ground truth

(b) Absolute error: SWIM-ODE

(c) Absolute error: ELM-ODE

(d) Absolute error: FEM

(e) Absolute error: PINN

Figure 13: Non-linear diffusion equation: absolute error plots and ground truth at four-time instants

Table 11: Non-linear diffusion equation equation 24: hyperparameter optimization for PINN varying layer width.

Layer width	Training time (s)	RMSE	Relative L^2 error
10	**61.09 $\pm$ 1.62**	4.11e-2 $\pm$ 2.04e-3	1.50e-2 $\pm$ 7.48e-4
20	68.05 $\pm$ 1.56	3.74e-2 $\pm$ 1.04e-3	1.37e-2 $\pm$ 3.82e-4
30	76.01 $\pm$ 0.57	**3.67e-2 $\pm$ 1.03e-3**	**1.34e-2 $\pm$ 3.78e-4**
40	82.43 $\pm$ 0.45	3.76e-2 $\pm$ 1.69e-3	1.37e-2 $\pm$ 6.21e-4

Table 12: Non-linear diffusion equation equation 24: hyperparameter optimization for PINN varying interior points

Interior points	Training time (s)	RMSE	Relative L^2 error
600	**65.08 $\pm$ 4.23**	3.74e-2 $\pm$ 1.04e-3	1.37e-2 $\pm$ 3.82e-4
1200	98.48 $\pm$ 3.78	3.51e-2 $\pm$ 6.67e-4	1.28e-2 $\pm$ 2.44e-4
2390	143.31 $\pm$ 5.50	**3.34e-2 $\pm$ 6.53e-4**	**1.22e-2 $\pm$ 2.38e-4**
11930	1154.48	2.01	0.73

Table 13: Summary of results for the non-linear diffusion equation.

Method	Training time (s)	RMSE	Relative L^2 error	architecture
PINN	143.31	3.34e-2 $\pm$ 6.53e-4	1.22e-2 $\pm$ 2.38e-4	(2, 4 $\times$ 30, 1)
ELM-ODE (our)	30.57	5.02e-5 $\pm$ 4.84e-5	5.12e-5 $\pm$ 4.95e-5	(2, 200, 1)
SWIM-ODE (our)	423	1.96e-6 $\pm$ 1.95e-6	2.00e-6 $\pm$ 1.99e-6	(2, 500, 1)
FEM	*2.71*	7.33e-3	2.68e-3	1193

(a) PINN   (b) Causal PINN   (c) IGA

(d) Ground truth

Figure 14: Burgers' equation: absolute error plots and ground truth

C.4.1 COMPARISON WITH CLASSICAL SPECTRAL METHODS

We compare to other traditional spectral methods by fitting the Burgers' equation solution directly at a certain time step, where the function has a locally steep gradient. We argue that if a method fails to approximate this function well, it is unlikely to achieve better results in solving the PDE.

Table 14: Network hyper-parameters used for SWIM-ODE and ELM-ODE to solve Burgers' equation.

	Parameter	Value
SWIM-ODE	Number of hidden layers	2
	Hidden layer width	$[450]$
	Activation	tanh
	L^2-regularization	$[10^{-6}, \mathbf{10^{-7}}, 10^{-8}, 10^{-10}, 10^{-12}]$
	Loss	mean-squared error
	# collocation points (space)	$[800]$
	# sampling points	$[6000]$
ELM-ODE	Number of hidden layers	2
	Hidden layer width	$[2000]$
	Activation	tanh
	L^2-regularization	$[10^{-6}, \mathbf{10^{-7}}, 10^{-8}, 10^{-10}, 10^{-12}]$
	Loss	mean-squared error
	# collocation points (space)	$[3000]$
	# sampling points	$[6000]$

Table 15: Network hyper-parameters used for PINN, Causal PINN, and IGA to solve Burgers' equation.

	Parameter	Value
PINN	Number of hidden layers	9
	Layer width	20
	Activation	tanh
	Optimizer	LBFGS
	Epochs	10000
	Loss	mean-squared error
	Learning rate	0.1
	Batch size	200
	Parameter initialization	Xavier (Glorot & Bengio, 2010)
	Loss weights, λ_1, λ_2	1, 1
	# Interior points	10000
	# Initial and boundary points	600
Causal PINN	Number of hidden layers	9
	Layer width	20
	Activation	tanh
	Optimizer	ADAM followed by LBFGS
	ADAM Epochs	5000
	LBFGS Epochs	10000
	Loss	mean-squared error
	Learning rate	0.1
	Batch size	200
	Parameter initialization	Xavier (Glorot & Bengio, 2010)
	Loss weights, λ_1, λ_2	1, 1
	# Interior points	40000
	# Initial and boundary points	600
	Causality parameter, ϵ	5
IGA	Number of nodes	400
	Degree of polynomials	8
	Number of basis functions	405

Figure 16 shows the approximation of the Burgers' equation solution at $t = 0.99$, using SWIM basis functions, ELM basis functions, Fourier series, and Chebyshev polynomials, respectively. The number of basis functions is 102 for all methods. Figure 15 shows the approximation error using a different number of basis functions. We can see that for ELM basis functions, Fourier series and Chebyshev polynomials, there are oscillations near the nonlinearity, and the error is large compared to the SWIM basis functions, where we are able to take the advantage of resampling data points and

Table 16: Summary of results for Burgers' Equation.

Method	Training time (s)	RMSE	Relative L^2 error	architecture
ELM-ODE (our)	2.41	1.51e-1 ± 3.27 e-4	2.47e-1 ± 5.33e-4	(1, 2000, 1)
PINN	275.23 ± 5.38	2.38e-3 ± 1.61e-3	3.88e-3 ± 2.61e-3	(2, 9×20, 1)
Causal-PINN	1531.79 ± 18.45	9.85e-3 ± 5.51e-3	1.60e-2 ± 8.97e-3	(2, 9×20, 1)
SWIM-ODE (our)	**141.35**	**2.05e-4 ± 2.84e-4**	**3.33e-4 ± 4.63e-4**	(1, 400, 1)
IGA-FEM	*13.61*	*1.35e-4*	*2.20e-4*	*405*

basis functions in order to adapt to the target function well. Note that in this experiment, the weights for the ELM basis functions are sampled from a Gaussian distribution with a standard deviation of 10 in order to increase the number of basis functions. The biases are sampled from a uniform distribution in $[-10, 10]$. For the Fourier series and Chebyshev polynomials, we use equispaced grid points. We also experimented with quadrature points and placed more points near the steep gradient in an attempt to mitigate the oscillations associated with the Gibbs phenomenon and the Runge phenomenon, but it did not lead to any significant improvement in the results.

Figure 15: Approximation error for four types of basis functions. Here, we directly fit the Burgers' equation solution at $t = 0.99$. The approximation error decreases as we increase the number of basis functions, and the SWIM basis functions yield the best result among all methods.

Figure 16: Approximation of Burgers' equation solution at $t = 0.99$ with four types of basis functions. The number of basis functions in all cases is 102. Oscillations can be seen near the steep gradient for the methods using ELM basis functions, Fourier functions, and Chebyshev polynomials.

C.5 HIGH-DIMENSIONAL HEAT EQUATION

We consider up to 10-dimensional heat equation on spatial domain $\Omega = [-1, 1]^d$ and time domain $t \in (0, 1]$:

$$u_t - \Delta u = \left(\frac{1}{d} - 1\right) \cos\left(\frac{1}{d}\sum_{i=1}^{d} x_i\right) \exp(-t), \quad x \in \Omega, \quad t \in [0, 1], \tag{30}$$

$$u(x, t) = \cos\left(\frac{1}{d}\sum_{i=1}^{d} x_i\right) \exp(-t), \tag{31}$$

$$u(x, 0) = \cos\left(\frac{1}{d}\sum_{i=1}^{d} x_i\right), \tag{32}$$

where $d \in \{3, 5, 7, 10\}$. This example is considered in (Wang & Dong, 2024), but only up to 7 dimensions. We demonstrate that ELM-ODE accurately solves the heat equation by visualizing the ground truth, the ELM-ODE solution, and the point-wise absolute error for the 10-dimensional heat equation across different cross-sections for a fixed time in Figure 17 and the time evolution of solution at some sampled points in space in Figure 18. The hyper-parameters for all neural PDE solvers considered in this work are presented in Table 17, and the results for heat equations with up to 3, 5, 7, and 10 dimensions are summarized in Table 18. For the heat equation, we use 16000 training points in the interior and 4000 points on the boundary randomly sampled using the Latin hypercube strategy. The test data contains 8000 points in the interior and 2000 points on the domain's boundary, which were also sampled with a Latin hypercube strategy.

Table 17: Summary of hyper-parameters for the 10-dimensional heat equation.

	Parameter	Value
SWIM-ODE	Number of hidden layers	2 (nonlinear and SVD layer)
	Hidden layer width	4000
	Activation	tanh
	L^2-regularization	10^{-10}
	SVD cutoff	10^{-10}
	ODE solver tolerance	10^{-6}
	Loss	mean-squared error
ELM-ODE-fast	Number of hidden layers	2 (nonlinear and SVD layer)
	Hidden layer width	1000
	Activation	tanh
	L^2-regularization	10^{-10}
	SVD cutoff	10^{-10}
	ODE solver tolerance	10^{-6}
	parameter range $[-r_m, r_m]$	$r_m = 0.05$
	Loss	mean-squared error
ELM-ODE-accurate	Number of hidden layers	2 (nonlinear and SVD layer)
	Hidden layer width	4000
	Activation	tanh
	L^2-regularization	10^{-10}
	SVD cutoff	10^{-10}
	ODE solver tolerance	10^{-6}
	parameter range $[-r_m, r_m]$	$r_m = 0.05$
	Loss	mean-squared error
PINN	Number of hidden layers	4
	Layer width	20
	Activation	tanh
	Optimizer	LBFGS
	Epochs	1000
	Loss	mean-squared error
	Learning rate	0.1
	Batch size	4000
	Parameter initialization	Xavier (Glorot & Bengio, 2010)
	Loss weights, λ_1, λ_2	1, 1
	# Interior points	16000
	# Initial and boundary points	4000

(a) x_2-x_3 plane

(b) x_4-x_5 plane

(c) x_9-x_{10} plane

Figure 17: 10-dimensional heat equation: Ground truth, ELM-ODE solution, and point-wise absolute error across different cross-sections of the spatio-temporal domain (located exactly in the center of the spatial-temporal domain with respect to the remaining coordinates).

(a) x_3-t plane

(b) x_5-t plane

(c) x_7-t plane

Figure 18: 10-dimensional heat equation: Ground truth, ELM-ODE solution, and point-wise absolute error at various planes at different time points (The rest of the spatial coordinates are set to the center of the spatial-temporal domain).

Table 18: Summary of results for high-dimension heat equation.

Dimension	Method	Training time (s)	RMSE	Relative L^2 error
3-d	PINN	102.32 ± 3.21	2.84e-4 $\pm$ 3.73e-5	4.54e-4 $\pm$ 5.97e-5
	SWIM-ODE (our)	85.73	2.18e-6 $\pm$ 1.93e-6	5.37e-6 $\pm$ 4.27e-7
	ELM-ODE-fast (our)	**0.9**	2.42e-6 $\pm$ 1.37e-6	3.90e-6 $\pm$ 2.98e-6
	ELM-ODE-accurate (our)	60.98	**3.48e-8 $\pm$ 2.17e-6**	**6.49e-8 $\pm$ 4.31e-8**
5-d	PINN	133.95 ± 2.66	2.91e-4 $\pm$ 5.34e-5	4.52e-4 $\pm$ 8.30e-5
	SWIM-ODE (our)	129.65	1.03e-4 $\pm$ 5.94e-5	2.39e-4 $\pm$ 8.69e-5
	ELM-ODE-fast (our)	**1.2**	1.25e-4 $\pm$ 2.42e-5	3.74e-4 $\pm$ 5.37e-5
	ELM-ODE-accurate (our)	102.95	**4.71e-7 $\pm$ 3.56e-7**	**7.5e-7 $\pm$ 3.92e-7**
7-d	PINN	163.89 ± 0.23	3.05e-4 $\pm$ 2.94e-5	4.69e-4 $\pm$ 4.51e-5
	SWIM-ODE (our)	154.20	3.96e-4 $\pm$ 1.03e-4	7.8e-4 $\pm$ 2.50e-4
	ELM-ODE-fast (our)	**5.95**	1.05e-5 $\pm$ 8.76e-6	2.21e-5 $\pm$ 1.01e-5
	ELM-ODE-accurate (our)	124.95	**1.19e-6 $\pm$ 2.93e-7**	**2.54e-6 $\pm$ 5.10e-7**
10-d	PINN	189.67 ± 11.69	3.98e-4 $\pm$ 6.59e-5	6.06e-4 $\pm$ 1.00e-4
	SWIM-ODE (our)	61.07	1.01e-3 $\pm$ 3.09e-4	2.31e-3 $\pm$ 1.03e-3
	ELM-ODE-fast (our)	**2.07**	2.89e-4 $\pm$ 5.91e-5	4.46e-4 $\pm$ 9.61e-5
	ELM-ODE-accurate (our)	182.91	**1.04e-5 $\pm$ 3.32e-6**	**2.28e-5 $\pm$ 5.91e-6**