Deep Bidirectional Language-Knowledge Pretraining

Abstract

Pretraining a language model (LM) on text helps various downstream NLP tasks. Recent works show that a knowledge graph (KG) can complement text data, offering structured background knowledge and scaffold useful for reasoning. However, these works are not pretrained to learn deep fusion of the two modalities at scale, limiting the potential to acquire fully joint representations of text and KG. Here we propose DRAGON (**D**eep Bidi**r**ectional L**a**n**g**uage-Kn**o**wledge Pretrai**n**ing), a self-supervised method to pretrain a deeply joint language-knowledge model from raw text and KG at scale. Specifically, our model takes pairs of text segments and relevant KG subgraphs as input and bidirectionally fuses information from both modalities. We pretrain this model by unifying two self-supervised reasoning objectives, masked language modeling and KG link prediction. DRAGON outperforms existing LMs and LM+KG models on diverse downstream tasks including question answering across general and biomedical domains, with +5% absolute gain on average across the board. In particular, DRAGON achieves notable performance on complex reasoning about language and knowledge (+10% on questions involving long context or multi-step reasoning) and low-resource QA (+8% on OBQA and RiddleSense), and new state-of-the-art results on various BioNLP tasks.

1 Introduction

Pretraining learns self-supervised representations from massive raw data to help various downstream tasks [1]. Language models (LMs) pretrained on large text data, such as BERT [2] and GPTs [3], have shown strong performance on many natural language processing (NLP) tasks. The success of these models comes from deeply interactive (contextualized) representations of inputs learned at scale via self-supervision [2, 4]. On the other hand, large knowledge graphs (KGs), like Freebase [5], Wikidata [6] and ConceptNet [7], provide complementary information to text data. KGs offer structured background knowledge by representing entities as nodes and relations between them as edges, and also offer scaffolds for structured reasoning such as multi-step reasoning about entities [8, 9, 10, 11] (§3.4.1). This motivates research in combining the strengths of text data and KGs and pretraining deeply interactive representations of the two modalities at scale.

How to effectively combine text and KGs for pretraining is an open problem and presents challenges. Given text and KG, we need both (i) a *deeply bidirectional* model for the two modalities to interact, and (ii) a *self-supervised* objective to learn joint reasoning over text and KG at scale. Several existing works [12, 13, 14, 15, 16] propose methods for self-supervised pretraining, but they only fuse text and KG in a shallow or uni-directional manner. Another line of work [8, 9] proposes bidirectional models for text and KG, but these models only perform finetuning on specific labeled downstream tasks and do not perform self-supervised learning. Consequently, existing methods may have limited capabilities to model and learn deep interactions over text and KG.

To address both of the above challenges and fully unify the strengths of text and KG, we propose DRAGON (**D**eep Bidi**r**ectional L**a**n**g**uage-Kn**o**wledge Pretrai**n**ing), an approach that performs deeply bidirectional, self-supervised pretraining of a language-knowledge model from raw text and KG. DRAGON has two core components: a cross-modal model that bidirectionally fuses text and KG, and

Figure 1: **Overview of our approach, DRAGON.** *Left*: Given raw data of a text corpus and a large knowledge graph, we create aligned (text, local KG) pairs by sampling a text segment from the corpus and extracting a relevant subgraph from the KG (§2.1). As the structured knowledge in KG can ground the text and the text can provide the KG with rich context for reasoning, we aim to pretrain a language-knowledge model jointly from the text-KG pairs (DRAGON). *Right*: To model the interactions over text and KG, DRAGON uses a cross-modal encoder that bidirectionally exchanges information across them to produce fused text token and KG node representations (§2.2). To pretrain DRAGON jointly on text and KG, we unify two self-supervised reasoning tasks: (1) masked language modeling, which masks some tokens in the input text and then predicts them, and (2) link prediction, which holds out some edges from the input KG and then predicts them. This joint objective encourages text and KG to mutually inform each other, facilitating the model to learn joint reasoning over text and KG (§2.3).

a bidirectional self-supervised objective that learns joint reasoning over text and KG. Concretely, as in Figure 1, we take a text corpus and a KG as raw data, and create inputs for the model by sampling a text segment from the corpus and extracting a relevant subgraph from the KG via entity linking, obtaining a (*text*, *local KG*) pair. We use a cross-modal model to encode this input into fused representations, where each layer of the model encodes the text with an LM and the KG with a graph neural network (GNN), and fuses the two with a bidirectional modality interaction module (GreaseLM [9]). We pretrain this model by unifying two self-supervised reasoning tasks: (1) masked language modeling (MLM), which masks and predicts tokens in the input text, and (2) link prediction, which drops and predicts edges in the input KG. The intuition is that by combining the two tasks, MLM makes the model use the text jointly with structured knowledge in the KG to reason about masked tokens in the text (e.g., in Figure 1, using the "round brush"–"art supply" multi-hop path from the KG helps), and link prediction makes the model use the KG structure jointly with the textual context to reason about missing links in the KG (e.g., recognizing that "round brush could be used for hair" from the text helps). This joint objective thus enables text to be grounded by KG structure and KG to be contextualized by text simultaneously, producing a deeply-unified language-knowledge pretrained model where information flows bidirectionally between text and KG for reasoning.

We pretrain DRAGON in two domains: a general domain, using the Book corpus and ConceptNet KG [7] (§3), and a biomedical domain, using the PubMed corpus and UMLS KG [17] (§4). We show that DRAGON improves on existing LMs and LM+KG models on diverse downstream tasks across domains. For the general domain, DRAGON outperforms RoBERTa [18], our base LM without KGs, on various commonsense reasoning tasks such as CSQA, OBQA, RiddleSense and HellaSwag, with +8% absolute accuracy gain on average. For the biomedical domain, DRAGON improves on the previous best LM, BioLinkBERT [19], and sets new states of the art on BioNLP tasks such as MedQA and PubMedQA, with +3% accuracy gain. In particular, DRAGON exhibits notable improvements on QA tasks involving complex reasoning about language and knowledge (+10% gain on multi-step, negation, hedge, or long context reasoning) and on downstream tasks with limited training data (+8% gain). These results show that our deep bidirectional self-supervision over text and KG produces significantly superior language-knowledge representations compared to existing models. All code, data and pretrained DRAGON models will be released upon publication.

1.1 Related work

Knowledge-augmented LM pretraining. Knowledge integration is an active research for improving LMs. One line of works is retrieval-augmented LMs [20, 21, 22], which retrieve relevant text from a corpus and integrate it into LMs as additional knowledge. Orthogonal to these works, we focus on using knowledge bases as background knowledge, to ground reasoning about entities and facts.

Closest to our work are works that integrate knowledge base information in LM pretraining. One line of research adds entity features to LMs [12, 23, 24], but they do not incorporate KG structure. Some works use KG entity information or structure to create additional training signals [13, 25, 14, 26, 27], but they do not fuse text and KG in the same input context to model their interactions for reasoning. Several works add KG information (e.g. triplets) directly to the LM input [28, 16, 15, 29, 30]. However, these methods propagate information from one side to the other (e.g., KG to text), limiting the capacity to jointly reason over the two modalities. Different from the above works, we propose to bidirectionally interact text and KG via a cross-modal model and joint self-supervised objective, so that text and KG are grounded and contextualized by each other. We find that this improves model performance on various reasoning tasks (§3). We also note that while above works often focus adding entity- or triplet-level knowledge in KGs to LMs, we use larger KG subgraphs (200 nodes) as input to enable richer contextualization and exploit the further potential of KGs as reasoning scaffolds.

KG-augmented question answering. Various works designed KG-augmented reasoning models for question answering [31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41]. In particular, recent works such as QAGNN [8] and GreaseLM [9] suggest that a KG can scaffold reasoning about entities with its graph structure and help for complex question answering (e.g., negation, multi-hop reasoning). However, these works focus on training or finetuning models on specific QA datasets. In contrast, we propose to generalize this and integrate KG-augmented reasoning into general-purpose pretraining. Our motivation is that self-supervised pretraining allows the model to learn from larger and more diverse data, helping to learn richer interactions between text and KGs and to acquire more diverse reasoning abilities beyond specific QA tasks. We find that our proposed pretraining approach (DRAGON) offers significant boosts over the baseline QA models (e.g. GreaseLM) on diverse downstream tasks (§3). This opens a new research avenue in scaling up various carefully-designed QA models to pretraining.

KG representation learning. Our link prediction task used in pretraining is motivated by research in KG representation learning. Link prediction is a fundamental task in KGs [42, 43], and various works study methods to learn KG entity and relation embeddings for link prediction, such as TransE [44], DistMult [45] and RotatE [46]. Several works additionally use textual data or pretrained LMs to aid learning KG embeddings and link prediction [47, 48, 49, 50, 51, 52]. While these works focus on the KG-side representations, we extend the scope and use the KG-side objective (link prediction) jointly with a text-side objective (language modeling) to train a mutually-interactive text-KG model.

2 Deep Bidirectional Language-Knowledge Pretraining (DRAGON)

We propose DRAGON, an approach that performs deeply bidirectional, self-supervised pretraining of a language-knowledge model from text and KG. Specifically, as illustrated in Figure 1, we take a text corpus and a large knowledge graph as raw data, and create input instances for the model by sampling coarsely-aligned (text segment, local KG) pairs (§2.1). To learn mutual interactions over text and KG, DRAGON consists of a cross-modal encoder (GreaseLM) that fuses the input text-KG pair bidirectionally (§2.2), and a pretraining objective that performs bidirectional self-supervision on the text-KG input (§2.3). Our pretraining objective unifies masked language modeling (MLM) and KG link prediction (LinkPred) to make text and KG mutually inform each other and learn joint reasoning over them. Finally, we describe how we finetune the pretrained DRAGON model for downstream tasks (§2.4). While the individual piece of our approach (GreaseLM, MLM, LinkPred) is not new in itself, our contribution is that we are the first to bring these pieces together, present how to unify them effectively and show that this produces a significantly performant pretrained model (§3, §4).

Definitions. We define a text corpus $\mathcal{W}$ as a set of text segments $\mathcal{W} = \{W\}$, and each text segment W as a sequence of tokens (words), $W = \{w_1, ..., w_I\}$. We define a knowledge graph (KG) as a multi-relational graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, where $\mathcal{V}$ is the set of entity nodes in the KG and $\mathcal{E} \subseteq \mathcal{V} \times \mathcal{R} \times \mathcal{V}$ is the set of edges (triplets) that connect nodes in $\mathcal{V}$, with $\mathcal{R}$ being the set of relation types $\{r\}$. Each triplet (h, r, t) in a KG can represent a knowledge fact such as (Paris, in, France). As a raw KG is often large, with millions of nodes, a subgraph of the raw KG (*local KG*) is considered: $G = (V, E)$ where $V = \{v_1, ..., v_J\} \subseteq \mathcal{V}$ and $E \subseteq \mathcal{E}$. We define a language-knowledge model to be a composition of two functions, $f_{\text{head}}(f_{\text{enc}}(X))$, where the encoder f_{enc} takes in an input $X = $ (text segment W, local KG G), and produces a contextualized vector representation for each text token, $\{\mathbf{H}_1, ..., \mathbf{H}_I\}$, and for each KG node, $\{\mathbf{V}_1, ..., \mathbf{V}_J\}$. A language model is a special case of a language-knowledge model with no KG ($J = 0$). The head f_{head} uses these representations to perform self-supervised tasks in the pretraining step and to perform downstream tasks in the finetuning step.

2.1 Input representation

Given a text corpus $\mathcal{W}$ and a large knowledge graph $\mathcal{G}$, we create input instances for the model by preparing (text segment W, local KG G) pairs. We want each pair's text and KG to be (roughly) semantically aligned so that the text and KG can mutually inform each other and facilitate the model to learn interactive reasoning between the two modalities. Specifically, for each text segment W from $\mathcal{W}$, we extract a relevant local KG G for it from $\mathcal{G}$ via the following KG retrieval process.

KG retrieval. Given a text segment W, we link entity mentions in W to entity nodes in $\mathcal{G}$ to get an initial set of nodes V_{el}. We then add their 2-hop bridge nodes from $\mathcal{G}$ to get the total retrieved nodes $V \subseteq \mathcal{V}$. Lastly, we add all edges that span these nodes in $\mathcal{G}$ to get $E \subseteq \mathcal{E}$, which yields the final local KG, $G = (V, E)$, as well as our final input instance $X = (W, G)$. Appendix B.1 provides more details on KG retrieval. Henceforth, we use "KG" to refer to this local KG G unless noted otherwise.

Modality interaction token/node. For each obtained (text, KG) pair, we further add a special token (interaction token) w_{int} to the text and a special node (interaction node) v_{int} to the KG, which will serve as an information pooling point for each modality as well as an interface for modality interaction in our cross-modal encoder (§2.2). Specifically, we prepend w_{int} to the original text $W = \{w_1, ..., w_I\}$, and connect v_{int} to the entity-linked nodes in the original KG, $V_{\text{el}} \subseteq V = \{v_1, ..., v_J\}$, using a new relation type r_{el}. The interaction token and node can also be used to produce a pooled representation of the whole input, e.g., when finetuning for classification tasks (§2.4).

2.2 Cross-modal encoder

To model mutual interactions over the text and KG, we use a bidirectional sequence-graph encoder for f_{enc} which takes in the text tokens and KG nodes and exchanges information across them for multiple layers to produce a fused representation of each token and node (Figure 1 right):

$$\{\mathbf{H}_{\text{int}}, \mathbf{H}_1, ..., \mathbf{H}_I\}, \{\mathbf{V}_{\text{int}}, \mathbf{V}_1, ..., \mathbf{V}_J\} = f_{\text{enc}}(\{w_{\text{int}}, w_1, ..., w_I\}, \{v_{\text{int}}, v_1, ..., v_J\}) \tag{1}$$

While we may use any deep bidirectional sequence-graph encoder for f_{enc}, for controlled comparison with existing works, we adopt the existing top-performing sequence-graph architecture, GreaseLM [9], which combines Transformers [53] and graph neural networks (GNNs) to fuse text-KG inputs.

Specifically, GreaseLM first uses N layers of Transformer language model (LM) layers to map the input text into initial token representations, and uses KG node embeddings to map the input KG nodes into initial node representations,

$$\{\mathbf{H}_{\text{int}}^{(0)}, \mathbf{H}_1^{(0)}, ..., \mathbf{H}_I^{(0)}\} = \text{LM-Layers}(\{w_{\text{int}}, w_1..., w_I\}), \tag{2}$$

$$\{\mathbf{V}_{\text{int}}^{(0)}, \mathbf{V}_1^{(0)}, ..., \mathbf{V}_J^{(0)}\} = \text{Node-Embedding}(\{v_{\text{int}}, v_1, ..., v_J\}). \tag{3}$$

Then it uses M layers of text-KG fusion layers to encode these token/node representations jointly into the final token/node representations,

$$\{\mathbf{H}_{\text{int}}, ..., \mathbf{H}_I\}, \{\mathbf{V}_{\text{int}}, ..., \mathbf{V}_J\} = \text{Fusion-Layers}(\{\mathbf{H}_{\text{int}}^{(0)}, ..., \mathbf{H}_I^{(0)}\}, \{\mathbf{V}_{\text{int}}^{(0)}, ..., \mathbf{V}_J^{(0)}\}), \tag{4}$$

where each of the fusion layers ($\ell = 1, ..., M$) performs the following:

$$\{\widetilde{\mathbf{H}}_{\text{int}}^{(\ell)}, \mathbf{H}_1^{(\ell)}, ..., \mathbf{H}_I^{(\ell)}\} = \text{LM-Layer}(\{\mathbf{H}_{\text{int}}^{(\ell-1)}, \mathbf{H}_1^{(\ell-1)}, ..., \mathbf{H}_I^{(\ell-1)}\}), \tag{5}$$

$$\{\widetilde{\mathbf{V}}_{\text{int}}^{(\ell)}, \mathbf{V}_1^{(\ell)}, ..., \mathbf{V}_J^{(\ell)}\} = \text{GNN-Layer}(\{\mathbf{V}_{\text{int}}^{(\ell-1)}, \mathbf{V}_1^{(\ell-1)}, ..., \mathbf{V}_J^{(\ell-1)}\}), \tag{6}$$

$$[\mathbf{H}_{\text{int}}^{(\ell)}; \mathbf{V}_{\text{int}}^{(\ell)}] = \text{MInt}([\widetilde{\mathbf{H}}_{\text{int}}^{(\ell)}; \widetilde{\mathbf{V}}_{\text{int}}^{(\ell)}]). \tag{7}$$

Here GNN induces graph structure-aware representations of KG nodes, $[\cdot \, ; \cdot]$ does concatenation, and MInt (modality interaction module) exchanges information between the interaction token (text side) and interaction node (KG side) via an MLP. For more details on GreaseLM, we refer readers to [9].

2.3 Pretraining objective

We aim to pretrain the DRAGON model so that it learns joint reasoning over text and a KG. To ensure that the text and KG mutually inform each other and the model learns bidirectional information flow, we unify two self-supervised reasoning tasks: masked language modeling and KG link prediction.

Masked language modeling (MLM). MLM is a common pretraining task used for language models (e.g., BERT [2], RoBERTa [18]), which masks some tokens in the input text and predicts them. This task makes the model use non-masked context to reason about masked tokens, and in particular, as

our approach takes a joint text-KG pair as input, we expect that MLM can encourage the model to learn to use the text *jointly with* structured knowledge in the KG to reason about masks in the text (e.g., in the example of Figure 1, besides the textual context, recognizing the "round brush"–"art supply" path from the KG can help together to predict the masked tokens "art supplies").

Concretely, to perform the MLM task, we mask a subset of tokens in the input text, $M \subseteq W$, with a special token [MASK], and let the task head f_{head} be a linear layer that takes the contextualized token vectors $\{\mathbf{H}_i\}$ from the encoder to predict the original tokens. The objective is a cross-entropy loss:

$$\mathcal{L}_{\text{MLM}} = - \sum_{i \in M} \log p(w_i \mid \mathbf{H}_i). \tag{8}$$

Link prediction (LinkPred).   While the MLM task predicts for the text side, link prediction holds out some edges from the input KG and predicts them. Link prediction is a fundamental task in KGs [46] and makes the model use the structure of KGs to perform reasoning (e.g., using a compositional path "X's mother's husband is Y" to deduce a missing link "X's father is Y"). In particular, as our approach takes a joint text-KG pair as input, we expect that link prediction can encourage the model to learn to use the KG structure *jointly with* the textual context to reason about missing links in the KG (e.g., in Figure 1, besides the KG structure, recognizing that "round brush could be used for hair" from the text can help together to predict the held-out edge (round_brush, at, hair)).

Concretely, to perform the link prediction task, we hold out a subset of edge triplets from the input KG, $S = \{(h, r, t)\} \subseteq E$. For the task head f_{head}, we adopt a KG representation learning framework, which maps each entity node (h or t) and relation (r) in the KG to a vector, $\mathbf{h}, \mathbf{t}, \mathbf{r}$, and defines a scoring function $\phi_r(\mathbf{h}, \mathbf{t})$ to model positive/negative triplets. Specifically, we let $\mathbf{h} = \mathbf{V}_h, \mathbf{t} = \mathbf{V}_t$, $\mathbf{r} = \mathbf{R}_r$, with $\{\mathbf{V}_j\}$ being the contextualized node vectors from the encoder, and $\mathbf{R} = \{\mathbf{r}_1, ..., \mathbf{r}_{|\mathcal{R}|}\}$ learnable relation embeddings. We consider a KG triplet scoring function $\phi_r(\mathbf{h}, \mathbf{t})$ such as

$$\text{DistMult [45]: } \langle \mathbf{h}, \mathbf{r}, \mathbf{t} \rangle, \quad \text{TransE [44]: } - \|\mathbf{h} + \mathbf{r} - \mathbf{t}\|, \quad \text{RotatE [46]: } - \|\mathbf{h} \odot \mathbf{r} - \mathbf{t}\|, \tag{9}$$

where $\langle \cdot, \cdot, \cdot \rangle$ denotes the trilinear dot product and $\odot$ the Hadamard product. A higher ϕ indicates a higher chance of (h, r, t) being a positive triplet (edge) instead of negative (no edge). We analyze the choices of scoring functions in §3.4.3. For training, we optimize the objective:

$$\mathcal{L}_{\text{LinkPred}} = \sum_{(h,r,t) \in S} \left(- \log \sigma(\phi_r(\mathbf{h}, \mathbf{t}) + \gamma) + \frac{1}{n} \sum_{(h',r,t')} \log \sigma(\phi_r(\mathbf{h}', \mathbf{t}') + \gamma) \right), \tag{10}$$

where (h', r, t') are n negative samples corresponding to the positive triplet (h, r, t), γ is the margin, and σ is the sigmoid function. The intuition of this objective is to make the model predict triplets of the held-out edges S as positive and other random triplets as negative.

Joint training.   To pretrain DRAGON, we optimize the MLM and LinkPred objectives jointly: $\mathcal{L} = \mathcal{L}_{\text{MLM}} + \mathcal{L}_{\text{LinkPred}}$. This joint objective unifies the effects of MLM and LinkPred, which encourage the model to simultaneously ground text with KG structure and contextualize KG with text, facilitating bidirectional information flow between text and KGs for reasoning. We show in §3.4.3 that the joint objective yields a more performant model than using one of the objectives alone.

2.4 Finetuning

Lastly, we describe how we finetune DRAGON for downstream tasks such as text classification and multiple-choice QA (MCQA). Given an input text W (e.g., concatenation of a question and an answer choice in the case of MCQA), we follow the same steps as §2.1 and §2.2 to retrieve a relevant local KG G and encode them jointly into contextualized token/node vectors, $\{\mathbf{H}_{\text{int}}, \mathbf{H}_1, ..., \mathbf{H}_I\}$, $\{\mathbf{V}_{\text{int}}, \mathbf{V}_1, ..., \mathbf{V}_J\}$. We then compute a pooled representation of the whole input as $\mathbf{X} = \text{MLP}(\mathbf{H}_{\text{int}}, \mathbf{V}_{\text{int}}, \mathbf{G})$, where $\mathbf{G}$ denotes attention-based pooling of $\{\mathbf{V}_j \mid v_j \in \{v_1, ..., v_J\}\}$ using $\mathbf{H}_{\text{int}}$ as a query. Finally, the pooled representation $\mathbf{X}$ is used to perform the downstream task, in the same way as how the [CLS] representation is used in LMs such as BERT and RoBERTa.

The difference from GreaseLM is that while GreaseLM only performs finetuning as described in this section (hence, it is an LM *finetuned* with KGs), DRAGON performs self-supervised pretraining as described in §2.3 (hence, it can be viewed as an LM *pretrained + finetuned* with KGs).

3 Experiments: General domain

We experiment with the proposed approach in a general domain first. We pretrain DRAGON using the Book corpus and ConceptNet KG (§3.1), and evaluate on diverse downstream tasks (§3.2). We show that DRAGON significantly improves on existing models (§3.4). We extensively analyze the effect of DRAGON's key design choices such as self-supervision and use of KGs (§3.4.1, 3.4.2, 3.4.3).

3.1 Pretraining setup

Data. For the text data, we use BookCorpus [54], a general-domain corpus widely used in LM pretraining (e.g., BERT, RoBERTa). It has 6GB of text from online books. For the KG data, we use ConceptNet [7], a general-domain knowledge graph designed to capture background commonsense knowledge. It has 800K nodes and 2M edges in total. To create a training instance, we sample a text segment of length up to 512 tokens from the text corpus, then retrieve a relevant KG subgraph of size up to 200 nodes (details in Appendix B.1), by which we obtain an aligned (text, local KG) pair.

Implementation. For our encoder (§2.2), we use the exact same architecture as GreaseLM [9] (19 LM layers followed by 5 text-KG fusion layers; 360M parameters in total). As done by [9], we initialize parameters in the LM component with the RoBERTa-Large release [18] and initialize the KG node embeddings with pre-computed ConceptNet entity embeddings (details in Appendix B.2). For the link prediction objective (§2.3, Equation 10), we use DistMult [45] for KG triplet scoring, with a negative exampling of 128 triplets and a margin of $\gamma = 0$. To pretrain the model, we perform MLM with a token masking rate of 15% and link prediction with an edge drop rate of 15%. We pretrain for 20,000 steps with a batch size of 8,192 and a learning rate of 2e-5 for parameters in the LM component and 3e-4 for the others. Training took 7 days on eight A100 GPUs using FP16. Additional details on the hyperparameters can be found in Appendix B.3.

3.2 Downstream evaluation tasks

We finetune and evaluate DRAGON on nine diverse commonsense reasoning benchmarks: Common-senseQA (**CSQA**) [55], OpenbookQA (**OBQA**) [56], RiddleSense (**Riddle**) [57], AI2 Reasoning Challenge–Challenge Set (**ARC**) [58], **CosmosQA** [59], **HellaSwag** [60], Physical Interaction QA (**PIQA**) [61], Social Interaction QA (**SIQA**) [62], and Abductive Natural Language Inference (**aNLI**) [63]. Appendix B.4 provides details on these tasks and data splits. For each task, we repeat three runs and report the average accuracy. Hyperparameters used for finetuning can be found in Appendix B.3.

3.3 Baselines

LM. To study the effect of using KGs, we compare DRAGON with the vanilla language model, RoBERTa [18]. As we initialize DRAGON's parameters using the RoBERTa-Large release (§3.1), for fair comparison, we let the baseline be such that we take the RoBERTa-Large release and continue pretraining it with the vanilla MLM objective on the same text data for the same number of steps as DRAGON. Hence, the only difference is that DRAGON uses KGs during pretraining while RoBERTa does not. We then perform standard LM finetuning of RoBERTa on downstream tasks.

LM finetuned with KG. We also compare with existing KG-augmented QA models, QAGNN [8] and GreaseLM [9], which *finetune* a vanilla LM (i.e. RoBERTa-Large) with a KG on downstream tasks, but do not *pretrain* with a KG. GreaseLM is the existing top-performing model in this paradigm. As we use the same encoder architecture as GreaseLM for DRAGON, the only difference from GreaseLM is that DRAGON performs self-supervised pretraining while GreaseLM does not.

3.4 Results

Table 1 shows performance on the 9 downstream commonsense reasoning tasks. Across all tasks, DRAGON consistently outperforms the existing LM (RoBERTa) and KG-augmented QA models (QAGNN, GreaseLM), e.g., +7% absolute accuracy boost over RoBERTa and +5% over GreaseLM on *OBQA*. DRAGON also performs competitively to all other top systems on the leaderboad (see Appendix C). These accuracy boosts indicate the advantage of DRAGON over RoBERTa (KG reasoning) and over GreaseLM (pretraining). The gain is especially significant on datasets that have small training

	CSQA	OBQA	Riddle	ARC	CosmosQA	HellaSwag	PIQA	SIQA	aNLI
RoBERTa [18]	68.7	64.9	60.7	43.0	80.5	82.3	79.4	75.9	82.7
QAGNN [8]	73.4	67.8	67.0	44.4	80.7	82.6	79.6	75.7	83.0
GreaseLM [9]	74.2	66.9	67.2	44.7	80.6	82.8	79.6	75.5	83.3
DRAGON (**Ours**)	**76.0**	**72.0**	**71.3**	**48.6**	**82.3**	**85.2**	**81.1**	**76.8**	**84.0**

Table 1: Accuracy on downstream commonsense reasoning tasks. DRAGON consistently outperforms the existing LM (RoBERTa) and KG-augmented QA models (QAGNN, GreaseLM) on all tasks. The gain is especially significant on tasks that have small training data (*OBQA*, *Riddle*, *ARC*) and tasks that require complex reasoning (*CosmosQA*, *HellaSwag*).

	Negation	Conjunction	Hedge	# Prepositional Phrases				# Entities
				0	1	2	3	>10
RoBERTa	61.7	70.9	68.6	67.6	71.0	71.1	73.1	74.5
QAGNN	65.1	74.5	74.2	72.1	71.6	75.6	71.3	78.6
GreaseLM	65.1	74.9	76.6	75.6	73.8	74.7	73.6	79.4
DRAGON (**Ours**)	**75.2**	**79.6**	**77.5**	**79.1**	**78.2**	**77.8**	**80.9**	**83.5**

Table 2: Accuracy of DRAGON on *CSQA + OBQA* dev sets for **questions involving complex reasoning** such as negation terms, conjunction terms, hedge terms, prepositional phrases, and more entity mentions. DRAGON consistently outperforms the existing LM (RoBERTa) and KG-augmented QA models (QAGNN, GreaseLM) in these complex reasoning settings.

data such as *ARC*, *Riddle* and *OBQA*, and datasets that require complex reasoning such as *CosmosQA* and *HellaSwag*, which we analyze in more detail in the following sections.

3.4.1 Analysis: Effect of knowledge graph

The first key contribution of DRAGON (w.r.t. existing LM pretraining methods) is that we incorporate KGs. We find that this significantly improves the model's performance for robust and complex reasoning, such as resolving multi-step reasoning and negation, as we discuss below.

Quantitative analysis. In Table 2, we study downstream task performance of DRAGON on questions involving complex reasoning. Building on [8, 9], we consider several proxies to categorize complex questions: (i) presence of negation (e.g. *no*, *never*), (ii) presence of conjunction (e.g. *and*, *but*), (iii) presence of hedge (e.g. *sometimes*, *maybe*), (iv) number of prepositional phrases, and (v) number of entity mentions. Having negation or conjunction indicates logical multi-step reasoning, having more prepositional phrases or entity mentions indicates involving more reasoning steps or constraints, and having hedge terms indicates involving complex textual nuance. DRAGON significantly outperforms the baseline LM (RoBERTa) across all these categories (e.g., +14% accuracy for negation), which confirms that our joint language-knowledge pretraining boosts reasoning performance. DRAGON also consistently outperforms the existing KG-augmented QA models (QAGNN, GreaseLM). We find that QAGNN and GreaseLM only improve moderately on RoBERTa for some categories like conjunction or many prepositional phrases (=2, 3), but DRAGON provides substantial boosts. This suggests that through self-supervised pretraining with larger and diverse data, DRAGON has learned more general-purpose reasoning abilities than the finetuning-only models like GreaseLM.

Qualitative analysis. Using the *CSQA* dataset, we further conducted case studies on the behavior of DRAGON's KG reasoning component, where we visualize how graph attention weights change given different question variations (Figure 2). We find that DRAGON exhibits abilities to extrapolate and perform robust reasoning. For instance, DRAGON adjusts the entity attention weights and final predictions accordingly when we add conjunction or negation about entities (A1, A2) or when we add extra context to an original question (B1→B2), but existing models, RoBERTa and GreaseLM, struggle to predict the correct answers. As these questions are more complex than ones typically seen in the *CSQA* training set, our insight is that while vanilla LMs (RoBERTa) and finetuning (GreaseLM) have limitation in learning complex reasoning, KG-augmented pretraining (DRAGON) helps acquire generalizable reasoning abilities that extrapolate to harder test examples.

3.4.2 Analysis: Effect of pretraining

Another key contribution of DRAGON (w.r.t. existing QA models like GreaseLM) is pretraining. Here we discuss when and why our pretraining is useful. Considering the three core factors in machine learning (data, task complexity, and model capacity), pretraining helps when the available downstream task data is smaller compared to the downstream task complexity or model capacity. Concretely, we find that DRAGON is especially helpful for the following three scenarios.

Downstream tasks with limited data. In Table 1, we find that DRAGON provides significant boosts over GreaseLM on downstream tasks with limited finetuning data available, such as *ARC* (3K training

Figure 2: Analysis of DRAGON's graph reasoning, where we visualize how graph attention weights and final predictions change given question variations. Darker and thicker edges indicate higher attention weights. **DRAGON exhibits abilities to extrapolate and perform robust reasoning**. DRAGON adjusts the entity attention weights and final predictions accordingly when conjunction or negation is given about entities (A1, A2) or when extra context is added to an original question (B1→B2), but existing models, RoBERTa and GreaseLM, struggle to predict the correct answers. **A1:** DRAGON's final GNN layer shows strong attention to "school" but weak attention to "trip", likely because the question states "*and* store one"—hence, the chair is *not* used for a trip. **A2:** DRAGON shows strong attention to "trip" and "beach", likely because the question now states "*but not* store one"—hence, the chair *is* used for a trip. **B1→B2:** DRAGON's final GNN layer shows strong attention to "movie" in the original question (B1), but after adding the extra context "don't enjoy pre-record" (B2), DRAGON shows strong attention to "live" and "concert", leading to making the correctly adjusted prediction "concert hall". One interpretation of these findings is that DRAGON leverages the KG's graph structure as a scaffold for performing complex reasoning.

Method	CosmosQA (10% train)	PIQA (10% train)
RoBERTa	72.2	66.4
GreaseLM	73.0	67.0
DRAGON (**Ours**)	**77.9**	**72.3**

Table 3: Performance in low-resource setting where 10% of finetuning data is used. DRAGON attains large gains, suggesting its benefit for downstream data efficiency.

Method	CSQA	OBQA
GreaseLM	74.2	66.9
GreaseLM-Ex	73.9	66.2
DRAGON (**Ours**)	76.0	72.0
DRAGON-Ex (**Ours**)	**76.3**	**72.8**

Table 4: Downstream performance when model capacity—number of text-KG fusion layers—is increased ("-Ex"). Increased capacity does not help for the finetuning-only model (GreaseLM), but helps when pretrained (DRAGON), suggesting the promise of DRAGON to be further scaled up.

Ablation Type	Ablation	CSQA	OBQA
Pretraining objective	MLM + LinkPred (**final**)	**76.0**	**72.0**
	MLM only	74.3	67.2
	LinkPred only	73.8	66.4
LinkPred head	DistMult (**final**)	**76.0**	**72.0**
	TransE	75.7	71.4
	RotatE	75.8	71.7
Cross-modal model	Bidirectional interaction (**final**)	**76.0**	**72.0**
	Concatenate at end	74.5	68.0
KG structure	Use graph (**final**)	**76.0**	**72.0**
	Convert to sentence	74.7	70.1

Table 5: Ablation study of DRAGON. Using joint pretraining objective MLM + LinkPred (§2.3) outperforms using one of them only. All variants of LinkPred scoring models (DistMult, TransE, RotatE) outperform the baseline without LinkPred ("MLM only"), suggesting the generality of DRAGON to be combined with KG representation learning models. Cross-modal model with bidirectional modality interaction (§2.2) outperforms combining text and KG representations only at the end. Finally, using KG as graph outperforms converting KG as sentences, suggesting the benefit of graph structure for reasoning.

instances; +4% accuracy gain), *Riddle* (3K instances; +4% accuracy) and *OBQA* (5K instances; +5% accuracy). For other tasks, we also experimented with a low-resource setting where 10% of finetuning data is used (Table 3). Here we also see that DRAGON attains significant gains over GreaseLM (+5% accuracy on *PIQA*), suggesting the improved data-efficiency of DRAGON.

Complex downstream tasks. In Table 1, we find that DRAGON provides substantial gains over GreaseLM on downstream tasks involving more complex reasoning, such as *CosmosQA* and *HellaSwag*, where the inputs have longer context and more entities (thus bigger local KGs). For these tasks, improvements of GreaesLM over RoBERTa were small (+0.1% on *CosmosQA*), but DRAGON provides substantial boosts (+1.8%). Our insight is that through self-supervised pretraining with larger and more diverse data, DRAGON has learned richer text-KG interactions than GreaseLM, enabling solving more complex downstream tasks. Similarly, as seen in §3.4.1, DRAGON also attains large gains over GreaseLM on complex questions containing negation, conjunction and prepositional phrases (Table 2), and extrapolates to questions more complex than seen in training sets (Figure 2).

Increased model capacity. In Table 4, we study downstream performance when the model capacity is increased—the number of text-KG fusion layers is increased from 5 to 7—for both GreaseLM and DRAGON. We find that increased capacity does not help for the finetuning-only model (GreaseLM) as was also reported in the original GreaseLM paper, but it helps when pretrained (DRAGON). This result reveals that increased model capacity can actually be beneficial when combined with pretraining, and suggests the promise of DRAGON to be further scaled up.

3.4.3 Analysis: Design choices of DRAGON

Pretraining objective (Table 5 top). The first important design choice of DRAGON is the joint pretraining objective: MLM + LinkPred (§2.3). Using the joint objective outperforms using MLM or LinkPred alone (+5% accuracy on *OBQA*). This suggests that having the bidirectional self-supervised tasks on text and KG facilitates the model to fuse the two modalities for reasoning.

Link prediction head choice (Table 5 middle 1). KG representation learning is an active area of research, and various KG triplet scoring models are proposed (Equation 9). We hence experimented with using different scoring models for DRAGON's link prediction head (§2.3). We find that while DistMult has a slight edge, all variants we tried (DistMult, TransE, RotatE) are effective, outperforming the baseline without LinkPred ("MLM only"). This result suggests the generality of DRAGON and its promise to be combined with various KG representation learning techniques.

Cross-modal model (Table 5 middle 2). Another core component of DRAGON is the cross-modal encoder with bidirectional text-KG fusion layers (§2.2). We find that if we ablate them and simply concatenate text and KG representations at the end, the performance drops substantially. This result suggests that deep bidirectional fusion is crucial to model interactions over text and KG for reasoning.

KG structure (Table 5 bottom). The final key design of DRAGON is that we leverage the graph structure of KGs via a sequence-graph encoder and link prediction objective. Here we experimented with an alternative pretraining method that drops the graph structure: we convert triplets in the local KG into sentences using a template [32], append them to the main text input, and perform vanilla MLM pretraining. We find that DRAGON substantially outperforms this variant (+2% accuracy on *OBQA*), which suggests that the graph structure of KGs helps the model perform reasoning.

4 Experiments: Biomedical domain

Biomedicine is a domain with extensive background knowledge [64, 65, 66, 1], and experts curate various knowledge bases for it [67, 17, 68, 69]. We hypothesize that these biomedical KGs can enable deeper understanding and reasoning about biomedical text. With this motivation, we pretrain DRAGON on a biomedical corpus and KG, and evaluate on biomedical downstream tasks.

Pretraining setup. For the text data, we use PubMed [70], a widely-used corpus in biomedial LM training (e.g., BioBERT [71], PubmedBERT [72]). It contains the abstracts of biomedical papers on PubMed and has 21GB of text. For the KG data, we use the Unified Medical Language System (UMLS) [17], a widely-used knowledge graph in biomedicine. It has 300K nodes and 1M edges in total. For training, we follow the same procedure as the experiment in the general domain (§3.1), except that we initialize DRAGON's LM component with BioLinkBERT-Large [19], the state-of-the-art biomedical LM, instead of RoBERTa-Large. Note that while "BioLinkBERT" has "Link" in its name, it is not about KG links but about citation links that the model was originally pretrained with.

Downstream evaluation tasks. We finetune and evaluate DRAGON on three popular biomedical NLP and reasoning benchmarks: MedQA-USMLE (**MedQA**) [73], **PubMedQA** [74], and **BioASQ** [75]. Appendix B.4 provides details on these tasks and data splits.

Baselines. We compare DRAGON with the vanilla LM (BioLinkBERT) and LMs finetuned with the KG (QAGNN and GreaseLM seeded with BioLinkBERT).

Results. Table 6 summarizes model performance on the downstream tasks. Across tasks, DRAGON outperforms all the existing biomedical LMs and KG-augmented QA models, e.g., +3% absolute accuracy boost over BioLinkBERT and +2% over GreaseLM on *MedQA*, achieving new state-of-the-art performance on

Method	MedQA	PubMedQA	BioASQ
BioBERT [71]	36.7	60.2	84.1
PubmedBERT [72]	38.1	55.8	87.5
BioLinkBERT [19]	44.6	72.2	94.8
+ QAGNN	45.0	72.1	95.0
+ GreaseLM	45.1	72.4	94.9
DRAGON (**Ours**)	**47.5**	**73.4**	**96.4**

Table 6: Accuracy on biomedical NLP tasks. DRAGON outperforms all previous biomedical LMs.

these tasks. This result suggests significant efficacy of KG-augmented pretraining for improving biomedical reasoning tasks. Combined with the results in the general commonsense domain (§3.4), our experiments also suggest the domain-generality of DRAGON, serving as an effective pretraining method across domains with different combinations of text, KGs and seed LMs.

5 Conclusion

We presented DRAGON, a self-supervised pretraining method to learn a deeply bidirectional language-knowledge model from text and knowledge graphs (KGs) at scale. In both general and biomedical domains, DRAGON outperforms existing language models and KG-augmented models on various NLP tasks, and exhibits notably strong performance on complex reasoning such as answering questions involving long context or multi-step reasoning.

References

[1] Rishi Bommasani et al. On the opportunities and risks of foundation models. *arXiv preprint arXiv:2108.07258*, 2021.

[2] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *North American Chapter of the Association for Computational Linguistics (NAACL)*, 2019.

[3] Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[4] Matthew E Peters, Mark Neumann, Mohit Iyyer, Matt Gardner, Christopher Clark, Kenton Lee, and Luke Zettlemoyer. Deep contextualized word representations. In *North American Chapter of the Association for Computational Linguistics (NAACL)*, 2018.

[5] Kurt Bollacker, Colin Evans, Praveen Paritosh, Tim Sturge, and Jamie Taylor. Freebase: a collaboratively created graph database for structuring human knowledge. In *SIGMOD*, 2008.

[6] Denny Vrandečić and Markus Krötzsch. Wikidata: A free collaborative knowledgebase. *Communications of the ACM*, 2014.

[7] Robyn Speer, Joshua Chin, and Catherine Havasi. Conceptnet 5.5: An open multilingual graph of general knowledge. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2017.

[8] Michihiro Yasunaga, Hongyu Ren, Antoine Bosselut, Percy Liang, and Jure Leskovec. QA-GNN: Reasoning with language models and knowledge graphs for question answering. In *North American Chapter of the Association for Computational Linguistics (NAACL)*, 2021.

[9] Xikun Zhang, Antoine Bosselut, Michihiro Yasunaga, Hongyu Ren, Percy Liang, Christopher D Manning, and Jure Leskovec. Greaselm: Graph reasoning enhanced language models for question answering. In *International Conference on Learning Representations (ICLR)*, 2022.

[10] Hongyu Ren, Weihua Hu, and Jure Leskovec. Query2box: Reasoning over knowledge graphs in vector space using box embeddings. In *International Conference on Learning Representations (ICLR)*, 2020.

[11] Hongyu Ren, Hanjun Dai, Bo Dai, Xinyun Chen, Michihiro Yasunaga, Haitian Sun, Dale Schuurmans, Jure Leskovec, and Denny Zhou. Lego: Latent execution-guided reasoning for multi-hop question answering on knowledge graphs. In *International Conference on Machine Learning (ICML)*, 2021.

[12] Zhengyan Zhang, Xu Han, Zhiyuan Liu, Xin Jiang, Maosong Sun, and Qun Liu. Ernie: Enhanced language representation with informative entities. In *Association for Computational Linguistics (ACL)*, 2019.

[13] Wenhan Xiong, Jingfei Du, William Yang Wang, and Veselin Stoyanov. Pretrained encyclopedia: Weakly supervised knowledge-pretrained language model. In *International Conference on Learning Representations (ICLR)*, 2020.

[14] Xiaozhi Wang, Tianyu Gao, Zhaocheng Zhu, Zhengyan Zhang, Zhiyuan Liu, Juanzi Li, and Jian Tang. Kepler: A unified model for knowledge embedding and pre-trained language representation. *Transactions of the Association for Computational Linguistics (TACL)*, 2021.

[15] Oshin Agarwal, Heming Ge, Siamak Shakeri, and Rami Al-Rfou. Knowledge graph based synthetic corpus generation for knowledge-enhanced language model pre-training. In *North American Chapter of the Association for Computational Linguistics (NAACL)*, 2021.

[16] Yu Sun, Shuohuan Wang, Shikun Feng, Siyu Ding, Chao Pang, Junyuan Shang, Jiaxiang Liu, Xuyi Chen, Yanbin Zhao, Yuxiang Lu, et al. Ernie 3.0: Large-scale knowledge enhanced pre-training for language understanding and generation. *arXiv preprint arXiv:2107.02137*, 2021.

[17] Olivier Bodenreider. The unified medical language system (UMLS): Integrating biomedical terminology. *Nucleic acids research*, 2004.

[18] Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019.

[19] Michihiro Yasunaga, Jure Leskovec, and Percy Liang. LinkBERT: Pretraining language models with document links. In *Association for Computational Linguistics (ACL)*, 2022.

[20] Kelvin Guu, Kenton Lee, Zora Tung, Panupong Pasupat, and Ming-Wei Chang. Realm: Retrieval-augmented language model pre-training. In *International Conference on Machine Learning (ICML)*, 2020.

[21] Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. Retrieval-augmented generation for knowledge-intensive nlp tasks. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[22] Sebastian Borgeaud, Arthur Mensch, Jordan Hoffmann, Trevor Cai, Eliza Rutherford, Katie Millican, George van den Driessche, Jean-Baptiste Lespiau, Bogdan Damoc, Aidan Clark, et al. Improving language models by retrieving from trillions of tokens. *arXiv preprint arXiv:2112.04426*, 2021.

[23] Matthew E. Peters, Mark Neumann, IV RobertLLogan, Roy Schwartz, V. Joshi, Sameer Singh, and Noah A. Smith. Knowledge enhanced contextual word representations. In *Empirical Methods in Natural Language Processing (EMNLP)*, 2019.

[24] Corby Rosset, Chenyan Xiong, Minh Phan, Xia Song, Paul Bennett, and Saurabh Tiwary. Knowledge-aware language model pretraining. *arXiv preprint arXiv:2007.00655*, 2020.

[25] Tao Shen, Yi Mao, Pengcheng He, Guodong Long, Adam Trischler, and Weizhu Chen. Exploiting structured knowledge in text via graph-guided representation learning. In *Empirical Methods in Natural Language Processing (EMNLP)*, 2020.

[26] Fangyu Liu, Ehsan Shareghi, Zaiqiao Meng, Marco Basaldella, and Nigel Collier. Self-alignment pretraining for biomedical entity representations. In *North American Chapter of the Association for Computational Linguistics (NAACL)*, 2021.

[27] Donghan Yu, Chenguang Zhu, Yiming Yang, and Michael Zeng. Jaket: Joint pre-training of knowledge graph and language understanding. In *AAAI Conference on Artificial Intelligence*, 2022.

[28] Weijie Liu, Peng Zhou, Zhe Zhao, Zhiruo Wang, Qi Ju, Haotang Deng, and P. Wang. K-bert: Enabling language representation with knowledge graph. In *AAAI Conference on Artificial Intelligence*, 2020.

[29] Tianxiang Sun, Yunfan Shao, Xipeng Qiu, Qipeng Guo, Yaru Hu, Xuan-Jing Huang, and Zheng Zhang. Colake: Contextualized language and knowledge embedding. In *International Conference on Computational Linguistics (COLING)*, 2020.

[30] Bin He, Di Zhou, Jinghui Xiao, Xin Jiang, Qun Liu, Nicholas Jing Yuan, and Tong Xu. Integrating graph contextualized knowledge into pre-trained language models. In *Findings of EMNLP*, 2020.

[31] Bill Yuchen Lin, Xinyue Chen, Jamin Chen, and Xiang Ren. Kagnet: Knowledge-aware graph networks for commonsense reasoning. In *Empirical Methods in Natural Language Processing (EMNLP)*, 2019.

[32] Yanlin Feng, Xinyue Chen, Bill Yuchen Lin, Peifeng Wang, Jun Yan, and Xiang Ren. Scalable multi-hop relational reasoning for knowledge-aware question answering. In *Empirical Methods in Natural Language Processing (EMNLP)*, 2020.

[33] Shangwen Lv, Daya Guo, Jingjing Xu, Duyu Tang, Nan Duan, Ming Gong, Linjun Shou, Daxin Jiang, Guihong Cao, and Songlin Hu. Graph-based reasoning over heterogeneous external knowledge for commonsense question answering. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2020.

[34] Kuan Wang, Yuyu Zhang, Diyi Yang, Le Song, and Tao Qin. Gnn is a counter? revisiting gnn for question answering. In *International Conference on Learning Representations (ICLR)*, 2022.

[35] Todor Mihaylov and Anette Frank. Knowledgeable reader: Enhancing cloze-style reading comprehension with external commonsense knowledge. In *Association for Computational Linguistics (ACL)*, 2018.

[36] An Yang, Quan Wang, Jing Liu, Kai Liu, Yajuan Lyu, Hua Wu, Qiaoqiao She, and Sujian Li. Enhancing pre-trained language representations with rich knowledge for machine reading comprehension. In *Association for Computational Linguistics (ACL)*, 2019.

[37] Haitian Sun, Bhuwan Dhingra, Manzil Zaheer, Kathryn Mazaitis, Ruslan Salakhutdinov, and William W Cohen. Open domain question answering using early fusion of knowledge bases and text. In *Empirical Methods in Natural Language Processing (EMNLP)*, 2018.

[38] Haitian Sun, Tania Bedrax-Weiss, and William W Cohen. Pullnet: Open domain question answering with iterative retrieval on knowledge bases and text. In *Empirical Methods in Natural Language Processing (EMNLP)*, 2019.

[39] Jun Yan, Mrigank Raman, Aaron Chan, Tianyu Zhang, Ryan Rossi, Handong Zhao, Sungchul Kim, Nedim Lipka, and Xiang Ren. Learning contextualized knowledge structures for commonsense reasoning. In *Findings of ACL*, 2021.

[40] Yueqing Sun, Qi Shi, Le Qi, and Yu Zhang. Jointlk: Joint reasoning with language models and knowledge graphs for commonsense question answering. In *North American Chapter of the Association for Computational Linguistics (NAACL)*, 2022.

[41] Yichong Xu, Chenguang Zhu, Shuohang Wang, Siqi Sun, Hao Cheng, Xiaodong Liu, Jianfeng Gao, Pengcheng He, Michael Zeng, and Xuedong Huang. Human parity on commonsenseqa: Augmenting self-attention with external attention. In *Association for Computational Linguistics (ACL)*, 2022.

[42] Théo Trouillon, Johannes Welbl, Sebastian Riedel, Éric Gaussier, and Guillaume Bouchard. Complex embeddings for simple link prediction. In *International conference on machine learning (ICML)*, 2016.

[43] Seyed Mehran Kazemi and David Poole. Simple embedding for link prediction in knowledge graphs. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2018.

[44] Antoine Bordes, Nicolas Usunier, Alberto Garcia-Duran, Jason Weston, and Oksana Yakhnenko. Translating embeddings for modeling multi-relational data. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2013.

[45] Bishan Yang, Wen-tau Yih, Xiaodong He, Jianfeng Gao, and Li Deng. Embedding entities and relations for learning and inference in knowledge bases. In *International Conference on Learning Representations (ICLR)*, 2015.

[46] Zhiqing Sun, Zhi-Hong Deng, Jian-Yun Nie, and Jian Tang. Rotate: Knowledge graph embedding by relational rotation in complex space. In *International Conference on Learning Representations (ICLR)*, 2019.

[47] Sebastian Riedel, Limin Yao, Andrew McCallum, and Benjamin M Marlin. Relation extraction with matrix factorization and universal schemas. In *North American Chapter of the Association for Computational Linguistics (NAACL)*, 2013.

[48] Kristina Toutanova, Danqi Chen, Patrick Pantel, Hoifung Poon, Pallavi Choudhury, and Michael Gamon. Representing text for joint embedding of text and knowledge bases. In *Empirical Methods in Natural Language Processing (EMNLP)*, 2015.

[49] Ruobing Xie, Zhiyuan Liu, Jia Jia, Huanbo Luan, and Maosong Sun. Representation learning of knowledge graphs with entity descriptions. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2016.

[50] Liang Yao, Chengsheng Mao, and Yuan Luo. Kg-bert: Bert for knowledge graph completion. *arXiv preprint arXiv:1909.03193*, 2019.

[51] Bosung Kim, Taesuk Hong, Youngjoong Ko, and Jungyun Seo. Multi-task learning for knowledge graph completion with pre-trained language models. In *International Conference on Computational Linguistics (COLING)*, 2020.

[52] Da Li, Sen Yang, Kele Xu, Ming Yi, Yukai He, and Huaimin Wang. Multi-task pre-training language model for semantic network completion. *arXiv preprint arXiv:2201.04843*, 2022.

[53] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems (NeurIPS)*, 2017.

[54] Yukun Zhu, Ryan Kiros, Rich Zemel, Ruslan Salakhutdinov, Raquel Urtasun, Antonio Torralba, and Sanja Fidler. Aligning books and movies: Towards story-like visual explanations by watching movies and reading books. In *International Conference on Computer Vision (ICCV)*, 2015.

[55] Alon Talmor, Jonathan Herzig, Nicholas Lourie, and Jonathan Berant. Commonsenseqa: A question answering challenge targeting commonsense knowledge. In *North American Chapter of the Association for Computational Linguistics (NAACL)*, 2019.

[56] Todor Mihaylov, Peter Clark, Tushar Khot, and Ashish Sabharwal. Can a suit of armor conduct electricity? a new dataset for open book question answering. In *Empirical Methods in Natural Language Processing (EMNLP)*, 2018.

[57] Bill Yuchen Lin, Ziyi Wu, Yichi Yang, Dong-Ho Lee, and Xiang Ren. Riddlesense: Reasoning about riddle questions featuring linguistic creativity and commonsense knowledge. In *Findings of ACL*, 2021.

[58] Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. Think you have solved question answering? try arc, the ai2 reasoning challenge. *arXiv preprint arXiv:1803.05457*, 2018.

[59] Lifu Huang, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. Cosmos qa: Machine reading comprehension with contextual commonsense reasoning. In *Empirical Methods in Natural Language Processing (EMNLP)*, 2019.

[60] Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. Hellaswag: Can a machine really finish your sentence? In *Association for Computational Linguistics (ACL)*, 2019.

[61] Yonatan Bisk, Rowan Zellers, Jianfeng Gao, Yejin Choi, et al. Piqa: Reasoning about physical commonsense in natural language. In *AAAI Conference on Artificial Intelligence*, 2020.

[62] Maarten Sap, Hannah Rashkin, Derek Chen, Ronan LeBras, and Yejin Choi. Socialiqa: Commonsense reasoning about social interactions. In *Empirical Methods in Natural Language Processing (EMNLP)*, 2019.

[63] Chandra Bhagavatula, Ronan Le Bras, Chaitanya Malaviya, Keisuke Sakaguchi, Ari Holtzman, Hannah Rashkin, Doug Downey, Scott Wen-tau Yih, and Yejin Choi. Abductive commonsense reasoning. In *International Conference on Learning Representations (ICLR)*, 2020.

[64] Elliot G Brown, Louise Wood, and Sue Wood. The medical dictionary for regulatory activities (meddra). *Drug safety*, 20(2):109–117, 1999.

[65] Carolyn E Lipscomb. Medical subject headings (mesh). *Bulletin of the Medical Library Association*, 88(3):265, 2000.

[66] Marinka Zitnik, Monica Agrawal, and Jure Leskovec. Modeling polypharmacy side effects with graph convolutional networks. *Bioinformatics*, 34(13):i457–i466, 2018.

[67] Michael Ashburner, Catherine A Ball, Judith A Blake, David Botstein, Heather Butler, J Michael Cherry, Allan P Davis, Kara Dolinski, Selina S Dwight, Janan T Eppig, et al. Gene ontology: tool for the unification of biology. *Nature genetics*, 25(1):25–29, 2000.

[68] David S Wishart, Yannick D Feunang, An C Guo, Elvis J Lo, Ana Marcu, Jason R Grant, Tanvir Sajed, Daniel Johnson, Carin Li, Zinat Sayeeda, et al. Drugbank 5.0: a major update to the drugbank database for 2018. *Nucleic acids research*, 2018.

[69] Camilo Ruiz, Marinka Zitnik, and Jure Leskovec. Identification of disease treatment mechanisms through the multiscale interactome. *Nature communications*, 12(1):1–15, 2021.

[70] PubMed. https://pubmed.ncbi.nlm.nih.gov/.

[71] Jinhyuk Lee, Wonjin Yoon, Sungdong Kim, Donghyeon Kim, Sunkyu Kim, Chan Ho So, and Jaewoo Kang. Biobert: a pre-trained biomedical language representation model for biomedical text mining. *Bioinformatics*, 2020.

[72] Yu Gu, Robert Tinn, Hao Cheng, Michael Lucas, Naoto Usuyama, Xiaodong Liu, Tristan Naumann, Jianfeng Gao, and Hoifung Poon. Domain-specific language model pretraining for biomedical natural language processing. *arXiv preprint arXiv:2007.15779*, 2020.

[73] Di Jin, Eileen Pan, Nassim Oufattole, Wei-Hung Weng, Hanyi Fang, and Peter Szolovits. What disease does this patient have? a large-scale open domain question answering dataset from medical exams. *Applied Sciences*, 2021.

[74] Qiao Jin, Bhuwan Dhingra, Zhengping Liu, William W Cohen, and Xinghua Lu. Pubmedqa: A dataset for biomedical research question answering. In *Empirical Methods in Natural Language Processing (EMNLP)*, 2019.

[75] Anastasios Nentidis, Konstantinos Bougiatiotis, Anastasia Krithara, and Georgios Paliouras. Results of the seventh edition of the bioasq challenge. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, 2019.

[76] Emily Sheng, Kai-Wei Chang, Premkumar Natarajan, and Nanyun Peng. Towards controllable biases in language generation. In *the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)-Findings, long*, 2020.

[77] Laura Weidinger, John Mellor, Maribeth Rauh, Conor Griffin, Jonathan Uesato, Po-Sen Huang, Myra Cheng, Mia Glaese, Borja Balle, Atoosa Kasirzadeh, et al. Ethical and social risks of harm from language models. *arXiv preprint arXiv:2112.04359*, 2021.

[78] Samuel Gehman, Suchin Gururangan, Maarten Sap, Yejin Choi, and Noah A Smith. Realtoxicityprompts: Evaluating neural toxic degeneration in language models. In *Findings of EMNLP*, 2020.

[79] Ninareh Mehrabi, Pei Zhou, Fred Morstatter, Jay Pujara, Xiang Ren, and A. G. Galstyan. Lawyers are dishonest? quantifying representational harms in commonsense knowledge resources. *ArXiv*, abs/2103.11320, 2021.

[80] Zhenzhong Lan, Mingda Chen, Sebastian Goodman, Kevin Gimpel, Piyush Sharma, and Radu Soricut. Albert: A lite bert for self-supervised learning of language representations. In *International Conference on Learning Representations (ICLR)*, 2020.

[81] Jun Yan, Mrigank Raman, Aaron Chan, Tianyu Zhang, Ryan Rossi, Handong Zhao, Sungchul Kim, Nedim Lipka, and Xiang Ren. Learning contextualized knowledge structures for commonsense reasoning. *arXiv preprint arXiv:2010.12873*, 2020.

[82] Weiwen Xu, Huihui Zhang, Deng Cai, and Wai Lam. Dynamic semantic graph construction and reasoning for explainable multi-hop science question answering. *arXiv preprint arXiv:2105.11776*, 2021.

[83] Peifeng Wang, Nanyun Peng, Pedro Szekely, and Xiang Ren. Connecting the dots: A knowledgeable path generator for commonsense question answering. *arXiv preprint arXiv:2005.00691*, 2020.

[84] Weiwen Xu, Yang Deng, Huihui Zhang, Deng Cai, and Wai Lam. Exploiting reasoning chains for multi-hop science question answering. *arXiv preprint arXiv:2109.02905*, 2021.

[85] Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of Machine Learning Research (JMLR)*, 2020.

[86] George Sebastian Pirtoaca. Ai2 leaderboard, 2020. URL https://leaderboard.allenai.org/open_book_qa/submission/brhieieqaupc4cnddfg0.

[87] Daniel Khashabi, Tushar Khot, Ashish Sabharwal, Oyvind Tafjord, Peter Clark, and Hannaneh Hajishirzi. Unifiedqa: Crossing format boundaries with a single qa system. In *Findings of EMNLP*, 2020.

[88] Zixian Huang, Ao Wu, Jiaying Zhou, Yu Gu, Yue Zhao, and Gong Cheng. Clues before answers: Generation-enhanced multiple-choice qa. *arXiv preprint arXiv:2205.00274*, 2022.

[89] Peter Clark, Oren Etzioni, Daniel Khashabi, Tushar Khot, Bhavana Dalvi Mishra, Kyle Richardson, Ashish Sabharwal, Carissa Schoenick, Oyvind Tafjord, Niket Tandon, et al. From 'f' to 'a' on the ny regents science exams: An overview of the aristo project. *arXiv preprint arXiv:1909.01958*, 2019.