AI that knows when it does not know - Uncertainty-Guided Self-Learning Framework for Semi-Supervised Multi-Organ Segmentation

Natália Alves[1] and Bram de Wilde[1]

Diagnostic Image Analysis Group, Department of Medical Imaging, Radboud
University Medical Center, 6500 HB Nijmegen, The Netherlands
{natalia.alves, bram.dewilde}@radboudumc.nl

Abstract. Manual voxel-level annotation of imaging studies is time-consuming and labour-intensive, limiting the number of available samples for developing segmentation AI models. We propose an uncertainty-guided framework for multi-organ segmentation on CT scans that uses a small labelled dataset to leverage a large unlabelled dataset in a semi-supervised setting. First, we train five models to segment 13 abdominal organs using 50 labelled training cases and 5-fold cross-validation. Then, we use these models to generate pseudo-labels for 2000 unlabelled cases and estimate the uncertainty associated with the pseudo-labels by calculating the pair-wise Dice score (DSC) for the five individual predictions. Cases with pair-wise mean DSC>0.9 for all organs are included in the training set at the next iteration, together with the respective pseudo-labels. This process is repeated for four iterations. All selected cases are combined in the last iteration, and a single model is trained to reduce the computational costs associated with ensembling. The self-configuring method for biomedical image segmentation nnU-Net is used to train the segmentation models. We obtained a mean DSC of 0.8388 on the validation set with the network trained using the labelled data alone. The Dice score improved to 0.8874 in the final iteration of the model, trained with the 50 labelled cases and 1813 unlabelled cases with pseudo-labels.

Keywords: Semi-supervised learning · Uncertainty · Pseudo-labeling

1 Introduction

Abdominal organ segmentation on medical images has many important applications, such as organ quantification, surgical planning, and disease diagnosis. Recently, deep learning models, in particular convolutional neural networks (CNNs), have shown outstanding performance at abdominal organ segmentation across different datasets and image modalities [5]. CNNs require large-scale labelled datasets for model training to generalise well to unseen cohorts. However, the manual voxel-level annotation of multiple abdominal organs is time-consuming and labour-intensive, limiting the number of samples available for training.

Semi-supervised learning (SSL) is a training strategy that uses a small amount of labelled data to leverage a large amount of unlabelled data [10]. In the medical domain, popular SSL techniques include transfer learning from a distant or related task, contrastive learning, and self-supervised representation learning with automatically generated labels [1]. A common approach for semi-supervised medical image segmentation is self-training, which consists of generating automatic pseudo-labels for the unlabelled data using the available annotated cases [1]. In particular, a segmentation CNN is first trained on the labelled samples, the trained model then segments the unlabelled samples, and finally, these samples, or a subset of these samples, are added to the training set. This process can be repeated several times, improving the pseudo-labels generated for the unlabelled data.

An inherent risk of the self-training method is the generation of low-quality pseudo-labels, which can lead to noisy training and poor generalisation. In order to lower this risk, only the most accurate pseudo-labels should be added to the training set at each iteration. This can be done, for example, by selecting the unlabelled cases with the most confident softmax output predictions. However, due to poor calibration of neural networks, wrong predictions can have high confidence, leading to the selection of low-quality pseudo-labels [8]. A more robust method also incorporates uncertainty quantification into the selection method. In a recent study, Rizve et al. propose an uncertainty-aware pseudo-label selection framework for natural image classification tasks, which improves pseudo-labelling accuracy by drastically reducing the amount of noise encountered in the training process [8].

In this work, we combine the state-of-the-art self-configuring method for biomedical image segmentation nnU-Net [5] with deep-ensemble uncertainty estimation [6] to build a self-learning framework that leverages prediction uncertainty to guide the pseudo-label selection procedure. All code is open-source and available on GitHub (https://github.com/DIAGNijmegen/flare22-brananas).

2 Method

2.1 Preprocessing

The proposed solution is based on the nnU-Net self-configuring framework for medical image segmentation [5]. All images are resampled to a resolution of $1.2 \times 1.2 \times 4$ mm^3. No other preprocessing is performed before training with the nnU-Net framework [5]. This framework applies its own cropping and intensity normalization strategies.

2.2 Proposed Method

The network architecture is the 3D full resolution variant of the nnU-Net framework [5], which is illustrated in Fig. 1. The loss function is the sum of Dice and Cross Entropy loss, as employed by default by nnU-Net.

Fig. 1: 3D U-Net variant automatically selected by the nnU-Net framework, when applying it to the labelled data (see section 3.1) resampled to $1.2 \times 1.2 \times 4$ mm^3.

For training, we propose an iterative uncertainty-guided process to generate pseudo-labels for the 2000 unlabelled cases in the dataset. Initially, we train 5 models with the 50 labelled cases using 5-fold cross validation. All models do individual inference on the 2000 unlabelled cases, which allows us to evaluate uncertainty for each case. The uncertainty metric we use is the mean pairwise DSC per organ considering the 5 individual models. Instead of using all 2000 cases for the next training iteration, we discard cases where the mean pairwise DSC is below 0.9 for at least one organ. In the next iteration, we train 5 models again using 5-fold cross validation, but now combining the 50 annotated cases with the pseudo-labelled cases that passed the uncertainty criterion. This process is continued for three iterations, after which we train a single model on all cases which pass the uncertainty threshold.

2.3   Post-processing

The inference is performed with a modified version of the nnU-Net framework. In particular, we increase the step size of strided inference from 0.5 to 0.9. This reduces the amount of 3D patches that have to pass through the network, reducing GPU time by a factor of 2. Additionally, we disable test-time augmentation to reduce GPU time by a factor of 2.5, as we observed modest gains in performance.

For post-processing, we start by correcting small noisy segmentations by removing all structures with a volume lower than the minimum volume for that organ in the labelled training set multiplied by 0.5. Then, we perform binary closing to the left and right adrenal gland masks with a $5 \times 5 \times 5$ kernel to connect any separate components on these small structures. We then mask the whole multi-organ segmentation based on the aorta, inferior vena cava and esophagus predictions to remove noisy labels outside the abdominal region. All slices above

the first slice containing at least one of these structures and all slices below the last slice containing at least one of these structures are set to 0. We observed that lesions in the liver were often wrongly segmented as gallbladder, driving down the Dice for both structures. To correct this issue, we check every separate connected component segmented as gallbladder and if it is completely contained within the liver on any 2D slice (in the axial plane), we set the component to liver. Finally, to further remove smaller noisy structures, for every organ we remove any connected component with a volume smaller than 10 % of the whole segmented volume for that organ.

3   Experiments

3.1   Dataset and evaluation measures

The FLARE2022 dataset is curated from more than 20 medical groups under the license permission, including MSD [9], KiTS [3,4], AbdomenCT-1K [7], and TCIA [2]. The training set includes 50 labelled CT scans with pancreas disease and 2000 unlabelled CT scans with liver, kidney, spleen, or pancreas diseases. The validation set includes 50 CT scans with liver, kidney, spleen, or pancreas diseases. The testing set includes 200 CT scans where 100 cases have liver, kidney, spleen, or pancreas diseases and the other 100 cases have uterine corpus endometrial, urothelial bladder, stomach, sarcomas, or ovarian diseases. All the CT scans only have image information and the center information is not available.

The evaluation measures consist of two accuracy measures: Dice Similarity Coefficient (DSC) and Normalized Surface Dice (NSD), and three running efficiency measures: running time, area under GPU memory-time curve, and area under CPU utilization-time curve. All measures will be used to compute the ranking. Moreover, the GPU memory consumption has a 2 GB tolerance.

3.2   Implementation details

Environment settings The development environments and requirements are presented in Table 1.

Training protocols The data augmentation strategy is determined automatically by the nnU-Net framework. Patch sampling during training is done randomly and the models we choose for inference are always the final checkpoints after 1000 training epochs. More details are provided in Table 2.

4   Results and discussion

4.1   Quantitative results on validation set

The validation DSC scores for various experiments are shown in Table 3. The results from iterations 1-3 were obtained by ensambling the models trained with

Table 1: Development environments and requirements.

Ubuntu version	20.04
CPU	Intel(R) Xeon(R) Gold 6152 CPU @ 2.10GHz (9 cores)
RAM	30GB
GPU (number and type)	1 NVIDIA RTX 2080 Ti
CUDA version	11.3 with cudnn 8
Programming language	Python 3.9
Deep learning framework	PyTorch (Torch 1.11, torchvision 0.12, apex 0.1)
Specific dependencies	nnunet

Table 2: Training protocol

Network initialization	"he" normal initialization
Batch size	2
Patch size	40×224×192
Total epochs	1000
Optimizer	SGD with nesterov momentum ($\mu = 0.99$)
Loss function	Dice + CE
Initial learning rate (lr)	0.01
Lr decay schedule	Exponentially decaying (poly lr)
Training time	1000 hours

5-fold cross-validation, while for iteration 4 only one model was trained using the selected training set. We can make a few observations regarding the use of the unlabelled data. Firstly, using all 2000 cases after training on only the annotated data improves performance by about 2%. Secondly, using uncertainty to select a subset of cases improves performance by an additional 1%. Lastly, continuing this iterative process leads to another 1% increase in performance.

The results for each organ in the best performing iteration are shown in Table 4. The worst performing organs were the adrenal glands, followed by the duodenum and the gallbladder. One explanation for this could be that down-sampling to the chosen spacing of $1.2 \times 1.2 \times 4$ mm^3 was too aggressive for these small structures, removing necessary information for an accurate segmentation.

4.2   Qualitative results on validation set

Fig. 2 shows the segmentations obtained across different model iterations and Fig. 3 depicts the effect of the post-processing step. From Fig. 2 we can see the clear improvement in segmentation quality for structures like the right kidney (Case 0002), the duodenum (Case 0042) and the left kidney (Case 0006) with the increasing model iterations. These improvements indicate that the model is generating better-quality pseudo-label for the unlabelled portion of the training set at each iteration, which in turn increases the model's generalization power

Table 3: Validation DSC per iteration

Configuration	DSC
Iteration 0 (50)	0.8388
Unfiltered iteration 1 (50 + 2000)	0.8566
Iteration 1 (50 + 401)	0.8658
Iteration 2 (50 + 1213)	0.8769
Iteration 3 (50 + 1628)	0.8761
Iteration 4 (50 + 1813)	0.8784
Iteration 4 + post-processing	0.8874

Table 4: Validation DSC per organ for Iteration 4 with post-processing

Organ	DSC
Liver	0.9721
Right Kidney	0.9374
Spleen	0.9565
Pancreas	0.8825
Aorta	0.9543
Inferior Vena Cava	0.8988
Right Adrenal Gland	0.7962
Left Adrenal Gland	0.7933
Gallbladder	0.8265
Esophagus	0.8650
Stomach	0.9141
Duodenum	0.8059
Left Kidney	0.9331

and the performance on the separate validation set. There are however still structures that are incorrectly segmented or not detected at all after iteration 4. We observe that this is more often the case with small structures, due to the aggressive re-sampling performed in the pre-processing step. This can be seen in Fig. 2, where for case 0002 the gallbladder and duodenum are missed at every iteration, while large structures such as the liver, stomach and kidneys are accurately segmented. We also observe that the model has difficulties in defining the boundaries of abnormal organs, especially for cases with kidney and and spleen disease. This is depicted in Fig. 2, where for case 0042 a significant portion of the enlarged, diseased right kidney gets classified as liver. One possible reason for these results is that the labelled training set only contains cases with pancreas disease, leading to the generation of noisy pseudo-labels for the cases with other diseases in the training set. Another common mistake we observed was the segmentation of liver lesions as gallbladder. To overcome this issue,

at post-processing all liver-enclosed components segmented as gallbladder are re-classified as liver, as is shown in Fig. 3.

Fig. 2: Segmentation results across model iterations. Clear improvement in segmentation quality are visible for structures like the right kidney (Case 0002), the duodenum (Case 0042) and the left kidney (Case 0006) with the increasing model iterations. However, the model still struggles with the segmentation of small structures (gallbladder and duodenum for Case 0002) and diseased organs (right kidney for Case 0042).

Fig. 3: Effect of post-processing. After iteration 4 the model wrongly segments the liver lesion as gallbladder. This is corrected with the post-processing step.

4.3   Segmentation efficiency results

CPU and RAM usage are shown in Fig. 4, for inference on the full validation set of 50 cases. To keep CPU and RAM usage low, inference is limited to a single CPU thread. The GPU memory usage for a single case is shown in Fig. 5 and is approximately 2.7 GB during inference. There is a short peak of 6 GB for the first predicted patch. About 1.3 GB on our testing machine is allocated by NVIDIA drivers, as is visible in the graph at the end of inference. This means that the model, together with the patches it predicts, takes about 1.4 GB.

Different combination of step size and test-time augmentations were tested to minimize GPU time. The ablation results are shown in Table 5. The minimum GPU time was achieved with a step size of 0.9 and no test-time augmentation, with minimal impact on the final segmentation accuracy. This was the selected configuration for the final model.

Fig. 4: The CPU utilization (left) and RAM (right) over time for a typical inference session.

Table 5: Ablation study for inference step size and test-time augmentation.

Step size	TTA	DSC	GPU time (s)
0.9	no	0.8848	56
0.9	yes	0.8860	102
0.5	no	0.8663	129
0.5	yes	0.8874	284

Fig. 5: The GPU memory usage over time a single case.

4.4   Limitations and future work

Currently, inference is done with the standard nnU-Net framework. This framework is not optimized for low GPU ($<$2GB) and low RAM ($<$28GB) environments. This may be improved with a custom inference pipeline, for example including ONNX runtime.

Apart from inference, the training process is very expensive in terms of GPU compute. This is because every iteration requires 5 models to be trained, each consuming roughly 40 GPU hours. The easiest way to improve this is to train each iteration for fewer epochs than the standard 1000 epochs of nnU-Net. Especially for the earlier model iterations it may not be as crucial to train for many epochs, but this has to be explored.

In this paper, we use the mean pairwise DSC per organ as uncertainty metric and propose a threshold of 0.9. For both of these, alternatives are possible, but have not been explored yet. Especially the threshold is interesting to investigate, as it determines the amount of samples per iteration.

5   Conclusion

This article proposes to use uncertainty to improve the quality of pseudo-labels. Specifically, the mean pairwise DSC per organ, obtained by comparing the output of 5 models, is used to discard unreliable cases for each training iteration. This improves DSC by 4% compared to not using unlabelled data at all and by 2% compared to using all unlabelled data without uncertainty-based selection.

Acknowledgements The authors of this paper declare that the segmentation method they implemented for participation in the FLARE 2022 challenge has not used any pre-trained models nor additional datasets other than those provided by the organizers. The proposed solution is fully automatic without any manual intervention.

References

1. Cheplygina, V., de Bruijne, M., Pluim, J.P.: Not-so-supervised: A survey of semi-supervised, multi-instance, and transfer learning in medical image analysis. Medical Image Analysis **54**, 280–296 (2019). https://doi.org/https://doi.org/10.1016/j.media.2019.03.009, https://www.sciencedirect.com/science/article/pii/S1361841518307588 2

2. Clark, K., Vendt, B., Smith, K., Freymann, J., Kirby, J., Koppel, P., Moore, S., Phillips, S., Maffitt, D., Pringle, M., et al.: The cancer imaging archive (tcia): maintaining and operating a public information repository. Journal of Digital Imaging **26**(6), 1045–1057 (2013) 4

3. Heller, N., Isensee, F., Maier-Hein, K.H., Hou, X., Xie, C., Li, F., Nan, Y., Mu, G., Lin, Z., Han, M., et al.: The state of the art in kidney and kidney tumor segmentation in contrast-enhanced ct imaging: Results of the kits19 challenge. Medical Image Analysis **67**, 101821 (2021) 4

4. Heller, N., McSweeney, S., Peterson, M.T., Peterson, S., Rickman, J., Stai, B., Tejpaul, R., Oestreich, M., Blake, P., Rosenberg, J., et al.: An international challenge to use artificial intelligence to define the state-of-the-art in kidney and kidney tumor segmentation in ct imaging. American Society of Clinical Oncology **38**(6), 626–626 (2020) 4

5. Isensee, F., Jaeger, P.F., Kohl, S.A., Petersen, J., Maier-Hein, K.H.: nnu-net: a self-configuring method for deep learning-based biomedical image segmentation. Nature Methods **18**(2), 203–211 (2021) 1, 2

6. Lakshminarayanan, B., Pritzel, A., Blundell, C.: Simple and scalable predictive uncertainty estimation using deep ensembles. In: Guyon, I., Luxburg, U.V., Bengio, S., Wallach, H., Fergus, R., Vishwanathan, S., Garnett, R. (eds.) Advances in Neural Information Processing Systems. vol. 30. Curran Associates, Inc. (2017), https://proceedings.neurips.cc/paper/2017/file/9ef2ed4b7fd2c810847ffa5fa85bce38-Paper.pdf 2

7. Ma, J., Zhang, Y., Gu, S., Zhu, C., Ge, C., Zhang, Y., An, X., Wang, C., Wang, Q., Liu, X., Cao, S., Zhang, Q., Liu, S., Wang, Y., Li, Y., He, J., Yang, X.: Abdomenct-1k: Is abdominal organ segmentation a solved problem? IEEE Transactions on Pattern Analysis and Machine Intelligence (2021). https://doi.org/10.1109/TPAMI.2021.3100536 4

8. Rizve, M.N., Duarte, K., Rawat, Y.S., Shah, M.: In defense of pseudo-labeling: An uncertainty-aware pseudo-label selection framework for semi-supervised learning. arXiv preprint arXiv:2101.06329 (2021) 2

9. Simpson, A.L., Antonelli, M., Bakas, S., Bilello, M., Farahani, K., Van Ginneken, B., Kopp-Schneider, A., Landman, B.A., Litjens, G., Menze, B., et al.: A large annotated medical image dataset for the development and evaluation of segmentation algorithms. arXiv preprint arXiv:1902.09063 (2019) 4

10. Zhou, Z.H.: A brief introduction to weakly supervised learning. National Science Review **5**(1), 44–53 (08 2017). https://doi.org/10.1093/nsr/nwx106, https://doi.org/10.1093/nsr/nwx106 2