CAN TRANSFORMERS DO ENUMERATIVE GEOMETRY?

ABSTRACT

We introduce a Transformer-based approach to computational enumerative geometry, specifically targeting the computation of ψ-class intersection numbers on the moduli space of curves. Traditional methods for calculating these numbers suffer from factorial computational complexity, making them impractical to use. By reformulating the problem as a continuous optimization task, we compute intersection numbers across a wide value range from 10^{-45} to 10^{45}. To capture the recursive and hierarchical nature inherent in these intersection numbers, we propose the Dynamic Range Activator (DRA), a new activation function that enhances the Transformer's ability to model recursive patterns and handle severe heteroscedasticity. Given precision requirements for computing ψ-class intersections, we quantify the uncertainty of the predictions using Conformal Prediction with a dynamic sliding window adaptive to the partitions of equivalent number of marked points. Beyond simply computing intersection numbers, we explore the enumerative "world-model" of Transformers. Our interpretability analysis reveals that the network is implicitly modeling the Virasoro constraints in a purely data-driven manner. Moreover, through abductive hypothesis testing, probing, and causal inference, we uncover evidence of an emergent internal representation of the the large-genus asymptotic of ψ-class intersection numbers. These findings suggest that the network internalizes the parameters of the asymptotic closed-form formula linearly while capturing the polynomiality phenomenon of ψ-class intersection numbers in a nonlinear manner.

1 INTRODUCTION

Enumerative geometry is a branch of mathematics concerned with counting geometric objects or finding invariants that satisfy certain geometric conditions (Mumford, 1983; Katz, 2006). A classical question in enumerative geometry is: *How many conics pass through five given points in the plane?* A more contemporary one is: *How many rational curves of degree one are there on a quintic threefold?* Addressing such problems often boils down to computing intersection numbers, which are fundamental in computing Weil–Petersson volumes, Hurwitz numbers, Gromov–Witten invariants, and quantum gravity amplitudes. An example of such objects is ψ-class intersection numbers. Traditional recursive methods like the KdV hierarchy (Witten, 1991; Kontsevich, 1992) have computational complexities that grow like $O(g! \cdot 2^n)$ with the g genus and n number of marked points n, making calculations infeasible even for simple curves. To overcome this computational bottleneck, we propose employing Machine Learning (ML), particularly Transformers (Vaswani et al., 2023), to approximate ψ-class intersection numbers.

It is well known that Transformer-based models have difficulty with even periodic patterns, let alone recursive problems (Ziyin et al., 2020). Therefore, we first examine the architectural design choices and training pipeline variants necessary for learning the recursive reasoning processes involved in topological recursion (Eynard & Orantin, 2007). Hence, we introduce a non-linear activation function, the Dynamic Range Activator (DRA), which is particularly suited for learning recursive functions. Consequently, we develop DynamicFormer, a modified Transformer-based model designed to predict ψ-class intersection numbers given the quantum Airy structure (Kontsevich & Soibelman, 2018) initial data. Additionally, we believe that a predictive model without uncertainty estimation is inherently unreliable. Therefore, we incorporate uncertainty quantification into our model's predictions using Conformal Prediction (Shafer & Vovk, 2008).

Going further, we investigate whether the network is capable of abductive reasoning for knowledge discovery. Specifically, we ask whether we can conduct parametric inference and extract mathematical insights from its internal understanding beyond the raw data provided to offer intuition and potentially generate new conjectures. We provide causal and correlational evidence that the network is actually understanding the underlying mathematics. As a result, we aim to introduce a new paradigm for using Transformers in algebraic geometry as both a powerful and explainable amortization method and a source of intuition for the mathematician.

1.1 RELATED WORKS

In recent years, a new frontier of ML applications, known as Artificial Intelligence (AI) for Mathematics (He et al., 2023), has emerged. This branch includes Automated Theorem Proving (Loos et al., 2017; Paliwal et al., 2020; An et al., 2024), Generation (Trinh et al., 2024; Wang & Deng, 2020; Lin et al., 2024), Autoformalization (Wang et al., 2020; Wu et al., 2022; Jiang et al., 2023; Mikuła et al., 2024; Ying et al., 2024), machine-human collaborative guidance (Bao et al., 2020; Anderson et al., 2021; Davies et al., 2021; Berman et al., 2022; Craven et al., 2023; Coates et al., 2023; Dong et al., 2024), examples/counterexamples search problems (Halverson et al., 2019; Gukov et al., 2021; Wagner, 2021; Gukov et al., 2023; Berglund et al., 2024; Romera-Paredes et al., 2024), and predictive problems (such as amplitude and mathematical expression prediction) (Saxton et al., 2019; Dersy et al., 2023; Alnuqaydan et al., 2023; d'Ascoli et al., 2022; Cai et al., 2024; Coates et al., 2024). These areas extensively use Transformers, particularly in problems arising from particle interactions and scattering processes. While these studies primarily focus on symbolic logic or compact numerical sequences, they fall short in handling the highly complex structures found in enumerative geometry. Existing models are limited to in-distribution settings and struggle with the high-variance and recursive nature of problems in computational algebraic geometry.

Our work bridges the domains of machine-human collaborative guidance and predictive problems while introducing new methods. In the prediction task, while most studies remain within in-distribution and compact settings, we extend our approach to out-of-distribution predictions, coupled with Conformal Prediction uncertainty estimation—a notably absent requirement in current literature. Precision is essential in mathematics, especially when a mathematician needs to assess whether an informed conjecture is correct based on available samples. In such decision-making processes, having access to the uncertainty of AI-predicted samples/values is crucial, as it provides insight into the reliability of the predictions and guides the validation of mathematical hypotheses. We also enhance the predictive task by using multi-modal data, involving both discrete sets and continuous graph (sequence) representations. This approach moves beyond the focus on mere compact symbolic/numerical sequence modalities (Meidani et al., 2024). Furthermore, in the field of machine-human collaborative guidance, we conduct causal inference and correlational analyses to understand the mathematical "world-model" of Transformers (Li et al., 2023; Micheli et al., 2023), offering deep insights into the underlying algebraic geometry problem at hand. To the best of our knowledge, this is the first time Transformers and explainable Machine Learning have been applied to enumerative problems in algebraic geometry, to extract knowledge and illuminate the model's internal understanding of deep research-level mathematical concepts. In the end, we aim to target both machine learning scientists and mathematicians, as our work is relevant to both communities.

2 QUANTUM AIRY STRUCTURES

The conceptually simplest approach to computing ψ-class intersection numbers involves using Virasoro constraints recast in the language of quantum Airy structures (Kontsevich & Soibelman, 2018). The latter is an algebraic reformulation of topological recursion (Eynard & Orantin, 2007). A quantum Airy structure on a complex vector space V, dually generated by $(x^i)_{i \in I}$, is a family of differential operators $(L_i)_{i \in I}$ in the Weyl algebra over V of the form

$$L_i = \hbar \partial_i - \hbar^2 \sum_{a,b \in I} \left(\frac{1}{2} A_{i,a,b} \, x^a x^b + B_{i,a}^b \, x^a \partial_b + \frac{1}{2} C_i^{a,b} \, \partial_a \partial_b \right) - \hbar^2 D_i \,, \qquad (2.1)$$

and forming a Lie sub-algebra of the Weyl algebra, where $\partial_i = \partial_{x^i}$ and $A_{i,a,b} = A_{i,b,a}$, $B_{i,a}^b$, $C_i^{a,b} = C_i^{b,a}$, and D_i, are scalars indexed by elements in I. $\hbar$ is a formal parameter that keeps track

of the genus. Given a quantum Airy structure, one can uniquely find a formal function Z on V, called *partition function*, which is annihilated by the differential operators $(L_i)_{i \in I}$. More precisely, the following theorem holds.

Theorem 2.1. *If $(L_i)_{i \in I}$ is a quantum Airy structure on V, there exists a unique formal function Z of the form*

$$Z(\boldsymbol{x}; \hbar) = \exp\left(\sum_{\substack{g \geq 0 \\ n > 0}} \frac{\hbar^{2g-2+n}}{n!} \sum_{d_1, \ldots, d_n \in I} F_{g; d_1, \ldots, d_n}\, x^{d_1} \cdots x^{d_n} \right) \tag{2.2}$$

with $F_{0;d_1} = F_{0;d_1,d_2} = 0$, $F_{g;d_1,\ldots,d_n}$ symmetric in $d_1, \ldots, d_n \in I$, and such that

$$L_i Z = 0 \qquad \forall i \in I. \tag{2.3}$$

The elements $F_{g,n} = \sum_{d_1,\ldots,d_n \in I} F_{g;d_1,\ldots,d_n}\, x^{d_1} \cdots x^{d_n}$ are symmetric tensors of rank n over V^*. The collection of coefficients (A, B, C, D) can also be regarded as tensors, and we will often refer to them as the quantum Airy structure initial data. For a given quantum Airy structure, the coefficients $F_{g;d_1,\ldots,d_n}$, called *quantum Airy structure amplitudes*, are determined recursively on (minus) the Euler characteristic $2g - 2 + n$. For the lowest values of g and n, the base cases are given by $F_{0;i,j,k} := A_{i,j,k}$ and $F_{1;i} := D_i$, where $A_{i,j,k}$ and D_i are part of the data of the quantum Airy structure. For higher values of g and n satisfying $2g - 2 + n > 0$, the recursion formula, known as *topological recursion*, is given by

$$F_{g;d_1,d_2,\ldots,d_n} = \sum_{m=2}^{n} \sum_{a \in I} B_{d_1,d_m}^{a} F_{g;a,d_2,\ldots,\widehat{d_m},\ldots,d_n}$$

$$+ \frac{1}{2} \sum_{a,b \in I} C_{d_1}^{a,b} \left(F_{g-1;a,b,d_2,\ldots,d_n} + \sum_{\substack{g_1+g_2=g \\ I_1 \sqcup I_2 = \{d_2,\ldots,d_n\}}} F_{g_1;a,I_1}\, F_{g_2;b,I_2} \right). \tag{2.4}$$

In general, the computation of the amplitudes has a computational complexity of $O(g! \cdot 2^n)$, which makes the calculation of the amplitudes at high genera problematic. For high-dimensional vector spaces V, finding a closed-form solution becomes increasingly impractical, if not impossible. The central example is the one associated to the ψ-class intersection numbers. In this case, the underlying vector space is generated by vectors indexed by $I = \mathbb{N}$, the non-negative integers. The differential operators $(L_i)_{i \geq 0}$ are determined by the tensors

$$A_{i,j,k} := \delta_{i,j,k}, \qquad\qquad B_{i,j}^{k} := \delta_{i+j,k+1} \frac{(2k+1)!!}{(2i+1)!!(2j-1)!!},$$

$$C_i^{j,k} := \delta_{i,j+k+2} \frac{(2j+1)!!(2k+1)!!}{(2i+1)!!}, \qquad\qquad D_i := \frac{\delta_{i,1}}{24}. \tag{2.5}$$

The resulting operators, after shifting of the indices as $\mathsf{L}_i = L_{i-1}$, form a representation of the Virasoro algebra: $[\mathsf{L}_i, \mathsf{L}_j] = \hbar^2(i-j)\mathsf{L}_{i+j}$ for all $i \geq -1$. Remarkably, the associated amplitudes coincide with ψ-class intersection numbers:

$$F_{g;d_1,\ldots,d_n} = \begin{cases} \langle \tau_{d_1} \cdots \tau_{d_n} \rangle_{g,n} & \text{if } d_1 + \cdots + d_n = d_{g,n}, \\ 0 & \text{otherwise.} \end{cases} \tag{2.6}$$

In this paper, we focus on the specific choice of quantum Airy structure data given by Equation (2.5), thereby computing the ψ-class intersection numbers. For ease of notation, we will denote a generic partition of $d_{g,n}$ of length n as $\boldsymbol{d} = (d_1, \ldots, d_n)$. The associated ψ-class intersection number will be denoted by $\langle \boldsymbol{d} \rangle_{g,n} := \langle \tau_{d_1} \cdots \tau_{d_n} \rangle_{g,n}$.

The goal of the next sections is to provide the possibility of regressing these numbers via a Transformer-based model, given the quantum Airy structure initial data. Our model is trained on known data computed by a brute force algorithm up to genus 13 and is tested up to genus 17. During experimentation, we observed that when comparing the contributions of B and C, the B tensor had a greater impact on ψ-class intersection numbers. Consequently, we incorporated only this initial datum (excluding C), a decision further supported by the inherent properties of the intersection numbers (see Appendix B). This initial observation motivated the subsequent series of explainability analysis experiments and findings.

3 METHODS

The recursive nature of functions in enumerative geometry, combined with the high-variance target distributions of ψ-class intersection numbers, introduces a high complexity in modeling and accurately approximating these functions. A main property of recursive maps (e.g factorial function), is their rapid growth. Learning this recursive behavior requires not only fitting high-frequency patterns within a bounded region but also successfully extrapolating those patterns beyond that region.

In time series prediction tasks, capturing periodic behavior is also a challenge. Various methods (Miller et al., 2024) have been employed to model such periodic patterns effectively. However, these approaches typically deal with uni-modal data that also exhibit relatively low variance in both In-Distribution (ID) and Out-Of-Distribution (OOD) regions and may not generalize well to datasets with the high variance observed in our context. Therefore, traditional methods for modeling high-variance recursive data, including those used in time series analysis and standard Transformer architectures, are insufficient for our needs (Lakretz et al., 2021; Zhang et al., 2024). Thus, to capture such behavior and perform proper inference for multi-modal recursive problems, we enhance Transformers and introduce DynamicFormer, depicted in Figure 5. In doing so we try to introduce minimal computational overhead that can seamlessly be integrated into existing neral networks without the need for significant architectural changes.

Dynamic Range Activator. It has been shown (Parascandolo et al., 2017; Dauphin et al., 2017; Ziyin et al., 2020; So et al., 2021) that the choice of activation functions plays an important role in the interpolation and extrapolation properties of Transformers. To enable Transformer models to precisely capture the recursive behavior of the data, we introduce a simple activation function that we call the Dynamic Range Activator (DRA). DRA integrates both harmonic and hyperbolic components as follows,

$$\mathrm{DRA}(x) \coloneqq x + a \sin^2 \left(\frac{x}{b} \right) + c \cos(bx) + d \tanh(bx) \,, \tag{3.1}$$

where a, b, c, d are learnable parameters. It allows the function to simultaneously model periodic data (through sine and cosine) and rapid growth or attenuation (through the hyperbolic tangent) response. DRA is inspired by the Snake non-linear function (Ziyin et al., 2020). However, Snake only offers a sinusoidal modulation added to a linear term, which, while providing a basic non-linear transformation, lacks the additional flexibility for rapid damping or amplification effects that hyperbolic tangents can provide.

To demonstrate the advantage of DRA in capturing recursive behavior, we set up a small experiment. We generate a small dataset based on the recursive function $r(n) = n + (n, \mathrm{AND}, r(n-1))$, where AND is the bitwise logical AND operator (Sloane, 2007). We train a fully connected neural network with two hidden layers consisting of 64 and 32 neurons over the interval $n \in [0, 120]$, then test the model over $n \in [121, 200]$. we also provide a comparison between MLP and the vanilla Kolmogorov-Arnold Networks (KAN) (Liu et al., 2024). The results are shown in Figure 1.

This experiment demonstrates that ReLU, Tanh, Gated Linear Unit (GLU) (So et al., 2021), and KAN are unable to capture the recursive nature of the underlying function within a finite training time. Snake appears to learn some periodicity in both the training and testing regions. In contrast, DRA shows a better ability to capture the correct fluctuations, as well as the rapid growth and drops of the underlying recursive function, in both the interpolation and extrapolation regimes. This provides evidence that DRA has the desired flexibility for modeling recursive behavior and has the potential to effectively model such problems. We further conduct experiments, in Section 4, to demonstrate the advantages of DRA over typical non-linear activation functions in predicting ψ-class intersection numbers.

4 RESULTS

To evaluate the performance, we consider two setups: In-Distribution (ID) and Out-Of-Distribution (OOD) settings. We use R^2 to compare the results and assess the goodness-of-fit in the intersection number regression task. We then compare DRA with ReLU, Snake, and GLU activation functions as baselines.

Figure 1: Comparison of DRA with Snake, ReLU, Tanh, and GLU non-linear activation functions, and KAN in training region $n \in [0, 120]$ and test (extrapolative) region $n \in [121, 200]$. We ensured that all models have a comparable number of parameters. The MLP with DRA non-linearity demonstrates superior performance in capturing the function's behavior.

4.1 IN-DISTRIBUTION RESULTS

In the ID setting, we examine data with the same genera as the training data, that is $g_{\text{ID}} = [1, 13]$, but with different, unseen numbers of marked points $n_{\text{ID}} \in [35, 11]$. In this setting, the R^2, the empirical coverage, and the conformal width (CW) (see Appendix E) are shown in Table 1a.

4.2 OUT-OF-DISTRIBUTION RESULTS

Now, we study the more challenging task of OOD prediction. In the OOD setting, we examine data with a higher genera than the training data, specifically $g_{\text{OOD}} = [14, 15, 16, 17]$, and a number of marked points $n_{\text{OOD}} \in [1, 9]$. In this setting, the R^2, the empirical coverage, and the conformal width are shown in Table 1b. As evidenced by Table 2, the DRA outperforms the ReLU, GLU, and Snake activation functions in predicting the recursive intersection numbers in the OOD setting.

5 HOW DOES THE NETWORK DO ENUMERATIVE GEOMETRY?

Up until now, we have tried to showcase that DynamicFormer is capable of predicting ψ-class intersection numbers. However, several key questions remain. *Do Transformers actually understand the underlying enumerative geometry? Is it possible to extract useful knowledge or hints toward a possible (re)discovery of a theorem?* To address these questions, we have made several interesting

(g,n)	$R^2 \uparrow$	Coverage	CW
$(1, 35)$	99.8	90.35	1.03
$(2, 33)$	99.6	83.60	0.84
$(3, 31)$	99.9	74.79	0.76
$(4, 29)$	98.7	95.66	1.11
$(5, 27)$	99.1	92.66	1.03
$(6, 25)$	99.3	91.18	0.80
$(7, 23)$	99.1	93.05	0.68
$(8, 21)$	99.8	90.88	0.76
$(9, 19)$	99.9	96.71	0.91
$(10, 17)$	99.9	90.01	1.04
$(11, 15)$	99.8	91.97	0.87
$(12, 13)$	99.6	89.08	1.30
$(13, 11)$	99.9	95.90	0.97

(a) R^2 and conformal uncertainty estimation results with $\alpha = 0.1$ (90% target coverage) in the ID setting.

(g,n)	$R^2 \uparrow$	Coverage	CW
$(14, [1, 9])$	99.6	93.82	0.93
$(15, [1, 7])$	95.9	84.27	0.91
$(16, [1, 5])$	94.1	89.60	3.55
$(17, [1, 3])$	93.8	95.27	8.30

(b) R^2 and conformal uncertainty estimation results with $\alpha = 0.1$ (90% target coverage) in the OOD setting.

ReLU		GLU		Snake		DRA	
$R^2 \uparrow$	CW $\downarrow$	$R^2 \uparrow$	CW $\downarrow$	$R^2 \uparrow$	CW $\downarrow$	$R^2 \uparrow$	CW $\downarrow$
71.5	9.73	74.7	8.34	82.9	6.55	**95.8**	**3.42**

Table 2: Comparison of R^2 and Conformal Width between models with ReLU, GLU, Snake, and DRA as their activation functions in the OOD regime.

observations throughout our work that offer deeper insights into the network's "world model" and learning process, hinting at potential mathematical knowledge discovery.

5.1 THE DILATON EQUATION

The topological recursion equation 2.4 for the specific case of ψ-class intersection numbers and the choice of $d_1 = 1$ takes a particularly simple form, known as the Dilaton equation,

$$\langle 1, d_1, \ldots, d_n \rangle_{g,n+1} = (2g - 2 + n)\langle d_1, \ldots, d_n \rangle_{g,n} . \tag{5.1}$$

The equation states that the intersection number involving a τ_1-term can be reduced to a simpler intersection number with one fewer marked point.

Let $\langle \boldsymbol{d} \rangle_{g,n}$ be the intersection numbers indexed by genus g and number of marked points n. Given the the set of values of the tensor $\boldsymbol{B}$ and the set of partitions $\boldsymbol{d} \in \mathbb{N}^n$, the neural network embedding $p_{g,n}\colon \{ \mathbb{R}^{d_{g,n} \times d_{g,n} \times d_{g,n}}, \mathbb{N}^n \} \to \mathbb{R}^k$ maps the input data to a k dimensional vector space $\mathbb{R}^k$ denoted as $\mathbf{x}_{g,n}(\langle \boldsymbol{d} \rangle_{g,n} \mid \boldsymbol{B}, \boldsymbol{d})$. This embedding describes the hidden understanding of the Transformer just before the prediction head, capturing the learned representation of the intersection numbers. By equipping $\mathbb{R}^k$ with the standard inner product, $S_{i,j}\colon \mathbb{R}^k \times \mathbb{R}^k \to \mathbb{R}$, we obtain the cosine of the angle between the normalized embeddings of ψ-class intersection numbers as a measure of geometric similarity:

$$S_{i,j} = \frac{\langle x_{g,n}^i, x_{g,n}^j \rangle}{\|x_{g,n}^i\| \, \|x_{g,n}^j\|} . \tag{5.2}$$

Observing an interesting recursive pattern in Figure 2, we hypothesize that they stem from the Virasoro constraints between intersection numbers. To verify this, we visualized the Dilaton equations and confirmed that the model has rediscovered it as relationships between intersection numbers. We translated the Dilaton equation into a Dilaton relation matrix by flagging any two intersection numbers that satisfy this equation. We then observed that the intersection numbers with high cosine similarity follow at least the Dilaton equation. We anticipate that other observed patterns may also be manifestations of the remaining Virasoro constraints. This phenomenon persists even in the OOD setting. This explains how the model has succeeded in generalizing well by learning the underlying symmetries and relations. It provides evidence that the network has learned the Virasoro constraints in a data-driven way without prior exposure to these governing rules.

Figure 2: The Dilaton relations matrix (left) between ψ-classes intersection numbers for $g = 13$ (top) and $g = 14$ (bottom). Cosine similarity between embeddings of predicted intersection numbers (right) and between embeddings of predicted intersection numbers with a cut $S_{i,j} \geq 0.98$ (middle).

5.1.1 LARGE GENUS ASYMPTOTIC AND ABDUCTIVE REASONING

Delecroix et al. (2021) conjectured that, in the large genus limit, ψ-class intersection numbers simplify to a specific asymptotic form.

Theorem 5.1. *For $n = o(\sqrt{g})$, uniformly in $d_1, \ldots, d_n$ as $g \to +\infty$:*

$$\langle \boldsymbol{d} \rangle_{g,n} \prod_{i=1}^{n} (2d_i + 1)!! = \frac{2^n}{4\pi} \frac{\Gamma(2g - 2 + n)}{(\frac{2}{3})^{2g-2+n}} \big(1 + o(1)\big). \tag{5.3}$$

Here $\Gamma(x)$ is the Euler Gamma function.

This theorem, proven by Aggarwal (2021), illustrates that, as the genus g grows large, the intersection numbers grow factorially as $(2g)!$, with a specific exponential behavior modulated by the constant $A = 2/3$. Recently, another approach for computing the large-genus asymptotics of intersection numbers was proposed by Eynard et al. (2023). The strategy of this proof is based on a resurgent analysis of the n-point functions of ψ-class intersection numbers, which are computed via determinantal formulae. The determinantal formula is a consequence of the integrability property of the intersection numbers, namely KdV. With this approach, the authors extended Aggarwal's results by computing all subleading corrections:

$$\langle \boldsymbol{d} \rangle_{g,n} \prod_{i=1}^{n} (2d_i + 1)!! = \frac{2^n}{4\pi} \frac{\Gamma(2g - 2 + n)}{(\frac{2}{3})^{2g-2+n}} \left(1 + \frac{\frac{2}{3}\alpha_1}{2g - 3 + n} + \cdots\right). \tag{5.4}$$

Abductive Reasoning: Identifying components and parameters such as $A = 2/3$ or the subleading corrections in Equation (5.4) can also be approached through abductive reasoning, framing the task as hypothesis testing. Abduction involves proposing plausible explanations for observed data, to determine which best aligns with the network's understanding of the data. In this context, we investigate how the network can infer the parameters like the constant $A = 2/3$ in the asymptotic formula, treating it as an inverse problem. Thus, an important question we want to answer is: *In scenarios where parameters in asymptotic formulas are unknown, can we use abduction to infer*

and provide evidence for their potential values? To address this, we first examine the reasoning of DynamicFormer by deciphering its understanding of the asymptotic parameters of the intersection numbers, which are not explicitly provided to the model. The parameters we aim to infer and rediscover are:

- The exponential growth A.

- The first few subleading asymptotic polynomials $\alpha_1, \alpha_2, \ldots$ (Guo & Yang, 2022; Eynard et al., 2023).

One can claim that there is evidence that the model's embedding vector space $p_{g,n}(\langle \boldsymbol{d} \rangle_{g,n} | \boldsymbol{B}, \boldsymbol{d})$ encodes the parameter $A = 2/3$ and the subleading polynomials if there is a correspondence between the embeddings and these parameters. A prominent method that attempts to shed light on this correspondence is *probing* (Conneau et al., 2018), also known as diagnostic prediction (Hupkes et al., 2020). Under this methodology, one trains a linear or non-linear model as a probe to predict any desired information from the latent representations of the network. Formally, we aim to evaluate how well the network's hidden representations encode the fundamental parameter A by predicting the target function I_j associated with each input j. Let $\mathbf{x}_{g,n}^j \in \mathbb{R}^k$ be the hidden state for input j, and I_j be defined based on approximate conjectural estimation of Equation (5.4). To map the hidden representations $\mathbf{x}_{g,n}^j$ to the target values I_j, we employ both linear and non-linear (MLP) probes f. The probe f is trained, using a conformal prediction procedure (Shafer & Vovk, 2008) to quantify the statistical uncertainty, by minimizing the squared error between the predicted and actual values of I_j, $f = \arg\min_\theta \sum_j \left(f_\theta \left(\mathbf{x}_{g,n}^j \right) - I_j \right)^2$. High prediction performance is interpreted as evidence that the information is encoded in the Transformer's enumerative world model. The efficacy of the encoding is gauged by the coefficient of determination (R^2) of the probe.

For $A = 2/3$, we set up the experiment with a grid of alternative hypotheses. Specifically, we probe a discrete value space for the numerator of A, $\text{num} = 1, \ldots, 10$, and the denominator, $\text{denom} = 1, \ldots, 10$, which covers 90 candidates (with $A = 1$ excluded as a trivial hypothesis). It is expected geometrically that A would a period on the associated Riemann Surface. For this specific enumerative problem, periods are in $\mathbb{Q}$, associated to the Wentzel–Kramers–Brillouin (WKB) method applied to the underlying Airy quantum curve. We use both linear and non-linear probes to see if the network's internal representation for $A = 2/3$ has a linear form or not. The higher and more precise performance of the non-linear probe to the linear one suggests that A could be encoded non-linearly, as shown in Figure 3

Figure 3: The network's internal representation's linear (left) and non-linear (right) predictive power of the exponential growth constant of ψ-class intersection numbers.

We perform the same analysis for the first few terms of the subleading series α_k with $k = 0, 1, 2, 3$. We found that with 90% coverage, the Transformer's vector space representation can predict the coefficients with an $R^2 = 0.98$. Notably, the linear probe yields yields a lower value $R^2 = 0.63$. **This suggests that the network's internal representation of the polynomiality phenomenon (Guo &**

Yang, 2022; Eynard et al., 2023) does not have a simple linear form, but a non-linear representation.

Causal Tracing: Originally, causal tracing (Vig et al., 2020) was introduced to quantify the storage and transfer of information within the intermediate components of Transformers (Meng et al., 2022; Feng & Steinhardt, 2024; Wang et al., 2024), which is not our focus here. We seek to use causal tracing to understand the model's decision-making process, specifically identifying which input modalities are more influential when predicting the intersection of ψ-classes. In other words, we want to uncover how the network causally comprehends the underlying mathematics. We will refer to an input modality as $m[i] = \{\, n[i], \boldsymbol{B}[i], \boldsymbol{d}[i] \,\}$ for each input instance i. There are then two steps:

1. **Clean run.** This run records the model's prediction on a regular input. With this run, we record auto-correlation of the predicted intersection numbers across different number of marked points.

2. **Counter-factual intervention.** We perform counterfactual interventions (Baron, 2023) by modifying instances in one modality while keeping others unchanged to observe how these changes affect the model's predictions. This involves incorrectly assigning features to instances—for example, associating the partition $\boldsymbol{d} = (29, 10, 5, 3, 1, 0)$ with $n = 3$ instead of $n = 6$. Previous research on factual associations in Transformers has explored methods such as adding noise to inputs (Meng et al., 2022), which creates redundant distribution shifts (Zhang & Nanda, 2024), and exchanging tokens (Feng & Steinhardt, 2024). Our approach is similar to the latter method, focusing on how changes in input tokens affect model predictions. In our case, for the modality of interest (while keeping the other modalities intact), we replace the input instances with random alternatives of the same genus. This replacement results in a miss-assignment of features to a sample, which alters the target prediction, i.e., $m[i] \to m[j]$ where $i \neq j$, to obtain $\mathbf{x}_{g,n}(\langle \boldsymbol{d} \rangle_{g,n} | \text{do}(m[i]))$. This allows us to study how the model relates features to instances and to attribute cause and effect between interventions and the intersections. The difference observed between the clean and intervened runs is measured by R^2, the autocorrelation of the intersection numbers, and the $\mathrm{R}^2_{\text{probe}}$ of the linear probe for the exponential growth constant $A = 2/3$.

	No Intervention	n	$\boldsymbol{B}$	$\boldsymbol{d}$
R^2	0.96	-12.6	0.54	-52.2
$\mathrm{R}^2_{\text{probe}}$	0.83	0.52	-2.77	0.43

Table 3: Causal Strength for Different Modalities

Figure 4: Autocorrelation plot across different number of marked points n for clean (leftmost) and intervened runs (from left to right) for n, $\boldsymbol{B}$, and $\boldsymbol{d}$ respectively.

What causal reasoning is the model learning? R^2 of the intersection of ψ-classes is heavily affected when using counter-factual instances for the number of marked points n and partitions $\boldsymbol{d}$. This indicates a strong causal connection between the partitions and the intersection numbers. This is also evident from the autocorrelation plot Figure 4, where the correlation between the intersection numbers is completely lost after disrupting the binding between instances and their partitions. The presence of such a strong causal relationship for n and $\boldsymbol{d}$ is not surprising, but their mild impact on $\mathrm{R}^2_{\text{probe}}$ is an interesting discovery. Despite a weak causal connection between $\boldsymbol{B}$ and the predicted intersection numbers, there is an evidence that *the exponential growth constant, $A = 2/3$, is causally connected to the quantum Airy structure initial datum $\boldsymbol{B}$*. This suggests that the network's hidden

states of the B initial datum encodes this parameter. Meanwhile, the weak causal impact of B on the intersection numbers results in only a mild effect on their autocorrelation. This is expected since B contributes linearly, shown in Equation (2.4), while the dependence in n and d are factorial.

6 CONCLUSION

In this work, we tried to address a fundamental question: *Can Transformers perform and learn enumerative geometry and topological recursion?* To answer, we investigated a deep enumerative problem in algebraic geometry, specifically the computation of ψ-class intersection numbers. As a result, we introduced DynamicFormer, a multi-modal Transformer-based model, to predict the ψ-class intersection numbers. We analyzed the ability of the network to tackle such a task in a zero-shot setting. Capturing the recursive behavior of intersections poses a non-trivial challenge for Transformers. Throughout our experiments, we identified the crucial role of non-linear activation functions and introduced a new activation function, Dynamic Range Activator (DRA), which improves prediction precision of recursive maps. One of the messages of this works is also that simply predicting or classifying a mathematical object with ML is not sufficient. A prediction without proper uncertainty estimation is not reliable, especially in mathematics. Here, we aimed to enhance reliability by incorporating conformal uncertainty estimation and explainability for knowledge discovery.

In the second part of the results, we asked a simple question: *How exactly does the network perform enumerative geometry?* To answer this, we conducted a series of correlational, conformal, and causal interoperability analyses. Firstly, by examining the internal vector space of the model, we discovered that the network is learning Virasoro constraints without being imposed on the model. This finding is intriguing because it suggests that in cases where such relations and equations are not known but are suspected to exist, a pre-trained Transformer could potentially aid in a human-machine collaboration by providing hints and evidence for these relations in a purely data-driven manner.

We further explored whether it is possible to perform some form of abductive reasoning and hypothesis testing to estimate the parameters of asymptotic form for intersection numbers. Often, there is an expectation for such asymptotic growths that leads to a process of conjecture building and deductive reasoning to derive the final formula. In this work, we advocate that by using the network's internal understanding of the data, one can provide informed guesses and even reject alternative hypotheses about candidate parameters. To achieve this, we conducted a grid search on the exponential growth constant of the asymptotic limit for ψ-class intersection numbers, based on the network's hidden representation. Using probing techniques, we showed that this information is encoded linearly in the model's internal representation. We also performed the same analysis on the first few terms of the subleading polynomial terms. We found that these subleading terms are encoded in a non-linear manner in the model's hidden space.

In the end, we analyzed the internal decision-making procedure of DynamicFormer using causal inference. By applying the causal tracing method with counterfactual interventions, we aimed to shed light on how various input modalities—namely, the partitions, quantum Airy structure, and number of marked points—are causally responsible for the model's understanding of the intersection numbers of ψ-classes and the parameters for large genus.

An interesting open question to explore with interpretability methods developed here, is the regime when $(n, g) \to \infty$ at the same time (so that g/n is kept bounded above and below). At the moment, there is not even a conjecture as to what the asymptotic should behave like, and how it should depend on the partitions.

Another fascinating avenue for future research is to explore recent developments in intersection numbers (Eynard & Mitsios, 2023). This new approach proposes a formula that involves sums over partitions of combinatorial factors and reveals that certain partitions with specific conditions have vanishing coefficients in their decomposition into elementary symmetric polynomials. Remarkably, empirical observations suggest that even more partitions have vanishing coefficients than the trivial ones. This unexpected result points to a deeper, hidden structure in intersection numbers, where the internal representation of the network could be very beneficial in examining these new results and uncovering the underlying patterns.

REFERENCES

Hervé Abdi, Vincent Guillemot, Aida Eslami, and Derek Beaton. *Canonical Correlation Analysis*. Springer New York, New York, NY, 2018. doi: 10.1007/978-1-4939-7131-2_110191.

Amol Aggarwal. Large genus asymptotics for intersection numbers and principal strata volumes of quadratic differentials. *Invent. Math.*, 226(3):897–1010, 2021. doi: 10.1007/s00222-021-01059-9.

Alexander Alexandrov. Cut-and-join operator representation for Kontsevich–Witten tau-function. *Mod. Phys. Lett. A*, 26(29):2193–2199, 2011. doi: 10.1142/S0217732311036607.

Abdulhakim Alnuqaydan, Sergei Gleyzer, and Harrison Prosper. SYMBA: symbolic computation of squared amplitudes in high energy physics with machine learning. *Mach. Learn.: Sci. Technol.*, 4 (1):015007, 2023.

Chenyang An, Zhibo Chen, Qihao Ye, Emily First, Letian Peng, Jiayun Zhang, Zihan Wang, Sorin Lerner, and Jingbo Shang. Learn from failure: Fine-tuning LLMs with trial-and-error data for intuitionistic propositional logic proving. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 776–790, Bangkok, Thailand, August 2024. Association for Computational Linguistics.

Jørgen Ellegaard Andersen, Gaëtan Borot, Séverin Charbonnier, Vincent Delecroix, Alessandro Giacchetto, Danilo Lewański, and Campbell Wheeler. Topological recursion for Masur–Veech volumes. *J. Lond. Math. Soc.*, 107(1):254–332, 2023. doi: 10.1112/jlms.12686.

Lara B. Anderson, Mathis Gerdes, James Gray, Sven Krippendorf, Nikhil Raghuram, and Fabian Ruehle. Moduli-dependent Calabi–Yau and SU(3)-structure metrics from Machine Learning. *J. High Energy Phys.*, 2021(5):1–45, 2021. doi: 10.1007/JHEP05(2021)013.

Randall Balestriero, Mark Ibrahim, Vlad Sobal, Ari Morcos, Shashank Shekhar, Tom Goldstein, Florian Bordes, Adrien Bardes, Gregoire Mialon, Yuandong Tian, Avi Schwarzschild, Andrew Gordon Wilson, Jonas Geiping, Quentin Garrido, Pierre Fernandez, Amir Bar, Hamed Pirsiavash, Yann LeCun, and Micah Goldblum. A cookbook of self-supervised learning, 2023.

Jiakang Bao, Sebastián Franco, Yang-Hui He, Edward Hirst, Gregg Musiker, and Yan Xiao. Quiver mutations, Seiberg duality, and machine learning. *Phys. Rev. D*, 102(8):086013, 2020. doi: 10.1103/PhysRevD.102.086013.

Sam Baron. Explainable ai and causal understanding: Counterfactual approaches considered. *Minds Mach.*, 33(2):347–377, 2023. doi: 10.1007/s11023-023-09637-x.

Kai Behrend. Gromov–witten invariants in algebraic geometry. *Invent. Math.*, 127(3):601–617, 1997. doi: 10.1007/s002220050132.

Michel Bergère and Bertrand Eynard. Determinantal formulae and loop equations, 2009.

Per Berglund, Giorgi Butbaia, Yang-Hui He, Elli Heyes, Edward Hirst, and Vishnu Jejjala. Generating triangulations and fibrations with reinforcement learning, 2024.

David S. Berman, Yang-Hui He, and Edward Hirst. Machine learning Calabi–Yau hypersurfaces. *Phys. Rev. D*, 105(6):066002, 2022. doi: 10.1103/PhysRevD.105.066002.

Tianji Cai, Garrett W. Merz, François Charton, Niklas Nolte, Matthias Wilhelm, Kyle Cranmer, and Lance J. Dixon. Transforming the bootstrap: Using transformers to compute scattering amplitudes in planar $\mathcal{N}=4$ super Yang–Mills theory, 2024.

Tom Coates, Alexander M Kasprzyk, and Sara Veneziale. Machine learning the dimension of a fano variety. *Nature Communications*, 14(1):5526, 2023.

Tom Coates, Alexander Kasprzyk, and Sara Veneziale. Machine learning detects terminal singularities. *Advances in Neural Information Processing Systems*, 36, 2024.

Alexis Conneau, German Kruszewski, Guillaume Lample, Loïc Barrault, and Marco Baroni. What you can cram into a single $&!#* vector: Probing sentence embeddings for linguistic properties. In Iryna Gurevych and Yusuke Miyao (eds.), *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 2126–2136, Melbourne, Australia, July 2018. Association for Computational Linguistics. doi: 10.18653/v1/P18-1198.

Gabriele Corso, Luca Cavalleri, Dominique Beaini, Pietro Liò, and Petar Veličković. Principal neighbourhood aggregation for graph nets, 2020.

Jessica Craven, Mark Hughes, Vishnu Jejjala, and Arjun Kar. Learning knot invariants across dimensions. *SciPost Phys.*, 14(2):021, 2023. doi: 10.21468/SciPostPhys.14.2.021.

Timothée Darcet, Maxime Oquab, Julien Mairal, and Piotr Bojanowski. Vision transformers need registers. In *The Twelfth International Conference on Learning Representations*, 2024.

Stéphane d'Ascoli, Pierre-Alexandre Kamienny, Guillaume Lample, and François Charton. Deep symbolic regression for recurrent sequences, 2022.

Yann N Dauphin, Angela Fan, Michael Auli, and David Grangier. Language modeling with gated convolutional networks. In *34th International Conference on Machine Learning*, pp. 933–941. PMLR, 2017.

Alex Davies, Petar Veličković, Lars Buesing, Sam Blackwell, Daniel Zheng, Nenad Tomašev, Richard Tanburn, Peter Battaglia, Charles Blundell, András Juhász, et al. Advancing mathematics by guiding human intuition with AI. *Nature*, 600(7887):70–74, 2021. doi: 10.1038/s41586-021-04086-x.

Vincent Delecroix, Élise Goujard, Peter Zograf, and Anton Zorich. Masur–Veech volumes, frequencies of simple closed geodesics, and intersection numbers of moduli spaces of curves. *Duke Math. J.*, 170(12):2633–2718, 2021. doi: 10.1215/00127094-2021-0054.

Aurélien Dersy, Matthew D. Schwartz, and Xiaoyuan Zhang. Simplifying polylogarithms with machine learning. *Int. J. Data Sci. Math. Sci.*, 01(02):135–179, 2023. doi: 10.1142/S2810939223500028.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, 2019.

Robbert Dijkgraaf, Herman L. Verlinde, and Erik P. Verlinde. Topological strings in $d < 1$. *Nucl. Phys. B*, 352:59–86, 1991. doi: 10.1016/0550-3213(91)90129-L.

Bin Dong, Xuhua He, Pengfei Jin, Felix Schremmer, and Qingchao Yu. Machine learning assisted exploration for affine Deligne–Lusztig varieties. *Peking Math. J.*, pp. 1–50, 2024. doi: 10.1007/s42543-024-00086-8.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2021.

Bertrand Eynard and Dimitrios Mitsios. A new formula for intersection numbers, 2023.

Bertrand Eynard and Nicolas Orantin. Invariants of algebraic curves and topological expansion. *Commun. Number Theory Phys.*, 1(2):347–452, 2007. doi: 10.4310/CNTP.2007.v1.n2.a4.

Bertrand Eynard, Elba Garcia-Failde, Alessandro Giacchetto, Paolo Gregori, and Danilo Lewański. Resurgent large genus asymptotics of intersection numbers, 2023.

Jiahai Feng and Jacob Steinhardt. How do language models bind entities in context? In *The Twelfth International Conference on Learning Representations*, 2024.

Jie Gui, Tuo Chen, Jing Zhang, Qiong Cao, Zhenan Sun, Hao Luo, and Dacheng Tao. A survey on self-supervised learning: Algorithms, applications, and future trends, 2024.

Sergei Gukov, James Halverson, Fabian Ruehle, and Piotr Sułkowski. Learning to unknot. *Mach. Learn.: Sci. Technol.*, 2(2):025035, 2021. doi: 10.1088/2632-2153/abe91f.

Sergei Gukov, James Halverson, Ciprian Manolescu, and Fabian Ruehle. Searching for ribbons with machine learning, 2023.

Jindong Guo and Di Yang. On the large genus asymptotics of psi-class intersection numbers. *Math. Ann.*, pp. 1–37, 2022. doi: 10.1007/s00208-022-02505-6.

James Halverson, Brent Nelson, and Fabian Ruehle. Branes with brains: exploring string vacua with deep reinforcement learning. *J. High Energy Phys.*, 2019(6):1–60, 2019. doi: 10.1007/JHEP06(2019)003.

Yang-Hui He, Elli Heyes, and Edward Hirst. Machine learning in physics and geometry. *Artif. Intell.*, 49:47, 2023. doi: 10.1016/bs.host.2023.06.002.

Dieuwke Hupkes, Verna Dankers, Mathijs Mul, and Elia Bruni. Compositionality decomposed: How do neural networks generalise? *J. Artif. Intell.*, 67:757–795, 2020. doi: 10.1613/jair.1.11674.

Sergey Ioffe. Batch normalization: Accelerating deep network training by reducing internal covariate shift, 2015.

Albert Q Jiang, Wenda Li, and Mateja Jamnik. Multilingual mathematical autoformalization, 2023.

Sheldon Katz. *Enumerative Geometry and String Theory*, volume 32. American Mathematical Soc., 2006.

Maxim Kontsevich. Intersection theory on the moduli space of curves and the matrix Airy function. *Commun. Math. Phys.*, 147:1–23, 1992. doi: 10.1007/BF02099526.

Maxim Kontsevich and Yan Soibelman. Airy structures and symplectic geometry of topological recursion. In *2016 AMS von Neumann Symposium, Topological Recursion and its Influence in Analysis, Geometry and Topology*, volume 100, pp. 433–489. Amer. Math. Soc., Providence, RI, 2018. doi: 10.1090/pspum/100.

Yair Lakretz, Théo Desbordes, Dieuwke Hupkes, and Stanislas Dehaene. Causal transformers perform below chance on recursive nested constructions, unlike humans, 2021.

Kenneth Li, Aspen K Hopkins, David Bau, Fernanda Viégas, Hanspeter Pfister, and Martin Wattenberg. Emergent world representations: Exploring a sequence model trained on a synthetic task. *ICLR*, 2023.

Xiaohan Lin, Qingxing Cao, Yinya Huang, Zhicheng Yang, Zhengying Liu, Zhenguo Li, and Xiaodan Liang. Atg: Benchmarking automated theorem generation for generative language models, 2024.

Ziming Liu, Yixuan Wang, Sachin Vaidya, Fabian Ruehle, James Halverson, Marin Soljačić, Thomas Y Hou, and Max Tegmark. Kan: Kolmogorov-arnold networks, 2024.

Sarah Loos, Geoffrey Irving, Christian Szegedy, and Cezary Kaliszyk. Deep network guided proof search. *EPiC Ser. Comput.*, 46:85–105, 2017. doi: 10.29007/8mwc.

Kazem Meidani, Parshin Shojaee, Chandan K. Reddy, and Amir Barati Farimani. SNIP: Bridging mathematical symbolic and numeric realms with unified pre-training. In *The Twelfth International Conference on Learning Representations*, 2024.

Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. Locating and editing factual associations in gpt. *Adv. Neural Inf. Process. Syst.*, 35:17359–17372, 2022.

Vincent Micheli, Eloi Alonso, and François Fleuret. Transformers are sample-efficient world models. In *The Eleventh International Conference on Learning Representations*, 2023.

Maciej Mikuła, Szymon Tworkowski, Szymon Antoniak, Bartosz Piotrowski, Albert Q. Jiang, Jin Peng Zhou, Christian Szegedy, Łukasz Kuciński, Piotr Miłoś, and Yuhuai Wu. Magnushammer: A transformer-based approach to premise selection. In *The Twelfth International Conference on Learning Representations*, 2024.

John A Miller, Mohammed Aldosari, Farah Saeed, Nasid Habib Barna, Subas Rana, I Budak Arpinar, and Ninghao Liu. A survey of deep learning and foundation models for time series forecasting. *arXiv preprint arXiv:2401.13912*, 2024.

Maryam Mirzakhani. Weil–Petersson volumes and intersection theory on the moduli space of curves. *J. Am. Math. Soc.*, 20(1):1–23, 2007. doi: 10.1090/S0894-0347-06-00526-1.

Maryam Mirzakhani. Growth of the number of simple closed geodesies on hyperbolic surfaces. *Ann. Math.*, pp. 97–125, 2008. doi: 10.4007/annals.2008.168.97.

David Mumford. Towards an enumerative geometry of the moduli space of curves. *Arithmetic and Geometry: Papers Dedicated to I. R. Shafarevich on the Occasion of His Sixtieth Birthday. Volume II: Geometry*, pp. 271–328, 1983.

Andrei Okounkov. Generating functions for intersection numbers on moduli spaces of curves. *Int. Math. Res. Not.*, 2002(18):933–957, 2002. doi: 10.1155/S1073792802110099.

Aditya Paliwal, Sarah Loos, Markus Rabe, Kshitij Bansal, and Christian Szegedy. Graph representations for higher-order logic and theorem proving. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 2967–2974, 2020.

Harris Papadopoulos, Volodya Vovk, and Alex Gammerman. Conformal prediction with neural networks. In *19th IEEE International Conference on Tools with Artificial Intelligence (ICTAI 2007)*, volume 2, pp. 388–395, 2007. doi: 10.1109/ICTAI.2007.47.

Giambattista Parascandolo, Heikki Huttunen, and Tuomas Virtanen. Taming the waves: sine as activation function in deep neural networks, 2017.

Bernardino Romera-Paredes, Mohammadamin Barekatain, Alexander Novikov, Matej Balog, M Pawan Kumar, Emilien Dupont, Francisco JR Ruiz, Jordan S Ellenberg, Pengming Wang, Omar Fawzi, et al. Mathematical discoveries from program search with large language models. *Nature*, 625(7995):468–475, 2024. doi: 10.1038/s41586-023-06924-6.

Phil Saad, Stephen H Shenker, and Douglas Stanford. JT gravity as a matrix integral, 2019.

David Saxton, Edward Grefenstette, Felix Hill, and Pushmeet Kohli. Analysing mathematical reasoning abilities of neural models. In *International Conference on Learning Representations*, 2019.

Glenn Shafer and Vladimir Vovk. A tutorial on conformal prediction. *J. Mach. Learn. Res.*, 9(3), 2008.

Neil J. A. Sloane. The on-line encyclopedia of integer sequences. In Manuel Kauers, Manfred Kerber, Robert Miner, and Wolfgang Windsteiger (eds.), *Towards Mechanized Mathematical Assistants*, pp. 130–130, Berlin, Heidelberg, 2007. Springer Berlin Heidelberg.

David So, Wojciech Mańke, Hanxiao Liu, Zihang Dai, Noam Shazeer, and Quoc V Le. Searching for efficient transformers for language modeling. *Adv. Neural Inf. Process. Syst.*, 34:6010–6022, 2021.

Trieu H Trinh, Yuhuai Wu, Quoc V Le, He He, and Thang Luong. Solving olympiad geometry without human demonstrations. *Nature*, 625(7995):476–482, 2024. doi: 10.1038/s41586-023-06747-5.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need, 2023.

Jesse Vig, Sebastian Gehrmann, Yonatan Belinkov, Sharon Qian, Daniel Nevo, Simas Sakenis, Jason Huang, Yaron Singer, and Stuart Shieber. Causal mediation analysis for interpreting neural NLP: the case of gender bias, 2020.

Volodya Vovk, Alexander Gammerman, and Craig Saunders. Machine-learning applications of algorithmic randomness. In *16th International Conference on Machine Learning*, ICML '99, pp. 444–453, San Francisco, CA, USA, 1999. Morgan Kaufmann Publishers Inc.

Adam Zsolt Wagner. Constructions in combinatorics via neural networks, 2021.

Boshi Wang, Xiang Yue, Yu Su, and Huan Sun. Grokked transformers are implicit reasoners: a mechanistic journey to the edge of generalization, 2024.

Mingzhe Wang and Jia Deng. Learning to prove theorems by learning to generate theorems. *Adv. Neural Inf. Process. Syst.*, 33:18146–18157, 2020.

Qingxiang Wang, Chad Brown, Cezary Kaliszyk, and Josef Urban. Exploration of neural machine translation in autoformalization of mathematics in mizar. In *Proceedings of the 9th ACM SIGPLAN International Conference on Certified Programs and Proofs*, pp. 85–98, 2020.

Wenxiao Wang, Lu Yao, Long Chen, Binbin Lin, Deng Cai, Xiaofei He, and Wei Liu. CrossFormer: a versatile vision transformer hinging on cross-scale attention, 2021.

Edward Witten. Two-dimensional gravity and intersection theory on moduli space. In *Surveys in Differential Geometry*, volume 1, pp. 243–310, 1991. doi: 10.4310/SDG.1990.v1.n1.a5.

Yuhuai Wu, Albert Qiaochu Jiang, Wenda Li, Markus Rabe, Charles Staats, Mateja Jamnik, and Christian Szegedy. Autoformalization with large language models. *Adv. Neural Inf. Process. Syst.*, 35:32353–32368, 2022.

Chen Xu and Yao Xie. Conformal prediction for time series, 2023.

Huaiyuan Ying, Zijian Wu, Yihan Geng, Jiayu Wang, Dahua Lin, and Kai Chen. Lean workbook: A large-scale lean problem set formalized from natural language math problems, 2024.

Jure Zbontar, Li Jing, Ishan Misra, Yann LeCun, and Stéphane Deny. Barlow Twins: self-supervised learning via redundancy reduction, 2021.

Dylan Zhang, Curt Tigges, Zory Zhang, Stella Biderman, Maxim Raginsky, and Talia Ringer. Transformer-based models are not yet perfect at learning to emulate structural recursion, 2024.

Fred Zhang and Neel Nanda. Towards best practices of activation patching in language models: metrics and methods, 2024.

Liu Ziyin, Tilman Hartwig, and Masahito Ueda. Neural networks fail to learn periodic functions and how to fix it. *Adv. Neural Inf. Process. Syst.*, 33:1583–1594, 2020.

A MATHEMATICAL BACKGROUND

In this section, we review some background on the original mathematical problem. Let $\overline{\mathcal{M}}_{g,n}$ be the moduli space of genus $g \geq 0$ complex stable algebraic curves with $n > 0$ distinct marked points. This is a complex, compact, smooth orbifold of dimension $3g - 3 + n$. Associated with each marked point is a natural cohomology class $\psi_i = c_1(\mathcal{L}_i)$, defined as the first Chern class of the cotangent line bundle $\mathcal{L}_i$ at the i-th marked point.

In the early 90s, Witten (Witten, 1991) analyzed a theory of two-dimensional topological quantum gravity, where ψ-classes play the role of observables, and the *intersection numbers* (sometimes called *amplitudes*)

$$\langle \tau_{d_1} \cdots \tau_{d_n} \rangle_{g,n} := \int_{\overline{\mathcal{M}}_{g,n}} \psi_1^{d_1} \cdots \psi_n^{d_n}, \qquad d_1 + \cdots + d_n = d_{g,n} := 3g - 3 + n, \qquad \text{(A.1)}$$

represent correlators of the theory, and are topological invariants of $\overline{\mathcal{M}}_{g,n}$. Based on a low genus profile and considerations from physics, Witten conjectured that the exponential generating function

$$Z(\boldsymbol{x}; \hbar) = \exp \left(\sum_{\substack{g \geq 0 \\ n > 0}} \frac{\hbar^{2g-2+n}}{n!} \sum_{\substack{d_1, \ldots, d_n \geq 0 \\ d_1 + \cdots + d_n = d_{g,n}}} \langle \tau_{d_1} \cdots \tau_{d_n} \rangle_{g,n} x^{d_1} \cdots x^{d_n} \right) \qquad \text{(A.2)}$$

satisfies a infinite tower of quadratic partial differential equations with respect to the formal variables $(x^i)_{i \geq 0}$ known as the Korteweg–de Vries (KdV) hierarchy. This was later proven by Kontsevich (Kontsevich, 1992).

In recent years, it has been discovered that many fundamental invariants in physics and geometry can be described via intersection numbers. In physics, interest in ψ-class intersection numbers has been revitalized due to their connection with Jackiw–Teitelboim gravity (Saad et al., 2019). From an algebraic geometry perspective, ψ-class intersection numbers represent the most basic form of Gromov–Witten invariants (Behrend, 1997). These intersection numbers are central to enumerative problems addressed by (Kontsevich, 1992) and (Mirzakhani, 2007) regarding the symplectic volumes of the moduli space of metric ribbon graphs and hyperbolic Riemann surfaces. Computing intersection numbers is pivotal in the asymptotic counting of geodesic curves in both flat and hyperbolic random geometries (Mirzakhani, 2008; Delecroix et al., 2021; Andersen et al., 2023).

Given the wide and fascinating applications of intersection numbers, computing them for arbitrarily large genera remains an open problem. Their association with the KdV hierarchy has been illuminating for calculating these invariants (Witten, 1991; Kontsevich, 1992). Another approach to characterizing these numbers involves Virasoro constraints (Dijkgraaf et al., 1991), where the partition function is annihilated by a collection of differential operators that form a representation of the Virasoro algebra. Alternative recursive approaches include topological recursion (Eynard & Orantin, 2007), the cut-and-join equation (Alexandrov, 2011), and exact formulae for the generating series, such as error-function-type integrals (Okounkov, 2002) and the determinantal formula (Bergère & Eynard, 2009). However, the general computation of intersection numbers remains an open problem, as these methods can only be used to compute ψ-class intersection numbers for cases with small g or n. Meanwhile, universality phenomena in flat and hyperbolic geometry and in the dynamics of surfaces manifest themselves in large genera. Only recently, Aggarwal (Aggarwal, 2021) has found a closed-form formula for the large genus asymptotic of ψ-class intersection numbers.

A simple example of quantum Airy structure   The simplest example of a quantum Airy structure involves taking $V = \mathbb{C}$ and setting $A = B = C = D = 1$. Under these conditions, we have a unique differential operator given by

$$L = \hbar \partial_x - \hbar^2 \left(\frac{x^2}{2} + x \partial_x + \frac{1}{2} \partial_x^2 + 1 \right). \tag{A.3}$$

The differential equation $LZ = 0$ can be reduced to the Airy differential equation (hence the name "quantum Airy structure"). Therefore, the associated formal power series Z is given by the properly normalized asymptotic expansion of the Airy function:

$$Z(x; \hbar) = \frac{e^{\frac{x}{\hbar}(1 - \frac{\hbar x}{2})}}{\mathrm{Bi}(0)} \mathrm{Bi} \left(\frac{1 - 2\hbar x - \hbar^2}{(2\hbar^2)^{2/3}} \right). \tag{A.4}$$

B   DATA REPRESENTATION AND SETUP

The input data during training consisted of the sparse tensors B and C from Equation (2.5), the genus g, the number of marked points n, and the partitions $\boldsymbol{d} = (d_1, \ldots, d_n)$ of $d_{g,n}$. We did not include A and D as input, as they are fixed initial conditions for all ψ-class intersection numbers.

As we will consider values of g and n such that the dimension $d_{g,n}$ will never exceed $d_{\max} = 100$, the initial data will consist of only finitely many data. More precisely, the initial data during training were represented as follows.

- **B Initial Data**: A rank 3 tensor $B_{i,j}^k \in \mathbb{R}^{d_{g,n} \times d_{g,n} \times d_{g,n}}$. Such a tensor links intersection numbers of the same genus (cf. Equation (2.4)). Since it is a sparse tensor with $d_{g,n} \leq d_{\max} = 100$, we chose to represent its non-zero components in the COO (Coordinate List) format. In the COO format, B is represented as a set of 4-tuples, each containing the indices and the corresponding non-zero value:

$$\boldsymbol{B} = \left\{ (i, j, k, B_{i,j}^k) \mid B_{i,j}^k \neq 0 \right\} \tag{B.1}$$

  where $i, j, k \in [0, d_{g,n}]$, and $B_{i,j}^k$ are the non-zero components of the tensor. With this choice of $d_{\max}$, the maximum length of $\boldsymbol{B}$ is approximately 1500.

- **C Initial Data**: A rank 3 tensor $C_i^{j,k} \in \mathbb{R}^{d_{g,n} \times d_{g,n} \times d_{g,n}}$. Such a tensor links intersection numbers of different genera (cf. Equation (2.4)). Again, since it is a sparse tensor with $d_{g,n} \leq d_{\max} = 100$, we chose to represent its non-zero components in the COO format. In the COO format, C is represented as a set of 4-tuples, each containing the indices and the corresponding non-zero value:

$$\boldsymbol{C} = \left\{ (i, j, k, C_i^{j,k}) \,\middle|\, C_i^{j,k} \neq 0 \right\} \tag{B.2}$$

where $i, j, k \in [0, d_{g,n}]$, and $C_i^{j,k}$ are the non-zero components of the tensor. With this choice of $d_{\max}$, the maximum length of $\boldsymbol{C}$ is approximately 1500. In this setup, C initial datum are excluded. This had been observed by Aggarwal (Aggarwal, 2021), that the C-terms contributes quadratically, while the B-term contributes linearly and has a stronger effect on computing ψ-class intersections.

- **Partitions**: The intersection numbers $\langle \boldsymbol{d} \rangle_{g,n}$ are labeled by partitions $\boldsymbol{d} = (d_1, \ldots, d_n) \in \mathbb{N}^n$ of $d_{g,n}$ of length n. An important feature of intersection numbers (and more generally, amplitudes computed from quantum Airy structures) is that they are invariant under permutation of the indices, that is, elements of the partition $\boldsymbol{d}$. For example given a partition $\boldsymbol{d} = (3, 0, 0)$, we have $\langle 3, 0, 0 \rangle_{1,3} = \langle 0, 3, 0 \rangle_{1,3} = \langle 0, 0, 3 \rangle_{1,3}$.

We trained the model using data up to genus $g = 13$ and then tasked it with predicting the intersection numbers for genera $g = 14, 15, 16$ and 17.

C MODEL DETAILS

Figure 5: Illustration of DynamicFormer. It processes two main input modalities: the quantum Airy structure datum B as an ordered sequence and partitions d as a permutation-invariant set. The genus g and number of marked points n are incorporated as input properties, modulated with the main modalities at various stages. All layers, including the Multi-Head Attention (MHA) blocks, use the Dynamic Range Activator (DRA) non-linear activation function. The MHA block for B-modality integrates Dynamic Positional bias with linear positioning as well. The Talking-Modalities block consists of Batch Normalization (Ioffe, 2015) and the self-supervised loss. The DRA prediction head is a 2-layer MLP that predicts ψ-class intersection numbers in logarithmic scale.

To handle the different input modalities, i.e. the continuous tensor B in COO sequence format and the discrete permutation invariant set $\boldsymbol{d} \in \mathbb{N}^n$, we want to develop a multi-modal Transformer-based model. Multi-Linear Perceptron (MLP) despite being a universal approximator, they lack

the inductive biases necessary to effectively handle the structured data and invariances inherent in our multi-modal input. They treat all input dimensions independently, making it challenging to leverage the sparse graph structure of B or the permutation symmetry of $\boldsymbol{d}$. This results in comparatively weaker scalability, especially when faced with the limited, complex, high-variance target distributions present in the ψ-class intersection numbers. Table 4 shows a comparison between MLPs and DynamicFormer.

Snake MLP		DRA MLP		DynamicFormer	
$R^2 \uparrow$	CW $\downarrow$	$R^2 \uparrow$	CW $\downarrow$	$R^2 \uparrow$	CW $\downarrow$
69.3	8.44	76.5	7.73	**95.8**	**3.42**

Table 4: Comparison of R^2 and Conformal Width between models DynamicFormer and MLP with DRA and Snake non-linearity in the OOD regime.

The trunk of DynamicFormer consists of two modified Transformers: one discrete, acting on the embedding of the partitions $\boldsymbol{d}$ and maintaining permutation equivariance, and one continuous, acting on the B tensor. The positions of elements in B, represented in COO format, correspond to particular combinations of indices that compute the intersection numbers. To enhance generalization for longer input sequences, we integrated a modified version of Dynamic Positional Bias (Wang et al., 2021; Zhang et al., 2024) with linear positioning. Dynamic Positional Bias computes a relative positional bias map for each attention head, which is learnable and adapts based on sequence length. Since it does not inherently account for the distance from the start or end of a COO sequence, we apply masking based on input sequence length.

After the Transformer trunk of the network, all the embedded information is aggregated by the Principal Neighbourhood Aggregation (PNA) layer (Corso et al., 2020), pooling the information from the modalities $(\boldsymbol{B}, \boldsymbol{d})$. Once the information from these two branches, for each sample, is modulated with their corresponding genus and number of marked points positional attributes, (g, n), it is mapped to the outputs, i.e., ψ-class intersection numbers, via an MLP head. DRA is the non-linear activation function used throughout these blocks. As the loss function, we use the Mean Absolute Error (MAE) loss. The total loss is, $\mathcal{L}_{\text{Total}} = \mathcal{L}_{\text{MAE}} + \mathcal{L}_{\text{TM}}$, where $\mathcal{L}_{\text{TM}}$ introduces a Self-Supervised Learning objective between the [DYN] registry tokens (Darcet et al., 2024) of each modality, inspired by Barlow Twins (Zbontar et al., 2021).

[DYN] registry tokens and Talking Modalities. In multi-modal learning, effectively sharing and integrating information across different modalities is crucial for building robust models. Inspired by the success of Self-Supervised Learning (SSL) (Gui et al., 2024), we introduce a simple modification to enhance correspondence between modalities. To achieve this, we concatenate dynamic register tokens (Darcet et al., 2024), [DYN], to each modality. These tokens are similar to [CLS] tokens in BERT (Devlin et al., 2019) and Vision Transformers (Dosovitskiy et al., 2021), in that they are passed through the attention layers alongside the input data. However, unlike [CLS] tokens, they are not directly used for the downstream supervised task of amplitude prediction. Instead, they are used indirectly, as register tokens (Darcet et al., 2024), which store and process global information, introduced for Vision Transformers. By attending to all tokens in the input, [DYN] tokens, similar to register tokens, do a soft contrastive learning update, enabling them to learn a global context for each sample. Unlike register tokens, [DYN] tokens are also optimized to ensure that the outputs from different modalities of data—specifically from the B tensor, which provides global information per sample, and the partitions $\boldsymbol{d}$, which serve as local information carriers—are as similar as possible while simultaneously reducing the redundancy of the information they carry. Their optimization is guided by the Canonical Correlation Analysis (Abdi et al., 2018) family of SSL, where the aim is to infer the relationship between two modalities by analyzing their cross-covariance matrices (Balestriero et al., 2023). Inspired by Barlow Twins (Zbontar et al., 2021), the two modalities start to have a "conversation", promoting an interaction in which the two modalities collaboratively refine their representations. The idea behind this is that such a consensus mechanism not only enhances the model's ability to generalize better to Out-Of-Distribution (OOD) data but also improves its robustness. The Talking Modalities loss is then defined as follows:

$$\mathcal{L}_{\text{TM}} = \sum_{i=1}^{k} \left(1 - \mathcal{C}_{ii}^{(\boldsymbol{B},\boldsymbol{d})}\right)^2 + \lambda \sum_{\substack{i,j=1,\dots,k \\ i \neq j}} \left(\mathcal{C}_{ij}^{(\boldsymbol{B},\boldsymbol{d})}\right)^2, \tag{C.1}$$

where $\mathcal{C}$ is the cross-correlation matrix of the representations from the two modalities, $(\boldsymbol{B}, \boldsymbol{d})$, k is the dimensionality of the model's embeddings (vector representations). and λ is the weighting factor that balances the contributions of talking modalities. The first term penalizes the diagonal elements of the cross-correlation matrix $\mathcal{C}$ for deviating from the identity, thus encouraging invariance. The second term penalizes the off-diagonal elements, encouraging the components of the representation vectors to be decorrelated. Table 5 shows that this modification slightly enhances the performance of the model in the OOD prediction regime.

None		[DYN]		[DYN]+TM	
$R^2 \uparrow$	CW $\downarrow$	$R^2 \uparrow$	CW $\downarrow$	$R^2 \uparrow$	CW $\downarrow$
91.1	4.91	94.6	4.05	**95.8**	**3.42**

Table 5: Comparison of R^2 and CW between models with and without [DYN] register token and Talking Modalities. A small performance improvement can be observed as a result of using register tokens Talking Modalities in the OOD regime.

D   COMPARISON BETWEEN TRUE AND PREDICTED INTERSECTION NUMBERS

Figure 6 shows the numerical comparison between the true ψ-class intersection numbers and the predictions by DynamicFormer, illustrating the model's performance in capturing the recursive behavior.

E   UNCERTAINTY QUANTIFICATION: CONFORMAL PREDICTION

To estimate the uncertainty of the prediction, we incorporate Conformal Prediction (CP) (Vovk et al., 1999). CP is a probabilistic uncertainty quantification technique that provides prediction intervals in finite samples without making any distributional assumptions. We integrate the Inductive Conformal Prediction (Papadopoulos et al., 2007) with a dynamic sliding window (Xu & Xie, 2023) that, given the high heteroscedasticity in the data, computes rolling residuals for predicted intersections for each partition of equivalent marked points n. In our modification, we fit a quantile regression model to the residuals within a rolling window of equivalent marked points. This ensures that the residuals are more scale-dependent and appropriately adjusted for the inherent variability in the data, potentially capturing trends and heteroscedasticity better. As a result, we also report the empirical coverage and conformal width (CW) in the log scale.

F   PRINCIPAL COMPONENT ANALYSIS OF MODEL'S INTERNAL REPRESENTATION

If we perform Principal Component Analysis (PCA) on the hidden embedding of each sample, $p_{g,n}$, we observe in Figure 7 that DynamicFormer shows hierarchical representations of intersection numbers across both the genus g and the number of marked points n. It seems that the model has indeed learned a recursive structure within the data.

(a) $g = 13$

(b) $g = 14$

(c) $g = 15$

Figure 6: Comparison of true, predicted, and R^2 values for $g = 13, 14, 15$.

Figure 7: The first two principle components of model's hidden states across different genera (left) and number of marked points (right).