RESPONSE TO REVIEWER COMMENTS

We'd first like to thank the reviewers for all of their feedback. Below, we've included our revised paper and our response to the reviewer feedback. Changes to the paper are shown in pink.

Reviewer 1

Weakness

Although the paper targets to be a pedagogical paper, it is not easy to read. Cleaning up writing may be necessary. Paper often gets not precise. Clear assumptions and thorough correctness arguments are missing. I think this paper has the potential to be a good tutorial to dependency graph-based consensus protocols. (I might change the title. I think this paper is specifically on dependency graph-based Paxos protocols, not for general multi-leader consensus protocols.) However, it wasn't a paper that reads smoothly, especially since this paper presents many different protocols. As it is targetting to be a pedagogical paper, I recommend authors to spend time on that. In the detailed comments below, I added a few suggestions.

Also, the paper gets loose on preciseness from time to time. I understand that it might be impossible to present proofs to all protocols presented. But it sometimes felt too loose to wrap my mind about correctness.

We addressed your detailed comments and suggestions below. Thanks to your suggestions, we think the paper now reads much easier and is more precise.

Finally, I felt the paper wanders among various PPaxos & other prior work. I wonder if setting up a goal upfront would be helpful. It might be useful to set the goal of understanding EPaxos like protocols and why people want them.

We edited the introduction to clarify that our goal is to answer questions such as: What problem do these protocols address? How can I choose between the various protocols? Why do these protocols work the way they do? What do they have in common? Where do they differ? Which parts of the protocols are straightforward? Which are more subtle than they appear? Are there simpler variants out there? What trade-offs do the protocols make, and which points in the design space are still unexplored?

Page 1.

- *"generalized [13, 18]" ⇒ Is it a widely accepted term? Personally, I didn't really see that term outside of generalized Paxos.*

Atlas [2], Caesar [1], and a handful of other papers in the space [8,10] use the term "generalized", so we decided to use it as well to be consistent with these papers.

- *In the introduction, I would clarify that this paper's scope is on dependency graph-based Paxos protocols. It*

We added a sentence to the introduction clarifying that the paper focuses on protocols based on dependency graphs.

Page 2.

- *"For example, with two proposers... the leader of the round" seems not important.*

We removed the example from the paper. We left the sentence clarifying our usage of the word "leader" though, as we it a lot throughout the paper.

- *"chosen" at the end is not defined. It seems different from "chosen" in page 4. I would clarify "chosen" and "voted" in page 3.*

We edited Section 2.2 to make the definition of chosen more clear. Formally, a value is considered chosen when a majority of the acceptors vote for the value in the same round.

Page 3.

- *Figure 1 added little value to me. Except "number of leaders", terms in other boxes are not yet defined. Also, it covers many protocols not discussed in the paper.*

We moved Figure 1 to Section 10 at the end of the paper; it's now Figure 15. Now, all of the terms in the figure are defined when the figure is introduced. We include protocols not discussed in the paper to more completely taxonomize the space of protocols.

- *Ditto for Table 1. "$\mathsf{maj}()$" is not defined either.*

We also moved Table 1 to Section 10 at the end of the paper; it's now Table 2. As with Figure 1, all of the terms in the table are now defined when the table is introduced.

- *I add details to Figure 3. The current version only shows how many message delays are required. I think a figure with terms $(vr, vv, \text{PHASE1A}\langle i \rangle, etc)$ used in the text will be very helpful.*

We added the terms you requested to the figure.

- *Meaning of "v" is mixed. Sometimes "v" means the value given by the client. Sometimes it's not.*

When we discuss state machine replication protocols like MultiPaxos, we try to use variables like x, y, and z to denote state machine commands proposed by the client. When we discuss consensus protocols like Paxos, however, there is no state machine, so there are no state machine commands. In this context, we use v to denote values being chosen to be consistent with the existing literature. You're right that sometimes these values are values proposed by the client (as in Paxos), and sometimes they are more complicated (like $(x, \text{deps}(v_x))$ in PPaxos). We tried our best to name variables as consistently and intuitively as possible, and we tried out a couple of different naming schemes before settling on the one in the paper.

Page 4.

- *If any message gets ignored, what does a proposer do?*

We added some text to the end of Section 2.2 clarifying what a proposer does if it does not receive sufficiently many responses from the acceptors. This can happen because the acceptors ignored the proposer's requests, because the network dropped the messages, because of acceptor failure, etc.

- *Can you elaborate on how replicas work? Why is it safe, and how to ensure consistency?*

Unlike proposers and acceptors, replicas are very passive and do not execute any complex protocol logic. Replicas simply receive chosen commands from the proposers, place the commands in their logs, and execute the commands in log order. This is illustrated in Figure 1. Intuitively, this provides linearizability almost trivially since every replica is literally executing every command serially. For a more formal proof of correctness, we refer you to Lamport's original descriptions of the protocols [5, 6].

Page 5.

- *Need an explanation on directed edges. There is no introduction of the meaning of direction. The definition of dependency explained so far doesn't pose any order.*

We added some text to section 3.1 clarifying the direction of edges as well as their meaning.

- *3.2, "Replicas execute conflict graphs in reverse topological order" ⇒ why? what goes wrong if executed in topological order? I could imagine it's like EPaxos, but unclear. I wish to see some explanation based on the ultimate goal.*

The direction of edges is arbitrary. With minor protocol modifications, we could flip the direction of the edges and instead execute in topological order. We adopted EPaxos' convention of reverse topological order to be consistent with the existing literature and because we believe this convention is more intuitive.

- *3.3 "a log one entry" ⇒ typo?*

Yes, oops. Fixed!

Page 7.

- *"$v_x = (p_i, m)$" ⇒ v_x, whose vertex id is (p_i, m). Mixing command, vertex, and vertex id was a bit confusing. For example, "globally unique vertex id $v_x = (p_i, m)$" but later in text, v_x means vertex, not id.*

We added some text to Section 3.1 to clarify this. You're right that a vertex and a vertex id are not exactly the same, but because every vertex is labelled with a globally unique vertex id, we sometimes refer to the vertex with vertex id v_x as v_x for brevity.

The distinction between commands and vertices is more fundamental. The same command can be proposed multiple times and may appear in multiple vertices, so we are forced to distinguish between the two. We also clarified this in Section 3.1

A vertex $v_x = (p_i, m)$ being constructed of a proposer id and proposer-local monotonically increasing id is just an implementation detail to ensure globally unique ids. Any mechanism to construct globally unique ids can be used.

Page 8.

- *Texts for figure 11 are difficult to read. Maybe move them to caption.*

We increased the font size on the subcaptions.

- *Here, you introduce the timer. I think Paxos protocols generally don't require a synchronous network. I think this new requirement should be declared earlier.*

As we state in Section 2, we don't assume a synchronous network, and we assume machines can operate at arbitrary speeds without any form of clock synchronization. The timers used during recovery are local to a machine. They can run arbitrarily fast or slow without violating the protocol's safety. The timers do not depend on a synchronous network.

- *Separate client request (command) from vertex id. If not, it seems that clients won't be able to retry after the vertex gets noop.*

We added some text to Section 4.4 explaining that clients re-propose their commands if they have not received a response for a sufficiently long period of time.

Page 9.

- *4.5 doesn't prove that the two invariants guarantee linearizability or something similar. I would like to see the correctness argument for SMR, not just to the two invariants.*

We added some text to Section 3.4 explaining why the two key invariants are sufficient to guarantee linearizable execution.

- *"commit time" is typically defined as the time period between a client sends a request and the client knows it's committed. Execution is not a requirement. It's an important distinction for EPaxos, whose commit latency is different from execution latency (which may be longer than commit latency).*

We think that defining commit time with respect to executing a command, rather than "committing" it, is less ambiguous and more intuitive. Through personal conversations with the EPaxos authors, they have also come to regret separating command commitment from execution, as it complicates the protocol for marginal gain.

Unfortunately, there is no great definition of what it means for a command to be "committed," and certain definitions artificially lower the commit time. For example, consider the following hypothetical MultiPaxos variant. To propose a command, a client first broadcasts the command to $2f + 1$ storage nodes. When a storage node receives a command, it stores the command and replies back to the client. When a client receives replies from $f + 1$ storage nodes, it considers the command "committed" because despite f failures, the command will be available on some storage node. Some other daemon process that runs in the background periodically scans the storage nodes and proposes any commands it finds to a MultiPaxos instance. Thus, when a command is "committed", it will eventually be chosen and executed. This protocol achieves the theoretical lowest commit time of two network delays, but it is worse than executing MultiPaxos directly.

- *I don't understand how EPaxos leverages FastPaxos. Also, EPaxos's key advantage is optimistic two wide-area message delays. More explanation is needed here on the delicate need of FastPaxos & why 4 message delays are considered "improvement" despite MultiPaxos also only needs 4 message delays. I guess adding multi-leader requires more message delays, which could be removed by "FastPaxos".*

MultiPaxos has four network delays in the best case because the client has to send the command to the leader (1), the leader has to perform a round trip of communication with the acceptors (2, 3), and the leader has to reply to the client (4). Simple PPaxos requires an additional round trip to the dependency service because the protocol is generalized. Unanimous PPaxos, Basic EPaxos, Atlas, Majority Commit PPaxos, EPaxos, and Caesar all leverage Fast Paxos to eliminate this extra round trip. Specifically, they use Fast Paxos to merge the round trip to the dependency service with the round trip to the acceptors. You're 100% right that if we look purely at commit time, these protocols are just as good as MultiPaxos, but MultiPaxos is not generalized. Also note that these protocols can be optimized to remove an additional network delay (MultiPaxos can't do that), but it complicates the protocols.

Page 10.

- *Why use both learner and replica? Any difference?*

We added some text to Section 5.1 to clarify this. Consensus protocols like Paxos and Fast Paxos don't replicate a state machine, so they don't have state machine replicas. In this context, we use the term learner. State machine replication protocols like MultiPaxos, on the other hand, have state machine replicas which act as learners. In this context, we call them replicas. We apologize for any confusion.

- *I feel "maj()" is awkward. Why not just use an equation? Also, I don't understand why maj() needs to be defined separately for odd n and even n.*

We edited the definition of maj() in Section 5 to be $\mathsf{maj}(n) = \lceil \frac{n+1}{2} \rceil$. We think maj() is more intuitive and less error prone than reading raw equations. For example, we prefer to read $\mathsf{maj}(f+1)$ and $\mathsf{maj}(f+1) - 1$ than $\lceil \frac{f+2}{2} \rceil$, $\lfloor \frac{f+1}{2} \rfloor + 1$, $\lceil \frac{f+1}{2} \rceil$, and $\lfloor \frac{f+1}{2} \rfloor$.

- *If you used the commit time defined earlier, it can get more than 4. It must wait for dependent commands.*

Great point. We edited Section 5 to mention that commit time refers to the best case. In general due to the FLP impossibility result [3], a command can always get delayed arbitrarily for any state machine replication protocol.

- *6.2 Recovery ⇒ the term recovery is overloaded. Here, it's just adding noop. In other places, it commits with real command.*

We added some text to Section 4.4 to clarify that a proposer uses the same procedure to propose a command as it does to propose a noop. This is a good thing, as it avoids having to introduce an additional reovery protocol. This is an advantage of Simple PPaxos, Fast PPaxos, and Unanimous PPaxos compared to more complex protocols that do have a sophisticated recovery procedure (e.g., Majority Commit PPaxos, EPaxos, Caesar).

- *In the bullet starting with "In Figure 14b," ⇒ remind readers about Paxos protocol. I think that's necessary to understand why "so is forced to propose (x, p_i)".*

We added some text to Section 6.3 reminding the reader about Paxos.

- *I initially didn't understand why proposer p_2 doesn't send the request to d_1, d_2, …. It felt more natural to do that. But I guess you strictly abided by the Paxos protocol.*

You're right. Proposers recover vertices by executing Paxos, so there is no need to communicate with the dependency service.

Page 14.

- *7.1 ⇒ first paragraph is complicated. Renaming phases and describing what they do would be helpful.*

We agree that the Phase 1 and Phase 2 terminology is a little opaque, but we use the terminology to be consistent with the existing literature [4].

Page 15.

- *Does Unanimous PPaxos modify the "Paxos" protocol part? Can you explain why replicas will still converge and agree?*

As we state in Section 7.1, Unanimous PPaxos is identical to Fast PPaxos except with fast Phase 2 quorums of size $2f + 1$. Unanimous PPaxos proposer pseudocode is given in Algorithm 3. It is identical to the pseudocode of a Fast Paxos proposer (Algorithm 1) except for a couple small changes highlighted in red.

Reviewer 2

Measurable benefits of switching to multi-leader protocols

Multi-leader consensus protocols are complex and it's harder to implement them than their leadered counterparts

but in theory they have better performance. As a practitioner I wonder if the benefits are worth the complexity but the paper doesn't give me an answer.

The authors advocate that the major benefit comes as increased throughput (in Raft/Paxos a leader sends and receives disproportionately more messages). I recommend to include either experiment data or an estimation of the upper limits of throughput for both systems.

E.g. napkin math shows that the throughput of multi-leader consensus is $(2f + 1)^2/(4f + 1)$ times better than leadered where f is max allowed numbers of failures, proposer, acceptors and learners are colocated, it uses $f + 1$ sized quorums and the command's payload is way more bigger than the result of command execution.

We wholeheartedly agree that a comprehensive evaluation of the protocols would greatly improve the paper. Unfortunately, we believe that such a performance comparison falls outside of the scope of our paper and would likely be such a large contribution that it would warrant a paper on its own.

We also believe that our paper will enable such a contribution in the future. Implementing and evaluating a generalized multi-leader state machine protocol is extremely challenging without first understanding the protocol deeply, and currently, there is no easy way to understand these protocols. Our hope is that our paper will allow researchers to understand these protocols at a much deeper level, paving the way for future research on performance comparisons.

Retrieving data from the state machines

Usually production Paxos-based systems depend on bypassing the replication protocol for serving reads but the paper doesn't contain any information on how to do it. For example the leader-based protocols have well understood models for lightweight reads:

to read from a leader after waiting for a round of the heartbeats or after checking that its lease doesn't expire to read from a combination of the followers using methods from "Linearizable Quorum Reads in Paxos" or "Paxos quorum leases: Fast reads without sacrificing writes" papers to accept a possibility of staleness and to read from any node But those models aren't applicable to the multi-leader case: it lacks the leader/follower roles and local reads lead not only to staleness but to observing incompatible histories too caused by the reordering of the commuting commands.

We agree that optimizing reads is important for practical deployments of state machine replication protocols, but we believe that inventing a novel optimization to speed up reads in generalized multi-leader protocols would warrant its own research paper and extends beyond the scope of our Systemization of Knowledge paper which is targeted at clarifying the existing body of literature on generalized multi-leader state machine replication protocols. We hope that our paper will

enable researchers to invent novel read optimizations in the future.

Reconfiguration

The last important missing part is reconfiguration. It's crucial from a practical perspective. Without reconfiguration there is no way to replace the failed nodes and since failures are inevitable then eventually the multi-leader consensus based systems lose a majority and become unavailable.

One of the reasons Raft got so widespread in the industry is an included reconfiguration protocol (joined consensus) so with the declared goal I recommend to update the paper to include the reconfiguration sub-protocol.

We totally agree that reconfiguration is an essential component of any state machine replication protocol, and without it, a protocol is unusable in practice. We have also submitted a paper titled "Donut Paxos: A Reconfigurable Consensus Protocol" to JSys that presents a novel reconfiguration protocol that can be adopted by generalized multi-leader state machine replication protocols more easily compared to existing approaches like MultiPaxos' horizontal reconfiguration or Raft's joint consensus. We believe this piece of research stands best as its own separate paper.

Other (minor) issues

"This paper assumes that at most f machines will fail" - from a practical standpoint it's impossible to guarantee; it's better to mention what happens then this threshold is passed if consistency or availability becomes violated.

We added some text to Section 2 explaining that the assumption of at most f failures is made only for liveness. All the protocols in the paper are safe despite any number of failures (except for Fast PPaxos, which is intentionally unsafe).

"To reach is consensus on a value, an execution of Paxos is divided into a number of integer value rounds" - it's a clever idea to pre-assign a set of ballot numbers to the machines but using a term "round" both for a ballot number and an act of communication is confusing. It may create a false impression that it's impossible to skip ballot numbers. Maybe it'd be better to mention that rounds also known as ballot numbers (paxos) or term (raft) and add a reference to "Paxos vs Raft: Have we reached consensus on distributed consensus?" to use it as a map between different protocols.

Great idea. We edited Section 2.2 with your suggestion.

Reviewer 3

Cons:

1. *I strongly believe that this paper is missing some evaluation. It will be really helpful if the authors can illustrate the performance of the four protocols they have proposed against some of the protocols like Epaox, Atlas and so on. Although the aim of this paper is not to evaluate performance of multi-leader protocols, graphs that illustrate the performance of the proposed variants can help understand various design choices, such as which scheme is better Tension Avoidance or Tension Resolution.*

We wholeheartedly agree that a comprehensive evaluation of the protocols would greatly improve the paper. Unfortunately, we believe that such a performance comparison falls outside of the scope of our paper and would likely be such a large contribution that it would warrant a paper on its own.

We also believe that our paper will enable such a contribution in the future. Implementing and evaluating a generalized multi-leader state machine protocol is extremely challenging without first understanding the protocol deeply, and currently, there is no easy way to understand these protocols. Our hope is that our paper will allow researchers to understand these protocols at a much deeper level, paving the way for future research on performance comparisons.

2. *This paper needs some more work to clarify the different proposed protocols. Further, for several sections, there is a sudden switch from normal phase to recovery phase, which makes it difficult to understand. I explain most of my concerns next:*

We addressed all of your concerns below.

Major comments:

1. *While explaining the recovery for Simple PPaxos, the paper mentions "unchosen vertex" at the start of Section 4.4. It will be helpful if the paper explains what is meant by unchosen here. Further, it is important to re-iterate how can a vertex be unchosen.*

Great point. We added some text to the beginning of Section 4.4 to explain what an unchosen vertex is and how a vertex can become unchosen.

2. *I am unsure why at line 21 of Algorithm 1, the propose is sending to at least $f + 1$ acceptors instead of all acceptors. As f of the acceptors may crash, so sending to all acceptors in important.*

You're right. We were implementing an optimization called "thriftiness" [9] or "cheapness" [7] in which proposers send to the bare minimum number of acceptors, but we didn't mentioned this in the paper and it's is more complicated than necessary. We replaced all mention of "at least $f + 1$" acceptors to just "the acceptors" throughout the paper.

3. It is unclear to me what is the benefit of waiting for messages from all the $2f + 1$ acceptors in line 1, Algorithm 3. The paper should explain what will be the issue if the proposer only waits for messages from $f + \mathsf{maj}(f + 1)$ acceptors. I understand that the change at line helps to resolve the safety bug of Fast PPaxos but not sure why change at line 1 important. Moreover, asking Unanimous Paxos's proposer to wait for messages from all the $2f + 1$ acceptors can hurt its liveness even if a single proposer fails. In such a case, how will the proposer recover the state. The paper needs to clarify this scenario.

We revised Section 7.1 to reference line 1 of Algorithm 3. The main idea behind increasing Phase 2 quorums to size $2f + 1$ on line 1 is to ensure that on line 18, a proposer is only forced to propose a set of dependencies if that set of dependencies was computed by $f + 1$ dependency service nodes. This allows the protocol to maintain the consensus and dependency invariants.

We also added a paragraph to the end of Section 7.1 discussing the disadvantages of having unanimous quorums, including, as you mention, the decreased liveness.

4. I think there is a typo for lines 6-7 in Algorithm 3. They are not identical to the lines is Algorithm 1.

Good catch. Those lines are different but not a typo. We edited Algorithm 3 to highlight them in red, along with the other changes made to Algorithm 1. Those lines are actually a simplification to the more generic Fast Paxos proposer pseudocode of Algorithm 1. Because Phase 2 quorums are unanimous in Unanimous PPaxos, if the proposer of round 0 does not receive a unanimous set of votes in round 0, it knows immediately that no value has been or ever will be chosen in round 0, so it can proceed immediately to Phase 2 of round 1 and propose that any value be chosen.

5. While explaining the Basic Epaxos optimization on Step 7, page 16, the paper states that "p_i receives $2f$ votes for... including a vote from d_i". I am not sure when did d_i sent a vote to p_i. In the presented algorithm, d_i only communicates with other d_j. This step needs to be clarified.

Oops! That's a typo. d_i should be a_i. We fixed that in the paper. The idea is that a proposer always receives a vote from its colocated acceptor (which was proposed by the colocated dependency service node).

6. It is unclear what is happening from steps (7) and (8) on Basic Epaxos. So, when p_i receives $2f$ votes it sends v to a_i. Then, a_i records v as chosen and sends back to p_i. Then p_i sends to all other ancestors, and waits for acknowledgments. Why can't these steps

be combined? Further, to reduce from $2f + 1$ to $2f$, the Basic Epaxos optimization requires more network communication–from proposer to all acceptors and then acknowledgments from acceptors to the proposer. This needs to be clarified.

You're right that when p_i receives $2f$ votes it sends v to a_i. Then, a_i records v as chosen and sends back to p_i. After that, however, p_i does not have to communicate with the acceptors. It notifies the replicas that v has been chosen. These messages are labeled (8) in Figure 14. Also note that messages (6) and (7) are local to the server hosting p_i, so they don't incur any network delays. We edited Section 7.2 to clarify this. In practice, you would likely implement every node on a server within a single process, so the steps would effectively be combined. We keep all nodes decoupled to keep the exposition simple.

Simple PPaxos with the Basic EPaxos optimization actually requires the same or less communication than Simple PPaxos without the optimization. Without the optimization, the proposer must communicate with all $2f + 1$ acceptors. With the optimization, the proposer can implement thriftiness [9] and only communicate with $2f$ acceptors, or it can opt out of thriftiness and communicate with all $2f + 1$.

Minor comments:

1. On Page 6, the paper states Consensus Invariants, which uses the terms $(x, deps(x))$. These terms have not been mentioned anytime before in this subsection. Although it can be understood by further reading, it will be helpful to the reader if explained before.

We edited Section 3.4 to clarify the terms $(x, \mathrm{deps}(v))$ before introducing the consensus invariant.

2. It will be helpful if the paper either uses the term replicas or learners. The paper switches between the terms, which makes it often confusing.

We added some text to Section 5.1 to clarify this. Consensus protocols like Paxos and Fast Paxos don't replicate a state machine, so they don't have state machine replicas. In this context, we use the term learner. State machine replication protocols like MultiPaxos, on the other hand, have state machine replicas which act as learners. In this context, we call them replicas. We apologize for any confusion.

3. The following line "We consider what happens when not every..." on page 11, left hand side column are confusing the reader, as I expected that following this line the solution will be presented, but that happens much later in this section. Either consider removing this line or re-write it a little.

> *4. It is worth separating the recovery algorithm and not receiving enough matching votes (in Fast Paxos section) with suitable titles to improve readability.*

Great suggestions. We added subsections, and used the subsections to clarify the "We consider what happens when not every..." sentence.

Reviewer 4

However, I am not entirely certain what went wrong for Fast PPaxos. The paper claims that it is due to a dilemma between reaching consensus and preserving dependency. But it seems to me that the bug is a result of multi-leader rather than dependency. It seems that the bug could be avoided by simply abandoning concurrent leaders. The first approach to fix this bug, increasing quorum size to $2f + 1$, also does not seem related to dependency; rather, it seems to be avoiding a tie between concurrent leaders. I would like to see more discussion on the root cause of the problem, and how exactly it is fixed. This is very important for the paper since at some point the authors claim that most of the design complexity comes from generalized as opposed to multi-leader.

We don't attribute Fast PPaxos's lack of safety directly to the fact that it is multi-leader or generalized. In fact, while the execution in Figure 13 has multiple leaders, none of these leaders has to execute concurrently. Instead, we attribute the lack of safety to the fact that Fast PPaxos does not correctly manage the tension between the consensus and dependency invariants. Increasing quorum sizes to $2f + 1$ resolves this tension. In short, being multi-leader or being generalized are ways to describe a protocol, but they do not inherently lead to lack of safety. It is the failure to maintain core invariants that leads to the safety violations.

> *When describing Fast Paxos, the authors use proposals, acceptors, and learners; but in Simple or Fast PPaxos, the authors use proposals, acceptors, and replicas. I suggest the authors stick to one convention, preferrably learners.*

We added some text to Section 5.1 to clarify this. Consensus protocols like Paxos and Fast Paxos don't replicate a state machine, so they don't have state machine replicas. In this context, we use the term learner. State machine replication protocols like MultiPaxos, on the other hand, have state machine replicas which act as learners. In this context, we call them replicas. We apologize for any confusion.

> *Page 11 right column touched on why the threshold must be > 1.5f. While this may be obvious for experts, it is helpful to elaborate on this in a tutorial paper for non-expert readers.*

We added a paragraph to Section 5.2 elaborating on the requirement of fast Phase 2 quorums to be of size $f + \mathsf{maj}(f + 1)$.

> *Section 2 says that messages can be dropped, and indeed Section 6.3 considers a situation that messages to d_3, d_4, d_5 are dropped. However, the default model of Paxos does not allow message drop. Otherwise, one runs into the two-general impossibility. In this particular example in Section 6.3, can we simply have p_1 crash before it sends messages to d_3, d_4, and d_5? If this is sufficient to break Fast PPaxos, then I suggest removing message drop from the model. If this is not sufficient, the authors need to carefully define the model regarding message drop, and explain why the two general's impossibility does not apply.*

All of the protocols discussed in the paper are safe despite the possibility of messages being dropped, delayed, or reordered (except for Fast PPaxos which is intentionally unsafe). On the contrary, due to the FLP impossibility result [3], none of the protocols are guaranteed to be fully live. The two generals impossibility result involves establishing common knowledge between a set of participants, which is slightly orthogonal to consensus.

> *Overall, I like this tutorial paper and would support its acceptance as a tutorial paper. However, it is currently submitted as an SoK paper. If judged as an SoK paper, I am less supportive. The paper mentions that there are few generalized multi-leader systems, and indeed it only reviews 3 papers in detail (EPaxos, Caesar, Atlas). The related work section mentions a few other works very briefly and they are not closely related. As such, I feel the area of generalized multi-leader state machine replication is still relatively young and small, and has not reached a stage of needing an SoK paper. This is not a criticism of the paper. I think the authors are well aware that their paper is more of a tutorial than SoK. The onus is on the editorial board to accept this paper under an appropriate category.*

We're more than happy to have the paper moved to the most appropriate category available.

References

[1] Balaji Arun, Sebastiano Peluso, Roberto Palmieri, Giuliano Losa, and Binoy Ravindran. Speeding up consensus by chasing fast decisions. In *Dependable Systems and Networks (DSN), 2017 47th Annual IEEE/IFIP International Conference on*, pages 49–60. IEEE, 2017.

[2] Vitor Enes, Carlos Baquero, Tuanir França Rezende, Alexey Gotsman, Matthieu Perrin, and Pierre Sutra. State-machine replication for planet-scale systems. In

Proceedings of the Fifteenth European Conference on Computer Systems, pages 1–15, 2020.

[3] Michael J. Fischer, Nancy A. Lynch, and Mike Paterson. Impossibility of distributed consensus with one faulty process. *J. ACM*, 32(2):374–382, 1985.

[4] Heidi Howard, Aleksey Charapko, and Richard Mortier. Fast flexible paxos: Relaxing quorum intersection for fast paxos. In *International Conference on Distributed Computing and Networking 2021*, pages 186–190, 2021.

[5] Leslie Lamport. The part-time parliament. *ACM Transactions on Computer Systems (TOCS)*, 16(2):133–169, 1998.

[6] Leslie Lamport et al. Paxos made simple. *ACM Sigact News*, 32(4):18–25, 2001.

[7] Leslie Lamport and Mike Massa. Cheap paxos. In *International Conference on Dependable Systems and Networks, 2004*, pages 307–314. IEEE, 2004.

[8] Giuliano Losa, Sebastiano Peluso, and Binoy Ravindran. Brief announcement: A family of leaderless generalized-consensus algorithms. In *Proceedings of the 2016 ACM Symposium on Principles of Distributed Computing*, pages 345–347. ACM, 2016.

[9] Iulian Moraru, David G Andersen, and Michael Kaminsky. There is more consensus in egalitarian parliaments. In *Proceedings of the Twenty-Fourth ACM Symposium on Operating Systems Principles*, pages 358–372. ACM, 2013.

[10] Pierre Sutra and Marc Shapiro. Fast genuine generalized consensus. In *Reliable Distributed Systems (SRDS), 2011 30th IEEE Symposium on*, pages 255–264. IEEE, 2011.

SoK: A Generalized Multi-Leader State Machine Replication Tutorial

Anonymous authors

Abstract

MultiPaxos and Raft are the two most popular and widely deployed state machine replication protocols. There is a more sophisticated family of generalized multi-leader state machine replication protocols like EPaxos, Caesar, and Atlas that have better performance, but they are extremely complicated and hard to understand. Due to their complexity, they have seen little to no industry adoption, and academically there has been a lack of clarity in analyzing, comparing, and extending the protocols. This paper is a tutorial on generalized multi-leader protocols. We explain why the protocols work the way they do, what they have in common, where they differ, which parts of the protocols are straightforward, which are more subtle than they appear, and so on. In doing so, we present four new generalized multi-leader protocols, identify key insights into existing protocols, and taxonomize the space.

1 Introduction

State machine replication protocols are a critical component of many fault tolerant distributed systems [4, 5, 8, 27, 29]. Given an arbitrary deterministic state machine, like a key-value store or a relational database, a state machine replication protocol can be used to deploy multiple copies, or replicas, of the state machine while guaranteeing that the states of the replicas stay in sync and do not diverge.

The most popular and widely deployed state machine replication protocols are Paxos [5, 8, 13] and Raft [1, 2, 23, 27]. These protocols have two distinguishing characteristics. First, they are leader based. All communication is funneled through a single leader. Second, these protocols totally order state machine commands into a log and have state machine replicas execute the commands in log order. Every replica executes the exact same commands in the exact same order.

There is another family of *generalized multi-leader* state machine replication protocols—including EPaxos [22], Caesar [3], and Atlas [10]—that improve the performance of protocols like MultiPaxos and Raft along these two dimensions. These protocols are **multi-leader** and avoid being throughput bottlenecked by a single leader. They are also **generalized** [14, 19]. This means that the protocols are based on dependency graphs. Every replica executes non-commuting commands in the exact same order, but the replicas are free to execute commuting commands in any order. As a result, commuting commands do not interfere with one another.

Unfortunately, these generalized multi-leader protocols are extremely complicated. Paxos has a well known reputation for being complex [16, 23, 30], and these generalized multi-leader protocols are significantly more complex than that. They require a strong understanding of more sophisticated Paxos variants like Fast Paxos [15] and are overall less intuitive and more nuanced. It's hard to measure this complexity precisely, but there are indications that the protocols are complicated. EPaxos, for example, had several bugs go undiscovered for years despite the popularity of the protocol [26]. Through personal conversations, we have also found that even domain experts find these protocols challenging to fully understand.

This complexity has negative consequences in industry and academia. The performance advantages of generalized multi-leader protocols make them an attractive option for industry practitioners. Despite this, generalized multi-leader protocols have little to no industry adoption. We postulate that this is largely due to their complexity. The engineers in [6] explain that implementing a state machine replication protocol requires making many small changes to the protocol to match the environment in which it is deployed. Making these changes without a strong understanding of the protocol is infeasible. Academically, it is challenging to compare and contrast the various protocols. They all seem very similar, yet vaguely distinct. This also makes it difficult to extend the protocols with further innovations. There are dozens of state machine replication protocols in the literature, yet relatively few generalized multi-leader variants.

This paper is a tutorial on generalized multi-leader state machine replication protocols. Our goal is to answer questions such as: What problem do these protocols address? How can I choose between the various protocols? Why do these protocols work the way they do? What do they have in common? Where do they differ? Which parts of the protocols are straightforward? Which are more subtle than they appear? Are there simpler variants out there? What trade-offs do the protocols make, and which points in the design space are still unexplored?

The tutorial has four parts, and in each part, we introduce a new protocol. First, we present the simplest possible generalized multi-leader protocol, which we called **Simple PPaxos** (Section 4). Simple PPaxos sacrifices performance for simplicity and is designed with the sole goal of being easy to understand. Simple PPaxos is the kernel from which all other generalized multi-leader protocols can be constructed. It en-

capsulates all the mechanisms and invariants that are common to the other protocols.

Second, we introduce a purely pedagogical protocol called **Fast PPaxos** (Section 6). Fast PPaxos achieves higher performance than Simple PPaxos, but it is unsafe. The protocol does not properly implement state machine replication. Why study a broken protocol? Because understanding why Fast PPaxos does *not* work leads to a fundamental insight on why other protocols do. Specifically, we discover that generalized multi-leader protocols encounter a fundamental tension between agreeing on commands and ordering commands. The way in which a protocol handles this tension is its key distinguishing feature. We taxonomize the protocols into those that avoid the tension and those that resolve the tension.

Third, we introduce **Unanimous PPaxos**, a simple *tension avoiding* protocol (Section 7). We describe how tension avoiding protocols carefully enlarge quorum sizes to sidestep the tension. We also explain how Basic EPaxos [22] and Atlas [10] can be expressed as optimized variants of Unanimous PPaxos.

Fourth, we introduce **Majority Commit PPaxos**, a *tension resolving* protocol (Section 8). We describe how tension resolving protocols perform detective work to resolve the tension without enlarging quorum sizes. We also discuss the relationship between Majority Commit PPaxos and other tension resolving protocols like EPaxos [21] and Caesar [3].

In summary, we make the following contributions.

- We explain generalized multi-leader protocols carefully and thoroughly, bringing clarity to an otherwise dense area of popular research.

- We present four new generalized multi-leader state machine replication protocols: Simple PPaxos, Fast PPaxos, Unanimous PPaxos, and Majority Commit PPaxos.

- We identify a fundamental tension between agreeing on commands and ordering commands and use this insight to taxonomize generalized multi-leader protocols into those that avoid the tension and those that resolve it.

2 A Primer on State Machine Replication

Throughout the paper, we assume a system model in which messages can be arbitrarily dropped, delayed, and reordered. We assume machines can fail by crashing but do not act maliciously; i.e., we do not consider Byzantine failures. We assume that machines operate at arbitrary speeds, and we do not assume clock synchronization. Every protocol discussed in this paper assumes that at most f machines will fail for some configurable f. If more than f machines fail, the protocols remain safe, but won't be live.

2.1 State Machine Replication

State machine replication is the act of choosing a sequence (a.k.a. log) of values. A state machine replication protocol manages a number of copies, or **replicas**, of a deterministic state machine. Over time, the protocol constructs a growing log of state machine commands, and replicas execute the commands in log order. By beginning in the same initial state, and by executing the exact same commands in the exact same order, all of the state machine replicas are kept in sync. This is illustrated in Figure 1.

(a) $t = 0$ (b) $t = 1$ (c) $t = 2$ (d) $t = 3$

Figure 1: At time $t = 0$, no state machine commands are chosen. At time $t = 1$ command x is chosen in slot 0. At times $t = 2$ and $t = 3$, commands z and y are chosen in slots 2 and 1. Executed commands are shaded green. Note that all state machines execute the commands x, y, z in log order.

State machine replication builds on the simpler problem of **consensus**. Rather than choosing a sequence of values, consensus involves choosing a single value. State machine replication protocols like MultiPaxos implement state machine replication using one instance of consensus for every log entry, so to understand state machine replication, we must first understand consensus. We review Paxos, the most popular consensus algorithm, and then extend Paxos to MultiPaxos.

2.2 Paxos

A Paxos [13] deployment that tolerates f faults consists of an arbitrary number of clients, $f + 1$ nodes called **proposers**, and $2f + 1$ nodes called **acceptors**, as illustrated in Figure 2. To reach consensus on a value, an execution of Paxos is divided into a number of integer valued rounds (also known as ballots, epochs, terms, views, etc. [12]). Every round has two phases, Phase 1 and Phase 2, and every round is orchestrated by a single pre-determined proposer. If a proposer is responsible for executing a round, we sometimes say the proposer is the leader of the round.

When a proposer executes a round, say round i, it attempts to get some value v "chosen" in that round. We'll define formally what it means for a value to be chosen momentarily. Paxos is a consensus protocol, so it must only choose a single value. Thus, Paxos must ensure that if a value v is chosen in round i, then no other value besides v can ever be chosen in any round less than i. This is the purpose of Paxos' two phases. In Phase 1 of round i, the proposer contacts the acceptors to (a) learn of any value that may have already been chosen in any round less than i and (b) prevent any new values from being chosen in any round less than i. In Phase 2, the proposer

(a) Phase 1   (b) Phase 2

Figure 2: An example execution of Paxos ($f = 1$).

proposes a value to the acceptors, and the acceptors vote on whether or not to choose it. In Phase 2, the proposer is careful to only propose a value v if it learned through Phase 1 that no other value has been or will be chosen in a previous round.

More concretely, Paxos executes as follows. When a client wants to propose a value v, it sends v to a proposer p. Upon receiving v, p begins executing one round of Paxos, say round i. First, it executes Phase 1. It sends PHASE1A$\langle i \rangle$ messages to the acceptors. An acceptor ignores a PHASE1A$\langle i \rangle$ message if it has already received a message in a larger round. Otherwise, it replies with a PHASE1B$\langle i, vr, vv \rangle$ message containing the largest round vr in which the acceptor voted and the value it voted for, vv. If the acceptor hasn't voted yet, then $vr = -1$ and $vv =$ null. When the proposer receives PHASE1B messages from a majority of the acceptors, Phase 1 ends and Phase 2 begins.

At the start of Phase 2, the proposer uses the PHASE1B messages that it received in Phase 1 to select a value v such that no value other than v has been or will be chosen in any round less than i. Specifically v is the vote value associated with the largest received vote round, or any value if no acceptor had voted (see [16] for details). Then, the proposer sends PHASE2A$\langle i, v \rangle$ messages to the acceptors. An acceptor ignores a PHASE2A$\langle i, v \rangle$ message if it has already received a message in a larger round. Otherwise, it votes for v and sends back a PHASE2B$\langle i \rangle$ message to the proposer. If a majority of acceptors vote for the value (i.e. if the proposer receives PHASE2B$\langle i \rangle$ messages from a majority of the acceptors), then the value is chosen—this is the formal definition of when a value is chosen—and the proposer informs the client. This execution is illustrated in Figure 2. If the proposer does not receive sufficiently many PHASE1B or PHASE2B responses from the acceptors (e.g., because of network partitions or dueling proposers), then the proposer restarts the protocol in a larger round.

Note that it is safe for the leader of round 0 (the smallest round) to skip Phase 1 and proceed directly to Phase 2. Recall that the leader of round i executes Phase 1 to learn of any value that may have already been chosen in any round less than i and to prevent any new values from being chosen in any round less than i. There are no rounds less than 0, so these properties are satisfied vacuously.

2.3 MultiPaxos

As mentioned earlier, MultiPaxos uses one instance of Paxos for every log entry, choosing the command in the ith log entry using the ith instance of Paxos. A MultiPaxos deployment that tolerates f faults consists of an arbitrary number of clients, at least $f + 1$ proposers, and $2f + 1$ acceptors (like Paxos), as well as at least $f + 1$ replicas, as illustrated in Figure 3.

Figure 3: An example execution of MultiPaxos ($f = 1$). The leader is adorned with a crown.

Initially, one of the proposers is elected leader and runs Phase 1 of Paxos for every log entry. Though there are an infinite number of log entries, all but a finite prefix of the log entries are empty, so the leader can run Phase 1 for all entries with only a small number of messages. When a client wants to propose a state machine command x, it sends the command to the leader (1). The leader assigns the command a log entry i and then runs Phase 2 of the ith Paxos instance to get the value x chosen in entry i. That is, the leader sends PHASE2A messages to the acceptors to vote for value x in slot i (2). In the normal case, the acceptors all vote for x in slot i and respond with PHASE2B messages (3). Once the leader learns that a command has been chosen in a given log entry, it informs the replicas (4). Replicas insert commands into their logs and execute the logs in prefix order.

Note that every command is sent to the leader, and the leader performs disproportionately more work per command compared to the other nodes in the protocol. For example, in Figure 3, the leader must send and receive a total of 7 messages per command while the acceptors and replicas send and receive at most 2. This is why the MultiPaxos leader is a well known throughput bottleneck [20, 22].

3 Conflict Graphs

3.1 Defining Conflict Graphs

By totally ordering state machine commands into a log, state machine replication protocols like MultiPaxos ensure that *every* replica executes *every* command in *exactly the same order*. This is a simple way to ensure that replicas are always in sync, but it is sometimes unnecessary [14]. For example, consider the log shown at the top of Figure 4. The command a=2 (i.e. set the value of variable a to 2) is chosen in log entry 1, and the command b=1 is chosen in log entry 2. With MultiPaxos, every replica would execute these two commands in exactly the same order, but this is not necessary because the commands commute. It is safe for some replicas to execute a=2 before b=1 while other replicas execute b=1 before a=2. The execution order of the two commands has no effect on the final state of the state machine, so they can be safely reordered, as shown in Figure 4.

Figure 4: If two commands commute, replicas can safely execute them in either order.

More formally, we say two commands *x* and *y* **conflict** if there exists a state in which executing *x* and then *y* does not produce the same responses or final state as executing *y* and then *x*. We say two commands **commute** if they do not conflict. If two commands conflict (e.g., a=1 and a=2), then they need to be executed by every state machine replica in the same order. But, if two commands commute (e.g., a=2 and b=1), then they do *not* need to be totally ordered. State machine replicas can execute them in either order.

Generalized Multi-leader state machine replication protocols like EPaxos, Caesar, Atlas, and all the PPaxos variants presented in this paper take advantage of command commutativity. Rather than totally ordering commands into a log, these protocols *partially* order commands into a directed graph such that every pair of conflicting commands has an edge between them. We call these graphs **conflict graphs**. An example log and corresponding conflict graph is illustrated in Figure 5. A log consists of a number log entries, and every log entry has a unique log index (e.g., 4). A conflict graph consists of a number of **vertices**, and every vertex has a unique **vertex id** (e.g., v_4). Because every vertex is assigned a globally unique vertex id, we often refer to the vertex with vertex id *v* as *v*. Also note that a command may appear in multiple vertices, in

Figure 5: A log and corresponding conflict graph.

much the same way a command may appear multiple times in a log.

Moreover, a vertex *v* can have directed edges to other vertices. These are called the **dependencies** of *v*, denoted deps(*v*). For example, if vertex v_i depends on vertex v_j, then there is an edge from v_i to v_j. Note that if a pair of commands conflict, then they must have an edge between them. This ensures that every replica executes the two commands in the same order. For example in Figure 5, the commands a=b (v_0) and a=2 (v_1) conflict, so they have an edge between them. If two commands commute, then they do not have an edge between them. This allows replicas to execute the commands in either oder. For example, the commands a=2 (v_1) and b=1 (v_2) commute, so there is no edge between them. Finally note that some conflicting commands (e.g., b=a (v_3) and a=3 (v_4)) have edges in both directions, forming a cycle. Ideally, conflict graphs would be acyclic, but cycles are sometimes unavoidable. The reason for this will become clear soon.

3.2 Executing Conflict Graphs

We now explain how to execute a static conflict graph. In the next subsection, we explain how to execute a dynamic conflict graph that grows over time. Replicas execute logs in prefix order. Replicas execute conflict graphs in reverse topological order, one strongly connected component at a time. The order of executing commands within a strongly connected component is not important, but every replica must choose the same order. For example, replicas can execute commands within a component sorted by their vertex id. The conflict graph in Figure 5 has four strongly connected components, each shaded a different color. Vertices v_0, v_1, and v_2 are each in their own components, and commands v_3 and v_4 are in their own component. Replicas execute these four strongly connected components in reverse topological order as follows:

- First, replicas execute a=b (v_0).

- Next, replicas either execute a=2 (v_1) then b=1 (v_2) or b=1 (v_2) then a=2 (v_1). There are no edges between vertex v_1 and vertex v_2, so every replica can execute the two vertices in either order.

Table 1: The differences between protocols like MultiPaxos and Raft that organize commands in logs and protocols like EPaxos, Caesar, and Atlas that organize commands in graphs.

	Logs	Graphs
data structure	log	conflict graph
	log entry	vertex
	log index (e.g., 4)	vertex id (e.g., v_4)
	total order	partial order
execution order	log order	reverse topological order
what's chosen?	commands	commands & dependencies

- Finally, replicas execute b=a (v_3) and a=3 (v_4) in some arbitrary but fixed order. For example, if replicas execute commands sorted by their vertex ids, then the replicas would all execute v_3 and then v_4.

Executing commands in this way, state machine replicas are guaranteed to remain in sync. Every replica executes conflicting commands in the same order, but are free to execute commuting commands in any order.

3.3 Constructing Conflict Graphs

In the previous subsection, we explained how to execute a static conflict graph. In reality, graphs are dynamic and grow over time. MultiPaxos constructs one log entry at a time. It uses one instance of consensus for every log entry i to choose which command should be placed in log entry i. Analogously, generalized multi-leader protocols construct a conflict graph one vertex at a time. They use one instance of consensus for every vertex v to choose which command should be placed in vertex v and what dependencies, or outbound edges, v should have.

In Figure 6, we illustrate an example execution of how the conflict graph from Figure 5 could be constructed over time. Figure 6 also shows an analogous execution in which a log is constructed over time. Note that a vertex v can be chosen with dependencies deps(v) before every vertex in deps(v) has itself been chosen. For example in Figure 6c, v_3 is chosen with deps(v_3) = $\{v_0, v_1, v_2, v_4\}$ before vertices v_2 and v_4 are chosen. This is analogous to how a command is chosen in log entry 3 in Figure 6h before a command is chosen in entry 2.

A summary of the differences between logs and graphs is given in Table 1.

3.4 Two Key Invariants

Protocols like EPaxos, Caesar, Atlas, and the PPaxos protocols in this paper all differ in how they assign commands to vertices, how they compute dependencies, how they implement consensus, and so on. Despite the differences, all the protocols construct conflict graphs one vertex at a time, choosing a command and a set of dependencies $(x, \text{deps}(v))$

for every vertex v. The protocols all rely on the following two key invariants for correctness. We call these the **consensus invariant** (Invariant 1) and the **dependency invariant** (Invariant 2).

Invariant 1 (Consensus Invariant). Consensus is implemented for every vertex v. That is, at most one value $(x, \text{deps}(v))$ is chosen for every vertex v.

Invariant 2 (Dependency Invariant). If $(x, \text{deps}(v_x))$ is chosen in vertex v_x and $(y, \text{deps}(v_y))$ is chosen in instance v_y, and if x and y conflict, then either $v_x \in \text{deps}(v_y)$ or $v_y \in \text{deps}(v_x)$ or both. That is, if two chosen commands conflict, there is an edge between them.

The consensus invariant ensures that replicas always agree on the state of the conflict graph. It makes it impossible, for example, for two replicas to disagree on which command is in a vertex or disagree on what dependencies a vertex has. The dependency invariant ensures that replicas execute conflicting commands in the same order but does not require that replicas execute commuting commands in the same order. These two invariants are sufficient to ensure linearizable execution. Intuitively, the history of command execution is equivalent to a serial history following any reverse topological ordering of the conflict graph. In fact, replicas literally do execute commands serially according to one of the reverse topological orderings. For a more formal proof, refer to [14] and [21].

4 Simple PPaxos

In this section, we introduce **Simple PPaxos**, an inefficient protocol that is designed to be easy to understand. By understanding Simple PPaxos, we will understand of the core mechanisms and invariants that are common to all generalized multi-leader protocols.

4.1 Overview

As illustrated in Figure 7, a Simple PPaxos deployment consists of a number of clients, a set of at least $f + 1$ Paxos proposers, a set of $2f + 1$ **dependency service nodes**, a set of $2f + 1$ Paxos acceptors, and a set of at least $f + 1$ replicas. These nodes have the following responsibilities.

- The dependency service nodes, collectively called the **dependency service**, compute dependencies and maintain the dependency invariant (Invariant 2).

- The proposers and acceptors implement one instance of Paxos for every vertex and maintain the consensus invariant (Invariant 1).

- The replicas construct and execute conflict graphs and send the results of executing commands back to the clients.

Figure 6: In subfigures (a) - (e), we see a conflict graph constructed over time. The most recently chosen vertex is drawn in red. The executed commands are shaded green. (a) The command a=b is chosen in vertex v_0 without any dependencies. The command is executed immediately. (b) The command a=2 is chosen in vertex v_1 with a dependency on v_0. The command is executed immediately. (c) The command b=a is chosen in vertex v_3 with dependencies on v_0, v_1, v_2, and v_4. No commands have been chosen in v_2 and v_4 yet, so v_3 cannot be executed. (d) The command b=1 is chosen in vertex v_2 with a dependency on v_0. The command is executed immediately. (e) The command a=3 is chosen in vertex v_4 with dependencies on v_0, v_1, and v_3. Now v_3 and v_4 are executed. In subfigures (f) - (j), we see an analogous execution for a log.

Figure 7: An example execution of Simple PPaxos ($f = 1$).

More concretely, Simple PPaxos executes as follows. The numbers here correspond to the numbered arrows in Figure 7.

- **(1)** When a client wants to propose a state machine command x, it sends x to *any* of the proposers. Note that with MultiPaxos, only one proposer is elected leader, but in Simple PPaxos, every proposer is a leader.

- **(2) and (3)** When a proposer p_i receives a command x, from a client, it places x in a vertex with globally unique vertex id $v_x = (p_i, m)$ where m is a monotonically increasing integer local to p_i. For example, proposer p_i places the first command that it receives in vertex $(p_i, 0)$, the next command in vertex $(p_i, 1)$, the next in $(p_i, 2)$, and so on. The proposer then performs a round trip of

communication with the dependency service. It sends v_x and x to the dependency service, and the dependency service replies with the dependencies $\text{deps}(v_x)$. For now, we leave this process abstract. We'll explain how the dependency service computes dependencies in Section 4.2.

- **(4) and (5)** The proposer p_i then executes Phase 2 of Paxos with the acceptors, proposing that the value $(x, \text{deps}(v_x))$ be chosen in the instance of Paxos associated with vertex $v_x = (p_i, m)$. This is analogous to a MultiPaxos leader running Phase 2, proposing the command x be chosen in the instance of Paxos associated with log entry m.

  Recall from Section 2 that the Paxos proposer executing round 0 can safely bypass Phase 1. By design, we predetermine that the proposer p_i leads round 0 for vertices of the form (p_i, m). This is why p_i can safely bypass Phase 1 and immediately execute Phase 2.

  In the normal case, p_i gets the value $(x, \text{deps}(v_x))$ chosen in vertex v_x. It is also possible that some other proposer erroneously concluded that p_i had failed and proposed some other value in vertex v_x, but we discuss this scenario later.

- **(6)** The proposer p_i broadcasts v_x, x, and $\text{deps}(v_x)$ to all of the replicas. The replicas add vertex v_x to their conflict graph with command x and with edges to the vertices in $\text{deps}(v_x)$. The replicas execute their conflict graphs as described in Section 3.

- **(7)** Once a replica executes command x, it sends the result of executing command x back to the client.

4.2 Dependency Service

The dependency service consists of $2f + 1$ dependency service nodes $d_1, \ldots, d_{2f+1}$. Every dependency service node maintains an acyclic conflict graph. These conflict graphs are similar but not equal to the conflict graph that Simple PPaxos ultimately executes.

When a proposer sends a vertex v_x with command x to the dependency service, it sends v_x and x to every dependency service node. When a dependency service node d_i receives v_x and x, it performs one of the following two actions depending on whether d_i's graph already contains vertex v_x.

- If d_i's conflict graph does not contain vertex v_x, then d_i adds vertex v_x to its graph with command x. d_i adds an edge from v_x to every other vertex v_y with command y if x and y conflict. Letting $\text{out}(v_x)$ be the set of vertices to which v_x has an edge, d_i then returns $\text{out}(v_x)$ to the proposer.

- Otherwise, if d_i's conflict graph already contains vertex v_x, then d_i does not modify its conflict graph. It immediately returns $\text{out}(v_x)$ to the proposer.

An example execution of a dependency service node is given in Figure 8.

When a proposer receives replies from $f + 1$ dependency service nodes, it takes the union of these responses as the value of $\text{deps}(v_x)$. For example, imagine $f = 1$ and a proposer receives dependencies $\{v_w, v_y\}$ from d_1 and dependencies $\{v_w, v_z\}$ from d_2. The proposer computes $\text{deps}(v_x) = \{v_w, v_y, v_z\}$. The dependency service maintains Invariant 3.

Invariant 3. If two conflicting commands x and y in vertices v_x and v_y yield dependencies $\text{deps}(v_x)$ and $\text{deps}(v_y)$ from the dependency service, then either $v_x \in \text{deps}(v_y)$ or $v_y \in \text{deps}(v_x)$ or both.

Proof. Consider conflicting commands x and y in vertices v_x and v_y with dependencies $\text{deps}(v_x)$ and $\text{deps}(v_y)$ computed by the dependency service. $\text{deps}(v_x)$ is the union of dependencies computed by $f + 1$ dependency service nodes D_x. Similarly, $\text{deps}(v_y)$ is the union of dependencies computed by $f + 1$ dependency service nodes D_y. Because $f + 1$ is a majority of $2f + 1$, D_x and D_y necessarily intersect. That is, there is some dependency service node d_i that is in D_x and D_y. d_i either received v_x or v_y first. If it received v_x first, then it returns v_x as a dependency of v_y, so $v_x \in \text{deps}(v_y)$. If it received v_y first, then it returns v_y as a dependency of v_x, so $v_y \in \text{deps}(v_x)$. $\square$

4.3 An Example

An example execution of Simple PPaxos with $f = 1$ is illustrated in Figure 9.

- In Figure 9a, proposer p_1 receives command x from a client, while proposer p_2 receives command y from a

client. The commands are placed in vertices v_x and v_y respectively.

- In Figure 9b, p_1 sends x in v_x to the dependency service, while p_2 concurrently sends y in v_y. Dependency service nodes d_1 and d_2 receive x and then y, so they compute $\text{deps}(v_x) = \emptyset$ and $\text{deps}(v_y) = \{v_x\}$. d_3, on the other hand, receives y and then x and computes $\text{deps}(v_x) = \{v_y\}$ and $\text{deps}(v_y) = \emptyset$

  p_1 receives $\emptyset$ from d_2 and $\{v_y\}$ from d_3. Two dependency service nodes form a majority, so p_1 computes $\text{deps}(v_x) = \{v_y\} \cup \emptyset = \{v_y\}$. Similarly, p_2 receives $\{v_x\}$ from d_2 and $\emptyset$ from d_3, so p_2 computes $\text{deps}(v_y) = \{v_x\} \cup \emptyset = \{v_x\}$. Note that p_1 and p_2 also receive responses from d_1, but proposers form dependencies from the first set of $f + 1$ dependency service nodes they hear from.

- In Figure 9c, p_1 executes Phase 2 of Paxos to get the value $(x, \{v_y\})$ chosen in vertex v_x. p_2 likewise gets the value $(y, \{v_x\})$ chosen in vertex v_y.

- In Figure 9d, the proposers broadcast their commands to the replicas. The replicas add v_x and v_y to their conflict graphs and execute the commands once they have received both. One or more of the replicas also sends the results of executing x and y back to the clients.

Note that the replicas' conflict graphs contain a cycle. This is because the dependency service nodes do not receive every command in the same order. In Figure 9, dependency service nodes d_2 and d_3 receive x and y in opposite orders, leading to the two commands depending on each other. It is tempting to enforce that every dependency service node receive every command in exactly the same order, but unfortunately, this would be tantamount to solving consensus [6].

4.4 Recovery

Imagine a proposer receives a command x from a client, places the command x in vertex v_x, sends v_x and x to the dependency service, and then crashes. Because a command and a set of dependencies have not been chosen in vertex v_x yet, we call v_x unchosen. It is possible that a command y chosen in vertex v_y depends on an unchosen vertex v_x. If vertex v_x remains forever unchosen, then the command y will never be executed. To avoid this liveness violation, if any replica notices that vertex v_x has been unchosen for some time, it notifies a proposer. The proposer then executes Phase 1 and Phase 2 of Paxos with the acceptors to get a **noop** chosen in vertex v_x without any dependencies. noop is a distinguished command that does not affect the state machine and does not conflict with any other command. An example of this execution is given in Figure 10.

Figure 8: In subfigures (a) – (e), we see the execution of a dependency service node d_i. (a) d_i receives command w in vertex v_w. d_i adds this vertex to its conflict graph and because there are no other vertices, it returns the dependencies $\text{deps}(v_w) = \emptyset$. (b) d_i receives command x in vertex v_x. d_i adds this vertex to its conflict graph. x conflicts with w, so d_i adds an edge from v_x to v_w and returns the dependencies $\text{deps}(v_x) = \{v_w\}$. (c) d_i receives command y in vertex v_y. d_i adds this vertex to its conflict graph. y conflicts with w and x, so d_i adds an edge from v_y to v_w and from v_y to v_x. It returns the dependencies $\text{deps}(v_y) = \{v_w, v_x\}$. (d) d_i receives command z in vertex v_z. d_i adds this vertex to its conflict graph. z conflicts with w and x, so d_i adds an edge from v_z to v_w and from v_z to v_x. It returns the dependencies $\text{deps}(v_z) = \{v_w, v_x\}$. (e) d_i receives command x in vertex v_x. d_i's graph already contains vertex v_x, so d_i returns the dependencies $\text{deps}(v_x) = \{v_w\}$ and does not modify its graph.

- In Figure 10a, proposer p_1 receives command x from a client. It places x in vertex v_x and sends v_x and x to the dependency service. Shortly after, it fails.

- In Figure 10b, proposer p_2 receives command y from a client. It places y in v_y and contacts the dependency service. The dependency service nodes have already received x in v_x, so they compute $\text{deps}(v_y) = \{v_x\}$. p_2 then gets y chosen in vertex v_y with a dependency on v_x and broadcasts it to the replicas.

- In Figure 10c, the replicas cannot execute vertex v_y because it depends on the unchosen vertex v_x. After a timeout expires, replica r_1 notifies p_2 that the vertex has been unchosen for some time.

- In Figure 10d, p_2 executes Phase 1 and Phase 2 of Paxos in some round $r > 0$ with the acceptors to get the command noop chosen in vertex v_x without any dependencies. p_2 notifies the replicas, and the replicas place the noop in vertex v_x. The replicas execute their conflict graphs in reverse topological order. They execute the noop first (which has no effect) and then execute y.

  Note that p_2 must execute both phases of Paxos because it is not in round 0. This is necessary to ensure that no other value could have been chosen in v_x.

Note that a Simple PPaxos proposer recovers a command and proposes a noop by executing Paxos as normal. Simple PPaxos does not require an additional recovery protocol. Rather, commands and noops are proposed in the exact same way. This simplifies the protocol.

Also note that if a client does not receive a response for its pending request for a sufficiently long period of time, it resends its request. This means that if a client's command is replaced by a noop, the client will eventually re-propose the command.

4.5   Safety

To ensure that Simple PPaxos is safe, we must ensure that it maintains the consensus invariant and the dependency invariant. Simple PPaxos maintains the consensus invariant because it implements Paxos. The dependency invariant follows immediately from Invariant 3 and the fact that noops don't conflict with any other command.

5   Fast Paxos

Simple PPaxos is designed to be easy to understand, but as shown in Figure 9, it takes seven network delays (in the best case) between when a client proposes a command x and when a client receives the result of executing x. Call this duration of time the **commit time**. Generalized multi-leader protocols like EPaxos, Caesar, and Atlas all achieve a commit time of only four network delays in the best case. They do so by leveraging Fast Paxos [15].

Fast Paxos is a Paxos variant that allows clients to propose values directly to the acceptors without having to initially contact a proposer. Fast Paxos is an optimistic protocol. If all of the acceptors happen to receive the same command from the clients, then Fast Paxos has a commit time of only three network delays. This is called the fast path. However, if multiple clients concurrently propose different commands, and not all of the acceptors receive the same command, then the protocol reverts to a slow path and introduces two additional network delays to the commit time. In this section, we review a slightly simplified version of Fast Paxos.

5.1   Overview

Like Paxos, a Fast Paxos deployment consists of some number of clients, $f + 1$ proposers, and $2f + 1$ acceptors. We also

(a) p_1 receives command x; p_2 receives command y.

(b) The proposers contact the dependency service.

(c) The proposers contact the acceptors.

(d) The proposers notify the replicas.

Figure 9: An example execution of Simple PPaxos ($f = 1$).

include a set of $f + 1$ **learners**. These nodes are notified of the value chosen by Fast Paxos. Note that we use the term learner rather than replica because Fast Paxos is a consensus protocol and not a state machine replication protocol, so there are no state machine replicas. A Fast Paxos deployment is illustrated in Figure 11. Proposer and acceptor pseudocode are given in Algorithm 1 and Algorithm 2.

Like Paxos, Fast Paxos is divided into a number of integer valued rounds. The key difference is that round 0 of Fast Paxos is a special "fast round." A client can propose a value directly to an acceptor in round 0 without having to contact a proposer first. The normal case execution of Fast Paxos is illustrated in Figure 11a. The execution proceeds as follows:

- **(1)** When a client wants to propose a value v, it sends v to all of the acceptors.

- **(2)** When an acceptor receives a value v from a client, the acceptor ignores v if it has already received a message in some round $i \geq 0$. Otherwise, it votes for v by updating its state and sending a PHASE2B$\langle 0, v \rangle$ message to the proposer that leads round 0. This is shown in Algorithm 2 line 1 – line 4.

- **(3)** Let $\mathsf{maj}(n) = \lceil \frac{n+1}{2} \rceil$ be a majority of n. If the proposer that leads round 0 receives PHASE2B$\langle 0, v' \rangle$ messages from $f + \mathsf{maj}(f + 1)$ acceptors for the same value v', then v' is chosen, and the proposer notifies the learners. This is shown in Algorithm 1 line 1 – line 3. We consider what happens when not every value is the same in Section 5.2.

(a) p_1 receives x, talks to the dependency service, and fails. (b) p_2 receives y, gets it chosen with a dependency on v_x.

(c) A replica notifies p_2 that v_x is unchosen.

(d) p_2 gets a noop chosen in v_x.

Figure 10: An example execution of Simple PPaxos recovery ($f = 1$).

5.2 Recovery

Note that in Paxos, a value is chosen when $f + 1$ acceptors vote for it in some round i. In round 0 of Fast Paxos, a value is chosen when $f + \mathsf{maj}(f + 1)$ acceptors vote for it. The larger number of required votes is needed to ensure the safety of recovery, which we now describe.

Let p be the proposer leading round 0. Recovery is the process by which a proposer other than p gets a value chosen. For example, if p fails, some other proposer must take over and get a value chosen. Recovery is illustrated in Figure 11b.

- **(1) and (2)** A recovering proposer performs Phase 1 of Paxos with at least $f + 1$ acceptors in some round $i > 0$. This is shown in Algorithm 1 line 7 – line 9 and Algorithm 2 line 5 – line 7.

- **(3) and (4)** The recovering proposer receives PHASE1B$\langle i, vr, vv \rangle$ messages from $f + 1$ acceptors. Call this quorum of acceptors A. The proposer computes k as the largest received vr (line 11). This is the largest round in which any acceptor in A has voted. If $k = -1$ (line 12), then none of the acceptors have voted in any round less than i, so the proposer is free to propose an arbitrary value. This is the same as in Paxos. If $k > 0$ (line 14), then the proposer must propose the value vv proposed in round k. Again, this is the same as in Paxos. vv may have been chosen in round k, so the proposer is forced to propose it as well. If $k = 0$ (line 16), then there are two cases to consider.

  First, if $\mathsf{maj}(f + 1)$ of the acceptors in A have all voted for some value v' in round 0, then it's possible that v'

Figure 11: Example executions of Fast Paxos ($f = 2$). The leader of round 0 is adorned with a crown. Client requests are drawn in red. Phase 1 messages are drawn in blue. Phase 2 messages are drawn in green.

was chosen in round 0 (line 17). Specifically, if all f of the acceptors not in A voted for v' in round 0, then along with the $\mathsf{maj}(f+1)$ of acceptors in A who also voted for v' in round 0, there is a quorum of $f + \mathsf{maj}(f+1)$ acceptors who voted for v' in round 0. In this case, the proposer must propose v' as well since it might have been chosen. Second, if there does not exist $\mathsf{maj}(f+1)$ votes for any value v', then the proposer concludes that no value was chosen or every will be chosen in round 0, so it is free to propose an arbitrary value (line 19). Once the recovering proposer determines which value to propose, it gets the value chosen with the acceptors using the normal Phase 2 of Paxos.

Note that a value must receive at least $f + \mathsf{maj}(f+1)$ votes in round 0 to be chosen. If this number were any smaller, it would be possible for a recovering proposer to find two distinct values v' and v'' that *both* could have been chosen in round 0. In this case, the proposer cannot make progress. It cannot propose v' because v'' might have been chosen, and it cannot propose v'' because v' might have been chosen

More concretely, imagine an Fast Paxos deployment with $f = 2$ and five acceptors a_1, a_2, ..., a_5. Further imagine that a value is considered chosen after receiving votes from only 3 (i.e. $f + 1$) acceptors rather than the correct number of 4 (i.e. $f + \mathsf{maj}(f+1)$). Consider a proposer executing Phase 1 in round 1. It contacts a_3, a_4, and a_5. a_3 voted for value x in round 0; a_4 voted for value y in round 0; and a_5 didn't vote in round 0. What value should the proposer propose in Phase 2? Well, x was maybe chosen in round 0 (if a_1 and a_2 both voted for x in round 0), so the proposer has to propose x. However, y was also maybe chosen in round 0 (if a_1 and a_2 both voted for y in round 0), so the proposer

also has to propose y. The proposer can only propose one value, so the protocol gets stuck. By requiring $f + \mathsf{maj}(f+1)$ votes rather than $f + 1$ votes, we eliminate these situations. It's not possible for two values to both potentially have received $f + \mathsf{maj}(f+1)$ votes. There isn't enough acceptors for this to be possible.

- **(5)** The proposer notifies the learners of the chosen value.

5.3 Coordinated Recovery

Finally, we consider what happens when the proposer of round 0 receives $f + \mathsf{maj}(f+1)$ PHASE1B messages from the acceptors, but without all of them containing the same value v'. Naively, the proposer could simply perform a recovery, executing both phases of Paxos is some round $r > 0$. However, if we assign rounds to proposers in such a way that the proposer of round 0 is also the proposer of round 1, then we can take advantage of an optimization called **coordinated recovery**. This is illustrated in Figure 11c and proceeds as follows:

- **(1)** Multiple clients send distinct commands directly to the acceptors.

- **(2)** The acceptors receive and vote for the commands and send PHASE2B messages to the leader of round 0. However, not every acceptor receives the same value first, so not all the acceptors vote for the same value.

- **(3) and (4)** The proposer receives PHASE2B messages from $f + \mathsf{maj}(f+1)$ acceptors, but the acceptors have not all voted for the same value. At this point, the proposer could naively perform a recovery in round 1 by executing Phase 1 and then Phase 2 of Paxos. But, executing Phase 1 in round 1 is redundant, since the PHASE2B

Algorithm 1 Fast Paxos Proposer

State: a value v, initially null
State: a round i, initially -1
 1: **upon** receiving PHASE2B$\langle 0, v'\rangle$ from $f + \mathsf{maj}(f+1)$
     acceptors as the proposer of round 0 with $i = 0$ **do**
 2:     **if** every value of v' is the same **then**
 3:         v' is chosen, notify the learners
 4:     **else**
 5:         $i \leftarrow 1$
 6:         proceed to line 11 viewing every PHASE2B$\langle 0, v'\rangle$
             as a PHASE1B$\langle 1, 0, v'\rangle$
 7: **upon** recovery **do**
 8:     $i \leftarrow$ next largest round owned by this proposer
 9:     send PHASE1A$\langle i\rangle$ to the acceptors
10: **upon** receiving PHASE1B$\langle i, vr, vv\rangle$ from $f + 1$ acceptors
     do
11:     $k \leftarrow$ the largest vr in any PHASE1B$\langle i, vr, vv\rangle$
12:     **if** $k = -1$ **then**
13:         $v \leftarrow$ an arbitrary value
14:     **else if** $k > 0$ **then**
15:         $v \leftarrow$ the corresponding vv in round k
16:     **else if** $k = 0$ **then**
17:         **if** there are $\mathsf{maj}(f+1)$ PHASE1B$\langle i, 0, v'\rangle$
             messages for some value v' **then**
18:             $v \leftarrow v'$
19:         **else**
20:             $v \leftarrow$ an arbitrary value
21:     send PHASE2A$\langle i, v\rangle$ to the acceptors
22: **upon** receiving PHASE2B$\langle i\rangle$ from $f + 1$ acceptors **do**
23:     v is chosen, notify the learners

Algorithm 2 Fast Paxos Acceptor

State: the largest seen round r, initially -1
State: the largest round vr voted in, initially -1
State: the value vv voted for in round vr, initially null
 1: **upon** receiving value v from client **do**
 2:     **if** $r = -1$ **then**
 3:         $r, vr, vv \leftarrow 0, 0, v$
 4:         send PHASE2B$\langle 0, v\rangle$ to proposer of round 0
 5: **upon** receiving PHASE1A$\langle i\rangle$ from p with $i > r$ **do**
 6:     $r \leftarrow i$
 7:     send PHASE1B$\langle i, vr, vv\rangle$ to p
 8: **upon** receiving PHASE2A$\langle i, v\rangle$ from p with $i \geq r$ **do**
 9:     $r, vr, vv \leftarrow i, i, v$
10:     send PHASE2B$\langle i\rangle$ to p

other protocols.

6.1 The Protocol

Figure 12: An example execution of Fast PPaxos ($f = 1$). The four network delays are drawn in red.

Fast PPaxos is largely identical to Simple PPaxos with one key observation. Rather than implementing Paxos, Fast PPaxos implements Fast Paxos. This allows the protocol to reduce the commit time by overlapping communication with the dependency service (to compute dependencies) and communication with the acceptors (to implement consensus).

As shown in Figure 12, a Fast PPaxos deployment consists of $2f + 1$ dependency service nodes, $2f + 1$ Fast Paxos acceptors, $2f + 1$ Fast Paxos proposers, and $2f + 1$ replicas. These logical nodes are co-located on a set of $2f + 1$ servers, where every physical server executes one dependency service node, one acceptor, one proposer, and one replica. For example, in Figure 12, server 2 executes d_2, a_2, p_2, and r_2. As illustrated in Figure 12, the protocol executes as follows:

- **(1)** When a client wants to propose a state machine com-

messages in round 0 contain exactly the same information as the PHASE1B messages in round 1. Specifically, the proposer can view every PHASE2B$\langle 0, v'\rangle$ message as a proxy for a PHASE1B$\langle 1, 0, v'\rangle$ message. Thus, the proposer instead jumps immediately to Phase 2 in round 1 to get a value chosen (line 4 – line 6).

- **(5)** Finally, the proposer notifies the learners of the chosen value.

6 Fast PPaxos

In this section, we present a purely pedagogical protocol called **Fast PPaxos**. Fast PPaxos achieves a commit time of four network delays (compared to Simple PPaxos' seven), but Fast PPaxos is unsafe. It does not properly implement state machine replication. To understand why more complex protocols like EPaxos, Caesar, and Atlas work the way they do, it helps to understand why simpler protocols like Fast PPaxos don't work in the first place. Understanding why Fast PPaxos is unsafe leads to fundamental insights into these

mand x, it sends x to *any* of the proposers.

- **(2)** When a proposer p_i receives a command x, from a client, it places x in a vertex with globally unique vertex id $v_x = (p_i, m)$ where m is a monotonically increasing integer local to p_i. p_i then sends v_x and x to all of the dependency service nodes. Note that we predetermine that proposer p_i is the leader of round 0 and 1 of the Fast Paxos instance associated with vertex $v_x = (p_i, m)$.

- **(3)** When a dependency service node d_j receives a command x in vertex v_x, it computes a set of dependencies $\text{deps}(v_x)$ in the exact same way as in Simple PPaxos (i.e. d_j maintains an acyclic conflict graph). Unlike Simple PPaxos however, d_j does not send $\text{deps}(v_x)$ back to the proposer. Instead, it proposes to the co-located Fast Paxos acceptor a_j that the value $(x, \text{deps}(v_x))$ be chosen in the instance of Fast Paxos associated with vertex v_x in round 0.

- **(4)** Fast PPaxos acceptors are unmodified Fast Paxos acceptors. In the normal case, when an acceptor a_j receives value $(x, \text{deps}(v_x))$ in vertex $v_x = (p_i, m)$, it votes for the value and sends the vote to p_i.

- **(5)** Fast PPaxos proposers are unmodified Fast Paxos proposers. In the normal case, p_i receives $f + \text{maj}(f + 1)$ votes for value $(x, \text{deps}(v_x))$ in vertex v_x, so $(x, \text{deps}(v_x))$ is chosen. The proposer broadcasts the command and dependencies to the replicas. If p_i receives $f + \text{maj}(f + 1)$ votes, but they are not all for the same value, the proposer executes coordinate recovery (see Algorithm 1 line 4 – line 6).

- **(6)** Fast PPaxos replicas are identical to Simple PPaxos replicas. Replicas maintain and execute conflict graphs, returning the results of executing commands to the clients.

Note that Figure 12 illustrates six steps of execution, but the commit time is only four network delays (drawn in red). Communication between co-located components (e.g., between d_1 and a_1 and between p_1 and r_1) does not involve the network and therefore does not contribute to the commit time.

6.2   Recovery

As with Simple PPaxos, it is possible that a command y chosen in vertex v_y depends on an unchosen vertex v_x that must be recovered for execution to proceed. Fast PPaxos performs recovery in the same way as Simple PPaxos. If a replica detects that a vertex v_x has been unchosen for some time, it notifies a proposer. The proposer then executes a Fast Paxos recovery to get a noop chosen in vertex v_x with no dependencies.

6.3   Lack of Safety

We now demonstrate why Fast PPaxos is unsafe. Consider the execution of Fast PPaxos ($f = 2$) illustrated in Figure 13.

- In Figure 13a, proposer p_1 receives command x from a client. It places x in vertex v_x and sends v_x and x to the dependency service. d_1 and d_2 receive the message. They place x in their conflict graphs without any dependencies, and send the value $(x, \emptyset)$ to their co-located acceptors. a_1 and a_2 vote for $(x, \emptyset)$ in vertex v_x, but p_1 crashes before it receives any of these votes. The messages sent to d_3, d_4, and d_5 are dropped by the network.

- Similarly in Figure 13a, proposer p_5 receives a conflicting command y, p_5 sends v_y and y to d_4 and d_5, d_4 and d_5 propose $(y, \emptyset)$ to a_4 and a_5, a_4 and a_5 vote for the proposed values, and p_5 fails.

- In Figure 13b, p_2 recovers vertex v_x. To recover v_x, p_2 executes Phase 1 of Fast Paxos with acceptors a_1, a_2, and a_3. p_2 observes that a_1 and a_2 both voted for the value $(x, \emptyset)$ in round 0. Therefore, p_2 concludes that $(x, \emptyset)$ may have been chosen in round 0, so it proceeds to Phase 2 and gets the value $(x, \emptyset)$ chosen in vertex v_x (Algorithm 1 line 17). p_2 cannot propose any other value (e.g., a noop) because $(x, \emptyset)$ may have already been chosen. This is a core invariant of Paxos. From our omniscient view of the execution, we know that $(x, \emptyset)$ was never chosen, but from p_2's myopic view, it cannot make this determination and so is forced to propose $(x, \emptyset)$. This is a **critical point** in the execution, which we will discuss further in a moment.

- In Figure 13b, proposer p_4 recovers vertex v_y in much the same way as p_2 recovers v_x. p_4 observes that a_4 and a_5 voted for $(y, \emptyset)$ in round 0, so it is forced to get the value $(y, \emptyset)$ chosen.

- Finally in Figure 13b, proposers p_2 and p_4 broadcast $(x, \emptyset)$ and $(y, \emptyset)$ to all of the replicas. The replicas place x and y in their conflict graphs without edges between them. This violates the dependency invariant. x and y conflict, so there must be an edge between them. Without an edge, the replicas can execute x and y in different orders, causing their states to diverge.

What went wrong? When p_2 was recovering v_x, Fast Paxos forced it to choose $(x, \emptyset)$. However, the dependencies $\text{deps}(v_x) = \emptyset$ were *not* computed by a majority of the dependency service nodes. They were computed only by d_1 and d_2. This is what allowed conflicting commands x and y to be chosen without a dependency on each other.

This example illustrates a **fundamental tension** between preserving the consensus invariant (Invariant 1) and preserving the dependency invariant (Invariant 2). Maintaining the consensus invariant in isolation is easy (e.g., use Paxos), and

(a) p_1 receives x, talks to the dependency service, and fails. p_2 receives y, talks to the dependency service, and fails.

(b) p_2 recovers v_x with command x and no dependencies. p_4 recovers v_y with command y and no dependencies.

Figure 13: A Fast PPaxos bug ($f = 2$). Conflicting commands x and y are executed in different orders by different replicas.

maintaining the dependency invariant in isolation is also easy (e.g., use the dependency service). But, maintaining both invariants simultaneously is tricky.

When performing a recovery, like the one in our example above, a proposer is sometimes forced to propose a particular value (e.g., $(x, \emptyset)$) in order to properly implement consensus and simultaneously forced *not* to propose the value in order to correctly compute dependencies. Resolving the tension between the consensus and dependency invariants during recovery is the single most important and the single most challenging aspect of generalized multi-leader protocols like EPaxos, Caesar, and Atlas. All of these protocols have a similar structure and execution on the normal path. They all compute dependencies from a majority of servers, and they all execute Fast Paxos variants to get these dependencies chosen. If you understand the normal case execution of one of these protocols, it is not difficult to understand the others. The key feature that distinguishes the protocols is how they resolve the fundamental tension between implementing consensus and computing dependencies.

These protocols all take different approaches to resolving the tension. In the next two sections, we broadly categorize the approaches into two main techniques: *tension avoidance* and *tension resolution*. Tension avoidance involves cleverly manipulating quorum sizes to avoid the tension entirely. This approach is used by Basic EPaxos [21] and Atlas [10]. The second technique, tension resolution, is significantly more complicated and involves detecting and resolving the tension through various means.

7 Tension Avoidance

In this section, we explain how to implement a generalized multi-leader state machine replication protocol using **tension avoidance**. The key idea behind tension avoidance is to avoid the tension between the consensus and dependency invariants

entirely. By manipulating quorum sizes in clever ways, we can ensure that whenever a proposer is forced to propose a set of dependencies $\text{deps}(v_x)$, this set of dependencies is guaranteed to satisfy the dependency invariant.

We first introduce Unanimous PPaxos, a simple protocol that implements tension avoidance. We then explain how Basic EPaxos and Atlas can be expressed as two optimized variants of Unanimous PPaxos.

7.1 Unanimous PPaxos

A Fast PPaxos deployment consists of $2f + 1$ servers. A proposer communicates with $f + 1$ acceptors in Phase 1 called a **Phase 1 quorum**, $f + \text{maj}(f + 1)$ acceptors in Phase 2 of round 0 called a **fast Phase 2 quorum**, and $f + 1$ acceptors in Phase 2 of rounds greater than 0 called a **classic Phase 2 quorum**. If we adjust the sizes of these quorums, we can avoid the tension between implementing consensus and computing dependencies. In [11], Howard et. al prove that Fast Paxos is safe so long as the following two conditions are met.

1. Every Phase 1 quorum and every classic Phase 2 quorum intersect. That is, for every Phase 1 quorum Q and for every classic Phase 2 quorum Q', $Q \cap Q' \neq \emptyset$.

2. Every Phase 1 quorum and every pair of fast Phase 2 quorums intersect. That is, for every Phase 1 quorum Q and for every pair of fast Phase 2 quorum Q', Q'', $Q \cap Q' \cap Q'' \neq \emptyset$.

Unanimous PPaxos takes advantage of this result and increases the size of fast Phase 2 quorums. Specifically, Unanimous PPaxos is identical to Fast PPaxos except with fast Phase 2 quorums of size $2f + 1$. Unanimous PPaxos proposer pseudocode is given in Algorithm 3. It is identical to the pseudocode of a Fast Paxos proposer (Algorithm 1) except for a couple small changes highlighted in red.

Algorithm 3 Unanimous PPaxos Proposer. Changes to Algorithm 1 are highlighted in red.

State: a value v, initially null
State: a round i, initially -1

1: **upon** receiving PHASE2B$\langle 0, v' \rangle$ from all $2f + 1$ acceptors as the proposer of round 0 with $i = 0$ **do**
2:      **if** every value of v' is the same **then**
3:          v' is chosen, notify the learners
4:      **else**
5:          $i \leftarrow 1$
6:          $v \leftarrow$ an arbitrary value satisfying the dependency invariant
7:          send PHASE2A$\langle i, v \rangle$ to the acceptors
8: **upon** recovery **do**
9:      $i \leftarrow$ next largest round owned by this proposer
10:      send PHASE1A$\langle i \rangle$ to the acceptors
11: **upon** receiving PHASE1B$\langle i, vr, vv \rangle$ from $f + 1$ acceptors **do**
12:      $k \leftarrow$ the largest vr in any PHASE1B$\langle i, vr, vv \rangle$
13:      **if** $k = -1$ **then**
14:          $v \leftarrow$ an arbitrary value satisfying the dependency invariant
15:      **else if** $k > 0$ **then**
16:          $v \leftarrow$ the corresponding vv in round k
17:      **else if** $k = 0$ **then**
18:          **if** all $f + 1$ messages are of the form PHASE1B$\langle i, 0, v' \rangle$ for some value v' **then**
19:              $v \leftarrow v'$
20:          **else**
21:              $v \leftarrow$ an arbitrary value satisfying the dependency invariant
22:      send PHASE2A$\langle i, v \rangle$ to the acceptors
23: **upon** receiving PHASE2B$\langle i \rangle$ from $f + 1$ acceptors **do**
24:      v is chosen, notify the learners

Unlike Fast PPaxos, Unanimous PPaxos is safe. The critical change is on line 18. With fast Phase 2 quorums of size $2f + 1$ (line 1), a recovering proposer knows that a value v' may have been chosen in round 0 only if all $f + 1$ acceptors that it communicates with in Phase 1 voted for v' in round 0. If even a single acceptor did not vote for v' in round 0, then v' could not have received a unanimous vote and therefore was not chosen in round 0.

With Fast PPaxos, a proposer executing line 17 of Algorithm 1 is forced to propose a value $(x, \mathrm{deps}(v_x))$ if $\mathsf{maj}(f + 1)$ acceptors voted for it in round 0, but the dependencies $\mathrm{deps}(v_x)$ may have only been computed by $\mathsf{maj}(f + 1)$ dependency service nodes, violating the dependency invariant. This is exactly what happened in Figure 13. Unanimous PPaxos avoids the tension entirely because a proposer is only forced to propose a value $(x, \mathrm{deps}(v_x))$ if $f + 1$ acceptors voted for it in round 0. Now, we are guaranteed that $\mathrm{deps}(v_x)$ was computed

by a majority (i.e. $f + 1$) of the dependency service nodes. Thus, Unanimous PPaxos safely maintains the consensus and dependency service invariants.

The obvious disadvantage of Unanimous PPaxos is the protocol's large quorum sizes. In order to get a command chosen, a proposer has to perform a round trip of communication with *every* acceptor. This not only slows down the protocol in the normal case, it also decreases the protocol's ability to remain live in the face of faults. If even a single acceptor fails, the protocol grinds to a halt. This problem can be partially fixed by using more flexible quorums (like what Atlas [10] does) or by using a tension resolving protocol (see Section 7).

We now present two independent optimizations that improve the performance of Unanimous PPaxos. These optimizations were introduced in EPaxos [22] and Atlas [10].

7.2 Basic EPaxos Optimization

Unanimous PPaxos has a lower commit time than Simple PPaxos (4 network delays instead of 7), but has larger fast Phase 2 quorums ($2f + 1$ acceptors instead of $f + 1$). We now discuss an optimization, used by Basic EPaxos [22], to reduce the fast Phase 2 quorum size to $2f$.

Figure 14: An example execution of Unanimous PPaxos ($f = 2$) with the Basic EPaxos optimization. The messages introduced by the optimization are drawn in red.

An execution of Unanimous PPaxos with the Basic EPaxos optimization is shown in Figure 14. We walk through the execution, highlighting the optimization's key changes. We assume $f > 1$ for now. Later, we discuss the case when $f = 1$.

- **(1)** When a client wants to propose a state machine command x, it sends x to *any* of the proposers.

- **(2)** When a proposer p_i receives a command x, from a client, it places x in a vertex with globally unique vertex id $v_x = (p_i, m)$. **Change:** p_i then sends v_x and x to the

co-located dependency service node d_i. It does not yet communicate with the other dependency service nodes.

- **(3) Change:** When d_i receives v_x and x, it computes the dependencies $\text{deps}(v_x)_i$ as usual using its acyclic conflict graph. d_i then sends v_x, x, and $\text{deps}(v_x)_i$ to all the other dependency service nodes.

- **(4)** When a dependency service node d_j receives v_x, x, and $\text{deps}(v_x)_i$, it computes the dependencies $\text{deps}(v_x)_j$ as usual using its acyclic conflict graph. **Change:** Then, d_j proposes to its co-located acceptor a_j that the value $(x, \text{deps}(v_x)_i \cup \text{deps}(v_x)_j)$ be chosen in vertex v_x in round 0. d_j combines the dependencies that it computed with the dependencies computed by d_i.

- **(5)** The acceptors are unchanged. In the normal case, when an acceptor a_j receives value $(x, \text{deps}(v_x))$ in vertex $v_x = (p_i, m)$, it votes for the value and sends the vote to p_i.

- **(6) and (7) Change:** In Unanimous PPaxos, a value $v = (x, \text{deps}(v_x))$ is considered chosen in round 0 if all $2f + 1$ acceptors vote for v in round 0. With the Basic EPaxos optimization, we only require $2f$ votes, and the act of choosing a value in round 0 is made more explicit. Specifically, if p_i receives $2f$ votes for value $v = (x, \text{deps}(v_x))$ in round 0, including a vote from a_i, then it sends v to the co-located acceptor a_i. When a_i receives v and is still in round 0 (i.e. $r = 0$ on Algorithm 2 line 0), then it records v as chosen and responds to p_i. The value v is considered chosen precisely when it is recorded by the acceptor. In the future a_i responds to every PHASE1A and PHASE2A message with a notification that v is chosen. If a_i receives v but is already in a round larger than 0 (i.e. $r > 0$), then it ignores v and sends a negative acknowledgement back to p_i. Note that these messages are all performed locally on the server hosting p_i and do not incur any network delay.

- **(8)** In the normal case, p_i learns that v was successfully chosen by a_i and it broadcasts v to all the acceptors. If p_i receives a negative acknowledgement, it performs coordinated recovery as in Unanimous PPaxos.

- **(9)** The replicas are unchanged. They maintain and execute conflict graphs, returning the results of executing commands to the clients.

In addition to these changes made to the normal path of execution, the Basic EPaxos optimization also introduces a key change to the recovery procedure. Specifically, we replace line 18 – line 21 in Algorithm 3 with the following procedure.

Assume that proposer p is recovering vertex $v_x = (p_j, m)$ in round $i > 0$. Either p received a message from a_j or it did not. We consider each case separately. First, assume that p does receive a message from a_j. If p receives a message indicating that some value v' has already been chosen in round 0, then p can terminate the recovery immediately. Otherwise, p receives a PHASE1B message from a_j. From this, p can conclude that a_j is in a round at least as large as i and therefore did not and will not record any value v' chosen in round 0. Because of this, p is safe to propose any value that satisfies the dependency invariant (e.g., $(\text{noop}, \emptyset)$).

Otherwise, p does not receive a message from a_j. If p receives f PHASE1B$\langle i, 0, v' \rangle$ messages for the same value $v' = (x, \text{deps}(v_x))$, then v' may have been chosen in round 0, so p must propose v' in order to maintain the consensus invariant. Note that $\text{deps}(v_x)$ also satisfies the dependency invariant despite the fact that p only received $\text{deps}(v_x)$ from f, as opposed to $f + 1$, dependency service nodes. This is because the dependency service nodes that are not co-located with d_j all propose dependencies that include the dependencies computed by d_j. Therefore, p determines that $\text{deps}(v_x)$ is the union of $f + 1$ dependencies and maintains the dependency invariant. If p does not receive f PHASE1B$\langle i, 0, v' \rangle$ for the same value v', then p concludes no value was chosen or will be chosen in round 0, so p is safe to propose any value that satisfies the dependency invariant.

Note that when $f = 1$ and $n = 3$, Phase 1 quorums, classic Phase 2 quorums, and fast Phase 2 quorums are all of size 2. This does *not* satisfy the conditions outlined by Howard et. al [11]. As a result, our protocol as stated is not safe for $f = 1$. The reason is that a recovering proposer may receive two different values in two separate PHASE1B messages from the two non-leader acceptors with values v' and v''. In this situation, the proposer is unable to determine which value to propose. Thankfully, we can avoid this situation by having the leader send only to $2f$ acceptors rather than to all $2f + 1$ acceptors.

Ignoring some minor cosmetic differences, Unanimous PPaxos with the Basic EPaxos optimization is roughly equivalent to Basic EPaxos [22].

7.3 Atlas Optimization

In the best case, also called the fast path, Unanimous PPaxos achieves a commit time of four network delays. As shown in line 2 of Algorithm 3, a proposer executes the fast path only when every single acceptor votes for the exact same set of dependencies. As we saw in Figure 13, if any two dependency service nodes receive conflicting commands in different orders, their computed dependencies will not be the same. If a proposer does not receive a unanimous vote, it executes coordinated recovery, adding two more network delays to the commit time.

Atlas [10] introduces the following optimization to relax the requirement of a unanimous vote and increase the probability of a proposer executing the fast path. Let $X_1, \ldots, X_{2f+1}$ be $2f + 1$ sets. Let $\text{popular}(X_1, \ldots, X_{2f+1}) =$

$\{x \mid x$ appears in at least $f + 1$ of the sets$\}$.

We change line 2 as follows. When a proposer receives dependencies $\text{deps}(v_x)_1, \ldots, \text{deps}(v_x)_{2f+1}$ from the $2f + 1$ acceptors, it executes the fast path with dependencies $\text{deps}(v_x) = \text{deps}(v_x)_1 \cup \cdots \cup \text{deps}(v_x)_{2f+1}$ if $\text{deps}(v_x) = \text{popular}(\text{deps}(v_x)_1, \ldots, \text{deps}(v_x)_{2f+1})$. That is, the proposer takes the fast path only if every dependency v_y computed by any of the dependency service nodes was computed by a majority of the dependency service nodes.

We also simplify line 18 – line 21. If a recovering proposer receives $f + 1$ sets of dependencies, it proposes their union. Otherwise, it proposes an arbitrary value. This is safe because a set of dependencies $\text{deps}(v_x)$ can be chosen in round 0, only if every dependency in $\text{deps}(v_x)$ was computed by a majority of the dependency service nodes. Thus, every such element will appear in at least one of the $f + 1$ dependency sets. Thus, the recovering proposer is sure to propose a dependency set if it was previously chosen (maintaining the consensus invariant), and it also proposes the union of $f + 1$ dependency sets (maintaining the dependency invariant).

Atlas [10] is roughly equivalent to Unanimous PPaxos with the Basic EPaxos optimization, the Atlas optimization, and the flexible constraints on quorum sizes outlined in [11].

8 Tension Resolution

The advantage of tension avoidance is that it is simple. The disadvantage is that it requires large fast Phase 2 quorums. In this section, we explain how to implement a generalized multi-leader state machine replication protocol using **tension resolution**. Tension resolution is significantly more complicated than tension avoidance, but it does not require large fast Phase 2 quorums.

Instead of avoiding the tension between the consensus and dependency invariant, tension resolution uses additional machinery to resolve it when it arrives. Consider a scenario where a proposer p is forced to propose a set of $\text{deps}(v_x)$ in round i to maintain the consensus invariant because $\text{deps}(v_x)$ may have been chosen in a previous round. Simultaneously, p is forced not to propose $\text{deps}(v_x)$ because it cannot guarantee that $\text{deps}(v_x)$ was computed by a majority of the dependency service nodes. This is the moment of tension that tension avoidance avoids. Tension resolution, on the other hand, allows this to happen. When it does, the proposer p leverages additional machinery built into the protocol to determine either that (a) $\text{deps}(v_x)$ was not chosen or (b) $\text{deps}(v_x)$ was computed by a majority of dependency service nodes.

We introduce Majority Commit PPaxos, a protocol that implements tension resolution. We then discuss the protocol's relationship with EPaxos [22] and Caesar [10].

8.1 Pruned Dependencies

Before we discuss Majority Commit PPaxos, we introduce the notion of pruned dependencies. Imagine a proposer p sends command x to the dependency service in vertex v_x, and the dependency service computes the dependencies $\text{deps}(v_x)$. Let $v_y \in \text{deps}(v_x)$ be one of v_x's dependencies. To maintain the dependency invariant, all of the protocols that we have discussed thus far would get v_x chosen with a dependency on v_y, but this is not always necessary.

Assume that that the proposer p knows that v_y has been chosen with command y and dependencies $\text{deps}(v_y)$. Further assume that $v_x \in \text{deps}(v_y)$. That is, v_y has already been chosen with a dependency on v_x. In this case, there is no need for v_x to depend on v_y. The dependency invariant asserts that if two vertices v_a and v_b are chosen with conflicting commands a and b, then either $v_a \in \text{deps}(v_b)$ or $v_b \in \text{deps}(v_a)$. Thus, in our example, if v_y has already been chosen with a dependency on v_x, then there is no need to propose v_x with a dependency on v_y. Similarly, if v_y has been chosen with noop as part of a recovery, then there is no need to propose v_x with a dependency on v_y because x and noop do not conflict.

Let $\text{deps}(v_x)$ be a set of dependencies computed by the dependency service. Let $P \subseteq \text{deps}(v_x)$ be a set of vertices v_y such that v_y has been chosen with noop or v_y has been chosen with $v_x \in \text{deps}(v_y)$. We call $\text{deps}(v_x) - P$ the **pruned dependencies** of v_x with respect to P. Majority Commit PPaxos maintains Invariant 4, the **pruned dependency invariant**. The pruned dependency invariant is a relaxation of the dependency invariant. If a protocol maintains the pruned dependency invariant, it is guaranteed to maintain the dependency invariant.

Invariant 4 (Pruned Dependency Invariant)**.** For every vertex v_x, either $(\text{noop}, \emptyset)$ is chosen in v_x or $(x, \text{deps}(v_x) - P)$ is chosen in v_x where $\text{deps}(v_x)$ are dependencies computed by the dependency service and where $\text{deps}(v_x) - P$ are the pruned dependencies of v_x with respect to some set P.

8.2 Majority Commit PPaxos

For clarity of exposition, we first introduce a version of Majority Commit PPaxos that can sometimes deadlock. Later, we modify the protocol to eliminate the possibility of deadlock.

Majority Commit PPaxos is identical to Fast PPaxos except for the following two modifications. First, every Fast Paxos acceptor maintains a conflict graph in exactly the same way as the replicas do. That is, when an acceptor learns that a vertex v_x has been chosen with command x and dependencies $\text{deps}(v_x)$), it adds v_x to its conflict graph with command x and with edges to every vertex in $\text{deps}(v_x)$. We will see momentarily that whenever a Majority Commit PPaxos proposer sends a PHASE2A message to the acceptors with value $v = (x, \text{deps}(v_x) - P)$, the proposer also sends P and all of the commands and dependencies chosen in in the vertices in

P. Thus, when an acceptor receives a PHASE2A message, it updates its conflict graph with the values chosen in *P*. Second and more substantially, a proposer executes a significantly more complex recovery procedure. This is shown in Algorithm 4.

As with Fast PPaxos, if $k = -1$ (line 3), if $k > 1$ (line 6), or if $k = 0$ and there does not exist $\mathsf{maj}(f + 1)$ matching values (line 29), recovery is straightforward.

Otherwise, there does exist a $v' = (x, \mathsf{deps}(v_x))$ voted for by at least $\mathsf{maj}(f + 1)$ acceptors in round 0 (line 9). As with Fast PPaxos, v' may have been chosen in round 0, so the proposer *must* propose v' in order to maintain the consensus invariant. But $\mathsf{deps}(v_x)$ may not be the union of dependencies computed by $f + 1$ dependency service nodes, so the proposer is simultaneously forced *not* to propose v' in order to maintain the dependency invariant. Unanimous PPaxos avoided this tension by increasing the size of fast Phase 2 quorums. Majority Commit PPaxos instead resolves the tension by performing a more sophisticated recovery procedure. In particular, the proposer does a bit of detective work to conclude either that v' was definitely not chosen in round 0 (in which case, the proposer can propose a different value) or that $\mathsf{deps}(v_x)$ happens to be a pruned set of dependencies (in which case, proposer is safe to propose v').

On line 11 and line 12, the proposer sends v_x and x to the dependency service nodes co-located with the acceptors in A (i.e. the $f + 1$ acceptors from which the proposer received PHASE1B messages). The proposer then computes the union of the returned dependencies, called $\mathsf{deps}(v_x)_A$. Note that this communication can be piggybacked on the PHASE1A messages that the proposer previously sent to avoid the extra round trip of communication. Also note that $\mathsf{deps}(v_x)$ was returned by $\mathsf{maj}(f + 1)$ nodes in A, so $\mathsf{deps}(v_x)$ is a subset of $\mathsf{deps}(v_x)_A$.

Next, the proposer enters a for loop in an attempt to prune $\mathsf{deps}(v_x)_A$ until it is equal to $\mathsf{deps}(v_x)$. That is, the proposer attempts to construct a set of vertices P such that $\mathsf{deps}(v_x) = \mathsf{deps}(v_x)_A - P$ is a set of pruned dependencies. For every, $v_y \in \mathsf{deps}(v_x)_A - \mathsf{deps}(v_x)$, the proposer first recovers v_y if it does not know if a value has been chosen in vertex v_y (line 17). After recovering v_y, assume the proposer learns that v_y is chosen with command y and dependencies $\mathsf{deps}(v_y)$. If $y = \mathsf{noop}$ or if $v_x \in \mathsf{deps}(v_y)$, then the proposer can safely prune v_y from $\mathsf{deps}(v_x)_A$, so it adds v_y to P (line 19).

Otherwise, the proposer contacts some quorum A' of acceptors (line 21). If any acceptor a_j in A' knows that vertex v_x has already been chosen, then the proposer can abort the recovery of v_x and retrieve the chosen value directly from a_j (line 23). Otherwise, the proposer concludes that no value was chosen in v_x in round 0 and is free to propose any value that maintains the dependency invariant (line 25). We will explain momentarily why the proposer is able to make such a conclusion. It is not obvious. Note that the proposer can piggyback its communication with A' on its PHASE1A messages.

Finally, if the proposer exits the for loop, then it has successfully pruned $\mathsf{deps}(v_x)_A$ into $\mathsf{deps}(v_x)_A - P = \mathsf{deps}(v_x)$ and can safely propose it without violating the consensus or pruned dependency invariant (line 28). As described above, when the proposer sends a PHASE2A message with value v', it also includes the values chosen in every vertex in P.

We now return to line 25 and explain how the proposer is able to conclude that v' was not chosen in round 0. On line 25, the proposer has already concluded that v_y was not chosen with noop and that $v_x \notin \mathsf{deps}(v_y)$. By the pruned dependency invariant, $\mathsf{deps}(v_y) = \mathsf{deps}(v_y)_D - P'$ is a set of pruned dependencies where $\mathsf{deps}(v_y)_D$ is a set of dependencies computed by a set D of $f + 1$ dependency service nodes. Because $v_x \notin \mathsf{deps}(v_y)_D - P'$, either $v_x \notin \mathsf{deps}(v_y)_D$ or $v_x \in P'$.

v_x cannot be in P' because if v_y were chosen with dependencies $\mathsf{deps}(v_y)_D - P'$, then some quorum of acceptors would have received P' and learned that v_x was chosen. But, when the proposer contacted the quorum A' of acceptors, none knew that v_x was chosen, and any two quorums intersect.

Thus, $v_x \notin \mathsf{deps}(v_y)_D$. Thus, every dependency service node in D processed instance v_y before instance v_x. If not, then a dependency service node in D would have computed v_x as a dependency of v_y. However, if every dependency service node in D processed v_y before v_x, then there cannot exist a fast Phase 2 quorum of dependency service nodes that processed v_x before v_y. In this case, $v' = (x, \mathsf{deps}(v_x))$ could not have been chosen in round 0 because it necessitates a fast Phase 2 quorum of dependency service nodes processing v_x before v_y because $v_y \notin \mathsf{deps}(v_x)$.

8.3 Ensuring Liveness

Majority Commit PPaxos is safe, but it is not very live. There are certain failure-free situations in which Majority Commit PPaxos can permanently deadlock. The reason for this is line 17 in which a proposer defers the recovery of one vertex for the recovery of another. There exist executions of Majority Commit PPaxos with a chain of vertices $v_1, \ldots, v_m$ where the recovery of every vertex v_i depends on the recovery of vertex $v_{i+1 \bmod m}$.

We now modify Majority Commit PPaxos to prevent deadlock. First, we change the condition under which a value is considered chosen on the fast path. A proposer considers a value $v = (x, \mathsf{deps}(v_x))$ chosen on the fast path if a fast Phase 2 quorum F of acceptors voted for v in round 0 *and* for every vertex $v_y \in \mathsf{deps}(v_x)$, there exists a quorum $A \subseteq F$ of $f + 1$ acceptors that knew v_y was chosen at the time of voting for v. Second, when an acceptor a_i sends a PHASE2B vote in round 0 for value $v = (x, \mathsf{deps}(v_x))$, a_i also includes the subset of vertices in $\mathsf{deps}(v_x)$ that a_i knows are chosen, as well as the values chosen in these vertices. Third, proposers execute Algorithm 4 but with the lines of code shown in Algorithm 5 inserted after line 10.

We now explain Algorithm 5. On line 11, the proposer

Algorithm 4 Majority Commit PPaxos Proposer. Pseudocode for initiating recovery and handling PHASE2B messages is ommitted because it is identical to the pseudocode in Algorithm 1.

State: a value v, initially null
State: a round i, initially -1

1: **upon** receiving PHASE1B$\langle i, vr, vv \rangle$ from $f + 1$ acceptors A **do**
2:     $k \leftarrow$ the largest vr in any PHASE1B$\langle i, vr, vv \rangle$
3:     **if** $k = -1$ **then**
4:         $v \leftarrow$ an arbitrary value satisfying the dependency invariant
5:         send PHASE2A$\langle i, v \rangle$ to the acceptors
6:     **else if** $k > 0$ **then**
7:         $v \leftarrow$ the corresponding vv in round k
8:         send PHASE2A$\langle i, v \rangle$ to the acceptors
9:     **else if** there are maj$(f + 1)$ PHASE1B$\langle i, 0, v' \rangle$ messages for some value v' **then**
10:         $(x, \text{deps}(v_x)) \leftarrow v'$
11:         send v_x and x to the dependency service nodes co-located with the acceptors in A
12:         $\text{deps}(v_x)_A \leftarrow$ the union of the dependencies returned by these dependency service nodes
13:
14:         $P \leftarrow \emptyset$
15:         **for** $v_y \in \text{deps}(v_x)_A - \text{deps}(v_x)$ **do**
16:             **if** we don't know if v_y is chosen **then**
17:                 recover v_y, blocking until v_y is recovered
18:             **if** v_y chosen with noop or with $v_x \in \text{deps}(v_y)$ **then**
19:                 $P \leftarrow P \cup \{v_y\}$
20:             **else**
21:                 contact a quorum A' of acceptors
22:                 **if** an acceptor in A' knows v_x is chosen **then**
23:                     abort recovery; v_x has already been chosen
24:                 **else**
25:                     $v \leftarrow$ an arbitrary value satisfying the dependency invariant
26:                     send PHASE2A$\langle i, v \rangle$ to the acceptors
27:         $v \leftarrow v'$
28:         send PHASE2A$\langle i, v \rangle$ and the values chosen in P to at least $f + 1$ acceptors
29:     **else**
30:         $v \leftarrow$ an arbitrary value satisfying the dependency invariant
31:         send PHASE2A$\langle i, v \rangle$ to the acceptors

---

computes the subset $M \subseteq A$ of acceptors that voted for v' in round 0. On line 12, the proposer determines whether there exists some instance $v_y \in \text{deps}(v_x)$ such that no acceptor in M knows that v_y is chosen. If such an v_y exists, then v' was not chosen in round 0. To see why, assume for contradiction that v' was chosen in round 0. Then, there exists some fast Phase 2 quorum F of acceptors that voted for v' in round 0, and there exists some quorum $A' \subseteq F$ of acceptors that know v_y has been chosen. However, A and A' intersect, but no acceptor in A both voted for v' in round 0 and knows that v_y was chosen. This is a contradiction. Thus, the proposer is free to propose any value satisfying the dependency invariant.

Next, it's possible that the proposer was previously recovering instance v_z with value $(z, \text{deps}(v_z))$ and executed line 17 of Algorithm 4, deferring the recovery of instance v_z until after the recovery of instance v_x. If so and if $v_z \in \text{deps}(v_x)$,

then some acceptor $a_j \in M$ knows that v_z is chosen. Thus, the proposer can abort the recovery of instance v_z and retrieve the chosen value directly from a_j (line 16). Otherwise, $v_z \notin \text{deps}(v_x)$. In this case, no value was chosen in round 0 of instance v_z, so the proposer is free to propose any value satisfying the pruned dependency invariant in instance v_z. Here's why. $v_z \notin \text{deps}(v_x)$, so every dependency service node co-located with an acceptor in M processed v_x before v_z. $|M| \geq \text{maj}(f + 1)$, so there strictly fewer than $f + \text{maj}(f + 1)$ remaining dependency service nodes that could have processed v_z before v_x. If the proposer was recovering instance v_z but deferred to the recovery of instance v_x, then $v_x \notin \text{deps}(v_z)$. In order for v_z to have been chosen in round 0 with $v_x \notin \text{deps}(v_y)$, it requires that at least $f + \text{maj}(f)$ dependency service nodes processed v_z before v_x, which we just concluded is impossible. Thus, v_z was not chosen in

Algorithm 5 Majority Commit PPaxos proposer modification to prevent deadlock.

11: $M \leftarrow$ the set of acceptors in A that voted for v' in round 0
12: **if** $\exists v_y \in \text{deps}(v_x)$ such that no acceptor in M knows that v_y is chosen **then**
13:    send any value satisfying the dependency invariant
14: **if** the proposer was recovering v_z and deferred to the recovery of v_x **then**
15:   **if** $v_z \in \text{deps}(v_x)$ **then**
16:     abort recovery of v_z; v_z has already been chosen
17:   **else**
18:     in vertex v_z, send any value satisfying the dependency invariant

round 0.

Majority Commit PPaxos is deadlock free for the following reason. If a proposer is recovering instance v_z and defers to the recovery of instance v_x, then either the proposer will recover v_x using line 12 of Algorithm 5 or the proposer will recover v_z using line 16 or line 18 of Algorithm 5. In either case, any potential deadlock is avoided.

8.4 EPaxos and Caesar

EPaxos [22] and Caesar [3] are two generalized multi-leader protocols that implement tension resolution. EPaxos is very similar Majority Commit PPaxos with the Basic EPaxos optimization from Section 7.2 used to reduce fast Phase 2 quorum sizes by 1. Majority Commit PPaxos and EPaxos both prune dependencies and perform a recursive recovery procedure with extra machinery to avoid deadlocks. Caesar improves on EPaxos in two dimensions. First, much like Atlas, a Caesar proposer does not require that a fast Phase 2 quorum of acceptors vote for the exact same value in order to take the fast path. Second, Caesar avoids a recursive recovery procedure. Caesar accomplishes this using a combination of logical timestamps and carefully placed barriers in the protocol.

9 Related Work

A Family of Leaderless Generalized Consensus Algorithms In [19], Losa et al. propose a generic generalized consensus algorithm that is structured as the composition of a generic dependency-set algorithm and a generic map-agreement algorithm. The invariants of the dependency-set and map-agreement algorithm are very similar to the consensus and dependency invariants, and the example implementations of these two algorithms in [19] form an algorithm similar to Simple PPaxos. Our paper builds on this body of work by introducing Fast PPaxos, Unanimous PPaxos, and Majority Commit PPaxos. We also identify the tension between the two invariants as the key distinguishing feature of

most protocols and taxonimize existing protocols by how they handle the tension.

Generalized Paxos and GPaxos Generalized Paxos [14] and GPaxos [26] are generalized protocols but are not fully multi-leader. Clients send commands directly to acceptors, behaving very much like a leader. However, in the face of collisions, Generalized Paxos and GPaxos rely on a single leader to resolve the collision. This single leader becomes a bottleneck in high contention workloads and prevents scaling.

SpecPaxos, NOPaxos, CURP SpecPaxos [25] and NOPaxos [17] combine speculative execution and ideas from Fast Paxos in order to reduce commit delay as low as two network delays. CURP [24] further introduces generalization, allowing commuting commands to be executed in any order. These protocols represent yet another point in the design space of state machine replication protocols. As the commit delay decreases, the complexity of the protocols generally increases. We think this is an exciting avenue of research and hope that an improved understanding of generalized multi-leader protocols can accelerate research in this direction.

Mencius Mencius [20] is a multi-leader, non-generalized protocol in which MultiPaxos log entries are round-robin partitioned among a set of leaders. Because Mencius is not generalized, a log entry cannot be executed until *all* previous log entries have been executed. To ensure log entries are being filled in appropriately, Mencius leaders perform all-to-all communication between each other. Mencius is significantly less complex that generalized multi-leader protocols like EPaxos, Caesar, and Atlas. This demonstrates that much of the complexity of these protocols come from being generalized rather than being multi-leader, though both play a role.

Chain Replication Chain Replication [31] is a state machine replication protocol in which the set of state machine replicas are arranged in a totally ordered chain. Writes are propagated through the chain from head to tail, and reads are serviced exclusively by the tail. Chain Replication has high throughput compared to MultiPaxos because load is more evenly distributed between the replicas. This shows that the leader bottleneck can be addressed without necessarily having multiple leaders.

Scalog Scalog [9] is a replicated shared log protocol that achieves high throughput using a sophisticated form of batching. A client does not send values directly to a centralized leader for sequencing in the log. Instead, the client sends its values to one of a number of batchers. Periodically, the batchers' batches are sealed and assigned an id. This id is then sent

to a state machine replication protocol, like MultiPaxos, for sequencing. Like Mencius, Scalog represents a way to avoid a leader bottleneck without needing multiple leaders.

PQR, Harmonia, and CRAQ PQR [7], Harmonia [32], and CRAQ [28] all implement optimizations so that reads (i.e. state machine commands that do not modify the state of the state machine) can be executed without contacting a leader, while writes are still processed by the leader. An interesting direction of future work could explore whether or not these read optimizations could be applied to generalized multi-leader protocols.

10   Conclusion

In this paper, we explained, analyzed, and taxonomized generalized multi-leader state machine replication protocols. Our taxonomy of state machine replication protocols is summarized in Figure 15, and a summary of the generalized multi-leader protocols that we discuss in this paper is given in Table 2. We showed via Simple PPaxos that simple generalized multi-leader protocols do exist, but they have high commit time. Reducing the commit time with Fast PPaxos, we discovered the fundamental tension between implementing consensus and computing dependencies between commands. We taxonomized existing protocols according to whether they avoid the tension (like Unanimous PPaxos) or they resolve the tension (like Majority Commit PPaxos). Ultimately, we hope that the clarity we have brought to the space can encourage more industry adoption of generalized multi-leader protocols and can spur new academic innovations in this space.

References

[1] A brief introduction of tidb. https://pingcap.github.io/blog/2017-05-23-perconalive17/. Accessed: 2019-10-21.

[2] Raft replication in yugabyte db. https://www.yugabyte.com/resources/raft-replication-in-yugabyte-db/. Accessed: 2019-10-21.

[3] Balaji Arun, Sebastiano Peluso, Roberto Palmieri, Giuliano Losa, and Binoy Ravindran. Speeding up consensus by chasing fast decisions. In *Dependable Systems and Networks (DSN), 2017 47th Annual IEEE/IFIP International Conference on*, pages 49–60. IEEE, 2017.

[4] Jason Baker, Chris Bond, James C Corbett, JJ Furman, Andrey Khorlin, James Larson, Jean-Michel Leon, Yawei Li, Alexander Lloyd, and Vadim Yushprakh. Megastore: Providing scalable, highly available storage for interactive services. In *CIDR*, volume 11, pages 223–234, 2011.

[5] Mike Burrows. The chubby lock service for loosely-coupled distributed systems. In *Proceedings of the 7th symposium on Operating systems design and implementation*, pages 335–350. USENIX Association, 2006.

[6] Tushar D Chandra, Robert Griesemer, and Joshua Redstone. Paxos made live: an engineering perspective. In *Proceedings of the twenty-sixth annual ACM symposium on Principles of distributed computing*, pages 398–407. ACM, 2007.

[7] Aleksey Charapko, Ailidani Ailijiang, and Murat Demirbas. Linearizable quorum reads in paxos. In *11th USENIX Workshop on Hot Topics in Storage and File Systems (HotStorage 19)*, 2019.

[8] James C Corbett, Jeffrey Dean, Michael Epstein, Andrew Fikes, Christopher Frost, Jeffrey John Furman, Sanjay Ghemawat, Andrey Gubarev, Christopher Heiser, Peter Hochschild, et al. Spanner: Google's globally distributed database. *ACM Transactions on Computer Systems (TOCS)*, 31(3):8, 2013.

[9] Cong Ding, David Chu, Evan Zhao, Xiang Li, Lorenzo Alvisi, and Robbert van Renesse. Scalog: Seamless reconfiguration and total order in a scalable shared log. In *17th USENIX Symposium on Networked Systems Design and Implementation (NSDI 20)*, pages 325–338, 2020.

[10] Vitor Enes, Carlos Baquero, Tuanir França Rezende, Alexey Gotsman, Matthieu Perrin, and Pierre Sutra. State-machine replication for planet-scale systems. In *Proceedings of the Fifteenth European Conference on Computer Systems*, pages 1–15, 2020.

[11] Heidi Howard, Aleksey Charapko, and Richard Mortier. Fast flexible paxos: Relaxing quorum intersection for fast paxos. In *International Conference on Distributed Computing and Networking 2021*, pages 186–190, 2021.

[12] Heidi Howard and Richard Mortier. Paxos vs raft: Have we reached consensus on distributed consensus? In *Proceedings of the 7th Workshop on Principles and Practice of Consistency for Distributed Data*, pages 1–9, 2020.

[13] Leslie Lamport. The part-time parliament. *ACM Transactions on Computer Systems (TOCS)*, 16(2):133–169, 1998.

[14] Leslie Lamport. Generalized consensus and paxos. 2005.

[15] Leslie Lamport. Fast paxos. *Distributed Computing*, 19(2):79–103, 2006.

[16] Leslie Lamport et al. Paxos made simple. *ACM Sigact News*, 32(4):18–25, 2001.

Figure 15: A non-exhaustive taxonomy of state machine replication protocols. The generalized multi-leader protocols that we discuss in this paper are shaded green.

Table 2: A summary of generalized multi-leader state machine replication protocols.

Protocol	Safe	Commit Time	Tension Handling	Number of Nodes	Phase 1 Quorum Size	Classic Phase 2 Quorum Size	Fast Phase 2 Quorum Size
Simple PPaxos (§4)	yes	7	N/A	$2f+1$	$f+1$	$f+1$	N/A
Fast PPaxos (§6)	no	4	N/A	$2f+1$	$f+1$	$f+1$	$f+\mathsf{maj}(f+1)$
Unanimous PPaxos (§7.1)	yes	4	avoidance	$2f+1$	$f+1$	$f+1$	$2f+1$
Basic EPaxos [22]	yes	4	avoidance	$2f+1$	$f+1$	$f+1$	$2f$
Atlas [10]	yes	4	avoidance	n	$f+1$	$n-f$	$\lfloor\frac{n}{2}\rfloor+f$
Maj. Commit PPaxos (§8.2)	yes	4	resolution	$2f+1$	$f+1$	$f+1$	$f+\mathsf{maj}(f+1)$
EPaxos [21]	yes	4	resolution	$2f+1$	$f+1$	$f+1$	$f+\mathsf{maj}(f+1)-1$
Caesar [3]	yes	4	resolution	$2f+1$	$f+1$	$f+1$	$f+\mathsf{maj}(f+1)$

[17] Jialin Li, Ellis Michael, Naveen Kr Sharma, Adriana Szekeres, and Dan RK Ports. Just say NO to paxos overhead: Replacing consensus with network ordering. In *12th USENIX Symposium on Operating Systems Design and Implementation (OSDI 16)*, pages 467–483, 2016.

[18] Barbara Liskov and James Cowling. Viewstamped replication revisited. 2012.

[19] Giuliano Losa, Sebastiano Peluso, and Binoy Ravindran. Brief announcement: A family of leaderless generalized-consensus algorithms. In *Proceedings of the 2016 ACM Symposium on Principles of Distributed Computing*, pages 345–347. ACM, 2016.

[20] Yanhua Mao, Flavio P Junqueira, and Keith Marzullo. Mencius: building efficient replicated state machines for wans. In *8th USENIX Symposium on Operating Systems Design and Implementation (OSDI 08)*, pages 369–384, 2008.

[21] Iulian Moraru, David G Andersen, and Michael Kaminsky. A proof of correctness for egalitarian paxos. Technical report, Technical report, Parallel Data Laboratory, Carnegie Mellon University, 2013.

[22] Iulian Moraru, David G Andersen, and Michael Kaminsky. There is more consensus in egalitarian parliaments. In *Proceedings of the Twenty-Fourth ACM Symposium on Operating Systems Principles*, pages 358–372. ACM, 2013.

[23] Diego Ongaro and John K Ousterhout. In search of an understandable consensus algorithm. In *USENIX Annual Technical Conference*, pages 305–319, 2014.

[24] Seo Jin Park and John Ousterhout. Exploiting commutativity for practical fast replication. In *16th USENIX Symposium on Networked Systems Design and Implementation (NSDI 19)*, pages 47–64, 2019.

[25] Dan RK Ports, Jialin Li, Vincent Liu, Naveen Kr Sharma, and Arvind Krishnamurthy. Designing distributed systems using approximate synchrony in data center networks. In *NSDI*, pages 43–57, 2015.

[26] Pierre Sutra and Marc Shapiro. Fast genuine generalized consensus. In *Reliable Distributed Systems (SRDS), 2011 30th IEEE Symposium on*, pages 255–264. IEEE, 2011.

[27] Rebecca Taft, Irfan Sharif, Andrei Matei, Nathan Van-Benschoten, Jordan Lewis, Tobias Grieger, Kai Niemi, Andy Woods, Anne Birzin, Raphael Poss, Paul Bardea, Amruta Ranade, Ben Darnell, Bram Gruneir, Justin Jaffray, Lucy Zhang, and Peter Mattis. Cockroachdb: The resilient geo-distributed sql database. In *Proceedings of the 2020 ACM SIGMOD International Conference on Management of Data*, pages 1493–1509. ACM, 2020.

[28] Jeff Terrace and Michael J Freedman. Object storage on craq: High-throughput chain replication for read-mostly workloads. In *USENIX Annual Technical Conference*, number June, pages 1–16. San Diego, CA, 2009.

[29] Alexander Thomson, Thaddeus Diamond, Shu-Chun Weng, Kun Ren, Philip Shao, and Daniel J Abadi. Calvin: fast distributed transactions for partitioned database systems. In *Proceedings of the 2012 ACM SIGMOD International Conference on Management of Data*, pages 1–12. ACM, 2012.

[30] Robbert Van Renesse and Deniz Altinbuken. Paxos made moderately complex. *ACM Computing Surveys (CSUR)*, 47(3):42, 2015.

[31] Robbert Van Renesse and Fred B Schneider. Chain replication for supporting high throughput and availability. In *OSDI*, volume 4, 2004.

[32] Hang Zhu, Zhihao Bai, Jialin Li, Ellis Michael, Dan RK Ports, Ion Stoica, and Xin Jin. Harmonia: Near-linear scalability for replicated storage with in-network conflict detection. *Proceedings of the VLDB Endowment*, 13(3):376–389, 2019.