Evaluations and Methods for Explanation through Robustness Analysis

Abstract

Feature based explanations, that provide importance of each feature towards the model prediction, is arguably one of the most intuitive ways to explain a model. In this paper, we establish a novel set of evaluation criteria for such feature based explanations by robustness analysis. In contrast to existing evaluations which require us to specify some way to "remove" features that could inevitably introduces biases and artifacts, we make use of the subtler notion of smaller adversarial perturbations. By optimizing towards our proposed evaluation criteria, we obtain new explanations that are loosely necessary and sufficient for a prediction. We further extend the explanation to extract the set of features that would move the current prediction to a target class by adopting targeted adversarial attack for the robustness analysis. Through experiments across multiple domains and a human study, we validate the usefulness of our evaluation criteria and our derived explanations.

1 Introduction

There is an increasing interest in machine learning models to be credible, fair, and more generally *interpretable* (Doshi-Velez & Kim, 2017). Researchers have explored various notions of model interpretability, ranging from trustability (Ribeiro et al., 2016), fairness of a model (Zhao et al., 2017), to characterizing the model's weak points (Koh & Liang, 2017; Yeh et al., 2018). Even though the goals of these various model interpretability tasks vary, the vast majority of them use so called feature-based explanations, that assign importance to individual features (Baehrens et al., 2010; Simonyan et al., 2013; Zeiler & Fergus, 2014; Bach et al., 2015; Ribeiro et al., 2016; Lundberg & Lee, 2017; Ancona et al., 2018; Sundararajan et al., 2017; Zintgraf et al., 2017; Shrikumar et al., 2017; Chang et al., 2019). There have also been a slew of recent *evaluation* measures for feature based explanations, such as completeness (Sundararajan et al., 2017), sensitivity-n (Ancona et al., 2018), infidelity (Yeh et al., 2019), causal local explanation metric (Plumb et al., 2018), and most relevant to the current paper, removal- and preservation-based criteria (Samek et al., 2016; Fong & Vedaldi, 2017; Dabkowski & Gal, 2017). A common thread in all these evaluation measures is that for a good feature based explanation, the most salient features are necessary, in that removing them should lead to a large difference in prediction score, and are also sufficient in that removing non-salient features should not lead to a large difference in prediction score.

Thus, common evaluations and indeed even methods for feature explanations involve measuring the function difference after "removing features", which in practice is done by setting the feature value to some reference value (also called baseline value sometimes). However, this would favor feature values that are far way from the baseline value (since this corresponds to a large perturbation, and hence is likely to lead to a function value difference), causing an intrinsic bias for these methods and evaluations. For example, if we set the feature value to black in RGB images, this introduces a bias favoring bright pixels: explanations that optimize such evaluations often omit important dark objects such as a dark-colored dog. An alternative approach to "remove features" is to sample from some predefined distribution or a generative model (Chang et al., 2019). This in turn incurs the bias inherent to the generative model, and accurate generative models that approximate the data distribution well might not be available in all domains.

Instead of defining prediction changes with "removal" of features (which introduces biases as we argued), we alternatively consider the use of small but *adversarial perturbations* instead. It is natural to assume that adversarial perturbations on irrelevant features should be ineffective, while those on relevant features should be effective. We can thus measure the necessity of a set of relevant features by measuring the consequences of adversarially perturbing the subset of "important features"

Figure 1: Illustration of our explanation highlighting both pertinent positive and negative features that support the prediction of "2". The blue circled region corresponds to pertinent positive features that when its value is perturbed (from white to black) will make the digit resemble "7"; while the green and yellow circled region correspond to pertinent negative features that when turned on (black to white) will shape the digit into "0","8", or "9".

of the explanations: if the features are relevant, this should lead to an appreciable change in the predictions. And complementarily, we could measure the sufficiency of the set of relevant features via measuring consequences of adversarially perturbing the irrelevant features: if the perturbed features are irrelevant, this should not lead to an appreciable change in the predictions. We emphasize that by our definition of "important features", our method may naturally find both pertinent positive and pertinent negative features (Dhurandhar et al., 2018) since both pertinent positive and pertinent negative features are the most suspect to adversarial perturbations, and we demonstrate the idea in Figure 1. While exactly computing such an effectiveness measure is NP-hard (Katz et al., 2017), we can leverage recent results from test-time robustness (Carlini & Wagner, 2017; Madry et al., 2017), which entail that perturbations computed by adversarial attacks can serve as reasonably tight upper bounds for our proposed evaluation. Given this adversarial effectiveness evaluation measure, we further design feature-based explanations that optimize this evaluation measure.

To summarize our contributions:

- We define new evaluation criteria for feature-based explanations based on robustness analysis involving small adversarial perturbations. These reduce the bias inherent in other recent evaluation measures that focus on "removing features" via large perturbations to some reference values, or sampling from some reference distribution.
- We design efficient algorithms to generate explanations that maximize the proposed criteria by incorporating game theoretic notions, and demonstrate the effectiveness and interpretability of our proposed explanation on image and language datasets: via our proposed evaluation metric, additional objective metrics, as well as qualitative results and a human study.

2 RELATED WORK

Our work defines a pair of new objective evaluation criteria for feature-based explanations, where existing measurements can be roughly categorized into two families. This first family of explanation evaluations are based on measuring fidelity of the explanation to the model. Here, the feature based explanation is mapped to a simplified model, and the fidelity evaluations measure how well this simplified model corresponds to the actual model. A common setting is where the feature vectors are locally binarized at a given test input, to indicate presence or "removal" of a feature. A linear model with the explanation weights as coefficients would then equal to the sum of attribution values for all present features. *Completeness* or *Sum to Delta* which requires the sum of all attributions to equal the prediction difference of the original input and baseline (Sundararajan et al., 2017; Shrikumar et al., 2017), while *sensitivity-n* which further generalize this to require the sums of subsets of attribution values to equal the prediction difference of the input with features present or absent corresponding to the subset, and the baseline (Ancona et al., 2018). *Local accuracy* (Ribeiro et al., 2016; Lundberg & Lee, 2017) measures the fidelity of local linear regression model corresponding to explanation weights; while *infidelity* is a framework that encompasses these instances above (Yeh et al., 2019). The second family of explanation evaluation are removal- and preservation-based measurements (Samek et al., 2016; Fong & Vedaldi, 2017; Dabkowski & Gal, 2017), which evaluates the ranking of feature-attribution score, with the key insight that removing the most (least) salient features should lead to the most (least) significant function value drop. Unlike previous evaluations, our proposed evaluation criteria are based on more nuanced and smaller adversarial perturbations which does not rely on "removing features".

Another close line of research is counterfactual and contrastive explanations (Wachter et al., 2017; Dhurandhar et al., 2018; Hendricks et al., 2018; van der Waa et al., 2018; Chang et al., 2019; Goyal et al., 2019; Joshi et al., 2019; Poyiadzi et al., 2020), which answers the question: "what to alter in the current input to change the outcome of the model". These studies enable interpretation of a model decision through a contrastive perspective and facilitate actionable means that one can actually undertake to change the model prediction (Joshi et al., 2019; Poyiadzi et al., 2020). While "the closest possible world" provided by counterfactual explanations gives insights on the features that

the model is most sensitive to, it does not necessarily cover the relevant features responsible for the "current" prediction. Moreover, while these identify features as relevant when their perturbation leads to prediction changes, it does not necessarily identify features as relevant when their complement is insensitive to perturbations (and where the relevant features are fixed). Xu et al. (2018) add group sparsity regularization to adversarial attacks that improves the semantic structure of the adversarial perturbations. Instead of outputting general adversarial perturbations, our work focuses specifically on identifying necessary and sufficient relevant features by measuring their susceptibility to adversarial perturbations. Ribeiro et al. (2018) find a set of features that once fixed, the prediction does not change much with high probability when perturbing other features. They measure this via a sampling approach, which is infeasible for high dimension images without super-pixels. In contrast, our method consider the class of adversarial perturbations, which is much more computationally feasible compared to sampling high-dimensional spaces.

3 ROBUSTNESS ANALYSIS FOR EVALUATING EXPLANATIONS

3.1 PROBLEM NOTATION

We consider the setting of a general K-way classification problem with input space $\mathcal{X} \subseteq \mathbb{R}^d$, output space $\mathcal{Y} = \{1, \ldots, K\}$, and a predictor function $f : \mathcal{X} \to \mathcal{Y}$ where $f(\boldsymbol{x})$ denotes the output class for some input example $\boldsymbol{x} = [\boldsymbol{x}_1, \ldots, \boldsymbol{x}_d] \in \mathcal{X}$. Then, for a particular prediction $f(\boldsymbol{x}) = y$, despite the different forms of existing feature based explanations ranging from attributing an importance value to each feature, ranking the features by their importance, to simply identify a set of important features, a common goal of them is to extract a compact set of relevant features with respect to the prediction.

3.2 EVALUATION THROUGH ROBUSTNESS ANALYSIS

A common thread underlying evaluations of feature based explanations, even ranging over axiomatic treatments Sundararajan et al. (2017); Lundberg & Lee (2017), is that the importance of a set of features corresponds to the change in prediction of the model when the features are removed from the original input. Nevertheless, as we discussed in the previous section, operationalizing such a removal of features, for instance, by setting them to some reference value, introduces biases. To finesse this, we leverage adversarial robustness, but to do so in this context, we rely on two key assumptions:

Assumption 1: When the values of the important features are anchored (fixed), perturbations restricted to the complementary set of features has a weaker influence on the model prediction.

Assumption 2: When perturbations are restricted to the set of important features, fixing the values of the rest of the features, even small perturbations could easily change the model prediction.

Based on these two assumptions, we propose a new framework leveraging adversarial robustness to evaluate feature based explanations.

Definition 3.1 *Given a set of features S, its minimum adversarial perturbation norm, which we will also term Robustness-S is defined as:*

$$\epsilon_S^* = g(\boldsymbol{x}, S) = \left\{ \min_{\boldsymbol{\delta}} \|\boldsymbol{\delta}\|_p \text{ s.t. } f(\boldsymbol{x} + \boldsymbol{\delta}) \neq y, \ \boldsymbol{\delta}_{\overline{S}} = 0 \right\}, \tag{1}$$

where $\overline{S} = U \setminus S$ is the complementary set of features, and $\boldsymbol{\delta}_{\overline{S}} = 0$ means that the perturbation is constrained to be zero along features in $\overline{S}$.

Suppose that the feature based explanation partitions the input features into a relevant set S_r, and an irrelevant set $\overline{S_r}$, Assumption 1 implies that the quality of the relevant set can be measured by $\epsilon_{\overline{S_r}}^*$ – by keeping the relevant set unchanged, and measuring the adversarial robustness norm by perturbing only the irrelevant set. Specifically, from Assumption 1, a larger coverage of pertinent features in set S_r entails a higher robustness value $\epsilon_{\overline{S_r}}^*$. On the other hand, from Assumption 2, a larger coverage of pertinent features in set S_r would in turn entail a smaller robustness value $\epsilon_{S_r}^*$, since only relevant features are perturbed. More formally, we propose the following twin criteria for evaluating the quality of S_r identified by any given feature based explanation.

Definition 3.2 *We define Robustness-$\overline{S_r}$ and Robustness-S_r as the following:*

$$\text{Robustness-}\overline{S_r} = \epsilon_{\overline{S_r}}^*. \quad \text{Robustness-}S_r = \epsilon_{S_r}^*.$$

Following our assumptions, a set S_r that has larger coverage of relevant features would yield higher *Robustness-$\overline{S_r}$* and lower *Robustness-S_r*.

Evaluation for Feature Importance. While *Robustness-*$\overline{S_r}$ and *Robustness-*S_r are defined on sets, general feature attribution based explanations could also easily fit into the evaluation framework. Given any feature attribution method that assigns importance score to each feature, we can sort the features in descending order of importance weights, and provide the top-K features as the relevant set S_r. The size of K (or $|S_r|$), can be specified by the users based on the application. An alternative approach that we adopt in our experiments is to vary the size of set K and plot the corresponding values of Robustness-$\overline{S_r}$ and Robustness-S_r over different values of K. With a graph where the $X-$axis is the size of K and the $Y-$axis is Robustness-$\overline{S_r}$ or Robustness-S_r, we are then able to plot an evaluation curve for an explanation and in turn compute its the area under curve (AUC) to summarize its performance. A larger (smaller) AUC for Robustness-$\overline{S_r}$ (Robustness-S_r) indicates a better feature attribution ranking. Formally, given a curve represented by a set of points $\mathcal{C} = \{(x_0, y_0), \ldots, (x_n, y_n)\}$ where $x_{i-1} < x_i$, we calculate the AUC of the curve by: $AUC(\mathcal{C}) = \sum_{i=1}^{n}(y_i + y_{i-1})/2 * (x_i - x_{i-1})$.

Untargeted v.s. Targeted Explanation. Definition 3.1 corresponds to the untargeted adversarial robustness – a perturbation that changes the predicted class to any label other than y is considered as a successful attack. Our formulation can also be extended to **targeted adversarial robustness**, where we replace Eqn. 1 by

$$\epsilon_{S,t}^{*} = \left\{ \min_{\boldsymbol{\delta}} \|\boldsymbol{\delta}\|_p \text{ s.t. } f(\boldsymbol{x} + \boldsymbol{\delta}) = t; \boldsymbol{\delta}_{\overline{S}} = 0 \right\}, \tag{2}$$

where t is the targeted class. Using this definition, our approach will try to address the question "Why is this example classified as y instead of t" by highlighting the important features that contrast between class y and t. Further examples of the "targeted explanations" are in the experiment section.

Robustness Evaluation under Fixed Anchor Set. It is known that computing the exact minimum distortion distance in modern neural networks is intractable (Katz et al., 2017), so many different methods have been developed to estimate the value. Adversarial attacks, such as C&W (Carlini & Wagner, 2017) and PGD attack (Madry et al., 2017), aim to find a feasible solution of Eqn. 1, which leads to an upper bound of ϵ_S^*. They are based on gradient based optimizers which are usually efficient. On the other hand, neural network verification methods aim to provide a lower bound of ϵ_S^* to ensure that the model prediction will not change within certain perturbation range (Singh et al., 2018; Wong & Kolter, 2018; Weng et al., 2018; Gehr et al., 2018; Zhang et al., 2018; Wang et al., 2018; Zhang et al., 2019). However, these methods are usually time consuming (often > 50 times slower than a backpropagation). The proposed framework can be combined with any method that aims to approximately compute Eqn. 1, including attack, verification, and some other statistical estimations.[1] However, for simplicity we only choose to evaluate Eqn. 1 by the state-of-the-art projected gradient descent (PGD) attack (Madry et al., 2017), since the verification methods are too slow and often lead to much looser estimation as reported in some recent studies (Salman et al., 2019). Our additional constraint restricting perturbation to only be on a subset of features specifies a set that is simple to project onto, where we set the corresponding coordinates to zero at each step of PGD.

4 EXTRACTING RELEVANT FEATURES THROUGH ROBUSTNESS ANALYSIS

Our adversarial robustness based evaluation allows us to evaluate any given feature based explanation. Here, we set out to design new explanations that explicitly optimize our evaluation measure. We focus on feature set based explanations, where we aim to provide an important subset of features S_r. Given our proposed evaluation measure, an optimal subset of feature S_r would aim to maximize (minimize) Robustness-$\bar{S_r}$ (Robustness-S_r), under a cardinality constraint on the feature set, leading to the following set of optimization problems:

$$\underset{S_r \in \{0,1\}^d}{\text{maximize}} \ g(\boldsymbol{x}, \overline{S_r}) \text{ s.t. } \|S_r\|_0 \leq K \tag{3}$$

$$\underset{S_r \in \{0,1\}^d}{\text{minimize}} \ g(\boldsymbol{x}, S_r) \text{ s.t. } \|S_r\|_0 \leq K \tag{4}$$

where K is a pre-defined size constraint on the set S_r, and $g(\boldsymbol{x}, S)$ computes the the minimum adversarial perturbation from Eqn. 1, with set-restricted perturbations.

It can be seen that this sets up an adversarial min-max game: the goal of the feature set explainer is to come up with a set S_r such that the minimal adversarial perturbation is as large as possible, while the adversarial attacker, given a set S_r, aims to design adversarial perturbations that are as small as possible. Directly solving these min-max problems in Eqn. 3 and Eqn. 4 is thus challenging, which is exacerbated by the discrete input constraint makes it intractable to find the optimal solution. We therefore propose a greedy algorithm in the next section to estimate the optimal explanation sets.

---

[1]See Appendix A for further discussions on estimating adversarial robustness for different types of model.

4.1 Greedy Algorithm to Compute Optimal Explanations

We first consider a greedy algorithm where, after initializing S_r to the empty set, we iteratively add to S_r the most promising feature that optimizes the objective at each local step until S_r reaches the size constraint. We thus sequentially solve the following sub-problem at every step t:

$$\arg \max_i \ g(\boldsymbol{x}, \overline{S_r^t \cup i}), \ \text{or} \ \arg \min_i \ g(\boldsymbol{x}, S_r^t \cup i), \ \forall i \in \overline{S_r^t} \tag{5}$$

where S_r^t is the anchor set at step t, and $S_r^0 = \emptyset$. We repeat this subprocedure until the size of set S_r^t reaches K. A straightforward approach for solving Eqn. 5 is to exhaustively search over every single feature. We term this method **Greedy**. While the method eventually selects K features for the relevant set S_r, the latter might lose the sequence in which the features were selected. One approach to encode this order would be to output a feature explanation that assigns higher weights to those features selected earlier in the greedy iterations.

4.2 Greedy by Set Aggregation Score

The main downside of using the greedy algorithm to optimize the objective function is that it ignores the interactions among features. Two features that may seem irrelevant when evaluated separately might nonetheless be relevant when added simultaneously. Therefore, in each greedy step, instead of considering how each individual feature will marginally contribute to the objective $g(\cdot)$, we propose to choose features based on their expected marginal contribution when added to the union of S_r and a random subset of unchosen features. To measure such an aggregated contribution score, we draw from cooperative game theory literature (Dubey & Shapley, 1979; Hammer & Holzman, 1992) to reduce this to a linear regression problem. Formally, let S_r^t and $\overline{S_r^t}$ be the ordered set of chosen and unchosen features at step t respectively, $\mathcal{P}^t(\overline{S_r^t})$ be all possible subsets of $\overline{S_r^t}$. We measure the expected contribution of including each unchosen feature to the relevant set would have on objective function by learning the following regression problem:

$$\boldsymbol{w}^t = \arg \min_{\boldsymbol{w}} \sum_{A \in \mathcal{P}^t(\overline{S_r^t})} ((\boldsymbol{w}^T B(A) + b) - g(\boldsymbol{x}, S_r^t \cup A))^2, \tag{6}$$

where B is a function that projects a set into its corresponding binary vector form: $B(A)[j] = \mathbb{I}(\overline{S_r^t}[j] \in A)$, i.e., ones in the vector indicate the inclusion of corresponding feature indices in the set and zeros otherwise. We note that $\boldsymbol{w}^t$ corresponds to the well-known Banzhaf value Banzhaf III (1964) when $S_r^t = \emptyset$, which can be interpreted as the importance of each player by taking coalitions into account Dubey & Shapley (1979). Hammer & Holzman (1992) show that the Banzhaf value is equivalent to the optimal solution of linear regression with pseudo-Boolean functions as targets, which corresponds to Eqn. 6 with $S_r^t = \emptyset$. We can thus treat the linear regression coefficients $\boldsymbol{w}$ in Eqn. 6 as each corresponding feature's expected marginal contribution when added to the union of S_r and a random subset of unchosen features.

We thus consider the following set-aggregated variant of our greedy algorithm in the previous section, and which we term **Greedy-AS**. In each greedy step, we choose features with the highest aggregation score (Banzhaf) value rather than simply the highest marginal contribution to the objective function as in vanilla greedy, which additionally considers interactions among the unchosen features when compared to vanilla greedy. The chosen features each step are then added to S_r^t and removed from $\overline{S_r^t}$. When S_r^t is not $\emptyset$, the solution of Eqn. 6 can still be seen as the Banzhaf value where the players are the unchosen features in $\overline{S_r^t}$, and the value function of a subset of players is equal to the adversarial perturbation objective that adds this subset of players to the current set of chosen features S_r^t. We solve the linear regression problem in Eqn. 6 by sub-sampling to lower the computational cost, and we validate the effectiveness of Greedy and Greedy-AS in the experiment section. [2]

5 Experiments

In this section, we first evaluate different model interpretability methods on the proposed criteria. We justify the effectiveness of the proposed Greedy-AS. We then move onto further validating the benefits of the explanations extracted by Greedy-AS through comparisons to various existing methods both quantitatively and qualitatively. Finally, we demonstrate the flexibility of our method with the ability to provide targeted explanations as mentioned in Section 3.2. We perform the experiments on two image datasets, MNIST LeCun et al. (2010) and ImageNet (Deng et al., 2009), as well as a text classification dataset, Yahoo! Answers (Zhang et al., 2015).

---

[2]We found that concurrent to our work, greedy with choosing the players with the highest restricted Banzhaf was used in Elkind et al. (2017).

Table 1: AUC of Robustness-$\overline{S_r}$ and Robustness-S_r for various explanations on MNIST and ImageNet. The higher the better for Robustness-$\overline{S_r}$; the lower the better for Robustness-S_r.

Datasets	Explanations	Grad	IG	SHAP	LOO	BBMP	CFX	Greedy-AS	Greedy	One-Step Banzhaf
MNIST	Robustness-$\overline{S_r}$	88.00	85.98	75.48	74.14	78.58	69.88	**98.01**	83.57	86.37
	Robustness-S_r	91.72	91.97	101.49	104.38	176.61	102.81	**82.81**	171.56	83.59
ImageNet	Robustness-$\overline{S_r}$	27.13	26.01	18.25	22.29	21.56	27.12	**31.62**	21.16	24.54
	Robustness-S_r	45.53	46.28	60.02	58.46	158.01	46.10	**43.97**	58.45	47.07

Setup. In the experiments, we consider $p = 2$ for $\| \cdot \|_p$ in Eqn. 1 and Eqn. 2, i.e., the L_2 norm if not otherwise specified. For all quantitative results including the evaluation curves and the corresponding AUCs, we report the average over 100 random examples. For the baseline methods, we include vanilla gradient (Grad) (Shrikumar et al., 2017) and integrated gradient (IG) (Sundararajan et al., 2017) from gradient-based approaches; leave-one-out (LOO), or occlusion-1, (Zeiler & Fergus, 2014; Li et al., 2016) and SHAP (Lundberg & Lee, 2017) from perturbation-based approaches (Ancona et al., 2018); black-box meaningful perturbation (BBMP) (Fong & Vedaldi, 2017) from removal/preservation-based approaches; and counterfactual explanation (CFX) proposed by Wachter et al. (2017).[3] For the proposed Greedy and Greedy-AS, at each greedy iteration, we include the top-5% features with highest scores into the relevant set to further speed up the selection process. We leave more implementation detail in Appendix B due to space limitation.

5.1 ROBUSTNESS ANALYSIS ON MODEL INTERPRETABILITY METHODS

Here we compare Greedy-AS, ablated variants of Greedy-AS, as well as various existing explanation methods under both the proposed evaluation criteria Robustness-$\overline{S_r}$ and Robustness-S_r. For ease of comparison, we calculate the area under curve (AUC) for each corresponding evaluation curves. We next discuss these results, listed in Table 1, with the detailed plots in Appendix D.

Ablation Study on Greedy-AS. As discussed in Section 4.2, Greedy-AS could be seen as a combination of the original greedy procedure with the approximated contribution of each feature computed by a regression. Here, we examine the importance of both components by comparing the Greedy-AS method to two baselines, where one selects important features based only on the pure Greedy method (Section 4.1) and the other utilizes only a single step of regression without the iterative greedy procedure. As the latter essentially corresponds to the Banzhaf value, we term this method as *One-Step Banzhaf.* As shown in Table 1, the pure Greedy method suffers degraded performances comparing to Greedy-AS under both criteria. The inferior performance could be explained by the ignorance of feature correlations which ultimately results in the introduction of noise (see Figure 6 in appendix). In addition, we also see that Greedy-AS performs better than One-Step Banzhaf. This could results from the fact that One-Step Banzhaf considers the feature interactions among all features with equal probability. However, in our objective, we only care about those interactions with the most important features. By iteratively selecting the features with highest Banzhaf value in Greedy-AS, we give more weight on the interactions among the most important features through iterations, and as a result lead to better performance.

Comparisons between Different Explanations. Furthermore from Table 1, we observe that the proposed Greedy-AS consistently outperforms other explanation methods on both criteria (see Appendix G for statistical significance of the improvements). On one hand, this suggests that the proposed algorithm indeed successfully optimizes towards the criteria; on the other hand, this might indicate the proposed criteria do capture different characteristics of explanations which most of the current explanations do not possess. Another somewhat interesting finding from the table is that while vanilla gradient has generally been viewed as a baseline method, it nonetheless performs competitively on the proposed criteria. We conjecture the phenomenon results from the fact that Grad does not assume any reference value as opposed to other baselines such as LOO which sets the reference value as zero to mask out the inputs. Indeed, it might not be surprising that Greedy-AS achieves the best performances on the proposed criteria since it is explicitly designed for so. To more objectively evaluate the usefulness of the proposed explanation, we demonstrate different advantages of our method by comparing Greedy-AS to other explanations quantitatively on existing commonly adopted measurements, and qualitatively through visualization in the following subsections.

---

[3]Since the original objective in (Wachter et al., 2017) has no control over the number of features that could differ from the input, we add L_0-norm constraint to enforce sparsity in the difference and enable selection of top-K most relevant features.

Table 2: AUC of the Insertion and Deletion criteria for various explanations on MNIST. The higher the better for Insertion; the lower the better for Deletion.

Datasets	Explanations	Grad	IG	SHAP	LOO	BBMP	CFX	Greedy-AS
MNIST	Insertion	250.81	262.74	200.50	174.51	96.28	150.17	**379.15**
	Deletion	281.88	273.71	362.68	492.79	568.19	297.96	**159.77**
ImageNet	Insertion	86.98	110.85	27.93	32.53	70.59	159.51	**184.25**
	Deletion	267.50	246.61	**163.59**	519.07	702.38	263.13	247.20

5.2 EVALUATING GREEDY-AS

The Insertion and Deletion Metric. To further justify the proposed explanation not only performs well on the very metric it optimizes, we evaluate our method on a suite of existing popular quantitative measurements. In particular, we adopt the *Deletion* and *Insertion* criteria proposed by Petsiuk et al. (2018), which are generalized variants of the *region perturbation* criterion presented in Samek et al. (2016). The Deletion criterion measures the probability drop in the predicted class as top-relevant features, indicated by the given explanation, are progressively removed from the input. On the other hand, the Insertion criterion measures the increase in probability of the predicted class as top-relevant features are gradually revealed from the input whose features are originally all masked. Similar to our proposed criteria, a quick drop (and thus a small area under curve) or a sharp increase (that leads to a large area under curve) in Deletion and Insertion respectively suggest a good explanation as the selected top-important features could indeed greatly influence the prediction. In the experiments, we follow Samek et al. (2016) to remove features by setting their values to randomly sampled values. We plot the evaluation curves (in Appendix E) and report corresponding AUCs in Table 2. On these additional two criteria, we observe that Greedy-AS performs favorably against other explanations (see Appendix G for statistical significance of the performance differences). The results further validate the benefits of the proposed explanation. We note that on ImageNet, SHAP obtains a better performance under the Deletion criterion. We however suspect such performance comes from adversarial artifacts (that are the features vulnerable to adversarial attack while not being semantically meaningful), since the explanation provided by SHAP seems to be rather noisy (as shown in Figure 3), and it has been observed that the Deletion criterion tends to favor adversarial artifacts in several previous work. (Dabkowski & Gal, 2017; Chang et al., 2019).

Sanity Check Metric. In Appendix F, we conduct experiments to verify that Greedy-AS could indeed pass the sanity check proposed by Adebayo et al. (2018).

5.3 QUALITATIVE RESULTS

Image Classification. To complement the quantitative measurements, we show several visualization results on MNIST and ImageNet in Figure 2 and Figure 3. More examples could be found in Appendix H and I. On MNIST, we observe that existing explanations tend to highlight mainly on the white pixels in the digits; among which SHAP and LOO show less noisy explanations comparing to Grad and IG. On the other hand, the proposed Greedy-AS focuses on both the "crucial positive" (important white pixels) as well as the "pertinent negative" (important black regions) that together support the prediction. For example, in the first row, a 7 might have been predicted as a 4 or 0 if the pixels highlighted by Greedy-AS are set to white. Similarly, a 1 may be turned to a 4 or a 7 given additional white pixels to its left, and a 9 may become a 7 if deleted the lower circular part of its head. From the results, we see that Greedy-AS focuses on *"the region where perturbation on its current value will lead to easier prediction change"*, which includes both the crucial positive and pertinent negative pixels. Such capability of Greedy-AS is also validated by its superior performance on the proposed robustness criteria, on which methods like LOO that highlights only the white strokes of digits show relatively low performance. The capability of capturing pertinent negative features has also been observed in explanations proposed in some recent work Dhurandhar et al. (2018); Bach et al. (2015); Oramas et al. (2019), and we further provide more detailed discussions and comparisons to these methods in Appendix J. From the visualized ImageNet examples shown in Figure 3, we observe that our method provides more compact explanations that focus mainly on the actual objects being classified. For instance, in the first image, our method focuses more on the face of the Maltese while others tend to have noisier results; in the last image, our method focuses on one of the Japanese Spaniel whereas others highlight both the dogs and some noisy regions.

Text Classification. In addition to image datasets, here we demonstrate how our explanation method could be applied to text classification models. In the experiments, we represent a length-n sentence by n embedding vectors following the common setting. We could then view each input consisting of $n \times d$ features, where d is the word embedding size. When applying our Greedy algorithm, at each iteration we will try to add an embedding vector to the relevant set S_r and choose

Figure 2: Visualization on top 20 percent relevant features provided by different explanations. We see Greedy-AS highlights both crucial positive and pertinent negative features supporting the prediction.

Figure 3: Visualization of different explanations on ImageNet, where the predicted class for each input is "Maltese", "hippopotamus", "zebra", and "Japanese Spaniel". Greedy-AS focuses more compactly objects.

Input	What kind of football cleats should I get. High Cut or Mid-cut. I am playing on the line?
Greedy	What kind of football[1] cleats[0] should[4] I get. High Cut[2] or Mid-cut. I[3] am playing on the line?
Grad	What kind of football[4] cleats[3] should I get.[0] High[1] Cut or Mid-cut. I am playing[2] on the line?
LOO	What kind of football[1] cleats[0] should I get. High Cut or Mid-cut. I[4] am[2] playing on[3] the line?

Most Relevant ▮▮▮▮▮ Less Relevant

Figure 4: Explanations on a text classification model which correctly predicts the label "sport". Unlike other methods, the top-3 relevant keywords highlighted by Greedy are all closely related to the concept "sport".

Figure 5: Visualization of targeted explanation. For each input, we highlight relevant regions explaining why the input is not predicted as the target class. We see the explanation changes in a semantically meaningful way as the target class changes.

the one with largest reward. Since there are only at most n choices, the Greedy algorithm doesn't suffer much from noise and has similar behavior to Greedy-AS. We perform experiments on an LSTM network which classifies a given sentence into one of the ten classes (Society, Science, ..., Health). We showcase an example with explanations generated with different methods in Figure 4. We note that although the top-5 relevant keyword generated by the three methods do not vary much, the rankings within the highlighted keywords for each explanation are quite different. We conduct a human study by asking the users to label keywords they believe to be the most relevant to the prediction. As an example, to predict the label of "sport", one might consider "cleats", "football", and "cut" as the strongest indications towards the concept "sport", and we ask 10 users to label keywords in the sentence that are the most relevant to the class, and compare the top words highlighted by explanations to the top words chosen by human. We observe that our method Greedy generates explanation that matches human intuition the most in the human study, and we report details of the human study and additional examples in Appendix L and K.

Targeted Explanation Analysis. Recall that in section 3.2, we discussed about the possibility of defining the robustness measurement by considering a targeted distortion distance as formulated in Eqn. 2. Here, we provide examples, as shown in Figure 5, where we answer the question of *"why the input digit is an A but not a B"* by defining a targeted perturbation distance towards class B as our robustness measurement. In each row of the figure, we provide targeted explanation towards two different target classes for a same input image. Interestingly, as the target class changes, the generated explanation varies in an interpretatble way. For example, in the first row, we explain why the input digit 7 is not classified as a 9 (middle column) or a 2 (rightmost column). The resulting explanation against 9 highlights the upper-left part of the 7. Semantically, this region is indeed pertinent to the classification between 7 and 9, since turning on the highlighted pixel values in the region (currently black in the original image) will then make the 7 resemble a 9. However, the targeted explanation against 2 highlights a very different but also meaningful region, which is the lower-right part of the 7; since adding a horizontal stroke on the area would turn a 7 into a 2.

6 CONCLUSION

In this paper, we establish the link between a set of features to a prediction with a new evaluation criteria, robustness analysis, which measures the minimum tolerance of adversarial perturbation. Furthermore, we develop a new explanation method to find important set of features to optimize this new criterion. Experimental results demonstrate that the proposed new explanations are indeed capturing significant feature sets across multiple domains.

REFERENCES

Julius Adebayo, Justin Gilmer, Michael Muelly, Ian Goodfellow, Moritz Hardt, and Been Kim. Sanity checks for saliency maps. In *Advances in Neural Information Processing Systems*, pp. 9525–9536, 2018.

Marco Ancona, Enea Ceolini, Cengiz Oztireli, and Markus Gross. A unified view of gradient-based attribution methods for deep neural networks. *International Conference on Learning Representations*, 2018.

Sebastian Bach, Alexander Binder, Grégoire Montavon, Frederick Klauschen, Klaus-Robert Müller, and Wojciech Samek. On pixel-wise explanations for non-linear classifier decisions by layer-wise relevance propagation. *PloS one*, 10(7):e0130140, 2015.

David Baehrens, Timon Schroeter, Stefan Harmeling, Motoaki Kawanabe, Katja Hansen, and Klaus-Robert MÃžller. How to explain individual classification decisions. *Journal of Machine Learning Research*, 11(Jun):1803–1831, 2010.

John F Banzhaf III. Weighted voting doesn't work: A mathematical analysis. *Rutgers L. Rev.*, 19: 317, 1964.

Wieland Brendel, Jonas Rauber, and Matthias Bethge. Decision-based adversarial attacks: Reliable attacks against black-box machine learning models. *arXiv preprint arXiv:1712.04248*, 2017.

Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks. In *2017 IEEE Symposium on Security and Privacy (SP)*, pp. 39–57. IEEE, 2017.

Chun-Hao Chang, Elliot Creager, Anna Goldenberg, and David Duvenaud. Explaining image classifiers by counterfactual generation. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=B1MXz20cYQ.

Hongge Chen, Huan Zhang, Duane Boning, and Cho-Jui Hsieh. Robust decision trees against adversarial examples. In *ICML*, 2019.

Minhao Cheng, Thong Le, Pin-Yu Chen, Jinfeng Yi, Huan Zhang, and Cho-Jui Hsieh. Query-efficient hard-label black-box attack: An optimization-based approach. *arXiv preprint arXiv:1807.04457*, 2018.

Piotr Dabkowski and Yarin Gal. Real time image saliency for black box classifiers. In *NIPS*, 2017.

J. Deng, W. Dong, R. Socher, L.-J. Li, K. Li, and L. Fei-Fei. ImageNet: A Large-Scale Hierarchical Image Database. In *CVPR09*, 2009.

Amit Dhurandhar, Pin-Yu Chen, Ronny Luss, Chun-Chen Tu, Paishun Ting, Karthikeyan Shanmugam, and Payel Das. Explanations based on the missing: Towards contrastive explanations with pertinent negatives. In *Advances in Neural Information Processing Systems*, pp. 592–603, 2018.

Finale Doshi-Velez and Been Kim. Towards a rigorous science of interpretable machine learning. *arXiv preprint arXiv:1702.08608*, 2017.

Pradeep Dubey and Lloyd S Shapley. Mathematical properties of the banzhaf power index. *Mathematics of Operations Research*, 4(2):99–131, 1979.

Edith Elkind, Piotr Faliszewski, Martin Lackner, Dominik Peters, and Nimrod Talmon. Committee scoring rules, banzhaf values, and approximation algorithms. In *4th workshop on exploring beyond the worst case in computational social choice (EXPLORE'17)*, 2017.

Ruth C. Fong and Andrea Vedaldi. Interpretable explanations of black boxes by meaningful perturbation. *2017 IEEE International Conference on Computer Vision (ICCV)*, pp. 3449–3457, 2017.

Timon Gehr, Matthew Mirman, Dana Drachsler-Cohen, Petar Tsankov, Swarat Chaudhuri, and Martin Vechev. Ai2: Safety and robustness certification of neural networks with abstract interpretation. In *2018 IEEE Symposium on Security and Privacy (SP)*, pp. 3–18. IEEE, 2018.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014.

Yash Goyal, Ziyan Wu, Jan Ernst, Dhruv Batra, Devi Parikh, and Stefan Lee. Counterfactual visual explanations. In *International Conference on Machine Learning*, pp. 2376–2384, 2019.

Peter L Hammer and Ron Holzman. Approximations of pseudo-boolean functions; applications to game theory. *Zeitschrift für Operations Research*, 36(1):3–21, 1992.

Lisa Anne Hendricks, Ronghang Hu, Trevor Darrell, and Zeynep Akata. Grounding visual explanations. In *ECCV*, 2018.

S. Joshi, O. Koyejo, Warut D. Vijitbenjaronk, Been Kim, and Joydeep Ghosh. Towards realistic individual recourse and actionable explanations in black-box decision making systems. *ArXiv*, abs/1907.09615, 2019.

Guy Katz, Clark Barrett, David L Dill, Kyle Julian, and Mykel J Kochenderfer. Reluplex: An efficient smt solver for verifying deep neural networks. In *International Conference on Computer Aided Verification*, pp. 97–117. Springer, 2017.

Pang Wei Koh and Percy Liang. Understanding black-box predictions via influence functions. In *International Conference on Machine Learning*, pp. 1885–1894, 2017.

Yann LeCun, Corinna Cortes, and CJ Burges. Mnist handwritten digit database. *ATT Labs [Online]. Available: http://yann. lecun. com/exdb/mnist*, 2, 2010.

Jiwei Li, Will Monroe, and Dan Jurafsky. Understanding neural networks through representation erasure. *CoRR*, abs/1612.08220, 2016. URL http://arxiv.org/abs/1612.08220.

Scott M Lundberg and Su-In Lee. A unified approach to interpreting model predictions. In *Advances in Neural Information Processing Systems*, pp. 4765–4774, 2017.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*, 2017.

Jose Oramas, Kaili Wang, and Tinne Tuytelaars. Visual explanation by interpretation: Improving visual feedback capabilities of deep neural networks. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=H1ziPjC5Fm.

Vitali Petsiuk, Abir Das, and Kate Saenko. Rise: Randomized input sampling for explanation of black-box models. *arXiv preprint arXiv:1806.07421*, 2018.

Gregory Plumb, Denali Molitor, and Ameet S Talwalkar. Model agnostic supervised local explanations. In *Advances in Neural Information Processing Systems*, pp. 2515–2524, 2018.

Rafael Poyiadzi, Kacper Sokol, Raúl Santos-Rodríguez, T. D. Bie, and Peter A. Flach. Face: Feasible and actionable counterfactual explanations. *Proceedings of the AAAI/ACM Conference on AI, Ethics, and Society*, 2020.

Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. Why should i trust you?: Explaining the predictions of any classifier. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 1135–1144. ACM, 2016.

Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. Anchors: High-precision model-agnostic explanations. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

Hadi Salman, Greg Yang, Huan Zhang, Cho-Jui Hsieh, and Pengchuan Zhang. A convex relaxation barrier to tight robust verification of neural networks. *arXiv preprint arXiv:1902.08722*, 2019.

Wojciech Samek, Alexander Binder, Grégoire Montavon, Sebastian Lapuschkin, and Klaus-Robert Müller. Evaluating the visualization of what a deep neural network has learned. *IEEE transactions on neural networks and learning systems*, 28(11):2660–2673, 2016.

Avanti Shrikumar, Peyton Greenside, and Anshul Kundaje. Learning important features through propagating activation differences. *International Conference on Machine Learning*, 2017.

Karen Simonyan, Andrea Vedaldi, and Andrew Zisserman. Deep inside convolutional networks: Visualising image classification models and saliency maps. *arXiv preprint arXiv:1312.6034*, 2013.

Gagandeep Singh, Timon Gehr, Matthew Mirman, Markus Püschel, and Martin Vechev. Fast and effective robustness certification. In *Advances in Neural Information Processing Systems*, pp. 10802–10813, 2018.

Mukund Sundararajan, Ankur Taly, and Qiqi Yan. Axiomatic attribution for deep networks. In *International Conference on Machine Learning*, 2017.

Jasper van der Waa, Marcel Robeer, Jurriaan van Diggelen, Matthieu Brinkhuis, and Mark Neerincx. Contrastive Explanations with Local Foil Trees. In *2018 Workshop on Human Interpretability in Machine Learning (WHI)*, 2018.

S. Wachter, Brent D. Mittelstadt, and Chris Russell. Counterfactual explanations without opening the black box: Automated decisions and the gdpr. *European Economics: Microeconomics Industrial Organization eJournal*, 2017.

Shiqi Wang, Kexin Pei, Justin Whitehouse, Junfeng Yang, and Suman Jana. Efficient formal safety analysis of neural networks. In *Advances in Neural Information Processing Systems*, pp. 6367–6377, 2018.

Tsui-Wei Weng, Huan Zhang, Hongge Chen, Zhao Song, Cho-Jui Hsieh, Luca Daniel, Duane Boning, and Inderjit Dhillon. Towards fast computation of certified robustness for relu networks. In *International Conference on Machine Learning*, pp. 5273–5282, 2018.

Eric Wong and Zico Kolter. Provable defenses against adversarial examples via the convex outer adversarial polytope. In *International Conference on Machine Learning*, pp. 5283–5292, 2018.

Kaidi Xu, Sijia Liu, Pu Zhao, Pin-Yu Chen, Huan Zhang, Quanfu Fan, Deniz Erdogmus, Yanzhi Wang, and Xue Lin. Structured adversarial attack: Towards general implementation and better interpretability. *arXiv preprint arXiv:1808.01664*, 2018.

Chih-Kuan Yeh, Joon Kim, Ian En-Hsu Yen, and Pradeep K Ravikumar. Representer point selection for explaining deep neural networks. In *Advances in Neural Information Processing Systems*, pp. 9291–9301, 2018.

Chih-Kuan Yeh, Cheng-Yu Hsieh, Arun Sai Suggala, David I. Inouye, and Pradeep Ravikumar. On the (in)fidelity and sensitivity for explanations. *CoRR*, abs/1901.09392, 2019.

Matthew D Zeiler and Rob Fergus. Visualizing and understanding convolutional networks. In *European conference on computer vision*, pp. 818–833. Springer, 2014.

Huan Zhang, Tsui-Wei Weng, Pin-Yu Chen, Cho-Jui Hsieh, and Luca Daniel. Efficient neural network robustness certification with general activation functions. In *Advances in neural information processing systems*, pp. 4939–4948, 2018.

Huan Zhang, Pengchuan Zhang, and Cho-Jui Hsieh. Recurjac: An efficient recursive algorithm for bounding jacobian matrix of neural networks and its applications. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 5757–5764, 2019.

Xiang Zhang, Junbo Zhao, and Yann LeCun. Character-level convolutional networks for text classification. In *Advances in neural information processing systems*, pp. 649–657, 2015.

Jieyu Zhao, Tianlu Wang, Mark Yatskar, Vicente Ordonez, and Kai-Wei Chang. Men also like shopping: Reducing gender bias amplification using corpus-level constraints. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pp. 2979–2989, 2017.

Luisa M. Zintgraf, Taco S. Cohen, Tameem Adel, and Max Welling. Visualizing deep neural network decisions: Prediction difference analysis. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*, 2017. URL https://openreview.net/forum?id=BJ5UeU9xx.

A MORE ON ESTIMATING ADVERSARIAL ROBUSTNESS

Our work relies on measuring the adversarial perturbation norm on a subset of features, which can be seen as a constrained adversarial robustness problem. Adversarial robustness has been extensively studied in the past few years. The adversarial robustness of a machine learning model on a given sample can be defined as the shortest distance from the sample to the decision boundary, which corresponds to our definition in Eqn. 1. Algorithms have been proposed for finding adversarial examples (feasible solutions of Eqn. 1), including (Goodfellow et al., 2014; Carlini & Wagner, 2017; Madry et al., 2017). However, those algorithms only work for neural networks, while for other models such as tree based models or nearest neighbor classifiers, adversarial examples can be found by decision based attacks (Brendel et al., 2017; Cheng et al., 2018; Chen et al., 2019). Therefore the proposed framework can also be used in other decision based classifiers. On the other hand, several works aim to solve the neural network verification problem, which is equivalent to finding a lower bound of Eqn. 1. Examples include (Singh et al., 2018; Wong & Kolter, 2018; Zhang et al., 2018). In principal, our work can also apply these verification methods for getting an approximate solution of Eqn. 1, but in practice they are very slow to run and often gives loose lower bounds on regular trained networks.

B IMPLEMENTATION DETAIL

Underlying Models Used.   In the experiments conducted on MNIST dataset, we train a convolutional neural network (CNN) with 99% testing accuracy. The training and testing split used in the experiments are the default split as provided by the original dataset. For each instance, the inputs are loaded into the range of $[0, 1]$. On ImageNet dataset, we deploy a pre-trained ResNet model obtained from the Pytorch library.[4] For each image, the inputs are first loaded into the range of $[0, 1]$ and normalized using mean $= [0.485, 0.456, 0.406]$ and standard deviation $= [0.229, 0.224, 0.225]$. On Yahoo! Answers dataset, we train a BiLSTM sentence classifier which attains testing accuracy of 71%. For the model configuration and training hyperparameters, we strictly follow the official GLUE repository [5]. Specifically, we first tokenize the dataset by word-level tokenizer; and then we use the pretrained GloVe word embedding to initialize the LSTM embedding layer where the hidden size is 300.

Hyperparameters.   As discussed in Section 3.2, we use PGD attack with binary search to approximately compute the robustness value in Eqn. 1. In the experiments, we set the PGD attack step size to be 1.0 and number of steps to be 100. The hyperparameters are chosen such that the PGD attack could most efficiently provide the tightest upper bound on the true robustness value. As mentioned in Section 4.2, we solve Eqn. 6 by subsampling from all possible subsets of $\overline{S_r^t}$. Specifically, we compute the coefficients w with respect to 5000 sampled subsets when learning the regression.

Evaluation Curves.   To plot the evaluation curves of a given explanation, we measure the explanation's Robustness-$\overline{S_r}$ and Robustness-S_r at different sizes of relevant set $|S_r|$. Specifically, we measure the explanation's performance when $|S_r|$ equals to 5%, 10%, . . ., 45% of the total number of features. Similarly for the Insertion and Deletion criteria, we progressively evaluate the explanation's performance when 5%, 10%, . . ., 45% of the features are inserted (or removed) from the inputs. After the evaluation curves are plotted, we then calculate the area under curves to summarize the explanation's overall performance under each criterion.

Hardware and Code.   All the experiments were performed on Intel(R) Xeon(R) CPU E5-2630 v4 @ 2.20GHz and NVIDIA GeForce GTX 1080 Ti GPU. We release our source code along with an example Jupyter notebook for more information.

---

[4] https://github.com/pytorch/pytorch
[5] https://github.com/nyu-mll/GLUE-baselines

Figure 6: Visualization on our proposed methods. The top features selected by Greedy-AS are less noisy.

(a) Greedy-AS, One-Step Banzhaf and Greedy. (b) Greedy-AS and other existing methods.

Figure 7: Evaluation curves of our proposed methods and existing explanations under Robustness-$\overline{S_r}$ and Robustness-S_r on MNIST. Note that we omit points in the plot with value too high to fit in the scale of y-axis.

(a) Greedy-AS, One-Step Banzhaf and Greedy. (b) Greedy-AS and other existing methods.

Figure 8: Evaluation curves of our proposed methods and existing explanations under Robustness-$\overline{S_r}$ and Robustness-S_r on ImageNet. Note that we omit points in the plot with value too high to fit in the scale of y-axis.

(a) Insertion (left) and Deletion (right) on MNIST. (b) Insertion (left) and Deletion (right) on ImageNet.

Figure 9: Evaluation curves of different explanations under the Insertion and Deletion criteria on MNIST and ImageNet. On each datatset, the Insertion (left subfigure) criterion measures the change in output logits as relevant features are inserted into the input; the Deletion (right subfigure) criterion measures the change in output logits as relevant features are removed from the input.

C VISUALIZE OF GREEDY, ONE-STEP BANZHAF, AND GREEDY-AS

We compare the visualization results of Greedy, One-Step Banzhaf, and Greedy-AS on an MNIST image, as shown in Figure 6. We see that the top features selected by Greedy-AS are less noisy than the other two.

D EVALUATION CURVES UNDER ROBUSTNESS-$\overline{S_r}$ AND ROBUSTNESS-S_r

We show the evaluation curves of different methods under the proposed robustness criteria on MNIST and ImangeNet in Figure 7 and Figure 8 respectively. For ease of comparison, on each dataset, we show the curves between Greedy-AS, One-Step Banzhaf, and Greedy in a set of plots; and we show the curves between Greedy-AS and other existing methods in another set of plots.

E EVALUATION CURVES UNDER INSERTION AND DELETION

We show the evaluation curves of different methods under the Insertion and Deletion criteria on MNIST and ImageNet in Figure 9a and Figure 9b respectively.

F SANITY CHECK

Recent literature has pointed out that an appropriate explanation should be related to the model being explained (Adebayo et al., 2018). To ensure that our proposed explanation does indeed reflect the model behavior, we conduct the sanity check proposed by Adebayo et al. (2018) to check if our explanations are adequately different when the model parameters are randomly re-initialized. In the experiment, we randomly re-initialize the last fully-connected layer of the neural network model. We then compute the rank correlation between explanation computed w.r.t. the original model and that w.r.t. the randomized model. From Table 3, we observe that Greedy-AS has a much lower rank correlation comparing to Grad, IG, and LOO, suggesting that Greedy-AS is indeed sensitive to model parameter change and is able to pass the sanity check.

Table 3: Rank correlation between explanations with respect to original and randomized model.

	Grad	IG	SHAP	LOO	BBMP	CFX	Greedy-AS
Corr.	0.30	0.30	0.11	0.49	0.17	0.26	0.18

G STUDENT'S t-TEST ON THE PERFORMANCE IMPROVEMENT OF GREEDY-AS OVER EXISTING METHODS

We conduct a set of Student's t-tests to further verify that the outperformances of the proposed Greedy-AS over existing methods are indeed statistically significant. We compare the AUCs of Greedy-AS and other methods across different criteria. In Table 4, we show the t-test results on the AUCs of Robustness-$\overline{S_r}$ and Robustness-S_r, as well as the results on the AUCs of Insertion and Deletion criteria. In the tables, *win* (*loss*) indicates that the performance improvement (drop) of Greedy-AS to the baselines is statistically significant; otherwise, we use *draw* to indicate insignificant difference between the performances. From the results, we positively verify the statistical significance of the performance improvements of our proposed method over existing explanations on various criteria.

Table 4: The proposed Greedy-AS versus other explanations under various criteria with Student's t-test at 95% confidence level.

Datasets	Criteria	Greedy-AS vs.					
		Grad	IG	SHAP	LOO	BBMP	CFX
MNIST	Robustness-$\overline{S_r}$	win	win	win	win	win	win
	Robustness-S_r	win	win	win	win	win	win
	Insertion	win	win	win	win	win	win
	Deletion	win	win	win	win	win	win
ImageNet	Robustness-$\overline{S_r}$	win	win	win	win	win	win
	Robustness-S_r	draw	win	win	win	win	draw
	Insertion	win	win	win	win	win	win
	Deletion	draw	draw	loss	win	win	draw

H VISUALIZATION ON MNIST

We provide more examples on visualized explanations on MNIST in Figure 10.

Figure 10: Visualization of different explanations on MNIST. The highlighted pixels are the top 20% relevant pixels selected by different methods. We see that Greedy-AS focuses both on crucial positive and pertinent negative regions.

I VISUALIZATION ON IMAGENET

We provide more examples on visualized explanations on ImageNet in Figure 11.

Figure 11: Visualization of different explanations on ImageNet. We see that Greedy-AS focuses more compactly on the areas containing the actual objects being classified.

(a) Targeted explanation for 2 against 0 and 7 respectively.

(b) Targeted explanation for 6 against 4 and 2 respectively.

Figure 12: Comparisons between different methods for targeted explanation against different target classes on MNIST. We note that Oramas et al. (2019) could not handle arbitrarily specified target class and thus is not available to produce different explanations for different target classes.

J COMPARISONS WITH OTHER EXPLANATIONS CAPTURING PERTINENT NEGATIVE FEATURES

While the capability of capturing not only the crucial positive but also the pertinent negative features have also been observed in some recently proposed explanations. Most current methods are not explicitly designed to handle the targeted explanation task which attempt to answer the question "what are the important features that lead to the prediction of class A but not class B", and thus has different limitations. For example, the ability of LRP Bach et al. (2015) to capture pertinent negative features heavily depends on the input range. In Samek et al. (2016), the input images are normalized to have zero mean and a standard deviation of one where the black background will have non-zero value. In such case, LRP would have non-zero attributions on the black background pixels which allows the explanation to capture pertinent negative features. However, as later shown in Dhurandhar et al. (2018), if the input pixel intensity is normalized into the range between 0 and 1 where the background pixels have the values of 0, LRP failed to highlight pertinent negative pixels since the background would always have zero attribution. This is due to the fact that LRP is equivalent to multiplication between Grad and input in a Rectified Linear Unit (ReLU) network as shown in Ancona et al. (2018). In Oramas et al. (2019), unlike our targeted explanation where we know exactly which targeted class the explanation is suggesting against (and by varying the targeted class we observe varying corresponding explanation given), their method by design does not convey such information. The pertinent negative features highlighted by their method by construction is not directly related to a specific target class, and users would need to infer by themselves what target class the pertinent negative features are preventing against. To further grasp the difference, we compare our explanation with theirs in Figure 12. We borrow the results from Oramas et al. (2019) for visualization of their method. Qualitatively, we observe that our method gives the most intuitive explanations. For example, in Figure 12a, the first row shows different explanations that highlight different relevant regions supporting the prediction of a 2 instead of 0. Among the explanations, our method is the only one that highlights the right tail part (green circled) of the digit 2 which also serves as crucial evidence of 2 against 0 in addition to the left vertical gap (which when presented would make 2 looks like a 0) that is roughly highlighted by all three methods. Furthermore, as we change the target class to 7 (as shown in the second row), the explanation provided by LRP does not seem to differ much. This suggests that LRP is not sensitive to the target class change and might fail to provide useful insights towards targeted explanation. On the contrary, we observe that our explanation has a drastic change between different target classes. When explaining against the target 7, our explanation highlights the lower left green circled part which when turned off will make 2 becomes a 7. These results might suggest our method is more capable of handling such targeted explanation task.

K   MORE EXAMPLES ON TEXT CLASSIFICATION

We provide more example explanations on text classification problem in Figure 13.

Figure 13: More examples for explanations on text classification model. The predicted classes for the three input sentences are "Sport", "Health", and "Politics & Government" respectively.

L HUMAN STUDY ON NLP DATASET

To compare and quantitatively measure the top-5 relevant keywords from various methods, we conducted a human study where we asked 10 different users to label the top 5 to 7 keywords for each sentence that they consider to be most relevant to the ground truth label. Then, using the majority chosen keywords as the ground truth, we calculate the precision@k and mean Average Precision (mAP) for the importance ranking from the methods. The results in Table 5 show that Greedy matches human labeling better.

Table 5: Human Study on NLP dataset

	p@1	p@2	p@3	p@4	p@5	mAP
Greedy	0.88	0.82	0.76	0.72	0.66	0.61
Grad	0.60	0.44	0.45	0.51	0.45	0.28