FAIR NODE REPRESENTATION LEARNING VIA ADAPTIVE DATA AUGMENTATION

ABSTRACT

Node representation learning has demonstrated its efficacy for various applications on graphs, which leads to increasing attention towards the area. However, fairness is a largely under-explored territory within the field, which may lead to biased results towards underrepresented groups in ensuing tasks. To this end, this work theoretically explains the sources of bias in node representations obtained via Graph Neural Networks (GNNs). Our analysis reveals that both nodal features and graph structure lead to bias in the obtained representations. Building upon the analysis, fairness-aware data augmentation frameworks on nodal features and graph structure are developed to reduce the intrinsic bias. Our analysis and proposed schemes can be readily employed to enhance the fairness of various GNN-based learning mechanisms. Extensive experiments on node classification and link prediction are carried out over real networks in the context of graph contrastive learning. Comparison with multiple benchmarks demonstrates that the proposed augmentation strategies can improve fairness in terms of statistical parity and equal opportunity, while providing comparable utility to state-of-the-art contrastive methods.

1 INTRODUCTION

Graphs are widely used in modeling and analyzing complex systems such as biological networks or financial markets, which leads to a rise in attention towards various machine learning (ML) tasks over graphs. Specifically, node representation learning is a field with growing popularity. Node representations are mappings from nodes to vector embeddings that contain both structural and attributive information. Their applicability on ensuing tasks has enabled various applications such as traffic forecasting (Opolka et al., 2019), recommendation systems (Ying et al., 2018), and crime forecasting (Jin et al., 2020). Graph neural networks (GNNs) have been prevalently used for representation learning, where node embeddings are obtained by repeatedly aggregating information from neighbors for both supervised and unsupervised learning tasks (Kipf & Welling, 2017; Veličković et al., 2018; García-Durán & Niepert, 2017; Veličković et al., 2019).

It has been shown that ML models propagate pre-existing bias in training data, which may lead to discriminative results for ensuing applications (Dwork et al., 2012; Beutel et al., 2017). Particular to ML over graphs, while GNN-based approaches achieve state-of-the-art results for graph representation learning, they also amplify already existing biases in the training data (Dai & Wang, 2020). For example, nodes in social networks tend to connect to other nodes with similar attributes, which leads to denser connectivity between the nodes with the same sensitive attributes (e.g., gender, race) (Hofstra et al., 2017). Therefore, by aggregating information from the neighbors, the representations obtained by GNNs may be highly correlated with the sensitive attributes. This causes discrimination in the ensuing learning tasks even when the sensitive attributes are not directly used in training (Hajian & Domingo-Ferrer, 2013).

Data augmentation has been widely utilized to improve the generalizability of the trained model, as well as to enable learning in unsupervised methods such as contrastive learning or self-supervised learning. Augmentation strategies have been extensively studied in vision (Shorten & Khoshgoftaar, 2019; Hjelm et al., 2018) and natural language processing (Zhang et al., 2015; Kafle et al., 2017) domains. However, there are comparatively limited work in the graph domain due to the complex, non-Euclidean structure of graphs.

This study focuses on the design of *fairness-aware* graph data augmentation schemes, where the input graph is *adaptively* corrupted to reduce possible bias inherited in both graph topology and nodal features. Although the proposed schemes are presented over their applications using contrastive learning, the introduced augmentation strategies can be flexibly utilized in several GNN-based learning approaches together with other fairness-enhancement methods. Our contributions in this paper can be summarized as follows:

c1) We theoretically analyze the sources of bias that is propagated towards node representations in a GNN-based learning framework.

c2) Based on the analysis, we develop novel fairness-aware graph data augmentations that can reduce potential bias in learning node representations. Our approach is adaptive to both input graph and sensitive attributes, and to the best of our knowledge, is the first study that tackles fairness enhancement through adaptive graph augmentation design.

c3) The proposed strategies incur low additional computation complexity compared to non-adaptive counterparts, and are compatible to operate in conjunction with various GNN-based learning frameworks, including other fairness enhancement methods.

c4) Theoretical analysis is provided to corroborate the effectiveness of the proposed feature masking and node sampling augmentation schemes.

c5) Performance of the proposed graph data augmentation schemes is evaluated on real networks for both node classification and link prediction tasks. It is shown that compared to state-of-the-art graph contrastive learning methods, the novel augmentation schemes improve fairness metrics while providing comparable utility measures.

2 RELATED WORK

Representation learning on graphs. Conventional graph representation learning approaches can be summarized under two categories: factorization-based and random walk-based approaches. Factorization-based methods aim to minimize the difference between the inner product of node representations and a deterministic similarity metric between the nodes (Ahmed et al., 2013; Cao et al., 2015; Ou et al., 2016). Random walk-based approaches, on the other hand, employ stochastic measures of similarity between nodes (Perozzi et al., 2014; Grover & Leskovec, 2016; Tang et al., 2015; Chen et al., 2018). GNNs have gained popularity in graph representation learning, for both supervised learning (Kipf & Welling, 2017; Veličković et al., 2018; Hu et al., 2019; Wu et al., 2019), and unsupervised tasks, e.g., (García-Durán & Niepert, 2017; Hamilton et al., 2017). Specifically, recent success of contrastive learning methods on unsupervised visual representation learning (Wu et al., 2018; Ye et al., 2019; Ji et al., 2019) has paved the way for contrastive learning for unsupervised graph representation learning.

Graph data augmentation. Augmentation strategies have been extensively investigated in vision (Shorten & Khoshgoftaar, 2019; Hjelm et al., 2018) and natural language processing (Zhang et al., 2015; Kafle et al., 2017) domains. However, the area is comparatively under-explored in the graph domain due to the complex, non-Euclidean topology of graphs. Graph augmentation based on graph structure modification has been developed to improve the utility of ensuing tasks (Rong et al., 2019; Zhao et al., 2020; Chen et al., 2020a). Meanwhile, graph data augmentation has been used to generate graph views for unsupervised graph contrastive learning, see, e.g., (Veličković et al., 2019; Opolka et al., 2019; Zhu et al., 2020; 2021), which achieves state-of-the-art results in various learning tasks over graphs such as node classification, regression, and link prediction (Opolka et al., 2019; Veličković et al., 2019; You et al., 2020; Zhu et al., 2020; Peng et al., 2020; Hassani & Khasahmadi, 2020). Among which, (Zhu et al., 2020) is the first study that aims to maximize the agreement of node-level embeddings across two corrupted graph views. Building upon (Zhu et al., 2020), (Zhu et al., 2021) develops adaptive augmentation schemes with respect to various node centrality measures and achieves better results. However, none of these studies are fairness-aware.

Fairness-aware learning on graphs. While fairness is gaining more and more attention in machine learning, it is comparably under-explored on graphs. A pioneering study tackling the fairness problem in graph representation learning based on random walks is developed in (Rahman et al., 2019). In addition, adversarial regularization is employed to account for fairness (Dai & Wang, 2020; Zafar et al., 2019). Furthermore, (Li et al., 2021) presents an algorithm to create a fair adjacency matrix for link prediction task based on dyadic fairness. A biased edge dropout scheme is proposed in (Spinelli et al., 2021). However, it is not adaptive to the graph structure, and can be viewed as a special case of

our framework. Fairness-aware graph contrastive learning is first studied in (Agarwal et al., 2021), where a layer-wise weight normalization scheme along with graph augmentations is introduced to ensure counterfactual fairness.

3 FAIRNESS IN GNN-BASED REPRESENTATION LEARNING

GNN-based approaches are the state-of-the-art for node representation learning. However, it has been demonstrated that the utilization of graph structure in the learning process not just propagates but also amplifies a possible bias towards certain sensitive groups (Dai & Wang, 2020). To this end, this section investigates the sources of bias in the generated representations via GNN-based learning. It carries out an analysis revealing that both nodal features and graph structure lead to bias, for which several graph data augmentation frameworks are introduced.

3.1 PRELIMINARIES

This study aims to learn fairness-aware nodal representations for a given graph $\mathcal{G} := (\mathcal{V}, \mathcal{E})$ where $\mathcal{V} := \{v_1, v_1, \cdots, v_N\}$ denotes the node set, and $\mathcal{E} \subseteq \mathcal{V} \times \mathcal{V}$ represents the edge set. $\mathbf{X} \in \mathbb{R}^{N \times F}$ and $\mathbf{A} \in \{0,1\}^{N \times N}$ are used to denote the feature and adjacency matrices, respectively, with the (i,j)-th entry $a_{ij} = 1$ if and only if $e_{ij} := (v_i, v_j) \in \mathcal{E}$. Degree matrix $\mathbf{D} \in \mathbb{R}^{N \times N}$ is defined to be a diagonal matrix with the nth diagonal entry d_n denoting the degree of v_n. For the fairness examination, sensitive attributes of the nodes are represented with $\mathbf{s} \in \{0,1\}^{N \times 1}$, where the existence of a single, binary sensitive attribute is considered. In this work, unsupervised methods are chosen as enabling schemes for the representation generation where given the inputs $\mathbf{A}, \mathbf{X}$, and $\mathbf{s}$, the main purpose is to learn a mapping $f : \mathbb{R}^{N \times N} \times \mathbb{R}^{N \times F} \times \mathbb{R}^{N \times 1} \to \mathbb{R}^{N \times F^L}$ that generates F^L dimensional (generally $F^L \ll F$) unbiased nodal representations $\mathbf{H}^L = f(\mathbf{A}, \mathbf{X}, \mathbf{s}) \in \mathbb{R}^{N \times F^L}$ through an L-layer GNN, which can be used in an ensuing task such as node classification. $\mathbf{x}_i \in \mathbb{R}^F$, $\mathbf{h}_i^l \in \mathbb{R}^{F^l}$, and $s_i \in \{0,1\}$ denote the feature vector, representation at layer l and the sensitive attribute of node v_i. Furthermore, $\mathcal{S}_0$ and $\mathcal{S}_1$ denote the set of nodes whose sensitive attributes are 0 and 1, respectively. Define inter-edge set $\mathcal{E}^\chi := \{e_{ij} | v_i \in \mathcal{S}_a, v_j \in \mathcal{S}_b, a \neq b\}$, while intra-edge set is defined as $\mathcal{E}^\omega := \{e_{ij} | v_i \in \mathcal{S}_a, v_j \in \mathcal{S}_b, a = b\}$. Similarly, the set of nodes having at least one inter edge is denoted by $\mathcal{S}^\chi$, while $\mathcal{S}^\omega$ defines the set of nodes that have no inter-edges. The intersection of the sets $\mathcal{S}_0, \mathcal{S}^\chi$ is denoted as $\mathcal{S}_0^\chi$. Additionally, d_i^χ and d_i^ω denote the numbers of inter-edges and intra-edges adjacent to v_i, respectively. Finally, $||$ denotes the entry-wise absolute value for scalar or vector inputs, while it is used for the cardinality when the input is a set.

3.2 ANALYSIS FOR BIAS IN GNN REPRESENTATIONS

This subsection presents an analysis to find out the sources of bias in node representations generated by GNNs. Analysis is developed for the mean aggregation scheme in which aggregated representations at layer l, $\mathbf{Z}^l \in \mathbb{R}^{N \times F^l}$, are generated such that $\mathbf{z}_i^l = \frac{1}{d_i} \sum_{v_j \in \mathcal{N}(i)} \mathbf{h}_j^{l-1}$ for $i = \{1, \cdots, N\}$, where $\mathbf{z}_i^l$ is the ith row of $\mathbf{Z}^l$ corresponding to node v_i, d_i denotes the degree of node v_i, $\mathcal{N}(i)$ refers to the neighbor set of node v_i (including itself). The recursive relation in a GNN layer in which left normalization is applied for feature smoothing is $\mathbf{H}^l = \sigma(\mathbf{D}^{-1}(\mathbf{A} + \mathbf{I}_N)\mathbf{H}^{l-1}\mathbf{W}^l)$ where $\mathbf{W}^l$ is the weight matrix in layer l, and $\mathbf{I}_N \in \mathbb{R}^{N \times N}$ denotes an identity matrix. With these definitions, the relation between the aggregated information $\mathbf{Z}^l$ and node representations $\mathbf{H}^l$ becomes equivalent to $\mathbf{H}^l = \sigma(\mathbf{Z}^l\mathbf{W}^l)$ at the lth GNN layer. As the provided analysis is applicable to every layer, l superscript is dropped in the following to keep the notation simple.

It has been demonstrated that features that are correlated with the sensitive attribute result in bias even when the sensitive attribute is not utilized in the learning process (Hajian & Domingo-Ferrer, 2013). This work provides an analysis on the correlation of $\mathbf{s}$ with $\mathbf{Z}$, and aims to reduce it. Note that, the reduction of correlation can still allow the generation of discriminable representations for different class labels, if the discriminability is provided by non-sensitive attributes. The correlation between the sensitive attributes $\mathbf{s}$ and aggregated representations can be written as

$$\rho_i = \text{Corr}(\tilde{\mathbf{z}}_{:,i}, \mathbf{s}) = \frac{\sum_{j=1}^N \left(z_{ji} - \frac{1}{N}\sum_{k=1}^n z_{ki}\right)\left(\mathbf{s}_j - \frac{1}{N}\sum_{k=1}^n \mathbf{s}_k\right)}{\sqrt{\sum_{j=1}^N \left(z_{ji} - \frac{1}{N}\sum_{k=1}^n z_{ki}\right)^2}\sqrt{\sum_{j=1}^N \left(\mathbf{s}_j - \frac{1}{N}\sum_{k=1}^N \mathbf{s}_k\right)^2}}$$

where $\tilde{\mathbf{z}}_{:,i}, i = 1 \cdots F$ denotes the ith column of $\mathbf{Z}$. In the analysis, it is assumed that the node representations have different distributions depending on the sensitive attributes such that $\mathbb{E}_{\mathbf{h}_i \sim U}[\mathbf{h}_i \mid v_i \in \mathcal{S}_0] = \boldsymbol{\mu}_0$ and $\mathbb{E}_{\mathbf{h}_j \sim U}[\mathbf{h}_j \mid v_j \in \mathcal{S}_1] = \boldsymbol{\mu}_1$, where U denotes the uniform distribution (Li et al., 2021). Additionally, it is assumed that these distributions have the same maximal deviation Δ, that is $\forall v_j \in S_i$ with $i \in \{0, 1\}$, $\|\mathbf{h}_j - \boldsymbol{\mu}_i\|_\infty \leq \Delta$. Based on these assumptions, the following theorem shows that $\|\boldsymbol{\rho}\|_1$ can be bounded from above, which will serve as a guideline to design a fairness-aware graph data augmentation scheme. The proof can be found in Appendix A.1.

Theorem 1. *The total correlation between the sensitive attributes* $\mathbf{s}$ *and representations* $\mathbf{Z}$ *that are obtained after a mean aggregation over graph* $\mathcal{G}$, $\|\boldsymbol{\rho}\|_1$, *can be bounded above by*

$$\|\boldsymbol{\rho}\|_1 \leq \|\mathbf{c}\|_1 (\|\boldsymbol{\delta}\|_1 \max(\gamma_1, \gamma_2) + 2N\Delta) \tag{1}$$

where $c_i := \frac{\sqrt{|\mathcal{S}_0||\mathcal{S}_1|}}{N\sigma_{\tilde{\mathbf{z}}_{:,i}}}$, *with* $\sigma_{\boldsymbol{\theta}} := \sqrt{\frac{1}{N}\sum_{n=1}^{N}(\theta_n - \frac{1}{N}\sum_{i=1}^{N}\theta_n)^2}, \forall \boldsymbol{\theta} \in \mathbb{R}^N$, $\boldsymbol{\delta} := \boldsymbol{\mu}_0 - \boldsymbol{\mu}_1$, $\gamma_1 :=$ $\left|1 - \frac{|\mathcal{S}_0^\chi|}{|\mathcal{S}_0|} - \frac{|\mathcal{S}_1^\chi|}{|S_1|}\right|$, $\gamma_2 = \left|1 - 2\min\left(\text{mean}\left(\frac{d_m^\chi}{d_m^\chi + d_m^\omega}|v_m \in \mathcal{S}_0\right), \text{mean}\left(\frac{d_n^\chi}{d_n^\chi + d_n^\omega}|v_n \in \mathcal{S}_1\right)\right)\right|$, *and* $\text{mean}(\cdot)$ *denotes the sample mean operation.*

The upper bound presented in equation 1 can be lowered by i) utilizing feature masking which has an effect on the term $\|\boldsymbol{\mu}_0 - \boldsymbol{\mu}_1\|_1$ at the first layer, ii) node sampling that can change the value of γ_1, and iii) edge augmentations that can reduce the value of γ_2.

3.3 FAIR GRAPH DATA AUGMENTATIONS

Data augmentation has been studied extensively in order to enable certain unsupervised learning schemes such as contrastive learning, self-supervised learning or as a general framework to improve the generalizability of the trained models over unseen data. However, the design of graph data augmentations is still a developing research area due to the challenges introduced by complex, non-Euclidean graph structure. Several augmentation schemes over the graph structure are proposed in order to enhance the generalizability of GNNs (Rong et al., 2019; Zhao et al., 2020), while both topological (e.g., edge/node deletion) and attributive (e.g., feature shuffling/masking) corruption schemes have been developed in the context of contrastive learning (Veličković et al., 2019; You et al., 2020; Zhu et al., 2021; 2020). However, none of these works are fairness-aware. Hence, in this work, novel data augmentation schemes that are *adaptive* to the sensitive attributes, as well as the input graph structure are introduced with Theorem 1 as guidelines.

3.3.1 FEATURE MASKING

In this subsection, an augmentation framework on nodal features $\mathbf{H}^0 = \mathbf{X}$ is presented in order to mitigate possible intrinsic bias propagated by them. Proposed scheme aims to reduce the term $\|\boldsymbol{\delta}\|_1$ in equation 1 for the first layer of GNN without losing significant information that the features provide. Specifically, the random feature masking scheme used in (You et al., 2020; Zhu et al., 2020) where each feature has the same masking probability is modified to assign higher masking probabilities to the features varying more across different sensitive groups. Thus, masking probabilities are generated based on the term $|\boldsymbol{\delta}|$. Let $\bar{\boldsymbol{\delta}} := \frac{|\boldsymbol{\delta}| - \min(|\boldsymbol{\delta}|)}{\max(|\boldsymbol{\delta}|) - \min(|\boldsymbol{\delta}|)}$ denote the normalized $|\boldsymbol{\delta}|$, the feature masking probability can then be designed as

$$\mathbf{p}^{(m)} = \min\left(\frac{\alpha\bar{\boldsymbol{\delta}}}{\frac{1}{F}\sum_{i=1}^{F}\bar{\delta}_i}, 1\right) \tag{2}$$

where α is a hyperparameter. The feature mask $\mathbf{m} \in \{0, 1\}^F$ is then generated as a random binary vector, with the i-th entry of $\mathbf{m}$ drawn independently from Bernoulli distribution with $p_i = (1 - p_i^{(m)})$ for $i = 1, \ldots, F$. The augmented feature matrix is obtained via

$$\tilde{\mathbf{X}} = [\mathbf{m} \circ \mathbf{x}_1; \ldots; \mathbf{m} \circ \mathbf{x}_N]^\top, \tag{3}$$

where $[\cdot; \cdot]$ denotes the concatenation operator, and $\circ$ represents the Hadamard product. Due to the probabilistic nature of the proposed feature masking scheme, the resulting $\tilde{\boldsymbol{\delta}}$ is a random vector with entry $\tilde{\delta}_i$ having

$$|\tilde{\delta}_i| = \begin{cases} |\delta_i|, & \text{with probability } p_i, \\ 0, & \text{with probability } 1 - p_i \end{cases} \tag{4}$$

where $p_i := 1 - p_i^{(m)}$ is the probability that the i^{th} feature is not masked in the graph view. The following proposition shows that the novel, adaptive feature masking approach can decrease $\|\boldsymbol{\rho}\|_1$ compared to random feature masking, the proof of which can be found in Appendix A.2.

Proposition 1. *In expectation, the proposed adaptive feature masking scheme results in a lower $\|\tilde{\boldsymbol{\delta}}\|_1$ value compared to uniform feature masking, meaning*

$$E_{\mathbf{p}}[\|\tilde{\boldsymbol{\delta}}\|_1] \leq E_{\mathbf{q}}[\|\tilde{\boldsymbol{\delta}}\|_1] \tag{5}$$

where $\mathbf{q}$ corresponds to the uniform masking scheme, with masking probability $1 - q_i$, and $q_i = \frac{1}{F} \sum_{j=1}^{F} p_j$.

3.3.2 NODE SAMPLING

In the present subsection, an adaptive node sampling framework is introduced to decrease the term $\gamma_1 := \left| 1 - \left(\frac{|\mathcal{S}_0^\chi|}{|\mathcal{S}_0|} + \frac{|\mathcal{S}_1^\chi|}{|\mathcal{S}_1|} \right) \right| = \left| 1 - \left(\frac{|\mathcal{S}_0^\chi|}{|\mathcal{S}_0^\chi| + |\mathcal{S}_0^\omega|} + \frac{|\mathcal{S}_1^\chi|}{|\mathcal{S}_1^\chi| + |\mathcal{S}_1^\omega|} \right) \right|$ in equation 1 in Theorem 1, and hence to reduce the intrinsic bias that the graph topology can create. Specifically, a subset of nodes is selected at every epoch and the training is carried over the subgraph induced by the sampled nodes. This augmentation mainly aims at reducing the bias by selecting a subset of more balanced groups, meanwhile it also helps reduce the computational and memory complexity in training.

The proposed node sampling is adaptive to the input graph, that is, it depends on the cardinalities of the sets $\mathcal{S}_0^\chi, \mathcal{S}_1^\chi, \mathcal{S}_0^\omega$, and $\mathcal{S}_1^\omega$. The developed scheme copes with the case $|\mathcal{S}^\chi| \leq |\mathcal{S}^\omega|$. In algorithm design, it is assumed that if $|\mathcal{S}^\chi| \leq |\mathcal{S}^\omega|$ then $|\mathcal{S}_0^\chi| \leq |\mathcal{S}_0^\omega|$ and $|\mathcal{S}_1^\chi| \leq |\mathcal{S}_1^\omega|$ (same for $\mathcal{S}^\omega$), which holds for all real graphs in our experiments, but our design principles can be readily extended to different settings as well.

Given input graph $\mathcal{G}$, the augmented graph $\tilde{\mathcal{G}}$ can be obtained as an induced subgraph from a subset of nodes $\tilde{\mathcal{V}}$. All nodes in $\mathcal{S}^\chi$ are retained, ($\tilde{\mathcal{S}}_0^\chi = \mathcal{S}_0^\chi$ and $\tilde{\mathcal{S}}_1^\chi = \mathcal{S}_1^\chi$), while subsets of nodes $\bar{\mathcal{S}}_0^\omega$ and $\bar{\mathcal{S}}_1^\omega$ are randomly sampled from $\mathcal{S}_0^\omega$ and $\tilde{\mathcal{S}}_1^\omega$ with sample sizes $|\bar{\mathcal{S}}_0^\omega| = |\mathcal{S}_0^\chi|$ and $|\bar{\mathcal{S}}_1^\omega| = |\mathcal{S}_1^\chi|$, respectively . See also Algorithm 1 in Appendix A.3. The cardinalities of node sets in the resulting graph augmentation $\tilde{\mathcal{G}}$ satisfy $\gamma_1 = 0$. (See Appendix A.3 for details.)

Remark 1. Note that the resulting graph $\tilde{\mathcal{G}}$ yields $\gamma_1 = 0$ as long as $|\tilde{\mathcal{S}}_0^\chi|/|\tilde{\mathcal{S}}_0| = 1/2 + \phi$ and $|\tilde{\mathcal{S}}_1^\chi|/|\tilde{\mathcal{S}}_1| = 1/2 - \phi$ is satisfied for any $-1/2 < \phi < 1/2$. The presented scheme here simply sets $\phi = 0$, which results in a balanced ratio across groups, but the performance can be improved if ϕ is selected carefully for specific datasets.

3.3.3 AUGMENTATION ON GRAPH CONNECTIVITY

In social networks, users connect to other users that are similar to themselves with higher probabilities (Mislove et al., 2010), hence the graph connectivity naturally inherits bias towards potential minority groups. Training a node representation learning model on such graphs may result in an intrinsic utilization of the sensitive attributes. The present subsection introduces augmentation schemes over edges to provide a balanced graph structure that mitigates the bias caused by the graph connectivity. We note that even though the strategy is presented for the case where $|\mathcal{E}_x| \leq |\mathcal{E}_o|$ (which holds for all datasets considered herein), the case for $|\mathcal{E}_x| \geq |\mathcal{E}_o|$ is simply its analogous.

Consider the extremely balanced case where all nodes in the network have the same number of neighbors from each sensitive group, i.e., $d_i^\omega = d_i^\chi, \forall v_i \in \mathcal{V}$. For this scenario, γ_2 in equation 1 is minimized, since $\gamma_2 = \left| 1 - \min \left(\frac{d_i^\chi}{d_i^\chi + d_i^\omega} | v_i \in \mathcal{S}_0 \right) - \min \left(\frac{d_j^\chi}{d_j^\chi + d_j^\omega} | v_j \in \mathcal{S}_1 \right) \right| = 0$. This suggests that an ideal augmented graph $\tilde{\mathcal{G}}$ could be generated by deleting edges from or adding edges to $\mathcal{G}$ such that each node has exactly the same number of neighbors from each sensitive group. However, such a per-node sampling scheme is computationally complex and may not be ideal for large-scale

graphs. To this end, we propose global probabilistic edge augmentation schemes such that in the augmented graph,

$$\mathbb{E}\left[|\tilde{\mathcal{E}}^{\omega}|\right] = \mathbb{E}\left[|\tilde{\mathcal{E}}^{\chi}|\right]. \tag{6}$$

Here the expectation is taken with respect to the randomness in the augmentation design. We note that the values of γ_2 obtained in our experiments on real datasets shows that the global approach can indeed help to reduce the value of γ_2 (see Appendix A.8).

Adaptive Edge Deletion. To obtain a balanced graph structure, we first develop an adaptive edge deletion scheme where edges are removed with certain deletion probabilities. Based on the graph structure and sensitive attributes, the probabilities are assigned as

$$p^{(e)}(e_{ij}) = \begin{cases} 1 - \pi, & \text{if } s_i \neq s_j \\ 1 - \frac{|\mathcal{E}^{\chi}|}{2\left|\mathcal{E}^{\omega}_{\mathcal{S}_0}\right|}\pi, & \text{if } s_i = s_j = 0 \\ 1 - \frac{|\mathcal{E}^{\chi}|}{2\left|\mathcal{E}^{\omega}_{\mathcal{S}_1}\right|}\pi, & \text{if } s_i = s_j = 1 \end{cases} \tag{7}$$

where $p^{(e)}(e_{ij})$ is the removal probability of the edge connecting nodes v_i and v_j, π is a hyperparameter, and $\mathcal{E}^{\omega}_{\mathcal{S}_i}$ denotes the set of intra-edges connecting the nodes in S_i. Note that π is chosen to be 1 in this work, but it can be selected by schemes such as grid search to improve performance.

While this graph-level edge deletion scheme does not not directly minimize γ_2, it provides a balanced global structure such that $\mathbb{E}_{\mathbf{p}^{(e)}}[|\tilde{\mathcal{E}}^{\omega}_{\mathcal{S}_0}|] = \mathbb{E}_{\mathbf{p}^{(e)}}[|\tilde{\mathcal{E}}^{\omega}_{\mathcal{S}_1}|] = \frac{1}{2}\mathbb{E}_{\mathbf{p}^{(e)}}[|\tilde{\mathcal{E}}^{\chi}|]$, henceforth equation 6 holds in the augmented graph $\tilde{\mathcal{G}}$, see Appendix A.4 for more details.

Adaptive Edge Addition. For graphs that are very sparse, edge deletion may not be an ideal graph augmentation as it may lead to unstable results. In this case, an adaptive edge addition framework is developed to obtain a more balanced graph structure. Specifically, for graphs where $|\mathcal{E}^{\chi}| \leq |\mathcal{E}^{\omega}|$ holds, $|\mathcal{E}^{\omega}| - |\mathcal{E}^{\chi}|$ pairs of the nodes are sampled uniformly from $\mathcal{S}^{\chi}_0$ and $\mathcal{S}^{\chi}_1$ with replacement. Then, a new edge is created to connect each sampled pair of nodes, in order to obtain an augmented graph $\tilde{\mathcal{G}}$ for which equation 6 holds. Note that experimental results in Section 4 also show that edge addition may become a better alternative over edge deletion for graphs that are sparse in inter-edges.

Remark 2. Overall, while a subset of these augmentation schemes can be employed based on the input graph properties (sparse/dense, large/small), all schemes can also be employed on the input graph sequentially. The framework where node sampling, edge deletion, edge addition are employed sequentially together with feature masking is called 'FairAug'. It is worth emphasizing that edge augmentation schemes should always follow node sampling, as performing node sampling changes the distribution of edges. Since the cardinalities of different sets will be calculated only once (in pre-processing), we note that the proposed augmentations will not incur significant additional cost.

4 EXPERIMENTS

In this section, experiments are carried out on 7 real-world datasets for node classification and link prediction tasks. Performances of our proposed adaptive augmentations are compared with baseline schemes in terms of utility and fairness metrics.

4.1 DATASETS AND SETTINGS

Datasets. Experiments are conducted on real-world social networks and citation networks consisting of Pokec-z, Pokec-n (Dai & Wang, 2020), UCSD34, Berkeley13 (Red et al., 2011), Cora, Citeseer, Pubmed. Pokec-z and Pokec-n sampled from a larger social network, Pokec (Takac & Zabovsky, 2012), are used in node classification experiments where Pokec is a Facebook-like, social network used in Slovakia. While the original social network includes millions of users, Pokec-z and Pokec-n are generated by collecting the information of users belonging to two major regions (Dai & Wang, 2020). The region information is treated as the sensitive attribute, while the working field of the users is the label to be predicted in the classification task. Both attributes are binarized, see also (Dai

& Wang, 2020). UCSD34 and Berkeley13 are Facebook networks where edges are created based on the friendship information in social media. Each user (node) has 7 dimensional nodal features including student/faculty status, gender, major, etc. Gender is utilized as the sensitive attribute in UCSD34 and Berkeley13. Cora, Citeseer, and Pubmed are citation networks that consider articles as nodes and descriptions of articles as their nodal attributes. In these datasets, the category of the articles is used as the sensitive attribute. Statistics for datasets are presented in Tables 5 and 6 of Appendix A.5.

Evaluation Metrics. Performance of the node classification task is evaluated in terms of accuracy. Two quantitative group fairness metrics are used to assess the effectiveness of fairness aware strategies in terms of **statistical parity**: $\Delta_{SP} = |P(\hat{y} = 1 \mid s = 0) - P(\hat{y} = 1 \mid s = 1)|$ and **equal opportunity**: $\Delta_{EO} = |P(\hat{y} = 1 \mid y = 1, s = 0) - P(\hat{y} = 1 \mid y = 1, s = 1)|$, where y and $\hat{y}$ denote the ground-truth and the predicted labels, respectively. Lower values for Δ_{SP} and Δ_{EO} imply better fairness performance (Dai & Wang, 2020). For the link prediction task, both accuracy and Area Under the Curve (AUC) are employed as utility metrics. As the fairness metrics, the definitions of statistical parity and equal opportunity are modified for link prediction such that $\Delta_{SP} = |P(\hat{y} = 1 \mid e \in \mathcal{E}^{\chi}) - P(\hat{y} = 1 \mid e \in \mathcal{E}^{\omega})|$ and $\Delta_{EO} = |P(\hat{y} = 1 \mid y = 1, e \in \mathcal{E}^{\chi}) - P(\hat{y} = 1 \mid y = 1, e \in \mathcal{E}^{\omega})|$, where e denotes the edges and $\hat{y}$ is the decision for whether the edge exists.

Implementation details. The proposed augmentation scheme is tested on social networks with node representations generated through an unsupervised contrastive learning framework. Node classification and link prediction are employed as ensuing tasks that evaluate the performances of generated node representations. In addition, we also provide link prediction results obtained via an end-to-end graph convolutional network (GCN) model on citation networks. Further details on the implementation of the experiments are provided in Appendix A.7. Contrastive learning is utilized to demonstrate the effects of the proposed augmentation schemes, as augmentations are inherently utilized in its original design (You et al., 2020). Specifically, GRACE (Zhu et al., 2020) is employed as our baseline framework. GRACE constructs two different graph views using random, non-adaptive augmentation schemes, which we replaced by augmentations obtained via FairAug in the experiments. For more details on the employed contrastive learning framework, see Appendix A.6.

Baselines.

We present the performances on a total of 7 baseline studies. As we examine our proposed augmentations in the context of contrastive learning, graph contrastive learning schemes are employed as the natural baselines. Said schemes are Deep Graph Infomax (DGI) (Veličković et al., 2019), Deep Graph Contrastive Representation Learning (GRACE) (Zhu et al., 2020), Graph Contrastive Learning with Adaptive Augmentations (GCA) (Zhu et al., 2021), and Fair and Stable Graph Representation Learning (NIFTY) (Agarwal et al., 2021). We note that the objective function of NIFTY (Agarwal et al., 2021) consists of both supervised and unsupervised components, and its results for the unsupervised setting are provided here given the scope of this paper. In addition, as another family of unsupervised approaches, random walk-based methods for unsupervised node representation generation are also considered. Such schemes include DeepWalk (Perozzi et al., 2014), Node2Vec (Grover & Leskovec, 2016), and FairWalk (Rahman et al., 2019). Lastly, for end-to-end link prediction, we present results for the random edge dropout scheme (Rong et al., 2019).

4.2 EXPERIMENTAL RESULTS

The comparison between baselines and our proposed framework FairAug is presented in Table 1. Note that 'FairAug wo ED' in Table 1 refers to FairAug where edge deletion (ED) is removed from the chain, but all node sampling (NS), edge addition (EA), and feature masking (FM) are still employed. Firstly, the results of Table 1 show that FairAug provides roughly 45% reduction in fairness metrics over GRACE, the strategy it is built upon, while providing similar accuracy values. Second, we note that similar to our framework, GCA is built upon GRACE through adaptive augmentations as well. However, the adaptive augmentations utilized in GCA are not fairness-aware, and the results of Table 1 demonstrate that the effect of such augmentations on the fairness metrics is unpredictable. Third, the results indicate that all contrastive learning methods provide better fairness performance than random walk-based methods on evaluated datasets, including Fairwalk, which is a fairness-aware study. Since the sole information source of random walk-based studies is the graph structure, obtained results confirm that the graph topology indeed propagates bias, which

Table 1: Comparative Results with Baselines on Node Classification

	Pokec-z			Pokec-n		
	Accuracy (%)	Δ_{SP} (%)	Δ_{EO} (%)	Accuracy (%)	Δ_{SP} (%)	Δ_{EO}(%)
DeepWalk	60.82 ± 0.77	9.79 ± 3.43	8.51 ± 1.67	59.66 ± 1.02	20.19 ± 3.38	22.96 ± 3.44
Node2Vec	61.56 ± 0.50	16.18 ± 12.40	14.88 ± 12.31	60.31 ± 0.75	20.76 ± 1.64	20.32 ± 1.36
FairWalk	57.48 ± 0.11	12.03 ± 10.19	10.95 ± 8.82	57.44 ± 0.73	15.00 ± 1.40	15.72 ± 1.80
DGI	65.56 ± 1.29	4.82 ± 1.89	5.81 ± 0.97	65.71 ± 0.24	5.18 ± 2.15	7.16 ± 2.44
GRACE	$\mathbf{67.09} \pm 0.47$	6.20 ± 2.22	6.18 ± 2.46	$\mathbf{67.90} \pm 0.13$	8.85 ± 1.39	10.13 ± 2.11
GCA	66.85 ± 0.71	7.40 ± 4.14	7.46 ± 4.09	67.02 ± 0.43	5.31 ± 0.62	7.75 ± 1.49
NIFTY	66.09 ± 0.40	5.86 ± 1.97	6.19 ± 1.72	65.44 ± 0.17	5.18 ± 2.80	5.78 ± 3.18
FairAug	67.04 ± 0.69	3.29 ± 1.66	$\mathbf{3.04} \pm 1.37$	67.88 ± 0.45	4.81 ± 0.59	6.52 ± 0.99
FairAug wo ED	67.38 ± 0.31	$\mathbf{2.66} \pm 3.22$	4.26 ± 2.92	67.57 ± 0.18	$\mathbf{3.37} \pm 0.62$	$\mathbf{5.13} \pm 1.12$

Table 2: Ablation Study on Node Classification

	Pokec-z			Pokec-n		
	Accuracy (%)	Δ_{SP} (%)	Δ_{EO} (%)	Accuracy (%)	Δ_{SP} (%)	Δ_{EO}(%)
GRACE	67.09 ± 0.47	6.20 ± 2.22	6.18 ± 2.46	67.90 ± 0.13	8.85 ± 1.39	10.13 ± 2.11
FairAug	67.04 ± 0.69	3.29 ± 1.66	$\mathbf{3.04} \pm 1.37$	67.88 ± 0.45	4.81 ± 0.59	6.52 ± 0.99
FairAug wo FM	66.88 ± 0.42	4.64 ± 1.91	5.50 ± 1.80	66.15 ± 0.75	7.61 ± 0.29	9.28 ± 1.06
FairAug wo NS	67.01 ± 0.41	6.05 ± 2.63	6.83 ± 2.88	66.33 ± 0.20	6.26 ± 0.26	9.16 ± 0.63
FairAug wo ED	$\mathbf{67.38} \pm 0.31$	$\mathbf{2.66} \pm 3.22$	4.26 ± 2.92	67.57 ± 0.18	$\mathbf{3.37} \pm 0.62$	$\mathbf{5.13} \pm 1.12$
FairAug wo EA	66.96 ± 1.08	2.86 ± 1.79	3.22 ± 1.29	$\mathbf{67.96} \pm 0.19$	7.13 ± 0.29	9.40 ± 0.81

is consistent with the motivation of our graph data augmentation design. Finally, the results of Table 1 demonstrate that the closest competitor scheme to FairAug is NIFTY (Agarwal et al., 2021) in terms of fairness measures. For Δ_{SP}, FairAug outperforms NIFTY on both datasets, whereas in terms of Δ_{EO}, FairAug and NIFTY outperform each other on Pokec-z and Pokec-n, respectively. Table 1 shows that the ED-removed version of FairAug, 'FairAug wo ED', outperforms NIFTY on Pokec-n as well, suggesting that at least one of the proposed strategies outperform all considered benchmark schemes in both Δ_{SP} and Δ_{EO}. This fairness performance improvement achieved by ED removal motivated us to conduct an ablation study on the building blocks of FairAug, which we present in the sequel.

Table 2 lists the results of an ablation study for FairAug, where the last four rows demonstrate the effects of the removal of FM, NS, ED, and EA, respectively. Pokec-z and Pokec-n are highly unbalanced datasets ($|\mathcal{E}^\omega| \approx 20|\mathcal{E}^\chi|$) with a considerable sparsity in inter-edges (see Table 5 of Appendix A.5). For such networks, the exact probabilities presented in equation 7 cannot be utilized for edge deletion as it would result in the deletion of a significantly large portion of the edges, damaging the structure of the graph. We employ an upper limit on the deletion probabilities to avoid this (see Appendix A.7). However, with such a limit, the proposed ED framework alone cannot sufficiently balance $|\mathcal{E}^\omega|$ and $|\mathcal{E}^\chi|$. At this point, we note that since $|\mathcal{S}^\omega| > |\mathcal{S}^\chi|$, node sampling also provides a way of decreasing $|\mathcal{E}^\omega|$ by excluding nodes from the set $\mathcal{S}^\omega$ when generating the subgraph. As the graph was already sparse initially in inter-edges (i.e., small $|\mathcal{E}^\chi|$), employing both NS and ED causes a similar over-deletion of intra-edges and creates unstable results due to the significantly distorted graph structure. Overall, combining this phenomenon with the results of Table 2, in order to balance the input graphs on both Pokec-z and Pokec-n consistently (which have $|\mathcal{E}^\omega| >> |\mathcal{E}^\chi|$ and inter-edge sparsity), node sampling is observed to be a better choice than edge manipulations.

Table 3 presents the obtained results for link prediction in the framework of contrastive learning. Results demonstrate that 'FairAug wo NS' consistently improves the fairness metrics of the framework it is built upon (GRACE), together with similar utility measures. In addition, comparing GCA and GRACE, obtained results confirm our previous assessment regarding the unpredictable effect of GCA's augmentations on the fairness metrics. Finally, comparing FairAug with and without NS, the results of Table 3 show that in UCSD34 and Berkeley13, the employment of node sampling can be ineffective in improving fairness metrics, or can even worsen them. In UCSD34 and Berkeley13, we have $|\mathcal{S}^\chi| >> |\mathcal{S}^\omega|$ (see Table 5 of Appendix A.5). Therefore, for NS on these datasets, half of the nodes are sampled randomly from the sets $\mathcal{S}_1^\chi$ and $\mathcal{S}_0^\chi$ (as the limit on the minimum node

Table 3: Link prediction results obtained on node representations

	UCSD34			Berkeley13		
	AUC (%)	Δ_{SP} (%)	Δ_{EO} (%)	AUC (%)	Δ_{SP} (%)	Δ_{EO}(%)
GCA	71.59 ± 0.29	0.70 ± 0.27	1.92 ± 0.45	69.69 ± 0.38	$\mathbf{0.50} \pm 0.36$	6.52 ± 0.99
GRACE	71.57 ± 0.28	0.49 ± 0.28	1.48 ± 0.70	69.55 ± 0.46	0.76 ± 0.44	4.34 ± 1.20
FairAug	71.46 ± 0.30	0.71 ± 0.38	1.62 ± 0.62	69.48 ± 0.29	0.70 ± 0.43	4.24 ± 0.90
FairAug wo NS	71.50 ± 0.31	$\mathbf{0.41} \pm 0.32$	$\mathbf{1.16} \pm 0.65$	69.65 ± 0.33	0.68 ± 0.34	$\mathbf{4.22} \pm 0.97$

Table 4: Employment of fair edge deletion as an edge dropout method

	Cora			
	Accuracy (%)	AUC (%)	Δ_{SP} (%)	Δ_{EO} (%)
Edge Dropout	82.79 ± 0.83	90.52 ± 0.52	57.22 ± 2.19	36.18 ± 4.53
Fair ED	80.38 ± 1.14	87.95 ± 1.22	48.78 ± 2.58	27.79 ± 3.89
	Citeseer			
Edge Dropout	78.30 ± 1.17	87.93 ± 1.05	43.05 ± 2.39	25.45 ± 3.69
Fair ED	77.26 ± 1.80	86.79 ± 1.39	39.90 ± 3.57	25.02 ± 6.93
	Pubmed			
Edge Dropout	88.63 ± 0.34	95.14 ± 0.16	45.59 ± 0.78	15.81 ± 0.92
Fair ED	87.48 ± 0.54	94.15 ± 0.36	40.90 ± 1.10	11.70 ± 0.68

sampling budget is half of the initial group size to avoid a possible over-sampling, see Appendix A.7). Since $|\mathcal{S}^\chi| >> |\mathcal{S}^\omega|$, such a sampling framework coincides with random sampling, which makes the effects of the proposed node sampling scheme unpredictable on the fairness metrics. Furthermore, while γ_1 suggests that the cardinality of the set $|\mathcal{S}^\chi|$ should be reduced when $|\mathcal{S}^\omega| \leq |\mathcal{S}^\chi|$, γ_1 actually appears in the upper bound and not in the exact $\|\boldsymbol{\rho}\|_1$ expression. The removal of nodes with inter-edges is actually counter-intuitive, as inter-edges generally help to reduce bias in graphs where $|\mathcal{E}^\omega| \geq |\mathcal{E}^\chi|$ (which holds for all datasets considered in this paper). Therefore, the proposed node sampling framework becomes effective for graph structures providing $|\mathcal{S}^\omega| \geq |\mathcal{S}^\chi|$. The effect of node sampling on Facebook networks is further investigated through γ_1 and γ_2 in Appendix A.8, which corroborates the explanations on the random/detrimental effect of node sampling for these datasets.

As also noted in Section 1, even though FairAug is presented through its application on graph constrastive learning in this section, the proposed approach can be fully or partially used in conjunction to other learning frameworks as well. To exemplify such a use case, Table 4 lists the results for an end-to-end link prediction task with a two-layer GCN where the proposed fair edge deletion scheme is employed as an edge dropout method. As the benchmark, random edge dropout (Rong et al., 2019) is considered, which is a scheme originally proposed to improve the generalizability of the model on unseen data (Rong et al., 2019). In the experiments, the number of deleted edges is the same for both strategies. The results demonstrate that our method 'Fair ED' can indeed enhance the fairness of the learning framework it is employed in while it slightly reduces the utility measures.

5 CONCLUSIONS

In this study, the source of bias in aggregated representations in a GNN-based framework has been theoretically analyzed. Based on the analysis, several fairness-aware augmentation schemes have been introduced on both graph structure and nodal features. The proposed augmentations can be flexibly utilized together with several GNN-based learning methods. In addition, they can readily be employed in unsupervised node representation learning schemes such as graph contrastive learning. Experimental results on real-world graphs demonstrate that the proposed adaptive augmentations can improve fairness metrics with comparable utilities to state-of-the-art in node classification and link prediction.

6 Reproducibility Statement

The proofs for Theorem 1 and Proposition 1 are presented together with all assumptions made for them in Appendix A.1 and Appendix A.2, respectively. Implementation details and hyperparameter values are presented in Appendix A.7 for the clarification of experimental settings. All codes that are needed to regenerate the presented results in Tables 1, 2, 3 and 4 are provided within the supplementary material together with a README file. Finally, the details on the utilized data sets are provided in Appendix A.5 where all datasets are publicly available.

References

Chirag Agarwal, Himabindu Lakkaraju*, and Marinka Zitnik*. Towards a unified framework for fair and stable graph representation learning. *arXiv preprint arXiv:2102.13186*, February 2021.

Amr Ahmed, Nino Shervashidze, Shravan Narayanamurthy, Vanja Josifovski, and Alexander J Smola. Distributed large-scale natural graph factorization. In *Proc. International Conference on World Wide Web (WWW)*, pp. 37–48, May 2013.

Alex Beutel, Jilin Chen, Zhe Zhao, and Ed H Chi. Data decisions and theoretical implications when adversarially learning fair representations. *arXiv preprint arXiv:1707.00075*, June 2017.

Shaosheng Cao, Wei Lu, and Qiongkai Xu. Grarep: Learning graph representations with global structural information. In *Proc. ACM International Conference on Information and Knowledge Management (CIKM)*, pp. 891–900, October 2015.

Deli Chen, Yankai Lin, Wei Li, Peng Li, Jie Zhou, and Xu Sun. Measuring and relieving the over-smoothing problem for graph neural networks from the topological view. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 3438–3445, 2020a.

Haochen Chen, Bryan Perozzi, Yifan Hu, and Steven Skiena. Harp: Hierarchical representation learning for networks. In *Proc. AAAI Conference on Artificial Intelligence*, volume 32, February 2018.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *Proc. International Conference on Machine Learning (ICML)*, pp. 1597–1607, July 2020b.

Enyan Dai and Suhang Wang. Say no to the discrimination: Learning fair graph neural networks with limited sensitive attribute information. *arXiv preprint arXiv:2009.01454*, September 2020.

Cynthia Dwork, Moritz Hardt, Toniann Pitassi, Omer Reingold, and Richard Zemel. Fairness through awareness. In *Proc. Innovations in Theoretical Computer Science (ITCS)*, pp. 214–226, January 2012.

Alberto García-Durán and Mathias Niepert. Learning graph representations with embedding propagation. In *Proc. International Conference on Neural Information Processing Systems (NeurIPS)*, pp. 5125–5136, December 2017.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proc. International Conference on Artificial Intelligence and Statistics (AISTATS)*, pp. 249–256, May 2010.

Ignacio S Gomez, Bruno G da Costa, and Maike AF Dos Santos. Majorization and dynamics of continuous distributions. *Entropy*, 21(6):590, 2019.

Aditya Grover and Jure Leskovec. node2vec: Scalable feature learning for networks. In *Proc. ACM International Conference on Knowledge Discovery and Data Mining (SIGKDD)*, August 2016.

Sara Hajian and Josep Domingo-Ferrer. A methodology for direct and indirect discrimination prevention in data mining. *IEEE Transactions on Knowledge and Data Engineering*, 25(7):1445–1459, July 2013. doi: 10.1109/TKDE.2012.72.

William L Hamilton, Rex Ying, and Jure Leskovec. Inductive representation learning on large graphs. In *Proc. International Conference on Neural Information Processing Systems (NeurIPS)*, pp. 1025–1035, December 2017.

Kaveh Hassani and Amir Hosein Khasahmadi. Contrastive multi-view representation learning on graphs. In *Proc. International Conference on Machine Learning (ICML)*, pp. 4116–4126, July 2020.

R Devon Hjelm, Alex Fedorov, Samuel Lavoie-Marchildon, Karan Grewal, Phil Bachman, Adam Trischler, and Yoshua Bengio. Learning deep representations by mutual information estimation and maximization. In *Proc. International Conference on Learning Representations (ICLR)*, April 2018.

Bas Hofstra, Rense Corten, Frank Van Tubergen, and Nicole B Ellison. Sources of segregation in social networks: A novel approach using facebook. *American Sociological Review*, 82(3): 625–656, May 2017.

Fenyu Hu, Yanqiao Zhu, Shu Wu, Liang Wang, and Tieniu Tan. Hierarchical graph convolutional networks for semi-supervised node classification. In *Proc. International Joint Conference on Artificial Intelligence, (IJCAI)*, August 2019.

Xu Ji, João F Henriques, and Andrea Vedaldi. Invariant information clustering for unsupervised image classification and segmentation. In *Proc. IEEE International Conference on Computer Vision (ICCV)*, pp. 9865–9874, October 2019.

Guangyin Jin, Qi Wang, Cunchao Zhu, Yanghe Feng, Jincai Huang, and Jiangping Zhou. Addressing crime situation forecasting task with temporal graph convolutional neural network approach. In *Proc. International Conference on Measuring Technology and Mechatronics Automation (ICMTMA)*, pp. 474–478, February 2020. doi: 10.1109/ICMTMA50254.2020.00108.

Kushal Kafle, Mohammed Yousefhussien, and Christopher Kanan. Data augmentation for visual question answering. In *Proceedings of the 10th International Conference on Natural Language Generation*, pp. 198–202, 2017.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *Proc. International Conference on Learning Representations (ICLR)*, April 2017.

Peizhao Li, Yifei Wang, Han Zhao, Pengyu Hong, and Hongfu Liu. On dyadic fairness: Exploring and mitigating bias in graph connections. In *Proc. International Conference on Learning Representations (ICLR)*, April 2021.

Albert W Marshall, Ingram Olkin, and Barry C Arnold. *Inequalities: theory of majorization and its applications*, volume 143. Springer, 1979.

Alan Mislove, Bimal Viswanath, Krishna P Gummadi, and Peter Druschel. You are who you know: inferring user profiles in online social networks. In *Proc. ACM International Conference on Web Search and Data Mining (WSDM)*, pp. 251–260, February 2010.

Felix L Opolka, Aaron Solomon, Cătălina Cangea, Petar Veličković, Pietro Liò, and R Devon Hjelm. Spatio-temporal deep graph infomax. *arXiv preprint arXiv:1904.06316*, April 2019.

Mingdong Ou, Peng Cui, Jian Pei, Ziwei Zhang, and Wenwu Zhu. Asymmetric transitivity preserving graph embedding. In *Proc. ACM International Conference on Knowledge Discovery and Data Mining (SIGKDD)*, pp. 1105–1114, August 2016.

Zhen Peng, Wenbing Huang, Minnan Luo, Qinghua Zheng, Yu Rong, Tingyang Xu, and Junzhou Huang. Graph representation learning via graphical mutual information maximization. In *Proc. Web Conference (WWW)*, pp. 259–270, April 2020.

Bryan Perozzi, Rami Al-Rfou, and Steven Skiena. Deepwalk: Online learning of social representations. In *Proc. ACM International Conference on Knowledge Discovery and Data Mining (SIGKDD)*, pp. 701–710, August 2014. URL `http://doi.acm.org/10.1145/2623330.2623732`.

Tahleen A Rahman, Bartlomiej Surma, Michael Backes, and Yang Zhang. Fairwalk: Towards fair graph embedding. In *Proc. International Joint Conference on Artificial Intelligence (IJCAI)*, pp. 3289–3295, August 2019.

Veronica Red, Eric D Kelsic, Peter J Mucha, and Mason A Porter. Comparing community structure to characteristics in online collegiate social networks. *SIAM review*, 53(3):526–543, 2011.

Yu Rong, Wenbing Huang, Tingyang Xu, and Junzhou Huang. Dropedge: Towards deep graph convolutional networks on node classification. *arXiv preprint arXiv:1907.10903*, 2019.

Connor Shorten and Taghi M Khoshgoftaar. A survey on image data augmentation for deep learning. *Journal of Big Data*, 6(1):1–48, 2019.

Indro Spinelli, Simone Scardapane, Amir Hussain, and Aurelio Uncini. Biased edge dropout for enhancing fairness in graph representation learning. *arXiv preprint arXiv:2104.14210*, 2021.

Lubos Takac and Michal Zabovsky. Data analysis in public social networks. In *International Scientific Conference and International Workshop. 'Present Day Trends of Innovations'*, volume 1, May 2012.

Jian Tang, Meng Qu, Mingzhe Wang, Ming Zhang, Jun Yan, and Qiaozhu Mei. Line: Large-scale information network embedding. In *Proc. International Conference on World Wide Web (WWW)*, pp. 1067–1077, May 2015.

Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. Graph attention networks. *Proc. International Conference on Learning Representations (ICLR)*, April 2018.

Petar Veličković, William Fedus, William L. Hamilton, Pietro Liò, Yoshua Bengio, and R Devon Hjelm. Deep graph infomax. In *Proc. International Conference on Learning Representations (ICLR)*, May 2019. URL `https://openreview.net/forum?id=rklz9iAcKQ`.

Felix Wu, Amauri Souza, Tianyi Zhang, Christopher Fifty, Tao Yu, and Kilian Weinberger. Simplifying graph convolutional networks. In *Proc. International Conference on Machine Learning (ICML)*, pp. 6861–6871, July 2019.

Zhirong Wu, Yuanjun Xiong, Stella X Yu, and Dahua Lin. Unsupervised feature learning via nonparametric instance discrimination. In *Proc. IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 3733–3742, June 2018.

Mang Ye, Xu Zhang, Pong C Yuen, and Shih-Fu Chang. Unsupervised embedding learning via invariant and spreading instance feature. In *Proc. IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 6210–6219, June 2019.

Rex Ying, Ruining He, Kaifeng Chen, Pong Eksombatchai, William L Hamilton, and Jure Leskovec. Graph convolutional neural networks for web-scale recommender systems. In *Proc. ACM International Conference on Knowledge Discovery & Data Mining (SIGKDD)*, pp. 974–983, July 2018.

Yuning You, Tianlong Chen, Yongduo Sui, Ting Chen, Zhangyang Wang, and Yang Shen. Graph contrastive learning with augmentations. *Proc. International Conference on Neural Information Processing Systems (NeurIPS)*, 33, December 2020.

Muhammad Bilal Zafar, Isabel Valera, Manuel Gomez-Rodriguez, and Krishna P. Gummadi. Fairness constraints: A flexible approach for fair classification. *Journal of Machine Learning Research (JMLR)*, 20(75):1–42, 2019.

Xiang Zhang, Junbo Zhao, and Yann LeCun. Character-level convolutional networks for text classification. *Advances in neural information processing systems*, 28:649–657, 2015.

Tong Zhao, Yozen Liu, Leonardo Neves, Oliver Woodford, Meng Jiang, and Neil Shah. Data augmentation for graph neural networks. *arXiv preprint arXiv:2006.06830*, 2020.

Yanqiao Zhu, Yichen Xu, Feng Yu, Qiang Liu, Shu Wu, and Liang Wang. Deep Graph Contrastive Representation Learning. In *Proc. International Conference on Machine Learning (ICML) Workshop on Graph Representation Learning and Beyond*, July 2020. URL `http://arxiv.org/abs/2006.04131`.

Yanqiao Zhu, Yichen Xu, Feng Yu, Qiang Liu, Shu Wu, and Liang Wang. Graph contrastive learning with adaptive augmentation. In *Proc. Web Conference (WWW)*, April 2021.

A APPENDIX

A.1 PROOF OF THEOREM 1

Let $\bar{s} = \frac{1}{N} \sum_{i=1}^{N} s_i = \frac{|\mathcal{S}_1|}{N}$ Hence, the elements of centered sensitive attribute vector can be written as

$$\rho_i = \frac{1}{N\sigma_{\mathbf{s}}\sigma_{\tilde{\mathbf{z}}_{:,i}}} \left(\sum_{v_m \in S_0} (0 - \bar{s})(z_{m,i} - \bar{z}_i) + \sum_{v_n \in S_1} (1 - \bar{s})(z_{n,i} - \bar{z}_i) \right), \tag{8}$$

where $\bar{z}_i = \frac{1}{N} \sum_{j=1}^{N} z_{ji}$ and z_{ji} is the element of matrix $\mathbf{Z}$ at row j, column i. Using $\bar{s}$ values, the equation 8 becomes

$$
\begin{aligned}
\rho_i &= \frac{1}{N\sigma_{\mathbf{s}}\sigma_{\tilde{\mathbf{z}}_{:,i}}} \left(\sum_{v_m \in S_0} \frac{-|\mathcal{S}_1|}{N}(z_{m,i} - \bar{z}_i) + \sum_{v_n \in S_1} \frac{|\mathcal{S}_0|}{N}(z_{n,i} - \bar{z}_i) \right), \\
&= \frac{1}{N\sigma_{\mathbf{s}}\sigma_{\tilde{\mathbf{z}}_{:,i}}} \left(\frac{|\mathcal{S}_0||\mathcal{S}_1|}{N}\bar{z}_i + \sum_{v_m \in S_0} \frac{-|\mathcal{S}_1|}{N} z_{m,i} - \frac{|\mathcal{S}_0||\mathcal{S}_1|}{N}\bar{z}_i + \sum_{v_n \in S_1} \frac{|\mathcal{S}_0|}{N} z_{n,i} \right), \\
&= \frac{1}{N\sigma_{\mathbf{s}}\sigma_{\tilde{\mathbf{z}}_{:,i}}} \left(\sum_{v_n \in S_1} \frac{|\mathcal{S}_0|}{N} z_{n,i} - \sum_{v_m \in S_0} \frac{|\mathcal{S}_1|}{N} z_{m,i} \right), \\
&= \frac{|\mathcal{S}_0||\mathcal{S}_1|}{N^2\sigma_{\mathbf{s}}\sigma_{\tilde{\mathbf{z}}_{:,i}}} \left(\frac{1}{|\mathcal{S}_1|} \sum_{v_n \in S_1} z_{n,i} - \frac{1}{|\mathcal{S}_0|} \sum_{v_m \in S_0} z_{m,i} \right).
\end{aligned}
\tag{9}
$$

Similarly analysis for $\sigma_{\mathbf{s}}$ follows as

$$
\begin{aligned}
\sigma_{\mathbf{s}} &:= \sqrt{\frac{1}{N} \sum_{n=1}^{N} (s_n - \bar{s})^2} = \sqrt{\frac{1}{N} \sum_{n=1}^{N} \left(\sum_{v_m \in S_0} \frac{|\mathcal{S}_1|^2}{N^2} + \sum_{v_n \in S_1} \frac{|\mathcal{S}_0|^2}{N^2} \right)} \\
&= \sqrt{\frac{1}{N} \left(\frac{|\mathcal{S}_0||\mathcal{S}_1|^2}{N^2} + \frac{|\mathcal{S}_1||\mathcal{S}_0|^2}{N^2} \right)} \\
&= \sqrt{\frac{1}{N} \left(|\mathcal{S}_0||\mathcal{S}_1| \frac{(|\mathcal{S}_0| + |\mathcal{S}_1|)}{(|\mathcal{S}_0| + |\mathcal{S}_1|)^2} \right)} \\
&= \frac{\sqrt{|\mathcal{S}_0||\mathcal{S}_1|}}{N}
\end{aligned}
\tag{10}
$$

Define $c_i := \frac{\sqrt{|\mathcal{S}_0||\mathcal{S}_1|}}{N\sigma_{\tilde{\mathbf{z}}_{:,i}}}$ and $\mathbf{c} \in \mathbb{R}^{F'}$ denote the vector whose elements are c_is. Then $\boldsymbol{\rho}$ equals to

$$\boldsymbol{\rho} = \mathbf{c} \circ \left(\frac{1}{|\mathcal{S}_1|} \sum_{v_n \in S_1} \mathbf{z}_n - \frac{1}{|\mathcal{S}_0|} \sum_{v_m \in S_0} \mathbf{z}_m \right) \tag{11}$$

where $\circ$ represents the Hadamard product. Therefore, $\|\boldsymbol{\rho}\|_1$ follows as

$$\|\boldsymbol{\rho}\|_1 = \left\| \mathbf{c} \circ \left(\frac{1}{|\mathcal{S}_1|} \sum_{v_n \in S_1} \mathbf{z}_n - \frac{1}{|\mathcal{S}_0|} \sum_{v_m \in S_0} \mathbf{z}_m \right) \right\|_1. \tag{12}$$

We first consider the terms $\frac{1}{|\mathcal{S}_1|} \sum_{v_n \in S_1} \mathbf{z}_n$ and $\frac{1}{|\mathcal{S}_0|} \sum_{v_m \in S_0} \mathbf{z}_m$ individually

$$
\begin{aligned}
\frac{1}{|\mathcal{S}_1|} \sum_{v_n \in S_1} \mathbf{z}_n &\in \frac{1}{|\mathcal{S}_1|} \sum_{v_n \in S_1} \left(\frac{1}{d_n} \sum_{a \in \mathcal{N}(n) \cap S_0} \boldsymbol{\mu}_0 + \frac{1}{d_n} \sum_{b \in \mathcal{N}(n) \cap S_1} \boldsymbol{\mu}_1 \right) \pm \Delta, \\
&\in \frac{1}{|\mathcal{S}_1|} \sum_{v_n \in S_1} \frac{d_n^\chi \boldsymbol{\mu}_0 + d_n^\omega \boldsymbol{\mu}_1}{d_n^\chi + d_n^\omega} \pm \Delta, \\
&\in \frac{1}{|\mathcal{S}_1|} \sum_{v_n \in S_1} \left(\boldsymbol{\mu}_1 + \frac{d_n^\chi}{d_n^\chi + d_n^\omega}(\boldsymbol{\mu}_0 - \boldsymbol{\mu}_1) \right) \pm \Delta.
\end{aligned}
\tag{13}
$$

Similarly, the expression for the term $\frac{1}{|\mathcal{S}_0|}\sum_{v_m \in S_0} \mathbf{z}_m$ can also be derived.

$$\frac{1}{|\mathcal{S}_0|} \sum_{v_m \in S_0} \mathbf{z}_m \in \frac{1}{|\mathcal{S}_0|} \sum_{v_m \in S_0} \left(\boldsymbol{\mu}_0 + \frac{d_m^\chi}{d_m^\chi + d_m^\omega}(\boldsymbol{\mu}_1 - \boldsymbol{\mu}_0) \right) \pm \Delta. \tag{14}$$

Define $\boldsymbol{\epsilon} := \frac{1}{|\mathcal{S}_1|}\sum_{v_n \in S_1}\mathbf{z}_n - \frac{1}{|\mathcal{S}_0|}\sum_{v_m \in S_0}\mathbf{z}_m$, the following can be written by equation 13 and equation 14

$$\boldsymbol{\epsilon} \in (\boldsymbol{\mu}_1 - \boldsymbol{\mu}_0)\left(1 - \frac{1}{|\mathcal{S}_1|}\sum_{v_n \in S_1}\left(\frac{d_n^\chi}{d_n^\chi + d_n^\omega}\right) - \frac{1}{|\mathcal{S}_0|}\sum_{v_m \in S_0}\left(\frac{d_m^\chi}{d_m^\chi + d_m^\omega}\right) \right) \pm 2\Delta. \tag{15}$$

$\boldsymbol{\epsilon}$ is bounded below, which follows as

$$1 - \frac{1}{|\mathcal{S}_1|}\sum_{v_n \in S_1}\left(\frac{d_n^\chi}{d_n^\chi + d_n^\omega}\right) - \frac{1}{|\mathcal{S}_0|}\sum_{v_m \in S_0}\left(\frac{d_m^\chi}{d_m^\chi + d_m^\omega}\right)$$

$$= 1 - \frac{1}{|\mathcal{S}_1|}\sum_{v_n \in S_1^\chi}\left(\frac{d_n^\chi}{d_n^\chi + d_n^\omega}\right) - \frac{1}{|\mathcal{S}_0|}\sum_{v_m \in S_0^\chi}\left(\frac{d_m^\chi}{d_m^\chi + d_m^\omega}\right) \tag{16}$$

$$\geq 1 - \frac{|\mathcal{S}_0^\chi|}{|\mathcal{S}_0|} - \frac{|\mathcal{S}_1^\chi|}{|S_1|} \tag{17}$$

equation 16 follows as $d_u^\chi = 0$ for $\forall v_u \in \mathcal{S}^\omega$. The upper bound equation 17 holds, since $\left(\frac{d_u^\chi}{d_u^\chi + d_u^\omega}\right) \leq 1$ for $\forall v_u \in \mathcal{G}$.

The upper bound for $\boldsymbol{\epsilon}$ follows as

$$1 - \frac{1}{|\mathcal{S}_1|}\sum_{v_n \in S_1}\left(\frac{d_n^\chi}{d_n^\chi + d_n^\omega}\right) - \frac{1}{|\mathcal{S}_0|}\sum_{v_m \in S_0}\left(\frac{d_m^\chi}{d_m^\chi + d_m^\omega}\right) \tag{18}$$

$$= 1 - \text{mean}\left(\frac{d_m^\chi}{d_m^\chi + d_m^\omega}|v_m \in \mathcal{S}_0\right) - \text{mean}\left(\frac{d_n^\chi}{d_n^\chi + d_n^\omega}|v_n \in \mathcal{S}_1\right) \tag{19}$$

$$\leq 1 - 2\min\left(\text{mean}\left(\frac{d_m^\chi}{d_m^\chi + d_m^\omega}|v_m \in \mathcal{S}_0\right), \text{mean}\left(\frac{d_n^\chi}{d_n^\chi + d_n^\omega}|v_n \in \mathcal{S}_1\right)\right), \tag{20}$$

where $\text{mean}(\cdot)$ denotes the sample mean operation. The main purpose is to generate an upper bound for $\|\boldsymbol{\rho}\|_1$, for which the first step is to derive the following bound

$$\|\boldsymbol{\rho}\|_1 \leq \|\mathbf{c}\|_1 \|\boldsymbol{\epsilon}\|_1 \tag{21}$$

equation 21 can be written, as $\|\mathbf{x} \circ \mathbf{y}\|_1 \leq \|\mathbf{x}\|_1 \|\mathbf{y}\|_1$ for arbitrary vectors $\mathbf{x}$ and $\mathbf{y} \in \mathbb{R}^N ((x_1 y_1)^2 + \cdots + (x_N y_N)^2 \leq (x_1^2 + \cdots + x_N^2)((y_1^2 + \cdots + y_N^2)$ due to additional non-negative cross-terms $(x_i y_j)^2, i \neq j$). The next step is to bound the ℓ_1 norm of the difference term $\boldsymbol{\epsilon}$:

$$\|\boldsymbol{\epsilon}\|_1 \leq \|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_0\|_1 \max(\gamma_1, \gamma_2) + 2N\Delta \tag{22}$$

using the derived bounds in equation 17, equation 20 and the equality $2\Delta \cdot \|\mathbf{1}\|_1 = 2N\Delta$, where $\mathbf{1}$ denotes an $N \times 1$ vector of ones, $\gamma_1 := \left|1 - \frac{|\mathcal{S}_0^\chi|}{|\mathcal{S}_0|} - \frac{|\mathcal{S}_1^\chi|}{|S_1|}\right|$, and $\gamma_2 = \left|1 - 2\min\left(\text{mean}\left(\frac{d_m^\chi}{d_m^\chi + d_m^\omega}|v_m \in \mathcal{S}_0\right), \text{mean}\left(\frac{d_n^\chi}{d_n^\chi + d_n^\omega}|v_n \in \mathcal{S}_1\right)\right)\right|$. Using equation 21 and equation 22, the final upper bound can be derived:

$$\|\boldsymbol{\rho}\|_1 \leq \|\mathbf{c}\|_1 \left(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_0\|_1 \max(\gamma_1, \gamma_2) + 2N\Delta\right). \tag{23}$$

A.2 PROOF OF PROPOSITION 1

The expected $\|\tilde{\boldsymbol{\delta}}\|_1$ can be written as:

$$
\begin{aligned}
E_{\mathbf{p}}[\|\tilde{\boldsymbol{\delta}}\|_1] &= E\left[\sum_{i=1}^{F}|\tilde{\delta}_i|\right] \\
&= \sum_{i=1}^{F}E[|\tilde{\delta}_i|] = \sum_{i=1}^{F}p_i|\delta_i|.
\end{aligned}
\tag{24}
$$

Similarly, the expected $\|\tilde{\boldsymbol{\delta}}\|_1$ for the uniform masking scheme is:

$$
E_{\mathbf{q}}[\|\tilde{\boldsymbol{\delta}}\|_1] = \sum_{i=1}^{F}q_i|\delta_i|
\tag{25}
$$

For fair comparison, set uniform keeping probability of the nodal features $q_i = \bar{p} = \frac{1}{F}\sum_{i=1}^{F}p_i$. Without loss of generality, assume, $|\delta_i|$s are ordered such that $|\delta_1| \leq \cdots \leq |\delta_F|$. With the ordered $|\delta_i|$s, assigned probabilities to keep the nodal features by our method will also be ordered such that $p_1 \geq \cdots \geq p_F$. Defining a dummy variable $|\delta_0| := 0$, equation 24 can be rewritten as:

$$
\begin{aligned}
\sum_{i=1}^{F}p_i|\delta_i| &= (|\delta_1| - |\delta_0|)(p_1 + \cdots + p_F) + (|\delta_2| - |\delta_1|)(p_2 + \cdots + p_F) + \ldots \\
&\quad \cdots + (|\delta_{F-1}| - |\delta_{F-2}|)(p_{F-1} + p_F) + (|\delta_F| - |\delta_{F-1}|)(p_F) \\
&= \sum_{l=1}^{F}(|\delta_l| - |\delta_{l-1}|)\sum_{i=l}^{F}p_i.
\end{aligned}
\tag{26}
$$

Following the definition in (Marshall et al., 1979), a sequence $\boldsymbol{x} = \{x_1, x_2, \ldots, x_F\}$ majorizes another sequence $\boldsymbol{y} = \{y_1, y_2, \ldots, y_F\}$, if the following holds:

$$
\begin{aligned}
\sum_{i=1}^{k}y_i &\leq \sum_{i=1}^{k}x_i \quad k = 1, \ldots, F-1, \\
\sum_{i=1}^{F}y_i &= \sum_{i=1}^{F}x_i.
\end{aligned}
\tag{27}
$$

Since the uniform sequence is majorized by any other non-increasing ordered sequence with the same sum (see (Gomez et al., 2019, Equation 3)), the sequence $\mathbf{p} = \{p_1, p_2, \cdots, p_F\}$ majorizes the sequence $\mathbf{q} = \{q_1, q_2, \ldots, q_F\}$ where $q_i = \bar{p}$, $\forall i \in \{1, \ldots, F\}$. Defining $\sum_{i=1}^{0}p_i := 0$, equation 26 can be re-written as

$$
\begin{aligned}
E_{\mathbf{p}}[\|\tilde{\boldsymbol{\delta}}\|_1] &= \sum_{l=1}^{F}(|\delta_l| - |\delta_{l-1}|)\sum_{i=l}^{F}p_i \\
&= \sum_{l=1}^{F}(|\delta_l| - |\delta_{l-1}|)(F\bar{p} - \sum_{i=1}^{l-1}p_i) \\
&\overset{(a)}{\leq} \sum_{l=1}^{F}(|\delta_l| - |\delta_{l-1}|)(F\bar{p} - \sum_{i=1}^{l-1}q_i) \\
&= \sum_{l=1}^{F}(|\delta_l| - |\delta_{l-1}|)\sum_{i=l}^{F}q_i \\
&= E_{\mathbf{q}}[\|\tilde{\boldsymbol{\delta}}\|_1],
\end{aligned}
\tag{28}
$$

where inequality (a) follows from the definition of majorization in equation 27.

Algorithm 1: Node Sampling

Data: $\mathcal{G} := (\mathcal{V}, \mathcal{E}), \mathbf{X}, \mathbf{s}, \beta$
Result: $\tilde{\mathcal{G}}, \tilde{\mathbf{X}}, \tilde{\mathbf{s}}$
Split $\mathcal{V}$ into sets $\{\mathcal{S}_0^\chi, \mathcal{S}_1^\chi, \mathcal{S}_0^\omega, \mathcal{S}_1^\omega\}$
if $|\mathcal{S}^\omega| \geq |\mathcal{S}^\chi|$ **then**
    Sample $|\mathcal{S}_0^\chi|$ nodes from $\mathcal{S}_0^\omega$ uniformly to obtain $\bar{\mathcal{S}}_0^\omega$;
    Sample $|\mathcal{S}_1^\chi|$ nodes from $\mathcal{S}_1^\omega$ uniformly to obtain $\bar{\mathcal{S}}_1^\omega$;
    $\tilde{\mathcal{V}} := \{\mathcal{S}^\chi, \bar{\mathcal{S}}_0^\omega, \bar{\mathcal{S}}_1^\omega\}$;
end
if $|\mathcal{S}^\chi| \geq |\mathcal{S}^\omega|$ **then**
    Sample $|\mathcal{S}_0^\omega|$ nodes from $\mathcal{S}_0^\chi$ uniformly to obtain $\bar{\mathcal{S}}_0^\chi$;
    Sample $|\mathcal{S}_1^\omega|$ nodes from $\mathcal{S}_1^\chi$ uniformly to obtain $\bar{\mathcal{S}}_1^\chi$;
    $\tilde{\mathcal{V}} := \{\bar{\mathcal{S}}_0^\chi, \bar{\mathcal{S}}_1^\chi, \mathcal{S}^\omega\}$;
end
Obtain subgraph $\tilde{\mathcal{G}}$ induced by $\tilde{\mathcal{V}}$ along with the nodal features $\tilde{\mathbf{X}}$ and sensitive attributes $\tilde{\mathbf{s}}$

A.3 NODE SAMPLING AND ITS EFFECTS

The overall node sampling scheme is presented in Algorithm 1.

Assuming $|\mathcal{S}^\omega| \geq |\mathcal{S}^\chi|$, all nodes in $\mathcal{S}^\chi$ are retained, meaning $\tilde{\mathcal{S}}_0^\chi = \mathcal{S}_0^\chi$ and $\tilde{\mathcal{S}}_1^\chi = \mathcal{S}_1^\chi$. While subsets of nodes $\bar{\mathcal{S}}_0^\omega$ and $\bar{\mathcal{S}}_1^\omega$ are randomly sampled from $\mathcal{S}_0^\omega$ and $\mathcal{S}_1^\omega$ respectively with sample size $|\bar{\mathcal{S}}_0^\omega| = |\mathcal{S}_0^\chi|$ and $|\bar{\mathcal{S}}_1^\omega| = |\mathcal{S}_1^\chi|$.

Therefore, in the resulting graph $\tilde{\mathcal{G}}$, we have

$$|\tilde{\mathcal{S}}_0^\omega| = |\bar{\mathcal{S}}_0^\omega| = |\mathcal{S}_0^\chi| \tag{29}$$

$$|\tilde{\mathcal{S}}_1^\omega| = |\bar{\mathcal{S}}_1^\omega| = |\mathcal{S}_1^\chi| \tag{30}$$

therefore

$$\frac{\left|\tilde{\mathcal{S}}_0^\chi\right|}{|\tilde{\mathcal{S}}_0^\chi| + |\tilde{\mathcal{S}}_0^\omega|} = \frac{|\mathcal{S}_0^\chi|}{|\mathcal{S}_0^\chi| + |\mathcal{S}_0^\chi|} = \frac{1}{2} \tag{31}$$

$$\frac{\left|\tilde{\mathcal{S}}_1^\chi\right|}{|\tilde{\mathcal{S}}_1^\chi| + |\tilde{\mathcal{S}}_1^\omega|} = \frac{|\mathcal{S}_1^\chi|}{|\mathcal{S}_1^\chi| + |\mathcal{S}_1^\chi|} = \frac{1}{2} \tag{32}$$

which leads to $\gamma_1 = 0$ for the obtained $\tilde{\mathcal{G}}$.

A.4 EFFECTS OF GLOBAL EDGE DELETION SCHEME IN EQUATION 7

Given the edge deletion scheme in equation 7, we have

$$\mathbb{E}_{\mathbf{p}^{(e)}}\left[|\tilde{\mathcal{E}}^\chi|\right] = \pi |\mathcal{E}^\chi| \tag{33}$$

$$\mathbb{E}_{\mathbf{p}^{(e)}}\left[|\tilde{\mathcal{E}}_{\mathcal{S}_0}^\omega|\right] = \frac{|\mathcal{E}^\chi|}{2\left|\mathcal{E}_{\mathcal{S}_0}^\omega\right|} \pi \times |\mathcal{E}_{\mathcal{S}_0}^\omega| = \frac{\pi |\mathcal{E}^\chi|}{2} \tag{34}$$

$$\mathbb{E}_{\mathbf{p}^{(e)}}\left[|\tilde{\mathcal{E}}_{\mathcal{S}_1}^\omega|\right] = \frac{|\mathcal{E}^\chi|}{2\left|\mathcal{E}_{\mathcal{S}_1}^\omega\right|} \pi \times |\mathcal{E}_{\mathcal{S}_1}^\omega| = \frac{\pi |\mathcal{E}^\chi|}{2}. \tag{35}$$

Therefore, $\mathbb{E}_{\mathbf{p}^{(e)}}\left[|\tilde{\mathcal{E}}_{\mathcal{S}_0}^\omega|\right] = \mathbb{E}_{\mathbf{p}^{(e)}}\left[|\tilde{\mathcal{E}}_{\mathcal{S}_1}^\omega|\right] = \frac{1}{2}\mathbb{E}_{\mathbf{p}^{(e)}}\left[|\tilde{\mathcal{E}}^\chi|\right]$ and equation 6 holds.

A.5 DATASET STATISTICS

Table 5: Dataset statistics for social networks

Dataset	$|\mathcal{S}_0^X|$	$|\mathcal{S}_0^\omega|$	$|\mathcal{S}_1^X|$	$|\mathcal{S}_1^\omega|$	$|\mathcal{E}^X|$	$|\mathcal{E}_{\mathcal{S}_0}^\omega|$	$|\mathcal{E}_{\mathcal{S}_1}^\omega|$
Pokec-z	622	4229	582	2226	1730	23428	15942
Pokec-n	423	3617	479	1666	1422	18548	10672
UCSD34	2246	118	1697	71	51607	36787	19989
Berkeley13	1619	80	1488	77	27542	19550	13582

Table 6: Dataset statistics for citation networks

Dataset	$|\mathcal{V}|$	# sensitive attr.	$|\mathcal{E}^X|$	$|\mathcal{E}^\omega|$
Cora	2708	7	1428	5964
Citeseer	3327	6	1628	4746
Pubmed	19717	3	12254	49802

A.6 CONTRASTIVE LEARNING OVER GRAPHS

The main goal of contrastive learning is to learn discriminable representations by contrasting the embeddings of positive and negative examples, through minimizing a specific contrastive loss (Opolka et al., 2019; Veličković et al., 2019; Zhu et al., 2021; 2020). The contrastive loss in the present work is designed to maximize node-level agreement, meaning that the representations of the same node generated from different graph views can be discriminated from the embeddings of other nodes. Let $\mathbf{H}^1 = f(\widetilde{\mathbf{A}}^1, \widetilde{\mathbf{X}}^1)$ and $\mathbf{H}^2 = f(\widetilde{\mathbf{A}}^2, \widetilde{\mathbf{X}}^2)$ denote the nodal embeddings generated with graph views $\widetilde{G}^1$ and $\widetilde{G}^2$, where $\widetilde{\mathbf{A}}^i$, and $\widetilde{\mathbf{X}}^i$ are the adjacency and feature matrices of $\widetilde{G}^i$, which are corrupted versions of the matrices $\mathbf{A}$ and $\mathbf{X}$. Let $\mathbf{h}_i^1$ and $\mathbf{h}_i^2$ denote the embeddings for v_i: They should be more similar to each other than to the embeddings of all other nodes. Hence, the representations of all other nodes are used as negative samples. The contrastive loss for generating embeddings $\mathbf{h}_i^1$ and $\mathbf{h}_i^2$ (considering $\mathbf{h}_i^1$ as the anchor representation) can be written as

$$\ell\left(\mathbf{h}_i^1, \mathbf{h}_i^2\right) = -\log \frac{e^{s\left(\mathbf{h}_i^1, \mathbf{h}_i^2\right)/\tau}}{e^{s\left(\mathbf{h}_i^1, \mathbf{h}_i^2\right)/\tau} + \sum_{k=1}^N 1_{[k \neq i]} e^{s\left(\mathbf{h}_i^1, \mathbf{h}_k^2\right)/\tau} + \sum_{k=1}^N 1_{[k \neq i]} e^{s\left(\mathbf{h}_i^1, \mathbf{h}_k^1\right)/\tau}} \tag{36}$$

where $s\left(\mathbf{h}_i^1, \mathbf{h}_i^2\right) := c\left(g(\mathbf{h}_i^1), g(\mathbf{h}_i^2)\right)$, with $c(\cdot, \cdot)$ denoting the cosine similarity between the input vectors, and $g(\cdot)$ representing a nonlinear learnable transform executed by utilizing a 2-layer multi-layer perceptron (MLP), see also, (Zhu et al., 2021; 2020; Chen et al., 2020b). τ denotes the temperature parameter, and $1_{[k \neq i]} \in \{0, 1\}$ is the indicator function which takes the value 1 when $k \neq i$. This objective can also be written in the symmetric form, when the generated representation $\mathbf{h}_i^2$ is considered as the anchor example. Therefore, considering all nodes in the given graph, the final loss can be expressed as

$$\mathcal{J} = \frac{1}{2N} \sum_{i=1}^N \left[\ell\left(\mathbf{h}_i^1, \mathbf{h}_i^2\right) + \ell\left(\mathbf{h}_i^2, \mathbf{h}_i^1\right)\right]. \tag{37}$$

A.7 HYPERPARAMETERS AND IMPLEMENTATION DETAILS

Contrastive Learning: In the GNN-based encoder, weights are initialized utilizing Glorot initialization (Glorot & Bengio, 2010) and ReLU activation is used after each GCN layer. All models are trained for 400 epochs by employing Adam optimizer (Kingma & Ba, 2014) together with a learning rate of 5×10^{-4} and ℓ_2 weight decay factor of 10^{-5}. The temperature parameter τ in contrastive loss is chosen to be 0.4 and the dimension of the node representations is selected as 256 for all datasets.

End-to-end training: All models are trained for 100 epochs by employing Adam optimizer (Kingma & Ba, 2014) together with a learning rate of 5×10^{-3}. The dimension of the node representations is selected as 128 for all datasets.

Table 7: Effects of proposed augmentations on γ_2

	Original	Node Sampling	Edge Deletion	Edge Addition
Pokec-z	0.90	0.59	0.87	0.77
Pokec-n	0.91	0.62	0.89	0.81
UCSD34	0.18	0.45	0.03	0.11
Berkeley13	0.18	0.43	0.03	0.06

Table 8: Effects of each step in FairAug

		Original Graph	Node Sampling	Edge Deletion	Edge Addition
Pokec-z	γ_1	0.66	0.11	0.11	0.11
	γ_2	0.90	0.59	0.50	0.43
Pokec-n	γ_1	0.67	0.15	0.15	0.15
	γ_2	0.91	0.62	0.55	0.50
UCSD34	γ_1	0.91	0.86	0.86	0.86
	γ_2	0.18	0.45	0.17	0.17
Berkeley13	γ_1	0.90	0.83	0.83	0.83
	γ_2	0.18	0.43	0.17	0.17

Implementation details: Node representations are obtained using a two-layer GCN (Kipf & Welling, 2017) for all contrastive learning baselines, which is kept the same as the one used in (Zhu et al., 2021; 2020) to ensure fair comparison. After obtaining node embeddings from different schemes, a linear classifier based on ℓ_2-regularized logistic regression is applied for the node classification and link prediction tasks, which is again the same as the scheme used in (Veličković et al., 2019; Zhu et al., 2021; 2020). In node classification, the classifier is trained on 90% of the nodes selected through a random split, and the remaining nodes constitute the test set. For each experiment, results for three random data splits are obtained, and the average together with standard deviations are presented. In link prediction, 90% of the edges are utilized in the training of GCN encoder and linear classifier. For each edge, the input to the linear classifier is the concatenated representations of the nodes that the edge connects. Results for link prediction are obtained for five different edge splits, the resulting average metrics and standard deviations are provided. Finally, in the end-to-end link prediction experiments, a two-layer GCN is trained, and results are obtained for 6 different random data splits.

Note that if the sizes of the sets $\hat{\mathcal{S}}$ and $\tilde{\mathcal{S}}$ are highly unbalanced, we put a limit on the minimum of sampling budgets in node sampling to prevent any excessive corruption of the input graph. If $\mathcal{S}^\omega \geq \mathcal{S}^\chi$, the minimum limit for each set is the 50% of the initial group size, otherwise the limit is the 25% of the initial group size. Furthermore, to avoid overly down sampling the edges, a minimum value for $p^{(e)}(e_{ij})$, $p^{(e)}_{min}$, is set for the edge deletion scheme. In the feature masking scheme, α in equation 2 is set to 0 and 0.1 for different graph views used in the contrastive loss (i.e., default parameter values provided for GCA are used directly). In edge deletion framework, $\pi = 1$, and $p^{(e)}_{min} = 0.5$ in the experiments of Pokec datasets and citation networks. For Facebook networks, $\pi = 0.8$, and $p^{(e)}_{min} = 0.4$, as the selection of π as 1 results in no edge deletion in one of the sensitive groups and degenerates the stochastic nature of edge deletion.

A.8 EFFECTS OF PROPOSED AUGMENTATIONS ON γ_1 AND γ_2

Tables 7 and 8 present the effects of the proposed framework on γ values for different datasets. In Table 7, the effect of each augmentation step on γ_2 is considered independently. Table 8 demonstrates the effect of augmentations sequentially in the overall algorithm in a cumulative manner (e.g., the "Edge Deletion" column implies both Node Sampling and Edge Deletion are applied). Both Tables 7 and 8 demonstrate that even though the edge deletion/addition schemes are not directly designed based on γ_2, the proposed approaches indeed reduce the values of it. In addition, presented γ values can also help to explain the ineffectiveness of edge deletion on Pokec networks. Due to the inter-edge sparsity and overly unbalanced structure of these datasets in terms of $|\mathcal{E}^\chi|$ and $|\mathcal{E}^\omega|$ (presented in Table 5 of Appendix A.5), node sampling becomes a better choice than edge deletion/addition to reduce the bias via an augmentation on the graph topology. Table 7 also shows the better effec-

tiveness of node sampling strategy in reducing γ_2 compared to edge deletion/addition frameworks, which also supports the findings of Table 2, that is, node sampling is an essential step of FairAug on the Pokec networks. Furthermore, γ values can also help to explain the random/detrimental effect of node sampling for Facebook networks, which is presented in Table 3. Tables 7 and 8 show that while node sampling is not very effective in reducing γ_1, it is observed to increase γ_2 for these networks. This effect results from the graph topologies of Facebook networks having $|\mathcal{S}^\chi| >> |\mathcal{S}^\omega|$. Note that γ_1 values are not 0 after node sampling due to the limit on the minimum of sampling budgets, see Appendix A.7.