INEQUALITY PHENOMENON IN l_∞-ADVERSARIAL TRAINING, AND ITS UNREALIZED THREATS

ABSTRACT

The appearance of adversarial examples raises attention from both academia and industry. Along with the attack-defense arms race, adversarial training is the most effective against adversarial examples. However, we find inequality phenomena occur during the l_∞-adversarial training, that few features dominate the prediction made by the adversarially trained model. We systematically evaluate such inequality phenomena by extensive experiments and find such phenomena become more obvious when performing adversarial training with increasing adversarial strength (evaluated by ϵ). We hypothesize such inequality phenomena make l_∞-adversarially trained model less reliable than the standard trained model when few "important features" are influenced. To validate our hypothesis, we proposed two simple attacks that either perturb or replace important features with noise or occlusion. Experiments show that l_∞-adversarially trained model can be easily attacked when a few important features are influenced. Our work shed light on the limitation of the practicality of l_∞-adversarial training.

1 INTRODUCTION

Szegedy et al. (2013) discovered adversarial examples of deep neural networks (DNNs), which pose significant threats to the deep learning-based applications such as autonomous driving and face recognition. Prior to deploying DNN-based applications in real-world scenarios safely and securely, we must defend against adversarial examples. After the emergence of adversarial examples, several defensive strategies have been proposed (Guo et al., 2018; Prakash et al., 2018; Mummadi et al., 2019; Akhtar et al., 2018). By retraining l_p-norm bounded adversarial samples generated in each training loop, adversarial training (Goodfellow et al., 2015; Zhang et al., 2019; Madry et al., 2018b) is regarded as the most effective defense against adversarial attacks. The most prevalent adversarial training is l_∞ adversarial training, which applies adversarial samples with l_∞ bounded perturbation by ϵ.

Numerous works have been devoted to theoretical and empirical comprehension of adversarial training (Andriushchenko & Flammarion, 2020; Allen-Zhu & Li, 2022; Kim et al., 2021). For example, Ilyas et al. (2019) proposed that an adversarially trained model learns robust features from adversarial examples and discards non-robust features. Engstrom et al. (2019) also proposed that adversarial training forces the model learning to be invariant to signals to which humans are also invariant. Therefore, the adversarial training results in feature representations that are more comparable to humans. Theoretically validated by Chalasani et al. (2020), the l_∞-adversarial training suppresses the significance of the redundant features, and the adversarially trained model, therefore, produces sparser and better-behaved feature representations. In general, previous research indicates that robust models have a sparse representation of features and view this sparse representation as advantageous because it is more human-aligned. Several works investigate this such property of an adversarially trained model and attempt to transfer it to standard trained model using various methods (Ross & Doshi-Velez, 2018; Salman et al., 2020; Deng et al., 2021).

However, contrary to the augmentation of previous work regarding such sparse feature representation as an advantage, we find that such sparseness also indicates inequality phenomena that may pose unanticipated threats to adversarially trained models. During l_∞-adversarial training, the model not only suppresses the significance assigned to redundant features (Chalasani et al., 2020) but also suppresses the importance of other features including robust ones. The degree of suppression is pro-

portional to the adversarial attack budget (evaluated by ϵ). Hence, for an l_∞-adversarially trained model, only a handful of features dominate the prediction with the provided input images. Intuitively, standard-trained models make decisions based on various features, and some redundant features serve as a "bulwark" when a few crucial features are accidentally distorted. However, in the case of a l_∞ robust model, the decision is primarily determined by a small number of characteristics, so the prediction is susceptible to change when these significant characteristics are modified (see Figure 1). As shown in Figure 1, an l_∞-adverarially trained model recognizes a street sign using very few regions of the sign. Even with very small occlusions, the adversarially-trained model cannot recognize a street sign if we obscure the region that the model considers to be the most important (but are well recognized by humans and standard-trained model). Even if an autonomous vehicle is deployed with an adversarially trained model that achieves high adversarial robustness against worst-case adversarial examples, it will still be susceptible to small occlusions. Thus, the applicability of such an adversarially trained model is debatable.

Figure 1: l_∞-**adversarially trained model fails to recognize street sign with small occlusions**. With given feature attribution maps that attribute the importance of each feature, we occlude the image's features of high importance with small patches. The resultant image fools the adversarially trained model successfully.)

In this work, we name such phenomenon that only a few features are extreme crucial for models' recognition as "inequality phenomenon". we first study the "inequality phenomenon" of l_∞-adversarial training quantitatively and qualitatively as primarily reflected in two aspects: 1) global inequality: characterized by the dominance of a small number of features. 2) regional inequality: characterized by the tendency of features deemed significant by the model to cluster in particular regions. Such phenomena are analyzed on ImageNet and Cifar10 with models with distinct architectures. We further devise attacks to expose the vulnerabilities resulting from such inequality based on our findings. Experiments demonstrate that, under the premise that human observers can recognize the resulting images,, l_∞-adversarially trained models are significantly more susceptible than the standard-trained models. Furthermore, they are susceptible to occlusion and noise with error rates of 100% and 94%, respectively, whereas standard-trained models are only affected by 30.1% and 34.5%. In summary, our contribution can be summed up in the following manner:

- We identify the occurrence of the inequality phenomenon during l_∞-adversarial training. We design correlative indices and assess such inequality phenomena from various perspectives (global and regional). We systematically evaluate such phenomena by conducting extensive experiments on broad datasets and models.

- Then, we identify unrealized threats posed by such inequality phenomena that l_∞-adversarially trained models are much more vulnerable than standard trained ones under inductive occlusion or noise. In this case, during the l_∞-adversarial training, the adversarial robustness is is achieved at the expense of another.

- Our work provides an intuitive understanding of the weakness of l_∞-adversarially trained model's feature representation from a novel perspective. Moreover, our work sheds light on the limitation and the hardness of l_∞-adversarial training.

This paper is organized as follows. Background and related work are discussed in Section 2. The proposed methodology is described in Section 3, then evaluated in Section 4. Finally, section 5 provides a discussion and conclusion about our work.

2 BACKGROUND AND RELATED WORK

2.1 ADVERSARIAL EXAMPLE

Given a model denoted as $f(x; \theta) : x \to \mathbb{R}^k$ and training dataset denoted as D, empirical risk minimization (ERM) is a standard way (denoted as standard training) to train the model f through:

$$\min_\theta E_{(x,y) \in D} loss(x, y) \tag{1}$$

where $y \in \mathbb{R}^k$ is the one-hot label for the image and $loss(x, y)$ is usually cross-entropy loss. With such a training scheme, the model typically performs well on clean test samples. Adversarial examples (Szegedy et al., 2013) aim to generate perturbation superimposed on clean sample x to fool a well-trained model f. Adversarial example x' can be crafted by either following the direction of adversarial gradients (Goodfellow et al., 2015; Kurakin et al., 2016; Madry et al., 2018a) or optimizing perturbation with a given loss (Carlini & Wagner, 2017; Chen et al., 2018). For most adversarial attacks, the generated adversarial perturbation is bounded by a l_p norm ball, where l_∞-norm is the most commonly used norm.

2.2 ADVERSARIAL TRAINING

Several defensive strategies are proposed to improve the models' adversarial robustness (Wong & Kolter, 2018; Akhtar et al., 2018; Meng & Chen, 2017; Raghunathan et al., 2018). However, analysis by Athalye et al. (2018) shows that among various defensive strategies against adversarial examples, only the adversarial training does not rely on the obfuscated gradient and truly increases the model's robustness. A model is considered robust against adversarial examples if:

$$argmax f(x; \theta) = argmax f(x + \sigma; \boldsymbol{\theta}), s.t. ||\sigma||_\infty \leq \epsilon \tag{2}$$

where ϵ represents the magnitude of the perturbation. Therefore, the core idea of adversarial training is to train models with adversarial examples, formally:

$$loss(x, y) = E_{(x,y) \in D}[\max_{||\sigma||_\infty \leq \epsilon} loss(x + \sigma, y)], \tag{3}$$

The objective $\max_{|\sigma| \leq \epsilon} loss(x + \sigma, y)$ introduces the model to minimize empirical risk on the training data points while also being locally stable in the (radius-ϵ) neighborhood around each of data points x. The objective is approximated via gradient-based optimization methods such as PGD (Madry et al., 2018b). Several works attempt to improve adversarial training (Shafahi et al., 2019; Sriramanan et al., 2021; Jia et al., 2022; Cui et al., 2021).

Interestingly, Ilyas et al. (2019) proposes that by suppressing the importance of non-robust features, adversarial training makes the trained model more focused on robust and perceptually-aligned feature representations. In this process, both the gradient and feature representation becomes more sparse. Chalasani et al. (2020); Salman et al. (2020); Utrera et al. (2020) suggests that the feature representation generated by an adversarially trained model is concise as it is sparse and human-friendly. It only assigns the feature that is truly predictive of the output with significant contributions.

2.3 HOW INEQUALITY FORMS DURING l_∞ ADVERSARIAL TRAINING

In (Chalasani et al., 2020), they theoretically prove the connection between adversarial robustness and sparseness: During l_∞-adversarial training, supposed the adversarial perturbation σ satisfying $||\sigma||_\infty \leq \epsilon$, the model attempts to find robust features serving as strong signals against perturbation. Meanwhile, the weights of non-robust ones which serve as relatively weak signals, are more aggressively shrunk toward zero. The shrinkage rate is proportional to adversaries' strength (evaluated by ϵ). In other words, standard training can result in models where many non-robust features have significant importance for models, whereas l_∞-adversarial training tends to selectively reduce the magnitude of the significance of non-robust features with weakly relevant or irrelevant signals and push their significance close to zero. In the end, the feature attribution maps generated by gradients-based feature attribution methods (Smilkov et al., 2017; Lundberg & Lee, 2017; Sundararajan et al., 2017) look more sparse. They regard such sparseness as a merit of adversarial training as it produces more concise and human-aligned feature attributions. However, we further study such sparseness and find it introduces a phenomenon of extreme inequality, which results in unanticipated threats to adversarially trained model.

3 METHODOLOGY

In this section, we introduced the index used to measure the inequality degree of the test data point's feature attribution map. Then we propose two types of attacks to validate our hypothesis: extreme inequality results in threats to l_∞-adversarially trained model.

3.1 MEASURING THE INEQUALITY OF A TEST DATA POINT

Firstly, feature attribution maps are required to characterize the inequality degree by given test data point x and model f. Several feature attribution methods have been proposed in recent years (Smilkov et al., 2017; Lundberg & Lee, 2017; Sundararajan et al., 2017). In general, feature attribution methods rank the input features according to their purported importance in model prediction. To be specific, we treat the input image x as a set of pixels $x = \{x_i, i = 1...M\}$ and denote the generated feature attribution map of x of model f as $A^f(x)$, where $A^f(x)$ is composed of a_i. Feature attribution methods attribute an effect a_i to each feature x_i, and summing the effects of all feature attributions approximates the output $f(x)$. x_i achieves the top-most score (a_i) is considered the most important feature for prediction, whereas those with the bottom-most score are considered least important.

With a given sorted $A^f(x) = \{a_i, i = 1...M | a_i < a_{i+1}\}$ generated by a typical feature attribution method, if the prediction f(x) can be approximated with the sum of N most important features and N is much less than M, we name such distribution of $A^f(x)$ is unequal. Namely, the prediction on x made by model f is dominated by few pixels. Formally, we use Gini index (Dorfman, 1979) to measure the inequality of the distribution of a given feature attribution map. Formally, given a population set indexed in non-decreasing order $\Phi = \{\phi_i, i = 1...n | \phi_i \leq \phi_{i+1}\}$, Gini coefficient can be calculated as:

$$gini(\Phi) = \frac{1}{n}\left(n + 1 - 2\frac{\sum_{i=1}^{n}(n+1-i)*\phi_i}{\sum_{i=1}^{n}\phi_i}\right) \tag{4}$$

An advantage of the $gini(\cdot)$ index is that inequality of the entire distribution can be summarized by using a single statistic that is relatively easy to interpret. The Gini index ranges from 0, when the value of every ϕ_i is equal, to 1, when a single ϕ_i takes all the sum. This allows us to compare the inequality degree among feature attributions with different sizes. We define two types of inequality as follows:

- **Global inequality:** Given a feature attribution map $A^f(x) = \{a_i, i = 1...M | a_i < a_{i+1}\}$ on test data point x, we only consider the inequality degree of the global distribution of $A^f(x)$ and take no into account for other factors, the inequality degree is calculated with $gini_g(A^f(x))$ directly. The higher of $gini_g(A^f(x))$, the more unequal the distribution $A^f(x)$, the fewer pixels take the most prediction power. When $gini_g(A^f(x))$ is equal to 1, it indicates one pixel dominates the prediction while all the other pixels have no contribution to the current prediction.

- **Regional inequality:** We also consider inequality degree together with spatial factor, whether important feature tends to cluster at specific regions. A region is defined as a block with size of $n*n$ of input space. We first divide pixels into different regions and calculate the sum of pixels' importance by regions, formally, $A_r^f(x) = \{a_{r_i}, i = 1...m | a_{r_i} < a_{r_{i+1}}\}$, where a_r is the sum of a_i in the region. Therefore, the Gini value on $A_r^f(x)$ reflects the inequality degree of different regions of input space. The higher the value of $gini_r(A_r^f(x))$, the more important features are tend to cluster in the specific regions. When $gini_r(A_r^f(x))$ is equal to 1, it represents all pixels contribute to the prediction cluster in one region (block).

In what follows, we propose potential threats caused by such inequality (global and regional inequality). We devise attacks utilizing common corruptions (noise and occlusion) to reveal the unreliability of such decision pattern by l_∞-adversarially trained model.

3.2 ATTACK ALGORITHMS

We propose two simple attacks to validate potential threats caused by such inequality phenomena: 1) inductive noise attack. 2) inductive occlusion attack.

3.2.1 Inductive Noise Attack

We evaluate the models' performance under attacks designed by two types of noise.

- **Noise (Type I):** Given a image x, we perturb the most influential pixels of images with Gaussian noise $\sigma \in \mathcal{N}(0, 1)$ via masking M. Formally:

$$x' = x + M * \sigma, \quad where \quad M_i = \begin{cases} 0, a_i < a_{tre} \\ 1, a_i \geq a_{tre} \end{cases} \quad (5)$$

  where a_{tre} represents the threshold. x_i with value that is below to the a_{tre} will be kept, and x_i whose $a_i \geq a_{tre}$ is perturbed by Gaussian noise.

- **Noise (Type II):** About the second type of noise attack, we directly replace important pixels with Gaussian noise, formally $x' = \overline{M} * x + M * \sigma$, where $\overline{M}$ represents reverse mask of M. Compared to Noise-I, Noise-II replace important pixels totally and disturbs images more severely.

If the model's decision pattern is extremely unequal, the performance will be highly influenced when important features are corrupted by inductive noise attacks.

3.2.2 Inductive Occlusion Attack

With respect to inductive occlusion attack, we obscure regions of important pixels with occlusions gradually. During the attack, the max count of occlusions is N with radius at max R. The order of regions to perturb is decided by the value of $A_r^f(x)$, that region of higher a_{r_i} is perturbed in priority by occlusions with size $r \in \{1...R\}$. The number of occlusions is constrained by $n \in \{1...N\}$. We also consider occlusion with different colors to reflect potential real-world occlusion. The inductive occlusion attack algorithm is listed as follows:

Algorithm 1 Inductive Occlusion Attack

Require: Test data point (x, y), Model f, Regional Attribution map $A_r^f(x)$, Max count and radius N, R, Perturb color c.
Ensure: $f(x) = y$ $\quad\quad\quad\quad\quad\quad\quad\quad$ ▷ Ensure the test data x is correctly classified by model f.
$\quad n \leftarrow 1, r \leftarrow 1, x' = x$
$\quad$ **for** $n = 1$ to N **do**
$\quad\quad$ **for** $r = 1$ to R **do**
$\quad\quad\quad M \leftarrow \text{get\_perturb\_mask}(A_r^f(x), \text{n}, \text{r})$ $\quad\quad$ ▷ A function to acquire the perturbation mask.
$\quad\quad\quad x' = \overline{M} * x + M * c$ $\quad\quad\quad\quad\quad\quad\quad\quad$ ▷ Perturb x by mask M with color c.
$\quad\quad\quad$ **If** $f(x') \neq y$:**break**
$\quad\quad$ **end for**
$\quad$ **end for**
$\quad$ **return** x'

Note the intention of this work is not to propose strong adversarial attacks. Although either noise or occlusion is beyond the threat model considered in l_∞ adversarial training, we intend to reveal the threats caused by such inequality phenomena that previous work ignored. In summary, the extreme inequality decision pattern of l_∞-trained adversarial models result in themselves more fragile under some corruptions.

4 Experiments

In this section, we first outline the experimental setup. We then evaluate the inequality degree (by Gini) of different models. Then, we evaluate the performance of under the proposed attacks. Finally, we perform an ablation study about the selection of feature attribution methods.

4.1 Experimental settings

Dataset and models. We perform a series of experiments on ImageNet Deng et al. (2009) and CIFAR10 Krizhevsky et al. (2009). With respect to experiments on ImageNet, we use ResNet18 (He

et al., 2016), ResNet50, WideResNet50 (Zagoruyko & Komodakis, 2016) provided by Microsoft [1]. For CIFAR10, we use ResNet18, DenseNet (Huang et al., 2017). See A.1 for more details of models including standard and robust accuracy. Regarding feature attribution methods (implementation by Captum[2]), we consider methods including Input X Gradients (Shrikumar et al., 2016), Integrated Gradients (Sundararajan et al., 2017), Shapley Value (Lundberg & Lee, 2017) and SmoothGrad (Smilkov et al., 2017). Considering space and time efficiency, we present experimental results based on Integrated Gradients and perform an ablation study on the other feature attribution methods.

Metrics. For all the tests about the models' performance, we use error rate (%) as the metric to evaluate the model's performance under corruptions (e.g., noise and occlusions), which is the proportion of misclassified test images among the total number of test images defined as $\frac{1}{N} \sum_{n=1}^{N} [f(x) \neq f(x')]$, where x represents clean test images, and x' represents test images corrupted by noise and occlusions.

4.2 INEQUALITY TEST

In this section, we first evaluate the inequality degree (both global and regional inequality) of l_∞-adversarially trained models and standard trained models with different architectures (ResNet18, ResNet50, WideResNet, DenseNet) trained on ImageNet and Cifar10. We also evaluate the inequality degree of different models adversarially trained with increasing l_∞-norms ($\epsilon = 1, 2, 4, 8$). In the case of the evaluation on Gini, We applied the Gini index to the sorted absolute value of the flattened feature attribution maps. On evaluating regional inequality, the region's size is $16 * 16$ for experiments on ImageNet and $4 * 4$ for CIFAR10. The results are presented in table 1. As shown in Table

Table 1: **Gini index across different models.** We evaluate the Gini coefficient of different models trained with different ϵ on ImageNet and Cifar10.

Dataset	Model	Std. trained	$\epsilon = 1.0$	$\epsilon = 2.0$	$\epsilon = 4.0$	$\epsilon = 8.0$
		Global Inequality				
Cifar10	ResNet18	0.58 ± 0.05	0.65 ± 0.05	0.67 ± 0.06	0.69 ± 0.06	0.73 ± 0.06
	DenseNet	0.57 ± 0.04	0.66 ± 0.06	0.67 ± 0.06	0.69 ± 0.06	0.72 ± 0.07
		Regional Inequality				
	ResNet18	0.79 ± 0.02	0.87 ± 0.04	0.87 ± 0.04	0.88 ± 0.04	0.88 ± 0.04
	DenseNet	0.79 ± 0.02	0.85 ± 0.04	0.86 ± 0.04	0.87 ± 0.04	0.88 ± 0.03
		Global Inequality				
	ResNet18	0.60 ± 0.04	0.69 ± 0.06	0.79 ± 0.04	0.92 ± 0.01	0.95 ± 0.01
	ResNet50	0.62 ± 0.04	0.75 ± 0.05	0.86 ± 0.03	0.92 ± 0.02	0.94 ± 0.01
ImageNet	WideResNet	0.62 ± 0.05	0.74 ± 0.05	0.79 ± 0.04	0.88 ± 0.03	0.94 ± 0.01
		Regional Inequality				
	ResNet18	0.80 ± 0.02	0.83 ± 0.04	0.88 ± 0.03	0.95 ± 0.01	0.97 ± 0.01
	ResNet50	0.84 ± 0.02	0.91 ± 0.05	0.95 ± 0.02	0.96 ± 0.01	0.97 ± 0.01
	WideResNet	0.81 ± 0.03	0.86 ± 0.03	0.88 ± 0.03	0.93 ± 0.03	0.97 ± 0.02

1, on Cifar10, the global inequality degree of the standard trained model with different architectures is around 0.58. The gini (global inequality) for l_∞-adversarially trained model is around 0.73 when $\epsilon = 8$. However, on ImageNet, the inequality phenomena are much more obvious. Especially for an adversarially trained Resnet50 ($\epsilon = 8$), the gini achieves 0.94, which indicates that only a handful of pixels decide the prediction. Experiments on Cifar10 and ImageNet show that l_∞-adversarially trained models rely on fewer pixels to support the prediction with the increasing of the adversarial strength (ϵ). We also test the inequality degree on different classes belonging to ImageNet; classes related to animal tends to have higher value on gini index. For example, class 'Bustard' has the highest value on gini of 0.950. Classes related to scene or stuff tend to have lower value on gini index. For example, class 'Web site' has the lowest inequality of 0.890 (See more results in Appendix A.7).

---

[1]https://github.com/microsoft/robust-models-transfer
[2]https://github.com/pytorch/captum

We visualize the features' attribution of given images for the standard and adversarially trained ResNet50 respectively in Figure 2. As shown in Figure 2, when the model is adversarially trained

Figure 2: **Feature attributions of different models.** We visualize feature attributions generated by $l_\infty-$adversarially trained models (adversarially trained by adversaries of different ϵ), the larger of ϵ, the fewer features that model relies on for prediction.

with weak adversarial strength ($\epsilon = 1$), the model has better feature attribution aligned to human observers. However, when the adversarial strength increases, the model gradually assigns higher importance to fewer pixels and resulting in extreme inequality regarding feature attribution. Moreover, these important features tend to gather in few specific regions (see more visualization results in Appendix A.10).

4.3 EVALUATION UNDER INDUCTIVE NOISE ATTACK

In this part, we compare the performance of standard- and adversarially- trained ResNet50 under random and inductive noise. For a fair comparison, we first select 1000 random images from ImageNet that are correctly classified by all the models. We set noise with different scales, including subpixels of 500, 1000, 5000, 10000, and 20000. We present the results in Figure 3.

Figure 3: **Evaluation under noise.** We plot the error rate of standard- and adversarially-trained models on images perturbed by the increasing number of noise.

Under random noise, the success rate of attack on adversarially-trained model achieves 73.4%, but only 18.8% for standard-trained model. Under Noise of Type I, the adversarially trained model is fooled by 94.0%, while the standard trained model is only fooled by 34.5%. Under Noise of Type II, even when we control the amount of noise with a small threshold (e.g., 1000 subpixels), more than 50% of predictions made by the adversarially trained model is affected. When we enlarge the threshold to 20000, the adversarially-trained model (ϵ=8) is almost fooled with a 100% success rate. In summary, compared to the standard trained model, l_∞-adversarial model relies on fewer features to make a decision; such a decision pattern results in unstable prediction under noise.

4.4 EVALUATION UNDER INDUCTIVE OCCLUSION ATTACK

In this part, we perform an inductive occlusion attack and evaluate the standard trained and l_∞-adversarially trained ResNet50s' performance. We set two group experiments with different thresholds. Also, for a fair comparison, we first select 1000 random images that are correctly classified by all the models.

In the first group of experiments, we generate occlusions with a max count of 5 and a max radius of 10. In this case, the adversarially-trained model is fooled at a 71.7% error rate, but the standard trained model' predictions are only affected by 31.6%. When we enlarge the threshold and set max count as 10 and radius as 20 for occlusions, both $\epsilon = 4$ and $\epsilon = 8$ adversarially trained model can be fooled with 100% success rate while only 41.2% attack success rate for the standard-trained model. We visualize the results in Figure 4. As the figure shows, l_∞-adversarially trained model with larger ϵ could be easily attacked by smaller occlusions even under the same threshold. For example, in Figure 4, the standard trained model can recognize 'Bulbul' well with the head part occluded, but the adversarially trained model fails to recognize the 'Bulbul' if only the beak of the bulbul is occluded. Moreover, compared with adversarial perturbation, occlusion is more

Table 2: **Models' performance (Error rate %) under occlusions.** We evaluate the models' performance by gradually occluding important areas with patches of different sizes and colors.

Model	Std.	$\epsilon = 1.0$	$\epsilon = 2.0$	$\epsilon = 4.0$	$\epsilon = 8.0$
		Max cnt N = 5, R = 10			
Occlusion-G	23.5%	31.6%	38.4%	32.4%	54.0%
Occlusion-W	28.3%	48.4%	57.5%	61.3%	71.7%
Occlusion-B	31.6%	51.5%	53.3%	48.9%	64.6%
		Max cnt N = 10, R = 20			
Occlusion-G	30.1%	48.2%	56.3%	100.0%	100.0%
Occlusion-W	40.1%	59.1%	73.3%	100.0%	100.0%
Occlusion-B	41.2%	70.2%	72.2%	100.0%	100.0%

Figure 4: **Visualization of occluded images.** We visualize images occluded with different patches of different sizes and the corresponding predictions made by standard and l_∞-adversarially trained models. Compared to a standard-trained model, the adversarially trained model is fragile when occlusion covers the area of important features.

practical as occlusion frequently appear in the real world.

4.5 ABLATION STUDY

We consider four attribution methods for ablation study: Input X Gradient (Shrikumar et al., 2016), SmoothGrad (Smilkov et al., 2017), Gradient Shapley Value (GradShap for short) (Lundberg & Lee, 2017) and Integrated Gradients (Sundararajan et al., 2017). More details and parameter settings of

feature attribution methods can be seen in Appendix A.8. We perform an ablation study to evaluate the effect of selection on the feature attribution methods (see Table 3).

Table 3: **Ablation study on selection.** We evaluate our hypothesis with different feature attribution methods.

Attribution Method	Model	Gini	Noise I	Noise II	Occlusion-B	Occlusion-G	Occlusion-W
Input X Gradient	Std. trained	0.63	16.1%	45.0%	24.7%	16.8%	23.5%
	Adv. trained	0.93	60.9%	90.4%	63.3%	51.2%	63.2%
GradShap	Std. trained	0.62	19.8%	54.7%	31.5%	24.1%	29.9%
	Adv. trained	0.93	62.3%	93.7 %	64.8%	53.3%	71.6%
SmoothGrad	Std. trained	0.75	63.5%	45.0%	32.3%	25.6%	30.3%
	Adv. trained	0.98	82.5%	98.3%	61.6%	49.7%	60.8%
Integrated Gradients	Std. trained	0.62	16.5%	55.5%	31.6%	23.5%	28.3%
	Adv. trained	0.94	63.9 %	95.5%	64.6%	54.0%	71.7%

Among various attribution methods, SmoothGrad produces more spare feature attribution maps and thus results in higher values on Gini. Regarding evaluation under noise, SmoothGrad increase inductive noise attack's success rate. Regarding evaluation under occlusion, Integrated Gradients improves the attack's success rate on models.

In conclusion, the selection of attribution methods slightly affects attacks' success rates but does not change our conclusion: the distribution of features' attribution by the adversarially trained model is more unequal; such inequality makes the adversarially trained model more susceptible to inductive noise and occlusions.

5   DISCUSSION AND CONCLUSION

In this work, we study the inequality phenomena that occur during l_∞-adversarial training. Specifically, we find l_∞-adversarially trained models' feature attribution is not as aligned with human perception as we expect. An ideal human-perceptual aligned model is expected to make decisions based on a series of core feature attributions. For example, if the model classifies an input image as a bird, it should take attributions, including the eye, the beak of the bird, and the shape of the bird, all of these attributions into account. However, we find l_∞-adversarially trained model only relies on individual attribution (only the bird's beak) for recognition. We name such phenomena as inequality phenomenon. We perform extensive experiments to evaluate such inequality phenomena and find that l_∞ robust model assigns a few features with extremely high importance. Thus, a few features dominate the prediction. Such extreme inequality of l_∞ adversarially trained model result in unreliability. We also design attacks (by utilizing noise and occlusion) to validate our hypothesis that adversarially trained models could be more susceptible under some scenarios. We find an attacker can easily fool the l_∞-trained model by modifying important features with either noise or occlusion easily. We suggest that both noise and occlusion are common in a real-world scenario. Robustness against either noise or occlusion is more essential and crucial than robustness against adversarial examples. Our work reveals the limitation and vulnerability of the current l_∞-adversarially trained model.

We also propose a strategy to release such inequality phenomena during l_∞-adversarial training. We combine Cutout (DeVries & Taylor, 2017) strategy with adversarial training and force the model learning features from different regions by cutting out part of training images at each iteration during the training (see the result in Appendix A.9). The strategy slightly releases the inequality degree of the adversarially trained model. More effective strategies releasing such extreme inequality could be a crucial and promising direction as future work. Besides safety and security issues, this work provides an intuitive understanding of adversarial models' feature representation. We hope our work can motivate new research into the characteristics of adversarial training and open up further challenges for reliable and practical adversarial training.

ETHICS STATEMENT

In this paper, we identify inequality phenomena occur during l_∞-adversarial training, that l_∞-adversarially trained model tends to use few features to make the decision. We give a systematical evaluation of such inequality phenomena across different datasets and models with different architectures. We further identified unrealized threats caused by such decision patterns and validated our hypothesis by designing corresponding attacks. Our findings provide a new perspective on inspecting adversarial training. Our goal is to understand current adversarial training's weaknesses and make DNNs truly robust and reliable. We did not use crowdsourcing and did not conduct research with human subjects in our experiments. We cited the creators when using existing assets (e.g., code, data, models).

REPRODUCIBILITY STATEMENT

We present the settings of hyper-parameters and how they were chosen in the experiment section. We repeat experiments multiple times with different random seeds and show the corresponding standard deviation in the tables. We plan to open the source code to reproduce the main experimental results later.

REFERENCES

Naveed Akhtar, Jian Liu, and Ajmal Mian. Defense against universal adversarial perturbations. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3389–3398, 2018.

Zeyuan Allen-Zhu and Yuanzhi Li. Feature purification: How adversarial training performs robust deep learning. In *2021 IEEE 62nd Annual Symposium on Foundations of Computer Science (FOCS)*, pp. 977–988. IEEE, 2022.

Maksym Andriushchenko and Nicolas Flammarion. Understanding and improving fast adversarial training. *Advances in Neural Information Processing Systems*, 33:16048–16059, 2020.

Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. In *International conference on machine learning*, pp. 274–283. PMLR, 2018.

Nicholas Carlini and David Wagner. Adversarial examples are not easily detected: Bypassing ten detection methods. In *ACM Workshop on Artificial Intelligence and Security*, pp. 3–14. ACM, 2017.

Prasad Chalasani, Jiefeng Chen, Amrita Roy Chowdhury, Xi Wu, and Somesh Jha. Concise explanations of neural networks using adversarial training. In *International Conference on Machine Learning*, pp. 1383–1391. PMLR, 2020.

Pin-Yu Chen, Yash Sharma, Huan Zhang, Jinfeng Yi, and Cho-Jui Hsieh. Ead: Elastic-net attacks to deep neural networks via adversarial examples. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.

Francesco Croce and Matthias Hein. Reliable evaluation of adversarial robustness with an ensemble of diverse parameter-free attacks. In *International conference on machine learning*, pp. 2206–2216. PMLR, 2020.

Jiequan Cui, Shu Liu, Liwei Wang, and Jiaya Jia. Learnable boundary guided adversarial training. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 15721–15730, 2021.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 248–255, 2009.

Zhun Deng, Linjun Zhang, Kailas Vodrahalli, Kenji Kawaguchi, and James Y Zou. Adversarial training helps transfer learning via better representations. *Advances in Neural Information Processing Systems*, 34:25179–25191, 2021.

Terrance DeVries and Graham W Taylor. Improved regularization of convolutional neural networks with cutout. *arXiv preprint arXiv:1708.04552*, 2017.

Robert Dorfman. A formula for the gini coefficient. *The review of economics and statistics*, pp. 146–149, 1979.

Logan Engstrom, Andrew Ilyas, Shibani Santurkar, Dimitris Tsipras, Brandon Tran, and Aleksander Madry. Adversarial robustness as a prior for learned representations. *arXiv preprint arXiv:1906.00945*, 2019.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *International Conference on Learning Representations*, 2015.

Chuan Guo, Mayank Rana, Moustapha Cisse, and Laurens van der Maaten. Countering adversarial images using input transformations. In *International Conference on Learning Representations*, 2018.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE/CVF Conference on Computer vision and Pattern Recognition*, pp. 770–778, 2016.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 4700–4708, 2017.

Andrew Ilyas, Shibani Santurkar, Dimitris Tsipras, Logan Engstrom, Brandon Tran, and Aleksander Madry. Adversarial examples are not bugs, they are features. In *Neural Information Processing Systems*, pp. 125–136, 2019.

Xiaojun Jia, Yong Zhang, Baoyuan Wu, Ke Ma, Jue Wang, and Xiaochun Cao. Las-at: Adversarial training with learnable attack strategy. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 13398–13408, 2022.

Hoki Kim, Woojin Lee, and Jaewook Lee. Understanding catastrophic overfitting in single-step adversarial training. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pp. 8119–8127, 2021.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Alexey Kurakin, Ian Goodfellow, and Samy Bengio. Adversarial examples in the physical world. *International Conference on Learning Representations*, 2016.

Scott M Lundberg and Su-In Lee. A unified approach to interpreting model predictions. *Advances in neural information processing systems*, 30, 2017.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In *International Conference on Learning Representations*, 2018a.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In *International Conference on Learning Representations*, 2018b.

Dongyu Meng and Hao Chen. Magnet: a two-pronged defense against adversarial examples. In *Proceedings of the 2017 ACM SIGSAC conference on computer and communications security*, pp. 135–147, 2017.

Chaithanya Kumar Mummadi, Thomas Brox, and Jan Hendrik Metzen. Defending against universal perturbations with shared adversarial training. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 4928–4937, 2019.

Aaditya Prakash, Nick Moran, Solomon Garber, Antonella DiLillo, and James Storer. Deflecting adversarial attacks with pixel deflection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8571–8580, 2018.

Aditi Raghunathan, Jacob Steinhardt, and Percy Liang. Certified defenses against adversarial examples. In *International Conference on Learning Representations*, 2018.

Andrew Ross and Finale Doshi-Velez. Improving the adversarial robustness and interpretability of deep neural networks by regularizing their input gradients. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.

Hadi Salman, Andrew Ilyas, Logan Engstrom, Ashish Kapoor, and Aleksander Madry. Do adversarially robust imagenet models transfer better? *Advances in Neural Information Processing Systems*, 33:3533–3545, 2020.

Ali Shafahi, Mahyar Najibi, Mohammad Amin Ghiasi, Zheng Xu, John Dickerson, Christoph Studer, Larry S Davis, Gavin Taylor, and Tom Goldstein. Adversarial training for free! *Advances in Neural Information Processing Systems*, 32, 2019.

Avanti Shrikumar, Peyton Greenside, Anna Shcherbina, and Anshul Kundaje. Not just a black box: Learning important features through propagating activation differences. *arXiv preprint arXiv:1605.01713*, 2016.

Daniel Smilkov, Nikhil Thorat, Been Kim, Fernanda Viégas, and Martin Wattenberg. Smoothgrad: removing noise by adding noise. *arXiv preprint arXiv:1706.03825*, 2017.

Gaurang Sriramanan, Sravanti Addepalli, Arya Baburaj, et al. Towards efficient and effective adversarial training. *Advances in Neural Information Processing Systems*, 34:11821–11833, 2021.

Mukund Sundararajan, Ankur Taly, and Qiqi Yan. Axiomatic attribution for deep networks. In *International conference on machine learning*, pp. 3319–3328. PMLR, 2017.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In *International Conference on Learning Representations*, 2013.

Francisco Utrera, Evan Kravitz, N Benjamin Erichson, Rajiv Khanna, and Michael W Mahoney. Adversarially-trained deep nets transfer better: Illustration on image classification. In *International Conference on Learning Representations*, 2020.

Eric Wong and Zico Kolter. Provable defenses against adversarial examples via the convex outer adversarial polytope. In *International Conference on Machine Learning*, pp. 5286–5295. PMLR, 2018.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. In *British Machine Vision Conference 2016*. British Machine Vision Association, 2016.

Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric Xing, Laurent El Ghaoui, and Michael Jordan. Theoretically principled trade-off between robustness and accuracy. In *International conference on machine learning*, pp. 7472–7482. PMLR, 2019.

A APPENDIX

A.1 DETAILS OF MODELS

A.1.1 DETAILS OF MODELS TRAINED ON IMAGENET

We summarize the clean and robust accuracy of models trained on ImageNet in Table **??**. Regarding robust accuracy, we use PGD for evaluation. During the training on ImageNet, the images are resized

Table 4

Model	Std. trained	$\epsilon=1/255$	$\epsilon=2/255$	$\epsilon=4/255$	$\epsilon=8/255$
ResNet-18	69.76	63.46 /33.38	59.63 /29.80	52.49 /26.52	42.11 /23.75
ResNet-50	76.13	72.05 /45.02	69.10 / 42.75	63.86 / 38.85	54.53 / 33.05
Wide-ResNet-50	81.60	74.65 /47.30	72.35 /45.95	68.41 /43.10	60.82 /38.35

to 256 using interpolation=InterpolationMode.BILINEAR, followed by a central crop of size=224. Finally, the values are first rescaled to [0.0, 1.0] and then normalized using mean=[0.485, 0.456, 0.406] and std=[0.229, 0.224, 0.225].

```
TRAIN_TRANSFORM = transforms.Compose([
    transforms.Resize(256),
    transforms.CenterCrop(224),
    transforms.RandomHorizontalFlip(),
    transforms.ToTensor(),
])
TEST_TRANSFORM = transforms.Compose([
    transforms.Resize(256),
    transforms.CenterCrop(224),
    transforms.ToTensor(),
])
```

A.1.2 DETAILS OF MODELS TRAINED ON CIFAR10

We summarize the clean and robust accuracy of models trained on CIFAR10 in Table 5. Regarding robust accuracy, we use AutoAttack Croce & Hein (2020) for evaluation.

Table 5

Model	Std. trained	$\epsilon=1/255$	$\epsilon=2/255$	$\epsilon=4/255$	$\epsilon=8/255$
ResNet-18	93.90	92.10 /86.60	90.40 /79.90	88.30 /68.80	81.20 /48.60
DenseNet	92.80	91.30 /86.60	89.90 /79.50	85.80 /65.90	79.60 /44.40

```
TRAIN_TRANSFORM = transforms.Compose([
    transforms.RandomCrop(32, padding=4),
    transforms.RandomHorizontalFlip(),
    transforms.ToTensor(),
])

TEST_TRANSFORM = transforms.Compose([
    transforms.ToTensor(),
])
```

A.2   FURTHER DISCUSSION ABOUT FEATURE ATTRIBUTION

Figure 5: **Visualizing feature attibution with and without post-procesing (by 3 deviaition).**

Figure 6: **More comparison** .

A.3 VISUALIZATION FOR CIFAR10

We visualize feature attribution maps and attack results for Cifar10. About the setting of attack, we set max count $N = 10$, with max radius $R = 4$. With occlusion with different colors (black, white and grey), success rates on 1000 correct classified images of l_∞-adversarially trained model are 60.4%, 60.5%, and 38.1% repsectively. And success rates for standard trained model are 34.6 %, 36.7% and 24.1% respectively. We visualize corresponding results in Figure 8.

Figure 7: **Visualization of feature attribution on CIFAR10.**

Figure 8: **Visualization of occluded images for CIFAR10.**

A.4 TRANSFERABILITY TEST

Attack	Occ -B (cnt=5, r=10)		Occ-B (cnt=10, r=20)		Noise-I		Noise-II	
Model	**Adv.**	**Std.**	**Adv.**	**Std.**	**Adv.**	**Std.**	**Adv.**	**Std.**
Adv.	100.0	11.4	100.0	17.4	100.0	10.6	100.0	18.6
Std.	22.8	100.0	43.6	100.0	26.8	100.0	58.2	100.0

A.5 COMPARED WITH l_2-ADVERSARIALLY TRAINED MODEL

Model	Clean acc	gini-g	gini-r	Occ-B	Occ-G	Occ-W	Noise-I	Noise-II
Std. trained	76.13%	0.62	0.84	33.0%	28.1%	36.5%	15.8%	49.8%
l2-AT model	56.13%	0.60	0.76	51.4%	32.5%	48.3%	2.9%	36.3%
linf-AT model	54.53%	0.95	0.97	81.5%	61.0%	77.2%	75.6%	96.1%

A.6 COMPARED WITH MODEL TRAINED WITH SPARSITY REGULARIZATION

Model	Clean Acc	Gini g	Gini r	Occ-B	Occ-G	Occ-W	Noise-I	Noise_II
Adv. trained	54.53%	0.94	0.97	78.2%	80.2%	60.2%	60.9%	95.1%
L1-norm sparsity	73.08%	0.60	0.80	56.8%	57.8%	52.5%	40.7%	89.2%
Weight-level Pruning	75.60%	0.62	0.81	33.1%	29.2%	25.8%	15.7%	49.9%

A.7 EQUALITY DEGREE OF DIFFERENT CLASSES

We test inequality degree of feature attributions' distribution of 50000 samples from 1000 classes in ImageNet. We present results in Table 6.

Table 6: **Global inequality degree of different classes ($l_\in$-Adv. traind, $\epsilon = 8$)**

Top-5	Class	Bustard	Manhole cover	Oystercatcher	Redshank	Pomeranian
	Gini	0.950	0.949	0.949	0.949	0.949
Bottom-5	Class	Web site	Slot	Grocery store	Grille	Comic book
	Gini	0.890	0.900	0.901	0.901	0.905

Classes with top-5 inequality (gini value) are: Bustard, Manhole cover, Oystercatcher, Redshank and Pomeranian. And their Gini values are 0.950, 0.949, 0.949, 0.949 and 0.949. Classes with bottom-5 inequality (gini value) are: Web site, Slot, Grocery store, Grille and Comic book. Their corresponding gini values are: 0.890, 0.900, 0.901, 0.901 and 0.905.

Regarding regional inequality, we present results in Table 7. Classes with high regional inequality

Table 7: **Regional inequality degree of different classes ($l_\in$-Adv. traind, $\epsilon = 8$)**

Top-5	Class	Redshank	American coot	Oystercatcher	Bustard	Gazelle
	Gini	0.976	0.975	0.975	0.974	0.974
Bottom-5	Class	Web site	Grocery store	Confectionery	Slot	Grille
	Gini	0.929	0.932	0.934	0.935	0.936

are similar to classes with high global inequality. Specifically, classes of the top 5 (regional inequality) are Redshank, American coot, Oystercatcher, Bustard and Gazelle. And the $gini_r(.)$ of these classes are: 0.976, 0.975, 0.975, 0.974 and 0.974. Classes in the bottom 5 (regional inequality) are Web site, Grocery store, Confectionery, Slot, and Grille. And the $gini_r(.)$ of these classes are: 0.929, 0.932, 0.934, 0.935 and 0.936.

A.8 Details about Feature Attribution Method

We use attribution methods including Input X Gradient, Smooth Gradient (short for SmoothGrad), Gradient Shapley Value (short for GradShap) and Integrated Gradients.

Input X Gradient: The Input X Gradient multiplies input with the gradient with respect to each input feature. It is a baseline approach for computing the attribution.

GradShap: Shapley Values aims compute each feature's attribution based on cooperative game theory. GradShap approximates Shapley Values by computing the expectations of gradients by randomly sampling from the distribution of $baselines$. It adds noise to each input sample $n_{samples}$ times, selects a random baseline from the baselines' distribution, and a random point along the path between the baseline and the input. Then it computes the gradient of outputs with respect to those selected random points. In our evaluation, we set $n_{samples} = 20$ for experiments with ImageNet and $n_{samples} = 10$ for experiments with Cifar10. We set $baseline = 0$ for all the experiments.

Integrated Gradients: Integrated Gradients is an axiomatic model which assigns an importance score to each input feature by approximating the integral of gradients of the model's output with respect to the inputs along the path (straight line) from given $baseline$ to inputs. Previous work points out Integrated Gradients method is sensitive to the choice of path. To reduce such sensitivity, Integrated Gradients are usually repeated for n_{step} steps. For all the experiments, we set $n_{step} = 20$, and $baseline \in \mathcal{N}(0, 1)$.

SmoothGrad: SmoothGrad adds gaussian noise to each input in the batch $n_{samples}$ times, then applies the given attribution algorithm to each of the samples. It returns the mean of the sampled attributions. SmoothGrad returns a sparser feature attribution map than other methods. In our experiment, we set $n_{samples} = 20$

A.9 How to release inequality phenomenon

We also try to propose a strategy to release the inequality phenomenon in adversarial training. Intuitively, we hope adversarially trained models learns to find robust features from the whole image rather than focus on a specific robust feature. Towards this end, we incorporate Cutout with adversarial training that Cutout enables the model to learn features from multiple spatial spaces. We evaluate our strategy on Cifar10. The results are presented in Table 8.

Model	Gini	Gini-R	Clean Acc.	Adv. Acc.	Noise I	Noise II	Occlusion-B	Occlusion-G	Occlusion-W
Adv. trained	0.73	0.88	82.10 %	48.50 %	40.31 %	1.58%	100.00%	100.00%	100.00%
Adv. trained+Cutout	0.70	0.88	81.40 %	47.20 %	40.78%	1.72%	93.39%	29.98%	55.06 %

Table 8: l_{∞}-**adversarial training with and without Cutout.**

As the table indicates, the Cutout strategy can slightly release the inequality of l_{∞}-adversarial training. But at a price, both clean accuracy and adversarial accuracy slightly decrease. Regarding performance under noise and occlusion, the strategy does not improve the adversarial trained model's performance under noise but improves its performance under occlusions. A more effective strategy to release inequality phenomena is highly required.

A.10 MORE VISUALIZATION RESULTS

Figure 9: Visualization of feature attributions generated by standard- and adversarially trained model with different ϵ.