Efficient Methods for Non-stationary Online Learning

Abstract

Non-stationary online learning has drawn much attention in recent years. In particular, *dynamic regret* and *adaptive regret* are proposed as two principled performance measures for online convex optimization in non-stationary environments. To optimize them, a two-layer online ensemble is usually deployed due to the inherent uncertainty of the non-stationarity, in which a group of base-learners are maintained and a meta-algorithm is employed to track the best one on the fly. However, the two-layer structure raises the concern about the computational complexity — those methods typically maintain $\mathcal{O}(\log T)$ base-learners simultaneously for a T-round online game and thus perform multiple projections onto the feasible domain per round, which becomes the computational bottleneck when the domain is complicated. In this paper, we present efficient methods for optimizing dynamic regret and adaptive regret, which reduce the number of projections per round from $\mathcal{O}(\log T)$ to 1. Moreover, our obtained algorithms require only one gradient query and one function evaluation at each round. Our technique hinges on the reduction mechanism developed in parameter-free online learning and requires non-trivial twists on non-stationary online methods. Empirical studies verify our theoretical findings.

1 Introduction

Classic online learning minimizes the static regret, which benchmarks the online learner's performance against the best fixed decision in hindsight. In many real-world online applications, however, the environments are non-stationary and static regret becomes less attractive since it would be unrealistic to assume the existence of a single decision behaved satisfactorily over time.

To address the limitation, in recent years, researchers have studied more strengthened performance measures to facilitate online algorithms with the capability of handling non-stationarity. In particular, dynamic regret [Zinkevich, 2003; Zhang et al., 2018a] and adaptive regret [Hazan and Seshadri, 2009; Daniely et al., 2015] are proposed as two principled metrics to guide the algorithm design. We focus on the online convex optimization (OCO) setting [Hazan, 2016]. OCO can be deemed as a game between the learner and the environments. At each round $t \in [T]$, the learner submits her decision $\mathbf{x}_t \in \mathcal{X}$ from a convex feasible domain $\mathcal{X} \subseteq \mathbb{R}^d$ and simultaneously environments choose a convex function $f_t : \mathcal{X} \mapsto \mathbb{R}$, and subsequently the learner suffers an instantaneous loss $f_t(\mathbf{x}_t)$.

1.1 Dynamic Regret and Adaptive Regret

Dynamic regret is proposed by Zinkevich [2003] to compare the online learner's performance against a sequence of *any* feasible comparators $\mathbf{u}_1, \ldots, \mathbf{u}_T \in \mathcal{X}$. Formally, it is defined as

$$\text{D-Reg}_T(\mathbf{u}_1, \ldots, \mathbf{u}_T) = \sum_{t=1}^{T} f_t(\mathbf{x}_t) - \sum_{t=1}^{T} f_t(\mathbf{u}_t). \tag{1}$$

Dynamic regret minimization enables the learner to track changing comparators. A favorable dynamic regret bound should scale with a certain non-stationarity measure dependent on the comparators such as the path-length $P_T = \sum_{t=2}^{T} \|\mathbf{u}_t - \mathbf{u}_{t-1}\|_2$. Notably, the classic static regret can be treated as a special case of dynamic regret by specifying the comparators as the best fixed decision in hindsight.

Adaptive regret is proposed by Hazan and Seshadhri [2009] and further strengthened by Daniely et al. [2015], which measures the regret over *any* interval $I = [r, s] \subseteq [T]$ with a length of $\tau = |I|$, i.e.,

$$\text{A-Reg}_T(|I|) = \max_{[r, r+\tau-1] \subseteq [T]} \left\{ \sum_{t=r}^{r+\tau-1} f_t(\mathbf{x}_t) - \min_{\mathbf{u} \in \mathcal{X}} \sum_{t=r}^{r+\tau-1} f_t(\mathbf{u}) \right\}. \tag{2}$$

Since the minimizers of different intervals can be different, adaptive regret minimization also ensures the capability of competing with changing comparators. A desired adaptive regret bound should be as close as the minimax static regret of this interval. Algorithms with adaptive regret matching static regret of this interval up to logarithmic terms in T are referred to strongly adaptive [Daniely et al., 2015]. Moreover, adaptive regret includes static regret when choosing $I = [T]$.

It is worth noting that the relationship between dynamic regret and adaptive regret for OCO is generally unclear [Zhang, 2020, Section 5], even though a black-box reduction from dynamic regret to adaptive regret has been proven for the simper expert setting (i.e., online linear optimization over simplex) [Luo and Schapire, 2015, Theorem 4]. Hence, the two measures are separately developed and many algorithms have been proposed, including algorithms for dynamic regret [Zinkevich, 2003; Hall and Willett, 2013; Luo and Schapire, 2015; Zhang et al., 2018a; Zhao et al., 2020, 2021; Baby and Wang, 2021; Luo et al., 2022] and the ones for adaptive regret [Hazan and Seshadhri, 2009; Daniely et al., 2015; Jun et al., 2017; Zhang et al., 2018b, 2019]. There are also studies [Zhang et al., 2020; Cutkosky, 2020] optimizing both measures simultaneously by an even strengthened metric $\sum_{t=r}^{s} f_t(\mathbf{x}_t) - \sum_{t=r}^{s} f_t(\mathbf{u}_t)$ over any interval $[r, s] \subseteq [T]$, hence called "interval dynamic regret".

1.2 Two-layer Structure and Projection Complexity Issue

The fundamental challenge of optimizing these two non-stationary regret measures is the uncertainty of the environmental non-stationarity. Concretely, to ensure the robustness to the unknown environments, dynamic regret aims to compete with *any* feasible comparator sequence, while adaptive regret examines the local performance over *any* intervals. The unknown comparators or unknown intervals bring considerable uncertainty to the online optimization. To address the issue, a two-layer structure is usually deployed to optimize the measures, where a set of base-learners are maintained to handle the different possibilities of online environments and a meta-algorithm is employed to combine them all and track the unknown best one. Such a framework successfully achieves many state-of-the-art results, including the $\mathcal{O}(\sqrt{T(1 + P_T)})$ minimax dynamic regret [Zhang et al., 2018a] and the $\mathcal{O}(\sqrt{(F_T + P_T)(1 + P_T)})$ small-loss dynamic regret for smooth functions [Zhao et al., 2020], where $P_T = \sum_{t=2}^{T} \|\mathbf{u}_t - \mathbf{u}_{t-1}\|_2$ is the path-length and $F_T = \sum_{t=1}^{T} f_t(\mathbf{u}_t)$ is the cumulative loss of comparators; as well as the $\mathcal{O}(\sqrt{|I| \log T})$ adaptive regret [Jun et al., 2017] and the $\mathcal{O}(\sqrt{F_I \log F_I \log F_T})$ small-loss adaptive regret for smooth functions [Zhang et al., 2019] for any interval $I = [r, s] \subseteq [T]$, where $F_I = \min_{\mathbf{x} \in \mathcal{X}} \sum_{t=r}^{s} f_t(\mathbf{x})$ and $F_T = \min_{\mathbf{x} \in \mathcal{X}} \sum_{t=1}^{T} f_t(\mathbf{x})$. Besides, an $\mathcal{O}(\sqrt{|I|(\log T + P_I)})$ interval dynamic regret is also achieved by a two-layer (or even three-layer) structure [Zhang et al., 2020], where $P_I = \sum_{t=r}^{s} \|\mathbf{u}_t - \mathbf{u}_{t-1}\|_2$ is the path-length over the interval.

The two-layer methods have demonstrated great effectiveness in tackling non-stationary online environments, whereas the gain is at the price of heavier computations than the methods for minimizing static regret. While it is believed that additional computations are necessary for more robustness, we are wondering whether it is possible to pay for a "minimal" computation overhead for adapting to the non-stationarity. To this end, we focus on the popular first-order online methods and aim to streamline unnecessary computations while retaining the same regret guarantees. Arguably, the most computationally expensive step of each round is the projection onto the convex feasible domain, namely, the projection operation $\Pi_{\mathcal{X}}[\mathbf{y}] = \arg\min_{\mathbf{x} \in \mathcal{X}} \|\mathbf{x} - \mathbf{y}\|_2$ for a convex set $\mathcal{X} \subseteq \mathbb{R}^d$. Typical two-layer non-stationary online algorithms require maintaining $N = \mathcal{O}(\log T)$ base-learners simultaneously to cover the possibility of unknown environments. Define the *projection complexity* of online methods as the number of projections onto the feasible domain per round. Then, those non-stationary methods suffer an $\mathcal{O}(\log T)$ projection complexity, whereas standard online methods for static regret minimization require only one projection per round such as online gradient descent [Zinkevich, 2003].

1.3 Our Contributions and Techniques

In this paper, we design a generic mechanism to reduce the projection complexity of many existing non-stationary methods from $\mathcal{O}(\log T)$ to 1 *without sacrificing the regret optimality*, hence matching the projection complexity of stationary methods. Our reduction is inspired by the recent advance in parameter-free online learning [Cutkosky and Orabona, 2018; Mhammedi et al., 2019]. The idea is simple: we reduce the original problem learned in the feasible domain $\mathcal{X}$ to an alternative one learned in a *surrogate domain* $\mathcal{Y} \supseteq \mathcal{X}$ such that the projection onto it is much cheaper, e.g., simply choosing $\mathcal{Y}$ as a properly scaled Euclidean ball. Moreover, a carefully designed *surrogate loss* is necessary for the alternative problem to retain the regret optimality. We reveal that as long as the non-stationary online algorithms satisfy the condition of *querying gradient once and evaluating function value once per round*, our reduction mechanism can be deployed in a black-box way to reduce the projection complexity. Several methods for minimax dynamic regret or adaptive regret already satisfy the requirements, so we can immediately deploy the reduction and obtain their efficient counterparts with the same regret guarantees and 1 projection complexity. However, many non-stationary algorithms, particularly those designed for small-loss bounds, do not satisfy the requirement. We thus require non-trivial twists to make them compatible to our reduction. As a consequence, we have developed a series of algorithms achieving minimax/small-loss dynamic regret and adaptive regret with one projection per round (actually, also one gradient query and one function evaluation per round). We further study the interval dynamic regret and obtain the *first* small-loss bound for this stringent measure, which is new to the literature. Again, this is achieved with a 1 projection complexity.

Despite that the reduction mechanism of this paper has been studied in parameter-free online learning, applying it to non-stationary methods requires new ideas and non-trivial twists. Here we highlight the technical innovations. The main challenge comes from the reduction condition mentioned earlier — as the surrogate loss involves the projection operation, our reduction requires the reduced algorithm to query one gradient and evaluate one function value at each round. However, many non-stationary methods do not satisfy the requirement, which is to be contrasted to the parameter-free algorithms such as MetaGrad [van Erven and Koolen, 2016; Mhammedi et al., 2019] that naturally satisfy the condition. For example, the SACS algorithm [Zhang et al., 2019] enjoys the best known small-loss adaptive regret, yet the method requires N gradient queries and $N + 1$ function evaluations at each round, where $N = \mathcal{O}(\log T)$ is the number of base-learners. we have to dig into the algorithm and modify it to fit our reduction. To achieve this purpose, we first replace their meta-algorithm with Adapt-ML-Prod [Gaillard et al., 2014], an expert-tracking algorithm with a *second-order* regret with excess losses to accommodate the linearized loss; second, we introduce a sequence of *time-varying* thresholds to adaptively determine the problem-dependent geometric covers in contrast to a fixed threshold used in their method. As a benefit, our final algorithm only requires one projection/gradient query/function evaluation at each round, substantially improving the efficiency of SACS algorithm that requires N projections/gradient queries/function evaluations per round. Similar techniques are also required when analyzing the interval dynamic regret, and additional twists in the geometric covers and base-algorithm are demanded due to the more complicated structure.

1.4 Assumptions

We list several standard assumptions used in OCO [Zinkevich, 2003; Hazan, 2016]. Notably, not all assumptions are always required. We will explicitly state the requirements in the theorem.

Assumption 1 (bounded gradient). The norm of the gradients of online functions over the domain $\mathcal{X}$ is bounded by G, i.e., $\|\nabla f_t(\mathbf{x})\|_2 \le G$, for all $\mathbf{x} \in \mathcal{X}$ and $t \in [T]$.

Assumption 2 (bounded domain). The domain $\mathcal{X} \subseteq \mathbb{R}^d$ contains the origin $\mathbf{0}$, and the diameter of the domain $\mathcal{X}$ is at most D, i.e., $\|\mathbf{x} - \mathbf{x}'\|_2 \le D$ for any $\mathbf{x}, \mathbf{x}' \in \mathcal{X}$.

Assumption 3 (non-negativity and smoothness). All the online functions are non-negative and L-smooth, i.e., for any $\mathbf{x}, \mathbf{x}' \in \mathcal{X}$ and $t \in [T]$, $\|\nabla f_t(\mathbf{x}) - \nabla f_t(\mathbf{x}')\|_2 \le L\|\mathbf{x} - \mathbf{x}'\|_2$.

Organization. The rest is structured as follows. Section 2 presents the reduction mechanism and illustrates its application to dynamic regret minimization. Section 3 contains efficient methods for optimizing adaptive regret and interval dynamic regret. Section 4 concludes the paper and makes several discussions. Due to page limits, we present the experiments in Appendix A. All the proofs and omitted details for algorithms are deferred to the remaining appendices.

2 The Reduction Mechanism and Dynamic Regret Minimization

We start with developing efficient methods for dynamic regret minimization, which is conceptually easier than optimizing the adaptive regret in our purpose. Below, we first briefly review existing methods for dynamic regret in Section 2.1, and then present our reduction mechanism and illustrate how to apply it to reducing the projection complexity of dynamic regret methods in Section 2.2.

2.1 A Brief Review of Dynamic Regret Minimization

Zhang et al. [2018a] propose a two-layer online algorithm called Ader with an $\mathcal{O}(\sqrt{T(1+P_T)})$ dynamic regret, which is proven to be minimax optimal for convex functions. Ader maintains a group of base-learners, each performing online gradient descent (OGD) [Zinkevich, 2003] with a customized step size specified by the pool $\mathcal{H} = \{\eta_1, \ldots, \eta_N\}$, and then uses a meta-algorithm to combine them all. Denoted by $\mathcal{B}_1, \ldots, \mathcal{B}_N$ the N base-learners. For each $i \in [N]$, $\mathcal{B}_i$ updates by

$$\mathbf{x}_{t+1,i} = \Pi_{\mathcal{X}}[\mathbf{x}_{t,i} - \eta_i \nabla f_t(\mathbf{x}_t)], \tag{3}$$

where $\eta_i \in \mathcal{H}$ is the associated step size and $\Pi_{\mathcal{X}}[\cdot]$ denotes the projection onto the feasible domain $\mathcal{X}$ with $\Pi_{\mathcal{X}}[\mathbf{y}] = \arg\min_{\mathbf{x} \in \mathcal{X}} \|\mathbf{y} - \mathbf{x}\|_2$. Notably, all the base-learners share the same gradient $\nabla f_t(\mathbf{x}_t)$ rather than using their individual one $\nabla f_t(\mathbf{x}_{t,i})$. This is because Ader optimizes the linearized loss $\ell_t(\mathbf{x}) = \langle \nabla f_t(\mathbf{x}_t), \mathbf{x} \rangle$, which enjoys the benign property of $\nabla \ell_t(\mathbf{x}_{t,i}) = \nabla f_t(\mathbf{x}_t)$ for all $i \in [N]$.

Furthermore, the meta-algorithm evaluates each base-learner by $\ell_t(\mathbf{x}_{t,i}) = \langle \nabla f_t(\mathbf{x}_t), \mathbf{x}_{t,i} \rangle$ and updates the weight vector $\boldsymbol{p}_{t+1} \in \Delta_N$ by the Hedge algorithm [Freund and Schapire, 1997], namely,

$$p_{t+1,i} = \frac{p_{t,i} \exp(-\varepsilon \langle \nabla f_t(\mathbf{x}_t), \mathbf{x}_{t,i} \rangle)}{\sum_{j=1}^{N} p_{t,j} \exp(-\varepsilon \langle \nabla f_t(\mathbf{x}_t), \mathbf{x}_{t,j} \rangle)}, \quad \forall i \in [N], \tag{4}$$

where $\varepsilon > 0$ is the learning rate of the meta-algorithm. The final prediction is obtained by $\mathbf{x}_{t+1} = \sum_{i=1}^{N} p_{t+1,i} \mathbf{x}_{t+1,i}$. The learner submits the prediction $\mathbf{x}_{t+1}$ and then receives the loss $f_{t+1}(\mathbf{x}_{t+1})$ and the gradient $\nabla f_{t+1}(\mathbf{x}_{t+1})$ as the feedback of this round. Under a suitable configuration of the step size pool $\mathcal{H}$ with $N = \mathcal{O}(\log T)$ and learning rate $\varepsilon = \Theta(\sqrt{(\ln N)/T})$, Ader enjoys an $\mathcal{O}(\sqrt{T(1+P_T)})$ dynamic regret [Zhang et al., 2018a, Theorem 4].

For convex and smooth functions, Zhao et al. [2021] demonstrate that a similar two-layer structure can attain an $\mathcal{O}(\sqrt{(F_T + P_T)(1+P_T)})$ small-loss dynamic regret under a suitable setting of the step size pool $\mathcal{H}$ and time-varying learning rates of meta-algorithm $\{\varepsilon_t\}_{t=1}^{T}$, where $F_T = \sum_{t=1}^{T} f_t(\mathbf{u}_t)$ is the cumulative loss of the comparators. This bound safeguards the minimax rate in the worst case, while can be much smaller in benign environments.

2.2 The Reduction Mechanism for Reducing Projection Complexity

As demonstrated in the update (3), all the base-learners require projecting the intermediate solution onto the domain $\mathcal{X}$ to ensure the feasibility. As a result, $\mathcal{O}(\log T)$ projections are required at each round, which is generally time-consuming particularly when the domain $\mathcal{X}$ is complicated.

We present a generic reduction mechanism for reducing the projection complexity and apply it to dynamic regret methods. Our reduction builds upon the seminal work [Cutkosky and Orabona, 2018] and a further refined result [Cutkosky, 2020], who propose a black-box reduction from constrained online learning to the unconstrained setting (or another constrained problem with a larger domain) .

Reduction mechanism. Given an algorithm for non-stationary online learning Algo whose projection complexity is $\mathcal{O}(\log T)$, our reduction mechanism builds on it to yield an algorithm Efficient-Algo with 1 projection onto $\mathcal{X}$ per round and retaining the same order of regret. The central idea is to replace expensive projections onto the original domain $\mathcal{X}$ with other much cheaper projections. To this end, we introduce a *surrogate domain* $\mathcal{Y}$ defined as the minimum Euclidean ball containing the feasible domain $\mathcal{X}$, i.e., $\mathcal{Y} = \{\mathbf{x} \mid \|\mathbf{x}\|_2 \leq D/2\} \supseteq \mathcal{X}$. Then, the reduced algorithm Algo works on $\mathcal{Y}$ whose projection can be realized by a simple rescaling. More importantly, to avoid regret degeneration, it is necessary to carefully construct the surrogate loss $g_t : \mathcal{Y} \mapsto \mathbb{R}$ as

$$g_t(\mathbf{y}) = \langle \nabla f_t(\mathbf{x}_t), \mathbf{y} \rangle - \mathbb{1}_{\{\langle \nabla f_t(\mathbf{x}_t), \mathbf{v}_t \rangle < 0\}} \cdot \langle \nabla f_t(\mathbf{x}_t), \mathbf{v}_t \rangle \cdot S_{\mathcal{X}}(\mathbf{y}), \tag{5}$$

Algorithm 1 Efficient Algorithm for Minimizing Dynamic Regret

---

Input: step size pool $\mathcal{H} = \{\eta_1, \ldots, \eta_N\}$, learning rate of meta-algorithm ε_t (or simply a fixed ε).

1: Initialization: let $\mathbf{x}_1$ and $\{\mathbf{y}_{1,i}\}_{i=1}^N$ be any point in $\mathcal{X}$; $\forall i \in [N], p_{1,i} = 1/N$.

2: **for** $t = 1$ **to** T **do**

3:     Receive the gradient information $\nabla f_t(\mathbf{x}_t)$.

4:     Construct the surrogate loss $g_t : \mathcal{Y} \mapsto \mathbb{R}$ according to Eq. (5).

5:     Compute the gradient $\nabla g_t(\mathbf{y}_t)$ according to Lemma 1.

6:     For each $i \in [N]$, the base-learner $\mathcal{B}_i$ produces the local decision by

$$\widehat{\mathbf{y}}_{t+1,i} = \mathbf{y}_{t,i} - \eta_i \nabla g_t(\mathbf{y}_t), \ \ \mathbf{y}_{t+1,i} = \widehat{\mathbf{y}}_{t+1,i}\Big(\mathbb{1}_{\{\|\widehat{\mathbf{y}}_{t+1,i}\|_2 \leq \frac{D}{2}\}} + \frac{D}{2\|\widehat{\mathbf{y}}_{t+1,i}\|_2} \cdot \mathbb{1}_{\{\|\widehat{\mathbf{y}}_{t+1,i}\|_2 \geq \frac{D}{2}\}}\Big).$$

7:     Meta-algorithm updates weight by $p_{t+1,i} \propto \exp(-\varepsilon_{t+1} \sum_{s=1}^t \langle \nabla g_s(\mathbf{y}_s), \mathbf{y}_{s,i} \rangle), i \in [N]$.

8:     Compute $\mathbf{y}_{t+1} = \sum_{i=1}^N p_{t+1,i} \mathbf{y}_{t+1,i}$.

9:     Submit $\mathbf{x}_{t+1} = \Pi_{\mathcal{X}}[\mathbf{y}_{t+1}]$. $\triangleright$ The only step projects onto feasible domain $\mathcal{X}$ per round.

10: **end for**

---

where $S_{\mathcal{X}}(\mathbf{y}) = \inf_{\mathbf{x} \in \mathcal{X}} \|\mathbf{y} - \mathbf{x}\|_2$ is the distance function to $\mathcal{X}$ and $\mathbf{v}_t = {(\mathbf{y}_t - \mathbf{x}_t)}/{\|\mathbf{y}_t - \mathbf{x}_t\|_2}$ is the vector indicating the projection direction.

The main protocol of our reduction is presented as follows. The input includes original functions $\{f_t\}_{t=1}^T$, the feasible domain $\mathcal{X}$, and the reduced algorithm Algo.

1: **for** $t = 1, \ldots, T$ **do**

2:     receive the gradient information $\nabla f_t(\mathbf{x}_t)$;

3:     construct the surrogate loss $g_t : \mathcal{Y} \mapsto \mathbb{R}$ according to Eq. (5);

4:     obtain the intermediate prediction $\mathbf{y}_{t+1} \leftarrow \mathsf{Algo}(g_t(\cdot), \mathbf{y}_t, \mathcal{Y})$;

5:     submit the final prediction $\mathbf{x}_{t+1} = \Pi_{\mathcal{X}}[\mathbf{y}_{t+1}]$;

6: **end for**

Our reduction enjoys the regret safeness due to the following benign properties of surrogate loss.

Theorem 1 (Theorem 2 of Cutkosky [2020]). *The surrogate loss $g_t : \mathcal{Y} \mapsto \mathbb{R}$ defined in (5) is convex. Then, we have $\|\nabla g_t(\mathbf{y}_t)\|_2 \leq \|\nabla f_t(\mathbf{x}_t)\|_2$ and for any $\mathbf{u}_t \in \mathcal{X}$*

$$\langle \nabla f_t(\mathbf{x}_t), \mathbf{x}_t - \mathbf{u}_t \rangle \leq g_t(\mathbf{y}_t) - g_t(\mathbf{u}_t) \leq \langle \nabla g_t(\mathbf{y}_t), \mathbf{y}_t - \mathbf{u}_t \rangle. \tag{6}$$

The theorem shows the convexity of the surrogate loss $g_t(\mathbf{y})$ and we thus have $f_t(\mathbf{x}_t) - f_t(\mathbf{u}_t) \leq \langle \nabla g_t(\mathbf{y}_t), \mathbf{y}_t - \mathbf{u}_t \rangle$, which implies that it suffices to optimize the linearized upper bound, i.e., to optimize function $\ell_t(\mathbf{y}) = \langle \nabla g_t(\mathbf{y}_t), \mathbf{y} \rangle$. The following lemma specifies the gradient calculation.

Lemma 1. *For any $\mathbf{y} \in \mathcal{Y}, \nabla g_t(\mathbf{y}) = \nabla f_t(\mathbf{x}_t)$ when $\langle \nabla f_t(\mathbf{x}_t), \mathbf{v}_t \rangle \geq 0$; and $\nabla g_t(\mathbf{y}) = \nabla f_t(\mathbf{x}_t) - \langle \nabla f_t(\mathbf{x}_t), \mathbf{v}_t \rangle \cdot (\mathbf{y} - \Pi_{\mathcal{X}}[\mathbf{y}])/\|\mathbf{y} - \Pi_{\mathcal{X}}[\mathbf{y}]\|_2$ when $\langle \nabla f_t(\mathbf{x}_t), \mathbf{v}_t \rangle < 0$. Here $\mathbf{v}_t = (\mathbf{y}_t - \mathbf{x}_t)/\|\mathbf{y}_t - \mathbf{x}_t\|_2$. In particular, $\nabla g_t(\mathbf{y}_t) = \nabla f_t(\mathbf{x}_t) - \langle \nabla f_t(\mathbf{x}_t), \mathbf{v}_t \rangle \cdot \mathbf{v}_t$ when $\langle \nabla f_t(\mathbf{x}_t), \mathbf{v}_t \rangle < 0$.*

Reduction requirements. An important condition for the reduction is to require the reduced algorithm satisfying *one gradient query* and *one function evaluation* at each round. Indeed, the reduction essentially updates according to the surrogate loss $\{g_t\}_{t=1}^T$. Note that the definition of surrogate loss involves the distance function $S_{\mathcal{X}}(\mathbf{y})$, see Eq. (5). Thus, each evaluation of $g_t(\mathbf{y})$ leads to one projection onto $\mathcal{X}$ due to the calculation of $S_{\mathcal{X}}(\mathbf{y})$. Similarly, each gradient query of $\nabla g_t(\mathbf{y})$ also contributes to one projection, see Lemma 1 for details. To summarize, we can use the reduction to ensure a 1 projection complexity, provided that the reduced algorithm satisfies the requirements of one gradient query and one function evaluation per round. Below, we demonstrate the usage of our reduction mechanism for two methods of dynamic regret minimization that satisfy the conditions, including the minimax method [Zhang et al., 2018a] and the small-loss method [Zhao et al., 2021].

Application to dynamic regret minimization. Algorithm 1 summarizes the main procedures of our efficient methods for optimizing dynamic regret, which is an instance of the reduction mechanism by picking Algo as Ader [Zhang et al., 2018a]. More specifically, Lines 6 – 8 are essentially performing Ader algorithm using the surrogate loss $\{g_t\}_{t=1}^T$ over the surrogate domain $\mathcal{Y}$. Note that the base update in Line 6 is essentially performing OGD with projection onto $\mathcal{Y}$, a scaled Euclidean ball, and thus the projection admits a simple closed form. The overall algorithm requires projecting onto $\mathcal{X}$ only once per round, see Line 9. Our method provably retains the same minimax dynamic regret.

Theorem 2. *Under Assumptions 1 and 2, setting the step size pool as $\mathcal{H} = \big\{ \eta_i = 2^{i-1}(D/G)\sqrt{7/T} \mid i \in [N] \big\}$ with $N = \lceil 2^{-1}\log_2(1 + 4T/7) \rceil + 1$ and the learning rate as $\varepsilon = \sqrt{(\ln N)/(1 + G^2 D^2 T)}$, our algorithm requires one projection onto $\mathcal{X}$ per round and enjoys*

$$\sum_{t=1}^{T} f_t(\mathbf{x}_t) - \sum_{t=1}^{T} f_t(\mathbf{u}_t) \leq \mathcal{O}\big(\sqrt{T(1 + P_T)}\big). \tag{7}$$

For smooth and non-negative functions, the Sword algorithm [Zhao et al., 2021] achieves an $\mathcal{O}(\sqrt{(F_T + P_T)(1 + P_T)})$ small-loss dynamic regret, which requires one gradient and one function value per iteration. However, notice that the surrogate loss $g_t(\cdot)$ in Eq. (5) is neither smooth nor non-negative, which hinders the application of our reduction to their method. Fortunately, owing to the benign property of $\|\nabla g_t(\mathbf{y}_t)\|_2 \leq \|\nabla f_t(\mathbf{x}_t)\|_2$ (see Theorem 1), we can still deploy the reduction via an improved analysis and finally obtain an efficient algorithm with the same small-loss bound.

Theorem 3. *Under Assumptions 1, 2, and 3), setting $\mathcal{H} = \big\{ \eta_i = 2^{i-2}\sqrt{7D/(LGT)} \mid i \in [N] \big\}$ with $N = \lceil 2^{-1}\log_2(GT/(7DL)) \rceil + 1$ and $\varepsilon_t = \sqrt{(\ln N)/(1 + D^2 \sum_{s=1}^{t-1} \|\nabla g_s(\mathbf{y}_s)\|_2^2)}$, our algorithm requires one projection onto $\mathcal{X}$ per round and enjoys the following small-loss type dynamic regret:*

$$\sum_{t=1}^{T} f_t(\mathbf{x}_t) - \sum_{t=1}^{T} f_t(\mathbf{u}_t) \leq \mathcal{O}\big(\sqrt{(F_T + P_T)(1 + P_T)}\big), \tag{8}$$

where $F_T = \sum_{t=1}^{T} f_t(\mathbf{u}_t)$ is the cumulative loss of the comparators.

3 Minimizing Adaptive Regret and Interval Dynamic Regret

In this section, we present our efficient methods to minimize adaptive regret. Based on the result, we further sketch our results for interval dynamic regret, where the *first* small-loss bound is provided.

3.1 Efficient Methods for Adaptive Regret

Adaptive regret ensures the online learner to be competitive with a fixed decision over every contiguous interval. For the minimax bound, the best known adaptive regret is the $\mathcal{O}(\sqrt{|I| \log T})$ achieved by the CBCE algorithm [Jun et al., 2017]. CBCE algorithm requires multiple gradients at each round. Wang et al. [2018] improve CBCE by using the linearized loss to make the algorithm requiring one gradient per iteration and retaining the same adaptive regret. Moreover, the improved CBCE algorithm only evaluates the function value once per iteration. Therefore, we can directly apply our reduction to the improved CBCE and obtain an efficient version with the same adaptive regret guarantee and meanwhile enjoys 1 projection complexity. More details can be found in Appendix D.1.

In the following, we focus on the more challenging case of small-loss bounds. In the literature, the best result is the $\mathcal{O}(\sqrt{F_I \log F_I \log F_T})$ bound for any interval $I = [r, s] \subseteq [T]$ obtained by the SACS algorithm [Zhang et al., 2019], where $F_I = \min_{\mathbf{x} \in \mathcal{X}} \sum_{t=r}^{s} f_t(\mathbf{x})$ and $F_T = \min_{\mathbf{x} \in \mathcal{X}} \sum_{t=1}^{T} f_t(\mathbf{x})$. However, SACS does not satisfy our reduction requirements, because it requires N gradient queries (i.e., $\nabla f_t(\mathbf{x}_{t,i})$ for $i \in [N]$) and $N + 1$ function evaluations (i.e., $f_t(\mathbf{x}_{t,i})$ for $i \in [N]$, and $f_t(\mathbf{x}_t)$) at round $t \in [T]$, where N denotes the number of active base-learners and $\mathbf{x}_{t,i}$ denotes local decision returned by the i-th base-learner. To address the difficulty, we have to modify the algorithm to fit our propose. In the following, we first sketch the SACS algorithm and then present our modifications.

To optimize the adaptive regret, an online algorithm usually consists of the three components:

   (i) base-algorithm: an online algorithm that can attain low (static) regret in a given interval;

  (ii) scheduling: a set of intervals and each one is associated with a base-learner who aims to minimize the static regret over the interval;

 (iii) meta-algorithm: an online aggregation algorithm that can track the best base-learner.

We briefly describe specific configurations of the SACS algorithm. First, SACS uses scale-free online gradient descent (SOGD) [Orabona and Pál, 2018] as the base-algorithm, which ensures a small-loss

regin in a given interval. Second, SACS employs AdaNormalHedge [Luo and Schapire, 2015] as the meta-algorithm, which supports the sleeping expert setup and also enjoys a small-loss regret. Finally, SACS designs a clever strategy of *problem-dependent* geometric covers to determine the set of intervals such that the number of active base-learners also depends on the small-loss quantity. As a benefit, the SACS algorithm can achieve a fully problem-dependent adaptive regret of order $\mathcal{O}(\sqrt{F_I \log F_I \log F_T})$, scaling with the cumulative loss of comparators.

Multiple gradient queries and function evaluations are involved in all the three components of SACS, and thus, plenty of twists are necessary to achieve an adaptive algorithm with small-loss adaptive regret yet requiring only gradient query and function evaluation per round. With such an algorithm on hand, we can then deploy our reduction to achieve an efficient method with 1 projection complexity. In the following, we present the details. By the reduction mechanism, it is noticeable that we only need to consider the input online functions as surrogate loss $\{g_t\}_{t=1}^T$, where g_t is defined in Eq. (5).

Base-algorithm. We use SOGD with a *linearized* surrogate loss $\langle \nabla g_t(\mathbf{y}_t), \mathbf{y} \rangle$ over the surrogate domain $\mathcal{Y}$. Denote by A_t the set of active base-learners' indices, then the base-learner $\mathcal{B}_i$ updates by

$$\mathbf{y}_{t+1,i} = \Pi_{\mathcal{Y}}[\mathbf{y}_{t,i} - \eta_{t,i} \nabla g_t(\mathbf{y}_t)], \tag{9}$$

with $\eta_{t,i} = \sqrt{D/(\delta + \sum_{s=\tau_i}^t \|\nabla g_s(\mathbf{y}_s)\|_2^2)}$, where τ_i denotes the starting time of the base-learner $i \in A_t$. The projection onto $\mathcal{Y}$ can be easily calculated by a simple rescaling if needed. Notably, owing to the convexity of the surrogate loss g_t, we can use the *same* gradient $\nabla g_t(\mathbf{y}_t)$ for all the base-learners at each round, ensuring one gradient query of $\nabla f_t(\mathbf{x}_t)$ at each round.

Geometric Covers. The covers consist of a set of intervals that specify the alive time of base-learners. To achieve a small-loss adaptive regret, SACS [Zhang et al., 2019] employs a clever covering construction called problem-dependent geometric covers (PGC) — instead of initiating a base-learner at each round t like earlier algorithms [Daniely et al., 2015; Jun et al., 2017], SACS adds a new base-learner only when the cumulative loss exceeds a pre-defined *threshold*. As a result, the number of active base-learners relates to the small-loss quantity such that the overall algorithm achieves a fully problem-dependent adaptive regret. Notably, to determine the threshold, SACS monitors the cumulative loss of the latest base-learner $f_t(\mathbf{x}_{t,i^\dagger})$ with $i^\dagger$ being the latest base-learner's index. However, this requires an additional function evaluation beyond $f_t(\mathbf{x}_t)$ at each round.

To avoid the limitation, instead of a fixed threshold, we design a a sequence of *time-varying thresholds* to adaptively decide the initiations of base-learners, bypassing the requirement of additional function evaluation. This realizes the condition of one function evaluation per round. Denote by $C_1, C_2, C_3, \ldots$ the sequence of thresholds. The thresholds will be determined by a threshold generating function $\mathcal{G}(\cdot) : \mathbb{N} \mapsto \mathbb{R}_+$, which will be specified later. Our problem-dependent geometric covers are set as follows. We initialize the setting by $s_1 = 1$. We set s_2 as the round when the cumulative loss of the overall algorithm (namely, $\sum_{s=1}^t f_s(\mathbf{x}_s)$) exceeds the threshold C_1 and then initialize a new instance of SOGD starting at this round. The process is repeated until the end of online game. We thus generate a sequence of points $s_1, s_2, \ldots$, referred to as the *markers*. See the condition in Line 7 and update procedures in Lines 8 – 10 of Algorithm 2. Our constructed PGC thus becomes

$$\widetilde{\mathcal{C}} = \bigcup_{k \in \mathbb{N} \cup \{0\}} \widetilde{\mathcal{C}}_k, \text{ where } \widetilde{\mathcal{C}}_k = \left\{ [s_{i \cdot 2^k}, s_{(i+1) \cdot 2^k}] \mid i \text{ is odd} \right\} \text{ for all } k \in \mathbb{N} \cup \{0\}. \tag{10}$$

Meta-algorithm. SACS uses the AdaNormalHedge [Luo and Schapire, 2015] as the meta-algorithm, however, this is not suitable for our propose. To ensure one projection per iteration, we cannot use multiple function values, i.e., $\{g_t(\mathbf{y}_{t,i})\}_{i=1}^N$, for meta-algorithm to evaluate the loss. Instead, we can only use the *linearized* loss value, namely, $\{\langle \nabla g_t(\mathbf{y}_t), \mathbf{y}_{t,i} \rangle\}_{i=1}^N$ in the weight update of meta-algorithm. The small-loss regret bound in the meta-algorithm of SACS crucially relies on the original function values, which is unfortunately inaccessible in our case. Technically, when fed with linearized loss, it is hard to establish a *squared* gradient-norm bound and then convert it to the small loss due to the *first-order* regret bound of AdaNormalHedge. Based on this crucial technical observation, we propose to use the Adapt-ML-Prod algorithm [Gaillard et al., 2014] as the meta-algorithm in our method. The key advantage is that it enjoys a *second-order* regret and also supports the sleeping expert setup. Adapt-ML-Prod maintains multiple learning rates $\boldsymbol{\eta}_{t+1}$ and an intermediate weight vector $\mathbf{w}_{t+1}$, which update by the following rule. For any active base-learner $i \in A_{t+1}$,

$$\eta_{t+1,i} = \min\left\{ \frac{1}{2}, \sqrt{\frac{\gamma_i}{1 + \sum_{k=s_i}^t (\widehat{\ell}_k - \ell_{k,i})^2}} \right\}, w_{t+1,i} = \left(w_{t,i} \left(1 + \eta_{t,i}(\widehat{\ell}_t - \ell_{t,i}) \right) \right)^{\frac{\eta_{t+1,i}}{\eta_{t,i}}}, \tag{11}$$

Algorithm 2 Efficient Algorithm for Problem-dependent Adaptive Regret

---

Input: threshold generating function $\mathcal{G}(\cdot) : \mathbb{N} \mapsto \mathbb{R}_+$.

1: Initialization: total intervals $m = 1$, threshold $C_1 = \mathcal{G}(1)$; let $\mathbf{x}_1$ be any point in $\mathcal{X}$.
2: **for** $t = 1$ **to** T **do**
3:     Receive the gradient information $\nabla f_t(\mathbf{x}_t)$.
4:     Construct the surrogate loss $g_t : \mathcal{Y} \mapsto \mathbb{R}$ according to Eq. (5).
5:     Compute the (sub-)gradient $\nabla g_t(\mathbf{y}_t)$ according to Lemma 1.
6:     Compute $L_t = L_{t-1} + f_t(\mathbf{x}_t)$
7:     **if** $L_t > C_m$ **then**
8:         Set $L_t = 0$, remove base-learners $\mathcal{B}_k$ whose ending point $e_k = m + 1$.
9:         Set $m \leftarrow m + 1$, $C_m = \mathcal{G}(m)$.
10:       Initialize a new base-learner with ending point $e_m = j$ satisfying $[m, j - 1] \in \mathcal{C}$, where $\mathcal{C} = \bigcup_{k \in \mathbb{N} \cup \{0\}} \mathcal{C}_k$ and $\mathcal{C}_k = \{[i \cdot 2^k, (i+1) \cdot 2^k] \mid i \text{ is odd}\}$ for all $k \in \mathbb{N} \cup \{0\}$.
11:       Set $\gamma_m = \ln(1 + 2m)$, $w_{t,m} = 1$, $\eta_{t,m} = \min\{1/2, \sqrt{\gamma_m}\}$ for the meta-algorithm.
12:     **end if**
13:     Send $\nabla g_t(\mathbf{y}_t)$ to all base-learners and obtain local predictions $\mathbf{y}_{t+1,i}$ for $i \in A_t$.
14:     Meta-algorithm updates weight $\boldsymbol{p}_{t+1} \in \Delta_{|A_{t+1}|}$ according to Eq. (11), Eq. (12), and Eq. (13)
15:     Compute $\mathbf{y}_{t+1} = \sum_{i \in A_{t+1}} p_{t+1,i} \mathbf{y}_{t+1,i}$.
16:     Submit $\mathbf{x}_{t+1} = \Pi_{\mathcal{X}}[\mathbf{y}_{t+1}]$.   ▷ The only projection onto feasible domain $\mathcal{X}$ per round.
17: **end for**

---

where $\gamma_i = \ln(1 + 2i)$ is a certain scaling factor and the feedback loss is constructed as for $i \in A_t$

$$\widehat{\ell}_t = \langle \nabla g_t(\mathbf{y}_t), \mathbf{y}_t \rangle / (2GD), \text{ and } \ell_{t,i} = \langle \nabla g_t(\mathbf{y}_t), \mathbf{y}_{t,i} \rangle / (2GD). \tag{12}$$

The final weight vector $\boldsymbol{p}_{t+1} \in \Delta_{|A_{t+1}|}$ is obtained by

$$p_{t+1,i} = \frac{w_{t+1,i} \cdot \eta_{t+1,i}}{\sum_{j \in A_{t+1}} w_{t+1,j} \cdot \eta_{t+1,j}}. \tag{13}$$

Notably, the meta update only uses one gradient at round t, namely, $\nabla g_t(\mathbf{y}_t)$.

Finally, we compute $\mathbf{y}_{t+1} = \sum_{i \in A_{t+1}} p_{t+1,i} \mathbf{y}_{t+1,i}$ as the overall prediction in the surrogate domain $\mathcal{Y}$ and calculate $\mathbf{x}_{t+1} = \Pi_{\mathcal{X}}[\mathbf{y}_{t+1}]$ to ensure the feasibility. This is the only projection onto $\mathcal{X}$ at each round. Algorithm 2 summarizes the main procedures of our efficient methods for small-loss adaptive regret. Albeit with a similar two-layer structure as SACS, our algorithm exhibits salient differences in base-algorithm, meta-algorithm, and geometric covers. As a benefit, we can successfully deploy our reduction mechanism and make the overall algorithm project onto the feasible domain $\mathcal{X}$ once per round, see Line 16. Our method retains the same small-loss adaptive regret as [Zhang et al., 2019].

Theorem 4. *Under Assumptions 1–3, setting the threshold generating function $\mathcal{G}(m) = \Theta(\log m)$ whose explicit form is in Eq. (34) of Appendix D, Algorithm 2 requires only one projection onto $\mathcal{X}$ per round and enjoys the small-loss adaptive regret:*

$$\sum_{t=r}^{s} f_t(\mathbf{x}_t) - \sum_{t=r}^{s} f_t(\mathbf{u}) \le \mathcal{O}\Big(\min \big\{ \sqrt{F_I \log F_I \log F_T}, \sqrt{|I| \log T} \big\} \Big) \tag{14}$$

for any interval $I = [r, s] \subseteq [T]$, where $F_I = \min_{\mathbf{x} \in \mathcal{X}} \sum_{t=r}^{s} f_t(\mathbf{x})$ and $F_T = \min_{\mathbf{x} \in \mathcal{X}} \sum_{t=1}^{T} f_t(\mathbf{x})$.

Remark 1. Note that the $\mathcal{O}(\sqrt{F_I \log F_I \log F_T})$ small-loss bound of Zhang et al. [2019] becomes $\mathcal{O}(\sqrt{|I| \log |I| \log T})$ in the worst case, looser than the $\mathcal{O}(\sqrt{|I| \log T})$ minimax bound [Jun et al., 2017] by a factor of $\log |I|$. We show that this limitation can be actually avoided by a refined analysis. Indeed, our result in (14) can *strictly* match the best minimax result in the worst case.

3.2 Efficient Methods for Interval Dynamic Regret

As mentioned in Section 1.1, adaptive regret and dynamic regret are generally incomparable for OCO. So researchers consider optimizing them simultaneously via a more stringent measure that competes with *any* changing comparator sequence over *any* interval [Zhang et al., 2020; Cutkosky, 2020].

Zhang et al. [2020] propose the AOA algorithm to optimize the interval dynamic regret and obtain a minimax bound of $\sum_{t=r}^{s} f_t(\mathbf{x}_t) - \sum_{t=r}^{s} f_t(\mathbf{u}_t) \leq \mathcal{O}(\sqrt{|I|(\log T + P_I)})$ for any interval $I = [r, s] \subseteq [T]$, where $P_I = \sum_{t=r+1}^{s} \|\mathbf{u}_t - \mathbf{u}_{t-1}\|_2$ denotes the path-length. The overall structure of AOA is similar to SACS [Zhang et al., 2019] described in Section 3.1, and the major difference is that AOA now employs Ader [Zhang et al., 2018a] rather than SOGD as the base-algorithm to minimize dynamic regret in a given interval. So the projection complexity of their method is $\mathcal{O}(\log^2 T)$ as each base-learner now also consists of two layers. Although AOA itself does not satisfy the condition of one gradient query and one function evaluation per round, it can be verified that simply using a linearized loss for AOA can achieve the same bound and also satisfy the reduction requirement. Thus, deploying the reduction mechanism yields an efficient algorithm that enjoys the same minimax bound and improves the projection complexity from $\mathcal{O}(\log^2 T)$ to 1. See Appendix E.1 for details.[1]

To the best of our knowledge, there is no small-loss type bound for the interval dynamic regret. We present the *first* such result for convex and smooth functions, and our algorithm ensures a 1 projection complexity. To achieve this, we employ the same structure of AOA, whereas we now use linearized loss for base-learners and use Adapt-ML-Prod as the meta-algorithm and additional efforts are required in constructing the problem-dependent geometric covers. The following theorem presents the regret guarantee. The algorithmic details and proofs are deferred to Appendix E.

Theorem 5. *Under Assumptions 1–3, setting the threshold generating function $\mathcal{G}(m) = \Theta(\log m)$ whose explicit form is in Eq. (42) of Appendix E, our algorithm (Algorithm 3 in Appendix E) requires only one projection onto $\mathcal{X}$ per round and enjoys the following small-loss interval dynamic regret:*

$$\sum_{t=r}^{s} f_t(\mathbf{x}_t) - \sum_{t=r}^{s} f_t(\mathbf{u}_t) \leq \mathcal{O}\left(\sqrt{(F_I + P_I) \cdot \left(P_I + \log(F_I + P_I) \cdot \log(F_T + P_T)\right)}\right) \quad (15)$$

for any interval $I = [r, s] \subseteq [T]$, where $P_I = \sum_{t=r+1}^{s} \|\mathbf{u}_t - \mathbf{u}_{t-1}\|_2$ denotes the path-length of comparators within the interval, $F_I = \min_{\mathbf{x} \in \mathcal{X}} \sum_{t=r}^{s} f_t(\mathbf{x})$ and $F_T = \min_{\mathbf{x} \in \mathcal{X}} \sum_{t=1}^{T} f_t(\mathbf{x})$.

When competing with a fixed comparator, the path-length $P_I = 0$ and interval dynamic regret (15) becomes $\mathcal{O}(\sqrt{F_I \log F_I \log F_T})$, recovering the small-loss adaptive regret exhibits in Theorem 4.

4 Conclusion

In this paper, we design a generic reduction mechanism that can reduce the projection complexity of two-layer methods for non-stationary online learning, hence approaching a clearer resolution of necessary computational overhead for robustness to non-stationarity. Building on the reduction mechanism, we develop a series of online methods for optimizing dynamic regret, adaptive regret, and interval dynamic regret. All the methods retain the best known regret guarantees, and more importantly, require one projection onto the feasible domain per iteration. It is worth mentioning that, due to the requirement of our reduction, all our methods only need one gradient query and one function evaluation at each round as well, which can be attractive in situations with limited feedback.

Our reduction can also be applied to other settings to achieve light project complexity, for example, dynamic regret of OCO with memory [Zhao et al., 2022], OCO with switching cost [Zhang et al., 2021], and related applications to online non-stochastic control [Hazan et al., 2020]. There is one important open question left on another type of problem-dependent bound that scales with gradient variation [Chiang et al., 2012], which plays an important role in establishing fast convergence in zero-sum games [Syrgkanis et al., 2015; Zhang et al., 2022]. Although Zhao et al. [2021] have devised a two-layer method that enjoys a gradient-variation dynamic regret and requires one gradient per iteration, it is quite challenging to incorporate the optimistic online learning into our reduction mechanism due to the constrained feasible domain and the complicated two-layer structure. In addition, this paper currently focuses on the convex functions and smooth functions, and it is interesting to investigate whether our reduction is applicable to other interesting function families such as exp-concave and strongly convex functions, which is left as the future work.

---

[1]Cutkosky [2020] employs a fundamentally different framework from the two-layer structure, who obtains an interval dynamic regret scaling with gradient norms. In Appendix E, we show that our two-layer method can achieve exactly the *same* gradient-norm bound (without smoothness). Moreover, their method requires at least $\mathcal{O}(\log T)$ projections onto feasible domain (or onto an even more complicated lifted domain) per round, and it is unclear how to reduce the projection complexity by our reduction due to a saliently different framework.

References

P. Auer, N. Cesa-Bianchi, and C. Gentile. Adaptive and self-confident on-line learning algorithms. *Journal of Computer and System Sciences*, 64(1):48–75, 2002.

D. Baby and Y.-X. Wang. Optimal dynamic regret in exp-concave online learning. In *Proceedings of the 34th Conference on Learning Theory (COLT)*, pages 359–409, 2021.

C.-K. Chiang, T. Yang, C.-J. Lee, M. Mahdavi, C.-J. Lu, R. Jin, and S. Zhu. Online optimization with gradual variations. In *Proceedings of the 25th Conference On Learning Theory (COLT)*, pages 6.1–6.20, 2012.

A. Cutkosky. Parameter-free, dynamic, and strongly-adaptive online learning. In *Proceedings of the 37th International Conference on Machine Learning (ICML)*, pages 2250–2259, 2020.

A. Cutkosky and F. Orabona. Black-box reductions for parameter-free online learning in banach spaces. In *Proceedings of the 31st Conference on Learning Theory (COLT)*, pages 1493–1529, 2018.

A. Daniely, A. Gonen, and S. Shalev-Shwartz. Strongly adaptive online learning. In *Proceedings of the 32nd International Conference on Machine Learning (ICML)*, pages 1405–1411, 2015.

Y. Freund and R. E. Schapire. A decision-theoretic generalization of on-line learning and an application to boosting. *Journal of Computer and System Sciences*, 55(1):119–139, 1997.

P. Gaillard, G. Stoltz, and T. van Erven. A second-order bound with excess losses. In *Proceedings of the 27th Conference on Learning Theory (COLT)*, pages 176–196, 2014.

E. C. Hall and R. Willett. Dynamical models and tracking regret in online convex programming. In *Proceedings of the 30th International Conference on Machine Learning (ICML)*, pages 579–587, 2013.

E. Hazan. Introduction to Online Convex Optimization. *Foundations and Trends in Optimization*, 2 (3-4):157–325, 2016.

E. Hazan and C. Seshadhri. Efficient learning algorithms for changing environments. In *Proceedings of the 26th International Conference on Machine Learning (ICML)*, pages 393–400, 2009.

E. Hazan, S. M. Kakade, and K. Singh. The nonstochastic control problem. In *Proceedings of the 31st International Conference on Algorithmic Learning Theory (ALT)*, pages 408–421, 2020.

K.-S. Jun, F. Orabona, S. Wright, and R. Willett. Improved strongly adaptive online learning using coin betting. In *Proceedings of the 20th International Conference on Artificial Intelligence and Statistics (AISTATS)*, pages 943–951, 2017.

H. Luo and R. E. Schapire. Achieving all with no parameters: AdaNormalHedge. In *Proceedings of the 28th Annual Conference Computational Learning Theory (COLT)*, pages 1286–1304, 2015.

H. Luo, M. Zhang, P. Zhao, and Z.-H. Zhou. Corralling a larger band of bandits: A case study on switching regret for linear bandits. In *Proceedings of the 35th Conference on Learning Theory (COLT)*, 2022.

Z. Mhammedi, W. M. Koolen, and T. van Erven. Lipschitz adaptivity with multiple learning rates in online learning. In *Proceedings of the 32nd Annual Conference Computational Learning Theory (COLT)*, pages 2490–2511, 2019.

F. Orabona. A Modern Introduction to Online Learning. *ArXiv preprint*, 1912.13213, 2019.

F. Orabona and D. Pál. Scale-free online learning. *Theoretical Computer Science*, 716:50–69, 2018.

R. Pogodin and T. Lattimore. On first-order bounds, variance and gap-dependent bounds for adversarial bandits. In *Proceedings of the 35th Conference on Uncertainty in Artificial Intelligence (UAI)*, pages 894–904, 2019.

S. Shalev-Shwartz. Online Learning: Theory, Algorithms and Applications. *PhD Thesis*, 2007.

V. Syrgkanis, A. Agarwal, H. Luo, and R. E. Schapire. Fast convergence of regularized learning in games. In *Advances in Neural Information Processing Systems 28 (NIPS)*, pages 2989–2997, 2015.

T. van Erven and W. M. Koolen. Metagrad: Multiple learning rates in online learning. In *Advances in Neural Information Processing Systems 29 (NIPS)*, pages 3666–3674, 2016.

G. Wang, D. Zhao, and L. Zhang. Minimizing adaptive regret with one gradient per iteration. In *Proceedings of the 27th International Joint Conference on Artificial Intelligence (IJCAI)*, pages 2762–2768, 2018.

L. Zhang. Online learning in changing environments. In *Proceedings of the 29th International Joint Conference on Artificial Intelligence (IJCAI)*, pages 5178–5182, 2020. Early Career.

L. Zhang, S. Lu, and Z.-H. Zhou. Adaptive online learning in dynamic environments. In *Advances in Neural Information Processing Systems 31 (NeurIPS)*, pages 1330–1340, 2018a.

L. Zhang, T. Yang, R. Jin, and Z.-H. Zhou. Dynamic regret of strongly adaptive methods. In *Proceedings of the 35th International Conference on Machine Learning (ICML)*, pages 5877–5886, 2018b.

L. Zhang, T.-Y. Liu, and Z.-H. Zhou. Adaptive regret of convex and smooth functions. In *Proceedings of the 36th International Conference on Machine Learning (ICML)*, pages 7414–7423, 2019.

L. Zhang, S. Lu, and T. Yang. Minimizing dynamic regret and adaptive regret simultaneously. In *Proceedings of the 23rd International Conference on Artificial Intelligence and Statistics (AISTATS)*, pages 309–319, 2020.

L. Zhang, W. Jiang, S. Lu, and T. Yang. Revisiting smoothed online learning. In *Advances in Neural Information Processing Systems 34 (NeurIPS)*, pages 13599–13612, 2021.

M. Zhang, P. Zhao, H. Luo, and Z.-H. Zhou. No-regret learning in time-varying zero-sum games. *ArXiv preprint*, 2201.12736, 2022.

P. Zhao, Y.-J. Zhang, L. Zhang, and Z.-H. Zhou. Dynamic regret of convex and smooth functions. In *Advances in Neural Information Processing Systems 33 (NeurIPS)*, pages 12510–12520, 2020.

P. Zhao, Y.-J. Zhang, L. Zhang, and Z.-H. Zhou. Adaptivity and non-stationarity: Problem-dependent dynamic regret for online convex optimization. *ArXiv preprint*, arXiv:2112.14368, 2021.

P. Zhao, Y.-X. Wang, and Z.-H. Zhou. Non-stationary online learning with memory and non-stochastic control. In *Proceedings of the 25th International Conference on Artificial Intelligence and Statistics (AISTATS)*, pages 2101–2133, 2022.

M. Zinkevich. Online convex programming and generalized infinitesimal gradient ascent. In *Proceedings of the 20th International Conference on Machine Learning (ICML)*, pages 928–936, 2003.