# EXPLAINING RL DECISIONS WITH TRAJECTORIES

## ABSTRACT

Explanation is a key component for the adoption of reinforcement learning (RL) in many real-world decision-making problems. In the literature, the explanation is often provided by saliency attribution to the features of the RL agent's state. In this work, we propose a complementary approach to these explanations, particularly for offline RL, where we attribute the policy decisions of a trained RL agent to the trajectories encountered by it during training. To do so, we encode trajectories in offline training data individually as well as collectively (encoding a set of trajectories). We then attribute policy decisions to a set of trajectories in this encoded space by estimating the sensitivity of the decision with respect to that set. Further, we demonstrate the effectiveness of the proposed approach in terms of quality of attributions as well as practical scalability in diverse environments that involve both discrete and continuous state and action spaces such as grid-worlds, video games (Atari) and continuous control (MuJoCo). We also conduct a human study on a simple navigation task to observe how their understanding of the task compares with data attributed for a trained RL policy.

## 1 INTRODUCTION

Reinforcement learning (Sutton & Barto, 2018) has enjoyed great popularity and has achieved huge success, especially in the online settings, post advent of the deep reinforcement learning (Mnih et al., 2013; Schulman et al., 2017; Silver et al., 2017; Haarnoja et al., 2018). Deep RL algorithms are now able to handle high-dimensional observations such as visual inputs with ease. However, using these algorithms in the real world requires - i) efficient learning from minimal exploration to avoid catastrophic decisions due to insufficient knowledge of the environment, and ii) being explainable. The first aspect is being studied under offline RL where the agent is trained on collected experience rather than exploring directly in the environment. There is a huge body of work on offline RL (Levine et al., 2020; Kumar et al., 2020; Yu et al., 2020; Kostrikov et al., 2021). However, more work is needed to address the explainability aspect of RL decision-making.

Previously, researchers have attempted explaining decisions of RL agent by highlighting important features of the agent's state (input observation) (Puri et al., 2019; Iyer et al., 2018; Greydanus et al., 2018). While these approaches are useful, we take a complementary route. Instead of identifying salient state-features, we wish to identify the past experiences (trajectories) that led the RL agent to learn certain behaviours. We call this approach as trajectory-aware RL explainability. Such explainability confers faith in the decisions suggested by the RL agent in critical scenarios (surgical (Loftus et al., 2020), nuclear (Boehnlein et al., 2022), etc.) by looking at the trajectories responsible for the decision. While this sort of training data attribution has been shown to be highly effective in supervised learning (Nguyen et al., 2021), to the best of our knowledge, this is the first work to study data attribution-based explainability in RL. In the present work, we restrict ourselves to offline RL setting where the agent is trained completely offline, i.e., without interacting with the environment and later deployed in the environment.

Contributions of this work are enumerated below:

1. A novel explainability framework for reinforcement learning that aims to find experiences(trajectories) that lead an RL agent learn certain behaviour.

2. A solution for trajectory attribution in offline RL setting based on state-of-the-art sequence modeling techniques. In our solution, we present a methodology that generates a single embedding for a trajectory of states, actions, and rewards, inspired by approaches in Natural

Language Processing (NLP). We also extend this method to generate a single encoding of data containing a set of trajectories.

3. Analysis of trajectory explanations produced by our technique along with analysis of the trajectory embeddings generated, where we demonstrate how different embedding clusters represent different semantically meaningful behaviours. Additionally, we also conduct a study to compare human understanding of RL tasks with trajectories attributed.

This paper is organized as follows. In Sec. 2 we cover the works related to explainability in RL and the recent developments in offline RL. We then present our trajectory attribution algorithm in Sec. 3. The experiments and results are presented in Sec. 4. We discuss the implications of our work and its potential extensions in the concluding Sec. 5.

## 2 BACKGROUND AND RELATED WORK

**Explainability in RL.** Explainable AI (XAI) refers to the field of machine learning (ML) that focuses on developing tools for explaining the decisions of ML models. Explainable RL (XRL) (Puiutta & Veith, 2020) is a sub-field of XAI that specializes in interpreting behaviours of RL agents. Prior works include approaches that distill the RL policy into simpler models such as decision tree (Coppens et al., 2019) or to human understandable high-level decision language (Verma et al., 2018). However, such policy simplification fails to approximate the behavior of complex RL models. In addition, causality-based approaches (Pawlowski et al., 2020; Madumal et al., 2020) aim to explain an action's agent by identifying the cause behind it using counterfactual samples. Further, saliency-based methods using input feature gradients (Iyer et al., 2018) and perturbations (Puri et al., 2019; Greydanus et al., 2018) provide state-based explanations that aid humans in understanding the agent's actions. To the best of our knowledge, for the first time, we explore the direction of explaining an agent's behaviour by attributing its actions to past encountered trajectories rather than highlighting state features.

**Offline RL.** Offline RL (Levine et al., 2020) refers to the RL setting where an agent learns from collected experiences and does not have direct access to the environment during training. There are several specialized algorithms proposed for offline RL including model-free ones (Kumar et al., 2020; 2019) and model-based ones (Kidambi et al., 2020; Yu et al., 2020). In this work, we use algorithms from both these classes to train offline RL agents. In addition, recently, the RL problem of maximizing long-term return has been cast as taking the best possible action given the sequence of past interactions in terms of states, actions, rewards (Chen et al., 2021; Janner et al., 2021; Reed et al., 2022; Park et al., 2018). Such sequence modelling approaches to RL, especially the ones based on transformer architecture (Vaswani et al., 2017), have produced state-of-the-art results in various offline RL benchmarks, and offer rich latent representations to work with. However, little to no work has been done in the direction of understanding these sequence representations and their applications. In this work, we base our solution on these sequence modelling approaches to leverage their high efficiency in capturing the policy and environment dynamics of the offline RL systems.

## 3 TRAJECTORY ATTRIBUTION

**Preliminaries.** We denote the offline reinforcement learning dataset using $\mathcal{D}$ that comprises a set of $n_\tau$ trajectories. Each trajectory, denoted by $\tau_j$ comprises of a sequence of observation ($o_k$), action ($a_k$) and per-step reward ($r_k$) tuples with $k$ ranging from 1 to the length of the trajectory $\tau_j$. We begin by training an offline RL agent on this data using any standard offline RL algorithm from the literature.

**Algorithm.** Having obtained the learned policy using an offline RL algorithm, our objective now is to attribute this policy, i.e., the action chosen by this policy, at a given state to a set of trajectories. We intend to achieve this in the following way. We want to find the smallest set of trajectories, the absence of which from the training data leads to different behaviour at the state under consideration. That is, we posit that this set of trajectories contains specific behaviours and respective feedbacks from the environment that train the RL agent to make decisions in a certain manner. This identified set of trajectories would then be provided as attribution for the original decision.

Figure 1: **Trajectory Attribution in Offline RL.** First, we encode trajectories in offline data using sequence encoders and then cluster the trajectories using these encodings. Also, we generate a single embedding for the data. Next, we train explanation policies on variants of the original dataset and compute corresponding data embeddings. Finally, we attribute decisions of RL agents trained on entire data to trajectory clusters using action and data embedding distances.

While this basic idea is straightforward and intuitive, it is not computationally feasible beyond a few small RL problems with discrete state and action spaces. The key requirement to scale this approach to large, continuous state and action space problems, is to group the trajectories into clusters which can then be used to analyse their role in the decision-making of the RL agent. In this work, we propose to cluster the trajectories using trajectory embeddings produced with the help of state-of-the-art sequence modelling approaches.

Fig. 1 gives an overview of our proposed approach involving five steps: (i) Trajectory encoding, (ii) Trajectory clustering, (iii) Data embedding, (iv) Training explanation policies, and (v) Cluster attribution, each of which is explained in the sequel.

**(i) Trajectory Encoding.** First, we tokenize the trajectories in the offline data according to the specifications of the sequence encoder used (e.g. decision transformer/trajectory transformer). The observation, action and reward tokens of a trajectory are then fed to the sequence encoder to produce corresponding latent representations, which we refer to as output tokens. We define the *trajectory embedding* as an average of these output tokens. This technique is inspired by average-pooling techniques (Choi et al., 2021; Briggs, 2021) in NLP used to create sentence embedding from embeddings of words present in it. (Refer to Alg. 1.)

---

**Algorithm 1:** encodeTrajectories

/* Encoding given set of trajectories individually                              */
**Input**      : Offline Data $\{\tau_i\}$, Sequence Encoder $E$
**Initialize:** Initialize array $T$ to collect the trajectory embeddings
1 **for** $\tau_j$ *in* $\{\tau_i\}$ **do**
  /* Using $E$, get output tokens for all the $o$, $a$ & $r$ in $\tau_j$      */
2   $(e_{o_{1,j}}, e_{a_{1,j}}, e_{r_{1,j}}, ..., e_{o_{\mathbb{T},j}}, e_{a_{\mathbb{T},j}}, e_{r_{\mathbb{T},j}}) \leftarrow E(o_{1,j}, a_{1,j}, r_{1,j}, ..., o_{\mathbb{T},j}, a_{\mathbb{T},j}, r_{\mathbb{T},j})$ // where $3\mathbb{T}$ = #input tokens
  /* Take mean of outputs to generate $\tau_j$'s embedding $t_j$              */
3   $t_j \leftarrow (e_{o_{1,j}} + e_{a_{1,j}} + e_{r_{1,j}} + e_{o_{2,j}} + e_{a_{2,j}} + e_{r_{2,j}} + ... + e_{o_{\mathbb{T},j}} + e_{a_{\mathbb{T},j}} + e_{r_{\mathbb{T},j}})/(3\mathbb{T})$
4   Append $t_j$ to $T$
**Output**   : Return the trajectory embeddings $T = \{t_i\}$

---

**(ii) Trajectory Clustering.** Having obtained trajectory embeddings, we cluster them using X-Means clustering algorithm (Pelleg et al., 2000) with implementation provided by Novikov (2019). While in principle, any suitable clustering algorithm can be used here, we chose X-Means as it is a simple

extension to the K-means clustering algorithm (Lloyd, 1982); it determines the number of clusters $n_c$ automatically. This enables us to identify all possible patterns in the trajectories without forcing $n_c$ as a hyperparameter (Refer to Alg. 2).

---

**Algorithm 2:** clusterTrajectories

/* Clustering the trajectories using their embeddings          */
**Input**    : Trajectory embeddings $T = \{t_i\}$, clusteringAlgo
1 $C \leftarrow$ clusteringAlgo(T) // Cluster using provided clustering algorithm
**Output**  : Return trajectory clusters $C = \{c_i\}_{i=1}^{n_c}$

---

**(iii) Data Embedding.** We need a way to identify the least change in the original data that leads to the change in behaviour of the RL agent. To achieve this, we propose a representation for data comprising collection of trajectories. The representation has to be agnostic to the order in which trajectories are present in the collection. So, we follow the set-encoding procedure prescribed in (Zaheer et al., 2017) where we first sum the embeddings of the trajectories in the collection, normalize this sum by division with a constant and further apply a non-linearity, in our case, simply, softmax over the feature dimension to generate a single *data embedding* (Refer to Alg. 3).

We use this technique to generate data embeddings for $n_c + 1$ sets of trajectories. The first set represents the entire training data whose embedding is denoted by $\bar{d}_{\text{orig}}$. The remaining $n_c$ sets are constructed as follows. For each trajectory cluster $c_j$, we construct a set with the entire training data but the trajectories contained in $c_j$. We call this set the complementary data set corresponding to cluster $c_j$ and the corresponding data embedding as the complementary data embedding $\bar{d}_j$.

---

**Algorithm 3:** generateDataEmbedding

/* Generating data embedding for a given set of trajectories  */
**Input**    : Trajectory embeddings $T = \{t_i\}$, Normalizing factor $M$, Softmax temperature $T_{\text{soft}}$
1 $\bar{s} \leftarrow \frac{\sum_i t_i}{M}$ // Sum the trajectory embeddings and normalize them
2 $\bar{d} \leftarrow \{d_j | d_j = \frac{exp(s_j/T_{\text{soft}})}{\sum_k exp(s_k/T_{\text{soft}})}\}$ // Take softmax along feature dimension
**Output**  : Return the data embedding $\bar{d}$

---

**(iv) Training Explanation Policies.** In this step, for each cluster $c_j$, using its complementary data set, we train an offline RL agent. We ensure that all the training conditions (algorithm, weight initialization, optimizers, hyperparameters, etc.) are identical to the training of original RL policy, except for the modification in the training data. We call this newly learned policy as the explanation policy corresponding to cluster $c_j$. We thus get $n_c$ explanation policies at the end of this step. In addition, we compute data embeddings for complementary data sets (Refer to Alg. 4).

---

**Algorithm 4:** trainExpPolicies

/* Train explanation policies and compute corresponding data
   embeddings                                                  */
**Input**    : Offline data$\{\tau_i\}$, Traj. Embeddings $T$, Traj. Clusters $C$, offlineRLAlgo
1 **for** $c_j$ *in* $C$ **do**
2 $\quad$ $\{\tau_i\}_j \leftarrow \{\tau_i\} - c_j$ // Compute complementary dataset corresp. to $c_j$
3 $\quad$ $T_j \leftarrow$ gatherTrajectoryEmbeddings$(T, \{\tau_i\}_j)$ // Gather corresp. $\tau$ embeds
4 $\quad$ Explanation policy, $\pi_j \leftarrow$ offlineRLAlgo$(\{\tau_i\}_j)$
5 $\quad$ Complementary data embedding, $\bar{d}_j \leftarrow$ generateDataEmbedding$(T_j, M, T_{\text{soft}})$
**Output**  : Explanation policies $\{\pi_j\}$, Complementary data embeddings $\{\bar{d}_j\}$

---

**(v) Cluster Attribution.** In this final step, given a state, we note the actions suggested by all the explanation policies at this state. We then compute the distances of these actions (where we assume a metric over the action space) from the action suggested by the original RL agent at the state. The explanation policies corresponding to the maximum of these distances form the candidate

attribution set. For each policy in this candidate attribution set, we compute the distance between its respective complementary data embedding and the data embedding of the entire training data using the Wasserstein metric for capturing distances between softmax simplices (Vallender, 1974). We then select the policy that has the smallest data distance and attribute the decision of the RL agent to the cluster corresponding to this policy(Refer to Alg. 5). Our approach comprised of all the five steps is summarized in Algorithm 6.

---

**Algorithm 5:** generateClusterAttribution

```
/* Generating cluster attributions for a_orig = π_orig(s)          */
```
**Input** : State $s$, Original Policy $\pi_{\text{orig}}$, Explanation Policies $\{\pi_j\}$, Original Data Embedding $\bar{d}_{\text{orig}}$, Complementary Data Embeddings $\{\bar{d}_j\}$

1 Original action, $a_{\text{orig}} \leftarrow \pi_{\text{orig}}(s)$
2 Actions suggested by explanation policies, $a_j \leftarrow \pi_j(s)$
3 $d_{a_{\text{orig}},a_j} \leftarrow \text{calcActionDistance}(a_{\text{orig}}, a_j)$// Compute action distance
4 $K \leftarrow \text{argmax}(d_{a_{\text{orig}},a_j})$// Get candidate clusters using argmax
5 $w_k \leftarrow W_{\text{dist}}(\bar{d}_{\text{orig}}, \bar{d}_k)$// Compute Wasserstein distance b/w complementary data embeddings of candidate clusters & orig data embedding
6 $c_{\text{final}} \leftarrow \text{argmin}(w_k)$// Choose cluster with min data embedding dist.

**Output** : $c_{\text{final}}$

---

## 4 EXPERIMENTS AND RESULTS

Next, we present experimental results to show the effectiveness of our approach in generating trajectory explanations. We address the following key questions: Q1) Do we generate reliable trajectory explanations?(Sec. 4.2) Q2) Do our generated explanations align with human understanding of the environment? (Sec. 4.3)

### 4.1 EXPERIMENTAL SETUP

We first describe the environments, models, and metrics designed to study the reliability of our trajectory explanations.

**RL Environments.** We perform experiments on three environments: i) *Grid-world* (Fig. 6) which has discrete state and action spaces, ii) *Seaquest* from Atari suite which has environments with continuous visual observations and discrete action spaces (Bellemare et al., 2013), and iii) *HalfCheetah* from MuJoCo environments which are control environments with continuous state and action spaces (Todorov et al., 2012).

**Offline Data and Sequence Encoders.** For grid-world, we collect offline data of 60 trajectories from policy rollout of other RL agents and train an LSTM-based trajectory encoder following the procedure described in trajectory transformer, replacing the transformer with LSTM. For Seaquest, we collect offline data of 717 trajectories from the D4RL-Atari repository[1] and use a pre-trained decision transformer[2] as trajectory encoder. Similarly, for HalfCheetah, we collect offline data of 1000 trajectories from the D4RL repository[3] (Fu et al., 2020) and use a pre-trained trajectory transformer[4] as a trajectory encoder. To cluster high-level skills in long trajectory sequences, we divide the Seaquest trajectories into 30-length sub-trajectories and the HalfCheetah trajectories into 25-length sub-trajectories. These choices were made based on the transformers' input block sizes and the quality of clustering.

**Offline RL Training and Data Embedding.** We train the offline RL agents for each environment using the data collected as follows - for grid-world, we use model-based offline RL, and for Seaquest and HalfCheetah, we employ DiscreteSAC (Christodoulou, 2019) and SAC (Haarnoja et al., 2018),

---

[1]https://github.com/takuseno/d4rl-atari
[2]https://huggingface.co/edbeeching/decision_transformer_atari
[3]https://github.com/Farama-Foundation/D4RL
[4]https://github.com/jannerm/trajectory-transformer

respectively, using d3rlpy implementations (Takuma Seno, 2021). We compute data embedding of entire training data for each of the environments. See Appendix A.3 for additional training details.

**Encoding of Trajectories and Clustering.** We encode the trajectory data using sequence encoders and cluster the output trajectory embeddings using the X-means algorithm. More specifically, we obtain 10 trajectory clusters for grid-world, 8 for Seaquest, and 10 for HalfCheetah.

**Complementary Data Sets.** We obtain complementary data sets using the aforementioned cluster information and provide 10 complementary data sets for grid-world, 8 for Seaquest, and 10 for HalfCheetah. Next, we compute data embeddings corresponding to these newly formed data sets.

**Explanation Policies.** Subsequently, we train explanation policies on the complementary data sets for each environment. The training produces 10 additional policies for grid-world, 8 policies for Seaquest, and 10 policies for HalfCheetah. In summary, we train the original policy on the entire data, obtain data embedding for the entire data, cluster the trajectories and obtain their explanation policies and complementary data embeddings.

**Trajectory Attribution.** Finally, we attribute a decision made by the original policy for a given state to a trajectory cluster. We choose top-3 trajectories from these attributed clusters by matching the context for the state-action under consideration with trajectories in the cluster in our experiments.

**Evaluation Metrics.** We compare policies trained on different data using three metrics (deterministic nature of policies is assumed throughout the discussion) – *1) Initial State Value Estimate* denoted by $\mathbb{E}(V(s_0))$ which is a measure of expected long-term returns to evaluate offline RL training as described in Paine et al. (2020), *2) Local Mean Absolute Action-Value Difference:* defined as $\mathbb{E}(|\Delta Q_{\pi_{\text{orig}}}|) = \mathbb{E}(|Q_{\pi_{\text{orig}}}(\pi_{\text{orig}}(s)) - Q_{\pi_{\text{orig}}}(\pi_j(s))|)$ that measures how original policy perceives suggestions given by explanation policies, and *3) Action Contrast Measure:* a measure of difference in actions suggested by explanation policies and the original action. Here, we use $\mathbb{E}(\mathbb{1}(\pi_{\text{orig}}(s) \neq \pi_j(s))$ for discrete action space and $\mathbb{E}((\pi_{\text{orig}}(s) - \pi_j(s))^2)$ for continuous action space. Further, we compute distances between embeddings of original and complementary data sets using Wasserstein metric: $W_{\text{dist}}(\bar{d}_{\text{orig}}, \bar{d}_j)$, later normalized to [0, 1]. Finally, the cluster attribution frequency is measured using metric $\mathbb{P}(c_{\text{final}} = c_j)$.

## 4.2 TRAJECTORY ATTRIBUTION RESULTS

**Qualitative Results.** Fig. 3 depicts a grid-world state - (1, 1), corresponding decision by the trained offline RL agent - 'right', and attribution trajectories explaining the decision. As we can observe, the decision is influenced not only by trajectory (traj.-i) that goes through (1, 1) but also by other distant trajectories(trajs.-ii, iii). These examples demonstrate that distant experiences (e.g. traj.-iii) could significantly influence the RL agent's decisions, deeming trajectory attribution an essential component of future XRL techniques.

Further, Fig. 4 shows Seaquest agent (submarine) suggesting action 'left' for given observation in the context of past few frames. The corresponding attributed trajectories provide the insights into how the submarine is aligning itself to target enemies coming from the left. Fig. 7 shows HalfCheetah observation, the agent suggested in terms of hinge torques, and corresponding attributed trajectories showing runs that influence suggested set of torques. Additional results are given in Sec. A.5.

**Quantitative Analysis.** Tables 1, 2 and 3 present quantitative analysis of the proposed trajectory attribution. The initial state value estimate for the original policy $\pi_{\text{orig}}$ matches or exceeds estimates for explanation policies trained on different complementary data sets in all three environment settings. This indicates that the original policy, having access to all behaviours, is able to outperform other policies that are trained on data lacking information about important behaviours (e.g. grid-world: reaching a distant goal, Seaquest: fighting in the top-right corner, HalfCheetah: stabilizing the frame while taking strides). Furthermore, local mean absolute action-value difference and action differences turn out to be highly correlated (Tab. 2 and 3), i.e., the explanation policies that suggest the most contrasting actions are usually perceived by the original policy as low-return actions. This evidence supports the proposed trajectory algorithm as we want to identify the behaviours which when removed make agent choose actions that are not considered suitable originally. In addition, we provide the distances between the data embeddings in the penultimate column. The cluster attribution distribution is represented in the last column which depicts how RL decisions are dependent on various behaviour clusters. Interestingly, in the case of grid-world, we found that only a few clus-

(a) Grid-world         (b) Seaquest         (c) HalfCheetah

Figure 2: **PCA Plot depicting Clusters of Trajectory Embeddings** for a) Grid-world, b) Seaquest, and c) HalfCheetah. We find that these clusters represent semantically meaningful high-level behaviours. A detailed discussion of these findings can be found in Appendix A.6.

Figure 3: **Grid-world Trajectory Attribution.** RL agent suggests taking action 'right' in grid cell (1,1) which is attributed to trajectories (i), (ii) and (iii) (Here a trajectory is annotated by $\wedge, \vee, >, <$ arrows for 'up', 'down', 'right', 'left' actions respectively, along with the time-step (starting with 0) associated with the actions). The figure shows that the action suggestion is influenced by trajectories distant from the cell under consideration.

Figure 4: **Seaquest Trajectory Attribution.** The agent (submarine) decides to take 'left' for the given observation under the provided context. Top-3 attributed trajectories are shown on the right (for each traj., here we show 6 sampled observations along with actions taken by data collection policy). We can infer from these trajectories how the agent is aligning itself to face enemies coming from left.

ters containing information about reaching goals and avoiding lava had the most significant effect on the original RL policy.

Table 1: **Quantitative Analysis of Grid-world Trajectory Attribution.** The analysis is provided using 5 metrics. Higher the $\mathbb{E}(V(s_0))$, better is the trained policy. High $\mathbb{E}(|\Delta Q_{\pi_{\text{orig}}}|)$ along with high $\mathbb{E}(\mathbb{1}(\pi_{\text{orig}}(s) \neq \pi_j(s))$ is desirable. The policies with lower $W_{\text{dist}}(\bar{d}, \bar{d}_j)$ and high action contrast are given priority while attribution. The cluster attribution distribution is given in the final column.

| $\pi$ | $\mathbb{E}(V(s_0))$ | $\mathbb{E}(|\Delta Q_{\pi_{\text{orig}}}|)$ | $\mathbb{E}(\mathbb{1}(\pi_{\text{orig}}(s) \neq \pi_j(s))$ | $W_{\text{dist}}(\bar{d}, \bar{d}_j)$ | $\mathbb{P}(c_{\text{final}} = c_j)$ |
|---|---|---|---|---|---|
| orig | **0.3061** | - | - | - | - |
| 0 | 0.3055 | 0.0012 | 0.0409 | **1.0000** | 0.0000 |
| 1 | 0.3053 | 0.0016 | 0.0409 | 0.0163 | 0.0000 |
| 2 | 0.3049 | 0.0289 | **0.1429** | 0.0034 | 0.0000 |
| 3 | 0.2857 | **0.0710** | 0.1021 | 0.0111 | 0.3750 |
| 4 | 0.2987 | 0.0322 | **0.1429** | 0.0042 | 0.1250 |
| 5 | 0.3057 | 0.0393 | 0.0409 | 0.0058 | 0.0000 |
| 6 | 0.3046 | 0.0203 | 0.1225 | 0.0005 | **0.5000** |
| 7 | 0.3055 | 0.0120 | 0.0205 | 0.0006 | 0.0000 |
| 8 | 0.3057 | 0.0008 | 0.0205 | 0.0026 | 0.0000 |
| 9 | 0.3046 | 0.0234 | **0.1429** | 0.1745 | 0.0000 |

Table 2: **Quantitative Analysis of Seaquest Trajectory Attribution.** The analysis is provided using 5 metrics. Higher the $\mathbb{E}(V(s_0))$, better is the trained policy. High $\mathbb{E}(|\Delta Q_{\pi_{\text{orig}}}|)$ along with high $\mathbb{E}(\mathbb{1}(\pi_{\text{orig}}(s) \neq \pi_j(s))$ is desirable. The policies with lower $W_{\text{dist}}(\bar{d}, \bar{d}_j)$ and high action contrast are given priority while attribution. The cluster attribution distribution is given in the final column.

| $\pi$ | $\mathbb{E}(V(s_0))$ | $\mathbb{E}(|\Delta Q_{\pi_{\text{orig}}}|)$ | $\mathbb{E}(\mathbb{1}(\pi_{\text{orig}}(s) \neq \pi_j(s))$ | $W_{\text{dist}}(\bar{d}, \bar{d}_j)$ | $\mathbb{P}(c_{\text{final}} = c_j)$ |
|---|---|---|---|---|---|
| orig | 85.9977 | - | - | - | - |
| 0 | 50.9399 | 1.5839 | 0.9249 | 0.4765 | 0.1129 |
| 1 | 57.5608 | 1.6352 | 0.8976 | 0.9513 | 0.0484 |
| 2 | 66.7369 | 1.5786 | 0.9233 | **1.0000** | 0.0403 |
| 3 | 3.0056 | **1.9439** | **0.9395** | 0.8999 | 0.0323 |
| 4 | 58.1854 | 1.5813 | 0.8992 | 0.5532 | 0.0968 |
| 5 | 87.3034 | 1.6026 | 0.9254 | 0.2011 | **0.3145** |
| 6 | 70.8994 | 1.5501 | 0.9238 | 0.6952 | 0.0968 |
| 7 | **89.1832** | 1.5628 | 0.9249 | 0.3090 | 0.2581 |

## 4.3 HUMAN EVALUATION

One of the key desiderata of explanations is to provide relevant information about the behaviour of complex AI models. To this end, prior works in other domains like vision (Goyal et al., 2019) and language (Liu et al., 2019) have conducted human studies to quantify the usefulness of output explanations. In context to reinforcement learning, humans possess an explicit understanding of RL gaming environments and can reason about actions at a given state to a satisfactory extent. To compare this human knowledge against trajectories found responsible for the RL agents' actions using our technique, we pilot a human study with 10 participants who had a complete understanding of the grid-world navigation environment.

**Study setup.** For the human study, we design two tasks: i) participants need to choose a trajectory that they think *best* explains the action suggested in a grid cell, and ii) participants need to identify *all relevant* trajectories that explain action suggested by RL agent. For instance, in Fig. 5a, we show one instance of the task where the agent is located at (1, 1) and is taking 'right' and a subset of attributed trajectories for this agent action. In both the tasks, in addition to attributions proposed by our technique we add i) a randomly selected trajectory as an explanation, and ii) a trajectory selected from a cluster different from the one attributed by our approach. These additional trajectories aid in identifying human bias toward certain trajectories while understanding the agents' behaviour. The link to the questionnaire used for the study is provided in Sec. A.7.

**Results.** On average, across three studies in Task 1, we found that 70% of the time, human participants chose trajectories generated by our proposed method as the best explanation for the agent's action. In Figure 5b, we observe a high alignment between human and RL understanding of the

grid-world environment. On average, across three studies in Task 2, nine participants chose the trajectories generated by our algorithm (Attributed Trajectory 2). Interestingly, the results also demonstrate that not all trajectories generated by our algorithm are considered relevant by humans, and often they are considered as good as a random trajectory (Figure 5b; Attributed Trajectory 1). This suggests that sometimes human understanding of the factors influencing RL decision-making could be insufficient and hence, the explainability tools such as the one proposed in this work become important.

Figure 5: **Column (a):** An example of the human study experiment where users are required to identify the attributed trajectories that best explain the state-action behavior of the agent. **Column (b):** Results from our human study experiments show that, on average, 9 humans agree with the trajectories generated by our proposed algorithm.

## 5 DISCUSSION

In this work, we proposed a novel explanation technique that attributes decisions suggested by an RL agent to trajectories encountered by the agent in the past. We provided an algorithm that enables us to perform trajectory attribution in offline RL. The key idea behind our approach was to encode trajectories using sequence modelling techniques, cluster the trajectories using these embeddings and then study the sensitivity of original RL agent's policy to the trajectories present in each of these clusters. We demonstrated the utility of our method using experiments in grid-world, Seaquest and HalfCheetah environments. In the end, we also presented a human evaluation of the results of our method to further underline the necessity of trajectory attribution.

The ideas presented in this paper, such as generating trajectory embedding using sequence encoders, creating an encoding of the set of trajectories, can be extended to other domains of RL. For instance, the trajectory embeddings could be beneficial in recognizing hierarchical behaviour patterns as studied under options theory (Sutton et al., 1999). The data encoding could prove useful in studying transfer learning (Zhu et al., 2020) in RL by utilizing the data embeddings from both the source and target decision-making tasks. As from the XRL point of view, we wish to extend our work to online RL settings where the agent constantly collects experiences through active interactions with the environment.

While all our experiments are very promising, we need to be cautious about the ability of sequential modelling techniques to learn complex temporal patterns, especially in problems involving high-dimensional, multi-modal observations and/or actions. Also, the training of multiple explanation policies could pose challenges due to extra computational requirements.

## REFERENCES

M. G. Bellemare, Y. Naddaf, J. Veness, and M. Bowling. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47:253–279, jun 2013.

Amber Boehnlein, Markus Diefenthaler, Nobuo Sato, Malachi Schram, Veronique Ziegler, Cristiano Fanelli, Morten Hjorth-Jensen, Tanja Horn, Michelle P. Kuchera, Dean Lee, Witold Nazarewicz, Peter Ostroumov, Kostas Orginos, Alan Poon, Xin-Nian Wang, Alexander Scheinker, Michael S. Smith, and Long-Gang Pang. icolloquium/i : Machine learning in nuclear physics. *Reviews of*

*Modern Physics*, 94(3), sep 2022. doi: 10.1103/revmodphys.94.031003. URL `https://doi.org/10.1103%2Frevmodphys.94.031003`.

James Briggs. How to get sentence embedding using bert?, Oct 2021. URL `https://datascience.stackexchange.com/a/103569`.

Lili Chen, Kevin Lu, Aravind Rajeswaran, Kimin Lee, Aditya Grover, Michael Laskin, Pieter Abbeel, Aravind Srinivas, and Igor Mordatch. Decision transformer: Reinforcement learning via sequence modeling. *arXiv preprint arXiv:2106.01345*, 2021.

Hyunjin Choi, Judong Kim, Seongho Joe, and Youngjune Gwon. Evaluation of bert and albert sentence embedding performance on downstream nlp tasks. In *2020 25th International conference on pattern recognition (ICPR)*, pp. 5482–5487. IEEE, 2021.

Petros Christodoulou. Soft actor-critic for discrete action settings. *arXiv preprint arXiv:1910.07207*, 2019.

Youri Coppens, Kyriakos Efthymiadis, Tom Lenaerts, Ann Nowé, Tim Miller, Rosina Weber, and Daniele Magazzeni. Distilling deep reinforcement learning policies in soft decision trees. In *Proceedings of the IJCAI 2019 workshop on explainable artificial intelligence*, pp. 1–6, 2019.

Justin Fu, Aviral Kumar, Ofir Nachum, George Tucker, and Sergey Levine. D4rl: Datasets for deep data-driven reinforcement learning, 2020.

Yash Goyal, Ziyan Wu, Jan Ernst, Dhruv Batra, Devi Parikh, and Stefan Lee. Counterfactual visual explanations. In *International Conference on Machine Learning*. PMLR, 2019.

Samuel Greydanus, Anurag Koul, Jonathan Dodge, and Alan Fern. Visualizing and understanding atari agents. In *International conference on machine learning*, pp. 1792–1801. PMLR, 2018.

Tuomas Haarnoja, Aurick Zhou, Kristian Hartikainen, George Tucker, Sehoon Ha, Jie Tan, Vikash Kumar, Henry Zhu, Abhishek Gupta, Pieter Abbeel, et al. Soft actor-critic algorithms and applications. *arXiv preprint arXiv:1812.05905*, 2018.

Rahul Iyer, Yuezhang Li, Huao Li, Michael Lewis, Ramitha Sundar, and Katia Sycara. Transparency and explanation in deep reinforcement learning neural networks. In *Proceedings of the 2018 AAAI/ACM Conference on AI, Ethics, and Society*, pp. 144–150, 2018.

Michael Janner, Qiyang Li, and Sergey Levine. Offline reinforcement learning as one big sequence modeling problem. In *Advances in Neural Information Processing Systems*, 2021.

Leslie Pack Kaelbling, Michael L Littman, and Anthony R Cassandra. Planning and acting in partially observable stochastic domains. *Artificial intelligence*, 101(1-2):99–134, 1998.

Rahul Kidambi, Aravind Rajeswaran, Praneeth Netrapalli, and Thorsten Joachims. Morel: Model-based offline reinforcement learning. *Advances in neural information processing systems*, 33: 21810–21823, 2020.

Ilya Kostrikov, Rob Fergus, Jonathan Tompson, and Ofir Nachum. Offline reinforcement learning with fisher divergence critic regularization. In *International Conference on Machine Learning*, pp. 5774–5783. PMLR, 2021.

Aviral Kumar, Justin Fu, G. Tucker, and Sergey Levine. Stabilizing off-policy q-learning via boot-strapping error reduction. In *NeurIPS*, 2019.

Aviral Kumar, Aurick Zhou, George Tucker, and Sergey Levine. Conservative q-learning for offline reinforcement learning. *Advances in Neural Information Processing Systems*, 33:1179–1191, 2020.

Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *CoRR*, abs/2005.01643, 2020. URL `https://arxiv.org/abs/2005.01643`.

Hui Liu, Qingyu Yin, and William Yang Wang. Towards explainable NLP: A generative explanation framework for text classification. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 5570–5581, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1560. URL `https://aclanthology.org/P19-1560`.

Stuart Lloyd. Least squares quantization in pcm. *IEEE transactions on information theory*, 28(2): 129–137, 1982.

Tyler J Loftus, Amanda C Filiberto, Yanjun Li, Jeremy Balch, Allyson C Cook, Patrick J Tighe, Philip A Efron, Gilbert R Upchurch Jr, Parisa Rashidi, Xiaolin Li, et al. Decision analysis and reinforcement learning in surgical decision-making. *Surgery*, 168(2):253–266, 2020.

Prashan Madumal, Tim Miller, Liz Sonenberg, and Frank Vetere. Explainable reinforcement learning through a causal lens. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pp. 2493–2500, 2020.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602*, 2013.

Giang Nguyen, Daeyoung Kim, and Anh Nguyen. The effectiveness of feature attribution methods and its correlation with automatic evaluation scores. *Advances in Neural Information Processing Systems*, 34:26422–26436, 2021.

Andrei Novikov. PyClustering: Data mining library. *Journal of Open Source Software*, 4(36):1230, apr 2019. doi: 10.21105/joss.01230. URL `https://doi.org/10.21105/joss.01230`.

Tom Le Paine, Cosmin Paduraru, Andrea Michi, Caglar Gulcehre, Konrad Zolna, Alexander Novikov, Ziyu Wang, and Nando de Freitas. Hyperparameter selection for offline reinforcement learning. *arXiv preprint arXiv:2007.09055*, 2020.

Seong Hyeon Park, ByeongDo Kim, Chang Mook Kang, Chung Choo Chung, and Jun Won Choi. Sequence-to-sequence prediction of vehicle trajectory via lstm encoder-decoder architecture. In *2018 IEEE Intelligent Vehicles Symposium (IV)*, pp. 1672–1678. IEEE, 2018.

Nick Pawlowski, Daniel Coelho de Castro, and Ben Glocker. Deep structural causal models for tractable counterfactual inference. *Advances in Neural Information Processing Systems*, 33:857–869, 2020.

Dan Pelleg, Andrew W Moore, et al. X-means: Extending k-means with efficient estimation of the number of clusters. In *Icml*, volume 1, pp. 727–734, 2000.

Erika Puiutta and Eric Veith. Explainable reinforcement learning: A survey. In *International cross-domain conference for machine learning and knowledge extraction*, pp. 77–95. Springer, 2020.

Nikaash Puri, Sukriti Verma, Piyush Gupta, Dhruv Kayastha, Shripad Deshmukh, Balaji Krishnamurthy, and Sameer Singh. Explain your move: Understanding agent actions using specific and relevant feature attribution. *arXiv preprint arXiv:1912.12191*, 2019.

Martin L Puterman. *Markov decision processes: discrete stochastic dynamic programming*. John Wiley & Sons, 2014.

Scott Reed, Konrad Zolna, Emilio Parisotto, Sergio Gomez Colmenarejo, Alexander Novikov, Gabriel Barth-Maron, Mai Gimenez, Yury Sulsky, Jackie Kay, Jost Tobias Springenberg, et al. A generalist agent. *arXiv preprint arXiv:2205.06175*, 2022.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, et al. Mastering the game of go without human knowledge. *nature*, 550(7676):354–359, 2017.

Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction.* MIT press, 2018.

Richard S Sutton, Doina Precup, and Satinder Singh. Between mdps and semi-mdps: A framework for temporal abstraction in reinforcement learning. *Artificial intelligence*, 112(1-2):181–211, 1999.

Michita Imai Takuma Seno. d3rlpy: An offline deep reinforcement library. In *NeurIPS 2021 Offline Reinforcement Learning Workshop*, December 2021.

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 5026–5033, 2012. doi: 10.1109/IROS.2012.6386109.

SS Vallender. Calculation of the wasserstein distance between probability distributions on the line. *Theory of Probability & Its Applications*, 18(4):784–786, 1974.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Abhinav Verma, Vijayaraghavan Murali, Rishabh Singh, Pushmeet Kohli, and Swarat Chaudhuri. Programmatically interpretable reinforcement learning. In *International Conference on Machine Learning*, pp. 5045–5054. PMLR, 2018.

Tianhe Yu, Garrett Thomas, Lantao Yu, Stefano Ermon, James Y Zou, Sergey Levine, Chelsea Finn, and Tengyu Ma. Mopo: Model-based offline policy optimization. *Advances in Neural Information Processing Systems*, 33:14129–14142, 2020.

Manzil Zaheer, Satwik Kottur, Siamak Ravanbakhsh, Barnabás Póczos, Ruslan Salakhutdinov, and Alexander J. Smola. Deep sets. *CoRR*, abs/1703.06114, 2017. URL http://arxiv.org/abs/1703.06114.

Zhuangdi Zhu, Kaixiang Lin, and Jiayu Zhou. Transfer learning in deep reinforcement learning: A survey. *arXiv preprint arXiv:2009.07888*, 2020.

## A APPENDIX

### A.1 OVERVIEW OF PROPOSED TRAJECTORY ATTRIBUTION

The following is an overview of our proposed 5-step trajectory attribution algorithm.

---

**Algorithm 6:** Trajectory Attribution in Offline RL

---

**Input** : Offline Data $\{\tau_i\}$, States needing explanation $\mathcal{S}_{\text{exp}}$, Sequence Encoder $E$, offlineRLAlgo, clusteringAlgo, Normalizing constant $M$, Softmax Temperature $T_{\text{soft}}$

```
/* Train original offline RL policy                        */
```
1 $\pi_{\text{orig}} \leftarrow$ offlineRLAlgo($\{\tau_i\}$)
```
/* Encode individual trajectories                          */
```
2 $T =$ encodeTrajectories($\{\tau_i\}, E$) // Algo. 1
```
/* Cluster the trajectories                                */
```
3 $C \leftarrow$ clusterTrajectories(T, clusteringAlgo) // Algo. 2
```
/* Compute data embedding for the entire dataset           */
```
4 $\bar{d}_{\text{orig}} =$ generateDataEmbedding(T, $M$, $T_{\text{soft}}$) // Algo. 3
```
/* Generate explanation policies and their corresponding
   complementary data embeddings                           */
```
5 $\{\pi_j\}, \{\bar{d}_j\} \leftarrow$ trainExpPolicies($\{\tau_i\}$, T, $C$, offlineRLAlgo)// Algo. 4
```
/* Attributing policy decisions for given set of states    */
```
6 **for** $s \in \mathcal{S}_{exp}$ **do**
7     $c_{\text{final}} \leftarrow$ generateClusterAttribution($s, \pi_{\text{orig}}, \{\pi_j\}, \bar{d}_{\text{orig}}, \bar{d}_j$) // Algo. 5
8     *Optionally, select top N trajectories in the cluster $c_{\text{final}}$ using a pre-defined criteria.

---

## A.2 GRID-WORLD ENVIRONMENT DETAILS

Figure 6: **Overview of the Grid-world Environment.** The aim of the agent is to reach any of the goal states (green squares) by avoiding lava (red square) and going around the impenetrable walls (grey squares). The reward for reaching the goal is +1; if the agent falls into the lava, it is -1. For any other transitions, the agent receives -0.1. The agent is allowed to take up, down, left or right as the action.

## A.3 ADDTIONAL TRAINING DETAILS

1. **Seaquest Atari Environment** – We employed Discrete SAC to train the original policy along with explanation policies, where the training was performed until saturation in the performance. We used the critic learning rate of $3 \times 10^{-4}$ and the actor learning rate of $3 \times 10^{-4}$ with a batch size of 256. The trainings were performed parallelly on a single Nvidia-A100 GPU hardware.

2. **HalfCheetah MuJoCo Environment** – We used SAC to train the original policy as well as explanation policies where we trained the agents until training performance saturated. We again used the critic learning rate of $3 \times 10^{-4}$ and the actor learning rate of $3 \times 10^{-4}$ with a batch size of 512. The policy trainings were performed parallelly on a single Nvidia-A100 GPU.

## A.4 HALFCHEETAH TRAJECTORY ATTRIBUTION RESULTS

Due to space constraints, we present the qualitative and quantitative results for the HalfCheetah environment here.

Figure 7: **HalfCheetah Trajectory Attribution.** The figure shows agent suggesting torques on different hinges for current position of the cheetah frame. The decision is influenced by the runs of cheetah shown on the right where the cheetah is getting up from the floor (here we show 5 sampled frames for a trajectory). Context is not shown here because unlike Seaquest environment, HalfCheetah decisions are made directly on a given observation (Puterman, 2014; Kaelbling et al., 1998).

Table 3: **Quantitative Analysis of HalfCheetah Trajectory Attribution.** The analysis is provided using 5 metrics. Higher the $\mathbb{E}(V(s_0))$, better is the trained policy. High $\mathbb{E}(|\Delta Q_{\pi_{\text{orig}}}|)$ along with high $\mathbb{E}((\pi_{\text{orig}}(s) - \pi_j(s))^2)$ is desirable. The policies with lower $W_{\text{dist}}(\bar{d}, \bar{d}_j)$ and high action contrast are given priority while attribution. The cluster attribution distribution is given in the final column.

| $\pi$ | Performance Metrics | | | | |
|---|---|---|---|---|---|
| | $\mathbb{E}(V(s_0))$ | $\mathbb{E}(|\Delta Q_{\pi_{\text{orig}}}|)$ | $\mathbb{E}((\pi_{\text{orig}}(s) - \pi_j(s))^2)$ | $W_{\text{dist}}(\bar{d}, \bar{d}_j)$ | $\mathbb{P}(c_{\text{final}} = c_j)$ |
| orig | 131.5449 | - | - | - | - |
| 0 | 127.1652 | 0.5667 | 0.6359 | 0.2822 | 0.0143 |
| 1 | 118.5663 | 0.4796 | 0.5633 | 0.0396 | 0.0214 |
| 2 | 122.0661 | 0.6904 | 0.9366 | 0.0396 | 0.1464 |
| 3 | 133.4590 | 0.5360 | 0.6611 | 0.0396 | 0.1250 |
| 4 | 118.3447 | 0.5622 | 0.6194 | **1.0000** | 0.0964 |
| 5 | **138.7517** | 0.6439 | 0.8262 | 0.0316 | 0.0893 |
| 6 | 120.7088 | 0.4740 | 0.4803 | 0.8813 | 0.0214 |
| 7 | 135.6848 | 0.5154 | 0.5489 | 0.0394 | **0.2036** |
| 8 | 113.3490 | 0.7826 | 1.0528 | 0.7067 | 0.1214 |
| 9 | 83.6211 | **0.9702** | **1.3453** | 0.0264 | 0.1607 |

## A.5 Additional Attribution Results

Figure 8: **Additional Trajectory Attribution Results.** Here we show randomly chosen trajectory from the top-3 attributed trajectories. a) Grid-world agent suggests taking 'DOWN' in cell (3,5) due to the attributed trajectory leading to lava. b) Seaquest agent suggests taking 'LEFT' and the corresponding attributed trajectory. c) HalfCheetah agent suggests a particular set of torques and the run found responsible for the same is shown side-by-side.

## A.6 Clustering Analysis

We observe that the trajectory embeddings obtained from the sequence encoders when clustered together demonstrate characteristic high-level behaviours. For instance, in the case of grid-world (Refer 9), the clusters comprise semantically similar trajectories where the agent demonstrates behaviours such as '*falling into the lava*', '*achieving the goal in the first quadrant*', '*mid-grid journey to the goal*', etc. For Seaquest 10, we obtain trajectory clusters that represent high-level behaviours such as '*filling in oxygen*', '*fighting along the surface*', '*submarine bursting due to collision with enemy*', etc. and for HalfCheetah in Fig. 11, we obtain trajectory clusters that represent high-level actions such as '*taking long forward strides*', '*jumping on hind leg*', '*running with head down*', etc.

Although these results look quite promising, in this work we mainly focus on trajectory attribution that leverages these findings. In future, we wish to analyse the trajectory embeddings and the behaviour patterns in greater detail.

Figure 9: **Cluster Behaviours for Grid-world.** The figure shows 3 example high-level behaviours along with the action description and id of the cluster representing such behaviour.

Figure 10: **High-level Behaviours found in clusters for Seaquest** formed using trajectory embeddings produced using decision transformer. The figure shows 3 example high-level behaviours along with the action description and id of the cluster representing such behaviour.

Jumping on Hind Leg – Cluster 2

Running with Head Down - Cluster 5

Forward Stride – Cluster 9

Figure 11: **High-level Behaviours found in clusters for HalfCheetah** formed using trajectory embeddings produced using trajectory transformer. The figure shows 3 example high-level behaviours along with the action description and id of the cluster representing such behaviour.

In the following figure 12, we present PCA plots of data embeddings (original + complementary) for the three environments.

(a) Grid-world          (b) Seaquest          (c) HalfCheetah

Figure 12: **PCA plot depicting Data Embeddings** of complementary data sets as well as original data set computed using proposed data encoding. Interestingly, the complementary data sets that could lead to very different behaviours lie close to the original data in the embedding space.

## A.7 LINK TO HUMAN EVALUATION QUESTIONNAIRE

The link to the questionnaire used for the study: https://forms.gle/RCyyT3mGxgtVAqFu8. We have ensured that this form doesn't reveal the identities of the authors or potentially that of the reviewers.