From Understanding to Engagement: Personalized pharmacy Video Clips via Vision Language Models (VLMs)

Abstract

Vision Language Models (VLMs) are poised to revolutionize the digital transformation of pharmacyceutical industry by enabling intelligent, scalable, and automated multi-modality content processing. Traditional manual annotation of heterogeneous data modalities (text, images, video, audio, and web links), is prone to inconsistencies, quality degradation, and inefficiencies in content utilization. The sheer volume of long video and audio data further exacerbates these challenges, (e.g. long clinical trial interviews and educational seminars).

Here, we introduce a domain-adapted Video-to-Video Clip Generation framework that integrates Audio-Language Models (ALMs) and Vision Language Models (VLMs) to produce clinically faithful highlight clips. Our contributions are threefold: (i) a reproducible Cut & Merge algorithm with fade-in/out and timestamp normalization, ensuring smooth transitions and audio/visual alignment; (ii) a personalization mechanism based on role definition and prompt injection for tailored outputs (marketing, training, regulatory); and (iii) a cost-efficient e2e pipeline strategy balancing ALM/VLM-enhanced processing. Evaluations on Video-MME benchmark (900) and our proprietary dataset of 16,159 pharmacy videos across 14 disease areas demonstrate 3–4× speedup, 4× cost reduction, and competitive clip quality. Beyond efficiency gains, we also report our methods improved clip coherence scores (0.348) and informativeness scores (0.721) over state-of-the-art VLM baselines (e.g., Gemini 2.5 Pro), highlighting the potential of transparent, customization, and compliance-ready video summarization for life sciences. We also provide access to our Demo.

____
* Patent application submitted to the EPO.

1 Introduction

In contemporary digital content landscape, efficient management and understanding of video assets are paramount, particularly within specialized domains such as medical and pharmacyceutical sectors(Zhang et al., 2024). The proliferation of extensive pharmacyceutical and medical videos — including clinical tryout interviews (Srinivasan et al., 2025), drug manufacturing workflows (Otesteanu et al., 2021), and educational seminars and conference long meetings, has highlighted a critical demand for scalable, high-fidelity video highlight clip generation approach (Tariq et al., 2025a).

Traditionally, the consumption and production of such supplementary long-form videos have been labor-intensive endeavors, often requiring several weeks and dedicated efforts of multiple personnel (Wu et al., 2018; Corin and Li, 2021; Yang et al., 2025a). Current user behavior typically involves reviewing video title and summary, then navigating to each specific frame to assess content, which often leads to a decline in interest. What's more, video creation & review was a protracted process, often extending over several weeks or at least several days (Lackmann et al., 2021). Generating video trailers or summary clips tailored to medical content can significantly reduce the time required for information retrieval and result verification (Liu et al., 2020). Beyond practical efficiencies, these trailers are also anticipated to foster viewer engagement and improve the re-usability of these existing video assets (Guo et al., 2024a).

Recent commercial tools & research works based on diffusion or generative models around video-to-video summarization or video clip generation (Lee et al., 2025a; Shang et al., 2024) can be categorized into three types: **Frames-to-Video**, **Video-to-Video**, and **Single Image+Prompts-to-Video**.

For **Frames-to-Video** methods, companies such as Oclips (OpusClip, 2023), Pika (Pika Labs, 2024), Synthesia (Synthesia, 2024), or HeyGen (HeyGen, 2024) typically extract key frames to form a video. Characteristics of these methods include: (1) Video

Figure 1: Solution architecture blueprint of the underlying LLM/VLM tech stack for video clip generation.

generation is slow (3-5 minutes per short clip, plus 20-30 minutes for long uploads). (2) Pre-processing is lengthy but accurate, requiring times-tamps and summaries. (3) Consistency is vital, as jumping frames can occur. (4) High customization, allowing frame adjustments, removal, additions, along with audio manipulation and highly realistic.

Direct Video-to-Video methods (Wang et al., 2018; Liu et al., 2021; Bansal et al., 2018; Li et al., 2025) features typically include: (1) Video genera-tion incurs shorter times (less than 1-2 minutes for one short clip), offers high accuracy and smooth output without issues of jumping frames, and re-quires the original video file (API, YouTube, or cloud link). (2) Lack of customization, often acting as an enterprise "black box" for frame selection, and post-selection requires more time to choose the best short clips.

Recent advances in Vision Language Models (VLMs) and Audio-Language Models (ALMs) en-able scalable multimodal understanding. Compa-nies like Stability AI (Stability AI, 2024), Sora (Brooks et al., 2024), Elevenlabs (ElevenLabs, 2023), DeepBrain (DeepBrain AI, 2024), Kaiber (Kaiber AI, 2024), and Animoto (Animoto, 2024) adopt **Single Image+Prompts-to-Video** methods, which has following characteristics: (1) Video gen-eration in under 1 minute. (2) Single-image in-put via API for enterprise users. (3) High accu-racy, smooth, and realistic output without jump-ing frames. (4) Current limitations include single-

image input (enterprise APIs may access frames), dedicated prompts, and output length (max 20 sec-onds). However, their direct application remains computationally expensive, fragmented in quality, and ill-adapted to clinical use (Hu et al., 2024), (Jiang et al., 2025).

In this work, we propose Infinite Video-to-Video Clips Generation framework designed for the chal-lenges of the pharmacyceutical domain. Unlike prior generic summarization pipelines, our ap-proach emphasizes (a) **traceability and frame preservation**, avoiding synthetic content that could compromise clinical accuracy; (b) **transparency and personalization**, allowing users to define roles and segment priorities; and (c) **efficiency and cost-awareness**, critical for large-scale VLMs industrial deployment. Our contributions include:

- Cut & Merge Algorithm: A reproducible, patent-pending algorithm that normalizes timestamps and applies fade-in/out boundaries to eliminate jump cuts, audio glitches, and frame freezing (see Fig:2, Alg:1)

- Personalization Mechanisms via Role Defini-tion & Prompt Injection: Systematically tai-loring clip generation (e.g., regulatory compli-ance vs. educational summaries) while main-taining transparency (see Fig:7, 8, 12).

- Infinite Video-to-Video Clips Generation framework, as illustrated in Fig:1, suitable

for industrial production adoption, characterized by lower cost 4x, 3-4x high speed (see Table 3, Figure 3) and better clip-quality scores (Clip Coherence, Informativeness, Redundancy scores in Table 5).

- We also present five key technical findings substantiated by comprehensive evaluation, namely, speech detection and voiceover extraction, a security safeguard for the Whisper model, multimodality versus single modality, alignment and clip personalization.

2 Related Work

Research on video summarization and generation has evolved rapidly in recent years, diffusion-based approaches (Ho et al., 2022; Wang et al., 2025; Xing et al., 2023) have become the dominant paradigm in video generation, replacing earlier GAN- and autoregressive-based methods (Vondrick et al., 2016; Yan et al., 2021). These diffusion-based models achieve impressive visual fidelity; however, scaling them to long videos remains challenging due to high computational demands, degraded frame coherence and consistency. For long video processing — essential in domains such as medical procedure or patient interview recording analysis — recent methods compress and summarize video content into tokens for scalable VLM input. Specific works like Video-XL (Shu et al., 2024), FiLA-Video (Guo et al., 2025), and LongVLM (Weng et al., 2024) have shown promise by using token-compression architectures to balance global context and local detail.

The rise of VLMs has enabled efficient multimodal understanding across video, image, and audio modalities(Brooks et al., 2024),(Yang et al., 2025b). Recent benchmarks such as Video-MME (Fu et al., 2025) establish standardized evaluation for long-video comprehension. Models like Qwen-VL (Bai et al., 2023), Gemini 2.5 (Google DeepMind, 2025), and GPT-4o (OpenAI, 2023) show strong performance on summarization and alignment tasks, but their outputs often lack transparency, are costly to scale, and remain black-box systems for enterprise use. Lee et al.(Lee et al., 2025b) also demonstrate the potential of LLMs for clip generation but highlight challenges in maintaining logical flow and informativeness, e.g. generate synthetic or poorly aligned content that risks clinical misinterpretation (Guo et al., 2024b),(Tariq et al., 2025b) or fail to provide customize clips.

For pharmacyceutical video-to-video clip generation, the primary goal is not to synthesize visually appealing transitions or animations, but rather to identify and extract clinically meaningful highlights, such as interviewer speech, key frames, or specific clinical interventions. In such contexts, preserving the original frames and content is often more valuable than generating new, visually enhanced footage (Hu et al., 2024; Jiang et al., 2025). Accordingly, we focus on developing compliance-ready summarization pipelines that balance scalability with clinical reliability, a critical requirement for deploying VLM-powered video-to-video systems in the pharmacyceutical industry.

3 Dataset And Experimental Settings

Table 1: Statistics of Our Proprietary Dataset.

Category	Details
VLM Models Covered	Gemini 1.5 Pro. 2.0-Flash, Gemini 2.5 Pro Gemini 2.5 Flash, Qwen-7B-VL, Qwen-72B Claude 3.5 Sonnet, GPT-4o.
ALM Models Covered	Whisper-turbo V3 and Whisper-large V2.
Number of Videos	Over **16,159** Long Videos. Sampled 300
Number of Audios	Over **888**.
Covered Variants	Over **14** Diseases areas. From Nephrology, Ophthalmology to Hematology, Immunology, Dermatology.
Video format Types	**8 types:**. MP4, M4V, QuickTime, WMV, WebM, MSVideo, MPG, and 3GPP.
Audio format Types	**4 types:**. '.mp3', '.wav', '.m4a', '.flac' .
Video Lengths	Major Longer length video from >30 min to over 3 hours.
Language Types	Over 20 languages, including German, Italian, English, Mandarin Hokkien, Hindi, Korean, French, Dutch, Spanish, and more.

Here, we primarily adopt well-established Video-MME (Fu et al., 2025), along with evaluations of major SOTA VLMs, as well as our pharmacycy proprietary dataset shown in Table 1, Figure 10.

Video-MME (Fu et al., 2025) is the first full-spectrum multi-modal evaluation benchmark designed specifically for video-based MLLMs. It stands out from existing benchmarks with several key features: (1) Diversity in video types, covering six primary visual domains with 30 subfields to ensure broad scenario generalizability; (2) Temporal coverage, including short-, medium-, and long-term videos ranging from 11 seconds to 1 hour. It comprises 900 manually selected videos, totaling 254 hours, with 300 videos in each categories.

Furthermore, our findings are validated using proprietary data from 14 disease areas, including over 300 long-form video data points (>30 minutes to over 3 hours, 8+ formats) and 888 audio files.

(a) Original Long Seminar Video (1.5h) (b) Ours w/ defined Output Length (c) Ours w/ Subtitles and covering Agenda

(d) Original Long Lecture Video (0.8h) (e) Frames to Video methods (f) Ours

Figure 2: **Qualitative comparison of our Infinite Video-to-Video Clips pipeline against frame-based approaches** (e.g. Runway Gen-2 (RunwayML, 2023)). Our method supports arbitrary input durations, allows user-defined output lengths, automatically extracts agenda-relevant segments, adds subtitles and vertical playback, while overcoming choppy transitions and frame skipping/freezing, e.g, (e).

Table 2: **Proprietary video dataset (>30 min, up to 3 h) distribution by scientific area**. Video content includes clinical trials, interviews, medical lectures, promotional/non-promotional drug materials (tutorials, advertising), oral presentations, disease case studies, medical imaging/genomics demonstrations (CT scans, microscopy, DNA/sequencing), cancer morphology animations, and public health/disease education.

Scientific Area (A)		Scientific Area (B)	
Area	**Count**	**Area**	**Count**
Oncology	**5824**	Movement Disorder	263
Neuroscience	**3306**	Nephrology	232
Hematology	**2369**	Infectious Disease	155
Not Applicable	1556	Inflammatory Disease	146
Ophthalmology	1664	Dermatology	30
Respiratory Disease	312	Cardiovascular	14
Immunology	282	Metabolism	6

4 Methodology, Business Impact And Technical Features

As shown in Figure 1, our methodology incorporates ALM, VLM, various practical libraries, our cut-and-merge algorithm, prompt injections, and clips selection pipeline. Voiceover transcriptions are extracted from uploaded videos using a predefined schema. Both Whisper V2 (Radford et al., 2022) and V3 (OpenAI, 2023) ALMs are employed for quality control. While V3 offers four times faster processing and more accurate language type detection, V2 produces more complete sentences, refer to Table 3 and Figure 5.

Using these transcription files, we then extract key segments guided by four constraints via Prompt Injections: (1) User-defined output video length, (2) Video type/style (e.g., marketing, training, promotional, educational), (3) Audio alignment with fade-in and fade-out transitions, and (4) Segment selection metrics. These metrics include full-length coverage (especially ensuring inclusion of the beginning and end), emphasis on workflow and transitions, key information presented in the agenda or video introduction, and highlights such as speaker pauses or intonation peaks in audio. For video does not have voiceover we still have VLMs' feature to watch all virtual info through the videos. Finally, instead of directly concatenating all segments, we then apply our cut and merge algorithm to produce the final video clip. Our approach also enables vertical or horizontal playback formats and supports subtitle integration. Below, we summarize the key features of our method.

(1) Infinite Video-to-Infinite Video: Unlike SOTA VLMs which have limitations on video length and storage size, we are capable of seamless integration between video sources of any length. (2) High transparency and customization: allowing users to tailor video clips and remove or enhance specific sections. (3) Scalability and Cost Efficiency: designed for large-scale production, achieving a 94.44% effort reduction for longer video summarization and 88% reduction across all pharmacy video categories compared to manual inspection.

Figure 3: **Processing Time Comparison**: Gemini 2.5 Pro / Flash vs Our Methods for generating video clips script on VideoMME Long Video Dataset. Gemini Pro is the slowest (avg. ~ 120s/video), with peaks on longer videos (e.g.,380s). Flash is faster ($\sim$80–85s) but still slower than our method ($\sim$30–55s), except for one outlier (413s). Our method is in general 3-4x faster.

Figure 4: **Comparison between the Gemini 2.5 Flash, Pro vs our, based on the number of select segments and the quality.** Here, we assess quality based on factors like segment length / numbers or the presence of coherent text. Flash often returns many but fragment segments (e.g. "Video ID: tslKtm6Le1s": 85 piece of segments). Pro tends to pick fewer, longer segments (reflected in its lower segment counts but higher average durations). Our method achieves balanced selection 4.37 segments vs. 7.38 (Gemini 2.5 Pro) and 13.30 (Gemini 2.5 Flash) for final clips.

5 Main Results

How to secure the complex & fast voice extraction? In our pipeline, FFmpeg (FFmpeg developers, 2024) is used for key operations such as format conversion and audio extraction to ensure broad compatibility. It general performs well on 1–2 hour videos with clean audio, averaging costs only 46.38 seconds per video. However, FFmpeg also encounter issues with long filenames, unsupported characters, incorrect encoding or compatibility errors. To handle more complex cases in reality, we also integrate MoviePy (Zulko, 2015) as a fallback solution. MoviePy offers a Pythonic interface for programmatic and efficient audio extraction across video batches. While slightly slower (averaging 64.71 seconds), it delivers comparable extraction quality. This combined approach ensures robust audio processing across a wider range of video files/kinds, with extraction times typically ranging from 10 to 79 seconds, as shown in Table 3).

Fragmented Sentences? Safe and accurate combination of Whisper V3/V2. As illustrated in Figure 1, 5), Whisper V3 (OpenAI, 2023) Whisper V3 offers significant speed improvements (up to 4x faster on industry datasets and VideoMME) and reliable language type detection. However, it often produces fragmented sentences, leading to unstable segmentation and less precise timestamp alignment(see Fig 5). In contrast, Whisper V2 (Radford et al., 2022) Whisper V2 provides more accurate timestamps, crucial for tasks like clip-cutting, and is therefore our primary model. While V2 occasionally excels at capturing full sentences, real-world tests with English videos revealed sporadic language misidentification (e.g., mistaking English for Welsh), resulting in corrupted transcriptions. To address this, we use V3 as a secondary validation layer for security guidance (see Figure 1).

Modality: A Key to Cost Reduction, Speed, Clips coherence As shown in Figures 3 and 4, utilizing ALM for accurate transcription, combined

Table 3: **Processing time comparison in each step.** Experiment setting: Proprietary Dataset and VideoMME, SDPA, FPS=0.01, AWS ml.g5.24xlarge, g5.2xlarge instance. * means Gemini 2.5 Pro has Timeout for longer waiting or error cases. - means not applicable.

			Processing time cost (avg / per video, in seconds)				
Video Type	VLM (Directly Video to Text)	ALM (Transcription by Whisper Turbo V3 V3 vs Large-V2)	FFmpeg/Moviepy (Voice Over abstraction, video to audio file)	LLM (Bedrock Claude Sonnet /Gemini 2.5 Pro Extract Timestamp and improve summary quality)	Cut & Merge Video Clips	Adding Subtitles	Video amount VideoMME / Proprietary Data
Longer video (above 30 minutes long)	Generate Summary and Key Frame Caption 1-4 Min for Gemini 2.5 Pro *	**90.96s** (15.16 Mins in total, Turbo v3 model) **358.74s** (59.79 Mins in total, Large-V2) (Proprietary Data & on g5.24xlarge) *avg, 22.08s (3h for 489 videos on video mme by Turbo V3 model) vs avg, 109s (15h for 493 videos on by Large-V2 model) (on g5.2xlarge)*	**79.2s**	**24.37s**	**30s-1Min**	**4Mins**	**300 / 100**
Medium (2 minutes < length < 30 minutes)	**1-4 Mins**	**17.04s** (2.84 minutes in total, Turbo V3) **59.52s** (9.92 Mins in total, Large-V2)	**29.76s**	**24.37s**	**30s-1mins**	**<4mins**	**300 / 100**
Short (less than 2 minutes)	-	**4.26s** (0.71 minutes In total for turbo)	**10.56s**	-	-	-	**300 / 100**
Total (avg)							**1200**

(a) Accuracy On LibriSpeech & Speed On AWS Hardware.

(b) V3 has more fragment transcriptions (upper V3).

Figure 5: **Qualitative comparison of Whisper V2 vs. V3: transcription accuracy on LibriSpeech (Panayotov et al., 2015) test-clean and inference speed on AWS hardware**. Whisper V3's performance is more sensitive to GPU type—achieving roughly 4–8× speedups and higher Accuracy compared to V2, but cuts speech more aggressively, resulting in increased sentence fragmentation that complicates downstream timestamp alignment and segment merging.

with Gemini 2.5 Pro (text-to-text), significantly reduces costs (up to 4-4.5× less, Table 13) and accelerates processing time (up to 4× faster, 30-55 seconds per video) compared to using Gemini 2.5 Pro on full video input (average 120s, max 350s per video). Our method maintains comparable accuracy in generating less redundant, high coherent, highly informative video clip scripts (258 meaningful words) compared to Gemini 2.5 Pro (325) and Gemini 2.5 Flash (203).

Furthermore, as shown in Table 5, Clips coherence scores (fraction of original segments covered by any summary clips segment), Informativeness (cosine similarity to its best-matching original segment, averaged across segments), and Redundancy scores (mean pairwise cosine similarity among segments (off-diagonal)), our approach efficiently provides comparable coherence (0.348), higher informativeness (0.721), reduced redundancy (0.339), and increased stability.

Gemini 2.5 Flash while generally faster (averaging 80–85 seconds per video) than 2.5 Pro, struggles more with non-English, abstract, or non-verbal video content. Gemini Pro tends to select fewer but longer segments, often influenced by visual information, leading to lower segment counts, higher average durations and standard deviations, and even reduced informativeness scores. Flash, conversely, selects more fragment but shorter clips (see Fig 4).

Audio and Speaker Alignment: Direct Con-

Table 4: **Overall Accuracy of VLMs in summarization on Video-MME.** (A) Overall accuracy on Video-MME (900 videos) with/without audio transcription. (B) Keyframe/time alignment and summary accuracy on long-video subset ($n = 300$). Gemini models achieve high accuracy on meaningful summary, but still struggle with timestamps.

(a) Overall Acc. with/without audio transcription

Model	w/o	w/	Δ
Gemini 2.5 Pro	**84.7**	**85.2**	+0.5
Gemini 1.5 Pro	75.0	81.3	+6.3
Qwen2 -VL	71.2	77.8	+6.6
GPT -4o	69.0	77.2	**+8.2**
LLaVA -Video	76.0	76.9	+0.9
Gemini 1.5 Flash	72.6	75.0	+2.4
Oryx -1.5	67.3	74.9	+7.6
InternVL2.5	67.6	74.0	+6.4
Aria	70.3	72.1	+1.8
LinVT	65.6	71.7	+6.1
TPO	66.2	71.5	+5.3

(b) Long-video Keyframe & Summary Accuracy

Method	Summary Acc. (%)
Gemini 2.5 Flash	**94.6**
Qwen -7b	74.3

Method	KeyFrame Time Acc. (%)
Gemini 2.5 Flash	**35.1**
Qwen -7b	5.4

Table 5: **Clip Coherence Scores / Informativeness based on Video-MME Benchmark (All Sampled Long Videos, $n = 300$) @ $\tau = 0.6$. Our Method:** Concise, 4× faster, 3.5–4× cheaper, consistently informative (0.721 informativeness, low redundancy 0.339). **Gemini 2.5 Pro:** Best logical flow but slower, more expensive, less consistent. **Gemini 2.5 Flash:** Overly long, fragmented, highly unpredictable summaries with high deviation.

Metric	Our Method	Gemini 2.5 Pro	Gemini 2.5 Flash
Clip Coherence scores (0-1) (How logically connected adjacent clips are)	0.348 ± 0.118	$\mathbf{0.446 \pm 0.111}$	0.410 ± 0.127
Informativeness scores (0-1) (How well summary clips represent the source)	$\mathbf{0.721 \pm 0.078}$	0.674 ± 0.158	0.701 ± 0.124
# Segments number of clips	6.46 ± 1.67	9.21 ± 10.40	$\mathbf{18.32 \pm 31.03}$
Redundancy Scores (Overlap among clips) (0-1)	$\mathbf{0.339 \pm 0.106}$	0.415 ± 0.117	0.379 ± 0.138
Clips meaningful text length	258.3	**325.6**	203.5
Speed(Generation time per clips)	**30–55s / video**	120s avg / video	**80–85s avg / video**
Cost in Dollar	**0.3 input / 2.5 output per M Token**	1.25 input / 10 output per M Token	0.3 input / 2.5 output per M Token

catenation Will Not Work! As shown in Figures 2(e), directly concatenating video segments using frame-level and ALM-generated timestamps often results in frame jumps and background noise. To address this, we developed an algorithm that combines segment encoding (for noise reduction) with audio/video fade-in and fade-out transitions (+/- 0.5 seconds for smooth transitions). This approach avoids the visual and auditory glitches typically seen with direct FFmpeg concatenation. Furthermore, we standardize ALM-generated timestamps to two decimal places to improve segment precision and overall clip smoothness. Figures 2(e)–(f) clearly demonstrate the advantages of our method: where other approaches show at the same timestamp a frozen eye or losing frames, but our transitions consistent with the original video.

Personalization: Prompt Injection, Role Definition, and Selection Metrics. In prompting, users can select a role and specify a maximum duration for video clips (e.g., up to 3-4 min-

utes). Additionally, the current process guides Gemini 2.5 Pro to explain its reasoning for selecting specific segments (See Appendix Figure 11, Table 12. This enables Gemini 2.5 to focus on key factors, such as smoothly transitions (finishing speaker's sentence), important key segments presented agenda topics/slides, keywords, full-length coverage, speaker's voice and pauses, and noun emphasis, rather than being distracted by numerous unrelated elements.

6 Ablation study on Role Definition and Prompt injections

How does each segment's metrics play a different role in the final outcome? We investigate how our segment metrics shape the final outcome by conducting an ablation that isolates those factors: (i) Keywords, ii) Agenda, (iii) speaker-voice tone. As shown in Figure 7, 1) Removing tone consistency can lead to visual-voice mismatches, 2) Agenda helps ensure clips retain key information, para-

(a) single-image-to-video (Runway)

(b) Frames-to-video (OpusClip)

(c) Ours w/ Subtitles

Figure 6: **Qualitative comparison of our Infinite Video-to-Infinite Video pipeline against single-image-to-video baselines and commercial tools** (e.g., Runway Gen-2 (RunwayML, 2023), OpusClip (OpusClip, 2023)). While existing methods generate from one or a few static frames, limited to 30s outputs, prone to choppy transitions and frame skipping (panel e), and relying on shot-selection heuristics. Our methods support arbitrary input durations, user-specified output lengths, optional subtitles, and vertical playback.

(a) Agenda

(b) Keywords

(c) Speaker tone

Figure 7: **Impact of role definition and prompt-selection metrics.** Agenda and keyword alignment ensure coverage of key sections; speaker tone, transitions, and fade-in/out reduce visual–voice mismatch and jump cuts; full-length coverage prevents unfinished and fragmented clips.

graphs, and segments, 3) Incorporating keywords (e.g., nouns, medical terms) increases the likelihood of important information being captured in segments, 4) Length coverage can prevents abrupt, incomplete clips, jump cut and sudden Ending.

7 Conclusion

In this work, we introduce a novel industrial, practical video-to-video clip highlights framework. This addresses the critical need for efficient video summarization and highly customizable video clip generation from long-form content. Our framework significantly facilitates content reuse in industrial settings by enabling users to generate diverse clips cost-effectively, reducing processing time from hours to mere minutes. Our key contributions include: (i) Cut & Merge algorithm that ensures smooth transitions through fade-in/out boundaries and timestamp normalization; (ii) Personalization mechanism using role definition and prompt injection to generate clips tailored for regulatory, educational, or promotional contexts; and (iii) end-to-end

framework that leverages ALM pipelines for efficiency and VLM-enhanced processing for visual-heavy content. Evaluations on Video-MME and a proprietary dataset of long-form videos across 14 disease areas demonstrate 3–4× speedups, 4× cost reduction, and competitive clip quality compared to state-of-the-art VLM baselines.

We further highlight following key findings: 1) Modality matters, using voice transcriptions as a single modality can achieve very fast, high-quality clips at a very low cost. 2) Models like Gemini 2.5 Pro/Flash often rely on external tools (e.g., Google Search or Data APIs) rather than processing frame by frame, which can cause losing focus and produce fragmented segments. 3) Combining sophisticated prompt Injections —including transitions, agenda topics, keywords, full-length coverage, speaker voice/pauses — substantially enhances the final quality of the generated clips, surpassing the results of direct concatenation.

8 Limitations

Our methodology focuses on applying Vision–Language Models (VLMs) to life sciences, rather than proposing entirely new model architectures. A main limitation of this study is to focus on justification of the domain-specific benefits. We provide a baseline comparison of more than eleven VLMs using both the Video-MME benchmark and our proprietary dataset. Future work should extend this line of research to other regulated domains, such as financial services and manufacturing, to further validate the generalizability of framework.

References

Animoto. 2024. Animoto: Image + text → video clip generation. Web-based video creator; builds short visuals using static images and prompts/text.

Jinze Bai, Shuai Bai, Shusheng Yang, Shijie Wang, Sinan Tan, Peng Wang, Junyang Lin, Chang Zhou, and Jingren Zhou. 2023. Qwen-vl: A versatile vision-language model for understanding, localization, text reading, and beyond. *arXiv preprint arXiv:2308.12966*.

Aayush Bansal, Shugao Ma, Deva Ramanan, and Yaser Sheikh. 2018. Recycle-gan: Unsupervised video retargeting. In *European Conference on Computer Vision (ECCV)*.

Tim Brooks, Bill Peebles, Connor Homes, Will DePue, Yufei Guo, Leo Jing, Daniel Schnurr, Jason Taylor, Troy Luhman, Eric Luhman, C. W. Y. Ng, R. Wang, and Aditya Ramesh. 2024. Video generation models as world simulators. OpenAI Technical Report.

Otesteanu Corin and Qiang Li. 2021. All you need is cell attention: Acell anno-tation tool for single-cell morphology data.

DeepBrain AI. 2024. Deepbrain ai: Image-based video synthesis with prompts. Commercial AI platform; synthesizes video clips from a still image guided by textual input.

ElevenLabs. 2023. How to use ai for creating dynamic video narratives. Company blog; describes using ElevenLabs' text-to-speech API to generate natural narration for AI-generated videos.

FFmpeg developers. 2024. Ffmpeg: A complete, cross-platform solution to record, convert and stream audio and video. FFmpeg Documentation.

Chaoyou Fu, Yuhan Dai, Yongdong Luo, Lei Li, Shuhuai Ren, Renrui Zhang, Zihan Wang, Chenyu Zhou, Yunhang Shen, Mengdan Zhang, Peixian Chen, Yanwei Li, Shaohui Lin, Sirui Zhao, Ke Li, Tong Xu, Xiawu Zheng, Enhong Chen, Caifeng Shan, Ran He, and Xing Sun. 2025. Video-mm e: The first-ever comprehensive evaluation benchmark of multi-modal llms in video analysis. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 24108–24118.

Google DeepMind. 2025. Gemini 2.5: Multi-modal foundation models for text, image, audio, and video understanding. https://deepmind.google/discover/blog/gemini-2-5-updates/. Accessed: 2025-09-29.

Yanan Guo, Wenhui Dong, Jun Song, Shiding Zhu, Xuan Zhang, Hanqing Yang, Yingbo Wang, Yang Du, Xianing Chen, and Bo Zheng. 2025. Fila-video: Spatio-temporal compression for fine-grained long video understanding. *arXiv preprint arXiv:2504.20384*.

Yawen Guo, Xiao Liu, Anjana Susarla, and Rema Padman. 2024a. Go to youtube and call me in the morning: Use of social media for chronic conditions. *Management Information Systems Quarterly*.

Yawen Guo, Xiao Liu, Anjana Susarla, and Rema Padman. 2024b. Go to youtube and call me in the morning: Use of social media for chronic conditions. *Management Information Systems Quarterly*.

HeyGen. 2024. Heygen: Ai avatar-based video clip generation.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. 2022. Video diffusion models. In *NeurIPS*.

Ming Hu, Kun Yuan, Yaling Shen, Feilong Tang, Xiaohao Xu, Lin Zhou, Wei Li, Ying Chen, Zhongxing Xu, Zelin Peng, Siyuan Yan, Vinkle Srivastav, Diping Song, Tianbin Li, Danli Shi, Jin Ye, Nicolas Padoy, Nassir Navab, Junjun He, and Zongyuan Ge. 2024. Ophclip: Hierarchical retrieval-augmented learning for ophthalmic surgical video-language pretraining. *arXiv preprint arXiv:2411.15421*.

Songtao Jiang, Yuan Wang, Sibo Song, Yan Zhang, Zijie Meng, Bohan Lei, Jian Wu, Jimeng Sun, and Zuozhu Liu. 2025. Omniv-med: Scaling medical vision-language model for universal visual understanding. *arXiv preprint arXiv:2504.14692*.

Kaiber AI. 2024. Kaiber ai: Single image-to-video with prompt-driven animation.

Sergej Lackmann, Pierre-Majorique Léger, Patrick Charland, Caroline Aubé, and Jean Talbot. 2021. The influence of video format on engagement and performance in online learning. *Brain Sciences*, 11:128.

Min Jung Lee, Dayoung Gong, and Minsu Cho. 2025a. Video summarization with large language models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

Min Jung Lee, Dayoung Gong, and Minsu Cho. 2025b. Video summarization with large language models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

Zhuoling Li, Hossein Rahmani, Qiuhong Ke, and Jun Liu. 2025. Longdiff: Training-free long video generation in one go. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

Kangning Liu, Shuhang Gu, Andres Romero, and Radu Timofte. 2021. Unsupervised multimodal video-to-video translation via self-supervised learning. In *Proceedings of the IEEE Conference on Applications of Computer Vision (WACV)*.

Tianrui Liu, Qingjie Meng, Athanasios Vlontzos, Jeremy Tan, Daniel Rueckert, and Bernhard Kainz. 2020. Ultrasound video summarization using deep reinforcement learning. *arXiv preprint arXiv:2005.09531*.

OpenAI. 2023. Gpt-4 technical report. *CoRR*, abs/2303.08774.

OpenAI. 2023. Introducing whisper large-v3. OpenAI Blog / Model Card.

OpusClip. 2023. Opusclip: Ai-powered clip generation from long-form video content.

Corin Otesteanu, Martina Ugrinic, Gregor Holzner, Yun-Tsan Chang, Christina Fassnacht, Emmanuella Guenova, Stavros Stavrakis, Andrew deMello, and Manfred Claassen. 2021. A weakly supervised deep learning approach for label-free imaging flow-cytometry-based blood diagnostics. *Cell Reports Methods*.

Vassil Panayotov, Guoguo Chen, Daniel Povey, and Sanjeev Khudanpur. 2015. Librispeech: an asr corpus based on public domain audio books. In *Acoustics, Speech and Signal Processing (ICASSP), 2015 IEEE International Conference on*, pages 5206–5210. IEEE.

Pika Labs. 2024. Pika labs: Animate still images or frames into video.

Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. 2022. Robust speech recognition via large-scale weak supervision (whisper).

RunwayML. 2023. Runway gen-2. https://runwayml.com/. Accessed: 2025-06-01.

Zirui Shang, Yubo Zhu, Hongxi Li, Shuo Yang, and Xinxiao Wu. 2024. Video summarization using denoising diffusion probabilistic model. *arXiv preprint arXiv:2412.08357*.

Yan Shu, Peitian Zhang, Zheng Liu, Minghao Qin, Junjie Zhou, Tiejun Huang, and Bo Zhao. 2024. Video-xl: Extra-long vision language model for hour-scale video understanding. *arXiv preprint arXiv:2409.14485*.

Murali Srinivasan, Porawit Kamnoedboon, Dusit Nantanapiboon, Piero Papi, and Umberto Romeo. 2025. Non-surgical management of peri-implantitis with photodynamic therapy: A systematic review and meta-analysis of clinical parameters and biomarkers. *Journal of Dentistry*.

Stability AI. 2024. Stable video diffusion: Image-to-video generation from a single frame.

Synthesia. 2024. Synthesia: Ai avatars and voice-based video clips.

Amara Tariq, Rimita Lahiri, Charles Kahn, and Imon Banerjee. 2025a. Position: Restructuring of categories and implementation of guidelines essential for vlm adoption in healthcare.

Amara Tariq, Rimita Lahiri, Charles Kahn, and Imon Banerjee. 2025b. Position: Restructuring of categories and implementation of guidelines essential for vlm adoption in healthcare. In *Proceedings of the 2025 Conference on Vision-Language Models in Healthcare*.

Carl Vondrick, Hamed Pirsiavash, and Antonio Torralba. 2016. Generating videos with scene dynamics. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 29.

TingChun Wang, MingYu Liu, JunYan Zhu, Guilin Liu, Andrew Tao, Jan Kautz, and Bryan Catanzaro. 2018. Video-to-video synthesis. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 31.

Yimu Wang, Xuye Liu, Wei Pang, Li Ma, Shuai Yuan, Paul Debevec, and Ning Yu. 2025. Survey of video diffusion models: Foundations, implementations, and applications. *arXiv preprint arXiv:2504.16081*.

Yuetian Weng, Mingfei Han, Haoyu He, Xiaojun Chang, and Bohan Zhuang. 2024. Longvlm: Efficient long video understanding via large language models. *arXiv preprint arXiv:2404.03384*.

Siqi Wu, Marian-Andrei Rizoiu, and Lexing Xie. 2018. Beyond views: Measuring and predicting engagement in online videos. In *Proceedings of the International AAAI Conference on Web and Social Media (ICWSM)*.

Zhen Xing, Qijun Feng, Haoran Chen, Qi Dai, Han Hu, Hang Xu, Zuxuan Wu, and Yu-Gang Jiang. 2023. A survey on video diffusion models. *ACM Computing Surveys*.

Xu Yan, Xinyang Zhang, Pieter Abbeel, and Aravind Srinivas. 2021. Videogpt: Video generation using vq-vae and transformers. *arXiv preprint arXiv:2104.10157*.

Shentao Yang, Haichuan Yang, Linna Du, Adithya Ganesh, Bo Peng, Boying Liu, Serena Li, and Ji Liu. 2025a. Swat: Statistical modeling of video watch time through user behavior analysis. In *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining V.1*, KDD '25. Association for Computing Machinery.

Xindi Yang, Baolu Li, Yiming Zhang, Zhenfei Yin, Lei Bai, Liqian Ma, Zhiyong Wang, Jianfei Cai, Tien-Tsin Wong, Huchuan Lu, and Xu Jia. 2025b. Towards physically plausible video generation via vlm planning. *arXiv preprint arXiv:2503.23368*.

Yuanhan Zhang Bo Li Songyang Zhang Wangbo Zhao Yike Yuan Jiaqi Wang Conghui He Ziwei Liu Kai Chen Dahua Lin Yuan Liu, Haodong Duan. 2023. Mmbench: Is your multi-modal model an all-around player? *arXiv:2307.06281*.

Jingyi Zhang, Jiaxing Huang, Sheng Jin, and Shijian Lu. 2024. Vision-language models for vision tasks: A survey. *IEEE Trans. Pattern Anal. Mach. Intell.*

Zachary Zulko. 2015. Moviepy: Video editing with python. https://github.com/Zulko/moviepy.

A   Appendix

In this section we provide the supplementary compiled together with the main paper includes:

Our Algorithm for Audio Fade-In and Fade-Out to improve transition alignment, as shown in Algorithm 1; Personalization and Key Segments Logic, along with sample outputs in Figure 8, 11 and Table 14; Our video Clips landing scenarios on medical domain in Figure 9, Table 6; The VideoMME Dataset, detailed in Table 10; Ablation Study on exciting video clip generation SaaS solutions, presented in Tables 7, 8 9, 10; Gemini Video-to-Text Limitations, including issue analysis and failure case examples in Figure 11, the cost breakdown in Table 13.

Algorithm 1 Clip Extraction & Merge Pipeline using Fade In & Out

---

Require: segments_json_path, input_video_path, clips_output_dir, merge_list_file, final_output_path

1: **mkdir**(clips_output_dir)   ▷ ensure output exists
2: data ← read_json(segments_json_path)
3: open merge_list_file for writing
4: **for all** (i, seg) **in** enumerate(data.selected_segments) **do**
5:     start ← seg.start;   end ← seg.end
6:     clip_path ← clips_output_dir/clip_{i}.mp4
7:     **cmd** ← [
   "ffmpeg", "-y",
   "-ss", start, "-to", end,
   "-i", input_video_path,
   "-vf", "format=yuv420p",
   "-af", "afade=in:0:0.5,afade=out:(end-start-0.5):0.5",   ▷ Audio fade
   "-c:v", "libx264", "-preset", "fast", "-crf", "23",   ▷ Avoid direct concatenation '-c copy'
   "-c:a", "aac", "-b:a", "128k", ▷ Re-encoding clips
   clip_path
8:     ]
9:     run(cmd)   ▷ generate each clip
10:    Post-select ″file 'clip_path'″ to merge_list_file
11: **end for**

(a) Prompt Logic

(b) Generated Highlights Clips Scripts

Figure 8: **Key Segments Selection Logic.** This logic has four main components: Role: Defining the role for GenAI in tasks. Output Requirements: Specifically on timestamp format for uniformity and error avoidance, and rephrasing needs. Example Output: Providing examples for clip script files. Core Task Definition: This includes segment selection criteria that cover key ideas, transitions, agenda points, distributed throughout the video (including beginning and end sections if relevant). For videos, consider the speaker's tone and pauses for smooth clip flow. Users can also input the role and additional requirements.

(a) Healthcare Innovation Talks (b) Medical Conference Retro (c) Medical Forum

(d) Podium Speech (e) Treatment Notes (f) Educational / Promotional Clip

Figure 9: **Sampled video inputs**: medical interview and lecture styles processed by our pipeline (talk-show interview, keynote remark, forum lecture, podium speech, treatment-slide session, and educational/promo clips).

Figure 10: **Comparison of the Video-MME (Fu et al., 2025) and MMBench-Video datasets (Yuan Liu, 2023) in terms of video categories and duration distributions.** The Video-MME dataset consists of 900 videos spanning six primary visual domains with 30 subfields, categorized into 300 short-term (<2 min), 300 medium-term (4-15 min), and 300 long-term (30-60 min) videos.

Landing scenarios	Patients/Doctors Interviews Listening
Consolidate summary across interviews - *Q1: Consolidate summaries for each interview quickly and cost-effectively via our pipeline?*	**Dr. Tolaney:** Presents a study showing low rates of hypersensitivity with Phesgo, supporting its home administration. She outlines the benefits of home administration for patient quality of life and identifies suitable patient populations and implementation challenges.
Dr. Crockford: Provides instructions on preparing and administering Phesgo as a subcutaneous injection, highlighting steps like gathering supplies, cleaning, drawing the correct dose, and patient monitoring.
Dr. Verrill: Discusses the development of subcutaneous drugs like Herceptin and Phesgo, emphasizing improved patient experience by moving administration out of hospitals to more convenient locations. He also covers dosing, safety, and training.
Dr. Loibl: Discusses the AFFINITY trial, which demonstrated an overall survival benefit for adding pertuzumab to trastuzumab and chemotherapy in HER2+ early breast cancer patients with higher risk factors, particularly those with node involvement..
Track who said what at when - *Q2: Would you prefer to use Phesgo in the neoadjuvant setting and in which patient population, or in adjuvant Residual Disease?*	**Dr. Tolaney:** mentions its use in the adjuvant setting after completion of chemotherapy for a year of therapy (segments 40-43, approx. 3:12.12-3:28.12). She also describes its use after pre-operative (neoadjuvant) therapy if a patient achieves a PCR and needs to complete a year of HER2-targeted therapy (segments 48-49, approx. 3:38.64-3:48.52). She states, 'In the preoperative setting, we're usually giving chemo with PheSGO so that wouldn't make sense [for home administration as they are coming in for chemo]' (segments 45-47, approx. 3:31.64-3:38.64)
Dr. Crockford: mentions his unit has been using 'FESCO' (Phesgo) 'for the last four years in the metastatic neoadjuvant and adjuvant setting' (segment 2, 0:20.52-0:25.76). This confirms its use in these settings but his interview focuses on the practical administration rather than clinical decision-making or preference between neoadjuvant and adjuvant residual disease, or specific patient populations beyond general HER2-positive eligibility.
Dr. Verrill: discusses his center's involvement with 'FESGO' (Phesgo) starting with the Federica trial and rapid transition to its use once commercially available (segments 5-8, approx. 0:41.58-1:06.76). He mentions giving Phesgo with chemotherapy (segment 53, approx. 5:43.44-5:51.02: 'because they're getting chemotherapy at the same time patients are usually in the hospital when they get the first doses of subcut treatment'), which is common in the neoadjuvant setting and potentially for concurrent adjuvant chemotherapy. He also discusses patients continuing treatment after chemotherapy, fitting the adjuvant setting. He states, 'most people having chemotherapy sitting in a chair' (segment 44, approx. 4:57.9-5:05.18) in the context of identifying patients for Phesgo.
Dr. Loibl: focuses entirely on the AFFINITY trial results, which investigated the addition of (IV) pertuzumab to trastuzumab and chemotherapy. Phesgo is not mentioned in her transcript.
Key theme per molecules, trial/drugs- *Q3: In light of upcoming Destiny Breast-09 readout, do you believe that all patients would need Phesgo till progression or would you consider induction Phesgo followed by Perjeta - Herceptin maintenance strategy, for which patients and what data you would need to see to implement that*	**Dr. Tolaney:** does not explicitly state a *preference* for neoadjuvant vs. adjuvant residual disease, but describes its current use in both contexts where appropriate (adjuvant after chemo, or continuing HER2 therapy post-neoadjuvant chemo/surgery if PCR achieved).
Dr. Crockford: mentions his unit has been using 'FESCO' (Phesgo) 'for the last four years in the metastatic neoadjuvant and adjuvant setting' (segment 2, 0:20.52-0:25.76). This confirms its use in these settings but his interview focuses on the practical administration rather than clinical decision-making or preference between neoadjuvant and adjuvant residual disease, or specific patient populations beyond general HER2-positive eligibility.
Dr. Verrill: doesn't express a specific preference for neoadjuvant versus adjuvant residual disease for Phesgo itself, nor does he detail specific patient population criteria beyond HER2-positivity. His focus is on decentralization and patient experience.
Dr. Loibl: interview focuses entirely on the AFFINITY trial results, which investigated the addition of (IV) pertuzumab to trastuzumab and chemotherapy. Phesgo is not mentioned in her transcript.

Table 6: **Landing scenario: Structured medical interview Q&A output from our pipeline.** Given multiple expert interviews, the pipeline extracts, identifies, and consolidates opinions around specific clinical queries (e.g., Phesgo usage). As queries become more domain-specific and knowledge-intensive, our system effectively handles such cases with precise localization of quoted statements. This demonstrates how structured summarization can support rapid evidence synthesis from long-form medical interviews.

Figure 11: **Gemini 2.5 's direct video-to-text feature still struggles with accurate timestamps** — for example, in a 10-minute video, it incorrectly selects a timestamp at the 15-minute mark.

Table 7: AI Video Generators from Video API (Commercial)

Company / Startup	Use case & Key features
DeepBrain API	Talking avatars; stylized visuals for short reels.
Runway API	Raw video generation from text prompts.
ElevenLabs + D-ID	Generate audio and sync to an avatar face; entertainment-industry grade.
Stability AI Sora	Image-to-video with full-scene 3D generation.

Table 8: AI Video Generators from Keyframe Images (Commercial)

Company / Startup	Use case & Key features
Kaiber	Turn images or music into animated videos; stylized visuals for music videos and short reels.
Animoto	Slideshow-style video maker with text overlays, captions, and voice-over to produce professional clips.

Table 9: AI Video Generators from Text / Transcript (Commercial)

Company / Startup	Use case & Key features
Runway Gen-2	Text-to-video or transform still images into 5–10s motion clips; very strong generative capability (e.g. "flying car from a static image").
Pika Labs	Generate short cinematic clips from prompts or stills; excellent for storytelling and scene/character animation.
Synthesia	Create talking-head videos from scripts, with avatars speaking multiple languages—ideal for explainers and tutorials.
HeyGen	Avatar-based video generation from transcripts; high-quality avatars with realistic lip-sync.
Veed.io	Video editing plus AI generation and stock templates; combines text, images, voice-over, and stock clips.

Table 10: AI Video Generators from Open Source Git (Open-source)

Git tool	Use case & Key features
Story Diffusion	Generate a short story video from a script: Script → Scenes → Image generation → Video stitching.
OpenVPI / Wav2Lip	Sync lip movements to speech by taking a face image + audio and producing a synced talking face.
Genmo AI (free tier + API)	Generate stylized videos from text or stills; partially open/research-based access.
Deforum	Create motion videos from prompts or image sequences, built on Stable Diffusion with animation configs.
OpenTalk / SadTalker	Educational or narrator-style talking-face generation from a still image + audio.

Table 11: **Gemini 2.5 Pro Multimodal Reasoning Chain** for Fail-Case Video ID: vDzNVHXc66U from Video-MME. It demonstrates the logic behind Gemini 2.5 Pro's processing steps after a video upload. Notably, extensive metadata retrieval via the Google Search API or related services occurs even before Gemini really "watching" the video content, as highlighted in blue.

Step	Description
Reframing the Approach	I'm now shifting my focus to analyzing the video itself, as the transcript proved unhelpful. The user's prompt suggests a direct video-analysis approach is required to create an effective highlight reel.
Adjusting the Strategy	I've realized that my previous approach, despite using use_audio_video_tokens=True, didn't adequately focus on the visual content. My initial prompt was still too centered on spoken words.
Implementing Visual Analysis	The previous try was ineffective due to the useless transcript. Now, I'm concentrating on the video's visual elements: requesting start/end times and scene descriptions, then formatting the output as JSON with visual cues in place of spoken text.
Exploring Visual Content Extraction	I'm currently trying to extract key segments from the video based on visual content. My initial strategy with YouTube failed, so I'm exploring object-detection and scene-recognition models to pinpoint visually important elements.
Assessing Metadata Retrieval	I've hit a roadblock with direct visual analysis due to a TypeError when using the YouTube tool. I'm pivoting to retrieving video metadata via YouTube.
Refocusing on Metadata	After the TypeError, I re-examined the problem and refocused on retrieving video metadata via YouTube. While not ideal, it's the only remaining path given the current tool limitations.
Investigating Video Content	I'm still trying to extract key visual segments. Both transcript and metadata strategies have failed, so I'm exploring alternative APIs and CV toolkits to process the raw frames directly.
Reframing Approach to the Video	I re-evaluated the YouTube tool's requirements: it needs a valid video_id. The provided URL https://www.youtube.com/watch?v=vDzNVHXc66U may be a placeholder, so I'm testing with a dummy ID ('0') to probe the tool's behavior.
Pivoting Strategy for Video ID	Recognizing the unusual link, I'm now assuming '0' is the ID and calling YouTube again to retrieve title/description and verify whether any metadata is accessible.
Facing Technical Roadblocks	Critical tool failures persist, halting any attempt to identify visual segments. I'm investigating workarounds but the issues remain unresolved.
Pinpointing Analysis Limitations	I've hit a wall: the audio transcript is useless gibberish, visual-analysis calls error out, and metadata retrieval fails.
Identifying Processing Barriers	I'm unable to process the video or extract information. Neither transcript, CV pipelines, nor metadata calls succeed. I cannot fulfill the request at this time.

Table 12: **Personalization via Gemini 2.5 Pro Multimodal Reasoning**: Side-by-side showing Gemini "thinking chains" for generating marketing-promo vs. training videos clips, showing how transcript segments are selected and formatted into JSON for clip generation.

Step	Marketing/Promo Pipeline	Training/Instruction Pipeline
Reframing the Approach	Focus on brand hooks and emotional leads: "Which moments sell the product benefit?"	Focus on concept clarity and tool intros: "Which segments clearly explain 'what and why'?"
Adjusting the Strategy	Emphasize calls-to-action, upbeat music cues, logo reveals.	Emphasize step-by-step demos, key terminology definitions, "do's don'ts."
Segment Selection	Pick high-impact visuals: product shots, testimonials, USPs.	Pick explanatory visuals: UI walkthroughs, process flows, compliance notes.
JSON Formatting	Output as promo video segments with start/end/text JSON for ad-style snippets.	Output as training video segments with start/end/text JSON for tutorial modules.
Immersive Update	Update the existing immersive ('id="promo video segments"') to focus on marketing highlights.	If persona changes, replace that immersive with 'id="training video segments"' containing tutorial clips.

Table 13: Comparison of Paid Tier Pricing for Gemini 2.5 Models (per 1M tokens in USD)

Pricing (USD per 1M tokens)	Gemini 2.5 Pro	Gemini 2.5 Flash	Gemini 2.5 Flash-Lite Preview
Input Price	1.25 (200k tokens), 2.50 (> 200k tokens)	0.30 (text/image/video), 1.00 (audio)	0.10 (text/image/video), 0.50 (audio)
Output Price	10.00 (200k tokens), 15.00 (> 200k tokens)	2.50	0.40
Context Caching	0.31 (200k tokens), 0.625 (> 200k tokens), 4.50 / 1M tokens	0.075 (text/image/video), 0.25 (audio), 1.00 / 1M tokens	0.025 (text/image/video), 0.125 (audio), 1.00 / 1M tokens
Grounding with Google Search	1,500 RPD (free), then $35 / 1,000 requests	1,500 RPD (free), then $35 / 1,000 requests	1,500 RPD (free), then $35 / 1,000 requests

Table 14: **Personalized Video Clips Comparison of Selected Segments for Marketing/Promo vs. Training/Educational Clips** based on same input 10mins Youtube video: FwOTs4UxQS4 using Gemini 2.5 Flash (Direct Video to Text). Different goals call for different segment selections: Marketing clips emphasize high-impact openings, motivational statements, famous expert mentions, pro tips, and distinctive traits of AI agents—highlighted in blue. In contrast, training clips prioritize a structured explanation of concepts, such as the three-level AI framework, detailed characteristics of LLMs and workflows, hypothetical examples. Here, Gemini 2.5 still struggles with generating correct timestamps, as highlighted in red.

Timestamp (s)	Marketing/Promotion Clips	Training/Educational Clips
0.2–17.1	... the most important sentence in this entire video, the one massive change that has to happen in order .....the human decision maker, to be replaced by an LLM.	–
19.1–23.9	... most explanations of AI agents is either too technical or too basic.	... most explanations of AI agents is either too technical or too basic. This video is meant for people like myself.
34.4–48.4	...No matter how many steps we add, this is still just an AI workflow...	–
38.4–55.2	...follow a simple 1-2-3 learning path by building on concepts you already understand, like ChatGPT, and then moving on to AI workflows, and then finally AI agents. All the while using examples you'll actually encounter in real life.	–
49.3–52.0	Pro tip: Because of this, the most common configuration for AI agents is the ReAct framework...	–
3.2–22.3	... key trait of AI agents is their ability to iterate.... rewrite the prompt to make the LinkedIn post funnier? ...the human,..repeat this iterative process a few times to get something	–
48.2–63.4	... real world AI agent example. Andrew Ng is a pre-eminent figure in AI, ... created this demo website that illustrates how an AI agent works... And then it's acting by looking at clips in video footage, ...indexing that clip, and then returning that clip to us.	–
36.3–59.5	Level three: AI agents. The AI agent receives a goal and the LLM performs reasoning to determine how best to achieve the goal,... The key trait here is that the LLM is the decision maker in the workflow.	–
107.5–119.0	–	Kicking things off at level one, large language models. Popular AI chatbots like ChatGPT,...are applications built on top of large language models, LLMs, ...fantastic at generating and editing text.
157.0–214.0	–	... two key traits of large language models. First, despite being trained on vast amounts of data, they have limited knowledge of proprietary information: like our personal information or internal company data. Second, LLMs are passive - they wait for our prompt and then respond,..
218.0–222.0	–	Moving to level two, AI workflows. Let's build on our example...
304.0–316.0	–	This is a fundamental trait of AI workflows. They can only follow predefined paths set by humans... this path is also called the control logic.
527.0–534.0	–	All right, level three, AI agents. Continuing the make.com example...
600.0–617.0	... this is the most important sentence in this entire video, the one massive change that has to happen in order for this AI workflow to become an AI agent is for me, the human decision maker, to be replaced by an LLM.	...and this is the most important sentence in this entire video, ...the human decision maker, to be replaced by an LLM.
649.0–702.0	Pro tip: ...the most common configuration for AI agents is the ReAct framework. All AI agents must reason and act, so ReAct.	Pro tip: Because of this, the most common configuration for AI agents is the ReAct framework. ..., so ReAct. Sound simple once we break it down, right?
703.0–722.0	–	A third key trait of AI agents is their ability to iterate. Remember when I had to manually rewrite the prompt to make the LinkedIn post funnier? I, the human, probably need to repeat this iterative process a few times to get something I'm happy with...
748.0–800.0	–	That was a hypothetical example... move on to a real world AI agent example. Andrew Ng is a pre-eminent figure in AI, and he created this demo website that illustrates how an AI agent works.
911.0–959.0	–	To wrap up, ...the three levels ... Level one, ... input and the LLM responds with an output...Level two, .. input and tell the LLM to follow a predefined path ... The key trait ... the human programs a path for the LLMs to follow. Level three, the AI agent receives a goal ... LLM is the decision maker in the workflow.