Robust Models are less Over-Confident

Abstract

Despite the success of convolutional neural networks (CNNs) in many academic benchmarks for computer vision tasks, their application in the real-world is still facing fundamental challenges. One of these open problems is the inherent lack of robustness, unveiled by the striking effectiveness of adversarial attacks. Current attack methods are able to manipulate the network's prediction by adding specific but small amounts of noise onto the input. In turn, adversarial training (AT) aims to achieve robustness against such attacks and ideally a better model generalization ability by including adversarial samples in the trainingset. However, an in-depth analysis of the resulting robust models beyond adversarial robustness is still pending. In this paper, we empirically analyze a variety of adversarially trained models that achieve high robust accuracies when facing state-of-the-art attacks and we show that AT has an interesting side-effect: it leads to models that are significantly less overconfident with their decisions even on clean data than non-robust models. Further, our analysis of robust models shows that not only AT but also the model's building blocks (like activation functions and pooling) have a strong influence on the models' prediction confidences.

1 Introduction

Convolutional Neural Networks (CNNs) have been shown to successfully solve problems across various tasks and domains. However, distribution shifts in the input data can have a severe impact on the prediction performance. In real-world applications, these shifts may be caused by a multitude of reasons including corruption due to weather conditions, camera settings, noise, and maliciously crafted perturbations to the input data intended to fool the network (adversarial attacks). In recent years, a vast line of research (e.g. [24, 35, 43]) has been devoted to solving robustness issues, highlighting a multitude of causes for the limited generalization ability of networks and potential solutions to facilitate the training of better models.

A second, yet equally important issue that hampers the deployment of deep learning based models in practical applications is the lack of calibration concerning prediction confidences. In fact, most models are overly confident in their predictions, even if they are wrong [30, 44, 55]. Specifically, most conventionally trained models are unaware of their own lack of expertise, i.e. they are trained to make confident predictions in any scenario, even if the test data is sampled from a previously unseen domain. Adversarial examples seem to leverage this weakness, as they are known to not only fool the network but also to cause very confident wrong predictions [45]. In turn, adversarial training (AT) is known to improve the prediction accuracy under adversarial attacks [22, 24, 63, 85]. Yet, a systematic synopsis of the two aspects, adversarial robustness and prediction confidence is still pending.

In this work, we provide an extensive empirical analysis of diverse adversarially robust models concerning their prediction confidences. Therefore, we evaluate the prediction confidences of more than 70 adversarially robust models and their conventionally trained counterparts that show low

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

robustness when exposed to adversarial examples. By measuring their predictive distributions on benign and adversarial examples for correct and erroneous predictions, we show that adversarially trained models have benefits beyond adversarial robustness and are less over-confident.

To cope with the lack of calibration in conventionally trained models, Corbière et al. [13] propose to rather use the true class probability than the standard confidence obtained after the Softmax layer, such as to circumvent the overlapping confidence values for wrong and correct predictions. However, we observe that exactly these overlaps are an indicator for insufficiently calibrated models and can be mitigated by the improvement of CNNs building blocks, namely downsampling and activation functions, that have been proposed in the context of adversarial robustness [17, 27].

Hence, our work analyzes the relationship between robust models and model confidences. Our experiments on the datasets Cifar10 [42], Cifar100 and ImageNet [19] confirm that non-robust models are overconfident with their false predictions under adversarial attacks. This highlights the challenges for usage in real-world applications. In contrast, we show that robust models are generally less confident in their predictions, and, especially CNNs which include improved building blocks (downsampling and activation) turn out to be better calibrated manifesting low confidence in wrong predictions and high confidence in their correct predictions.

Our contributions can be summarized as follows:

- We provide an extensive analysis of the prediction confidence of 71 adversarially trained models, and their conventionally trained counterparts. We observe that most non-robust models are exceedingly over-confident while robust models exhibit less confidence and especially are better calibrated. Thus achieving more reliable networks for real-world applications.
- We observe that specific layers, that are considered to improve model robustness impact the models' confidences. In detail, improved downsampling layers and activation functions can lead to an even better calibration of the learned model.

Our analysis provides a first synopsis of adversarial robustness and model calibration and aims to foster research that addresses both challenges jointly rather than considering them as two separate research fields. To further promote research, we will release all re-trained models upon acceptance.

2 Related Work

In the following, we first briefly review the related work on model calibration which motivates our empirical analysis. Then, we revise the related work on adversarial attacks and model hardening.

Confidence Calibration. For many models that perform well with respect to standard benchmarks, it has been argued that the robust or regular model accuracy may be an insufficient metric [2, 13, 18, 77], in particular when real-world applications with potentially open-world scenarios are considered. In these settings, reliability must be established which can be quantified by the prediction confidence [56]. Ideally, a reliable model would provide high confidence predictions on correct classifications, and low confidence predictions on false ones [13, 55]. However, most networks are not able to provide a sufficient calibration instantly. Hence, confidence calibration is a vivid field of research and proposed methods are based on additional loss functions [31, 34, 44, 47, 50], on adaptions of the training input by label smoothing [52, 58, 61, 73] or on data augmentation [20, 44, 74, 86]. Further, [56] present a benchmark on classification models regarding model accuracy and confidence under dataset shift. Additionally, different evaluation methods have been provided to distinguish between correct and incorrect predictions [13, 54]. Naeini et al. [54] defined the networks *expected calibration error* (ECE) for a model f by with $0 \leq p \leq \infty$

$$\text{ECE}_p = \mathbb{E}[|\hat{z} - \mathbb{E}[1_{\hat{y}=y}|\hat{z}]|^p]^{\frac{1}{p}} \tag{1}$$

where the model f predicts $\hat{y} = y$ with the confidence $\hat{z}$. This can be directly related to the over-confidence $o(f)$ and under-confidence $u(f)$ of a network as follows [79]:

$$|o(f)\mathbb{P}(\hat{y} \neq y) - u(f)\mathbb{P}(\hat{y} = y)| \leq \text{ECE}_p, \tag{2}$$

where [53]

$$o(f) = \mathbb{E}[\hat{z}|\hat{y} \neq y] \quad u(f) = \mathbb{E}[1 - \hat{z}|\hat{y} = y], \tag{3}$$

i.e. the over-confidence measures the expectation of $\hat{z}$ on wrong prediction, under-confidence measured the expectation of $1 - \hat{z}$ on correct predictions and ideally both should be zero. The ECE provides an upper bound for the difference between the probability of the prediction being wrong weighted by the networks over-confidence and the probability of the prediction being correctly weighted by the networks under-confidence and converges to this value for the parameter $p \to 0$ (in eq. 1]). We also recur to this metric as an aggregate measure to evaluate model confidence. Yet, it should be noted that the ECE metric is based on the assumption that networks make correct as well as incorrect predictions. A model that always makes incorrect predictions and is less confident in its few correct decisions than it is in its many erroneous decisions can end up with a comparably low ECE. Therefore, ECE values for models with an accuracy below 50% are hard to interpret.

Most common CNNs are over-confident [30, 44, 55]. Moreover, the most dominantly used activation in modern CNNs [33, 38, 67, 71] remains the ReLU function, while is has been pointed out by Hein et al. [34] that ReLUs cause a general increase in the model's prediction confidences, regardless of the prediction validity. This is also the case for the vast majority of the adversarially trained models we consider, except for the model by [17] to which we devote particular attention.

Adversarial Attacks. Adversarial attacks intentionally add perturbations to the input samples, that are almost imperceptible to the human eye, yet lead to (high-confidence) false predictions of the attacked model [24, 51, 72]. These attacks can be classified into two categories: white-box and black-box attacks. In black-box attacks, the adversary has no knowledge of the model intrinsics [4], and can only query its output. These attacks are often developed on surrogate models [10, 41, 76] to reduce interaction with the attacked model in order to prevent threat detection. In general, though, these attacks are less powerful due to their limited access to the target networks. In contrast, in white-box attacks, the adversary has access to the full model, namely the architecture, weights, and gradient information [24, 43]. Based on this information the attacker can perform extremely powerful attacks customized to the model. One of the earliest approaches, the *Fast Gradient Sign Method* (FGSM) by [24] uses the sign of the prediction gradient to perturb input samples into the direction of the gradient, thereby increasing the loss and causing false predictions. This method was further adapted and improved by *Projected Gradient Descent* (PGD) [43], *DeepFool* (DF) [51], *Carlini and Wagner* (CW) [5] or *Decoupling Direction and Norm* (DDN) [63]. While FGSM is a single step attack, meaning that the perturbation is computed in one single gradient ascent step limited by some ϵ bound, multi-step attacks such as PGD iteratively search for the most effective perturbation in the ϵ-bound needed to change the models prediction. These attacks generally perform better but come at an increased cost of the attack. Recently, *AutoAttack* [14], an ensemble of different attacks including an adaptive version of PGD, was proposed as a baseline for adversarial robustness. In particular, it is used in robustness benchmarks such as RobustBench [15].

Adversarial Training and Robustness. To improve robustness, adversarial training (AT) has proven to be quite successful on common robustness benchmarks. Some attacks can be simply defended by using their adversarial examples in the training set [24, 63] through an additional loss [22, 85]. Furthermore, the addition of more training data, by using external data, or data augmentation techniques such as generation of synthetic data, has been shown to be promising for more robust models [6, 25, 26, 60, 66, 78]. RobustBench [15] provides a leaderboard to study the improvements made by the aforementioned approaches on robustness in a comparable manner in terms of their robust accuracy. Madry et al. [48] observed that the performance of adversarial training depends on the model's capacity. High-capacity models are able to fit the (adversarial) training data better, leading to an increased robust accuracy. Later research investigated the influence on increased model width and depth [25, 83]. Consequently, the best-performing entries on RobustBench [15] are often using Wide-ResNets-70-16 or even larger architectures, which supports these findings. Yet, only very few but notable prior works such as [44] have investigated adversarial training with respect to model calibration. Without providing a systematic overview, they show that AT can help to smooth the predictive distributions of CNN models. [75] introduce an adversarial calibration loss to reduce the calibration error. Further, [70] propose confidence calibrated adversarial training to force adversarial samples to show uniform confidence, while clean samples should be one hot encoded. Complementary to [15], we provide an analysis of the predictive confidences of adversarially trained, robust models and release conventionally trained counterparts of the models from [15] to facilitate future research on the analysis of the impact of training schemes versus architectural choices.

Defense besides adversarial training, can be established by the detection and rejection of malicious input. Most detection methods are based on input sample statistics [23, 29, 32, 36, 46], while others

143 attempt to detect adversarial samples via inference on surrogate models, yet these models themselves
144 might be vulnerable to attacks [12, 49].

3 Analysis

146 In the following, we first describe our experimental setting in which we then conduct an extensive
147 analysis on the two CIFAR datasets with respect to robust and non-robust model confidence on
148 clean and perturbed samples as well as their ECE. Further, we observe by computing the ROC
149 curves of these models that robust models are best suited to distinguish between correct and incorrect
150 predictions based on their confidence. In addition we point out that the improvement of pooling
151 operations or activation functions within the network can enhance the models' calibration further.
152 Last, we also investigate ImageNet as a high resolution dataset and observe that the model with the
153 highest capacity and AT can achieve the best performance results and calibration.

3.1 Experimental Setup

155 We have collected 71 checkpoints of robust models [1, 3, 7–9, 11, 16, 17, 21, 22, 25, 26, 37, 39, 40,
156 57, 59, 60, 62, 65, 66, 68, 69, 78, 81, 82, 84, 85, 87, 88] listed on the ℓ_∞-*RobustBench* leaderboard
157 [15]. Additionally, we compare each appearing architecture to a second model trained without AT or
158 any specific robustness regularization, and without any external data (even if the robust counterpart
159 relied on it). Training details can be found in appendix A. We provide all models and weights at
160 www.after-accept.com.

161 Then we collect the predictions alongside their respective confidences of robust and non-robust
162 models on clean validation samples, as well as on samples attacked by a white-box attack (PGD),
163 and a black-box attack (Squares). PGD (and its adaptive variant APGD [14]) is the most widely
164 used white-box attack and adversarial training schemes explicitly (when using PGD samples for
165 training) or implicitly (when using the faster but strongly related FGSM attack samples for training)
166 optimize for PGD robustness. In contrast, the *Squares* attack alters the data at random with an allowed
167 budget until the label flips. Such samples are rather to be considered out-of-domain samples even for
168 adversarially trained models and provide a proxy for a model's generalization abitily.

3.2 CIFAR Models

170 **CIFAR10** [42] is a simple ten class dataset consisting of 50,000 training and 10,000 validation images
171 with a resolution of 32×32. Since it is significantly cheaper to train on this dataset in comparison to
172 e. g. ImageNet, this dataset became a welcome benchmark for robustness allowing to discount the
173 additional cost of adversarial training. Thus entries on RobustBench [15] typically aim at improving
174 models robustness on CIFAR10.

175 Figure 1 shows an overview of all robust and non-robust models trained on CIFAR10 in terms of
176 their accuracy as well as their confidence in their correct and incorrect predictions. The red star
177 in the lower right corner indicates the optimal point where models are highly confident in correct
178 predictions and have zero confidence in their incorrect predictions. Along the isolines, the ratio
179 between confidence in correct and incorrect predictions is constant. The gray area indicates sce-
180 narios where models are even more confident in their incorrect predictions than in their correct
181 predictions. Concentrating on the models' confidence, we can see that robust models (marked by
182 a diamond) are in general less confident in their predictions, while non-robust models (marked
183 by a circle) exhibit high confidence in all their predictions, both correct and incorrect. This indi-
184 cates that non-robust models are not only more susceptible to (adversarial) distribution shifts but
185 are also highly over-confident in their false predictions. Practically, such behaviour can lead to
186 catastrophic consequences in safety-related, real-world applications. Robust models tend to have
187 lower average confidence and a favorable confidence trade-off even on clean data (Figure 1, top
188 left). When adversarial samples using PGD are considered (Figure 1, top middle), the non-robust
189 models even fall into the gray area of the plot where more confident decisions are likely incorrect. As
190 expected, adversarially trained models not only make fewer mistakes in this case but are also better
191 adjusted in terms of their confidence. Black-box attacks (Figure 1,top right) provide non-targeted
192 out of domain samples. Adversarially trained models generalize overall well to this case, i.e. their
193 mean confidences are hardly affected whereas non-robust models' confidences fluctuate heavily.

CIFAR10

CIFAR100

Figure 1: Mean model confidences on their correct (x-axis) and incorrect (y-axis) predictions over the full CIFAR10 dataset (top) and CIFAR100 dataset (bottom), clean (left) and perturbed with the attacks PGD (middle) and Squares (right). Each point represents a model. Circular points (purple color-map) represent non-robust models and diamond-shaped points (green color-map) represent robust models. The color of each point represents the models accuracy, darker signifies higher accuracy (better) on the given data samples. The star in the bottom right corner indicates the optimal model calibration and the gray area marks the area were the confidence distribution of the network is worse than random, i.e. more confident in incorrect predictions than in correct ones.

Figure 2: Overconfidence (lower is better) bar plots of robust models and their non-robust counterparts trained on CIFAR10. Non-robust models are highly overconfident, in contrast, their robust counterparts are less over-confident.

194

195 Four models stand out in Figure 1 (top
196 left): two robust and two non-robust
197 models which are much less confident
198 in their true and false predictions than
199 others. These less confident models
200 are indeed trained from two different
201 model architectures, with and without
202 adversarial training. [57] uses a hyper-
203 sphere embedding which normalizes

Samples \ Robustness	Clean	PGD	Squares
non-robust models	0.6736 ± 0.1208	0.6809 ± 0.1061	0.6635 ± 0.1156
robust models	0.1894 ± 0.1531	0.2688 ± 0.1733	0.2126 ± 0.1431

Table 1: Mean ECE (lower is better) and standard deviation over all non-robust model versus all their robust counterparts trained on CIFAR10. Robust model exhibit a significantly lower ECE on all samples.

204 the features in the intermediate layers and weights in the softmax layer, the other model [11] uses an
205 ensemble of three different pretrained models (ResNet-50) to boost robustness. These architectural
206 changes have a significant impact on the absolute model confidence, yet, do not necessarily lead to
207 a better calibration. These models are under-confident in their correct predictions and tend to be
208 comparably confident in wrong predictions.

Figure 3: Average ROC curve for all robust and all non-robust models trained on CIFAR10 (top) and CIFAR100 (bottom). Standard deviation is marked by the error bars. The dashed line would mark a model which has the same confidence for each prediction. We observe that the models confidences can be an indicator for the correctness of the prediction. However, on PGD samples the non-robust models fail while the robust models can distinguish correct from incorrect predictions based on the prediction confidence.

Table 1 reports the mean ECE over all robust models and their non-robust counterparts. Robust model are better calibrated which results in a significantly lower ECE [1]. Figure 12 further visualizes the significant decrease in over-confidence of robust models w.r.t. their non-robust counterparts.

CIFAR100, although otherwise similar to CIFAR10, includes 100 classes and can be seen as a more challenging classification task. This is reflected in the reduced model accuracy on the clean and adversarial samples (Figure 1 , bottom). On this data, robust models are again less over-confident. They are slightly closer to the optimal calibration point in the lower right corner even on clean data and perform significantly better on PGD samples where the confidences of non-robust models are again reversed (middle). The Squares attack again illustrates the stable behavior of robust models' confidences[2]. We also report the ECE values for CIFAR100 in the Appendix. Please note that the accuracy of the CIFAR100 models is not very high (ranging between 56.87% and 70.25% even for clean samples), resulting in an unreliable calibration metric. Especially under PGD attacks, non-robust networks make mostly incorrect predictions such that the ECE collapses to being the expected confidence value of incorrect predictions (see eq. [1]), regardless of the confidences of the few correct predictions. In this case, ECE is not meaningful.

Another interesting observation is that non-robust models can achieve higher accuracy on the clean data and, quite surprisingly, on the applied black-box attacks (Figure 1, right). This indicates that most robust models overfit white-box attacks used during training and are not generalizing very well to other attacks. While making more mistakes, robust models still have a favorable distribution of confidence over non-robust models in this case.

Model confidences can predict erroneous decisions. Next, we evaluate the prediction confidences in terms of their ability to predict whether a network prediction is correct or incorrect. We visualize the ROC curves for all models and compare the averages of robust and non-robust models in Figure 3 (top row for CIFAR10, bottom row for CIFAR100), which allows us to draw conclusions about the confidence behavior. While robust and non-robust models perform on average very similarly on clean

---

[1]The models' full empirical confidence distributions are given in Figure 9 in the Appendix.

[2]The models' full empirical confidence distributions are given in Figure 10 in the Appendix

Figure 4: Average ROC curve over all robust and non-robust models of confidence on clean correctly classified samples and perturbated wrongly classified samples. The robust model confidences can be used as threshold for detection of white-box adversarial attacks (PGD). For black-box adversarial attacks (Squares) the robust as well as non-robust models can partially detect the erroneous samples.

data, robust model confidences can reliable predict erroneous classification results on adversarial examples where non-robust models fail. Also, for out-of-domain samples from the black-box attack *Squares* (right), robust models can reliably assess their prediction quality and can better predict whether their classification result is correct.

Robust model confidences can detect adversarial samples. Further, we evaluate the adversarial detection rate of the robust models based on their ROC curves (averaged over all robust models) in Figure 4, comparing the confidence of correct predictions on clean samples and incorrect predictions caused by adversarial attacks. We observe that the confidences of robust models can be used to detect adversarial samples by simple thresholding.

Downsampling techniques. Most common CNNs apply downsampling to compress featuremaps with the intent to increase spatial invariance and overall higher sparsity. However, Grabinski et al. [28] showed that aliasing during the downsampling operation highly correlates with the lack of adversarial robustness, and provided a new kind of downsampling operation, called *frequency low cut pooling* [27], which enables improved downsampling of the featuremaps. Figure 5 compares the confidence distribution of three different networks. The top row shows a PRN-18 baseline without adversarial training, the second row the approach by Grabinski et al. [27] applied to the same architecture (additional models are evaluated in the appendix D), and the third row a robust model trained by Rebuffi et al. [60]. The baseline model is highly susceptible to adversarial attacks, especially under white-box attacks, while the two robust counter-parts remain low-confident in false predictions, and show higher confidence in correct predictions. However, while the model of Rebuffi et al. [60] shows a high variance amongst the predicted confidences, the approach by Grabinski et al. [27] significantly improves this by disentangling the confidences. Their model provides low-variance and high-confidence on correct predictions and reduced confidence on false predictions across all evaluated samples.

Activation functions. Next, we analyze the influence of activation functions. Only one Robust-Bench model utilizes an activation other than ReLU. Dai et al. [17] introduce learnable activation functions with the intent to improve robustness. Figure 6 shows at the top row a WRN-28-10 baseline model without AT, the model by Dai et al. [17] in the middle and a model with the same architecture adversarially trained by Carmon et al. [6].

Although this is an arguably sparse basis for a thorough investigation, we observe that the model by [17] can retain high confidence in correct predictions for both clean and perturbed samples. Furthermore, the model is much less confident in its wrong predictions for the clean as well as the adversarial samples. Similar to the used pooling variation, also the activation function seems to influence the model's calibration.

Summary of low resolution datasets. On CIFAR10 and CIFAR100 non-robust models can achieve higher standard accuracy and at least match or even exceed the performance of robust models under black-box attacks like *Squares*. Only under the white-box attack PGD, the robust models show higher accuracy. However non-robust models are highly over-confident in all their predictions and are hence limited in their applicability for real-world tasks. In contrast, the correctness of a robust models' prediction can be estimated by the prediction confidence. and is additionally serving as a defence against adversarial attacks. Further, we observe that the confidence of non-robust models decreases

Figure 5: Confidence distribution on three different PRN-18. The first row shows a model without adversarial training and standard pooling, the second row the model by Grabinski et al. [28] which uses flc pooling instead of standard pooling and the third row shows the model by Rebuffi et al. [60] adversarially trained and with standard pooling.

Figure 6: Confidence distribution on three different WRN-28-10. The first row shows a model without adversarial training and standard activation (ReLu), the second row the model by Dai et al. [17] which uses learnable activation functions instead of fixed ones and the third row shows the model by Carmon et al. [6] adversarially trained and with the standard activation (ReLu).

with increasing task complexity. In contrast, robust models are less affected by the increased task complexity and exhibit similar confidence characteristics on both datasets.

3.3 ImageNet

As previously introduced, we rely on the models provided by RobustBench [15] for our ImageNet evaluation. We report the clean and robust accuracy against *PGD* and *Squares* in Table 4 in the appendix. The non-robust model, trained without AT, achieves the highest performance on clean samples but collapses under white- and black-box attacks. Further, the models trained with multistep adversaries by Engstrom et al. [22] and Salman et al. [64] achieve higher robust and clean accuracy than the model trained by Wong et al. [81] which is trained with single-step adversaries. Moreover, the largest model, a WRN-50-2, yields the best robust performance. Still, the amount of robust networks on ImageNet is quite small, thus we can not make any generalized assumptions.

Figure 8 shows the precision-recall curve for our evaluated models. Under evaluation with clean samples, the non-robust model without AT performs best. Under both attacks (*PGD* and *Squares*) the largest model (a WRN-50-2 by Salman et al. [64]) performs best and the worst performer is the smallest model (RN-18). This may be suggesting that bigger models can not only achieve the better trade-off in clean and robust accuracy but also more successfully disentangle confidences between correct and incorrect predictions. Figure 7 confirms that the over-confidence is decreased in robust models and the ECE is lower than in the non-robust models.

4 Discussion

Our experiments confirm that the prediction confidence of non-robust models is an insufficient indicator for the correctness of the prediction, especially under attacks. In contrast, robust models are better behaved and, thus, allow their prediction confidence to serve as a threshold to detect wrongly classified samples. Further, our results indicate that the selection of the activation functions as well as the downsampling are important factors for the models' performance and confidence. The method by Grabinski et al. [27], which improves the downsampling, as well as the method by Dai et al. [17], which improves the activation function, exhibit the best calibration for the networks prediction. While

Figure 7: Overconfidence (left) and ECE (right) (lower is better) bar plots of the models trained on ImageNet provided by RobustBench [15] and their non-robust counterparts. The non-robust baselines exhibits the highest overconfidence and ECE. In contrast, the robust models are better calibrated.

Figure 8: Precision Recall curves for the classification of correct versus erroneous predictions based on the confidence on ImageNet, evaluated over 10000 samples. Robust and non-robust models are taken from RobustBench [15]. For clean samples (left) the non robust baseline performs best, while its confidences are less reliable under attack (middle and right). The robust WRN-50-2 by Salman et al. [64] performs best on the PGD and Squares samples.

further optimizing deep neural networks' architectures and training schemes, we should consider the synopsis of model robustness and calibration instead of optimizing each of these aspects separately.

Limitations. Our evaluation is based on the models provided on RobustBench [15]. Thus the amount of networks on more complex datasets, like ImageNet, is rather small and therefore the evaluation not universally applicable. While the number of models for CIFAR10 and CIFAR100 is large, the proposed database can only be understood as a starting point for future research. This is particularly true for the analysis of neural network building blocks - models that are adversarially trained and employ smooth activation functions might be very promising concerning their calibration but a more in-depth analysis of this setting with new, dedicated datasets is desirable. Additionally, we rely simply on the confidence obtained after the Softmax layer, while there are many other metrics for uncertainty measurement. Hence, an analysis of robust models with respect to those measures might be valuable and we encourage such research by releasing our dataset of trained models.

5 Conclusion

We provide an extensive study on the confidences of robust models and observe an overall trend: robust models tent to be less over-confident than non-robust models. Thus, while achieving a higher robust accuracy, adversarial training provides better calibrated models which are more suited for real-world application. Further, the prediction confidence of robust models can actually be used to reject wrongly classified samples on clean data and even adversarial examples.

Moreover, we see indications that exchanging simple building blocks like the activation function [17] or the downsampling method [28] alters the properties of robust models with respect to confidence calibration. On the examples we investigate, the models' prediction confidence on their correct predictions can be increased while the confidence on the erroneous predictions remains low. Our findings should nurture future research on jointly considering model calibration and robustness.

References

[1] Sravanti Addepalli, Samyak Jain, Gaurang Sriramanan, Shivangi Khare, and Venkatesh Babu Radhakrishnan. Towards achieving adversarial robustness beyond perceptual limits. In *ICML 2021 Workshop on Adversarial Machine Learning*, 2021. URL `https://openreview.net/forum?id=SHB_znlW5G7`.

[2] Dario Amodei, Chris Olah, Jacob Steinhardt, Paul Christiano, John Schulman, and Dan Mané. Concrete problems in ai safety, 2016. URL `https://arxiv.org/abs/1606.06565`.

[3] Maksym Andriushchenko and Nicolas Flammarion. Understanding and improving fast adversarial training. *Advances in Neural Information Processing Systems*, 33:16048–16059, 2020.

[4] Maksym Andriushchenko, Francesco Croce, Nicolas Flammarion, and Matthias Hein. Square attack: a query-efficient black-box adversarial attack via random search. In *European Conference on Computer Vision*, pages 484–501. Springer, 2020.

[5] Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks. In *2017 ieee symposium on security and privacy (sp)*, pages 39–57. IEEE, 2017.

[6] Yair Carmon, Aditi Raghunathan, Ludwig Schmidt, John C Duchi, and Percy S Liang. Unlabeled data improves adversarial robustness. *Advances in Neural Information Processing Systems*, 32, 2019.

[7] Yair Carmon, Aditi Raghunathan, Ludwig Schmidt, Percy Liang, and John C. Duchi. Unlabeled data improves adversarial robustness, 2022.

[8] Erh-Chung Chen and Che-Rung Lee. Ltd: Low temperature distillation for robust adversarial training, 2021.

[9] Jinghui Chen, Yu Cheng, Zhe Gan, Quanquan Gu, and Jingjing Liu. Efficient robust training via backward smoothing, 2021.

[10] Pin-Yu Chen, Huan Zhang, Yash Sharma, Jinfeng Yi, and Cho-Jui Hsieh. Zoo: Zeroth order optimization based black-box attacks to deep neural networks without training substitute models. In *Proceedings of the 10th ACM workshop on artificial intelligence and security*, pages 15–26, 2017.

[11] Tianlong Chen, Sijia Liu, Shiyu Chang, Yu Cheng, Lisa Amini, and Zhangyang Wang. Adversarial robustness: From self-supervised pre-training to fine-tuning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 699–708, 2020.

[12] Gilad Cohen, Guillermo Sapiro, and Raja Giryes. Detecting adversarial samples using influence functions and nearest neighbors. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 14453–14462, 2020.

[13] Charles Corbière, Nicolas Thome, Avner Bar-Hen, Matthieu Cord, and Patrick Pérez. Addressing failure prediction by learning model confidence. *Advances in Neural Information Processing Systems*, 32, 2019.

[14] Francesco Croce and Matthias Hein. Reliable evaluation of adversarial robustness with an ensemble of diverse parameter-free attacks. In *ICML*, 2020.

[15] Francesco Croce, Maksym Andriushchenko, Vikash Sehwag, Nicolas Flammarion, Mung Chiang, Prateek Mittal, and Matthias Hein. Robustbench: a standardized adversarial robustness benchmark. *arXiv preprint arXiv:2010.09670*, 2020.

[16] Jiequan Cui, Shu Liu, Liwei Wang, and Jiaya Jia. Learnable boundary guided adversarial training, 2021.

[17] Sihui Dai, Saeed Mahloujifar, and Prateek Mittal. Parameterizing activation functions for adversarial robustness, 2021.

[18] Morris H DeGroot and Stephen E Fienberg. The comparison and evaluation of forecasters. *Journal of the Royal Statistical Society: Series D (The Statistician)*, 32(1-2):12–22, 1983.

[19] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pages 248–255, 2009. doi: 10.1109/CVPR.2009.5206848.

[20] Terrance DeVries and Graham W Taylor. Improved regularization of convolutional neural networks with cutout. *arXiv preprint arXiv:1708.04552*, 2017.

[21] Gavin Weiguang Ding, Yash Sharma, Kry Yik Chau Lui, and Ruitong Huang. Mma training: Direct input space margin maximization through adversarial training. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=HkeryxBtPB`.

[22] Logan Engstrom, Andrew Ilyas, Hadi Salman, Shibani Santurkar, and Dimitris Tsipras. Robustness (python library), 2019. URL `https://github.com/MadryLab/robustness`.

[23] Reuben Feinman, Ryan R Curtin, Saurabh Shintre, and Andrew B Gardner. Detecting adversarial samples from artifacts. *arXiv preprint arXiv:1703.00410*, 2017.

[24] Ian J. Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples, 2015.

[25] Sven Gowal, Chongli Qin, Jonathan Uesato, Timothy Mann, and Pushmeet Kohli. Uncovering the limits of adversarial training against norm-bounded adversarial examples, 2021.

[26] Sven Gowal, Sylvestre-Alvise Rebuffi, Olivia Wiles, Florian Stimberg, Dan Andrei Calian, and Timothy A Mann. Improving robustness using generated data. *Advances in Neural Information Processing Systems*, 34, 2021.

[27] Julia Grabinski, Steffen Jung, Janis Keuper, and Margret Keuper. Frequencylowcut pooling–plug & play against catastrophic overfitting. *arXiv preprint arXiv:2204.00491*, 2022.

[28] Julia Grabinski, Janis Keuper, and Margret Keuper. Aliasing coincides with CNNs vulnerability towards adversarial attacks. In *The AAAI-22 Workshop on Adversarial Machine Learning and Beyond*, 2022. URL `https://openreview.net/forum?id=vKc1mLxBebP`.

[29] Kathrin Grosse, Praveen Manoharan, Nicolas Papernot, Michael Backes, and Patrick McDaniel. On the (statistical) detection of adversarial examples. *arXiv preprint arXiv:1702.06280*, 2017.

[30] Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In Doina Precup and Yee Whye Teh, editors, *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 1321–1330. PMLR, 06–11 Aug 2017. URL `https://proceedings.mlr.press/v70/guo17a.html`.

[31] Corina Gurau, Alex Bewley, and Ingmar Posner. Dropout distillation for efficiently estimating model confidence. *arXiv preprint arXiv:1809.10562*, 2018.

[32] Paula Harder, Franz-Josef Pfreundt, Margret Keuper, and Janis Keuper. Spectraldefense: Detecting adversarial attacks on cnns in the fourier domain. In *2021 International Joint Conference on Neural Networks (IJCNN)*, pages 1–8. IEEE, 2021.

[33] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition, 2015.

[34] Matthias Hein, Maksym Andriushchenko, and Julian Bitterwolf. Why relu networks yield high-confidence predictions far away from the training data and how to mitigate the problem, 2019.

[35] Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. *Proceedings of the International Conference on Learning Representations*, 2019.

[36] Dan Hendrycks and Kevin Gimpel. Early methods for detecting adversarial images. *arXiv preprint arXiv:1608.00530*, 2016.

[37] Dan Hendrycks, Kimin Lee, and Mantas Mazeika. Using pre-training can improve model robustness and uncertainty. In *International Conference on Machine Learning*, pages 2712–2721. PMLR, 2019.

[38] Gao Huang, Zhuang Liu, Laurens van der Maaten, and Kilian Q. Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, July 2017.

[39] Hanxun Huang, Yisen Wang, Sarah Monazam Erfani, Quanquan Gu, James Bailey, and Xingjun Ma. Exploring architectural ingredients of adversarially robust deep neural networks, 2022.

[40] Lang Huang, Chao Zhang, and Hongyang Zhang. Self-adaptive training: beyond empirical risk minimization, 2020.

[41] Andrew Ilyas, Logan Engstrom, Anish Athalye, and Jessy Lin. Black-box adversarial attacks with limited queries and information. In *International Conference on Machine Learning*, pages 2137–2146. PMLR, 2018.

[42] Alex Krizhevsky. Learning multiple layers of features from tiny images. *University of Toronto*, 05 2012.

[43] Alexey Kurakin, Ian Goodfellow, and Samy Bengio. Adversarial machine learning at scale, 2017.

[44] Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. *Advances in neural information processing systems*, 30, 2017.

[45] Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks, 2018. URL https://arxiv.org/abs/1807.03888.

[46] Xin Li and Fuxin Li. Adversarial examples detection in deep networks with convolutional filter statistics. In *Proceedings of the IEEE international conference on computer vision*, pages 5764–5772, 2017.

[47] Zhizhong Li and Derek Hoiem. Improving confidence estimates for unfamiliar examples. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2686–2695, 2020.

[48] Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*, 2017.

[49] Jan Hendrik Metzen, Tim Genewein, Volker Fischer, and Bastian Bischoff. On detecting adversarial perturbations. *arXiv preprint arXiv:1702.04267*, 2017.

[50] Jooyoung Moon, Jihyo Kim, Younghak Shin, and Sangheum Hwang. Confidence-aware learning for deep neural networks. In *international conference on machine learning*, pages 7034–7044. PMLR, 2020.

[51] Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, and Pascal Frossard. Deepfool: a simple and accurate method to fool deep neural networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2574–2582, 2016.

[52] Rafael Müller, Simon Kornblith, and Geoffrey E Hinton. When does label smoothing help? *Advances in neural information processing systems*, 32, 2019.

[53] Dennis Mund, Rudolph Triebel, and Daniel Cremers. Active online confidence boosting for efficient object classification. In *2015 IEEE International Conference on Robotics and Automation (ICRA)*, pages 1367–1373, 2015. doi: 10.1109/ICRA.2015.7139368.

[54] Mahdi Pakdaman Naeini, Gregory Cooper, and Milos Hauskrecht. Obtaining well calibrated probabilities using bayesian binning. In *Twenty-Ninth AAAI Conference on Artificial Intelligence*, 2015.

[55] Anh Nguyen, Jason Yosinski, and Jeff Clune. Deep neural networks are easily fooled: High confidence predictions for unrecognizable images. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 427–436, 2015.

[56] Yaniv Ovadia, Emily Fertig, Jie Ren, Zachary Nado, David Sculley, Sebastian Nowozin, Joshua Dillon, Balaji Lakshminarayanan, and Jasper Snoek. Can you trust your model's uncertainty? evaluating predictive uncertainty under dataset shift. *Advances in neural information processing systems*, 32, 2019.

[57] Tianyu Pang, Xiao Yang, Yinpeng Dong, Kun Xu, Jun Zhu, and Hang Su. Boosting adversarial training with hypersphere embedding. *Advances in Neural Information Processing Systems*, 33: 7779–7792, 2020.

[58] Yao Qin, Xuezhi Wang, Alex Beutel, and Ed Chi. Improving calibration through the relationship with adversarial robustness. *Advances in Neural Information Processing Systems*, 34:14358–14369, 2021.

[59] Rahul Rade and Seyed-Mohsen Moosavi-Dezfooli. Helper-based adversarial training: Reducing excessive margin to achieve a better accuracy vs. robustness trade-off. In *ICML 2021 Workshop on Adversarial Machine Learning*, 2021. URL https://openreview.net/forum?id=BuD2LmNaU3a.

[60] Sylvestre-Alvise Rebuffi, Sven Gowal, Dan A. Calian, Florian Stimberg, Olivia Wiles, and Timothy Mann. Fixing data augmentation to improve adversarial robustness, 2021.

[61] Scott Reed, Honglak Lee, Dragomir Anguelov, Christian Szegedy, Dumitru Erhan, and Andrew Rabinovich. Training deep neural networks on noisy labels with bootstrapping. *arXiv preprint arXiv:1412.6596*, 2014.

[62] Leslie Rice, Eric Wong, and Zico Kolter. Overfitting in adversarially robust deep learning. In *International Conference on Machine Learning*, pages 8093–8104. PMLR, 2020.

[63] Jérôme Rony, Luiz G Hafemann, Luiz S Oliveira, Ismail Ben Ayed, Robert Sabourin, and Eric Granger. Decoupling direction and norm for efficient gradient-based l2 adversarial attacks and defenses. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 4322–4330, 2019.

[64] Hadi Salman, Andrew Ilyas, Logan Engstrom, Ashish Kapoor, and Aleksander Madry. Do adversarially robust imagenet models transfer better? *Advances in Neural Information Processing Systems*, 33:3533–3545, 2020.

[65] Vikash Sehwag, Shiqi Wang, Prateek Mittal, and Suman Jana. Hydra: Pruning adversarially robust neural networks, 2020.

[66] Vikash Sehwag, Saeed Mahloujifar, Tinashe Handina, Sihui Dai, Chong Xiang, Mung Chiang, and Prateek Mittal. Robust learning meets generative models: Can proxy distributions improve adversarial robustness?, 2021.

[67] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition, 2015.

[68] Chawin Sitawarin, Supriyo Chakraborty, and David Wagner. Sat: Improving adversarial training via curriculum-based loss smoothing, 2021.

[69] Kaustubh Sridhar, Oleg Sokolsky, Insup Lee, and James Weimer. Improving neural network robustness via persistency of excitation, 2021.

[70] David Stutz, Matthias Hein, and Bernt Schiele. Confidence-calibrated adversarial training: Generalizing to unseen attacks. In *International Conference on Machine Learning*, pages 9155–9166. PMLR, 2020.

[71] Christian Szegedy, Wei Liu, Yangqing Jia, Pierre Sermanet, Scott Reed, Dragomir Anguelov, Dumitru Erhan, Vincent Vanhoucke, and Andrew Rabinovich. Going deeper with convolutions, 2014.

[72] Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In *International Conference on Learning Representations*, 2014. URL `http://arxiv.org/abs/1312.6199`.

[73] Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2818–2826, 2016.

[74] Sunil Thulasidasan, Gopinath Chennupati, Jeff A Bilmes, Tanmoy Bhattacharya, and Sarah Michalak. On mixup training: Improved calibration and predictive uncertainty for deep neural networks. *Advances in Neural Information Processing Systems*, 32, 2019.

[75] Christian Tomani and Florian Buettner. Towards trustworthy predictions from deep neural networks with fast adversarial calibration. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 9886–9896, 2021.

[76] Chun-Chen Tu, Paishun Ting, Pin-Yu Chen, Sijia Liu, Huan Zhang, Jinfeng Yi, Cho-Jui Hsieh, and Shin-Ming Cheng. Autozoom: Autoencoder-based zeroth order optimization method for attacking black-box neural networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 742–749, 2019.

[77] Kush R Varshney and Homa Alemzadeh. On the safety of machine learning: Cyber-physical systems, decision sciences, and data products. *Big data*, 5(3):246–255, 2017.

[78] Yisen Wang, Difan Zou, Jinfeng Yi, James Bailey, Xingjun Ma, and Quanquan Gu. Improving adversarial robustness requires revisiting misclassified examples. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=rklOg6EFwS`.

[79] Jonathan Wenger, Hedvig Kjellström, and Rudolph Triebel. Non-parametric calibration for classification. In *International Conference on Artificial Intelligence and Statistics*, pages 178–190. PMLR, 2020.

[80] Ross Wightman. Pytorch image models. `https://github.com/rwightman/pytorch-image-models`, 2019.

[81] Eric Wong, Leslie Rice, and J. Zico Kolter. Fast is better than free: Revisiting adversarial training. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=BJx040EFvH`.

[82] Dongxian Wu, Shu-Tao Xia, and Yisen Wang. Adversarial weight perturbation helps robust generalization. *Advances in Neural Information Processing Systems*, 33:2958–2969, 2020.

[83] Cihang Xie and Alan Yuille. Intriguing properties of adversarial training at scale. *arXiv preprint arXiv:1906.03787*, 2019.

[84] Dinghuai Zhang, Tianyuan Zhang, Yiping Lu, Zhanxing Zhu, and Bin Dong. You only propagate once: Accelerating adversarial training via maximal principle, 2019.

[85] Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric P. Xing, Laurent El Ghaoui, and Michael I. Jordan. Theoretically principled trade-off between robustness and accuracy. In *International Conference on Machine Learning*, 2019.

[86] Hongyi Zhang, Moustapha Cisse, Yann N Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. *arXiv preprint arXiv:1710.09412*, 2017.

[87] Jingfeng Zhang, Xilie Xu, Bo Han, Gang Niu, Lizhen Cui, Masashi Sugiyama, and Mohan Kankanhalli. Attacks which do not kill training make adversarial learning stronger, 2020.

[88] Jingfeng Zhang, Jianing Zhu, Gang Niu, Bo Han, Masashi Sugiyama, and Mohan Kankanhalli. Geometry-aware instance-reweighted adversarial training. In *International Conference on Learning Representations*, 2021. URL `https://openreview.net/forum?id=iAX0l6Cz8ub`.