Heavy-tailed Linear Bandit with Huber Regression

Abstract

Linear bandit algorithms have been extensively studied and have shown successful in sequential decision tasks despite their simplicity. Many algorithms however work under the assumption that the reward is the sum of linear function of observed contexts and a sub-Gaussian error. In practical applications, errors can be heavy-tailed, especially in financial data. In such reward environments, algorithms designed for sub-Gaussian error may under-explore, resulting in suboptimal regret. In this paper, we propose a novel algorithm for linear bandits with heavy-tailed errors. The proposed algorithm utilizes Huber regression. When the $(1 + \delta)$-th moment of the error is bounded by a constant, we show that the high-probability upper bound of the regret is $O(\sqrt{d}T^{\frac{1}{1+\delta}}(\log T)^{\frac{\delta}{1+\delta}})$, where d is the dimension of context variables, T is the time horizon, and $\delta \in (0, 1]$. This bound improves on the state-of-the-art regret bound of the Median of Means and Truncation algorithm by a factor of $\sqrt{\log T}$ and $\sqrt{d}$ for the case where the time horizon T is unknown. We also remark that when $\delta = 1$, the order is the same as the regret bound of linear bandit algorithms designed for sub-Gaussian errors. We support our theoretical findings with synthetic experiments.

1 INTRODUCTION

Bandit algorithms are widely used in sequential decision-making problems such as mobile health [Lei et al., 2017], clinical trial [Villar et al., 2015] where the goal of the learning agent is to select good actions successively out of many available actions at each time point. Linear bandits make use of contextual information when choosing the arms. Upon choosing an arm, a random reward is revealed to the agent.

The agent then learns the reward model using rewards observed so far under assumption that the expected value of the reward is a linear function of context variables. Using the updated model and various exploration strategies, the agent chooses the next arm. Most bandit research is studied under the assumption that error distribution is sub-Gaussian. However, we encounter heavy-tailed data distribution in many practical applications including financial markets and insurance[Rachev, 2003, Stehlík et al., 2010, Ibragimov et al., 2015]. We propose a novel linear bandit algorithm robust to heavy-tailed error. There are some ways to define the heaviness of tail distribution. Followings are from Cooke and Nieboer [2011]. One is the regularly varying function. A distribution function $F_X(x) = \mathbb{P}(X \leq x)$ is regularly varying at infinity with index $-\alpha$ if

$$\lim_{x \to \infty} \frac{1 - F_X(tx)}{1 - F_X(x)} = t^{-\alpha}, \ \alpha \in [0, \infty].$$

Other definition is the sub-exponential distribution. A distribution function $F_X(x)$ with support $(0, \infty)$ is a sub-exponential if $\forall n \geq 2$,

$$\lim_{x \to \infty} \frac{1 - F_X^{n^*}(x)}{1 - F_X(x)} = n,$$

where $F_X^{n^*}(x)$ denote the n-th convolution of $F_X(x)$. The class of heavy-tailed distribution we consider in the paper is when the second or lower moment of the error is finite. That is, for error ϵ, we have $\mathbb{E}[|\epsilon|^{1+\delta}] \leq \nu_\delta < \infty$, for some $\delta \in (0, 1]$. This is common in the bandit contexts [Bubeck et al., 2013, Medina and Yang, 2016, Shao et al., 2018, Xue et al., 2020]. We propose to use Huber estimator [Huber, 1964] with such data in bandit setting. The Huber loss works as a square loss when the error is small and works as an absolute loss otherwise. It corrects errors that deviate significantly from the mean. It suppresses the loss value when an observation deviated significantly from the mean, so that it does not dominates on other observations. Sun et al. [2020] proposed adaptive Huber regression with robustification parameter adapted to dimension and size of sample and

moment bound on the error. The upper bound of L_2-norm of the estimation error depends on the minimum eigenvalue of the Gram matrix of the covariates. When the covariates are i.i.d(independently and identically distributed) and are sampled from a distribution with positive definite covariance matrix, it can be shown that their Gram matrix is strictly bigger than 0 with high probability for sufficiently large samples. However, data accumulated by bandit agents are not i.i.d. since the arm selection depends on the arms chosen before. Hence, the Gram matrix formed by contexts has no guarantee to have strictly positive minimum eigenvalue, and the estimation error can be higher. We use forced-sampling method [Bastani and Bayati, 2020, Goldenshluger and Zeevi, 2013] to guarantee the minimum eigenvalue bound. In Section 2, we explain our problem settings. Then in Section 3, previous works on the linear bandit with a heavy-tailed error are reviewed. We introduce previous results needed for our theoretical analysis of estimator including the formal definition of the Huber regression in Section 4. In Section 5, a description of the proposed algorithm and its theoretical analysis are presented. Section 6 is devoted to the simulation study of the proposed algorithm compared with two other algorithms.

2 PROBLEM FORMULATION

In linear bandits, we assume that the expected value of the reward is linear in the contexts. The bandit agent aims to learn the unknown linear parameter through consecutive arm pulls. We denote d-dimensional context vector at time t by $X_t \in \mathbb{R}^d$. In each time step, X_t is sampled from unknown distribution $P_{\mathcal{X}}$ independently. We denote the number of arms as K. When the learning agent pulls the i-th arm at time t, the arm reveals a stochastic reward

$$y_t = X_t^T \beta_i + \epsilon_{i,t}, \tag{1}$$

where $\beta_i \in \mathbb{R}^d$ is an arm-specific fixed parameter and each $\epsilon_{i,t}$ is a heavy-tailed noise. Specifically, we assume $\mathbb{E}[\epsilon_{i,t} \mid \mathcal{F}_{t-1}] = 0$ and $\mathbb{E}\left[|\epsilon_{i,t}|^{1+\delta} \mid \mathcal{F}_{t-1}\right] \leq \nu_\delta < \infty$, for $\nu_\delta > 0$ and for some $\delta \in (0,1]$, where $\mathcal{F}_t = \sigma(X_1,...,X_{t+1},\epsilon_1,...,\epsilon_t)$. Note that sub-Gaussian errors satisfy this assumption with $\delta = 1$. The regret at time t is defined by

$$r_t := X_t^T \beta_{a^*(t)} - X_t^T \beta_{a(t)},$$

where $a(t)$ is the arm the learning agent chooses at time t and $a^*(t) = \arg\max_{j \in [K]} X_t^T \beta_j$ is the optimal arm.

In related literature on bandits for linear payoffs, the formulation is sometimes presented as follows, where instead of arm-specific parameters and single context, we have a single parameter $\beta \in \mathbb{R}^d$ and arm-specific contexts, $X_{i,t} \in \mathbb{R}^d$ for each arm i.

$$y_t = X_{i,t}^T \beta + \epsilon_{i,t}. \tag{2}$$

However, we note that an algorithm designed for one setting can always be applied to the other setting. For example, when the algorithm designed for (1) needs to be applied on (2), we simply let $X_t = \{X_{1,t}^T \cdots X_{K,t}^T\}^T \in \mathbb{R}^{Kd}$ and $\beta_i = \{\mathbf{0}^T \cdots \mathbf{0}^T \beta^T \mathbf{0}^T \cdots \mathbf{0}^T\} \in \mathbb{R}^{Kd}$, where $\mathbf{0}$ is a d-dimensional zero vector and all the elements up to the $d \times (i-1)$-th element and after the $d \times i$-th element are all 0 in β_i. On the other hand, when we apply an algorithm designed for (2) on setting (1), we simply let $\beta = \{\beta_1^T \cdots \beta_K^T\} \in \mathbb{R}^{Kd}$ and $X_{i,t} = \{\mathbf{0}^T \cdots \mathbf{0}^T X^T \mathbf{0}^T \cdots \mathbf{0}^T\} \in \mathbb{R}^{Kd}$.

Notations For any vector $v \in \mathbb{R}^d$ and positive semi-definite matrix $A \in \mathbb{R}^{d \times d}$, we let $||v||_A := \sqrt{v^T A v}$. We let $[N] = \{1, 2, \cdots, N\}$ for any natural number N. We let $\lambda_{\min}(A)$ and $\lambda_{\max}(A)$ be the minimum and maximum eigenvalues of matrix A respectively. For any vector $v \in \mathbb{R}^d$, $v = (v_1,...,v_d)^T$, L_2-norm is $||v||_2 = (\sum_{i=1}^d |v_i|^2)^{\frac{1}{2}}$ and max norm is $||v||_\infty = \max_{1 \leq i \leq d} |v_i|$. For any matrices $A, B \in \mathbb{R}^{d \times d}$, let $A \succcurlyeq B$ if $B - A$ is positive semi definite. For any set A, let $\mathbb{1}_A(\cdot)$ denote indicator function. The set $\mathbb{N}$ denotes the set of natural numbers. When $Z \subset \mathbb{N}$, we denote the Gram matrix as $\hat{\Sigma}(Z) := \frac{1}{|Z|} \sum_{r \in Z} X_r X_r^T$.

3 RELATED WORK

When errors are sub-Gaussian and the time horizon is unknown, LinOFUL[Abbasi-Yadkori et al., 2011] is the state-of-the-art algorithm, achieving a tight regret bound of order $\tilde{O}(d\sqrt{T})$ for setting (2), where $\tilde{O}(\cdot)$ ignores logarithmic terms. The strategy of LinOFUL is to construct a tight confidence region of the true parameter β^* at each time step and pull the arm according to the *Optimism in the Face of Uncertainty (OFU)* principle. The confidence region at time t is an ellipsoid of the form $C_t = \{\beta : ||\beta - \hat{\beta}_t||_{V_t} \leq \alpha_t\}$, in which the center $\hat{\beta}$ is the Ridge estimator of β^* using the contexts and rewards of the chosen arms up to time t as covariate and outcome respectively and V_t is the Gram matrix of the covariates. The Mahalanobis norm $||\beta^* - \hat{\beta}_t||_{V_t} \approx ||\sum_{r=1}^t X_{a(r),r}\epsilon_{a(r),r}||_{V_t^{-1}}$ is a self-normalized martingale, where $\sum_{r=1}^t X_{a(r),r}\epsilon_{a(r),r}$ forms a martingale and $V_t \approx \sum_{r=1}^t X_{a(r),r}X_{a(r),r}^T$ is the normalization term. Abbasi-Yadkori et al. [2011] proved that when ϵ is sub-Gaussian, C_t contains the true parameter with high probability for small enough positive value of α_t. The main challenge in the proof is that the self-normalized martingale is not a martingale when arms are chosen adaptively. Hence, standard Azuma-Hoeffding inequalities cannot apply. Abbasi-Yadkori et al. [2011] applied the inequality for self-normalized martingales [de la Pena et al., 2004, Peña et al., 2009] instead.

When errors $\epsilon_{i,t}$ are not sub-Gaussian but have only finite second moments, the self-normalized inequality does not hold anymore. Therefore, we do not have a guarantee that

the Ridge estimator of β converges to the true value fast enough to allow a tight confidence region and optimal regret. Hence, other estimators than the naive Ridge estimators should be considered. Recently, novel estimators [Medina and Yang, 2016, Shao et al., 2018, Xue et al., 2020] have been proposed motivated from the Median of Means (MoM) method and truncation method of Bubeck et al. [2013] for multi-armed bandits without contexts. All these works follow Abbasi-Yadkori et al. [2011] in that they first construct a confidence region of β and then choose the arm according to the OFU principle.

Medina and Yang [2016] was the first to extend the MoM method to the estimation of the linear regression parameter, β. They proposed an algorithm which conducts in batches, where during each batch, the agent pulls the same arm with the same context variable repeatedly. At the end of each batch, the algorithm computes the MoM of the rewards which share the same context variable. Then the algorithm updates the Ridge estimator of β using the context and MoM of rewards as new covariate-outcome pair. The caveat of the method is that while the errors of the individual rewards are heavy-tailed, the error of the MoM can be shown to be sub-Gaussian with high-probability. Therefore, the self-normalized inequality applies straightforwardly and a tight confidence region can be constructed. The paper derived a high-probability upper bound of the regret of order $O(\sqrt{d}T^{\frac{1+2\delta}{1+3\delta}}(\log T)^{\frac{3\delta+1}{2(1+\delta)}})$. We remark that when $\delta = 1$, the order reduces to $\tilde{O}(dT^{\frac{3}{4}})$ which is suboptimal when applied to sub-Gaussian rewards which have finite second moments. The MoM method does not recover the tight $O(\sqrt{T})$ regret bound despite the sub-Gaussianity of MoMs because we need multiple samples, up to $O(T^{\frac{1+\delta}{1+3\delta}})$ samples, to construct a single MoM.

Shao et al. [2018] refined the MoM method of Medina and Yang [2016] and proposed a novel algorithm called MENU which enjoys a tighter regret upper bound. MENU also executes in batches and requires to pull the same arm with the same context repeatedly in each batch. Instead of computing the MoM of rewards however, MENU first computes different estimates of β where each estimate uses one context-reward pair as a new observation. Among the different estimates $\hat{\beta}^1, \hat{\beta}^2, \cdots, \hat{\beta}^k$, MENU then selects the estimate which has the median value of $||\hat{\beta}^j - \beta^*||_{V_t}$ where β^* is the true value of β. While $\hat{\beta}^1, \hat{\beta}^2, \cdots, \hat{\beta}^k$ have not all a tight estimation error bound, it can be shown that $\hat{\beta}^j$ which has the median Mahalanobis distance with β^* achieves a tight estimation error bound. This refined estimator requires less samples k in each batch to achieve the same estimation error bound as in the MoM method. Consequently, the regret of MENU is $O(d^{\frac{3+\delta}{2(1+\delta)}}T^{\frac{1}{1+\delta}}(\log T)^{\frac{3\delta+1}{2(1+\delta)}})$. Now we observe that the bound is optimal with respect to T when $\delta = 1$. The MENU algorithm is easy to employ and runs fast. However, the restriction that the same context variable should be observed during the same batch can be restrictive.

In practice, context variables are often stochastic. Even for the same arm, the context information may change. In this case, we cannot run MENU.

Medina and Yang [2016] proposed an alternative estimator which does not require to pull the same arm with the same context variable in a row. The algorithm computes a Ridge estimator using truncated reward $\hat{y}_t = y_t \mathbb{1}_{|y_t| \leq b_t}$, where the value of b_t increases with time t. The quantity $\hat{y}_t$ is bounded but biased. Hence, the error $\hat{y}_t - X_{i,t}^T\beta$ can be decomposed into a sub-Gaussian variable plus a bias term. The authors carefully choose the value of b_t to trade off the self-normalized bound for the sub-Gaussian variables and the bound on the cumulative bias. Consequently, their algorithm achieves a high probability regret bound of $O(dT^{\frac{2+\delta}{2(1+\delta)}}\log T)$. This bound also does not recover the $O(\sqrt{T})$ bound when $\delta = 1$.

Shao et al. [2018] refined the truncation estimator of Medina and Yang [2016]. Instead of truncating the reward y_t, they truncated each element of $V_t^{-1/2}X_{a(r),r}y_r$ for every $r = 1, 2, \cdots, t$ by a time increasing threshold b_t. Hence, the truncation depends not only on the reward but also on the contexts of the chosen arms so far. Also, at each time t, the truncation is re-operated on all observations up to time t. This increases the time complexity of the algorithm but makes the estimator more accurate to obtain the tight regret upper bound of $O(dT^{\frac{1}{1+\delta}}(\log T)^{\frac{3\delta+1}{2(1+\delta)}})$ which reproduces the optimal regret bound with respect to T when $\delta = 1$. The analysis however relies on Bernstein's inequalities for martingales, which can be applied to self-normalized martingales under restrictive conditions only. We note that a self-normalized martingale becomes a martingale only when the contexts of chosen arms constitute a fixed design, i.e., when the covariates used in the estimator are fixed prior to observing the outcomes(rewards). In adaptively collected data, we usually do not have a fixed design since the covariate at time t is chosen based on the rewards up to time $t-1$.

Xue et al. [2020] blended the median of means and truncation method with the SupLinUCB algorithm [Chu et al., 2011] and achieved the regret bounds $O(\sqrt{d}(\log T)^{\frac{3}{2}}T^{\frac{1}{1+\delta}})$ and $O(\sqrt{d}(\log T)^2 T^{\frac{1}{1+\delta}})$, respectively. They refined the estimators of Medina and Yang [2016] and Shao et al. [2018] so that the contexts at the current time point are also considered when taking median of means and truncation. However, the derivation of the confidence interval for β based on their estimators is valid under fixed design only. Therefore, the authors adopted the phased structure of SupLinUCB[Chu et al., 2011] which ensures that the contexts of arms chosen at time points in the same phase constitute a fixed design [Auer, 2002]. Therefore, the arms that are chosen at time points in the same phase are only correlated with rewards from precedent phases and not correlated with rewards in the same phase. Hence, when an estimator $\hat{\beta}$ based on MoM

or truncation is computed from observations in the same phase, the Hoeffding's inequality can be applied to the self-normalized martingales. The bounds of Xue et al. [2020] are state-of-the-art, shaving off $\sqrt{d}$ factor from the bounds of Shao et al. [2018]. However, their algorithm requires to know the time horizon T prior to running the algorithm to determine the optimal number of phases. In this paper, we propose a novel algorithm which does not require the knowledge of T.

4 PRELIMINARIES

In this paper, we propose to estimate the parameter β_i in (1) with Huber regression. Huber loss function [Huber, 1964] is defined by

$$l_\tau(x) = \begin{cases} x^2/2, & \text{if } |x| \le \tau, \\ \tau|x| - \tau^2/2, & \text{if } |x| > \tau, \end{cases}$$

for some constant $\tau > 0$. When Z is a set of time steps, the Huber estimator of β fitted on data observed at time steps in Z is defined as

$$\hat{\beta}(Z) = \arg\min_{\beta \in \mathbb{R}^d} \mathcal{L}_\tau(\beta)$$

where

$$\mathcal{L}_\tau(\beta) = \frac{1}{|Z|} \sum_{r \in Z} l_\tau(y_r - X_r^T \beta).$$

The Huber loss works as a square loss when the difference $|y_r - X_r^T \beta|$ is smaller than τ and works as an absolute loss otherwise. Sun et al. [2020] analyzed the estimation error bound of Huber estimator in the fixed-design setting. They derived the value of τ which minimizes the estimation error bound in the following theorem.

Theorem 1 (Theorem1 of Sun et al. [2020]). *For any $\epsilon > 0$, $\tau_0 \ge \nu_\delta$, the estimator $\hat{\beta}([t])$ with $\tau = \tau_0(t/\epsilon)^{1/(1+\delta)}$ satisfies the bound*

$$||\hat{\beta}([t]) - \beta||_2 \le 4c_l^{-1} L\tau_0 d^{1/2} \left(\frac{\epsilon}{t}\right)^{\frac{\delta}{1+\delta}}$$

with probability at least $1 - (2d+1)e^{-\epsilon}$, provided that

$$t \ge \max\{8M^4 c_l^{-1}\epsilon, \ 2^{4+\delta}M^2 c_l^{-1}\epsilon, \ 16\sqrt{2}c_l^{-1}LMd^{1/2}\epsilon\}.$$

Here, $c_l \le \lambda_{\min}(\hat{\Sigma}([t]))$, $\hat{\Sigma}([t]) = \frac{1}{t}\sum_{r \in [t]} X_r X_r^T$, $M = \max_{1 \le r \le t} ||X_r||_2$, $L = \max_{1 \le r \le t} ||X_r||_\infty$.

In Theorem 1, we observe that the estimation error bound is proportional to the inverse of c_l, the minimum eigenvalue of the Gram matrix $\hat{\Sigma}([t])$. The following theorem shows that when X_r's are sampled independently and identically from a distribution with positive-definite covariance matrix, then $\lambda_{\min}(\hat{\Sigma}([t])) > 0$ with high probability for sufficiently large t.

Theorem 2 (Theorem 1.1 of Tropp [2012]). *Consider a finite sequence $\{X_k\}$ of independent, random, self-adjoint matrix with dimension d. Assume $X_k \succcurlyeq 0$ and $\lambda_{\max}(X_k) \le M$ a.s. Then*

$$\mathbb{P}(\lambda_{\min}(\sum_k X_k) \le \epsilon\mu_{\min}) \le d\exp\left(-\frac{(1-\epsilon)^2\mu_{\min}}{2M}\right),$$

where $\epsilon \in [0, 1]$, $\mu_{\min} := \lambda_{\min}(\mathbb{E}[\sum_k X_k])$.

In bandits however, the problem is that we do not have i.i.d. data due to adaptivity in the choice of arms. In (1), even if X_t's are sampled i.i.d. from $P_\mathcal{X}$, we can only use a subset of X_t's for the estimation of β_i for each arm i. Due to adaptivity in the choice of arms, the subset is not a random sample from the full set of X_t's. We propose to use the forced-sampling strategy of Goldenshluger and Zeevi [2013] to tackle this problem. The main idea behind the strategy is to maintain two estimators for each β_i, one using a small number of observations forcibly sampled in an i.i.d. fashion and another estimator which uses all observations, both forcibly sampled and adaptively sampled. The forced-sample estimator is then used to discard the suboptimal arms and concentrate the arm choices to optimal arms. Consequently, a constant portion of the adaptively sampled data is guaranteed to follow an i.i.d. distribution over a specific region in $\mathcal{X}$. Hereby, the all-sample estimator which uses both forcibly and adaptively sampled data enjoys a tight estimation error bound.

Goldenshluger and Zeevi [2013] first proposed the forced sampling strategy for a contextual bandit setting. Bastani and Bayati [2020] extended this strategy to the multiple-arm setting and used it to prove a tight estimation error bound of the Lasso estimator in bandit settings which also requires a similar minimum eigenvalue bound as the one Huber estimator requires.

Before proceeding, we state few assumptions here.

Assumption 1. *At each time t, a context variable $X_t \in \mathbb{R}^d$ is sampled i.i.d. form $P_\mathcal{X}$. When arm i is pulled, the arm returns a stochastic reward y_t as in equation (1).*

Assumption 2. *Without loss of generality, we assume*

$$||X_t||_2 \le 1, \ ||\beta_i||_2 \le 1, \ \forall t \in [T], i \in [K].$$

If the given norm bound increase, the cumulative regret bound increases by a constant factor.

Assumption 3. *[Arm optimality, Assumption 3 of Bastani and Bayati [2020]] The arm set partitioned into two sets, optimal arm and sub optimal arm.*

$$[K] = K_{opt} \cup K_{sub} \text{ where } K_{opt} \cap K_{sub} = \emptyset.$$

$i \in K_{sub}$ satisfies for $h > 0$,

$$X^T \beta_i < \max_{j \neq i} X^T \beta_j - h \quad \forall X \in \mathcal{X}.$$

For $i \in K_{opt}$ ∃ non-empty set

$$U_i = \left\{ x \in \mathcal{X} | X^T \beta_i > \max_{j \neq i} X^T \beta_j + h \right\}$$

such that $\mathbb{P}_{\mathcal{X}}(X \in U_i) \geq p > 0$.

Assumption 4. *For all $i \in K_{opt}$ defined in Assumption 3, $\lambda_{\min}\left(\mathbb{E}[XX^T | X \in U_i]\right) \geq \gamma$ for $\gamma > 0$, where expectation is taken with respect to the distribution $P_{\mathcal{X}}$.*

Assumption 4 states that the expected Gram matrix of contexts in U_i is positive definite, for each $i \in K_{opt}$. Assumption 3 and 4 also guarantee a positive minimum eigenvalue for $\mathbb{E}[XX^T]$ via the following lemma.

Lemma 1. *Let U be a set with $\mathbb{P}(X \in U) = p$. If $\lambda_{\min}\left(\mathbb{E}[XX^T | X \in U]\right) \geq \gamma$ for $\gamma > 0$, then*

$$\lambda_{\min}\left(\mathbb{E}[XX^T]\right) \geq \gamma p.$$

5 PROPOSED ESTIMATOR AND ALGORITHM

Let the set $T_i := \{(2^n - 1)Kq + j | n \in \mathbb{N} \cup \{0\}, j \in \{q(i-1) + 1, q(i-1) + 2, ..., qi\}, q \in \mathbb{N}\}$ be the set of forced sampling time steps for arm i and $T_{i,t} = T_i \cap [t]$ be the set of forced sampling time steps until time t. Since $|T_{i,t}| = O(\log T)$, the regret at forced sampling steps is $O(K \log T)$ at maximum. Let the set of time steps we choose arm i until time t be $S_{i,t} = \{r | a(r) = i, r \leq t\}$ and we call it all-sample set of the arm i. We have $T_{i,t} \subset S_{i,t}$.

At each time $t \geq 1$, we observe context X_t. If $t \in T_{i,t}$, we pull the arm i. If $t \notin T_{i,t}$, we choose the arm using a two step procedure. First, we eliminate arms that are supposed to be suboptimal using the forced-sampling estimator $\hat{\beta}(T_{i,t-1})$. Afterward, we choose the arm i which has maximum value of $X_t^T \hat{\beta}(S_{i,t})$ among the arms that survived the first step.

We first establish the estimation error bound of the forced sampling estimator.

Lemma 2 (Forced-sampling estimator bound). *Define an event at time t as*

$$A_t := \left\{ ||\hat{\beta}(T_{i,t}) - \beta_i||_2 \leq \frac{h}{4}, \ \forall i \in [K] \right\}.$$

For $\alpha \in (0, 1)$, we have $\mathbb{P}(A_t) \geq 1 - 2K\alpha/t^2$, provided that $t \geq (Kq)^2$.

Proof. The lemma is direct application of Theorem 1. The proof follows the lines in Proposition 2 of Bastani and Bayati [2020]. Since the forced sampling set $T_{i,t}$ is set deterministically prior to running the algorithm, the samples in

---

Algorithm 1 Huber bandit

1: **Input:** h, ν_δ, α
2: $\hat{\beta}(T_{i,t}) = \hat{\beta}(S_{i,0}) = 0^d$
3: **for** $t \in [T]$ **do**
4:     Observe $X_t \sim \mathcal{P}_{\mathcal{X}}$
5:     **if** $t \in T_i$ **then**
6:         $a(t) = i$
7:     **else**
8:         $\mathcal{D} = \{i \in [K] | \max_{j \in [K]} X_t^T \hat{\beta}(T_{j,t-1}) - X_t^T \hat{\beta}(T_{i,t-1}) \leq \frac{h}{2}\}$.
9:         $a(t) = \arg \max_{i \in \mathcal{D}} X_t^T \hat{\beta}(S_{i,t-1})$
10:    **end if**
11:    Update $S_{a(t),t} = S_{a(t),t-1} \cup \{t\}$
12:    Observe reward $y_t = X_t^T \beta_{a(t)} + \epsilon_t$
13:    **if** $t \in T_i$ **then**
14:        $\tau(T_{i,t}) = \nu_\delta(|T_{i,t}|/\log(t^2(2d+1)/\alpha))^{1/(1+\delta)}$
15:        $\hat{\beta}(T_{i,t}) = \arg \min_{\beta \in \mathbb{R}^d} \frac{1}{|T_{i,t}|} \sum_{r \in T_{i,t}} l_\tau(y_r - X_r^T \beta)$
16:    **else**
17:        $\tau(S_{i,t}) = \nu_\delta(|S_{i,t}|/\log(t^2(2d+1)/\alpha))^{1/(1+\delta)}$
18:        $\hat{\beta}(S_{i,t}) = \arg \min_{\beta \in \mathbb{R}^d} \frac{1}{|S_{i,t}|} \sum_{r \in S_{i,t}} l_\tau(y_r - X_r^T \beta)$
19:    **end if**
20: **end for**

$T_{i,t}$ are i.i.d.. Therefore, the minimum eigenvalue bound c_l of the Gram matrix can be derived from Lemma 1 and Theorem 2. $\square$

The following lemma states that under the high-probability event A_t, the set $\mathcal{D}$ of arms after discarding the suboptimal arms using $\hat{\beta}(T_{i,t})$ always contains the optimal arm $a^*(t)$.

Lemma 3 (Lemma EC.18 of Bastani and Bayati [2020]). *If A_{t-1} holds, then $\mathcal{D} = \{i \in [K] | \max_{j \in [K]} X_t^T \hat{\beta}(T_{j,t-1}) - X_t^T \hat{\beta}(T_{i,t-1}) \leq \frac{h}{2}\}$ contains the optimal arm $a^*(t)$ and no arms from K_{sub}.*

Now we derive the estimation error bound of the all sample estimator which is sharper than the constant $\frac{h}{4}$ in Lemma 2 due to larger number of samples. We first define the following subset of $[t]$ which describes the time steps where contexts are sampled from the optimal regions U_i's and where the forced sampling estimators up to that time point have low estimation error bound.

$$\mathcal{A}_{i,t} := \{r \in [t] | A_{r-1} \text{ holds}, X_r \in U_i \text{ and } r \notin \cup_{j \in [K]} T_{j,t}\}.$$

Lemma 4 states that $\mathcal{A}_{i,t}$ is a subset of $S_{i,t}$ and Lemma 5 states that the size of $\mathcal{A}_{i,t}$ is large enough. Particularly, Lemma 5 guarantees that the size of $\mathcal{A}_{i,t}$ is at least proportional to t.

Lemma 4 (All sample set, Lemma EC.11 of). *Bastani and Bayati [2020]] For $i \in K_{opt}$, if $t \in \mathcal{A}_{i,t}$, then $a(t) = i$.*

Lemma 5 (All sample set, Lemma EC.14 of Bastani and Bayati [2020]). *If $t \geq (Kq)^2$,*

$$\mathbb{P}(|\mathcal{A}_{i,t}| \geq tp/4) \geq 1 - \frac{\alpha}{t^2}.$$

Observe that the random variables $\{x_r | r \in \mathcal{A}_{i,t}\}$ are i.i.d. in U_i. This is because the event $\{x_r \in U_i\}$ is independent of the event A_{r-1} while the event $\{r \notin T_{j,t}\}$ is deterministic. Therefore, we can prove $\lambda_{\min}(\hat{\Sigma}(\mathcal{A}_{i,t}))$ is strictly positive with high probability via Assumption 4 and Theorem 2. Finally, we can derive a lower bound for $\lambda_{\min}(\hat{\Sigma}(S_{i,t}))$ using the following lemma.

Lemma 6 (Lemma EC.7 of Bastani and Bayati [2020]). *Let A be a set of random variables. Consider a subset $A' \subset A$ of i.i.d. random variables. If $\lambda_{\min}(\hat{\Sigma}(A')) \geq \gamma$ for some $\gamma > 0$, then*

$$\lambda_{\min}(\hat{\Sigma}(A)) \geq \frac{|A'|}{|A|}\gamma.$$

Lemma 6 states that we can get the minimum eigenvalue bound of the Gram matrix for a possibly non i.i.d. set A, if we know the bound for an i.i.d. subset of the set A. Substituting $S_{i,t}$ into A and $\mathcal{A}_{i,t}$ into A' in Lemma 6, we get the minimum eigenvalue bound of $\hat{\Sigma}(S_{i,t})$. Since $|\mathcal{A}_{i,t}|$ is proportional to t and $|S_{i,t}| \leq t$, the ratio $|A'|/|A|$ is of constant order.

We now adapt Theorem 1, which is originally proved for independent data, to work for adaptively collected data. Using the lower bound result on $\lambda_{\min}(\hat{\Sigma}(S_{i,t}))$ for arms $i \in K_{opt}$, we obtain a tight estimation error bound of the all sample estimator for arms in K_{opt}.

Lemma 7 (All sample estimator bound). *Let $\tau = \tau_0(|S_{i,t}|/\log(t^2(2d+1)/\alpha))^{1/(1+\delta)}$, $\tau_0 \geq \nu_\delta$. If $t \geq (Kq)^2$, we have with probability at least $1 - \frac{3\alpha}{t^2}$,*

$$||\hat{\beta}(S_{i,t}) - \beta_i||_2$$
$$\leq \left(\frac{4}{pt}\log(t^2(2d+1)/\alpha)\right)^{\delta/(1+\delta)} \frac{32\tau_0 d^{1/2}}{\gamma p}.$$

for $i \in K_{opt}$,

Proof. We mainly provide the difference from the proof of Sun et al. [2020]. For generality the proof below is based on the set $[t]$ not $S_{i,t}$. LinOFUL [Abbasi-Yadkori et al., 2011] could achieve the tight regret bound of $\tilde{O}(d\sqrt{T})$ using self-normalized martingales inequality [de la Pena et al., 2004, Peña et al., 2009] on the Mahalanobis norm $||\beta^* - \hat{\beta}_t||_{V_t} \approx ||\sum_{r=1}^t X_{a(r),r}\epsilon_{a(r),r}||_{V_t^{-1}}$. However, this inequality only holds on sub-Gaussian error distribution. Instead, if we know the minimum eigenvalue bound of the Gram matrix, we can obtain L_2-norm bound

$$||\hat{\beta}([t]) - \beta_i||_2 \leq 2c_l^{-1}||\sum_{r=1}^t \psi_\tau(\epsilon_r)X_r||_2$$

where $c_l \leq \lambda_{\min}(\sum_{r=1}^T X_r X_r^T)$, and $\psi_\tau(\epsilon_r) := l_\tau'(\epsilon_r)$ is the derivative of the Huber loss. The detailed explanation can be found in Section C.3 of Sun et al. [2020]. The L_2-norm is bounded by max-norm.

$$||\sum_{r=1}^t \psi_\tau(\epsilon_r)X_r||_2 \leq d^{1/2}||\sum_{r=1}^t \psi_\tau(\epsilon_r)X_r||_\infty$$
$$= d^{1/2}\tau \max_{1 \leq j \leq d}|\sum_{r=1}^t (X_{rj}/\tau)\psi_\tau(\epsilon_r)|, \tag{3}$$

where we use $\max_{1 \leq r \leq t}||X_r||_\infty \leq 1$ and X_{rj} is j-th element of the context X_r. We observe that in bandit settings, the right-hand side of (3) is the sum of adapted data. To bound this quantity, we invoke a bound on supermartingales. We can first construct a supermartingale as follows. Let

$$M_t := \exp\left(\sum_{r=1}^t \left[(X_{rj}/\tau)\psi_\tau(\epsilon_r) - \frac{\nu_\delta}{\tau^{1+\delta}}\right]\right).$$

Then

$$\mathbb{E}[M_t|\mathcal{F}_{t-1}]$$
$$= M_{t-1}\mathbb{E}\left[\exp\left((X_{tj}/\tau)\psi_\tau(\epsilon_t)\right)|\mathcal{F}_{t-1}\right]/\exp\left(\frac{\nu_\delta}{\tau^{1+\delta}}\right)$$
$$\leq M_{t-1}\mathbb{E}[1 + X_{tj}(\epsilon_t/\tau) + |\epsilon_t/\tau|^{1+\delta}|\mathcal{F}_{t-1}]/\exp\left(\frac{\nu_\delta}{\tau^{1+\delta}}\right)$$
$$= M_{t-1}\left[1 + \frac{\nu_\delta}{\tau^{1+\delta}}\right]/\exp\left(\frac{\nu_\delta}{\tau^{1+\delta}}\right)$$
$$\leq M_{t-1}\exp\left(\frac{\nu_\delta}{\tau^{1+\delta}}\right)/\exp\left(\frac{\nu_\delta}{\tau^{1+\delta}}\right)$$
$$= M_{t-1}$$

shows that M_t is a supermartingale with $M_0 := 1$, where the second inequality is derived from

$$\exp((X_{rj}/\tau)\psi_\tau(\epsilon_r))$$
$$\leq (1 + \epsilon_r/\tau + |\epsilon_r/\tau|^{1+\delta})^{X_{rj}\mathbb{1}_{x_{rj}>0}}$$
$$\cdot (1 - \epsilon_r/\tau + |\epsilon_r/\tau|^{1+\delta})^{-X_{rj}\mathbb{1}_{x_{rj}<0}}$$
$$\leq 1 + X_{rj}(\epsilon_r/\tau) + |\epsilon_r/\tau|^{1+\delta}.$$

Iteratively applying the law of total expectation on M_t gives $\mathbb{E}[M_t] \leq 1$ and hence,

$$\mathbb{E}\left[\exp\left(\sum_{r=1}^t (X_{rj}/\tau)\psi_\tau(\epsilon_r)\right)\right] \leq \exp(t\nu_\delta \tau^{-1-\delta}).$$

Markov's inequality gives

$$\mathbb{P}\left(\sum_{r=1}^t (X_{rj}/\tau)\psi_\tau(\epsilon_r) > \nu_\delta tz\right)$$
$$\leq \exp(-\nu_\delta tz)\mathbb{E}\left[\exp\left(\sum_{r=1}^t (X_{rj}/\tau)\psi_\tau(\epsilon_r)\right)\right]$$
$$\leq \exp(\nu_\delta t(\tau^{-1-\delta} - z))$$

for some $z > 0$. Then when $\tau \geq (2/z)^{1/(1+\delta)}$ and $z = \frac{2}{\nu_\delta t} \log(t^2(2d+1)/\alpha)$, with probability at least $1 - \alpha/t^2$, the same bound as in Theorem 1 can be obtained. We are left with the minimum eigenvalue bound c_l for a adaptively chosen data set $S_{i,t}$. First consider the i.i.d. subset $\mathcal{A}_{i,t}$ of $S_{i,t}$. Theorem 2 states that

$$\mathbb{P}\left(\lambda_{\min}\left(\hat{\Sigma}(\mathcal{A}_{i,t})\right) \leq \frac{\gamma}{2}\right) \leq d \exp\left(-\frac{|\mathcal{A}_{i,t}|\gamma}{8}\right),$$

for $\gamma > 0$. The size of the set $\mathcal{A}_{i,t}$ is guaranteed by Lemma 5. When $q \geq (\log(d/\alpha) + 1)\frac{128}{\gamma p}$, with probability at least $1 - \frac{\alpha}{t^2}$,

$$\begin{aligned}
|\mathcal{A}_{i,t}| > \frac{tp}{4} \geq \frac{|T_{i,t}|p}{4} &\geq \frac{pq}{8} \log t \\
&\geq \frac{16}{\gamma}(\log(d/\alpha) + 1) \log t \\
&\geq \frac{8}{\gamma}(\log(d/\alpha) + \log t^2).
\end{aligned}$$

Therefore, together with Lemma 6, with probability at least $1 - \frac{2\alpha}{t^2}$,

$$\lambda_{\min}\left(\hat{\Sigma}(\mathcal{A}_{i,t})\right) \geq \frac{\gamma}{2} \text{ and hence,}$$
$$\lambda_{\min}\left(\hat{\Sigma}(S_{i,t})\right) > \frac{\gamma|\mathcal{A}_{i,t}|}{2|S_{i,t}|} > \frac{\gamma|\mathcal{A}_{i,t}|}{2t} > \frac{p\gamma}{8}.$$

$\square$

The Lemma 8 states the size of $|T_{i,t}|$.

Lemma 8 (Lemma EC.8 of Bastani and Bayati [2020]). *When $t \geq (Kq)^2$, $Kq \geq 4$,*

$$\frac{1}{2}q \log t < |T_{i,t}| < 2q \log t.$$

Finally, we are ready to obtain the regret bound of order $O(\sqrt{d}T^{\frac{1}{1+\delta}}(\log T)^{\frac{\delta}{1+\delta}})$.

Theorem 3. *When*

$$\begin{aligned}
q \geq \max\Bigg\{ &6\left(\log(5K/\phi) + 1\right)\left(\frac{32\tau_0 d^{1/2}}{h\gamma p}\right)^{(1+\delta)/\delta}, \\
&\frac{36}{p^2}\left(\log(5K/\phi) + 1\right), \left(\log(5dK/\phi) + 1\right)\frac{128}{\gamma p}, \\
&\left(\log(5K/\phi) + 1\right)\frac{3072}{\gamma p}d^{1/2}\Bigg\},
\end{aligned}$$

and $\tau_o \geq \nu_\delta$, the cumulative regret $R(T)$ is bounded by

$$\begin{aligned}
R(T) \leq &(T^{\frac{1}{1+\delta}} - 1)(1 + \delta) \cdot \\
&\left(\frac{4}{p}\log(T^2(2d+1)5K/\phi)\right)^{\delta/(1+\delta)}\frac{64\tau_0 d^{1/2}}{\gamma p} \\
&+ 4Kq \log T + 2(Kq)^2.
\end{aligned}$$

with probability at least $1 - \phi$.

proof of theorem 3. We consider two cases; (a) when $t < (Kq)^2$ or $t \in \cup_{i\in[K]}T_{i,t}$, (b) when $t \geq (Kq)^2$ and $t \notin \cup_{i\in[K]}T_{i,t}$. For (a), we know that $|\cup_{i\in[K]}T_{i,t}| \leq 2Kq \log T$ from Lemma 8. Hence, the time occupied by the event (a) is at most $4Kq \log T + 2(Kq)^2$. For (b), due to Lemma 2, we have with probability at least $1 - 4\alpha K$, A_t holds $\forall t \in \mathbb{N}$. When A_{t-1} holds, Lemma 3 ensures that the set $\mathcal{D}$ contains optimal arm $a^*(t)$ and no arm from K_{sub}. Then all sample estimator bound in Lemma 7 hold for all arms in $\mathcal{D}$. That is, with probability at least $1 - 5\alpha K$, $\forall i \in \mathcal{D}$, we have the bound in Lemma 7. Then let $\phi = 5\alpha K$ gives the desired result. $\square$

If we add additional assumption of marginal condition, we can get $\tilde{O}(\log T)$ expected regret.

Assumption 5 (Assumption 2 of Bastani and Bayati [2020]). *$\exists C_0 \in \mathbb{R}^+$ such that $\forall i, j \in [K]$ where $i \neq j$,*

$$\mathbb{P}(0 < |X^T(\beta_i - \beta_j)| \leq \kappa) \leq C_0\kappa \quad \forall \kappa \in \mathbb{R}^+.$$

Theorem 4. *When*

$$\begin{aligned}
q \geq \max\Bigg\{ &6\left(\log(5K/\phi) + 1\right)\left(\frac{32\tau_0 d^{1/2}}{h\gamma p}\right)^{(1+\delta)/\delta}, \\
&\frac{36}{p^2}\left(\log(5K/\phi) + 1\right), \left(\log(5dK/\phi) + 1\right)\frac{128}{\gamma p}, \\
&\left(\log(5K/\phi) + 1\right)\frac{3072}{\gamma p}d^{1/2}\Bigg\},
\end{aligned}$$

and $\tau_o \geq \nu_\delta$, the expected regret is

$$\begin{aligned}
\sum_{t=1}^T \mathbb{E}[r_t] = &\sum_t^T \mathbb{E}[X^T\beta_{a^*(t)} - X^T\beta_{a(t)}] \\
\leq &((\log T)^2 + \log T)4^7 d\left(\frac{\tau_0}{\gamma}\right)^2\frac{1}{p^3}KC_0 \\
&+ 12K(2d+1)(\log T + 1)
\end{aligned}$$

when $\delta = 1$ and

$$\begin{aligned}
\sum_{t=1}^T \mathbb{E}[r_t] \leq &T^{\frac{1-+\delta}{1+\delta}}(\log T)^{\frac{2\delta}{1+\delta}}64^2 16^{\frac{\delta}{1+\delta}}d\left(\frac{\tau_0}{\gamma}\right)^2\frac{1}{p^{\frac{2+4\delta}{1+\delta}}} \\
&\cdot KC_0\left(\frac{1+\delta}{1-\delta}\right) + 12K(2d+1)(\log T + 1)
\end{aligned}$$

when $0 < \delta < 1$.

6 EXPERIMENTS

We compare the Huber bandit algorithm with TOFU [Shao et al., 2018] and OLS bandit. OLS bandit has the same structure of the forced-sampling as the Huber bandit but the OLS estimator substitutes the Huber estimator. TOFU

Figure 1: Cumulative regret of Huber bandit, OLS bandit, TOFU.

is designed for the single parameter $\beta \in R^d$ and arm-specific contexts, $X_{i,t} \in \mathbb{R}^d, i \in [K]$ setting. To bring the algorithm to our setting, we reshape arm parameter $\beta_i \in \mathbb{R}^d, i \in [K]$ into one parameter $\beta \in R^{dK}$ and context X_t into $X_{i,t} \in \mathbb{R}^{dK}, i \in [K]$ such that $X_{i,t}^T \beta = X_t^T \beta_i$. We randomly generate context $x \in \mathbb{R}^d$ and arm parameter $\beta_i \in \mathbb{R}^d, i \in [K]$ from a uniform distribution in $[-1, 1]$ and normalize them to satisfy the assumption 2. Due to random generations of the samples, the assumption 3 might not be satisfied. Instead, we fix the value h equal to 0.2. Even though, the Huber bandit shows a good performance. The error term ϵ_t is generated from the student's t-distribution with a degree of freedom(df) $\{1.1, 1.5, 2, 3\}$. If $df > n$, fi-

nite n-th moment of the student's t-distribution exists. In the experiment, we assume $1 + \delta = $ df -0.05 moments exist. We take the dimension $d = 5$, the number of arms $K = 10$, the time horizon $T = 1000$. We run 100 iterations each with a new data set. The results of cumulative regret of Huber, OLS, and TOFU, averaged over 100 iterations are shown in figure 1. The shade of the graph shows the standard deviation of 100 iterations. For the hyperparameter of the Huber bandit, we use $q = 3, \alpha = 0.001$, of the OLS bandit we use $q = 3$, and of the TOFU, we use $\alpha = 0.1$, conf $= 0.5$. The value conf indicates the size of the confidence region. We found the hyper parameter from grid search with $q = \{2, 3, 4\}$, conf$= \{0.5, 1, 1.5\}, \alpha = \{0.001, 0.01, 0.1\}$. We note that we used the size of the confidence region as the hyperparameter of the TOFU since the theoretical confidence region was too high and the cumulative regret did not converge.

7 CONCLUSION

In this paper, we proposed the Huber bandit algorithm robust to heavy-tailed error. The theoretical analysis shows that the algorithm achieves the regret bound of $O(\sqrt{d}T^{\frac{1}{1+\delta}}(\log T)^{\frac{\delta}{1+\delta}})$ which reproduces the state-of-the-art regret bound for linear bandits with sub-Gaussian errors when $\delta = 1$. The practical performance was proved by comparing it with OLS bandit and the state-of art bandit algorithm designed for heavy-tailed data.

References

Yasin Abbasi-Yadkori, Dávid Pál, and Csaba Szepesvári. Improved algorithms for linear stochastic bandits. *Advances in neural information processing systems*, 24, 2011.

Peter Auer. Using confidence bounds for exploitation-exploration trade-offs. *Journal of Machine Learning Research*, 3(Nov):397–422, 2002.

Hamsa Bastani and Mohsen Bayati. Online decision making with high-dimensional covariates. *Operations Research*, 68(1):276–294, 2020.

Sébastien Bubeck, Nicolo Cesa-Bianchi, and Gábor Lugosi. Bandits with heavy tail. *IEEE Transactions on Information Theory*, 59(11):7711–7717, 2013.

Wei Chu, Lihong Li, Lev Reyzin, and Robert Schapire. Contextual bandits with linear payoff functions. In *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics*, pages 208–214. JMLR Workshop and Conference Proceedings, 2011.

Roger M Cooke and Daan Nieboer. Heavy-tailed distributions: Data, diagnostics, and new developments. *Resources for the Future Discussion Paper*, (11-19), 2011.

Victor H de la Pena, Michael J Klass, and Tze Leung Lai. Self-normalized processes: exponential inequalities, moment bounds and iterated logarithm laws. 2004.

Alexander Goldenshluger and Assaf Zeevi. A linear response bandit problem. *Stochastic Systems*, 3(1):230–261, 2013.

Peter J Huber. Robust estimation of a location parameter. *The Annals of Mathematical Statistics*, pages 73–101, 1964.

Marat Ibragimov, Rustam Ibragimov, and Johan Walden. *Heavy-tailed distributions and robustness in economics and finance*, volume 214. Springer, 2015.

Huitian Lei, Yangyi Lu, Ambuj Tewari, and Susan A Murphy. An actor-critic contextual bandit algorithm for personalized mobile health interventions. *arXiv preprint arXiv:1706.09090*, 2017.

Andres Munoz Medina and Scott Yang. No-regret algorithms for heavy-tailed linear bandits. In *International Conference on Machine Learning*, pages 1642–1650. PMLR, 2016.

Victor H Peña, Tze Leung Lai, and Qi-Man Shao. *Self-normalized processes: Limit theory and Statistical Applications*. Springer, 2009.

Svetlozar Todorov Rachev. *Handbook of heavy tailed distributions in finance: Handbooks in finance, Book 1*. Elsevier, 2003.

Han Shao, Xiaotian Yu, Irwin King, and Michael R Lyu. Almost optimal algorithms for linear stochastic bandits with heavy-tailed payoffs. *Advances in Neural Information Processing Systems*, 31, 2018.

Milan Stehlík, Rastislav Potockỳ, Helmut Waldl, and Zdeněk Fabián. On the favorable estimation for fitting heavy tailed data. *Computational Statistics*, 25:485–503, 2010.

Qiang Sun, Wen-Xin Zhou, and Jianqing Fan. Adaptive huber regression. *Journal of the American Statistical Association*, 115(529):254–265, 2020.

Joel A Tropp. User-friendly tail bounds for sums of random matrices. *Foundations of computational mathematics*, 12: 389–434, 2012.

Sofía S Villar, Jack Bowden, and James Wason. Multi-armed bandit models for the optimal design of clinical trials: benefits and challenges. *Statistical science: a review journal of the Institute of Mathematical Statistics*, 30(2): 199, 2015.

Bo Xue, Guanghui Wang, Yimu Wang, and Lijun Zhang. Nearly optimal regret for stochastic linear bandits with heavy-tailed payoffs. *arXiv preprint arXiv:2004.13465*, 2020.