LONG RANGE LANGUAGE MODELING VIA GATED STATE SPACES

ABSTRACT

State space models have shown to be effective at modeling long range dependencies, especially on sequence classification tasks. In this work we focus on autoregressive sequence modeling over English books, Github source code and ArXiv mathematics articles. Based on recent developments around the effectiveness of gated activation functions, we propose a new layer named *Gated State Space* (GSS) and show that it trains significantly faster than the diagonal version of S4 (i.e. DSS) on TPUs, is competitive with several well-tuned Transformer-based baselines and exhibits zero-shot generalization to longer inputs while being straightforward to implement. Finally, we show that leveraging self-attention to model local dependencies improves the performance of GSS even further.

1 INTRODUCTION

Modeling long range dependencies on sequential data is a crucial step towards closing the gap with human-level performance on many tasks. Attention based models like Transformer (Vaswani et al., 2017) have proven to be a strong choice of backbone architecture for a considerable number of tasks across modalities and scale (Devlin et al., 2019; Brown et al., 2020; Dosovitskiy et al., 2021). Vanilla Multi-Head-Attention famously incurs $\Omega(L^2)$ penalty in modeling a sequence of length L. This is prohibitive at best for tasks where the model is required to capture long range dependencies from various parts of the input. Over the years, a variety of improvements have been proposed to alleviate this quadratic complexity (Tay et al., 2020; Choromanski et al., 2021; Ramsauer et al., 2021; Wang et al., 2020; Katharopoulos et al., 2020; Peng et al., 2021; Ainslie et al., 2020; Zaheer et al., 2020; Beltagy et al., 2020; Dai et al., 2020; Kitaev et al., 2020; Vyas et al., 2020).

On a somewhat orthogonal direction, attention-free models based on state spaces, such as S4 (Gu et al., 2022a) and DSS (Gupta et al., 2022), have shown remarkable improvements on Long Range Arena (LRA) (Tay et al., 2021), a benchmark designed with long range modeling as its focus and consists of diverse tasks with 1k-16k sequence length across modalities. These models require careful initialization, originally borrowing ideas from the theory of HiPPO matrices (Voelker et al., 2019; Gu et al., 2020), to achieve good results on LRA.

In this work, we explore and extend the use of state space models by focusing solely on the task of autoregressive sequence modeling (Brown et al., 2020; Rae et al., 2021; Chowdhery et al., 2022; Zhang et al., 2022; Hoffmann et al., 2022; Srivastava et al., 2022). Several key properties endowed by the state space model family makes it particularly attractive in the context of language modeling. First, it reduces the $\Omega(L^2)$ complexity on input sequence length to $O(L \log L)$. This complexity results from the use of Fast Fourier Transform (FFT) (Cooley & Tukey, 1965) for performing convolutions, which will be described in detail in later sections. Second, the state space model is fully parallelizable in the length dimension. This is an arguably subtle but an important property at training time. Note that transformers are also fully parallelizable, a worthy advantage over traditional RNNs for modeling sequences, which otherwise incurs only an $O(L)$ penalty. While this parallelism is useful at training time, it may also be a curse at inference time where decoding every token requires attending to the whole past. The ideal model is parallelizable at training time but incurs a small constant cost (per decoded token) at inference time. This brings us to the final point. Due to the inherent convolution-recurrence equivalence of the state space model, it can be made to accumulate state and unroll like an RNN at inference time without any approximations.

```
def gss(x, F=4096, L=4096, E=1024, H=256):
    shortcut, x = x, norm(x)
    v = dense(x, F, activation='gelu')
    u = dense(x, H, activation='gelu')
    y = dss(u, H, L)
    # yh1,..,yhL are linear in uh1,..,uhL
    uc = dense(y, F)
    o = dense(uc * v, E)
    return o + shortcut
```

Figure 1: (a) Our proposed Gated State Space (GSS) layer, (b) Pseudocode for GSS (full implementation in §A.2).

Despite these attractive properties, we found that current state space models (e.g. S4, DSS) run slower than we expected on TPUs, our accelerator of choice. We take this opportunity to modify the architecture to reduce dimensionality of specific bottleneck operations. Our proposed changes borrow from a well-supported empirical success of gating units (Shazeer, 2020). Specifically, Hua et al. (2022) observed that replacing the Feed-Forward layer in the Transformer with gating units allows for a reduced dimensionality when mixing tokens along the length dimension using self-attention. We extend the use of gating units to state space model family and observe that, even in our context, the use of gating units allows for a reduction in dimensionality when performing FFT operations, which we observed to be the main bottleneck behind slow training. Furthermore, somewhat contrary to observations made by S4 and DSS authors, we found the performance on language modeling tasks to be much less sensitive to initialization: only the scale and structural aspects of initialization of state space variables were important and not the exact values. We were able to successfully train the model while initializing the state space variables randomly. This departs from the reliance of the design on the theory of HiPPO matrices, which led the S4 model to employ several numerical linear algebra tricks to able to make it work. Combining both of these contributions, we propose a layer named Gated State Space (GSS) (Figure 1), which we empirically verified to be 2-3× faster than DSS while keeping the perplexity on several language modeling benchmarks (Table 1).

Going one step further, we also perform a comparison with well-tuned and performant baselines reported in Block Recurrent Transformers (Hutchins et al., 2022), on several long range language modeling benchmarks over modalities such as English books, raw source code from Github and LaTeX source of ArXiv mathematics articles. As detailed in Table 2, while our GSS model currently lags behind on some tasks when compared in the fixed-parameter setting, it is competitive in the *fixed-compute* setting where we measure compute as the amount of TPUv4 hours spent on training, which is a good proxy for the cost of training that model. Furthermore, we also experimented with a hybrid model in which we sparingly interleave Transformer layers (having local attention) in a GSS stack to allow for a richer modeling of short range interactions. To our delight, this further improves performance at (roughly) no extra training cost, both in terms of parameters and compute.

In our experiments we *train* on sequences of length at most 4k, but *evaluate* on a wide range of sequence lengths up to 65k. The performance actually *improves* as the sequence length is increased, suggesting that GSS utilizes extra context despite not being trained with this context. Further, at inference time, state space models including GSS are quite efficient since decoding can happen in recurrent mode (as much as 60× better in the case of S4 (Gu et al., 2022a)). Though, the hybrid model which also uses local attention complicates this advantage a bit.

In summary, we propose GSS, a simple-to-implement alternative to S4 and DSS which trains 2-3× faster, and is competitive with Transformer-based baselines on long-range language modeling benchmarks.

2 RELATED WORK

In recent years, attention-based models have emerged as a dominant technique for sequence modeling, achieving remarkable improvements in a wide range of tasks, starting in NLP (Vaswani et al., 2017;

Devlin et al., 2019; Radford et al., 2019; Liu et al., 2019), then moving to other classical machine learning areas such as computer vision (Dosovitskiy et al., 2021) and now to the physical sciences (Avsec et al., 2021; Jumper et al., 2021). In brief, an attention layer takes as input three matrices K, Q, V in $\mathbb{R}^{L \times d}$, which should usually be thought of as length L lists of d-dimensional vectors. The attention layer then outputs $Y = \sigma(QK^\top)V \in \mathbb{R}^{L \times d}$ where σ indicates a row-wise softmax operation. In the popular self-attention variant, K, Q and V are themselves learned functions of a single input sequence $X = (x_1, \ldots, x_L)^\top \in \mathbb{R}^{L \times d}$. Unfortunately, this requires $O(L^2)$ time and space due to the need to construct the matrix $QK^\top \in \mathbb{R}^{L \times L}$.

The surge in popularity of attention has engendered a corresponding surge in interest on methods for increasing the context length L while controlling the $O(L^2)$ computational cost. Broadly speaking, most approaches fall into two camps: those that attempt to "linearize" attention, and those that sparsify the attention matrix $QK^\top$. The first camp exploits the fact that, when softmax is removed, we have $(QK^\top)V = Q(K^\top V)$, where now $K^\top V \in \mathbb{R}^{d \times d}$ and so the whole operation is only linear in L rather than quadratic. This idea is the underlying principle behind methods such as the Performer (Choromanski et al., 2021), Linear Attention (Katharopoulos et al., 2020), Random Feature Attention (Peng et al., 2021) or cosFormer (Qin et al., 2022). In the other camp, one simply sparsifies the matrix $QK^\top$ limit computation and storage requirements. This camp includes BigBird (Zaheer et al., 2020), GMAT (Gupta & Berant, 2020), Longformer (Beltagy et al., 2020), and Blockwise self-attention (Qiu et al., 2020), Reformer (Kitaev et al., 2020) and Hawthorne et al. (2022). In essence, these approaches can be viewed as a trade-off between performance, and computation time (or memory).

Despite its current empirical success, the attention mechanism is not the only approach for modeling sequence data, nor even necessarily the most natural. For example, a classical *recursive* or *state space* layer operates on an input $(x_1, \ldots, x_L)^\top \in \mathbb{R}^{d \times L}$ by defining a sequence of "states" $s_{t+1} = T(s_t, x_{t+1})$ and returning the output sequence $y_t = E(s_t)$ where T and E are learned "transition" and "emission" functions. Assuming T and E can be computed efficiently, this requires only $O(L)$ time in theory. Through the years, many different possibilities for T and E have appeared, such as the simple RNN, which sets T and E to both be MLPs, or more complicated LSTM layer (Hochreiter & Schmidhuber, 1997). Nevertheless, the performance of state space models has in many cases been quickly surpassed by attention.

There have been several recent efforts to recapture the favorable properties of state space models while maintaining or improving upon the performance of attention models, such as the Transformer-XL (Dai et al., 2019) or the Block-Recurrent Transformer (Hutchins et al., 2022). Of particular relevance to this paper, alternative models based on linear dynamical systems have shown great promise (Gu et al., 2022a; Gupta et al., 2022; Gu et al., 2022b). Rather than attempting to "fix" attention, these are classical state space models where both T and E are linear. An important insight in these works is to recast the model as a convolution with a very large kernel, and then leverage the convolution theorem to compute the sequence y_t in $O(L \log(L))$ time using Fast Fourier Transform (Cooley & Tukey, 1965). While seemingly worse than $O(L)$, this operation is easily parallelizable, and so in practice is significantly faster. Moreover, in a situation in which the $\log(L)$ factor is onerous, one may still fall back to the serial $O(L)$ algorithm. Our approach will build on these works.

3 METHOD

We start by reviewing the necessary background on state spaces required to fully describe our model (§3.1). We then formally define our GSS model in §3.2 and the GSS-Transformer-Hybrid in §3.3.

3.1 STATE SPACE PRELIMINARIES

While in this work we are interested in modeling sequences of vectors, let us first review how state space models define a sequence-to-sequence map for 1-D sequences.

State Spaces A discretized state space, parameterized by a state matrix $A \in \mathbb{R}^{N \times N}$, vectors $B \in \mathbb{R}^{N \times 1}$, $C \in \mathbb{R}^{1 \times N}$ and a sample time $\Delta \in \mathbb{R}_{>0}$ defines a sequence-to-sequence map from input

$(u_0, \ldots, u_{L-1}) = u \in \mathbb{R}^L$ to output $(y_0, \ldots, y_{L-1}) = y \in \mathbb{R}^L$ via the recurrence[1],

$$x_k = \overline{A}x_{k-1} + \overline{B}u_k \quad , \quad y_k = \overline{C}x_k$$
$$\overline{A} = e^{A\Delta} \;, \; \overline{B} = (\overline{A} - I)A^{-1}B \;, \; \overline{C} = C \; . \tag{1}$$

Assuming $x_{-1} = 0$ for simplicity, the above recurrence can be explicitly unrolled as

$$y_k \;=\; \sum_{j=0}^{k} \overline{CA}^j\overline{B} \cdot u_{k-j} \; . \tag{2}$$

For convenience, the scalars $\overline{CA}^k\overline{B}$ are gathered to define the SSM kernel $\overline{K} \in \mathbb{R}^L$ as

$$\overline{K} \;=\; (\overline{CB}, \overline{CAB}, \ldots, \overline{CA}^{L-1}\overline{B}) \;=\; (\, Ce^{A \cdot k\Delta}(e^{A\Delta} - I)A^{-1}B \,)_{0 \le k < L}, \tag{3}$$

where the last equality follows by substituting the values of $\overline{A}, \overline{B}, \overline{C}$ from Equation 1. Hence,

$$y_k \;=\; \sum_{j=0}^{k} \overline{K}_j \cdot u_{k-j} \; . \tag{4}$$

where $\overline{K}_j$ denotes the value of the kernel at position j. Given an input sequence $u \in \mathbb{R}^L$, it is possible to compute the output $y \in \mathbb{R}^L$ sequentially via the recurrence in Equation 1. While this property is highly desirable for autoregressive decoding, a sequential computation is prohibitively slow to train with long inputs and, instead, Equation 4 can be used to compute all elements of y in parallel, provided we have already computed $\overline{K}$.

Computing y from u and $\overline{K}$ is easy. Given an input sequence $u \in \mathbb{R}^L$ and the SSM kernel $\overline{K} \in \mathbb{R}^L$, naively using Equation 4 for computing y would require $O(L^2)$ multiplications. Fortunately, this can be done much more efficiently by observing that for the univariate polynomials

$$\overline{K}(z) = \sum_{i=0}^{L-1} \overline{K}_i z^i \;\; \text{and} \;\; u(z) = \sum_{i=0}^{L-1} u_i z^i,$$

y_k is the coefficient of z^k in the polynomial $\overline{K}(z) \cdot u(z)$, i.e. all y_k's can be computed simultaneously by multiplying two degree $L-1$ polynomials. It is well-known that this can be done in $O(L \log(L))$ time via Fast Fourier Transform (FFT) (Cormen et al., 2009). We denote this fast computation of Equation 4 via the discrete convolution as

$$y = \overline{K} *_{\mathrm{c}} u \; . \tag{5}$$

Diagonal State Spaces The challenging part is computing $\overline{K}$ itself as it involves computing L distinct matrix powers (Equation 3). Gupta et al. (2022) observed that the state matrix A can be assumed to be diagonal without loss in performance, thereby allowing a straighforward computation of $\overline{K}$. Their $\mathrm{DSS}_{\mathrm{EXP}}$ model (DSS from hereon) assumes A to be a diagonal matrix $\mathrm{diag}(\lambda_1, \ldots, \lambda_N)$ and assumes $B = (1)_{1 \le i \le N}$. DSS has parameters $\Lambda_{\mathrm{re}}, \Lambda_{\mathrm{im}} \in \mathbb{R}^N$, $C \in \mathbb{C}^N$ and $\Delta_{\mathrm{log}} \in \mathbb{R}$. The diagonal of A (i.e. $(\lambda_1, \ldots, \lambda_N)$) is computed as $-\text{elementwise-exp}(\Lambda_{\mathrm{re}}) + i \cdot \Lambda_{\mathrm{im}}$ where $i = \sqrt{-1}$ and Δ is computed as $\exp(\Delta_{\mathrm{log}}) \in \mathbb{R}_{>0}$. For this parameterization, the kernel (Equation 3) can be computed as a matrix-vector product

$$\overline{K} \;=\; (C * \big((e^{\lambda_i \Delta} - 1)/\lambda_i\big)_{1 \le i \le N})_{1 \times N} \cdot \text{elementwise-exp}(P_{N \times L}) \tag{6}$$

where $P_{i,k} = \lambda_i k\Delta$ and $*$ denotes elementwise multiplication.

This formally defines a *linear* sequence-to-sequence map for 1-D sequences. In the case of sequences of H-dimensional vectors, state space models are applied individually on the H features as follows.

---

[1]Discretization used in Equation 1 relies on zero order hold (ZOH) which assumes a constant value between sampled times. We also experimented with other discretization methods such as bilinear transform but did not see much difference in performance.

Each DSS layer receives a length-L sequence u of H-dimensional vectors as input, i.e., $u \in \mathbb{R}^{H \times L}$, and produces an output $y \in \mathbb{R}^{H \times L}$. The parameters of the layer are $\Lambda_{\text{re}}, \Lambda_{\text{im}} \in \mathbb{R}^{N}, \Delta_{\log} \in \mathbb{R}^{H}$ and $C \in \mathbb{C}^{H \times N}$. For each coordinate $h = 1, \ldots, H$, a state space kernel $\overline{K}_h \in \mathbb{R}^{L}$ is computed for $\Lambda_{\text{re}}, \Lambda_{\text{im}}, (\Delta_{\log})_h, C_h$ via Equation 6. The output $y_h \in \mathbb{R}^{L}$ for coordinate h is computed from $u_h \in \mathbb{R}^{L}$ and $\overline{K}_h$ using Equation 5.

For batch size B, sequence length L and hidden size H, the DSS layer requires $O(NHL)$ time to compute the kernels, and $O(BHL \log(L))$ time for the discrete convolution. In S4 and DSS, the authors suggest to use $N = 64$ as default and for this choice of N, the time taken to compute the kernels becomes an important factor, specially for small batches.

3.2 GSS Layer

We build on the idea of the recently introduced Gated Attention Unit (GAU) (Hua et al., 2022) and replace the $\Omega(L^2)$ attention used in GAU by a further simplified DSS layer (§3.1). Gating allows our model to be contextualized over a reduced dimensionality and the use of state spaces provides it with superior contextualizing abilities, while enjoying $O(L \log L)$ complexity out of the box.

Concretely, our *Gated State Space* ("GSS") layer maps a sequence $X \in \mathbb{R}^{L \times E}$ to an output $O \in \mathbb{R}^{L \times E}$ as

$$U = \phi(XW_1) \in \mathbb{R}^{L \times H} \qquad V = \phi(XW_2) \in \mathbb{R}^{L \times F} \tag{7}$$

$$Y = \text{DSS}(U) \in \mathbb{R}^{L \times H} \qquad U_{\text{context}} = YW_3 \in \mathbb{R}^{L \times F} \tag{8}$$

$$O = (U_{\text{context}} * V)W_4 \in \mathbb{R}^{L \times E} \tag{9}$$

where $*$ denotes elementwise multiplication and ϕ denotes GELU (Hendrycks & Gimpel, 2016). Note that, contrary to Hua et al. (2022), in our experiments, we did not observe much benefit from using RELU^2 or Swish activations instead of GELU.

In Equation 8, a contextualized representation of U is formed via DSS in $O(NHL) + O(BHL \log L)$ time. In most of our experiments we used $H = E/4 = 256$, $N = 512$ and $F = 4096$. Similar to GAU, gating allows us to perform a weaker contextualization using the state space layer by reducing the dimension of the input to DSS, by $4\times$ in our case. This offers a much needed increase in throughput since we observed that FFT ops were the main bottleneck (measured on TPUs). As shown in Table 1, this provides more than $3\times$ speedups over the vanilla DSS block described in §3.1.

Simplified DSS used in GSS layer   In Equation 8, instead of directly using DSS as described in §3.1, we made several key simplifications based on our exploratory results.

As described in §3.1, S4 and DSS train a separate Δ for each of the H coordinates resulting in the creation of H separate P matrices in Equation 6. In the DSS layer used in GSS, we decided to eliminate the use of Δ by fixing it as 1. This reduces the compute required for creating the kernels and makes the kernel computation simpler.

Secondly, we found that randomly initializing the parameters corresponding to Λ works just as well as the Skew-Hippo initialization suggested in (Gupta et al., 2022). Importantly, we parametrize both real and imaginary parts of Λ in log space, so that the random initializations span many orders of magnitude (§A.2). The effectiveness of random initialization is in contrast to the findings of Gu et al. (2022a) and Gupta et al. (2022) who reported their respective initializations of the state space parameters to be critical to the model performance. We do however note that the experiments in our setting of large-scale language modeling are conducted on orders of magnitude larger scale of compute than what is used in the tasks considered in these works. Moreover, the data modalities we consider in this work are different from the tasks considered in these works (e.g. Long Range Arena) which are specifically designed to stress test long-range reasoning.

3.3 GSS-Transformer-Hybrid

Conceptually, GSS looks fairly different from the current workhorse of machine learning; the Transformer architecture. Given this, it is not immediately clear if one is decidedly better than the

other or if they each provide some orthogonal benefits. If its the latter, one might wonder if there are synergies between these architectures which can be exploited to create a hybrid model which is stronger than either one of them individually. To that end, we also consider a conceptually simple hybrid between GSS and Transformer where we sparingly interleave traditional Transformer blocks with GSS layers. Despite its glaring simplicity, as shown in Table 2, we observed that it shows consistent and significant improvements on all tasks.

Chunking long inputs   In all our experiments we used sequence lengths large enough to be prohibitive for traditional Transformer layers. To get around this restriction at the Transformer layers used in our hybrid model, we chunk their inputs into non-overlapping chunks of length 512 and run the Transformer layer on each of them independently. While the GSS layers are apt at modeling both short and longer range interactions, the interleaved Transformer layers can potentially allow for a richer modeling of short range interactions.

4   RESULTS

We conduct experiments with GSS on 4 different datasets, LM1B, PG19, ArXiv and Github, each of them varying qualitatively with another in terms of modality and average document length.

LM1B is a standard and reasonably big dataset (1B tokens) where each training example consists of a short sentence (Chelba et al., 2014). This is different from rest of the datasets which consists of a much larger sequence of tokens per example. Although, our primary goal is to measure GSS's ability to capture long range dependencies, we include results on LM1B benchmark and compare with vanilla Transformer baseline, which is hard to do for larger sequence lengths.

PG19 dataset is constructed from extracting a large collection of full-length books from Project Gutenberg (Rae et al., 2020). All extracted books were written before 1919 and only contain tokens from the English language. Over the years PG-19 has become a standard benchmark for measuring progress on long range dependency modeling over text.

ArXiv Math dataset was recently collected by Wu et al. (2022) and contains LaTeX source for articles focusing on Mathematics. Even though articles are typically shorter than full-length books, as in PG19, since LaTeX source can have many special characters, typical sub-piece vocabularies are not very effective and tends to produce examples of similar size, as measured by number of tokens. It is possible to train a custom sub-piece vocabulary for this dataset, but we stick with the vocabulary used by both Wu et al. (2022) and Hutchins et al. (2022) for fair comparison.

Github was also first collected and used by Wu et al. (2022). It is a corpus of raw source code collected from several Github repositories with open-source licences. The dataset contains code from several programming languages, including C, C++, Java, Python, Go and Typescript. In this case individual files can be small but code repositories are typically is organized so that code can be reused across file boundaries. Thus, for every repository, all the files were concatenated to produce a single document.

We do token level modeling on all the datasets and report resulting perplexity numbers on a heldout set of examples. Perplexity numbers are obtained using teacher forcing (or parallel mode) where the correct output from the heldout set is used for decoding the next token at each position. For a fair comparison with the baselines we considered, we keep the vocabularies consistent as used by the baselines models. Specifically, we used custom trained 30k sized sentence-piece vocab for LM1B, T5 vocab with 32k tokens for PG19 (Raffel et al., 2020) and Meena vocab with 32k tokens (Adiwardana et al., 2020) for both ArXiv and Github datasets.

4.1   COMPARING DSS AND GSS

As shown in Table 1, in our first set of results, we compare DSS and GSS models both in terms of perplexity and throughput, as measure by steps per second on all 4 datasets. For the PG-19, Arxiv and Github datasets, all models were trained with 4k sequence length at training time. However, at evaluation time, we present results for on a large range of sequence lengths. Despite being a (slightly) smaller model, GSS improves perplexity while being 2-3× faster depending on these datasets. In contrast, for LM1B, we train and evaluate with sequence length of 512, since the dataset only contains short sentences, most examples comfortably fully fitting in the context window.

Dataset	Model	Params	Throughput (steps/sec)	Eval Sequence Length			
				Perplexity			
				512	4k	16k	65k
LM1B	Transformer	182M	6.6	13.51			
	DSS	188M	1.8	13.59			
	GSS	190M	5.6	13.26			
PG-19	DSS	209M	1.8	14.51	13.53	692.1	OOM
	GSS	192M	5.3	14.01	12.84	12.94	12.47
Arxiv	DSS	209M	1.8	3.65	3.13	284.6	OOM
	GSS	192M	5.3	3.57	3.08	3.08	2.75
Github	DSS	209M	1.8	3.65	3.21	242.7	OOM
	GSS	192M	5.3	2.68	2.35	2.31	2.12

Table 1: Comparison of DSS and GSS models in fixed-param setting. We consistently find that GSS outperforms DSS (with hyperparameters taken from Gupta et al. (2022)) while being 2-3× faster on all tasks. Training sequence length is 4k, except for LM1B for which it is 512.

Furthermore, we observe significant generalization over changes in sequence length on all the datasets. Not only does the performance not degrade when increasing sequence length, it actually improves quite a bit! This suggests that the model is effective at utilizing the extra context even though the model was not trained with that amount of context. Note that we used default hyperparameters suggested by Gupta et al. (2022) for initializing state space variables for DSS. But, for GSS, since we made several structural changes, we retuned the hyperparameters related to initialization on PG19 alone and used them for all the datasets. Since we had access to evaluation metrics for all sequence lengths, length generalization factored in for our choice of hyperparameters, which is not true for DSS. It may be possible to see similar length generalization even with vanilla DSS if initialization hyperparameters were retuned.

Similar to language modeling experiments in (Gu et al., 2022a), every block of DSS baseline consists of DSS layer followed by GLU (Dauphin et al., 2017) and a Feedforward layer similar to the one used in Transformer block with GELU activation (Hendrycks & Gimpel, 2016). DSS baseline consists 12 layers and an embedding dimension of 1024. For GSS, we increased the number of layers to 16 to match the parameter count.

4.2 COMPARISON WITH OTHER BASELINES

In this section, we turn our attention towards apples-to-apples comparison of GSS versus well-tuned baselines on these datasets. For a complete picture of the cost of training these models, we report both the number of parameters and time spent training as measured by TPUv4 hours. For baselines, we selected the best performing models reported in (Hutchins et al., 2022) for every dataset and compare with GSS model both in fixed-param and fixed-compute settings.

GSS models GSS consists of 16 layers and an embedding dimension of 1024. We also consider a larger variant with 32 layers as denoted by GSS-L. For GSS-Hybrid model, we used vanilla Transformer blocks at every 4th layer starting with the 2nd layer. Since GSS layers are inherently position aware, using them for the 1st layer eschews any need of explicit position embeddings typically used with otherwise position invariant Transformer blocks. Thus, barring position aware nature of GSS layers, we don't use any kind of explicit position embedding or bias in our models. For the Transformer blocks used in hybrid models, we use multi-head self-attention with 8 heads, each with size 128.

Baselines We considered 3 high-performing baselines and numbers reported in (Hutchins et al., 2022). Block Recurrent Transformer leverages recurrence over blocks of Transformer layer to model long range dependencies. Hutchins et al. (2022) performed a comprehensive exploration of open design space of incorporating recurrence across blocks. Somewhat surprisingly, Rec:fixed:skip, which accumulates recurrent state vector as an exponential moving average over time performs

Dataset	Model	Params	TPUv4 hours	Eval Sequence Length			
				Perplexity			
				512	4k	16k	65k
PG-19	Rec:fixed:skip	196M	0.8k		11.55		
	Feedback:lstm:single	196M+	0.8k+		11.31		
	Feedback:fixed:skip	196M+	0.8k+		11.24		
	GSS (**this work**)	192M	0.5k	14.01	12.84	12.94	12.47
	GSS-L	352M	0.8k	12.48	11.33	11.16	11.12
	GSS-Hybrid-L	373M	0.8k	11.45	**10.52**	10.44	10.1
Arxiv	Rec:fixed:skip	196M	0.8k		2.36		
	Feedback:lstm:single	196M+	0.8k+		**2.33**		
	Feedback:fixed:skip	196M+	0.8k+		2.36		
	GSS	192M	0.5k	3.57	3.08	3.08	2.75
	GSS-L	352M	0.8k	3.29	2.71	2.72	2.51
	GSS-Hybrid-L	373M	0.8k	2.94	2.51	18.27	125.2
Github	Rec:fixed:skip	196M	3k		2.04		
	Feedback:lstm:single	196M+	3k+		2.07		
	Feedback:fixed:skip	196M+	3k+		2.16		
	GSS	192M	0.5k	2.68	2.35	2.31	2.12
	GSS-L	352M	1.8k	2.31	1.99	2.20	2.28
	GSS-Hybrid-L	373M	1.8k	2.34	**1.88**	1.74	2.09

Table 2: Comparing GSS variants with best-performing models from Hutchins et al. (2022) in both fixed-param and fixed-compute settings. While, in the fixed-param setting, GSS currently lags behind performance of best Block Recurrent Transformer baseline, it is fairly competitive in the fixed-compute setting (as measured by total TPUv4 hours taken to complete training). For the larger model GSS-L used for fixed compute comparison, we simply double the layers from 16 to 32 keeping everything else fixed. In addition, due to the inherent recurrent view of state space model family, decoding at inference time is much faster than Transformer based baselines. For block-recurrent baselines, adding feedback increases both parameter count and training time, we stick with conservative estimates derived from Hutchins et al. (2022) for both, which we denote by '+'. Hutchins et al. (2022) report $\log_2$ of perplexity which we convert to raw perplexity in this table. Param count for all the models include embedding layers as well.

better than more complicated gating designs. Another variation which performed well with Block Recurrence is the idea of adding a feedback mechanism over blocks similar to Feedback Transformer (Fan et al., 2020). Note that feedback mechanism makes training more expensive due to additional cross-attention modules and corresponding paramaters.

Fixed-param comparison As shown in Table 2, we see that GSS variants come very close but not quite beat the strongest block recurrent baseline in the fixed-param setting. In this case, we are comparing GSS model which has roughly 192M parameters (including embeddings) with the baselines all of which have around 196M parameters. Even though the parameter count is fixed, we see that GSS runs faster than block recurrent baselines, likely due to the fact that all the layers can be completely parallelized unlike the the recurrence in the baselines which run in a sequential fashion.

Fixed-compute comparison Since the GSS model runs faster than the baselines, we also train with versions larger than GSS such that the training time (as measured by total TPUv4 hours) matches the time taken by the baselines. We simply double the number of layers from 16 to 32 to construct GSS-L. As expected, adding more parameters improves perplexity numbers on the eval set of all the datasets. Moreover, we find that the GSS-Hybrid versions of the model outperform the best baseline model on PG-19 and Github datasets. We do see significant improvements for Arxiv dataset as well but unfortunately not enough to be stronger than the baseline. We think this may be resolved by the use of a vocabulary more suited to Arxiv symbols. On the flip side, we can no longer do a fair comparison with token level perplexity if we change the vocabulary, so we stick with the vocabularies used by the baselines for this study.

Model	Params	Layers	WLP	Vocabulary
Transformer-XL (Rae et al., 2020)		36	36.3	32k
Compressive Transformer (Rae et al., 2020)		36	33.6	32k
Routing Transformer (Roy et al., 2021)	490M	22	33.2	98k
Perceiver AR (Hawthorne et al., 2022)	974.6M	60	28.9	32k
Block Recurrent Trans (Hutchins et al., 2022)	1.3B	24	26.5	32k
GSS-Hybrid (ours)	341M	32	32.9	32k
	681M	64	30.2	32k
	1B	96	28.0	32k
	1.4B	128	27.3	32k

Table 3: Comparison of GSS with other competitive models on PG-19 across multiple scales as measured by word-level perplexity (WLP) on test set of PG-19. We evaluated WLP on 16k sequence length for GSS-Hybrid set of models. Model size numbers for Perceiver AR (Hawthorne et al., 2022) and Routing Transformer (Roy et al., 2021) are taken from Hutchins et al. (2022).

Length generalization We train all variants of GSS with sequence length of 4k but evaluate on 4 different lengths $l \in [512, 4k, 16k, 65k]$. On PG-19, we see significant length generalization across the board. Not only the performance doesn't degrade as the sequence length is increased but it gets significantly better for all model variants. On Arxiv and Github, the situation is a little more complicated. For smaller models, we still see length generalization but it tends to degrade when either the model is made bigger or the dataset has a lot of noise (as indicated by variation in perplexity metric over time). How to robustly achieve length generalization is an interesting research question on it is own and we believe one can design interventions which can lead to further improvements, which we don't explore here.

Note that block recurrent baselines, with or without feedback mechanism, process documents in a sequential fashion such that recurrent state from previous segment from the document is passed to the next segment, with backward pass truncated to the current segment. This means that, even though the segment sequence length is set to 4k, block recurrent models have (arguably weak) access to almost the entire past. Thus, perplexity comparison at sequence length 4k is slightly unfair towards GSS models since they do *not* employ such state caching mechanisms.

4.3 SCALING UP

In this section, we further scale up the GSS model focusing only on PG19 dataset. As shown in Table 3, even though GSS does not beat current state of the art on a fixed-param basis, it is quite relieving that we consistently observe significant gains from simply scaling up, similar to popular Transformer based language models like GPT-3 (Brown et al., 2020) and PaLM (Chowdhery et al., 2022). Furthermore, GSS also outperforms Routing Transformer (Roy et al., 2021) and Perceiver AR (Hawthorne et al., 2022) when comparing similar sized models.

5 CONCLUSION

We introduce GSS, a general purpose sequence model which leverages gated units and trains significantly faster as shown on several language modeling benchmarks. Further comparison with well tuned Transformer baselines suggests that GSS is fairly competitive in fixed-compute setting. We further show that a hybrid model constructed by interleaving GSS and Transformer improves performance even further. Finally, we also show that, similar to popular Transformer based LLMs, performance of GSS keeps improving with scale on PG-19. We however recognize that perplexity numbers alone are not satisfying for gauging overall model performance. As part of future work, we will explore scaling GSS even further and conducting few-shot evaluation on standardized benchmarks, comparing it against other popular large language models.

BIBLIOGRAPHY

Daniel Adiwardana, Minh-Thang Luong, David R. So, Jamie Hall, Noah Fiedel, Romal Thoppilan, Zi Yang, Apoorv Kulshreshtha, Gaurav Nemade, Yifeng Lu, and Quoc V. Le. Towards a human-like open-domain chatbot. *ArXiv*, abs/2001.09977, 2020.

Joshua Ainslie, Santiago Ontanon, Chris Alberti, Philip Pham, Anirudh Ravula, and Sumit Sanghai. Etc: Encoding long and structured data in transformers. *ArXiv preprint*, abs/2004.08483, 2020. URL https://arxiv.org/abs/2004.08483.

Žiga Avsec, Vikram Agarwal, Daniel Visentin, Joseph R Ledsam, Agnieszka Grabska-Barwinska, Kyle R Taylor, Yannis Assael, John Jumper, Pushmeet Kohli, and David R Kelley. Effective gene expression prediction from sequence by integrating long-range interactions. *Nature methods*, 18 (10):1196–1203, 2021.

Iz Beltagy, Matthew E Peters, and Arman Cohan. Longformer: The long-document transformer. *ArXiv preprint*, abs/2004.05150, 2020. URL https://arxiv.org/abs/2004.05150.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhari-wal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agar-wal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCan-dlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/1457c0d6bfcb4967418bfb8ac142f64a-Abstract.html.

Ciprian Chelba, Tomas Mikolov, Mike Schuster, Qi Ge, T. Brants, Phillip Todd Koehn, and Tony Robinson. One billion word benchmark for measuring progress in statistical language modeling. In *INTERSPEECH*, 2014.

Krzysztof Marcin Choromanski, Valerii Likhosherstov, David Dohan, Xingyou Song, Andreea Gane, Tamás Sarlós, Peter Hawkins, Jared Quincy Davis, Afroz Mohiuddin, Lukasz Kaiser, David Ben-jamin Belanger, Lucy J. Colwell, and Adrian Weller. Rethinking attention with performers. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021. URL https://openreview.net/forum?id=Ua6zuk0WRH.

Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, Parker Schuh, Kensen Shi, Sasha Tsvyashchenko, Joshua Maynez, Abhishek B Rao, Parker Barnes, Yi Tay, Noam M. Shazeer, Vinodkumar Prabhakaran, Emily Reif, Nan Du, Benton C. Hutchinson, Reiner Pope, James Bradbury, Jacob Austin, Michael Isard, Guy Gur-Ari, Pengcheng Yin, Toju Duke, Anselm Levskaya, Sanjay Ghemawat, Sunipa Dev, Henryk Michalewski, Xavier García, Vedant Misra, Kevin Robinson, Liam Fedus, Denny Zhou, Daphne Ippolito, David Luan, Hyeontaek Lim, Barret Zoph, Alexander Spiridonov, Ryan Sepassi, David Dohan, Shivani Agrawal, Mark Omernick, Andrew M. Dai, Thanumalayan Sankaranarayana Pillai, Marie Pellat, Aitor Lewkowycz, Erica Oliveira Moreira, Rewon Child, Oleksandr Polozov, Katherine Lee, Zongwei Zhou, Xuezhi Wang, Brennan Saeta, Mark Diaz, Orhan Firat, Michele Catasta, Jason Wei, Kathleen S. Meier-Hellstern, Douglas Eck, Jeff Dean, Slav Petrov, and Noah Fiedel. Palm: Scaling language modeling with pathways. *ArXiv preprint*, abs/2204.02311, 2022. URL https://arxiv.org/abs/2204.02311.

James W. Cooley and John W. Tukey. An algorithm for the machine calculation of complex fourier series. *Mathematics of Computation*, 19:297–301, 1965.

Thomas H. Cormen, Charles E. Leiserson, Ronald L. Rivest, and Clifford Stein. *Introduction to Algorithms*. The MIT Press, 3rd edition, 2009.

Zihang Dai, Zhilin Yang, Yiming Yang, Jaime Carbonell, Quoc Le, and Ruslan Salakhutdinov. Transformer-XL: Attentive language models beyond a fixed-length context. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 2978–2988, Florence, Italy, 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1285. URL https://aclanthology.org/P19-1285.

Zihang Dai, Guokun Lai, Yiming Yang, and Quoc Le. Funnel-transformer: Filtering out sequential redundancy for efficient language processing. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/2cd2915e69546904e4e5d4a2ac9e1652-Abstract.html.

Yann N. Dauphin, Angela Fan, Michael Auli, and David Grangier. Language modeling with gated convolutional networks. In *Proceedings of the 34th International Conference on Machine Learning - Volume 70*, ICML'17, pp. 933–941. JMLR.org, 2017.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, Minneapolis, Minnesota, 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423. URL https://aclanthology.org/N19-1423.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021. URL https://openreview.net/forum?id=YicbFdNTTy.

Angela Fan, Thibaut Lavril, Edouard Grave, Armand Joulin, and Sainbayar Sukhbaatar. Addressing some limitations of transformers with feedback memory. *ArXiv preprint*, abs/2002.09402, 2020. URL https://arxiv.org/abs/2002.09402.

Albert Gu, Tri Dao, Stefano Ermon, Atri Rudra, and Christopher Ré. Hippo: Recurrent memory with optimal polynomial projections. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/102f0bb6efb3a6128a3c750dd16729be-Abstract.html.

Albert Gu, Karan Goel, and Christopher Ré. Efficiently modeling long sequences with structured state spaces. In *International Conference on Learning Representations*, 2022a. URL https://openreview.net/forum?id=uYLFoz1vlAC.

Albert Gu, Ankit Gupta, Karan Goel, and Christopher Ré. On the parameterization and initialization of diagonal state space models. In *Annual Conference on Neural Information Processing Systems (NeurIPS)*, 2022b.

Ankit Gupta and Jonathan Berant. Gmat: Global memory augmentation for transformers. *ArXiv preprint*, abs/2006.03274, 2020. URL https://arxiv.org/abs/2006.03274.

Ankit Gupta, Albert Gu, and Jonathan Berant. Diagonal state spaces are as effective as structured state spaces. In *Annual Conference on Neural Information Processing Systems (NeurIPS)*, 2022.

Curtis Hawthorne, Andrew Jaegle, Cătălina Cangea, Sebastian Borgeaud, Charlie Nash, Mateusz Malinowski, Sander Dieleman, Oriol Vinyals, Matthew Botvinick, Ian Simon, Hannah Sheahan, Neil Zeghidour, Jean-Baptiste Alayrac, Joao Carreira, and Jesse Engel. General-purpose, long-context autoregressive modeling with perceiver AR. In Kamalika Chaudhuri,

Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 8535–8558. PMLR, 17–23 Jul 2022. URL https://proceedings.mlr.press/v162/hawthorne22a.html.

Dan Hendrycks and Kevin Gimpel. Bridging nonlinearities and stochastic regularizers with gaussian error linear units. *ArXiv preprint*, abs/1606.08415, 2016. URL https://arxiv.org/abs/1606.08415.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, Tom Hennigan, Eric Noland, Katie Millican, George van den Driessche, Bogdan Damoc, Aurelia Guy, Simon Osindero, Karen Simonyan, Erich Elsen, Jack W. Rae, Oriol Vinyals, and L. Sifre. Training compute-optimal large language models. *ArXiv preprint*, abs/2203.15556, 2022. URL https://arxiv.org/abs/2203.15556.

Weizhe Hua, Zihang Dai, Hanxiao Liu, and Quoc V. Le. Transformer quality in linear time. In *Proceedings of the 39th International Conference on Machine Learning (ICML)*, 2022. URL https://arxiv.org/abs/2202.10447.

DeLesley Hutchins, Imanol Schlag, Yuhuai Wu, Ethan Dyer, and Behnam Neyshabur. Block-recurrent transformers. *ArXiv preprint*, abs/2203.07852, 2022. URL https://arxiv.org/abs/2203.07852.

John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, et al. Highly accurate protein structure prediction with alphafold. *Nature*, 596(7873):583–589, 2021.

Angelos Katharopoulos, Apoorv Vyas, Nikolaos Pappas, and François Fleuret. Transformers are rnns: Fast autoregressive transformers with linear attention. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pp. 5156–5165. PMLR, 2020. URL http://proceedings.mlr.press/v119/katharopoulos20a.html.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In Yoshua Bengio and Yann LeCun (eds.), *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015. URL http://arxiv.org/abs/1412.6980.

Nikita Kitaev, Lukasz Kaiser, and Anselm Levskaya. Reformer: The efficient transformer. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=rkgNKkHtvB.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *ArXiv preprint*, abs/1907.11692, 2019. URL https://arxiv.org/abs/1907.11692.

Hao Peng, Nikolaos Pappas, Dani Yogatama, Roy Schwartz, Noah A. Smith, and Lingpeng Kong. Random feature attention. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021. URL https://openreview.net/forum?id=QtTKTdVrFBB.

Zhen Qin, Weixuan Sun, Hui Deng, Dongxu Li, Yunshen Wei, Baohong Lv, Junjie Yan, Lingpeng Kong, and Yiran Zhong. cosformer: Rethinking softmax in attention. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=Bl8CQrx2Up4.

Jiezhong Qiu, Hao Ma, Omer Levy, Wen-tau Yih, Sinong Wang, and Jie Tang. Blockwise self-attention for long document understanding. In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pp. 2555–2565, Online, 2020. Association for Computational Linguistics. URL https://aclanthology.org/2020.findings-emnlp.232.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

Jack W. Rae, Anna Potapenko, Siddhant M. Jayakumar, Chloe Hillier, and Timothy P. Lillicrap. Compressive transformers for long-range sequence modelling. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=SylKikSYDH.

Jack W. Rae, Sebastian Borgeaud, Trevor Cai, Katie Millican, Jordan Hoffmann, Francis Song, John Aslanides, Sarah Henderson, Roman Ring, Susannah Young, Eliza Rutherford, Tom Hennigan, Jacob Menick, Albin Cassirer, Richard Powell, George van den Driessche, Lisa Anne Hendricks, Maribeth Rauh, Po-Sen Huang, Amelia Glaese, Johannes Welbl, Sumanth Dathathri, Saffron Huang, Jonathan Uesato, John F. J. Mellor, Irina Higgins, Antonia Creswell, Nathan McAleese, Amy Wu, Erich Elsen, Siddhant M. Jayakumar, Elena Buchatskaya, David Budden, Esme Sutherland, Karen Simonyan, Michela Paganini, L. Sifre, Lena Martens, Xiang Lorraine Li, Adhiguna Kuncoro, Aida Nematzadeh, Elena Gribovskaya, Domenic Donato, Angeliki Lazaridou, Arthur Mensch, Jean-Baptiste Lespiau, Maria Tsimpoukelli, N. K. Grigorev, Doug Fritz, Thibault Sottiaux, Mantas Pajarskas, Tobias Pohlen, Zhitao Gong, Daniel Toyama, Cyprien de Masson d'Autume, Yu-jia Li, Tayfun Terzi, Vladimir Mikulik, Igor Babuschkin, Aidan Clark, Diego de Las Casas, Aurelia Guy, Chris Jones, James Bradbury, Matthew G. Johnson, Blake A. Hechtman, Laura Weidinger, Iason Gabriel, William S. Isaac, Edward Lockhart, Simon Osindero, Laura Rimell, Chris Dyer, Oriol Vinyals, Kareem W. Ayoub, Jeff Stanway, L. L. Bennett, Demis Hassabis, Koray Kavukcuoglu, and Geoffrey Irving. Scaling language models: Methods, analysis & insights from training gopher. *ArXiv preprint*, abs/2112.11446, 2021. URL https://arxiv.org/abs/2112.11446.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *J. Mach. Learn. Res.*, 21:140:1–140:67, 2020. URL http://jmlr.org/papers/v21/20-074.html.

Hubert Ramsauer, Bernhard Schäfl, Johannes Lehner, Philipp Seidl, Michael Widrich, Lukas Gruber, Markus Holzleitner, Thomas Adler, David P. Kreil, Michael K. Kopp, Günter Klambauer, Johannes Brandstetter, and Sepp Hochreiter. Hopfield networks is all you need. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021. URL https://openreview.net/forum?id=tL89RnzIiCd.

Aurko Roy, Mohammad Saffar, Ashish Vaswani, and David Grangier. Efficient content-based sparse attention with routing transformers. *Transactions of the Association for Computational Linguistics*, 9:53–68, Feb 2021. ISSN 2307-387X. doi: 10.1162/tacl_a_00353. URL http://dx.doi.org/10.1162/tacl_a_00353.

Noam M. Shazeer. Glu variants improve transformer. *ArXiv preprint*, abs/2002.05202, 2020. URL https://arxiv.org/abs/2002.05202.

Aarohi Srivastava, Abhinav Rastogi, Abhishek B Rao, Abu Awal Md Shoeb, Abubakar Abid, Adam Fisch, Adam R. Brown, Adam Santoro, Aditya Gupta, Adrià Garriga-Alonso, Agnieszka Kluska, Aitor Lewkowycz, Akshat Agarwal, Alethea Power, Alex Ray, Alex Warstadt, Alexander W. Kocurek, Ali Safaya, Ali Tazarv, Alice Xiang, Alicia Parrish, Allen Nie, Aman Hussain, Amanda Askell, Amanda Dsouza, Ameet Annasaheb Rahane, Anantharaman S. Iyer, Anders Johan Andreassen, Andrea Santilli, Andreas Stuhlmuller, Andrew M. Dai, Andrew D. La, Andrew Kyle Lampinen, Andy Zou, Angela Jiang, Angelica Chen, Anh Vuong, Animesh Gupta, Anna Gottardi, Antonio Norelli, Anu Venkatesh, Arash Gholamidavoodi, Arfa Tabassum, Arul Menezes, Arun Kirubarajan, Asher Mullokandov, Ashish Sabharwal, Austin Herrick, Avia Efrat, Aykut Erdem, Ayla Karakacs, Bridget R. Roberts, Bao Sheng Loe, Barret Zoph, Bartlomiej Bojanowski, Batuhan Ozyurt, Behnam Hedayatnia, Behnam Neyshabur, Benjamin Inden, Benno Stein, Berk Ekmekci, Bill Yuchen Lin, Blake Stephen Howald, Cameron Diao, Cameron Dour, Catherine Stinson,

Cedrick Argueta, C'esar Ferri Ram'irez, Chandan Singh, Charles Rathkopf, Chenlin Meng, Chitta Baral, Chiyu Wu, Chris Callison-Burch, Chris Waites, Christian Voigt, Christopher D. Manning, Christopher Potts, Cindy Tatiana Ramirez, Clara Rivera, Clemencia Siro, Colin Raffel, Courtney Ashcraft, Cristina Garbacea, Damien Sileo, Daniel H Garrette, Dan Hendrycks, Dan Kilman, Dan Roth, Daniel Freeman, Daniel Khashabi, Daniel Levy, Daniel Gonz'alez, Danny Hernandez, Danqi Chen, Daphne Ippolito, Dar Gilboa, David Dohan, D. Drakard, David Jurgens, Debajyoti Datta, Deep Ganguli, Denis Emelin, Denis Kleyko, Deniz Yuret, Derek Chen, Derek Tam, Dieuwke Hupkes, Diganta Misra, Dilyar Buzan, Dimitri Coelho Mollo, Diyi Yang, Dong-Ho Lee, Ekaterina Shutova, Ekin Dogus Cubuk, Elad Segal, Eleanor Hagerman, Elizabeth Barnes, Elizabeth P. Donoway, Ellie Pavlick, Emanuele Rodolà, Emma FC Lam, Eric Chu, Eric Tang, Erkut Erdem, Ernie Chang, Ethan A. Chi, Ethan Dyer, Ethan Jerzak, Ethan Kim, Eunice Engefu Manyasi, Evgenii Zheltonozhskii, Fan Xia, Fatemeh Siar, Fernando Mart'inez-Plumed, Francesca Happ'e, François Chollet, Frieda Rong, Gaurav Mishra, Genta Indra Winata, Gerard de Melo, Germán Kruszewski, Giambattista Parascandolo, Giorgio Mariani, Gloria Wang, Gonzalo Jaimovitch-L'opez, Gregor Betz, Guy Gur-Ari, Hana Galijasevic, Han Sol Kim, Hannah Rashkin, Hanna Hajishirzi, Harsh Mehta, Hayden Bogar, Henry Shevlin, Hinrich Schütze, Hiromu Yakura, Hongming Zhang, Hubert Wong, Ian Aik-Soon Ng, Isaac Noble, Jaap Jumelet, Jack Geissinger, John Kernion, Jacob Hilton, Jaehoon Lee, Jaime Fernández Fisac, J. Brooker Simon, James Koppel, James Zheng, James Zou, Jan Koco'n, Jana Thompson, Jared Kaplan, Jarema Radom, Jascha Sohl-Dickstein, Jason Phang, Jason Wei, Jason Yosinski, Jekaterina Novikova, Jelle Bosscher, Jenni Marsh, Jeremy Kim, Jeroen Taal, Jesse Engel, Jesujoba Oluwadara Alabi, Jiacheng Xu, Jiaming Song, Jillian Tang, Jane W Waweru, John Burden, John Miller, John U. Balis, Jonathan Berant, Jorg Frohberg, Jos Rozen, José Hernández-Orallo, Joseph Boudeman, Joseph Jones, Joshua B. Tenenbaum, Joshua S. Rule, Joyce Chua, Kamil Kanclerz, Karen Livescu, Karl Krauth, Karthik Gopalakrishnan, Katerina Ignatyeva, Katja Markert, Kaustubh D. Dhole, Kevin Gimpel, Kevin Ochieng' Omondi, Kory Wallace Mathewson, Kristen Chiafullo, Ksenia Shkaruta, Kumar Shridhar, Kyle McDonell, Kyle Richardson, Laria Reynolds, Leo Gao, Li Zhang, Liam Dugan, Lianhui Qin, Lidia Contreras-Ochando, Louis-Philippe Morency, Luca Moschella, Luca Lam, Lucy Noble, Ludwig Schmidt, Luheng He, Luis Oliveros Col'on, Luke Metz, Lutfi Kerem cSenel, Maarten Bosma, Maarten Sap, Maartje ter Hoeve, Madotto Andrea, Maheen Saleem Farooqi, Manaal Faruqui, Mantas Mazeika, Marco Baturan, Marco Marelli, Marco Maru, M Quintana, Marie Tolkiehn, Mario Giulianelli, Martha Lewis, Martin Potthast, Matthew Leavitt, Matthias Hagen, M'aty'as Schubert, Medina Baitemirova, Melissa Arnaud, Melvin Andrew McElrath, Michael A. Yee, Michael Cohen, Mi Gu, Michael I. Ivanitskiy, Michael Starritt, Michael Strube, Michal Swedrowski, Michele Bevilacqua, Michihiro Yasunaga, Mihir Kale, Mike Cain, Mimee Xu, Mirac Suzgun, Monica Tiwari, Mohit Bansal, Moin Aminnaseri, Mor Geva, Mozhdeh Gheini, T MukundVarma, Nanyun Peng, Nathan Chi, Nayeon Lee, Neta Gur-Ari Krakover, Nicholas Cameron, Nicholas S. Roberts, Nicholas Doiron, Nikita Nangia, Niklas Deckers, Niklas Muennighoff, Nitish Shirish Keskar, Niveditha Iyer, Noah Constant, Noah Fiedel, Nuan Wen, Oliver Zhang, Omar Agha, Omar Elbaghdadi, Omer Levy, Owain Evans, Pablo Casares, Parth Doshi, Pascale Fung, Paul Pu Liang, Paul Vicol, Pegah Alipoormolabashi, Peiyuan Liao, Percy Liang, Peter W. Chang, Peter Eckersley, Phu Mon Htut, Pi-Bei Hwang, P. Milkowski, Piyush S. Patil, Pouya Pezeshkpour, Priti Oli, Qiaozhu Mei, QING LYU, Qinlang Chen, Rabin Banjade, Rachel Etta Rudolph, Raefer Gabriel, Rahel Habacker, Ram'on Risco Delgado, Raphaël Millière, Rhythm Garg, Richard Barnes, Rif A. Saurous, Riku Arakawa, Robbe Raymaekers, Robert Frank, Rohan Sikand, Roman Novak, Roman Sitelew, Ronan Lebras, Rosanne Liu, Rowan Jacobs, Rui Zhang, Ruslan Salakhutdinov, Ryan Chi, Ryan Lee, Ryan Stovall, Ryan Teehan, Rylan Yang, Sahib J. Singh, Saif M. Mohammad, Sajant Anand, Sam Dillavou, Sam Shleifer, Sam Wiseman, Samuel Gruetter, Sam Bowman, Samuel S. Schoenholz, Sanghyun Han, Sanjeev Kwatra, Sarah A. Rous, Sarik Ghazarian, Sayan Ghosh, Sean Casey, Sebastian Bischoff, Sebastian Gehrmann, Sebastian Schuster, Sepideh Sadeghi, Shadi Sameh Hamdan, Sharon Zhou, Shashank Srivastava, Sherry Shi, Shikhar Singh, Shima Asaadi, Shixiang Shane Gu, Shubh Pachchigar, Shubham Toshniwal, Shyam Upadhyay, Shyamolima Debnath, Siamak Shakeri, Simon Thormeyer, Simone Melzi, Siva Reddy, Sneha Priscilla Makini, Soo hwan Lee, Spencer Bradley Torene, Sriharsha Hatwar, Stanislas Dehaene, Stefan Divic, Stefano Ermon, Stella Rose Biderman, Stephanie C. Lin, Stephen Prasad, Steven T. Piantadosi, Stuart M. Shieber, Summer Misherghi, Svetlana Kiritchenko, Swaroop Mishra, Tal Linzen, Tal Schuster, Tao Li, Tao Yu, Tariq A. Ali, Tatsuo Hashimoto, Te-Lin Wu, Theo Desbordes, Theodore Rothschild, Thomas Phan, Tianle Wang, Tiberius Nkinyili, Timo Schick, T. N. Kornev, Timothy Telleen-Lawton, Titus Tunduny, Tobias Gerstenberg, Trenton Chang, Trishala Neeraj, Tushar Khot, Tyler O. Shultz,

Uri Shaham, Vedant Misra, Vera Demberg, Victoria Nyamai, Vikas Raunak, Vinay V. Ramasesh, Vinay Uday Prabhu, Vishakh Padmakumar, Vivek Srikumar, William Fedus, William Saunders, William Zhang, W Vossen, Xiang Ren, Xiaoyu F Tong, Xinyi Wu, Xudong Shen, Yadollah Yaghoobzadeh, Yair Lakretz, Yang Song, Yasaman Bahri, Ye Ji Choi, Yichi Yang, Yiding Hao, Yifu Chen, Yonatan Belinkov, Yu Hou, Yu Hou, Yushi Bai, Zachary Seid, Zhao Xinran, Zhuoye Zhao, Zi Fu Wang, Zijie J. Wang, Zirui Wang, Ziyi Wu, Sahib Singh, and Uri Shaham. Beyond the imitation game: Quantifying and extrapolating the capabilities of language models. *ArXiv*, abs/2206.04615, 2022.

Yi Tay, Mostafa Dehghani, Dara Bahri, and Donald Metzler. Efficient transformers: A survey. *ArXiv preprint*, abs/2009.06732, 2020. URL https://arxiv.org/abs/2009.06732.

Yi Tay, Mostafa Dehghani, Samira Abnar, Yikang Shen, Dara Bahri, Philip Pham, Jinfeng Rao, Liu Yang, Sebastian Ruder, and Donald Metzler. Long range arena : A benchmark for efficient transformers. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021. URL https://openreview.net/forum?id=qVyeW-grC2k.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pp. 5998–6008, 2017. URL https://proceedings.neurips.cc/paper/2017/hash/3f5ee243547dee91fbd053c1c4a845aa-Abstract.html.

Aaron Voelker, Ivana Kajic, and Chris Eliasmith. Legendre memory units: Continuous-time representation in recurrent neural networks. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pp. 15544–15553, 2019. URL https://proceedings.neurips.cc/paper/2019/hash/952285b9b7e7a1be5aa7849f32ffff05-Abstract.html.

Apoorv Vyas, Angelos Katharopoulos, and François Fleuret. Fast transformers with clustered attention. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/f6a8dd1c954c8506aadc764cc32b895e-Abstract.html.

Sinong Wang, Belinda Li, Madian Khabsa, Han Fang, and Hao Ma. Linformer: Self-attention with linear complexity. *ArXiv preprint*, abs/2006.04768, 2020. URL https://arxiv.org/abs/2006.04768.

Yuhuai Wu, Markus Norman Rabe, DeLesley Hutchins, and Christian Szegedy. Memorizing transformers. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=TrjbxzRcnf-.

Manzil Zaheer, Guru Guruganesh, Kumar Avinava Dubey, Joshua Ainslie, Chris Alberti, Santiago Ontañón, Philip Pham, Anirudh Ravula, Qifan Wang, Li Yang, and Amr Ahmed. Big bird: Transformers for longer sequences. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/c8512d142a2d849725f31a9a7a361ab9-Abstract.html.

Susan Zhang, Stephen Roller, Naman Goyal, Mikel Artetxe, Moya Chen, Shuohui Chen, Christopher Dewan, Mona Diab, Xian Li, Xi Victoria Lin, Todor Mihaylov, Myle Ott, Sam Shleifer, Kurt Shuster, Daniel Simig, Punit Singh Koura, Anjali Sridhar, Tianlu Wang, and Luke Zettlemoyer. Opt: Open pre-trained transformer language models. *ArXiv preprint*, abs/2205.01068, 2022. URL https://arxiv.org/abs/2205.01068.

A   SUPPLEMENTAL MATERIAL

A.1   FAST CONVOLUTION VIA FFT

For $u, v \in \mathbb{C}^{1 \times L}$ the Circular Convolution Theorem states that,

$$\mathrm{invFFT}_L(\mathrm{FFT}_L(u) * \mathrm{FFT}_L(v)) = v \cdot \begin{bmatrix} u_0 & u_1 & \cdots & u_{L-1} \\ u_{L-1} & u_0 & \ddots & \vdots \\ \vdots & \ddots & \ddots & u_1 \\ u_1 & \cdots & u_{L-1} & u_0 \end{bmatrix} = v \cdot \mathrm{circulant}(u) \ .$$

where $*$ denotes elementwise multiplication. As $\mathrm{FFT}, \mathrm{invFFT}$ can be done in $O(L \log L)$ time this provides a fast algorithm for circulant matrix-vector product. In practice, linear systems can often be expressed as a circulant matrix-vector product and is also true in the case of Equation 4 which can be equivalently expressed as

$$[y_0 \ \ldots \ y_{L-1} \mid 0 \ \ldots \ 0]_{1 \times 2L} = [\overline{K} \mid 0 \ \ldots \ 0]_{1 \times 2L} \cdot \mathrm{circulant}([u_0 \ \ldots \ u_{L-1} \mid 0 \ \ldots \ 0])_{2L \times 2L} \ .$$

A.2   IMPLEMENTATION OF GSS

```python
def simplified_dss_kernel(H, L, N=512):
    # Lambda_re, Lambda_im: [N]
    # C_re, C_im: [H N]
    Lambda = -Lambda_re.exp() + 1j*Lambda_im.exp()   # [N]
    C = C_re + 1j*C_im                               # [H N]
    S = (Lambda * arange(L).view(1,L)).exp()         # [N L]
    C = C * (Lambda.exp() - 1) / Lambda              # [H N]
    return einsum('hn,nl->hl', C, S).real            # [H L]

def dss(u, H, L):
    u = norm(u)
    # compute H state space kernels
    K = simplified_dss_kernel(H, L)
    K_f = rfft(K, pad_to=2*L)
    u_f = rfft(u, pad_to=2*L)
    y = irfft(K_f * u_f)[...,:L]
    # param D: [H,1]
    return y + D * u

def gss(x, F=4096, L=4096, E=1024, H=256):
    shortcut, x = x, norm(x)
    v = dense(x, F, activation='gelu')
    u = dense(x, H, activation='gelu')
    y = dss(u, H, L)
    uc = dense(y, F)
    o = dense(uc * v, E)
    return o + shortcut
```

Figure 2: Pseudocode of GSS (§3.2).

B   TRAINING DETAILS

B.1   TRAINING DETAILS FOR RESULTS IN TABLE 1

All the models in Table 1 were trained with 2^{19} tokens per batch and 125k total training steps. We make sure to change the batch size as a function of the sequence length so that number of tokens in the batch remains the same. For example, for LM1B we set batch size to 1024 and sequence length to 512 but for rest of the datasets we use batch size of 128 and sequence length of 4k. For datasets with longer documents, we also considered increasing the sequence length even further. Intuitively,

training on longer sequences would help the model learn longer range dependencies better. On the flip side, it makes the optimization a bit more challenging due to large number of correlated tokens per batch and would even likely result in overfitting. Since GSS is able to generalize beyond the length it was trained on in most cases, we found sequence length of 4k to be a reasonable middle ground for this set of experiments.

B.2 Training details for results in Table 2

Similar to Section 4.3, unless otherwise mentioned, all the non-baseline models were trained using 64 TPUv4 cores for 125k steps. We use batch size of 128 and 4k sequence length at training time, with a total of 2^{19} tokens per batch. We increase the batch size to 256 for the Github dataset (with a token count of 2^{20} per batch) since we observed a lot of noise in our metrics. This is consistent with observations made by Hutchins et al. (2022).

We used Adam optimizer (Kingma & Ba, 2015) and tuned the base learning rate over a grid of $\in$ $[0.0064, 0.0032, 0.0016, 0.0008]$. We also employ linear warmup for 1k steps and cosine decay until 1e-6. We also observed better performance by using a higher than typical weight decay rate of 0.1, other than that we did not employ any additional regularization techniques, including dropout. Note that similar to (Gu et al., 2022a; Gupta et al., 2022), we used a constant learning rate of 1e-3 and set weight decay rate to 0.0 for state space parameters part of GSS Layer . In addition, we clip the gradient to norm 1.0 before passing to the optimizer. Both of these helped with certain instabilities we observed in our preliminary experiments.

B.3 Training details for results in Table 3

For these experiments, we build on our best performing model from Section 4.2 on PG-19 i.e. GSS-Hybrid-L. In order to scale up GSS, we simply increase the number of layers in the model. We also increased the batch size to 256 (from 128) while using 4k sequence length at training time, with a total of 2^{20} tokens per batch, keeping everything else exactly the same.