On the role of population heterogeneity in emergent communication

Abstract

Populations have often been perceived as a structuring component for language to emerge and evolve: the larger the population, the more structured the language. While this observation is widespread in the sociolinguistic literature, it has not been consistently reproduced in computer simulations with neural agents. In this paper, we thus aim to clarify this apparent contradiction. We explore emergent language properties by varying agent population size in the speaker-listener Lewis Game. After reproducing the experimental paradox, we challenge the simulation assumption that the agent community is homogeneous. We first investigate how speaker-listener asymmetry alters language structure to examine two potential diversity factors: training speed and network capacity. We find out that emergent language properties are only altered by the relative difference of factors between speaker and listener, and not by their absolute values. From then, we leverage this observation to control population heterogeneity without introducing confounding factors. We finally show that introducing such training speed heterogeneities naturally sort out the initial paradox: larger simulated communities start developing more systematic and structured languages.

1 Introduction

Language emergence has been explored in linguistics and artificial intelligence for two main reasons (Lazaridou & Baroni, 2020). On the one hand, artificially reproducing language emergence may help to understand the evolution of human languages (Steels, 1997; Briscoe, 2002; Wagner et al., 2003). On the other hand, language is known to be structured, and compositional (Bickerton, 2007), and imitating such properties would enhance machine learning representations. As a result, there exists a constant back and forth between cognitive sciences, linguistics, and artificial intelligence to retrieve the core ingredients of language emergence (Kirby et al., 2008). In this paper, we explore how the size of a population may impact the structure of emerging languages by using neural reinforcement learning methods.

Especially, we explore the following socio-linguistic hypothesis: larger communities create more systematic languages (Raviv et al., 2019; 2020). This hypothesis has been supported by a number of ethnographic (Gary Lupyan, 2010) and socio-linguistics (Raviv et al., 2020) observations as well as behavioral studies mimicking language emergence in a controlled setup (Raviv et al., 2019). Few neural language emergence papers have explored how community size impacts language structure so far, but the available evidence is mitigated at best. Tieleman et al. (2019) observed a small but consistent regularization effect when pairing auto-encoders within a population. Similarly, Cogswell et al. (2019) observed slight improvements in language compositionality with a large population but only reported them in few experimental settings. Finally, Graesser et al. (2019) studied the impact of contact-agents for different population sizes, but they did not observe a correlation between the population size and the convergence speed, success rate, or mutual agent intelligibility.

The following paradox arises: why does community size not improve language properties in recent emergent communication literature, although it is a key structuring factor in broader linguistics literature? We argue that recent emergent communication models are limited as they ignore individual learning capacities by working only with homogeneous populations. Consequently, they miss coupling effects emerging from agents' asymmetries. As a result, we hypothesize that community size effects could occur as soon as local heterogeneities are introduced into populations.

In this work, we explore the effects of population size with neural agents in the well-known Lewis referential game (Lewis, 1969). In this game, a speaker describes a hidden object to a listener, which must then reconstruct object properties. Both agents thus need to co-develop a communication protocol to solve the task. The population-based variant of this game randomly pairs one speaker and one listener from their respective communities. The goal is to observe whether increasing the number of agents enhances the communication protocol qualities, e.g. success rate, compositionality, generalization etc. (Kottur et al., 2017; Chaabouni et al., 2020; Lazaridou et al., 2018).

Firstly, we reproduce Lewis reconstruction setting and confirm the contradiction: when increasing the number of agents, we do not observe improvements over various emergent language metrics. We thus question the current paradigm to model population in the language emergence literature. In particular, all agents are trained uniformly, i.e., their learning speed, capacity, sampling are identical (Tieleman et al., 2019; Cogswell et al., 2019; Fitzgerald, 2019). Secondly, we evaluate the impact of two potential sources of model heterogeneities: (i) agents learning speed, (ii) agents capacities. In both cases, we observe a similar pattern: the absolute value of speaker-listener speed and capacity is not important, yet their relative value is crucial. We hence shed light on the strong correlation between language structures and agents relative training facilities. Thirdly, we push this reasoning further by distributing learning speeds across the population thus creating heterogeneous populations. We there observe an improvement of language scores combined with a variance reduction when increasing population sizes. In other words, larger communities of neural agents start developing more systematic and structured languages when being heterogeneously designed. This observation brings a first stone toward solving the empirical and computational contradiction.

Our experiments partially removed the apparent contradiction between the socio-linguistic observations and the recent emergent communication literature. They illustrate how crucial population training dynamics are in shaping emergent languages and how population heterogeneity may have been underestimated in the recent emergent communication literature. All in all, our contributions are three-fold: (i) we empirically show that the community size is not a structuring factor in language emergence by or in itself in the classic homogeneous Lewis setting; (ii) we give evidences that speaker-listener relative dynamics strongly affects language properties; (iii) we provide the first computational cues to remove the apparent contradiction between socio-linguistic literature and recent neural emergent communication works.

2 RELATED WORK

Population size in sociolinguistics. Population size is a core parameter defining the social environment an agent interacts with. Its impact on language structures has largely been studied on humans (Nettle, 2012; Bromham et al., 2015; Reali et al., 2018; Raviv et al., 2019) and animals (Blumstein & Armitage, 1997; McComb & Semple, 2005; Wilkinson, 2013). By analyzing 2000 languages (Dryer & Haspelmath, 2013), a clear correlation was drawn between population size and diverse language features, e.g. larger communities tend to develop simpler grammars (Gary Lupyan, 2010; Meir et al., 2012; Reali et al., 2018). Raviv et al. (2019) went one step further by arguing that the community size is predictive, i.e. a causal factor, of language structure and diversity. To do so, they split 150 people into different groups of given community size to isolate confounding factors. While people played a speaker-listener Lewis game, they observe that the greater the community size, the simpler and more consistent the generated language. Here, we intend to test this assumption in the context of neural language emergence. All things considered, we adopt a setting close to Raviv et al. (2019)'s when computationally modeling human population.

Populations in simulated emergent communication. Recent works in emergent communication have been debating the prerequisites to the emergence of language universals such as compositionality (Li & Bowling, 2019; Ren et al., 2020; Lazaridou et al., 2018; Mordatch & Abbeel, 2018; Resnick et al., 2020; Kottur et al., 2017; Choi et al., 2018; Łukasz Kuciński et al., 2020), generalisation (Baroni, 2020; Chaabouni et al., 2020; Hupkes et al., 2020; Denamganaï & Walker, 2020), efficiency (Chaabouni et al., 2019; Rita et al., 2020) or stability (Kharitonov et al., 2020; Lu et al., 2020). Among them, a few works explored how different population structures may impact properties of emergent languages. Inspired by iterated learning methods (Kirby et al., 2008), Ren et al. (2020); Li & Bowling (2019); Lu et al. (2020) look at language evolution across multiple generations of agent pairs, i.e. population is spread over time. However, we consider here a population where multiple agent-pairs coexist simultaneously within a single generation. There, Graesser et al.

(2019) show that community of agents start coordinating their language when at least three agents are present in the community. They later assume that increasing the community size may impact the emergent shared language, but did not observe it in their initial experiments. A similar hypothesis was also made by Bouchacourt & Baroni (2019) while analyzing the influence of symmetric agents in the emergence of a common language. With different research objectives, Cogswell et al. (2019) exhibit a slight compositionality enhancement when increasing population size without the need of language transmission. Analogously, Tieleman et al. (2019) explicitly study community size and display a small but consistent gain of abstraction and structure within speakers' latent representations by increasing population size. Eventually, Fitzgerald (2019) suggest that populations improve regularization and generalization compared to single speaker-listener pairs but underlines that there is not a clear correlation between community size and leaning properties. In this paper, we aim at analyzing how population size affects those discussed properties. We align with emergent communication literature and show that naively increasing community size does not consistently improve language properties. We then challenge the homogeneity assumption made in all population designs.

3 METHOD

We here describe the different components of language emergence in a population-based Lewis Game, namely, game rules, notations, training dynamics, and evaluation metrics. Finally, we define how we alter population dynamics by asymmetrizing agents and injecting heterogeneities.

3.1 RECONSTRUCTION GAME.

Game Rules: We study emergent communication in the context of the Lewis referential games (Lewis, 1969). There, a speaker observes all the attributes of an object. The speaker then outputs a descriptive message, which a second agent, the listener, receives. The listener must accurately reconstruct each value of each attribute to solve the task. Both agents are finally rewarded in light of the reconstruction accuracy. Note that another variant of this game requires the listener to retrieve the correct object within a list of distractors, but both settings are inherently similar.

Game Formalism: The observed object $v \in \mathcal{V}^K$ is characterized by $|K|$ attributes where each attribute may take $|\mathcal{V}|$ values. We encode the observed object by a concatenation of one-hot representations of the attributes $v_k \in \mathcal{V}$ of the object v for each attribute $k \in K$. For each new run, the set of objects is split into a training set $\mathcal{X}$ and test set. The intermediate message $m \in \mathcal{W}^T$ is a sequence of $|T|$ tokens, $m = (m_t)_{t=0}^{T-1}$ where each token is taken from a vocabulary $\mathcal{W}$ of dimension $|\mathcal{W}|$, finishing by a hard-coded end-of-sentence token EoS. The speaker and listener are two neural agents respectively parametrized by θ and ϕ. The speaker follows a recurrent policy π_θ: given an input object v, it samples for all t a token m_t with probability $\pi_\theta(m_t|m_{<t}, v)$. We denote $\pi_\theta(m|v)$ the probability distribution of the entire message given an input object v. The listener outputs for each k attributes a probability distributions over the values $\mathcal{V}$: $\pi_\phi^k(v_k|m)$. At training time, the speaker message is generated by sampling the policy $m \sim \pi_\theta(\cdot|v)$. At test time we use the greedy message $\hat{m}_t = \arg\max_{\bar{m}} \pi_\theta(\bar{m}|\hat{m}_{<t}, v)$.

Game Objective: As in (Chaabouni et al., 2020), we define the listener training goal to be the average of the multi-classification log-likelihood loss per attribute:

$$\mathcal{L}_\phi = -\frac{1}{|\mathcal{X}|.|K|} \sum_{v \in \mathcal{X}} \sum_{m \in \mathcal{W}^T} \sum_{k \in |K|} \pi_\theta(m|v) \cdot \log\left(\pi_\phi^k(v_k|m)\right). \tag{1}$$

In our setting, we want the speaker to optimize the same objective. To do so, we define the speaker game reward as the negative loss of the listener,

$$r_t(v, m_{<t}) = \begin{cases} \frac{1}{|K|} \sum_{k \in |K|} \log\left(\pi_\phi^k(v_k|m)\right) & \text{if } t = T, \\ 0 & \text{otherwise.} \end{cases} \tag{2}$$

Following the gradient policy theorem (Sutton et al., 2000), we maximize the speaker reward by minimizing the following objective over θ:

$$\mathcal{L}_\theta = -\frac{1}{|\mathcal{X}|} \sum_{v \in \mathcal{X}} \sum_{t \in |T|} \log \pi_\theta^k(m_t|x, m_{<t}) \cdot r_t(v, m_{<t}), \tag{3}$$

where m is sampled according to the speaker policy π_θ.

3.2 POPULATION-BASED RECONSTRUCTION GAME

We first create a population of N speakers and N listeners, so we have a total number of agents of $2N$. Following (Tieleman et al., 2019), at each step, we uniformly sample one speaker and one listener and pair them together. We then proceed as in the classic one pair Lewis game: both agents play the game with a batch of inputs and receive an optimization step minimizing (Equation 3 & 1). This operation is repeated until convergence, i.e., all speaker-listener pairs have stable test losses. While standard, we note that this training procedure relies on strong latent assumptions: (i) each speaker (resp. listener) is uniformly sampled, i.e., there is no preponderant agent within the population, (ii) the communication graph is fully connected and uniform, i.e., all speakers may be paired with all listeners with the same probability, (iii) agents cannot be differentiated, i.e., agents have no information about the identity of their partners, (iv) speakers and listeners are all similar, i.e., there is no difference in the agent definitions nor in the optimization process. Overall, those hypotheses create a homogeneous training setting. In practice, the agents only differ by their initialization and optimization updates, e.g., stochastic agent pairing, game generations, and message sampling.

3.3 ASSESSING EMERGENT LANGUAGE IN LEWIS GAMES.

We here introduce various metrics to assess emergent languages structure and quality. To do so, we first need to introduce two distances in the input/object space and in the message space. We define the distance between two objects v and v' as the proportion of common attributes computed by $D_{obj}(v, v') = \frac{1}{|K|} \sum_k \mathbb{1}\{v_k = v'_k\}$. For the distance between two messages m and m' we use the edit-distance (Levenshtein et al., 1966) and note it $D_{mes}(m, m')$.

Speakers synchronization: Within populations, we measure how close speakers' languages are by introducing a distance between the two languages. Given two set of speaker weights θ_1 and θ_2 and their respective language $\mathbf{L}_{\theta_1}$ and $\mathbf{L}_{\theta_2}$,

$$D_L(\mathbf{L}_{\theta_1}, \mathbf{L}_{\theta_2}) := \mathbf{E}_{v \in \mathcal{X}, m_1 \sim \pi_{\theta_1}(.|v), m_2 \sim \pi_{\theta_1}(.|v)}[D_{mes}(m_1, m_2)] \tag{4}$$

It computes the average distance between two speakers' messages over all the dataset. When considering an entire population of N speakers, we can then compute the synchronization score $\mathbf{r}_{sync}$ by averaging the distance between all pairs of speakers: $\mathbf{r}_{sync} = \frac{2}{N(N-1)} \sum_{i \neq j} D_L(\mathbf{L}_{\theta_i}, \mathbf{L}_{\theta_j})$.

Entropy: To measure language coherence, we study the entropy of the speaker language $\mathcal{H}_\theta$:

$$\mathcal{H}_\theta := \mathbf{E}_{v, m \sim \pi_\theta(\cdot|v)} \big[\log(\pi_\theta(m|v)) \big] = \mathbf{E}_{v \in \mathcal{X}} \left[\sum_{t=0}^{L-1} h(\pi_\theta(m_t|m_{<t}, v)) \right], \tag{5}$$

where $h : w \to w \log(w)$. In our setting, we seek to minimize entropy as it reduces language complexity, denotes language stability, and reinforces the informational bottleneck principle (Kharitonov et al., 2020; Tishby et al., 2000). For instance, when $\mathcal{H}_\theta$ is minimal, the speaker uses a unique message to refer to an object. When $\mathcal{H}_\theta$ is high, the speaker generates synonyms to refer to the same object. While some entropy is beneficial with noisy communication channels, they do not improve robustness in our case; it only makes the listener's task harder. Finally, to ease reading, we display the negative entropy (Neg-Entropy), so all metrics increases correspond to language improvement.

Topographic Similarity: We use topographic similarity as a quantitative measure of compositionality (Brighton & Kirby, 2006; Lazaridou et al., 2018). Topographic similarity captures how well similarities between objects are transcribed by similarities in the message space by computing the Spearman correlation (Kokoska & Zwillinger, 2000; Virtanen et al., 2020) between pairwise object distance ($D_{obj}(v_1, v_2)$) and the corresponding message distances ($D_{mes}(m_{v_1}, m_{v_2})$).

Generalization: Test accuracy quantifies how well agents generalize to unseen objects. It measures the average reconstruction success on the test set where we define a success when the greedy prediction perfectly matches the input object. The greedy prediction $\hat{v}$ is the one which maximizes the likelihood computed by the listener given the greedy message $\hat{m}$: $\hat{v} = \arg\max_v \prod_k \pi_\phi^k(v_k|\hat{m})$ with $\hat{m}_t = \arg\max_{\bar{m}} \pi_\theta(\bar{m}|\hat{m}_{<t}, v)$ the greedy message.

3.4 ALTERING POPULATION DYNAMICS

We here list potential diversity factors and how they can be distributed when asymmetrizing speaker-listener in minimal size population ($N = 2$), or introducing heterogeneity within larger populations.

Diversity factors: We aim to vary specific agent features toward creating diversity in the population and target two core components: the training speed and the network capacity. First, we control agents' training speed by changing the number of gradient updates. Formally, we introduce the probability p of an agent to be optimized after each iteration of the game. Therefore, the lower p, the slower agent training. This approach has two positive features: (i) it neither alters the communication graph nor the agent sampling, preserving other homogeneity hypotheses in the population, (ii) it is more stable than modifying the learning rate as it avoids large destructive updates. Second, we control the network capacity by varying the agent hidden size h in the recurrent core. Note that we only control training speed or network capacity, never both at once.

Control parameters of local asymmetry: We provide control parameters to characterize diversity at the scale of a minimal size population ($N = 2$). Noticeably, $N = 2$ is the closer setting to a single-pair of agents where we can compute speakers synchronization. To analyze the effect of speaker-listener asymmetries, we introduce the relative training speed $\rho_{speed} := p^S/p^L$ and the relative capacity $\rho_{capacity} := h^S/h^L$ where p_S (resp. p^L) is speaker's learning speed (resp. listener's learning speed) and h^S (resp. h^L) is speaker's hidden size (resp. listener's hidden size).

Distributing Population Heterogeneity: To create heterogeneous populations, we characterize every single speaker and listener with individual properties. We then sampled them once at the beginning of the training. Formally, when altering training speed, we sample $p_i \sim \text{Log-}\mathcal{N}(\eta_p, \sigma_p)$ for every i agent in the population, where Log-$\mathcal{N}$ is a log normal distribution. As explained in section 5.2, we only perform this experiment with the update probability factor.

4 EXPERIMENTAL SETTING

Game Properties: In the main paper, we use $|K| = 4$ attributes with $|\mathcal{V}| = 4$ values. We also report scores with $|K| = 2$ attributes and $|V| = 10$ values in the Appendix E to illustrate that our observation still holds in a different setting. Finally, we use a vocabulary size of $|\mathcal{W}| = 20$ and a message length $T = 10$. For each run, we generate objects in $\mathcal{V}^K$ uniformly at random, and we split them into a train and a test sets, which respectively contains 80% and 20% of the objects.

Neural architectures: The speaker first encodes the input object v in a one hot encoding and then processes it with a linear layer. It uses it to initialize a single layer LSTM (Hochreiter & Schmidhuber, 1997) with layernorm (Kiros et al., 2015) and a (default) hidden size of 128. Finally, the LSTM output is fed to a linear layer of dimension $|\mathcal{W}|$ followed by a softmax activation. The listener is composed of a look-up table of dimension 128 followed by a LSTM with layernorm and a (default) hidden size of 128. Then, for each attribute $k \in \{1, ..., K\}$, we apply a linear projection of dimension $|\mathcal{V}|$ followed by a softmax activation to the last LSTM output.

Optimization: For both agents, we use a Adam optimizer with a learning rate of $5e10^{-3}$, $\beta_1 = 0.9$ and $\beta_2 = 0.999$ and a training batch size of 1024 when optimizing for their respective loss. For the speaker, we set the entropy coefficient of 0.02. Finally, we re-normalize the reward by using $\bar{r}(x, w_{<t}) = \frac{r(x, w_{<t}) - \eta_t^r}{\sigma_t^r}$ to reduce the gradient variance (Sutton et al., 2000), where η_t^r and σ_t^r are respectively the average and the standard deviation of the reward within the batch at each time step. In practice, they are respectively equal to zero and one for all the timesteps but the last.

We use the EGG toolkit (Kharitonov et al., 2019) as a starting framework. The code is available at HIDDEN. All experiments are run over six seeds. In all figures, bars show one standard deviation.

5 RESULTS AND DISCUSSION

This section first reproduces the impact of the population size on language properties in the homogeneous Lewis setting. We then study speaker-listener asymmetry by altering networks training speed and capacity, and highlight the importance of relative training speed in shaping language. We finally use relative training speed as a non-confounding heterogeneity factor when varying the community-size, and thus tackle the initial contradiction.

Figure 1: Emergent languages properties of homogeneous populations of increasing sizes. Based on socio-linguistics results, all curves should trend upward with population size.

5.1 COMMUNITY SIZE IS NOT ALONE A LANGUAGE STRUCTURING FACTOR

Language properties are not enhanced by community size. In Figure 1, we observe that increasing population size does not improve language properties: speaker synchronization and compositionality remain almost constant, and entropy and generalization are even deteriorating. In addition, we do not observe any language systematicity. By systematicity, we mean languages whose properties are stable across seeds. Here, increasing community size does not reduce the standard deviation of the language metrics across seeds. Finally, we note that the speaker synchronization is high despite using large communication channel, as also observed by (Graesser et al., 2019). Overall, we confirm that community size does not improve the language properties of neural agents.

The potential pitfall of homogeneity. We hypothesize that the absence of positive correlation between population size and language properties may be explained by the simplicity of population modeling. The homogeneity assumption seems restrictive as it implies two main limitations: (i) although agents are not identically initialized, they have the same training dynamics in expectation, (ii) all agents have the same optimization process, whereas real communities are inherently diverse. Consequently, we formulate the subsequent hypothesis: Community size may be a structuring factor as soon as heterogeneity is introduced in populations design.

5.2 LANGUAGE PROPERTIES ARE CONTROLLED BY SPEAKER-LISTENER ASYMMETRIES

Figure 2: Emergent language properties as a function of speed ratio ρ_{speed} (top) and capacity ratio $\rho_{capacity}$ (bottom) with $N = 2$. From left to right on the x axis, the speaker have higher training speed/capacity while the listener have lower training speed/capacity.

Before generating heterogeneous populations, we explore potential diversity factors at the scale of a minimal size population ($N = 2$). The aim is to characterize those factors at a small scale in order not to add confounding factors and better intuit population dynamics. As described in Section 3.4, we here modify the learning speed and network capacity for a minimal size population. Note that we compute this ratio through multiple values of p^S/p^L and h^S/h^L, where $p \in \{0.01, 0.02, 0.04, 0.1, 0.2, 0.5, 1.\}$ and $h \in \{32, 64, 128, 256, 512, 1024\}$.

Relative differences between speaker and listener significantly affect language properties. In Figure 2, we display the evolution of language properties with ρ_{speed} and $\rho_{capacity}$. We observe that asymmetrizing speaker-listener learning speed and capacity significantly influences language

Figure 3: Training accuracy evolution of speaker-listener pair where one agent is pretrained. In left figure (resp. right), the listener (resp. speaker) was pretrained with a speaker and frozen and we show accuracy evolution when paired with new speakers (resp. listeners) of increasing capacity.

properties. When the speakers have a large update probability p_s or are over-parametrized compared to the listeners, we note a global improvement of language properties: (i) speakers synchronization rate is very high, (ii) language neg-entropy is reaching almost 0, meaning almost a bijective language mapping, (iii) compositionality is significantly improved and (iv) test accuracy is close its optimal value. On the contrary, when listeners have a large update probability or are over-parametrized compared to the speakers, we note the opposite trend.

As a sanity check, we then verify that altering p and h does not fundamentally change the language properties per itself. We thus sweep over the network capacity h and the gradient update probability p while setting a minimal population size of $N = 2$, and compute the Spearman correlation in Table 1. We observe that both hyperparameter p and h have no statically significant correlations with most of the language scores, i.e. their Spearman coefficients are below 0.4 with p-values above 0.05. The only noteworthy correlation is between the network capacity h and the Neg-entropy with a Spearman correlation of 0.89 and a p-value< 0.05. However, as shown in Appendix A the variations are two orders of magnitude lower than neg-entropy variations in Figure 2. Therefore, the impact of this correlation is small enough in our experiments to be neglected. In sum, it is not the magnitude of the parameters that is critical to shape language, but the relative ratio between them.

Understanding learning speed asymmetries. We here try to provide some pieces of intuitions to understand ρ_{speed} by looking at the extreme cases. In the limit $\rho_{speed} \ll 1$, i.e. $p_s \ll p_l$, we can consider that the listener is almost optimal wrt. the speaker at each speaker update. It implies that listener's cross-entropy loss is optimally minimized for each message sampled by the speaker that refers to a single input. Then, as soon as speakers develop a language where each message refers to a single input, the game is over as speaker's rewards are immediately optimal. It means that many languages can emerge from this limit case, including languages with high entropy, small synchronization rates, poor compositionality, low generalization.

In the limit $\rho_{speed} \gg 1$, i.e. $p_s \gg p_l$, we can consider that the speaker is almost optimal wrt. the listener at each listener update. The speaker therefore targets the messages providing the highest rewards as in a stationary RL task. We can safely assume that the set of messages providing the highest rewards for each input is small. It then explains why the speaker converges to a low entropy language. In addition, when $N = 2$, both speakers solve the same communication task and obtain similar rewards. As a result, they are more likely to align on a similar language as they observe the same quasi-stationary environment. This use-case also suggests that when speakers are "fast enough", the only requirement to the emergence of a common language is a common interlocutor. Finally, we push further the assumption by interpreting the gain of compostionality through "ease-of-teaching" (Li & Bowling, 2019). The authors show that compositional languages are easier to teach for listeners. We then hypothesize here that 'faster' speakers develop languages easier to learn for 'slow' listeners and thus higher quality languages.

Table 1: Spearman Correlation between h, p and language scores. p-values < 0.05 are underlined.

Param.	Sweep	Sp. sync	Neg-Entropy	Compo.	Gene.
p	{0.01, 0.02, 0.04, 0.1, 0.2, 0.5, 1. }	0.13	0.33	0.05	-5e-3
h	{32, 64, 128, 256, 512, 1024 }	-0.14	0.89	0.29	0.11

Network capacity may be confounded with training speed. While the effect of training speed may be partially intuited, the impact of capacity is more tedious to analyze. As we have already observed that training speed is a crucial parameter, we thus test whether a correlation between net-

work capacity and learning speed can be established. In Figure 3 and Appendix D, we pair a fixed pretrained listener (resp. speaker) with newly initialized speakers (resp. listeners) of increasing capacities and see how fast those new speakers (resp. listeners) reach convergence. We observe that all trained agents converge to the same accuracy. However, we also note that they have different convergence speeds. Speakers (resp. listeners) of capacity 512, 128, 32 respectively have to see 100, 250, and 900 batches (resp. 50, 100 and 250 batches) to reach train accuracy of 95%. In short: the larger the network, the faster the training speed. We conclude that network capacity is a confounding factor of training speed in our setting. Therefore, we only explore the training speed ratio in our next experiments. More generally, we suspect that many other parameters may be latently related to speed of training, e.g. community-graph (Graesser et al., 2019), newborn agents (Ren et al., 2020; Cogswell et al., 2019; Li & Bowling, 2019), or broadcasting by using different speaker-listener ratios as illustrated in Appendix B, but we leave it for future analysis. Besides, the Lewis game remains synthetic and capacity cannot be reduced to training speed in other settings (Kaplan et al., 2020; Resnick et al., 2020).

5.3 COMMUNITY SIZE STRUCTURES LANGUAGES OF HETEROGENEOUS POPULATIONS

Figure 4: Emergent languages properties of heterogeneous populations of increasing sizes.

Previous sections have identified that learning speed is a powerful controlling factor and could alter language structure when asymmetrizing speaker-listener pairs. However, these experiments remain limited for (i) we have not yet observed larger population-size tend to generate more systematic and structured language, (ii) this asymmetry remains artificial and specific to our Lewis game setting. Therefore, we here leverage this training speed factor within a population, characterizing individual agents with different update probabilities. We hence sample agent update probability with $p \sim$ Log-$\mathcal{N}(\eta_p, \sigma_p)$ with $\eta_p = -1$ and $\sigma_p = 0.5$ if not specified otherwise.

Larger heterogeneous population leads to higher quality language. In Figure 4, we observe that emergent language metrics are now positively correlated with population size. When increasing the population size from 2 to 20; the speaker synchronization, neg-entropy, compositionality, and generalization increase by 41%, 64%, 8%, and 2% on average. As detailed in Appendix C, compositionality and generalization have a small positive but statistically significant correlation with Spearman coefficients above 0.3 (p-values> 0.05), and we do not observe a language score contraction as initially noted with homogeneous population in Figure 1. Those are the first hints toward our initial goal: when individuals are heterogeneous, a large population size correlates with higher quality and stable language properties.

The overall gain over language metrics can be interpreted in light of Section 5.2. Language score evolution depends on the relative speaker-listener learning speeds. In heterogeneous populations, the probability of sampling extreme learning speed p from the distribution tails and thus enforcing speaker-listener asymmetries increases when N grows. One explanation would be that extreme agents, especially slow listeners, behave as kinetic bottlenecks, forcing the speakers to structure their languages. Thus, language emergent properties would be particularly determined by fast speakers and/or slow listeners.

Larger heterogeneous population leads to more systematic language. Similarly, the population size correlates with the variance of the language scores across seeds. Hence, when increasing the population size from 2 to 20; the standard deviations of speakers synchronization, neg-entropy, compositionality are divided by 5, 7 and 2; yet compostionality is less affected. One hypothesis for this variance reduction is that smaller communities are more likely to be disparate because of the sampling procedure. For instance, if we characterize a population with the empirical average of the training speeds $\hat{\eta}_p$, it has high variance with small N. On the other side, the bigger the community, the closer is the average training speed to the mean of distribution law, $\lim_{N \to \infty} \hat{\eta}_p = \eta_p$,

and the less variance we have in the language properties. In other words, larger heterogeneous communities have more systematic languages because of Law of large numbers in our models. Such a phenomenon may not occur in the homogeneous population, hence the initial apparent contradiction.

Increasing diversity enforces population size benefits. In Figure 5, we challenge further the impact of heterogeneity on population by varying the standard deviation σ_p of the learning speed distribution. For each value of σ_p, we run the game with populations of size $N = 2$ and $N = 10$ and compare the relative evolution of the scores between the two population sizes. We note that the higher σ_p, the larger the gain of synchronization, neg-entropy, generalization when increasing N. Trends are particularly significant for neg-entropy and speaker synchronization. For the generalization, the 10% relative improvement is noteworthy as it corresponds to reaching close to 100% test accuracy. The more discrepancy exists within the population (large σ_p), the more beneficial is to have large populations. Furthermore, speaker synchronization, neg-entropy and generalization standard deviations reduce up to almost 80% when having $\sigma_p > 2$. In sum, this result corroborates that larger populations lead to more systematic language.

Figure 5: Relative variations in average language scores (top) or standard deviations (bottom) between populations of size $N = 10$ and $N = 2$ as a function of increasing heterogeneity $\sigma_p = \{0, 0.1, 0.5, 1, 2, 3, 4, 5\}$. It is defined by $100 \times (\bar{y}_{N=10} - \bar{y}_{N=2})/\bar{y}_{N=2}$ where $\bar{y}_N$ is the average of the mean (or std) across seeds for a population of size N. The blue (resp. orange) line shows relative variations of the mean (resp. std) score between populations with $N = 10$ and $N = 2$. Larger population better benefits when diversity is high: language is of higher quality (blue), and the language is more systematic (orange).

6 CONCLUSION

One objective of language emergence simulations is to identify simple (non-biological) rules that characterized language evolution (Steels, 1997; Briscoe, 2002; Wagner et al., 2003; Kirby, 2001). However, those models require a delicate balance between simplicity to ease analysis and complexity to remain realistic. In this paper, we argue that the current population-based models may actually be to simplistic as they assume homogeneous communities. We show that this simplification is a potential root cause of the contradiction between neural computational observations and socio-linguistic literature. Namely, larger populations should lead to more systematic and structured languages, which is not observed in recent emergent models. Yet, as soon as we add diversity within populations, this contradiction vanishes. We advocate for better integrating population diversity and dynamics in emergent literature if we want computational models to be useful. In this journey, we also observe that the relative training speed of the agents may be an underestimated factor in shaping languages. Worse, other agent properties may be confounded with it, such as network capacity.

This work also opens many questions. First, our observations were performed in the Lewis game so far, and it would be interesting to observe the impact of diversity in more complex settings. Second, while heterogeneity is a structuring factor in population, the core factors are yet to be investigated, e.g., how to correctly model diversity, are there some causal components? Third, we break the homogeneous assumptions in our work, but other procedures may exist that solve the initial contradiction. Finally, training speed is a natural controlling parameter for computational models, but it is unclear how it may relate to human behavior. Overall, we hope that this paper provides new insights toward modeling populations in language emergence, and it is part of this constant back and forth between cognitive sciences, linguistics, and artificial intelligence.

REFERENCES

Marco Baroni. Linguistic generalization and compositionality in modern artificial neural networks. *Philosophical Transactions of the Royal Society B: Biological Sciences*, 375(1791):20190307, 2020. doi: 10.1098/rstb.2019.0307.

Derek Bickerton. Language evolution: A brief guide for linguists. *Lingua*, 117(3):510–526, 2007.

Daniel T. Blumstein and Kenneth B. Armitage. Does sociality drive the evolution of communicative complexity? a comparative test with ground-dwelling sciurid alarm calls. *The American Naturalist*, 150(2):179–200, 1997.

Diane Bouchacourt and Marco Baroni. Miss tools and mr fruit: Emergent communication in agents learning about object affordances. In *Proc. of the Association for Computational Linguistics (ACL)*, 2019.

Henry Brighton and Simon Kirby. Understanding Linguistic Evolution by Visualizing the Emergence of Topographic Mappings. *Artificial Life*, 12(2):229–242, 04 2006. ISSN 1064-5462. doi: 10.1162/artl.2006.12.2. 229.

Ted Briscoe. *Linguistic evolution through language acquisition*. Cambridge University Press, 2002.

Lindell Bromham, Xia Hua, Thomas G. Fitzpatrick, and Simon J. Greenhill. Rate of language evolution is affected by population size. *Proc. of the National Academy of Sciences*, 112(7):2097–2102, 2015. ISSN 0027-8424. doi: 10.1073/pnas.1419704112.

Rahma Chaabouni, Eugene Kharitonov, Emmanuel Dupoux, and Marco Baroni. Anti-efficient encoding in emergent communication. In *Proc. of Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

Rahma Chaabouni, Eugene Kharitonov, Diane Bouchacourt, Emmanuel Dupoux, and Marco Baroni. Compositionality and generalization in emergent languages. In *Proc. of the Association for Computational Linguistics (ACL)*, 2020.

Edward Choi, Angeliki Lazaridou, and Nando de Freitas. Multi-agent compositional communication learning from raw visual input. In *Proc. of International Conference on Learning Representations (ICLR)*, 2018.

Michael Cogswell, Jiasen Lu, Stefan Lee, Devi Parikh, and Dhruv Batra. Emergence of compositional language with deep generational transmission. *arXiv preprint arXiv:1904.09067*, 2019.

Kevin Denamganaï and James Alfred Walker. On (emergent) systematic generalisation and compositionality in visual referential games with straight-through gumbel-softmax estimator. *arXiv preprint arXiv:2012.10776*, 2020.

Matthew S. Dryer and Martin Haspelmath (eds.). *WALS Online*. Max Planck Institute for Evolutionary Anthropology, Leipzig, 2013. URL https://wals.info/.

Nicole Fitzgerald. To populate is to regulate. *arXiv preprint arXiv:1911.04362*, 2019.

Rick Dale Gary Lupyan. Language structure is partly determined by social structure. *PLoS ONE 5*, 1, 2010.

Laura Graesser, Kyunghyun Cho, and Douwe Kiela. Emergent linguistic phenomena in multi-agent communication games. In *Proc. of Empirical Methods in Natural Language Processing (EMNLP)*, 2019.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8):1735–1780, 1997.

Dieuwke Hupkes, Verna Dankers, Mathijs Mul, and Elia Bruni. Compositionality decomposed: how do neural networks generalise? *Journal of Artificial Intelligence Research*, 67:757–795, 2020.

Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. Scaling laws for neural language models. *arXiv preprint arXiv:2001.08361*, 2020.

Eugene Kharitonov, Rahma Chaabouni, Diane Bouchacourt, and Marco Baroni. Egg: a toolkit for research on emergence of language in games. In *Proc. of Empirical Methods in Natural Language Processing (EMNLP)*, 2019.

Eugene Kharitonov, Rahma Chaabouni, Diane Bouchacourt, and Marco Baroni. Entropy minimization in emergent languages. In *Proc. of International Conference on Machine Learning (ICML)*, 2020.

Simon Kirby. Spontaneous evolution of linguistic structure-an iterated learning model of the emergence of regularity and irregularity. *IEEE Transactions on Evolutionary Computation*, 5(2):102–110, 2001.

Simon Kirby, Hannah Cornish, and Kenny Smith. Cumulative cultural evolution in the laboratory: An experimental approach to the origins of structure in human language. In *Proc. of the National Academy of Sciences of the United States of America (PNAS)*. National Academy of Sciences, 2008.

Ryan Kiros, Yukun Zhu, Russ R Salakhutdinov, Richard Zemel, Raquel Urtasun, Antonio Torralba, and Sanja Fidler. Skip-thought vectors. In *Proc. of Advances in Neural Information Processing Systems (NIPS)*, 2015.

Stephen Kokoska and Daniel Zwillinger. *CRC standard probability and statistics tables and formulae*. Crc Press, 2000.

Satwik Kottur, José Moura, Stefan Lee, and Dhruv Batra. Natural language does not emerge 'naturally' in multi-agent dialog. In *Proc. of Empirical Methods in Natural Language Processing (EMNLP)*, 2017.

Angeliki Lazaridou and Marco Baroni. Emergent multi-agent communication in the deep learning era. *arXiv preprint arXiv:2006.02419*, 2020.

Angeliki Lazaridou, Karl Moritz Hermann, Karl Tuyls, and Stephen Clark. Emergence of linguistic communication from referential games with symbolic and pixel input. In *Proc. of International Conference on Learning Representations (ICLR)*, 2018.

Vladimir I Levenshtein et al. Binary codes capable of correcting deletions, insertions, and reversals. In *Soviet physics doklady*, volume 10:8, pp. 707–710. Soviet Union, 1966.

David K. Lewis. *Convention: A Philosophical Study*. Wiley-Blackwell, 1969.

Fushan Li and Michael Bowling. Ease-of-teaching and language structure from emergent communication. In *Proc. of Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

Yuchen Lu, Soumye Singhal, Florian Strub, Aaron Courville, and Olivier Pietquin. Countering language drift with seeded iterated learning. In *Proc. of International Conference on Machine Learning (ICML)*, 2020.

Karen McComb and Stuart Semple. Coevolution of vocal communication and sociality in primates. *Biology letters*, 1(4):381–385, 2005.

Irit Meir, Assaf Israel, Wendy Sandler, Carol A Padden, and Mark Aronoff. The influence of community on language structure: evidence from two young sign languages. *Linguistic Variation*, 12(2):247–291, 2012.

Igor Mordatch and Pieter Abbeel. Emergence of grounded compositional language in multi-agent populations. In *Proc. of Conference on Artificial Intelligence (AAAI)*, 2018.

Daniel Nettle. Social scale and structural complexity in human languages. *Philosophical Transactions of the Royal Society B: Biological Sciences*, 367(1597):1829–1836, 2012. doi: 10.1098/rstb.2011.0216.

Limor Raviv, Antje Meyer, and Shiri Lev-Ari. Larger communities create more systematic languages. *Proc. of the Royal Society B: Biological Sciences*, 286(1907):20191262, 2019. doi: 10.1098/rspb.2019.1262.

Limor Raviv, Antje Meyer, and Shiri Lev-Ari. The role of social network structure in the emergence of linguistic structure. *Cognitive Science*, 44(8):e12876, 2020.

Florencia Reali, Nick Chater, and Morten H. Christiansen. Simpler grammar, larger vocabulary: How population size affects language. *Proc. of the Royal Society B: Biological Sciences*, 285(1871):20172586, 2018. doi: 10.1098/rspb.2017.2586.

Yi Ren, Shangmin Guo, Matthieu Labeau, Shay B. Cohen, and Simon Kirby. Compositional languages emerge in a neural iterated learning model. In *Proc. of International Conference on Learning Representations (ICLR)*, 2020.

Cinjon Resnick, Abhinav Gupta, Jakob Foerster, Andrew M. Dai, and Kyunghyun Cho. Capacity, bandwidth, and compositionality in emergent language learning. In *Proc. of Autonomous Agents and Multiagent Systems (AAMAS)*, 2020.

Mathieu Rita, Rahma Chaabouni, and Emmanuel Dupoux. "LazImpa": Lazy and impatient neural agents learn to communicate efficiently. In *Proc. of the Conference on Computational Natural Language Learning (CoNLL)*, 2020.

Luc Steels. The synthetic modeling of language origins. *Evolution of communication*, 1(1):1–34, 1997.

Richard S Sutton, David A McAllester, Satinder P Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. In *Proc. of Advances in Neural Information Processing Systems (NIPS)*, 2000.

Olivier Tieleman, Angeliki Lazaridou, Shibl Mourad, Charles Blundell, and Doina Precup. Shaping representations through communication: community size effect in artificial learning systems. *Visually Grounded Interaction and Language (ViGIL) Workshop*, 2019.

Naftali Tishby, Fernando C Pereira, and William Bialek. The information bottleneck method. *arXiv preprint physics/0004057*, 2000.

Pauli Virtanen, Ralf Gommers, Travis E. Oliphant, Matt Haberland, Tyler Reddy, David Cournapeau, Evgeni Burovski, Pearu Peterson, Warren Weckesser, Jonathan Bright, Stéfan J. van der Walt, Matthew Brett, Joshua Wilson, K. Jarrod Millman, Nikolay Mayorov, Andrew R. J. Nelson, Eric Jones, Robert Kern, Eric Larson, C J Carey, İlhan Polat, Yu Feng, Eric W. Moore, Jake VanderPlas, Denis Laxalde, Josef Perktold, Robert Cimrman, Ian Henriksen, E. A. Quintero, Charles R. Harris, Anne M. Archibald, Antônio H. Ribeiro, Fabian Pedregosa, Paul van Mulbregt, and SciPy 1.0 Contributors. SciPy 1.0: Fundamental Algorithms for Scientific Computing in Python. *Nature Methods*, 17:261–272, 2020. doi: 10.1038/s41592-019-0686-2.

Kyle Wagner, James A Reggia, Juan Uriagereka, and Gerald S Wilkinson. Progress in the simulation of emergent communication and language. *Adaptive Behavior*, 11(1):37–69, 2003.

Gerald S. Wilkinson. *12. Social and Vocal Complexity in Bats:*. Harvard University Press, 2013.

Łukasz Kuciński, P. Kołodziej, and Piotr Milos. Emergence of compositional language in communication through noisy channel. In *Language in Reinforcement Learning (LaReL), ICML Workshop*, 2020.

A   NON-CONFOUDING PARAMETERS

Figure 6: Variations of language metrics with increasing values of gradient update probability p.

Figure 7: Variations of language metrics with increasing values of agents hidden size h.

In Figure 6 & 7, we show the variations of language scores with increasing values of p and h, while being identical for speaker and listener. In Table 1, we shows the Spearman correlation between the metrics and the control parameters. We do not observe significant correlation when working with p. In addition, both the relative and absolute variations of the parameters are negligible compared to experiments displayed in Figure 2.

B   ALTERING THE SPEAKERS AND LISTENERS RATIO

Figure 8: Language metrics for different ratio between $N_{speaker}$ and $N_{listener}$ where $N_{speaker}$ and $N_{listener}$ are in the range $\{1, 2, 4, 8, 16, 24, 50, 75100\}$. Experiments are run with $|K| = 2$ and $|V| = 10$.

We extends results of Section 5.2 to another population factor and intuit how it relates to learning speed. We introduce the ratio between the number of speakers and the number of listeners within a population $\rho_{agents} := \frac{N_{listener}}{N_{speaker}}$. Note that this ratio cannot be applied to a single speaker-listener pair. Yet, it introduces an asymmetry between the community of speakers and the community of listeners. We show the evolution of language metrics in Figure 8. There, we observe than unbalancing N_s and N_l has a strong impact on language scores. Speaker synchronization reach upper and lower bound depending on the ratio, Neg-entropy either is very low or close to 0, and compositionality and generalization increase. ρ_{agents} is thus an additional control factor of language properties. Extreme cases coincide with the training speed interpretation of Section 5.2. Indeed, at each iteration of the game, each speaker (resp. listener) has a probability $1/N_{speakers}$ (resp. $1/N_{listeners}$) to be sampled. Thus, speakers have $N_{listeners}/N_{speakers}$ more of less learning steps than listeners. Consequently,

when $\rho_{agents} \gg 1$, individual speakers (resp. listeners) have way more optimization steps than individual listeners (resp. speakers) and we fairly hypothesize that speakers (resp. listeners) train faster than listeners (resp. speakers). This ratio may therefore be a confounding factor of a training speed mechanism. Note that, interestingly, ρ_{agents} can also be related to different sampling procedures, or broadcasting phenomenon.

C ADDITIONAL CORRELATIONS

Table 2: Spearman Correlation between community size and language scores for homogeneous and heterogeneous populations ($\eta_p = -1$, $\sigma_p = 0.5$). These correlations are related respectively to Figure 1 and Figure 4. We underline correlation with $p > 0.05$.

Experiment	Sp. sync	Neg-Entropy	Compo.	Gene.
Homogeneous population	-0.44	-0.52	-0.15	-0.14
Heterogeneous population	0.35	0.37	0.15	-0.07

Table 3: Spearman Correlation between controlling factor ratios and language scores in Figure 2. We underline correlation with $p > 0.05$.

Param.	Sp. sync	Neg-Entropy	TopSim	Accuracy
ρ_{speed}	0.96	0.97	0.63	0.34
$\rho_{capacity}$	0.49	0.77	0.33	0.09

D INFLUENCE OF CAPACITY ON AGENTS LEARNING SPEED

Figure 9: Training accuracy of speaker-listener pair where listener is pretrained and fixed. For all curves, a listener has been pretrained with a random speaker, frozen and paired with new initialized speakers of increasing sizes. Each row corresponds to a new pretrained listener ; each column to a new initalization of the speakers.

Figure 10: Training accuracy for speaker-listener pair where the speaker is pretrained and fixed. For all curves, a speaker has been pretrained with a random listener, frozen and paired with new initialized listeners of increasing sizes. Each row corresponds to a new pretrained speaker ; each column to a new initalization of the listeners

In Section 5.2, we shed light on the link between the network capacity and the training speed. We here complete this observation. In Figure 9 (resp. Figure 10), we pair a fixed pretrained listener (resp. speaker) with newly initialized speakers (resp. listeners) of increasing capacity and then display the evolution of their training accuracies, and confirmed further our observation. Please note in Figure 9, some limit cases appear with the pure RL task, i.e. fixed listener. Speakers' convergence become instable across seeds for small networks ($h_S = 32$). Yet, the training is still stable in supervised task, i.e. fixed speaker, in Figure 10.

E COMPLEMENTARY SETTING

In this section, we reproduce our core experiments in a different Lewis game setting, with $|K| = 2$ attributes containing each $|V| = 10$ values.

Figure 11: Language scores with homogeneous population with $N = \{1, 2, 4, 6, ..., 20\}$, $|K| = 2$ and $|V| = 10$. Corresponding figure with $|K| = 4$ and $|V| = 4$ in the main paper is Figure 1

Figure 12: Language scores with heterogeneous population with $N = \{1, 2, 4, 6, ..., 20\}$, $\eta_p = -1$, $\sigma_p = 0.5$, $|K| = 2$ and $|V| = 10$. Corresponding figure with $|K| = 4$ and $|V| = 4$ in the main paper is Figure 4