NN-Baker: A Neural-network Infused Algorithmic Framework for Optimization Problems on Geometric Intersection Graphs

Abstract

Recent years have witnessed a surge of approaches to use neural networks to help tackle combinatorial optimization problems, including graph optimization problems. However, theoretical understanding of such approaches remains limited. In this paper, we consider the geometric setting, where graphs are induced by points in a fixed dimensional Euclidean space. We show that several graph optimization problems can be approximated by an algorithm that is linear in graph size n via a framework we propose, called the Baker-paradigm. A key advantage of the Baker-paradigm is that it decomposes the input problem into (at most linear number of) small sub-problems of **bounded sizes** (independent of the size of the input). For the family of such bounded-size sub-problems, we can now design neural networks with universal approximation guarantees to solve them. This leads to a mixed algorithmic-ML framework, which we call NN-Baker that has the capacity to approximately solve a family of graph optimization problems (e.g, maximum independent set and minimum vertex cover) in time linear in the input graph size. We instantiate our NN-Baker by a CNN version and GNN version, and demonstrate the effectiveness and efficiency of our approach via a range of experiments.

1 Introduction

Many tasks in science and engineering can be naturally modeled by combinatorial optimization problems over graphs, such as maximum independent set, minimum vertex cover, minimum multi-way cut, maximum clique, and so on. These problems are often NP-hard. Hence there has been great effort devoted to developing efficient approximation algorithms. However, many such problems are hard to approximate in the general setting as well: for example, it is known that the maximum independent set problem is NP-hard, and it is even NP-hard to approximate within $n^{1-\varepsilon}$ on n-vertex graphs, for any $\varepsilon > 0$ [1].

On the other hand, many of these hard problems admit PTAS in the *geometric setting* when the graphs are assumed to be induced by points in fixed-dimensional Euclidean space. Here, a *PTAS (polynomial-time approximation scheme)* is a polynomial time algorithm which for any fixed $\varepsilon > 0$, can approximate a maximization problem within a factor of $(1 + \varepsilon)$ (or within a factor of $(1 - \varepsilon)$ for a minimization problem). One most prominent example is the travelling salesman problem (TSP), where in general there is no PTAS available (and currently the best known approximation algorithm achieves an factor of $3/2 - \alpha$, for some $\alpha > 10^{-36}$ [2]). However a PTAS, more specifically in this case a near linear time $(1 + \varepsilon)$-approximation algorithm, was developed for the Euclidean TSP problem in a ground breaking work by Arora [3]. The maximum independent set problem is known to remain NP-hard in the geometric setting [4], but it is known that it also admits a PTAS [5, 6, 7].

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

Nevertheless, for problems of large size, even these PTAS are still not practical, especially since many of them involve large constant that are **exponential** in some fixed parameter (e.g, having a term like $n^{\frac{1}{\varepsilon}}$ where $(1 + \varepsilon)$ is the approximation factor). In applications, practitioners often rely on handcrafted heuristic search strategies to find high-quality solutions.

Recently, there has been a surge on using machine learning (ML) for combinatorial optimization problems; see the review paper by Bengio *et al.* [8] which also provides a nice categorization of different ways that a ML component may contribute to the combinatorial optimization problems. Earlier such approaches focus on several graph combinatorial optimization problems, including TSP, minimum vertex cover and maximum independent sets; see e.g., [9, 10, 11, 12, 13, 14, 15, 16]. More recently, there has been a range of approaches developed to tackle more general mixed integer linear programming problems (MILP); e.g, [17, 18, 19, 20, 21]. See Section 1.1 for more detailed description of some related work.

In general, an ML framework can be trained to solve an optimization problem in *an end-to-end manner* (e.g, [10, 11, 12, 15, 16]). Alternatively, many recent approaches use ML module as a component *within a specific algorithmic framework* to help make hopefully better (either in terms of quality or efficiency) decisions during the execution of this algorithm: such as using imitation learning or reinforcement learning to learn a good policy to decide which variable to branch in a branch-and-bound algorithm [18, 20]. Despite the tremendous progress in combining ML with optimization problems, theoretical understanding remains limited: Does a proposed ML pipeline has the expressiveness capacity to solve the combinatorial optimization problem exactly or approximately? What is a suitable model for input data distribution to talk about generalization?

Consider the capacity question: While neural networks are known to have many universal approximation results for real or complex valued continuous functions (or some other special families of functions), e.g, [22, 23, 24, 25], combinatorial optimization problems, say finding the maximum independent set, cannot be easily modeled to fit into such function approximation frameworks. Nevertheless, a very interesting recent work [13] shows that for graph combinatorial optimization problems, the so-called vector-vector consistent graph neural networks (VV_C-GNNs), can solve the same family of problems as the distributed local algorithms in the so-called port-numbering models. Leveraging the literature in distributed local algorithms [26, 27], this leads to several positive results on the capacity of GNNs for approximating minimum vertex cover or maximum matching problems with certain constant factors, however **only for graphs with bounded degrees** – intuitively, the depth of the GNN will depend on the bound Δ on the maximum node degree of input graphs. Unfortunately, the connection to distributed local algorithms also leads to negative results: roughly speaking, these constant factor approximations for the special family of **constant-degree graphs** are the best that a GNN can do for these graph optimization problems. See [13] for details.

Our work. The aforementioned results (on the capacity of GNNs) are for the case where GNNs are used to solve an optimization problem *in an end-to-end manner*, and other than the bound on max-degree, the input graphs are abstract graphs. In this paper, we advocate the study of using ML for optimization problems in the *geometric setting* where (graph) optimization problems are induced by points in a fixed dimensional Euclidean space $\mathbb{R}^d$. This is a rather common scenario in practice, such as solving TSP in road networks spanned by cities in $\mathbb{R}^2$, or solving maximum independent set in a communication network spanned by sensor nodes in $\mathbb{R}^2/\mathbb{R}^3$ (i.e, the unit-ball model that we will introduce in Section 2.1). Such graphs can also be the result of an embedding of an input arbitrary graph into a certain latent space. At the same time, the geometric setting brings special structures to the problem at hand, which an algorithm and also ML can then leverage.

In particular, using the maximum independent set (MIS) problem as an example, we first propose what we call *the Baker-paradigm* in Section 2, which is an approximation framework for geometric optimization problem inspired by Baker's work in [28]. We show that the Baker-paradigm gives a bi-criteria approximation for the MIS in the Euclidean setting (Theorem 2.1). The running time is only *linear* in the size of input point set, but *exponential* in terms of the parameters. This framework is general and can be extended to several other geometric optimization problems (Section 2.3).

A key advantage of our Baker-paradigm is that it decomposes the problem into (at most a linear number of) small sub-problems of fixed size (independent of size of input graphs). For the family of such fixed-size sub-problems, we can now design neural networks with universal approximation guarantees to solve them. Using such a neural network to replace (Step-2) of our Baker-paradigm,

we then obtain a mixed algorithmic-ML framework, which we refer to as NN-Baker, that has the capacity to produce a bi-criteria approximation of MIS within *any* constant factor in near linear time (i.e, a bi-criteria PTAS); see Section 3.1 and Theorem 3.2. Note that while Theorem 2.1 already gives a near-linear time bi-criteria PTAS for MIS, the constant involved in the time complexity is **exponential** in the approximation parameters, making it inefficient in practice. In contrast, the NN-Baker has a constant that is only **polynomial** in approximation parameters, and is very efficient as we show in Section 4.

In Section 3.2, we provide two specific instantiations of the NN component for (Step-2) of the Baker-paradigm: based on CNN and GNN respectively. We present a range of experimental results in Section 4 to show the effectiveness of both the CNN-Baker and GNN-Baker frameworks. Note that our NN-Baker can be used together with other SOA NN framework to solve combinatorial optimization problems and to further improve them (sometimes significantly). For example, we deploy different SOA GNNs for graph optimization problems to instantiate (Step-2) in NN-Baker, including TGS of [12] in the supervised setting, LwD of [16] in the reinforcement learning setting, as well as Erdős-GNN [15] in the unsupervised setting. We show that as the problem size increases, the performance of each original GNN decreases (the GNN is always trained and tested on problems of similar sizes). However, using GNN-Baker significantly improves the performance of the original GNN as the problem size increases – This is partly because that independent of the problem size, in (Step 2) our GNN-Baker only needs to train and test the GNN component on a small graph (of bounded size). Thus the trained GNN can adapt to the problem structure much better and require much fewer training samples.

Our NN-Baker is, to our best knowledge, the first (bi-criteria) PTAS for a combinatorial problem for an ML-based approach (in terms of expressiveness). The recent line of work of using a ML component (e.g a GNN trained by imitation learning) to make branching decisions within the branch-and-bound algorithmic framework [18, 20] may solve the exact problem *given enough running time*. However, the number of times the algorithm calls the NN component may be exponential in the input size. Our NN-Baker framework instead calls the neural network involved only linear time. Our approach can open new directions to design NN-infused algorithmic frameworks with theoretical guarantees.

1.1 More on related work

The idea of using neural networks to tackle optimization problems traces back to the 1980's. One of the most important frameworks in this direction is the Hopfield Neural Network (HNN) [29, 30]. In particular, the HNN is a feedback neural network with pre-specified weights (whose assignments depend on the optimization problem at hand), which encodes a dynamic system whose associated energy function characterize the optimization problem to be solved. To use it to solve an optimization problem, one starts with an initial state, and iterates till convergence.

As branch-and-bound (B&B) has been proved to be a powerful framework in solving optimization problems, especially in MILP (mixed integer-linear programing) problems, researchers proposed different machine learning algorithms to boost B&B. [17] provided a list of features of variables and designed a learning-to-rank model on selecting branching variables. [18, 20, 21] developed GNN approaches to learn the policy of choosing branching variables after formulating MILP problems as graphs by imitation learning or reinforcement learning. Besides MILP problems, GNNs are also applied on graph combinatorial optimization problems. [9] encodes the input graphs as sequences and takes an attention RNN to process the sequences. It can be used to search convex hull or solve problems like TSP. [10, 11, 31, 32, 16] takes reinforcement learning on graphs to solve routing problems like TSP, and other problems like maximum independent set. [12] solves graph theory problems by supervised learning setup after solving a set of cases as training set by existing solvers, while [15] introduces unsupervised approaches by designing loss function and training setup based on objective functions and variables constraints. In addition, there are works [13, 33, 34] that study the power of GNN on solving different kinds of combinatorial optimization problems.

2 The Baker-paradigm

We now propose a framework to obtain approximation algorithms for certain geometric optimization problems based on the work of Baker [28]. We will show in the next section how neural networks can be used to obtain efficient algorithms within this framework. We begin with some definitions.

Figure 1: Illustration of Baker-paradigm in 2D. First we put a randomly shifted grid on input points X. Consider a cell C, empty dots close to boundary are X'_C. We then snap points in $X_\mathsf{C}/X'_\mathsf{C}$ into pixels in a second level grid; and those dark (non-empty) pixels form $\widehat{X}_\mathsf{C}$. The MIS $\widehat{Y}_\mathsf{C}$ (bigger orange nodes) is then computed on the graph $G_{\widehat{X}_\mathsf{C}}$ spanned by dark pixels $\widehat{X}_\mathsf{C}$; note that for clarity of illustration, in the 4-th picture we use the center of each pixel to represent this pixel (instead of its bottom-left corner). The solution $\widehat{Y}_\mathsf{C}$ is then converted to a MIS $Y_\mathsf{C} \subseteq X_\mathsf{C}$. In (Step 3), the union of all Y_C for all cells is returned as the final MIS.

2.1 Preliminaries

We consider the geometric setting: i.e., combinatorial optimization problems on geometric intersection graphs. We present our methods for the case when the input is a **unit-ball graph**, which is the intersection graph of unit balls in $\mathbb{R}^d$. Specifically, graph nodes correspond to a set of balls of unit radius in $\mathbb{R}^d$, and two nodes are connected by an edge iff the two balls intersect. Our approach can be extended to intersection graphs of several other geometric objects such as unit hypercubes, ellipsoids of bounded aspect ratio, and so on. For the sake of succinctness, we focus on the case of unit balls.

Approximations and bi-criteria relaxations. The algorithms we will develop are bi-criteria approximations. The precise definition of a bi-criteria optimization problem depends on the space of feasible solutions. For concreteness, let us focus on the *d-dimensional Maximum Independent Set of Unit Balls problem* (denoted by d-**MIS**), for some fixed dimension $d \in \mathbb{N}$: The input to the d-MIS problem is a set of points $X \subset \mathbb{R}^d$, which corresponds to the set of centers of unit balls. Let $G_X = (X, E)$ denote the intersection graph spanned by points in X, where $(x, x') \in E$ if the unit balls $\mathsf{ball}(x, 1)$ and $\mathsf{ball}(x', 1)$ intersect (meaning that $\|x - x'\| \le 2$). The goal is to find the maximum independent set of G_X, which is equivalent to finding some maximum cardinality subset of disjoint balls centered at X. Let $\mathsf{OPT}(X)$ denote the size of a maximum independent set for G_X. For any $\alpha > 0$, an algorithm is an α-*approximation* for d-MIS if on any input $X \subset \mathbb{R}^d$, it outputs some independent set $Y \subseteq X$, with $\mathsf{OPT}(X)/\alpha \le Y \le \mathsf{OPT}(X)$.

The bi-criteria version of the problem is defined as follows. Let $\varepsilon > 0$. We say that some $Y \subseteq X$ is $(1 + \varepsilon)$-*independent* if the balls of radius $1/(1 + \varepsilon)$ centered at the points in Y are disjoint; that is, for all $p, q \in Y$, we have $\|p - q\|_2 > 2/(1 + \varepsilon)$. We denote the size of the maximum $(1 + \varepsilon)$-independent subset of X by $\mathsf{OPT}_{1+\varepsilon}(X)$. For any $\alpha \ge 1, \beta \ge 1$, We say that an algorithm is (α, β)-*bi-criteria approximation* if on any input $X \subset \mathbb{R}^d$, outputs some β-independent set $Y \subseteq X$, with $\mathsf{OPT}(X)/\alpha \le |Y| \le \mathsf{OPT}_\beta(X)$.

Randomization. The algorithms we present for d-MIS are randomized, and thus the size of the output is a random variable. We use the following standard extensions of the above definitions in this setting. We say that a randomized algorithm is α-approximation in expectation if on any input X it outputs a solution Y with $\mathsf{OPT}(X)/\alpha \le \mathbf{E}[|Y|] \le \mathsf{OPT}(X)$. We say that a randomized algorithm is (α, β)-bi-criteria approximation in expectation if on any input X it outputs a solution Y with $\mathsf{OPT}(X)/\alpha \le \mathbf{E}[|Y|] \le \mathsf{OPT}_\beta(X)$.

2.2 Baker's paradigm for d-MIS

In this section, we describe our Baker-paradigm to obtain an approximation algorithm for d-MIS. We will later see that the same method can be extended to several other optimization problems on geometric intersection graphs. Let $\varepsilon > 0$ be arbitrarily small but fixed. The algorithm proceeds in the following steps: See Figure 1 for an illustration.

178 **Algorithm Baker-**MIS: The input is a set of points $X \subset \mathbb{R}^d$, with $|X| = n$, where each point in X
179 is the center of a unit ball. The algorithm has three steps.

180 **Step 1: The randomly shifted grid.** Let Γ be an axis-parallel hyper-grid, where each cell is a d-D
181   axis-parallel hypercube of side-length $r = \frac{2d}{\varepsilon}$. Specifically, let $\Gamma = \bigcup_{i=1}^{d} \bigcup_{j \in \mathbb{Z}} \{h_i + j\frac{2d}{\varepsilon}e_i\}$,
182   where $e_1, \ldots, e_d$ is the standard orthonormal basis, and for $i \in [1, d]$, h_i is the $(d\text{-}1)$-D
183   hyperplane that passes through the origin and is orthogonal to e_i. Pick $\tau \in [0, 2d/\varepsilon)^d$
184   uniformly at random. Let $\Gamma + \tau$ denote the grid obtained by shifting Γ by the vector τ.

185 **Step 2: Bi-criteria solution for the problem locally on each cell.** Now given a cell C of $\Gamma + \tau$,
186   let $P_\mathsf{C} = P \cap \mathsf{C}$ denote the restriction of set P within C. Let X' be the set of centers of the
187   unit balls in X that intersect the shifted grid $\Gamma + \tau$ (i.e., these are points within distance-1 to
188   the hyperplanes (or gridlines for the 2D case) in the grid). Let $\delta > 0$, and set $\delta' = \delta/\sqrt{d}$.
189   We partition **each cell** C of $\Gamma + \tau$ to a d-dimensional grid of pixels, where each pixel is a
190   d-dimensional hypercube of side length δ'. We snap each point in $X \setminus X'$ to the corner
191   of the pixel containing it that is closest to the origin, thus obtaining the set $\widehat{X}$, ignoring
192   multiplicities; that is

$$\widehat{X} = \bigcup_{(p_1, \ldots, p_d) \in X \setminus X'} \{(\delta'\lfloor\frac{p_1}{\delta'}\rfloor, \ldots, \delta'\lfloor\frac{p_d}{\delta'}\rfloor)\}.$$

193   Now for each cell C of $\Gamma + \tau$, $\widehat{X}_\mathsf{C}$ (the restriction of $\widehat{X}$ to C) consists of the bottom-left
194   corners of those pixels containing some points in $X_\mathsf{C} \setminus X'_\mathsf{C}$. Let $G_{\widehat{X}_\mathsf{C}}$ be the intersection
195   graph of the unit balls with centers in $\widehat{X}_\mathsf{C}$. Note that the size of $\widehat{X}_\mathsf{C}$ is at most $(\frac{2d}{\varepsilon\delta'})^d$, and
196   thus the graph $G_{\widehat{X}_\mathsf{C}}$ is of bounded size. Furthermore, note that any independent set of $G_{\widehat{X}_\mathsf{C}}$
197   can be of size at most $s = V_d(\frac{2d}{\varepsilon})^d$ (due to a simple packing argument), where V_d denotes
198   the volume of the d-dimensional unit ball. We can then compute the maximum independent
199   set $\widehat{Y}_\mathsf{C} \subseteq \widehat{X}_\mathsf{C}$ in $G_{\widehat{X}_\mathsf{C}}$ by a brute-force enumeration of all subsets of $\widehat{X}_\mathsf{C}$ of cardinality at
200   most s, and returning the maximum cardinality subset that is independent in $G_{\widehat{X}_\mathsf{C}}$. Finally,
201   we compute $Y_\mathsf{C} \subseteq X_\mathsf{C}$ by mapping each point $\widehat{p} \in \widehat{Y}_\mathsf{C}$ to an arbitrary point $p \in X_\mathsf{C}$ that lies
202   in the pixel that $\widehat{p}$ represents.

203 **Step 3: The final solution** is $Y = \bigcup_\mathsf{C} Y_\mathsf{C}$, the union of MIS returned within all non-empty cells.

204 The proof of our first main theorem can be found in the Supplement.

205 **Theorem 2.1.** *Let $\varepsilon, \delta > 0$. The algorithm Baker-MIS is a $(1 + \varepsilon, 1 + \delta)$-bi-criteria approximation*
206 *in expectation for MIS. On input a set of size n, the algorithm runs in time $(1/(\varepsilon\delta))^{(d/\varepsilon)^{O(d)}} n$.*

207 Recall that our algorithm removes those points X' within distance 1 to the grid. Intuitively, we need
208 randomly shifted grid so that this X' does not contain too many points from an optimal maximum
209 independent set in expectation. Note that in practice, we can further improve the quality of the output:
210 Specifically, currently, all points within distance 1 to the shifted grid $\Gamma + \tau$ (i.e, $X' \subseteq X$) are removed.
211 The reason is to ensure that solutions (max-independent sets) of neighboring cells do not conflict
212 each other. We can add some of those points from X' back to the solution Y as long as they do not
213 cause conflict (i.e, within distance 2) to any points in Y. We can do so in a greedy manner in practice
214 to obtain an even better solution. Our theorem above holds for this greedily improved solution as it
215 remains an independent set and is a superset of Y.

216 **Removing the Bi-Criteria Condition.** We remark that we can in fact modify our algorithm Baker-
217 MIS to obtain a $(1 + \varepsilon)$-approximation for MIS (instead of a bi-criteria approximation). Detials ae
218 in the Supplement. As shown in the following theorem, the price to pay is that the dependency of
219 time complexity on n increases from previous n (i.e, linear) to $n^{(1/\varepsilon)^{O(d)}}$, which is significant.

220 **Theorem 2.2.** *We can modify Baker-paradigm to provide a $(1 + \varepsilon)$-approximation in expectation for*
221 *MIS. On input a set of size n, this modified algorithm runs in time $n^{(1/\varepsilon)^{O(d)}}$.*

222 2.3 Other graph optimization problems

223 We now briefly discuss how the above general framework can be extended to other problems on unit
224 ball graphs, with only minor modifications. We describe some representative such problems.

Minimum vertex cover. In the Minimum Vertex Cover (MVC) problem, we are given a graph G and the goal is to find a minimum cardinality set $U \subseteq V(G)$, such that all edges in G have at least one endpoint in U. In the case were G is a unit ball graph in $\mathbb{R}^d$, this problem can be solved by modifying the Baker paradigm as follows. In Step 2, we enlarge each cell C of $\Gamma + \tau$ by increasing its side length to $2 + 2d/\varepsilon$. Thus, any two adjacent cells have an intersection of width 2, and some points in X may fall in multiple cells. By the linearity of expectation, it follows that the expected number of points in any optimal solution that fall in multiple cells (counting multiplicities), is at most and $\varepsilon|\mathsf{OPT}(X)|$. Therefore, by solving the problem independently on each cell and taking the union of all the solutions we obtain a $(1 + \varepsilon)$-approximate solution for the initial problem X. Discretizing each cell into further pixels gives rise to a more efficient, but bi-criteria approximation.

Maximum Acyclic Subgraph, Planar Subgraph, and $\mathcal{F}$-Minor Free Subgraph. In the Maximum Acyclic Subgraph problem we are given a graph G and the goal is to compute a subgraph of G with a maximum number of vertices that is acyclic. It follows by the linearity of expectation, that the expected number of balls in any optimal solution that intersect the randomly shifted grid is at most $\varepsilon|\mathsf{OPT}(X)|$. Thus, solving the problem on each cell and taking the union of all the acyclic subgraphs found, results in a $(1 + \varepsilon)$-approximate optimal acyclic subgraph of the input. (Similar to MVC, discretizing each cell into further pixels gives rise to a more efficient, but bi-criteria approximation.) The exact same argument works also for the Maximum Planar Subgraph problem, where the goal is to find a subgraph with a maximum number of vertices that is planar. Finally, the same argument extends to the case of the more general Maximum $\mathcal{F}$-Minor Free Subgraph problem, where the goal is to find a subgraph with a maximum number of vertices that does not contain as a minor any of the graphs in a fixed family $\mathcal{F}$. We note that this problem generalizes the Maximum Acyclic Subgraph problem (when $\mathcal{F}$ contains the triangle graph) and the Maximum Planar Subgraph problem (when $\mathcal{F}$ contains K_5 and $K_{3,3}$).

3 A NN-Baker framework

3.1 Infusing neural network inside the Baker-paradigm

Instead of solving (Step 2) of Baker-paradigm in a brute-force manner, we can replace it by a neural network, and we refer to the resulting generic paradigm as *NN-Baker*. Specifically, we replace Step 2 of algorithm Baker-MIS, with the following:

Step 2'. We follow the same notations as in Step 2 of algorithm Baker-MIS. For each cell C of the grid $\Gamma + \tau$, we proceed as follows. Recall $\widehat{X}_{\mathsf{C}}$ is a set of corners of all non-empty pixels (i.e, containing some point from $X \setminus X'$) in C. Let W_{C} be the set of all pixels in C, and let $\mathcal{P}_{\mathsf{C}}$ be the powerset of W_{C}. Let $f_{\mathrm{MIS}} : \mathcal{P}_{\mathsf{C}} \to \mathcal{P}_{\mathsf{C}}$ be such that for all $Z \in \mathcal{P}_{\mathsf{C}}$, $f_{\mathrm{MIS}}(Z)$ is some optimal solution to the MIS problem on input Z; that is, f_{MIS} maps an instance to an optimal MIS solution. Since every point in $X_{\mathsf{C}} \setminus X'_{\mathsf{C}}$ is at distance at most δ from some point in $\widehat{X}_{\mathsf{C}}$, it follows that $f_{\mathrm{MIS}}(\widehat{X}_{\mathsf{C}})$ is a $(1, 1 + \delta)$-bi-criteria solution for the set of points in $X_{\mathsf{C}} \setminus X'_{\mathsf{C}}$. We can view f_{MIS} as a mapping between indicator vectors of subsets of W_{C}; i.e. $f_{\mathrm{MIS}} : \{0,1\}^k \to \{0,1\}^k$, where $k = |\mathcal{P}_{\mathsf{C}}| = 2^{(2d/(\varepsilon\delta))^d}$. Let $\widehat{f}_{\mathrm{MIS}} : [0,1]^k \to [0,1]^k$ be any continuous extension of f_{MIS}. We then approximate $\widehat{f}_{\mathrm{MIS}}$ by a function $g_{\mathcal{N}} : [0,1]^k \to [0,1]^k$ as computed by a neural network $\mathcal{N}$. We round coordinate-wise the output of g_{MIS} to a vector in $\{0,1\}^k$, by setting every value greater than $1/2$ to 1, and all other values to 0. We thus obtain the indicator vector of some $Y_{\mathsf{C}} \subset W_{\mathsf{C}}$. Alternatively, we can produce a discrete solution by the following greedy strategy: We sort the points in W_{C} in non-increasing order of their values in the vector $g_{\mathcal{N}}(\widehat{X}_{\mathsf{C}})$, and we take $\widehat{Y}_{\mathsf{C}}$ to be a maximal prefix of this sorted order that forms an $(1 + \delta)$-independent set in G_{C}. Finally, we compute $Y_{\mathsf{C}} \subseteq X_{\mathsf{C}}$ by mapping each point $\widehat{p} \in \widehat{Y}_{\mathsf{C}}$ to any point $p \in X_{\mathsf{C}}$ within the pixel represented by $\widehat{p}$.

Universal-Baker. We now give a theoretical instantiation of NN-Baker using the neural network obtained by the following universal approximation result.

Theorem 3.1 (Cybenko [22])**.** *Let σ be any continuous sigmoidal function. Let $m \in \mathbb{N}$, and let $\mathcal{C}$ be a compact subset of $\mathbb{R}^m$. Let $f : \mathcal{C} \to \mathbb{R}$ be a continuous function, and $\gamma > 0$. Then, there exists*

Figure 2: Given the set of points $X_\mathsf{C} \setminus X'_\mathsf{C}$ contained in cell C, the top row shows the processing of it by a CNN component as in CNN-Baker, while the bottom row shows it for a GNN component as in GNN-Baker.

$N \in \mathbb{N}$, $a_1, \ldots, a_N \in \mathbb{R}$, $y_1, \ldots, y_N \in \mathbb{R}^m$, and $\theta_1, \ldots, \theta_N \in \mathbb{R}$, such that the function $g : \mathcal{C} \to \mathbb{R}$, with $g(x) = \sum_{i=1}^N a_i \sigma(y_i^T x + \theta_i)$, satisfies $\sup_{x \in \mathcal{C}} |g(x) - f(x)| < \gamma$.

Using the neural network given by the above result, we can then argue that our NN-Baker has the capacity (expressiveness) of solving MIS problem (for unit-ball graphs) in a bi-criteria approximation. The simple proof of this theorem can be found in the Supplement.

Theorem 3.2. *Let $\varepsilon, \delta > 0$. There exists $N = N(\varepsilon, \delta, d)$, such that the following holds. Suppose that the function $g_{\mathcal{N}^*}$ in Step 2' of the NN-Baker framework is computed by the neural network $\mathcal{N}^*$ given by Theorem 3.1, with a single hidden layer of size N. Then, the resulting algorithm is a $(1 + \varepsilon, 1 + \delta)$-bi-criteria approximation in expectation for d-MIS, and it will call this (same) neural network $O(n)$ times where n is the number of points generating the input graph.*

Remark 3.1. *A similar statement to Theorem 3.2 holds for the Vertex Cover problem, yielding a $(1 + \varepsilon, 1 + \delta)$-bi-criteria approximation using the modifications discussed in Section 2.3.*

3.2 Instantiation of NN-Baker

Above we introduce a generic NN-Baker framework and a theoretical instantiation. We now provide two specific practical instantiations of this framework: a CNN-Baker and a GNN-Baker where (Step 2) in Baker-paradigm is replaced by a CNN or by a specific GNN. We provide details below. Specifically, recall that the input is a set of points $X \subset \mathbb{R}^d$, and for a randomly shifted grid $\Gamma + \tau$, let us focus on a specific grid cell $\mathsf{C} \in \Gamma + \tau$. Recall that in NN-Baker, given C and $\widehat{X}_\mathsf{C}$, we will use a neural network to compute a subset of $\widehat{Y}_\mathsf{C}$ which ideally approximates a maximum independent set of the (unit-ball) geometric intersection graph $G_{\widehat{X}_\mathsf{C}}$ spanned by $\widehat{X}_\mathsf{C}$. The set $\widehat{Y}_\mathsf{C}$ (of pixels) is further relaxed to a subset $Y_\mathsf{C} \subset X_\mathsf{C}$ as an independent set solution within cell C.

CNN-Baker. We can view the set of pixels in a cell as an image of size $\beta^d = \beta \times \beta \ldots \beta$ where $\beta = \Theta(\frac{1}{\varepsilon \delta})$. Specifically, given a grid cell C and a subset of pixels Z, we define the I_Z over β^d such that $I_Z[\mathsf{p}] = 1$ if $\mathsf{p} \in Z$ and $I_Z[\mathsf{p}] = 0$ otherwise. We call such an image *an induced image by* C, and denote the space of images of size by $SpIm$. Now, in (Step 2') of NN-Baker, we are given a subset pixels $(Z =)\widehat{X}_\mathsf{C}$ of a cell C, and aim to compute a subset $\widehat{Y}_\mathsf{C} \subseteq \widehat{X}_\mathsf{C}$ that forms an independent set for the unit-ball graph spanned by $Z = \widehat{X}_\mathsf{C}$. Our CNN-Baker uses a CNN architecture $\mathcal{N}_C$ to compute a map $g_{\mathcal{N}_C} : SpIm \to SpIm$, which takes as input $I_{\widehat{X}_\mathsf{C}}$ and outputs $I_{\widehat{Y}_\mathsf{C}}$. Since the input and output are both images of the same size, this problem can be also viewed as an image segmentation problem, and thus we can use a UNet architecture for the map $\mathcal{N}_C$. More specifically, the input is a binary image $I_{\widehat{X}_\mathsf{C}}$, and the output is a grayscaled image I' where the value at each pixel, $I'[i] \in [0, 1]$, indicates the likelihood that this pixel belongs to a maximum independent set in the geometric intersection graph $G_{\widehat{X}_\mathsf{C}}$. To output a set of pixels as an independent set, we then perform a greedy approach as described

Figure 3: Results of Erdos-GNN, TGS and LwD on MIS problems with different sizes of graphs in 2D setting. We report the ratio to ground truth computed by KaMIS.

in (Step 2'): We sort all pixels corresponding to points in $Z = \widehat{X}_{\mathsf{C}}$ in decreasing order of their pixel values, and assume $Z = \{z_1, \ldots, z_\ell\}$ is this sorted list. We then inspect them one-by-one in order. At the beginning, initialize an output set Z' to be empty. Then in the i-th iteration, if z_i is independent to all points in Z' (i.e, it is more than 2 away for all points in Z'), add z_i to Z'; and otherwise, do nothing. In the end after ℓ iterations, we obtain a set of $Z' \subseteq Z(= \widehat{X}_{\mathsf{C}})$ pixels which is guaranteed to be an independent set for graph $G_{\widehat{X}_{\mathsf{C}}}$. Set $\widehat{Y}_{\mathsf{C}} = Z'$. We then relax $\widehat{Y}_{\mathsf{C}}$ to a set $\widehat{Y}'_{\mathsf{C}} \subset X_{\mathsf{C}} \setminus X'_{\mathsf{C}}$ as before, and return it as the independent set for this cell.

GNN-Baker. For GNN-Baker, we instead directly use the unit-ball graph $G_{\widehat{X}_{\mathsf{C}}}$ as input, with the initial node feature $\mu^0(v)$. At the last L-th layer, the node feature $\mu^L(v)$ gives the likelihood that v is in the maximum independent set. We then retrieve an independent set $\widehat{Y}_{\mathsf{C}}$ (and Y_{C}) by the same greedy approach as for the case of CNN-Baker. For the specific choice of the GNN architecture, we can use any of the existing models, such as GCN [35], GraphSAGE [36], GIN [37], GAT [38], and VV$_C$-GNN [13]. In our later experiments, we will use TGS [12] and LwD [16] in our GNN-Baker framework, as these are state-of-the-art (SOA) approaches specifically designed for graph combinatorial problems. (Our experiments show that using a general purpose GNN has much worse performance than TGS and LwD.) In particular, TGS, a supervised learning approach, takes GCN to process reduced graphs and use a tree search approach to label nodes whether they are in an independent set or not. LwD is reinforcement-learning based, and designs a policy network and value network on each MIS problem state with GraphSAGE architecture. We will also use the Erdős-GNN [15], designed for optimization problems in the *unsupervised setting*. Erdős-GNN takes multiple GIN layers followed by a GAT layer to learn graphs' distribution. It designs a differentiable loss function based on expectations of optimization problems objective functions and a probabilistic penalty function.

4   Experimental results

We present results for d-MIS here. More results, including for minimum vertex cover (MVS), can be found in the Supplement. We consider 5 families of unit-ball graphs: (2D-dense) consists of a set of graphs, each with points distributed uniformly on a 2D rectangular region with around 40K – 50K points. (2D-sparse) consists of a set of graphs, each with 40k – 50k points distributed uniformly on a 2D rectangular region four times larger than the dense region . (2D-Gaussian) consists of graphs each spanned by points sampled from a Gaussian-mixture distribution with 40K – 50K points over the same region size as the dense region. (3D) consists of graphs each spanned by points sampled from a 3D region. (Torus-4D) consists of graphs each spanned by points sampled from a torus embedded in $\mathbb{R}^4$ (see Supplement for details). To report accuracy, we use KaMIS [39] to compute ground truth solutions and report the average ratio of MIS obtained over true MIS size as metric for accuracy (so 1.0 means that it always computes the optimal MIS).

Before we show results of CNN-Baker and GNN-Baker, we first show how the SOA GNN-based approaches, TGS [12], LwD [16] and Erdős-GNN [15], all of which are specifically designed for graph optimization problems (see discussions in Section 3.2), perform as the size of graph increases. Here for each target size, 1000 graphs spanned by points sampled from the same dense distribution in 2D are used for training, then tested on 100 graphs of roughly the same target size. As shown in Figure 3, the accuracy decreases as the size of (geometric) graphs increase.

Table 1: The ratio of MIS results from different GNNs and GNN-Baker approaches to groud truth.

	UNetBaker	Erdős	ErdősBaker	TGS	TGSBaker	LwD	LwDBaker
2D-dense	0.915	0.834	0.923	0.915	0.936	0.917	0.955
2D-sparse	0.919	0.822	0.917	0.909	0.931	0.908	0.926
2DGaussian	0.917	0.769	0.848	0.905	0.927	0.911	0.925
3D	-	0.856	0.930	0.924	0.948	0.902	0.954
Torus-4D	-	0.812	0.926	0.923	0.937	0.910	0.937

NN-Baker setup. For each of the five setup, we train on 1000 graphs and test on 200 graphs each containing between 40k - 50k points. However, inside our NN-Baker framework, the input domain is partitioned into cells of side-length 12.8, and each cell is further partitioned into 128×128 pixels (each with side-length $= 0.1$). In other words, each cell can be viewed a 128x128 image. This means that the training set for the NN component involved contains only small graphs restricted to such cells. In the end, each training graph consists around 400 points for the cases of (2D-dense), (3D) and(Torus-4D), and around 100 to 125 points for the case of (2D-sparse). The size of each small training graph for Gaussian case is non-uniform. For CNN-Baker, we apply a UNet which reduces the input 128x128 image to an 8x8 image after 4 down-scaling layers, each of which consists of two convolutional layers, a dropout layer and a max pooling layer. From the 8x8 image, there are then 4 upsampling/concatenation layers to bring the size back to 128x128. This model is denoted by UNet-Baker in Table 1. For GNN-Baker, as mentioned in Section 3.2, we test TGS-Baker, LwD-Baker, and Erdős-Baker. For each individual neural network involved, we use the same training setup and hyperparameters as those in their official implementations. For LwD and Erdős-GNN, we use node degree as initial node features, while for TGS, we simply use a constant vector. The accuracy of these different methods over the 5 families of graphs are shown in Table 1. The number of parameters for these GNN-Bakers range from 50K to 600K, while the UNet-Baker uses around 80M parameters.

As shown in Table 1, using Baker framework consistently improve the performance of these SOA neural networks on geometric MIS problem. The improvement over the unsupervised Erdős-GNN (i.e, Erdős-Baker vs. Erdős-GNN) is particularly significant. We remark that we have also experimented with using a simple multi-layer fully connected NN (i.e., a multi-layer version of the NN used in Theorem 3.2) to instantiate our NN-Baker, and the performance (under similar number of parameters as our UNet-Baker) is much worse, between 70%-80%. We can also use NN-Baker trained on one type of graphs (e.g, 2D-dense) but apply it to graphs from the other families to study the generalization of the resulting framework – we observe that the accuracy decreases but still improves over the non-Baker version. See the Supplement for these more results (including variance of these accuracy), as well as the performance of NN-Baker for minimum vertex cover problem (where our NN-Baker framework receives similar improvement in performance).

5 Concluding remarks

The advancement in neural network architectures, and their power in potentially better adapting to problem structure and input distribution in a data-driven manner, have brought new ways to tackle traditionally challenging tasks, such as graph optimization problems. In this paper, we advocate two points of view: (1) Problems in geometric settings can provide structures that both algorithms and neural networks can leverage; for example, they can help to decompose problems into local versions of bounded size and thus lead to more effective NN components. (2) Infusing NN + learning into an algorithmic paradigm can lead to a more powerful framework for hard problems, potentially with theoretical guarantees. While the latter is a view that has already attracted momentum in recent years, our work provides new perspectives (e.g, the decomposition into bounded-size sub-problems) together with some theoretical guarantees, and we show that the resulting method is indeed more powerful empirically too. The main limitation of our present algorithms is that they currently apply to only geometric intersection graphs. Nevertheless, we believe that such ideas go beyond the geometric setting which we hope to explore in the future – indeed, the algorithms and theoretical computer science community has developed many beautiful algorithmic paradigms that may be suitable to be infused with NN+ML ideas. Finally, to our best knowledge, this work does not have direct negative societal impacts.

References

[1] Johan Håstad. Clique is hard to approximate within $n^{1-\varepsilon}$. *Acta Mathematica*, 182(1):105–142, 1999.

[2] Anna R Karlin, Nathan Klein, and Shayan Oveis Gharan. A (slightly) improved approximation algorithm for metric tsp. *arXiv preprint arXiv:2007.01409*, 2020.

[3] Sanjeev Arora. Polynomial time approximation schemes for euclidean traveling salesman and other geometric problems. *Journal of the ACM (JACM)*, 45(5):753–782, 1998.

[4] Robert J Fowler, Michael S Paterson, and Steven L Tanimoto. Optimal packing and covering in the plane are np-complete. *Information processing letters*, 12(3):133–137, 1981.

[5] Timothy M Chan. Polynomial-time approximation schemes for packing and piercing fat objects. *Journal of Algorithms*, 46(2):178–189, 2003.

[6] Thomas Erlebach, Klaus Jansen, and Eike Seidel. Polynomial-time approximation schemes for geometric intersection graphs. *SIAM Journal on Computing*, 34(6):1302–1323, 2005.

[7] Timothy M Chan and Sariel Har-Peled. Approximation algorithms for maximum independent set of pseudo-disks. *Discrete & Computational Geometry*, 48(2):373–392, 2012.

[8] Yoshua Bengio, Andrea Lodi, and Antoine Prouvost. Machine learning for combinatorial optimization: a methodological tour d'horizon. *European Journal of Operational Research*, 2020.

[9] Oriol Vinyals, Meire Fortunato, and Navdeep Jaitly. Pointer networks. In *Proceedings of the 28th International Conference on Neural Information Processing Systems-Volume 2*, pages 2692–2700, 2015.

[10] Irwan Bello, Hieu Pham, Quoc V. Le, Mohammad Norouzi, and Samy Bengio. Neural combinatorial optimization with reinforcement learning. *5th International conference on Learning Representations Workshop Track*, 2017.

[11] Hanjun Dai, Elias B Khalil, Yuyu Zhang, Bistra Dilkina, and Le Song. Learning combinatorial optimization algorithms over graphs. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, pages 6351–6361, 2017.

[12] Zhuwen Li, Qifeng Chen, and Vladlen Koltun. Combinatorial optimization with graph convolutional networks and guided tree search. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, pages 537–546, 2018.

[13] Ryoma Sato, Makoto Yamada, and Hisashi Kashima. Approximation ratios of graph neural networks for combinatorial problems. *Proceedings of the 33rd International Conference on neural Information Processing Systems*, 2019.

[14] Thomas Barrett, William Clements, Jakob Foerster, and Alex Lvovsky. Exploratory combinatorial optimization with reinforcement learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 3243–3250, 2020.

[15] Nikolaos Karalias and Andreas Loukas. Erdos goes neural: an unsupervised learning framework for combinatorial optimization on graphs. In *Proceedings of the 34th International Conference on Neural Information Processing Systems*, 2020.

[16] Sungsoo Ahn, Younggyo Seo, and Jinwoo Shin. Learning what to defer for maximum independent sets. In *International Conference on Machine Learning*, pages 134–144. PMLR, 2020.

[17] Elias Khalil, Pierre Le Bodic, Le Song, George Nemhauser, and Bistra Dilkina. Learning to branch in mixed integer programming. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 30, 2016.

[18] Maxime Gasse, Didier Chételat, Nicola Ferroni, Laurent Charlin, and Andrea Lodi. Exact combinatorial optimization with graph convolutional neural networks. In *Advances in Neural Information Processing Systems 32*, 2019.

[19] Aaron Ferber, Bryan Wilder, Bistra Dilkina, and Milind Tambe. Mipaal: Mixed integer program as a layer. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 1504–1511, 2020.

[20] Prateek Gupta, Maxime Gasse, Elias Khalil, Pawan Mudigonda, Andrea Lodi, and Yoshua Bengio. Hybrid models for learning to branch. *Advances in Neural Information Processing Systems*, 33, 2020.

[21] Vinod Nair, Sergey Bartunov, Felix Gimeno, Ingrid von Glehn, Pawel Lichocki, Ivan Lobov, Brendan O'Donoghue, Nicolas Sonnerat, Christian Tjandraatmadja, Pengming Wang, et al. Solving mixed integer programs using neural networks. *arXiv preprint arXiv:2012.13349*, 2020.

[22] George Cybenko. Approximation by superpositions of a sigmoidal function. *Mathematics of control, signals and systems*, 2(4):303–314, 1989.

[23] Allan Pinkus. Approximation theory of the mlp model in neural networks. *Acta Numerica*, 8:143–195, 1999.

[24] Franco Scarselli, Marco Gori, Ah Chung Tsoi, Markus Hagenbuchner, and Gabriele Monfardini. Computational capabilities of graph neural networks. *IEEE Transactions on Neural Networks*, 20(1):81–102, 2008.

[25] Jorge Pérez, Javier Marinković, and Pablo Barceló. On the turing completeness of modern neural network architectures. In *International Conference on Learning Representations*, 2018.

[26] Dana Angluin. Local and global properties in networks of processors. In *Proceedings of the twelfth annual ACM symposium on Theory of computing*, pages 82–93, 1980.

[27] Matti Åstrand, Patrik Floréen, Valentin Polishchuk, Joel Rybicki, Jukka Suomela, and Jara Uitto. A local 2-approximation algorithm for the vertex cover problem. In *International symposium on distributed computing*, pages 191–205. Springer, 2009.

[28] Brenda S Baker. Approximation algorithms for np-complete problems on planar graphs. *Journal of the ACM (JACM)*, 41(1):153–180, 1994.

[29] John J Hopfield. Neural networks and physical systems with emergent collective computational abilities. *Proceedings of the national academy of sciences*, 79(8):2554–2558, 1982.

[30] John J Hopfield and David W Tank. "neural" computation of decisions in optimization problems. *Biological cybernetics*, 52(3):141–152, 1985.

[31] Michel Deudon, Pierre Cournut, Alexandre Lacoste, Yossiri Adulyasak, and Louis-Martin Rousseau. Learning heuristics for the tsp by policy gradient. In *International conference on the integration of constraint programming, artificial intelligence, and operations research*, pages 170–181. Springer, 2018.

[32] Marcelo Prates, Pedro HC Avelar, Henrique Lemos, Luis C Lamb, and Moshe Y Vardi. Learning to solve np-complete problems: A graph neural network for decision tsp. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 4731–4738, 2019.

[33] Keylu Xu, Jingling Li, Mozhi Zhang, Simon S Du, Ken-ichi Kawarabayashi, and Stefanie Jegelka. What can neural networks reason about? *International Conference on Learning Representations*, 2020.

[34] Andreas Loukas. What graph neural networks cannot learn: depth vs width. In *International Conference on Learning Representations*, 2019.

[35] Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *International Conference on Learning Representations*, 2017.

[36] William L Hamilton, Rex Ying, and Jure Leskovec. Inductive representation learning on large graphs. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, pages 1025–1035, 2017.

[37] Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? *International Conference on Learning Representations*, 2019.

[38] Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, and Yoshua Bengio. Graph attention networks. *International Conference on Learning Representations*, 2018.

[39] Sebastian Lamm, Peter Sanders, Christian Schulz, Darren Strash, and Renato F. Werneck. Finding near-optimal independent sets at scale. *J. Heuristics*, 23(4):207–229, 2017.