JOINT STATE-ACTION EMBEDDING FOR EFFICIENT REINFORCEMENT LEARNING

ABSTRACT

While reinforcement learning has achieved considerable successes in recent years, state-of-the-art models are often still limited by the size of state and action spaces. Model-free reinforcement learning approaches use some form of state representations and the latest work has explored embedding techniques for actions, both with the aim of achieving better generalization and applicability. However, these approaches consider only states or actions, ignoring the interaction between them when generating embedded representations. In this work, we propose a new approach for jointly embedding states and actions that combines aspects of model-free and model-based reinforcement learning, which can be applied in both discrete and continuous domains. Specifically, we use a model of the environment to obtain embeddings for states and actions and present a generic architecture that uses these to learn a policy. In this way, the embedded representations obtained via our approach enable better generalization over both states and actions by capturing similarities in the embedding spaces. Evaluations of our approach on several gaming and recommender system environments show it significantly outperforms state-of-the-art models in discrete domains with large state/action space, thus confirming the efficacy of joint embedding and its overall superior performance.

1 INTRODUCTION

Reinforcement learning (RL) has been successfully applied to a range of comparatively simple tasks, including gaming scenarios (Mnih et al., 2015). However, the application of RL in many real-world domains is often hindered by the large number of possible states and actions these settings present. For instance, resource management in computing clusters (Mao et al., 2016; Evans & Gao, 2016), portfolio management (Jiang et al., 2017), and recommender systems (Lei & Li, 2019; Liu et al., 2018) all suffer from extremely large state/action spaces, thus challenging to be tackled by RL.

In this work, we investigate efficient training of reinforcement learning agents in the presence of large state-action spaces, aiming to improve the applicability of RL to real-world domains. Previous work attempting to address this challenge has explored the idea of learning representations (embeddings) for states or actions. Specifically, for state embeddings, using machine learning to obtain meaningful features from raw state representations is a common practice in RL, e.g. through the use of convolutional neural networks for image input (Mnih et al., 2013). While for action embeddings, the most recent works by Tennenholtz & Mannor (2019) and Chandak et al. (2019) propose methods for learning embeddings for discrete actions that can be directly used with an RL agent and improve generalization over actions. However, these works consider the state representation and action representation as isolated tasks, which ignore the underlying relationships between them. In this regard, we take a different approach and propose to jointly learn embeddings for states and actions, aiming for better generalization over both states and actions in their respective embedding spaces.

To this end, we propose an architecture consisting of two models: a model of the environment that is used to generate state and action representations and a model-free RL agent that learns a policy using the embedded states and actions. By using these two models, our approach combines aspects of model-based and model-free reinforcement learning and effectively bridges the gap between both approaches. One key benefit of this approach is that state and action representations can be learned in a supervised manner, which greatly improves sampling efficiency and also potentially enables their use for transfer learning. In sum, our key contributions are:

- We formulate an embedding model for states and actions, along with an internal policy π_i that leverages the learned state/action embeddings, as well as the corresponding overall policy π_o. We show the existence of an overall policy π_o that achieves optimality in the original problem domain.

- We further prove the equivalence between updates to the internal policy π_i acting in embedding space and updates to the overall policy π_o.

- We present a supervised learning algorithm for the proposed embedding model that can be combined with any policy gradient based RL algorithms.

- We evaluate our methodology on a set of game-based tasks as well as real-world recommender systems and find that it outperforms state-of-the-art models in discrete domains.

The remainder of this paper is structured as follows: In Section 2, we provide some background on RL. We then give an overview of related work in Section 3, before presenting our proposed methodology in Section 4, which we evaluate in Section 5.

2 BACKGROUND

We consider an agent interacting with its environment over discrete time steps, where the environment is modelled as a discrete-time *Markov decision process* (MDP), defined by a tuple $(\mathcal{S}, \mathcal{A}, \mathcal{T}, \mathcal{R}, \gamma)$. Specifically, $\mathcal{S}$ and $\mathcal{A}$ are the sets of all possible states and actions, referred to as the *state space* and *action space*, respectively. In this work, we consider both discrete and continuous state and action spaces. The transition function $\mathcal{T} : \mathcal{S} \times \mathcal{A} \mapsto \mathcal{S}$ defines the probability of transitioning from one state to another, given an action. The agent receives a reward at each time step defined by $\mathcal{R} : \mathcal{S} \times \mathcal{A} \mapsto \mathbb{R}$. $\gamma \in [0, 1]$ denotes the reward discounting parameter. The state, action, and reward at time $t \in \{0, 1, 2...\}$ are denoted by the random variables S_t, A_t, and R_t.

The initial state of the environment comes from an initial state distribution d_0. Thereafter, the agent follows a policy π, defined as a conditional distribution over actions given states, i.e., $\pi(a|s) = P(A_t = a|S_t = s)$. The goal of the reinforcement learning agent is to find an optimal policy π^* that maximizes the expected sum of discounted accumulated future rewards for a given environment, i.e., $\pi^* \in \arg\max_\pi \mathbb{E}[\sum_{t=0}^\infty \gamma^t R_t|\pi]$. For any policy, we also define the state value function $v^\pi(s) = \mathbb{E}[\sum_{k=0}^\infty \gamma^k R_{t+k}|\pi, S_t = s]$ and the state-action value function $Q^\pi(s, a) = \mathbb{E}[\sum_{k=0}^\infty \gamma^k R_{t+k}|\pi, S_t = s, A_t = a]$.

3 RELATED WORK

One prominent use of embedding techniques is in natural language processing (NLP), where the context of a word is used to generate a representation, such as Word2Vec (Mikolov et al., 2013c), CBOW (Mikolov et al., 2013b), and the more complicated BERT (Devlin et al., 2019). While for the application of embeddings in reinforcement learning, Munk et al. (2016) pre-train an environment model and use it to provide state representations for an RL agent. Furthermore, de Bruin et al. (2018) investigate several additional learning objectives to learn state representations, and Francois-Lavet et al. (2019) propose the use of an environment model to generate an abstract state representation; their learned state representations are then used by a Q-learning agent. State representations are also used in RL-based NLP tasks, such as Narasimhan et al. (2015), who jointly train an LSTM-based state representation module and a DQN agent, and Ammanabrolu & Riedl (2018), who propose the use of a knowledge graph based state representation.

In addition to state representations, previous work has explored the use of additional models to learn meaningful action representations. In particular, Van Hasselt & Wiering (2009) investigate the use of a continuous actor in a policy gradient based approach to solve discrete action MDPs, where the policy is learned in continuous space and actions are discretized before execution in the environment. Dulac-Arnold et al. (2015) propose a similar methodology, where a policy is learned in continuous action embedding space and then mapped to discrete actions in the original problem domain. Both Van Hasselt & Wiering (2009) and Dulac-Arnold et al. (2015) only consider actions and assume that embeddings are known a priori. Tennenholtz & Mannor (2019) propose a methodology called Act2Vec, where they introduce an embedding model similar to the Skip-Gram model

Figure 1: (a) Overall architecture, using the state embedding function ϕ, the internal policy π_i, and the action mapping function f; (b) Embedding model used to learn state embedding function ϕ and the auxiliary action embedding function g.

(Mikolov et al., 2013a) that is trained using data from expert demonstrations and then combined with a DQN agent. One significant drawback of this approach is that information on the semantics of actions has to be injected via expert demonstration and is not learned automatically. In contrast, Chandak et al. (2019) propose a method that enables the self-supervised learning of action representations from experience collected by the RL agent, using an embedding model that resembles CBOW. The approach presented in (Chandak et al., 2019) is most closely related to our method in the way of integrating embeddings with policy gradient based RL algorithms. However, they only consider action embeddings, while we jointly embed states and actions and improve the performance significantly. As an alternative to embedding methods, Pazis & Parr (2011) and Sallans & Hinton (2004) represent actions in binary format, where they learn a value function associated with each bit, and Sharma et al. (2017) propose the use of factored actions, where actions are expressed using underlying primitive actions. Again, these three methods rely on handcrafted action decomposition.

Previous embedding approaches consider either states or actions in isolation, embedding only one of the two or using separate models for each. By contrast, in addition to capturing structure in the state or action space respectively, we leverage interdependencies between the two by jointly learning embeddings for them, and thus improve the quality of embeddings.

4 METHODOLOGY

We propose an embedding model to jointly learn state and action embeddings and present a generic framework that uses the learned embeddings in conjunction with any policy gradient algorithms.

4.1 ARCHITECTURE

Our proposed approach has three components: (i) state-action embedding model, (ii) policy gradient based RL agent that takes in the embeded states and outputs actions in action embedding space, and (iii) action mapping function that maps embedded actions to actions in the original problem domain.

We define two embedding spaces, i.e., a state embedding space $\mathcal{X} \in \mathbb{R}^m$ and an action embedding space $\mathcal{E} \in \mathbb{R}^d$; states are projected to the state embedding space via a function $\phi : \mathcal{S} \mapsto \mathcal{X}$. On the other hand, we define a function $f : \mathcal{E} \mapsto \mathcal{A}$ that maps points in the embedding space to actions in the original problem domain. With these embedding spaces, we further define an internal policy π_i that takes in the embedded state and outputs the embedded action, i.e., $\pi_i : \mathcal{X} \mapsto \mathcal{E}$. Furthermore, the mapping functions ϕ and f, together with the internal policy π_i form the overall policy $\pi_o : \mathcal{S} \mapsto \mathcal{A}$, i.e., π_o is characterized by the following three components:

$$X_t = \phi(S_t), E_t \sim \pi_i(\cdot|X_t), \text{and } A_t = f(E_t),$$

where random variables $S_t \in \mathcal{S}$, $X_t \in \mathcal{X}$, $E_t \in \mathcal{E}$, and $A_t \in \mathcal{A}$ denote the state in the original problem domain, state in the embedding domain, action in the embedding domain, and action in the original domain at time t, respectively. The overall model architecture is illustrated in Figure 1a. In Figure 1a, function ϕ is directly learned using an embedding model illustrated in Figure 1b (detailed in Section 4.3.1). However, function f is not directly part of this embedding model, but uses the obtained action embeddings to learn a mapping from $e \in \mathcal{E}$ to $a \in \mathcal{A}$ (see Section 4.3.2 for details).

For an RL problem, the ultimate goal is to optimize the policy π in the original problem domain, i.e., π in the $\mathcal{S} \times \mathcal{A}$ space. For the proposed architecture, the idea is to first establish efficient embeddings for both states and actions in $\mathcal{S}$ and $\mathcal{A}$. Then we reduce the problem of finding the optimal π^* in the original problem domain to the problem of internal policy π_i optimization that acts purely in the embedding space. However, it is still unclear how the optimization of π_i is related to π^*. In addition, the overall policy π_o relying on ϕ and f further complicates the policy learning. In this regard, we establish the relationships among π, π_o, and π_i in the next section, which is the foundation to justify the validity of leveraging joint state-action embeddings in RL.

4.2 THEORETICAL FOUNDATIONS: RELATIONSHIPS AMONG π, π_o, AND π_i

To understand the relationships among π, π_o, and π_i, we first derive how π_o is related to π, after which we prove the existence of π_o that achieves optimality in the original problem domain. For this goal, two further assumptions are required on the nature of the state embedding function ϕ and the action mapping function f.

Assumption 1. *Given an embedding E_t, A_t is deterministic and defined by a function $f : \mathcal{E} \mapsto \mathcal{A}$, i.e., there exists a such that $P(A_t = a | E_t = e) = 1$.*

Assumption 2. *Given a state S_t, X_t is deterministic and defined by a function $\phi : \mathcal{S} \mapsto \mathcal{X}$, i.e., there exists x such that $P(X_t = x | S_t = s) = 1$.*

Note that we also assume the Markov property for our environment, which is a standard assumption for reinforcement learning problems. With slight abuse of notation, we denote the inverse mapping from an action $a \in \mathcal{A}$ to its corresponding points in the embedding space (one-to-many mapping) by $f^{-1}(a) := \{e \in \mathcal{E} : f(e) = a\}$.

Lemma 1. *Under Assumptions 1 and 2, for policy π in the original problem domain, there exists π_i such that*

$$v^\pi(s) = \sum_{a \in A} \int_{\{e\}=f^{-1}(a)} \pi_i(e|x = \phi(s)) Q^\pi(s, a) \, de \, .$$

Proof Sketch. Based on the Bellman equation for the value function v^π in the original domain, we introduce the embedded state $x = \phi(s)$ using Assumption 2. By the law of total probability and Assumption 1, we then introduce the embedded action e. From the Markovian property and the definition of our model, we can derive Claims 1 - 5 on (conditional) independence in Appendix A.2, which then allow us to remove the original state and action from the expression of the policy, leaving us with π_i. See Appendix A.2 for the complete proof. $\square$

By Assumptions 1 and 2, Lemma 1 allows us to express the overall policy π_o in terms of the internal policy π_i as

$$\pi_o(a|s) = \int_{\{e\}=f^{-1}(a)} \pi_i(e|x = \phi(s)) \, de \, , \tag{1}$$

bridging the gap between the original problem domain and the policy in embedding spaces $\mathcal{X}$ and $\mathcal{E}$. Under π^* in the original domain, we define $v^* := v^{\pi^*}$ and $Q^* := Q^{\pi^*}$ for the ease of discussions. Then using Lemma 1, we now prove the existence of an overall policy π_o that is optimal.

Theorem 1. *Under Assumptions 1 and 2, there exists an overall policy π_o that is optimal, such that $v^{\pi_o} = v^*$.*

Proof. Under finite state and action sets, bounded rewards, and $\gamma \in [0, 1)$, at least one optimal policy π^* exists. From Lemma 1, we then have

$$v^*(s) = \sum_{a \in A} \int_{\{e\}=f^{-1}(a)} \pi_i(e|\phi(s)) Q^*(s, a) \, de \, . \tag{2}$$

Thus, $\exists\, \phi$, f, and π_i, representing an overall policy π_o, which is optimal, i.e., $v^{\pi_o} = v^*$. $\square$

Theorem 1 suggests that in order to get the optimal policy π^* in the original domain, we can focus on the optimization of the overall policy π_o, which will be discussed in the next section.

4.3 ARCHITECTURE EMBODIMENT AND TRAINING

In this section, we first present the implementation and training of the joint state-action embedding model (illustrated in Figure 1b). Based on this method and according to Theorem 1, we then propose a strategy to train the overall policy π_o, where functions ϕ and f are iteratively updated.

4.3.1 JOINT STATE-ACTION EMBEDDING

In this section, we elaborate on our proposed embedding model for jointly learning state and action embeddings. Specifically, we require two components: (i) function ϕ that projects S_t into embedding space $\mathcal{X}$ and (ii) function f that maps each point in embedding space $\mathcal{E}$ to an action A_t in the original problem domain. Since these functions are not known in advance, we train estimators using a model of the environment, illustrated in Figure 1b. This environment model requires two further components: (iii) function $g : \mathcal{A} \mapsto \mathcal{E}$ and (iv) transition model $T : \mathcal{E} \times \mathcal{X} \mapsto \mathcal{S}$ that predicts the next state from the embeddings of the current state and action. Denoting the estimators of components (i) - (iv) by $\hat{\phi}, \hat{f}, \hat{g}, \hat{T}$, the target of the environment model can be written as

$$\hat{P}(S_{t+1}|S_t, A_t) = \hat{T}(S_{t+1}|X_t, E_t)\hat{g}(E_t|A_t)\hat{\phi}(X_t|S_t). \tag{3}$$

The difference between the true transition probabilities $P(S_{t+1}|S_t, A_t)$ and the estimated probabilities $\hat{P}(S_{t+1}|S_t, A_t)$ can be measured using the Kullback-Leibler (KL) divergence, i.e.,

$$D_{KL}(P||\hat{P}) = -\mathbb{E}\Big[\ln\Big(\frac{\hat{P}(S_{t+1}|S_t, A_t)}{P(S_{t+1}|S_t, A_t)}\Big)\Big]. \tag{4}$$

In Equation (4), the denominator does not depend on ϕ, g, or T. Therefore, we define the loss function for the embedding model as

$$\mathcal{L}(\hat{\phi}, \hat{g}, \hat{T}) = -\mathbb{E}\Big[\ln(\hat{P}(S_{t+1}|S_t, A_t))\Big]. \tag{5}$$

Note that the estimator $\hat{f}$ is not directly included in the embedding model. Instead, we find $\hat{f}$ by minimizing the reconstruction error between the original action and the action reconstructed from the embedding. We can again define this using the KL divergence as

$$\mathcal{L}(\hat{f}) = -\mathbb{E}\Big[\ln(\hat{f}(A_t|E_t))\Big]. \tag{6}$$

Then, all components of our embedding model can be learned by minimizing the loss functions $\mathcal{L}(\hat{\phi}, \hat{g}, \hat{T})$ and $\mathcal{L}(\hat{f})$. Here, we give the target of the embedding model for the case of discrete state and action spaces. However, the model is equally applicable to continuous domains. In this case, the loss functions $\mathcal{L}(\hat{\phi}, \hat{g}, \hat{T})$ and $\mathcal{L}(\hat{f})$ must be replaced with loss functions suitable for continuous domains. For continuous domains, we adopt a mean squared error loss instead of the losses given in Equations (5) and (6), but other loss functions may also be applicable. For our experiments, we parameterize all components of the embedding model illustrated in Figure 1b as neural networks. More details on this can be found in Appendix A.4.

4.3.2 JOINT STATE-ACTION EMBEDDING AND POLICY LEARNING

Theorem 1 only shows that optimizing π_o can help us achieve the optimality in the original domain. Then a natural question is whether we can optimize π_o by directly optimizing the internal policy π_i using the state/action embeddings in Section 4.3.1. To answer this question, we first mathematically derive that updating π_i is equivalent to updating π_o. We then proceed to present an iterative algorithm for jointly learning the state-action embeddings and the internal policy.

Suppose π_i is parameterized by θ. Then with the objective of optimizing π_o by only updating π_i, we define the performance function of π_o as[1]

$$J_o(\phi, \theta, f) = \sum_{s \in \mathcal{S}} d_0(s) \sum_{a \in \mathcal{A}} \pi_o(a|s)Q^{\pi_o}(s, a). \tag{7}$$

---

[1]Equation (7) is for the overall policy with discrete states and actions. Note that our approach is also applicable in continuous domains. $\sum_{s \in \mathcal{S}}$ and $\sum_{a \in \mathcal{A}}$ would then be replaced by $\int_s$ and $\int_a$, respectively.

Algorithm 1: Joint Training of State-Action Embeddings and the Internal Policy

---

Initialize the state and action embeddings (optional pre-training);
for *Epoch = 0, 1, 2 ...* **do**
    for *t = 1, 2, 3 ...* **do**
        Generate state embedding $X_t = \phi(S_t)$;
        Sample action embedding $E_t \sim \pi_i(\cdot|X_t)$;
        Map embedded action to $A_t = f(E_t)$;
        Execute A_t in the environment to observe S_t, R_t;
        Update the π_i and the critic using some policy gradient algorithms;
        Update ϕ and f by minimizing the losses in Equations (5) and (6);

Let the state-action-value function for the internal policy be $Q^{\pi_i}(x, e) = \mathbb{E}[\sum_{k=0}^{\infty} \gamma^k R_{t+k}|\pi_i, X_t = x, E_t = e]$. We can then define the performance function of the internal policy as

$$J_i(\theta) = \int_{x \in \mathcal{X}} d_0(x) \int_{e \in \mathcal{E}} \pi_i(e|x) Q^{\pi_i}(x, e) \, de \, dx \,. \tag{8}$$

The parameters of the overall policy π_o can then be learned by updating its parameters θ in the direction of $\partial J_o(\phi, \theta, f)/\partial \theta$, while the parameters of the internal policy can be learned by updating θ in the direction of $\partial J_i(\theta)/\partial \theta$. With one additional assumption, we have the following lemma.

Assumption 3. *The state embedding function $\phi(s)$ maps each state s to a unique state embedding $x = \phi(s)$, i.e., $\forall s_i \neq s_j$, $P(\phi(s_i) = \phi(s_j)) = 0$.*

Lemma 2. *Under Assumptions 1–3, for all deterministic functions f and ϕ, which map each point $e \in \mathcal{E}$ and $s \in \mathcal{S}$ to an action $a \in \mathcal{A}$ and to an embedded state $x \in \mathcal{X}$, and the internal policy π_i parameterized by θ, the gradient of the internal policy's performance function $\frac{\partial J_i(\theta)}{\partial \theta}$ equals the gradient of the overall policy's performance function $\frac{\partial J_o(\phi, \theta, f)}{\partial \theta}$, i.e.,*

$$\frac{\partial J_i(\theta)}{\partial \theta} = \frac{\partial J_o(\phi, \theta, f)}{\partial \theta} \,.$$

Proof Sketch. Assumptions 1 and 3 allow us to show the equivalence between the internal state-action-value function and the overall state-action-value function. Using this equivalence, we can then remove functions ϕ and f from $\partial J_o(\phi, \theta, f)/\partial \theta$ and are left with the gradient of the internal policy π_i only. The complete proof is deferred to Appendix A.3. $\square$

Lemma 2 shows that the updates to the internal policy π_i and the overall policy π_o are equivalent. This allows us to optimize the overall policy by making updates directly to the internal policy π_i, thereby avoiding the potentially intractable computation of the inverse functions f^{-1} and ϕ^{-1}. Since there are no special restrictions on the internal policy π_i, we can use any policy gradient algorithm designed for continuous control to optimize the policy. Note that Assumption 3 is not theoretically guaranteed by the definition of our embedding model. Nevertheless, we test this empirically using the experiments in Section 5 and find that no two states share the same embedded representation in any of our experiments, thus justifying Assumption 3 in practical scenarios considered in this work.

With Lemma 2, we can directly update π_i using the embeddings in Section 4.3.1. Alternatively, we can also iteratively update parameters for jointly learning ϕ, f, and π_i, as shown in Algorithm 1.

5 EMPIRICAL EVALUATION

We evaluate our proposed architecture on several environments, including game-based applications, robotic control, and a real-world recommender system. The environments used for experimentations cover different combinations of discrete and continuous state and action spaces. Our methodology is evaluated using a Vanilla Policy Gradient (VPG), a Proximal Policy Optimization (PPO) (Schulman et al., 2017) and a Soft Actor Critic (SAC) (Haarnoja et al., 2018) algorithm. We benchmark the performance against these algorithms without embeddings and with action embeddings generated by the method called policy gradients with Representations for Actions (RA) proposed by Chandak et al. (2019). Complete parameterizations are presented in Appendix A.4.

Figure 2: Performance of our approach (JSAE, Joint State Action Embedding) compared against benchmarks without embeddings and/or benchmarks with action embeddings by RA (all results are the average return over 10 episodes, with mean and std. dev. over 5 random seeds).

5.1 PROOF-OF-CONCEPT: GRIDWORLD AND SLOTMACHINE

Gridworld: It is similar to that used by Chandak et al. (2019). States are given as a continuous coordinate, while actions are defined via n actuators, equally spaced around the agent, which move the agent in the direction they are pointing towards. Then each combination of actuators forms an action, resulting in 2^n unique actions. We run two sets of experiments in this environment: (i) we use the continuous state directly and (ii) we discretize the coordinate in a 40×40 grid. The agent receives small step and collision penalties and a large positive reward for reaching the goal state.

Slotmachine: It consists of several reels, each of which can be individually spun by the agent for a fraction of a full turn. Then, each unique combination of these fractions constitutes an action. The discrete state is given by the numbers on the front of the reels.

Both scenarios yield large discrete action spaces, rendering them well-suited for evaluating our approach. The results for the gridworld and slotmachine environments are shown in Figure 2a, 2b, and 2c. We find that our approach outperforms both benchmarks on the discretized gridworld and the slotmachine environments and is comparable for the continuous-state gridworld. Such observation suggests that our approach is particularly well suited for discrete domains. Intuitively, this is because the relationship between different states or action in discrete domains is usually not apparent, e.g., in one-hot encoding. In continuous domains, however, structure in the state and action space is already

captured to some extent, rendering it harder to uncover additional structure by embeddings, which explains the differences in performance between the discrete and continuous domains.

5.2 ROBOTIC CONTROL

We use the *half-cheetah* environment from the robotic control simulator Mujoco (Todorov et al., 2012). Here, the agent observes continuous states (describing the current position of a cheetah) and then decides on the force to apply to each of the joints of the cheetah. Both states and actions are thus continuous. Rewards are calculated based on the distance covered in an episode. From the results presented in Figure 2d, we observe that our method does not outperform the benchmark without embeddings. Similar to the experiments in a continuous gridworld, it is less likely that embedding uncovers additional structure in the state/action space on top of the structure inherent to the continuous state and action, explaining the comparable performance with and without embeddings.

5.3 RECOMMENDER SYSTEM

In addition to game-based environments, we also test our methodology on a real-world application of a recommender system. We use data on user behavior, such as views and purchases of items, from an e-commerce store collected in October 2019 (Kechinov, 2019). The environment is constructed as an n-gram based model, following Shani et al. (2005). Based on a sequence of n previously purchased items, a user's purchasing likelihood is computed for each item in the store. Recommending an item then scales the likelihood for that item by a pre-defined factor. For our experiments, we restrict our focus to purchases and exclude items that were purchased less than 100 times and users that made less than 3 purchases. We are then left with 835 unique items. States are represented as a concatenation of the last n purchased items and each item forms an action. The results obtained under various RL methods are reported in Figure 2e. We find that our approach leads to significant improvements in both the convergence speed and final performance compared to benchmarks. This result confirms that our embedding technique is particularly useful in the presence of large discrete state and action spaces. Interestingly, the PPO and VPG benchmarks outperform the benchmarks using the RA methodology. We conjecture that the action embeddings generated in RA on this particular environment in fact obfuscate the effect an action has, and thus limit the agent's performance.

5.4 APPLICATION IN TRANSFER LEARNING

In addition to improving the convergence speed and the accumulated reward, we test whether the policies learned in one environment can be transferred to a similar one. Specifically, we consider two environments (old and new) that differ by only the state space or the action space. To leverage the previous experience, if the two environments have the same state (or action) space, the state (or action) embedding component in the new environment is initialized with the weights learned from the old environment; we then train our model in this new environment. This idea is evaluated in two gridworld environments with the same state space, but the numbers of actions are 512 (old) and 2048 (new), respectively. Results in Figure 2f show that the model with the transferred knowledge outperforms the case where the entire model is trained from scratch, in terms of the convergence speed. Therefore, it confirms that the previously learned policy serves as a critical initialization for the new gridworld environment. Such observation sheds light on the potential of our approach in transfer learning for RL tasks; evaluations in other applications are left for future work.

6 CONCLUSION

In this paper, we presented a new architecture for jointly embedding states/actions and combined this with common reinforcement learning algorithms. Our theoretical results confirm the validity of the proposed approach, i.e., the existence of an optimal policy in the embedding space. We empirically evaluated our method on several environments, where it outperforms state-of-the-art RL approaches in the presence of large discrete state-action spaces. Our approach is easily extensible as it can be combined with most existing RL algorithms and there are no special restrictions on the parameterizations of the embedding model. Consequently, we conclude that the proposed methodology fosters the applicability of reinforcement learning to real-world scale problems.

REFERENCES

Joshua Achiam. Spinning Up in Deep Reinforcement Learning. 2018.

Prithviraj Ammanabrolu and Mark O Riedl. Playing text-adventure games with graph-based deep reinforcement learning. *arXiv preprint arXiv:1812.01628*, 2018.

Yash Chandak, Georgios Theocharous, James Kostas, Scott Jordan, and Philip S. Thomas. Learning Action Representations for Reinforcement Learning. *36th International Conference on Machine Learning (ICML)*, pp. 1565–1582, 2019.

Tim de Bruin, Jens Kober, Karl Tuyls, and Robert Babuška. Integrating state representation learning into deep reinforcement learning. *IEEE Robotics and Automation Letters*, pp. 1394–1401, 2018.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL)*, pp. 4171–4186, 2019.

Gabriel Dulac-Arnold, Richard Evans, Hado van Hasselt, Peter Sunehag, Timothy Lillicrap, Jonathan Hunt, Timothy Mann, Theophane Weber, Thomas Degris, and Ben Coppin. Deep reinforcement learning in large discrete action spaces. *arXiv preprint arXiv:1512.07679*, 2015.

Richard Evans and Jim Gao. Deepmind AI reduces google data centre cooling bill by 40%. *DeepMind blog*, 2016. URL https://deepmind.com/blog/article/deepmind-ai-reduces-google-data-centre-cooling-bill-40.

Vincent Francois-Lavet, Yoshua Bengio, Doina Precup, and Joelle Pineau. Combined Reinforcement Learning via Abstract Representations. pp. 3582–3589. Association for the Advancement of Artificial Intelligence (AAAI), 2019.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. *arXiv preprint arXiv:1801.01290*, 2018.

Zhengyao Jiang, Dixing Xu, and Jinjun Liang. A deep reinforcement learning framework for the financial portfolio management problem. *arXiv preprint arXiv:1706.10059*, 2017.

Michael Kechinov. ecommerce behavior data from multi category store, 2019. URL https://www.kaggle.com/mkechinov/ecommerce-behavior-data-from-multi-category-store.

Yu Lei and Wenjie Li. Interactive recommendation with user-specific deep reinforcement learning. *ACM Transactions on Knowledge Discovery from Data (TKDD)*, 13:1–15, December 2019.

Feng Liu, Ruiming Tang, Xutao Li, Weinan Zhang, Yunming Ye, Haokun Chen, Huifeng Guo, and Yuzhou Zhang. Deep reinforcement learning based recommendation with explicit user-item interactions modeling. *arXiv preprint arXiv:1810.12027*, 2018.

Hongzi Mao, Mohammad Alizadeh, Ishai Menache, and Srikanth Kandula. Resource management with deep reinforcement learning. In *Proceedings of the 15th ACM Workshop on Hot Topics in Networks*, pp. 50–56, 2016.

Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. Efficient estimation of word representations in vector space. *arXiv preprint arXiv:1301.3781*, 2013a.

Tomas Mikolov, Quoc V Le, and Ilya Sutskever. Exploiting similarities among languages for machine translation. *arXiv preprint arXiv:1309.4168*, 2013b.

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg Corrado, and Jeffrey Dean. Distributed representations of words and phrases and their compositionality. In *Proceedings of the 26th International Conference on Neural Information Processing Systems (NIPS)*, pp. 3111–3119, 2013c.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602*, 2013.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518:529–533, 2015.

Jelle Munk, Jens Kober, and Robert Babuška. Learning state representation for deep actor-critic control. In *2016 IEEE 55th Conference on Decision and Control (CDC)*, pp. 4667–4673, 2016.

Karthik Narasimhan, Tejas Kulkarni, and Regina Barzilay. Language understanding for text-based games using deep reinforcement learning. *arXiv preprint arXiv:1506.08941*, 2015.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems 32 (NIPS)*, pp. 8024–8035. 2019.

Jason Pazis and Ronald Parr. Generalized value functions for large action sets. In *Proceedings of the 28th International Conference on International Conference on Machine Learning (ICML)*, pp. 1185–1192, 2011.

Brian Sallans and Geoffrey E Hinton. Reinforcement learning with factored states and actions. *Journal of Machine Learning Research*, 5(Aug):1063–1088, 2004.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Guy Shani, David Heckerman, and Ronen I Brafman. An mdp-based recommender system. *Journal of Machine Learning Research*, 6(Sep):1265–1295, 2005.

Sahil Sharma, Aravind Suresh, Rahul Ramesh, and Balaraman Ravindran. Learning to factor policies and action-value functions: Factored action space representations for deep reinforcement learning. *arXiv preprint arXiv:1705.07269*, 2017.

Guy Tennenholtz and Shie Mannor. The natural language of actions. volume 97 of *Proceedings of Machine Learning Research*, pp. 6196–6205, 2019.

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 5026–5033, 2012.

Hado Van Hasselt and Marco A Wiering. Using continuous action spaces to solve discrete problems. In *2009 International Joint Conference on Neural Networks (IJCNN)*, pp. 1149–1156, 2009.

A APPENDIX

A.1 CLAIMS

In addition to Assumptions 1 and 2, we derive three claims on conditional independence from the definition of our embedding model and the Markovian property of the environment, listed below.

Claim 1. *Action A_t is conditionally independent of S_t given a state embedding X_t:*

$$P(A_t = a, S_t = s | X_t = x) = P(A_t = a | X_t = x) P(S_t = s | X_t = x).$$

Claim 2. *Action A_t is conditionally independent of S_t given state and action embeddings X_t and E_t:*

$$P(A_t = a, S_t = s | X_t = x, E_t = e) = P(A_t = a | X_t = x, E_t = e) P(S_t = s | X_t = x, E_t = e).$$

Claim 3. *Next state S_{t+1} is conditionally independent of E_t and X_t given A_t and S_t:*

$$P(S_{t+1} = s', E_t = e, X_t = x | A_t = a, S_t = s) =$$
$$P(S_{t+1} = s' | A_t = a, S_t = s) P(E_t = e, X_t = x | A_t = a, S_t = s).$$

Using Claims 1 - 3, we can derive two further auxiliary claims that will be used in the proof of Lemma 1.

Claim 4. *The probability of next state S_{t+1} is independent of E_t and X_t, given state S_t and action A_t, i.e.,*

$$P(S_{t+1} = s' | E_t = e, X_t = x, A_t = a, S_t = s) = P(S_{t+1} = s' | A_t = a, S_t = s).$$

Proof. From Claim 3, we have

$$P(s', e, x | a, s) = P(s' | a, s) P(e, x | a, s)$$
$$P(s' | e, x, a, s) P(e, x | a, s) = P(s' | a, s) P(e, x | a, s)$$
$$P(s' | e, x, a, s) = P(s' | a, s).$$

$\square$

Claim 5. *The probability of action A_t is independent of S_t and X_t, given action embedding E_t, i.e.,*

$$P(A_t = a | S_t = s, X_t = x, E_t = e) = P(A_t = s | E_t = e).$$

Proof. From Claim 2, we have

$$P(a, s | x, e) = P(a | x, e) P(s | x, e)$$
$$P(a | s, x, e) = P(a | x, e).$$

Since action a only depends on the action embedding e in our model, this becomes

$$P(a | s, x, e) = P(a | e).$$

$\square$

A.2 PROOF OF LEMMA 1

Lemma 1. *Under Assumptions 1 and 2, for policy π in the original problem domain, there exists π_i such that*

$$v^\pi(s) = \sum_{a \in \mathcal{A}} \int_{\{e\} = f^{-1}(a)} \pi_i(e | x = \phi(s)) Q^\pi(s, a) \, de$$

Proof. The Bellman equation for a MDP is given by

$$v^\pi(s) = \sum_{a \in \mathcal{A}} \pi(a | s) \sum_{s' \in \mathcal{S}} P(s' | s, a) G,$$

where G denotes the return, which is a function of s, a, and s'. By re-arranging terms we get

$$v^\pi(s) = \sum_{a \in \mathcal{A}} \sum_{s' \in \mathcal{S}} \pi(a | s) P(s' | s, a) G$$

$$= \sum_{a \in \mathcal{A}} \sum_{s' \in \mathcal{S}} \pi(a | s) \frac{P(s', s, a)}{P(s, a)} G$$

$$= \sum_{a \in \mathcal{A}} \sum_{s' \in \mathcal{S}} \pi(a | s) \frac{P(s', s, a)}{\pi(a | s) P(s)} G$$

$$= \sum_{a \in \mathcal{A}} \sum_{s' \in \mathcal{S}} \frac{P(a | s', s) P(s', s)}{P(s)} G.$$

Since s can be deterministically mapped to x via $x = \phi(s)$, by Assumption 2, we have

$$
\begin{aligned}
v^\pi(s) &= \sum_{a \in \mathcal{A}} \sum_{s' \in \mathcal{S}} \frac{P(x, a | s', s) P(s', s)}{P(s)} G \\
&= \sum_{a \in \mathcal{A}} \sum_{s' \in \mathcal{S}} \frac{P(x, a | s', s) P(s', s) P(x|s)}{P(x|s) P(s)} G \\
&= \sum_{a \in \mathcal{A}} \sum_{s' \in \mathcal{S}} \frac{P(x, a, s', s) P(x|s)}{P(x, s)} G \\
&= \sum_{a \in \mathcal{A}} P(x|s) \sum_{s' \in \mathcal{S}} \frac{P(x, a, s', s)}{P(x, s)} G \\
&= \sum_{a \in \mathcal{A}} P(x|s) \sum_{s' \in \mathcal{S}} \frac{P(a, s'|x, s) P(x, s)}{P(x, s)} G \\
&= \sum_{a \in \mathcal{A}} P(x|s) \sum_{s' \in \mathcal{S}} P(a, s'|x, s) G \\
&= \sum_{a \in \mathcal{A}} P(x|s) \sum_{s' \in \mathcal{S}} P(s'|a, x, s) P(a|s, x) G .
\end{aligned}
$$

From Claim 1, we know that $P(a|s, x) = P(a|x)$. Therefore,

$$
v^\pi(s) = \sum_{a \in \mathcal{A}} P(x|s) \sum_{s' \in \mathcal{S}} P(s'|a, x, s) P(a|x) G .
$$

Since $P(x|s)$ is deterministic by Assumption 2 and evaluates to 1 for the representation of $\phi(s) = x$, we can rewrite the equation above to

$$
v^\pi(s) = \sum_{a \in \mathcal{A}} \sum_{s' \in \mathcal{S}} P(s'|a, x, s) P(a|x) G .
$$

We now proceed to establish the relationship with the action embedding. From above we have

$$
\begin{aligned}
v^\pi(s) &= \sum_{a \in \mathcal{A}} \sum_{s' \in \mathcal{S}} P(a|x) P(s'|a, x, s) G \\
&= \sum_{a \in \mathcal{A}} \sum_{s' \in \mathcal{S}} P(a|x) \frac{P(s', a, x, s)}{P(a, x, s)} G .
\end{aligned}
$$

From Claim 1, a and s are conditionally independent given x. Therefore, $P(a, x, s) = P(a|x) P(s|x) P(x)$, which allows us to rewrite the above equation as

$$
\begin{aligned}
v^\pi(s) &= \sum_{a \in \mathcal{A}} \sum_{s' \in \mathcal{S}} P(a|x) \frac{P(s', a, x, s)}{P(a|x) P(x, s)} G \\
&= \sum_{a \in \mathcal{A}} \sum_{s' \in \mathcal{S}} \frac{P(s', a, x, s)}{P(x, s)} G \\
&= \sum_{a \in \mathcal{A}} \sum_{s' \in \mathcal{S}} \frac{P(a|s', x, s) P(s', x, s)}{P(x, s)} G .
\end{aligned}
$$

By the law of total probability, we can now introduce the new variable e, which is the embedded action. Then

$$v^\pi(s) = \sum_{a \in \mathcal{A}} \sum_{s' \in \mathcal{S}} \int_e \frac{P(a, e | s', x, s) P(s', x, s)}{P(x, s)} G\, de$$

$$= \sum_{a \in \mathcal{A}} \sum_{s' \in \mathcal{S}} \int_e P(e | x, s) \frac{P(a, e | s', x, s) P(s', x, s)}{P(e | x, s) P(x, s)} G\, de\,.$$

Since e is uniquely determined by x, we can drop s in $P(e | x, s)$, and thus

$$v^\pi(s) = \sum_{a \in \mathcal{A}} \sum_{s' \in \mathcal{S}} \int_e P(e | x) \frac{P(a, e, s', x, s)}{P(e, x, s)} G\, de$$

$$= \sum_{a \in \mathcal{A}} \sum_{s' \in \mathcal{S}} \int_e P(e | x) P(a, s' | e, x, s) G\, de$$

$$= \sum_{a \in \mathcal{A}} \sum_{s' \in \mathcal{S}} \int_e P(e | x) P(s' | a, e, x, s) P(a | x, e, s) G\, de\,.$$

Using the previously derived Claims 4 and 5, the above equation can be simplified to

$$v^\pi(s) = \sum_{a \in \mathcal{A}} \sum_{s' \in \mathcal{S}} \int_e P(e | \phi(s)) P(s' | a, s) P(a | e) G\, de\,.$$

Since the function f, mapping e to a, is deterministic by Assumption 1 and only evaluates to 1 for a particular a and 0 elsewhere, we can rewrite this further as

$$v^\pi(s) = \sum_{a \in \mathcal{A}} \sum_{s' \in \mathcal{S}} \int_{f^{-1}(a)} P(e | \phi(s)) P(s' | a, s) G\, de\,.$$

Summarizing the terms, this becomes

$$v^\pi(s) = \sum_{a \in \mathcal{A}} \int_{f^{-1}(a)} \pi_i(e | \phi(s)) Q^\pi(a, s)\, de\,.$$

$\square$

A.3 Proof of Lemma 2

Lemma 2. *Under Assumptions 1–3, for all deterministic functions f and ϕ which map each point $e \in \mathcal{E}$ and $s \in \mathcal{S}$ to an action $a \in \mathcal{A}$ and to an embedded state $x \in \mathcal{X}$, and the internal policy π_i parameterized by θ, the gradient of the internal policy's performance function $\frac{\partial J_i(\theta)}{\partial \theta}$ equals the gradient of the overall policy's performance function $\frac{\partial J_o(\phi, \theta, f)}{\partial \theta}$, i.e.,*

$$\frac{\partial J_i(\theta)}{\partial \theta} = \frac{\partial J_o(\phi, \theta, f)}{\partial \theta}\,.$$

Proof. Recall from Lemma 1 that the overall policy is defined using the internal policy

$$\pi_o(a | s) = \int_{f^{-1}(a)} \pi_i(e | \phi(s))\, de\,.$$

Figure 3: Illustration of π_i' in the combined model.

We can then define the performance function of the overall policy using the internal policy as

$$J_o(\phi, \theta, f) = \sum_{s \in \mathcal{S}} d_0(s) \sum_{a \in \mathcal{A}} \int_{f^{-1}(a)} \pi_i(e|\phi(s)) Q^{\pi_o}(s, a) \, de \,.$$

The gradient of this performance function w.r.t. θ is

$$\frac{\partial J_o(\phi, \theta, f)}{\partial \theta} = \frac{\partial}{\partial \theta} \Big[\sum_{s \in \mathcal{S}} d_0(s) \sum_{a \in \mathcal{A}} \int_{f^{-1}(a)} \pi_i(e|\phi(s)) Q^{\pi_o}(s, a) \, de \Big]. \tag{9}$$

Now consider another policy π_i' as illustrated in Figure 3, i.e., a policy that takes the raw state input S_t and outputs E_t in embedding space. By Assumption 1, $Q^{\pi_o}(s, a) = Q^{\pi_i'}(s, e)$ as e is deterministically mapped to a. However, $Q^{\pi_i}(x, e) = \mathbb{E}_{s \sim \phi^{-1}(x)}[Q^{\pi_i'}(s, e)] = \mathbb{E}_{s \sim \phi^{-1}(x)}[Q^{\pi_o}(s, a)]$, where $\phi^{-1}(\cdot)$ is the inverse mapping from x to s. Nevertheless, by Assumption 3, $\mathbb{E}_{s \sim \phi^{-1}(x)}[Q^{\pi_o}(s, a)] = Q^{\pi_o}(s, a)$. Therefore, we can replace the overall $Q^{\pi_o}(a, s)$ in Equation (9) by the internal $Q^{\pi_i}(\phi(s), e)$ as follows

$$\frac{\partial J_o(\phi, \theta, f)}{\partial \theta} = \frac{\partial}{\partial \theta} \Big[\sum_{s \in \mathcal{S}} d_0(s) \sum_{a \in \mathcal{A}} \int_{f^{-1}(a)} (\pi_i(e|\phi(s)) Q^{\pi_i}(\phi(s), e) \Big] \, de \,.$$

Then the deterministic mapping of e to a by function f further allows us to replace the integral over $f^{-1}(a)$ and the summation over $\mathcal{A}$ with an integral over e. Moreover, by Assumption 3, we have $d_0(s) = d_0(x = \phi(s))$. Therefore, the above can be rewritten as

$$\begin{aligned}
\frac{\partial J_o(\phi, \theta, f)}{\partial \theta} &= \frac{\partial}{\partial \theta} \Big[\int_{x \in \mathcal{X}} d_0(x) \int_{e \in \mathcal{E}} \pi_i(e|x) Q^{\pi_i}(x, e) \, de \, dx \Big] \\
&= \frac{\partial J_i(\theta)}{\partial \theta} \,.
\end{aligned}$$

$\square$

A.4   PARAMETERIZATION

A.4.1   IMPLEMENTATION AND ENVIRONMENTS

We implement all evaluated models in Python and use the PyTorch library for neural network implementation (Paszke et al., 2019). The implementation for the benchmark models is adapted from OpenAI's SpinningUp package (Achiam, 2018). In the following, we elaborate on the different environments used for experimentation.

Gridworld   The gridworld environments are constructed using a 1×1 grid to represent the underlying continuous state space. For the continuous state version of the environment, a continuous

coordinate with the position of the agent in this grid is used as the state. In the discrete state version, we discretize this continuous coordinate in a 40×40 grid. Actions in these environments are generated from n actuators, equally spaced around the agent, which move the agent in the direction they are pointing towards. Then each combination of actuators forms a unique action, resulting in 2^n unique actions. An illustration of this environment can be seen in Figure 4. We limit the maximum number of steps the agent can take in an episode to 150 and set the maximum step size to 0.2.

Slotmachine The slotmachine environment is defined using 4 reels, with 6 values per reel, randomly sampled from the range between 0 and 8. Note that we sample these reels once and then keep them fixed across all experiments to ensure that these run in the same environment. The action space is defined by the fraction of a full turn for which each reel is spun. We set the maximum fraction to 0.8 and use increments of 0.1 to set the fraction of a full turn. Since each combination of fractions forms an action, we get $4,096$ actions in total. The maximum number of steps per episode is set to 20. Rewards are calculated according to

$$R_t = \sum_{i=1,2,3,4} v_i \times \mathbb{1}\{n_i \geq m\},$$

where v_i denotes the value of the i^{th} reel, n_i is the number of times v_i occurred across all 4 reels, m is the minimum number of times it has to occur to result in non-zero reward, and $\mathbb{1}\{\cdot\}$ is an indicator function. In our experiments, we set the threshold $m = 3$.

Robotic Control: Half-Cheetah For the experiments in a robotic control environment, we use the physics engine Mujoco and use the *Half-Cheetah* environment implemented therein (Todorov et al., 2012). We limit the maximum number of steps per episode to 250.

Real-world Recommender System The environment model for the recommender system is constructed from a publicly available data set containing data on approximately 43 million user interactions collected from a multi-category e-commerce store (Kechinov, 2019). We only use purchase events to create our model, where we filter out items that were bought fewer than 100 times and users that made less than 3 purchases. We are then left with approximately $250,000$ data points and 835 items. The environment model is then created using an n-gram based model, with n set to 2. For more details on the environment model used, please refer to Shani et al. (2005), whose methodology is adopted. The state is represented as the concatenation of the n last items purchased and each item available for recommendation forms an action. We thus have 835 actions and $697,225$ possible states. The transition function in this environment is stochastic as we have transition probabilities for each item and each state. We parameterize a categorical distribution with these transition probabilities to sample the next item. Recommending an item increases its transition probability by a factor $\alpha = 3$, after which the sum of all transition probabilities for the current state are normalized to sum to 1. As the reward function, we simply use the revenue obtained in each time step, i.e., the price of the item that the customer bought after making a certain recommendation.

Figure 4: Gridworld environment as used for evaluation The goal state is in blue, the agent is in red, and the obstacles are shown in gray.

A.4.2 HYPER PARAMETERS

Training for all experiments is conducted in epochs, where each epoch corresponds to a set of samples. At the end of an epoch, the actor and critic are trained for a number of iterations using their respective learning rates. The environment configuration is kept fixed for each environment across different models as well as the hyper parameter searches to ensure comparability.

We conduct a gridsearch over different parameter combinations for each experiment and report the average per episode return and standard deviation achieved over 5 runs with different random seeds, using the hyper parameters that perform the best in the gridsearch. The actor and critic learning rates are searched over $\{0.001, 0.0003, 0.0001\}$ for all environments. We also search the initialization value for the standard deviation of the actor over $\{0.3, 0.6, 0.8\}$ in all experiments and keep $\gamma = 0.99$ and $\lambda = 0.97$ fixed. Note that λ is only used for general advantage estimation in the VPG algorithm. For all experiments apart from those using the recommender system, we pre-train the embedding model using $30,000$ randomly collected samples and keep the embeddings fixed thereafter. For the recommender system, we allow continuous updating of the learned embeddings. In all cases, we apply a *Tanh* non-linearity to the learned embeddings to bound their effective range. Throughout our experiments, we keep the learning rate of the embedding model fixed at 0.01. For continuous domains, we parameterize the mapping function f as a neural network with a single layer with 64 hidden units. In discrete domains, we use a simpler nearest neighbor mapping function to parameterize f, i.e., we map the output of the internal policy π_i to the action that is closest in embedding space $\mathcal{E}$.

For experiments on the gridworld environments, we fix the state and action embedding dimensions at 8 and 2, respectively. The network size for the actor and critic is set to $(64, 64)$, i.e., a two-layer network with 64 neurons in each layer. We then train the agent for 700 epochs, with $1,500$ steps, i.e., a minimum of 10 episodes per epoch.

In the experiments on the slotmachine environment, the dimension for state and action embeddings is searched over $\{8, 16\}$ and $\{2, 4\}$, respectively. The network size for the actor and critic is kept fixed at $(64, 64)$. The agent is trained for $2,500$ epochs, with 200 samples (a minimum of 10 episodes per epoch).

For experiments on the Half-Cheetah environment, the state and action embedding dimensions are searched over $\{10, 20\}$ and $\{6, 10\}$, respectively. We search the network size over $\{(64, 64), (128, 128)\}$ and train the agent for $1,000$ epochs with $1,500$ steps per epoch, i.e., 6 episodes per epoch.

On the recommender system environment, we evaluate Proximal Policy Optimisation (PPO) and Soft Actor Critic (SAC) algorithms in addition to the previously used Vanilla Policy Gradient (VPG). For the experiments using the SAC algorithm, we search the actor parameter α, which corresponds to an exploration-exploitation trade-off over $\{0.1, 0.3\}$. For experiments involving a PPO algorithm, we set the gradient clipping ratio to 0.2 and keep this fixed throughout. Embedding dimensions for states and actions are searched over $\{8, 16, 32\}$ and $\{4, 8, 12\}$, respectively. In all experiments, the embedding functions are pre-trained using $200,000$ randomly generated samples. In contrast to experiments on other environments, we enable continuous updating of these learned embeddings for the recommender system. We search the size of the actor and critic network over $\{(64, 64), (128, 128)\}$ and train the agent for $1,000$ epochs with $1,000$ steps per epoch. The episode length is set to 20 steps.