Adaptive Sparse Federated Learning in Large Output Spaces via Hashing

Abstract

This paper focuses on the on-device training efficiency of federated learning (FL), and demonstrates it is feasible to exploit sparsity in the client to save both computation and memory for deep neural networks with large output space. To this end, we propose a sparse FL scheme using hash-based adaptive sampling algorithm. In this scheme, the server maintains neurons in hash tables. Each client looks up a subset of neurons from the hash table in the server and performs training. With the locality-sensitive hash functions, this scheme could provide valuable negative class neurons with respect to the client data. Moreover, the cheap operations in hashing incur low computation overhead in the sampling. In our empirical evaluation, we show that our approach can save up to 70% on-device computation and memory during FL while maintaining the same accuracy. Moreover, we demonstrate that we could use the savings in the output layer to increase the model capacity and obtain better accuracy with a fixed hardware budget.

1 Introduction

Recently, federated learning (FL) [17] and its applications [34, 13, 16, 22] receive attentions from both research community and industry. FL defines a practical yet challenging task: given a set of devices where each device maintains its private data locally, we would like to collaboratively train a model on these devices without data exchange. Significant effort has been made in improving optimization strategy [14, 29], privacy protection [8] and fairness [15] of FL.

A Challenge in On-device Training: FL introduces a device shift in the distributed training of machine learning models. In the cloud center, we were able to train large-scale foundation models on massive graphic processing units (GPUs) in a centralized way. In FL setting, our training hardware is limited to system-on-chip (SoC) on mobile devices. This shift leads to significant efficiency issues in FL: (1) The models we trained on GPU clusters are giant in terms of parameters. It is standard to have billion-scale parameters for language [2] and recommendation [18] models. However, the memory constraint for FL devices forces us to limit the model parameter size to make on-device training feasible, which causes a model size mismatch between FL and centralized models. This mismatch would degrade the FL model performance and prevent us from the benefits of large deep models. (2) In the centralized training, the advantages of specialized hardware such as TPU provide efficient matrix multiplication for training deep neural networks. However, the on-device tensor chips like TPUs in Pixel phones [23] are not as powerful as their serverside counterpart, which would significantly improve the training efficiency in FL. (3) The training of deep models through forward and backward propagation requires memory to store the intermediate results. Same the previous two issues, the hardware constraint of mobile devices would affect the efficiency of memory read and write during training, which exaggerates the computation overhead in FL.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

An Opportunity of Sparsity: There is an emerging trend on exploring sparsity in neural network training [26, 7, 6, 10]. An interesting direction is to switch the matrix multiplication from dense to sparse mode. For instance, given an input matrix $X \in \mathbb{R}^{n \times d}$ and the linear layer weight matrix $W \in \mathbb{R}^{d \times m}$, we view each row of X as an embedding and each column of W as a neuron. In this way, for each embedding in X, we could only select a subset of neurons in W for computation. As a result, we perform a sparse version of operation XW. Well-known research literature in this area includes the lottery ticket hypothesis [12, 35], sub-linear deep learning engine (SLIDE) [7, 6] and independent subnet training [36]. In this paper, we argue that there is an opportunity to improve the on-device training efficiency of FL with sparsity. Firstly, although the sparse training strategy does not change the model architecture, it only activates a subset of model parameters in each iteration. This feature could help us in FL so that each client only selects a subset of trainable parameters from the model for iterative optimization. As a result, the on-device parameter size would be reduced. Moreover, the sparse alternative to the matrix multiplication could significantly reduce the computation overhead, making FL easy on CPU only devices. Furthermore, the sparse training generates sparse intermediate results, which also reduces the memory access on the device.

Exploiting Adaptive Sparsity in Large Output Spaces: In this paper, we focus on the sparse FL for deep neural networks in large output spaces (LOS). LOS is common in deployed deep models. For instance, in language processing tasks such as next word prediction [19] and question answering [20], the output space would be the vocabulary size. In recommendation systems [18], the output space would be the number of products in the database. In both cases, the number of classes in the output space could be enormous. As a result, the output linear layer would contain the most model parameters if we would like to train them on-device using FL. On the other hand, since we would perform Softmax function on the output logits, we could approximate the output layer by focusing on the logits with high values. In fact, the LOS would be a perfect scenario for sparse training. If we could adaptively pre-select the neurons in the output linear layer that may incur a large inner product with the hidden input vector, we could only do forward and backward computation on the selected neurons [1, 7, 10, 6, 28]. Therefore, we could perform efficient on-device FL by saving both the computation and memory.

However, the combination of sparse training with FL could still be challenging: (1) An efficient design is required for sparse training in FL so that we can maintain the full model on the server and a sparse model on the client device. (2) It remains unknown whether the adaptive sparsity would be effective in the federated optimization with non-i.i.d data distribution. (3) How to use the saved computation and memory by sparsity for further improvements in the model accuracy. In other words, how to improve the model performance with a fixed hardware budget using sparsity?

1.1 Our Contributions

In this paper, we introduce an empirical study on the sparse FL in LOS. We propose to use hashing algorithms that adaptively select neurons in the output layer for forward and backward computation. Specifically, our contributions could be summarized as:

1. We introduce an adaptive hash-based sparse FL scheme for training in LOS. In this scheme, the server hashes the output layer's neurons in hash table. Next, the server sends the hash function to each client. Each client uses the hash function to generate hash codes of their own data. Next, each client uses the hash codes to look up the near neighbor neurons of its data from the server. Finally, each client only performs forward and backward propagation on the selected neurons.

2. We empirically show that the hash-based sparse training in the output layer is effective in the federated optimization. We could maintain the same model accuracy with 30% parameters in the output layer. As a result, the on-device training efficiency would be improved.

3. We demonstrate that in the proposed hash-based sparse FL scheme, the saved on-device model parameters in the output layer would be used to improve the model capacity. We show that on a fixed on-device parameter budget, if we perform sparse training on the output layer and use the saved parameters to increase the embedding and hidden dimension of the model, we could have better accuracy with on-device FL.

2 Related Work

Hashing Algorithms for Sparse Machine Learning: The hashing algorithms have demonstrated empirical effectiveness in the sparse training of machine learning models [7, 10, 6, 32, 30]. [7] proposes SLIDE algorithm that uses locality-sensitive hashing (LSH) [11] to preprocess the neurons of a wide output layer in hash tables. Next, given a batch of embeddings, SLIDE use them as a query and lookup the neurons that are close in cosine similarity from hash tables. Finally, SLIDE only performs forward and backward computation in the selected neurons. [10] shows that SLIDE can be further accelerated with the advance in hardware. [6] demonstrates that SLIDE could be improved by learnable hash functions. [32] focuses on the Frank-Wolfe optimization algorithm. In particular, [32] preprocess the vertices of the weight space in hash tables. Next, given the current weight, instead of computing it with all vertices, we only need to compute with near neighbor vertices and choose one as the next direction. [30] proposes parallel memory writing algorithms for the sparsified gradients in the data-parallel distributed training and provide up to $3.52\times$ speedups.

Efficient On-device Training in FL: There are two major techniques for improving the on-device efficiency of FL. The first technique is named partial variable training (PVT) [33, 25]. PVT aims at freezing a fraction of trainable parameters when we train models on the client devices. For instance, we could freeze some of the fully-connected layers and only perform federated optimization on the other parts of the model. [25] focuses on saving the communication cost of transferring model gradients. [33] is also trying to save the on-device model size and memory for intermediate results. Meanwhile, we observe some computation saving in the backpropagation. Another technique is called federated dropout (FedDrop) [3, 9]. The FedDrop randomly selects a subset of neurons from the model and sends it to the client for training. Although FedDrop saves the on-device computation and memory, the nature of randomness would cause an accuracy gap between the FedDrop and original training when we increase the sparsity. The major reason behind this phenomenon is that FedDrop's random sampling is not adaptive to the status of input embeddings. For instance, it is shown that the neurons with large inner products to input embedding should be a more important example in the output layer. As a result, the missing of these neurons would lead to slower convergence.

3 Method

In this section, we introduce our hashing algorithms for sparse federated learning in wide output layer. We start with a formal introduction of hash-based sampling. Next, we propose a sparse FL scheme using hashing.

3.1 Hash-based Sampling in Neural Network

In this section, we present how to use hash-based Sampling [26, 31, 7] in the training of neural network. We start with introducing a simple yet effective LSH function, namely SimHash [4].

Definition 1 (SimHash). *Let K denote the number of hash bits. Let $A \in \mathbb{R}^{K \times d}$ denote a random matrix where each entry is drawn i.i.d from normal distribution $\mathcal{N}(0, 1)$. Given an input vector $x \in \mathbb{R}^d$, we define the SimHash function $h : \mathbb{R}^d \to \mathbb{R}^k$ as*

$$h(x) = \textsf{sign}(Ax),$$

where $\textsf{sign}$ is an element-wise sign function that set nonzero values to 1 and other values to 0. Moreover, we show that for any two vectors $x, y \in \mathbb{R}^d$,

$$\Pr[h(x) = h(y)] = (1 - \frac{\theta_{xy}}{\pi})^K,$$

where θ_{xy} is the angle between x and y.

The SimHash's definition (see Definition 1) suggests that if two vectors are close in angle, with high probability they would have the same hash code. Moreover, previous work suggests that with a pair of asymmetric transforms applied on x and y [24], respectively, the collision probability $\Pr[h(x) = h(y)]$ would be monotonic to the inner product $x^\top y$. Taking advantages of this property, the hash-based sampling algorithm for a linear layer can be summarized as below:

1. Given a weight matrix $W \in \mathbb{R}^{d \times m}$, extract each column W_i from w and compute $h(W_i)$. Build a hash table that allocates W_is with the same hash code in a bucket.

2. Given a batch of embedding $X \in \mathbb{R}^{n \times d}$, for each row x_j in X, compute $h(x_j)$ and lookup the W_is that has the same hash code with $h(x_j)$. Next, we take the union of the retrieved W_is and write it as matrix W_{select}. Finally, we subsample on W_{select} with fix sparsity ratio and compute $X W_{\text{select}}$ for forward/backward propagation.

In practice, we use L hash tables and take the union of weight columns retrieved by each hash table. Noted that both K and L are tuning parameters. For an input batch of embedding X, hash-based sampling could return a sub-matrix W_{select} that the inner product between each row in X and each column in W_{select} may incur large inner product. In LOS, W_{select} represents the neurons that may have larger logits with X. In the practical setting, we may sub-sample on the columns of W_{select} or randomly add more columns to W_{select} so that we can fix the sparsity budget.

3.2 A Scheme of Sparse FL

In this section, we design a server-client scheme for sparse FL in LOS. As introduced in Section 3.1, hash-based sampling could select the neurons that may have large logits in the LOS. However, the maintenance of hash tables and the preprocessing of neurons may generate extra computation overhead. In fact, the computation in hashing the neurons should be carefully handled by smart scheduler in centralized training [6]. In our work, we take a FL view of this procedure and argue that the computation overhead can be reduced by the powerful computation resources in the server. Specifically, we introduce our scheme as below:

1. **Hash table maintenance:** The server uses SimHash (see Definition 1) and preprocesses the columns of the weight W in the output layer in hash table. The server refreshes the hash table after each round.

2. **Client initialization:** When a new client comes, the server sends the hash function and the weights of layers before the output layer to the client. The client performs forward pass and generate embedding vectors of its own data.

3. **Client hashing:** The client hashes the embedding using the received hash function and generates a set of bucket locations in the hash table.

4. **Neuron Retrieval:** The client transfers the bucket locations to the server and looks up the neurons of output layer in the corresponding buckets.

5. **On-deivce training:** The client receives the lookup-ed neurons and performs forward and backward computation.

6. **Aggregation:** The client passes the model updates such as gradients back to the server for aggregation.

The advantages of the proposed scheme can be summarized as: (1) the client device does not have to maintain the hash tables, which reduces the computation overhead in preprocessing neurons during the centralized training, (2) the client only lookups a subset of parameters in the output layer, which reduces the communication cost and on-device model memory, (3) the client trains on neurons that may have higher logits in the output layer, which served as an effective negative sampling for faster convergence. Note that we could use the FedSelect [5] to look up neurons with privacy protection.

3.3 Improving Model Capacity in Fixed Budget

As shown in the previous sections, our sparse FL scheme with hashing reduces the on-device parameter size for the last output layer. For a SoC with fixed hardware memory budget, we could use the saved space to increase the trainable parameters in other parts of the model to have better performance. We suggest two major directions: (1) increase the hidden dimension in both embedding and linear layer for better feature representation, (2) add more attention blocks [27] or linaer layers for better feature mixing. In the experiment section, we will discuss how these two directions would help us improve the empirical performance of on-device FL.

4 Experiment

In this section, we introduce an empirical evaluation for the proposed sparse FL training scheme in LOS with hashing. We start with introducing the next word prediction task we focus on. Next, we

Table 1: Parameter Size of Transformer Model for Stackoverflow Dataset. We also include the percentage of token embedding (ouput layer) in the model.

Emb. Dim	FFN. Dim	Attn. Size	Emb. Size (10K)	Emb. Size (80K)
96	1536	330K	960K (49.2%)	7.68M (88.5%)

introduce the models we evaluate. Finally, we present the experimental results with abalation study. We also provide a visualization of hash tables in Appendix A.

4.1 Settings

Dataset. We evaluate the proposed sparse FL scheme on the next word prediction task using Stack Overflow (SO) dataset. The SO dataset contains 342477 training clients. The total training example size is 135M. The SO dataset has 38758 clients for validation with dataset size 16M In the next word prediction setting, we take the first 256 sentences and truncate each sentence to a sequence length 20. We aim to predict the next word given the previous context words. It is standard to set the vocabulary size to 10K by taking the most frequent words from the training data. In our paper, we also extend the vocabulary size to 80K since larger vocabulary has larger word coverage.

The Transformer Model. In this paper, we study the performance of Transformer model. We profile the parameter size of transformer models in Table 1. In the model, we set the token embedding size as 96. We also set the hidden dimension of the Q, K, V layer in attention as 96. For the FFN dimension in attention block, we set it to 1536. There would be 330K parameters for each attention blocks. But the embedding table size would be 960K for 10K vocabulary and 7.68M for 80K vocabulary. In this paper, we shared the weights between the embedding and the last output layer so that the largest parameter tensor in the model is the embedding table. In this case, if we train the full model on each client, we have to send all the embedding tables to the client so that they can use them for output layer. On the contrary, if we could perform sparse training on the output layer by selecting a subset of neurons, we only need to send a subset of embeddings from the embedding table to the client. It is obvious that this scheme would save the transmission of the largest weight tensor.

Parameters. In the federated optimization, we use SGD as the client optimizer and Adam as the server optimizer following FedAdam approach introduced in [21]. For the Adam optimizer in the server, we vary the epsilon between 10^{-3} and 10^{-4}. We also perform a grid search on server learning rate set $\{10^{-1}, 10^{-1.5}, 10^{-2}\}$ and client learning rate set $\{10^{-1}, 10^{-1.5}, 10^{-2}\}$. The training steps and rounds follow the same setting as [29]. We chose the K and L shown in Section 3.1 from $\{2, 4, 6, 8\}$. For the evaluation metrics, we use the accuracy with the out-of-vocabulary, padding, EOS and BOS tokens masked.

4.2 Results in Sparse FL

To start with, we would like to evaluate the performance of our hash-based sampling in the output layer. Specifically, we would like to answer the following question: does hash-based sampling achieves better accuracy than random sampling in the training in LOS with different sparsity? Here we conduct an experiment on the Stack Overflow dataset, we vary the sparsity level and compare the hash-based sampling with random sampling. In Figure 1, we present the evaluation accuracy versus the actual computed parameters. For each parameter, we repeat the experiment for 10 times and plot the average accuracy and 95% confidence interval. As shown in the figure, if we fix the computed parameter, hash-based sampling is able to outperform random sampling with better final accuracy. Moreover, we show that, with above 30% of the parameters, the hash-based sampling is able to be less than 0.05% full training accuracy. In the next section, we would like to show how to use this observation for better on-device training accuracy.

4.3 Model Improvement in Fixed Budget

In this section, we study how to improve the model accuracy with a fix parameter. Specifically, we would like to answer the following question: does the on-device parameters saving in the output layer help us improve the model by adding parameters in other parts? Here we use the parameter

Figure 1: Evaluation accuracy versus the computed parameters in the output layer. Here the percentage of the computed parameter represents the sparsity level in the training. Left: vocabulary 10K, Right: vocabulary 80K. Note that the red line indicates the training accuracy if we compute on all the parameters in the output layer.

Table 2: Model accuracy in fix parameter budget. Here Params. represent the total number of parameters for the model. Vocab. represents the vocabulary size.

Emb. Dim	LOS Parameters	Sparse Approach	Vocab.	Params.(M)	Eval. Acc.	Test. Acc.
96	100%	Full	10K	1.92	23.45±0.04	24.29±0.03
128	30%	Random	10K	1.71	23.67±0.22	24.04±0.17
128	30%	Hashing	10K	1.71	**23.84**±0.09	**24.49**±0.08
96	100%	Full	80K	8.65	23.41±0.02	24.10 ±0.02
256	30%	Random	80K	8.48	23.03±0.33	23.76±0.31
256	30%	Hashing	80K	8.48	**24.04**±0.10	**24.46**±0.09

size of the full transformer model described in Section 4.1 as our budget. We would like to apply sparse training in the output layer while increasing the embedding dimension so that we could get closer but not exceed the parameter size budget. Moreover, with the knowledge from Section 4.2, we only keep 30% of the parameters in the output layer. In Table 2, we present the results. For vocabulary size 10K, if we use hash-based sampling with 30% compute parameters in the output layer and increase the embedding dimension to 128, we can outperform the original full model training accuracy in both evaluation and test dataset. Moreover, if we increase the vocabulary size to 80K, the improvement of hash-based sampling would be enlarged. With the same 30% parameters, while the random sampling cannot outperform the original model's results by increasing the embedding dimension to 256, hash-sampled sampling could achieve it with an accuracy boost. These experiments validate that our hash-based sparse FL scheme is able to improve the model performance without increasing the on-device parameter size.

5 Conclusion

In this paper, we propose a sparse federated learning (FL) scheme using hash-based adaptive sampling algorithm. We argue that during the FL training of deep neural networks in large output space, we can sample a subset of neurons in the output layer and perform forward and backward propagation on these neurons only. Moreover, we introduce a hash-based adaptive sampling approach in the neuron sampling for FL. We pre-index the neurons of the output layer in hash tables. Next, given the input embedding to the output layer, we could look up its near neighbor neurons from hash tables for the sparse training. Furthermore, we introduce a sparse FL scheme based on this hash-based sampling approach. In our scheme, the server takes over the neuron indexing and maintains the hash tables, while the client only maintains a subset of neurons in the last layer through hash table lookups. In this way, we show via extensive experiments that we could use around 30% parameters in the last layer and obtain the same final accuracy as full parameter training. We also show that with our approach, we could perform sparse training in the output layer and use the saved parameters to improve the model capacity in embedding and fully-connected layers. This design leads us to better on-device FL accuracy with the same parameter budget.

References

[1] Yoshua Bengio and Jean-Sébastien Senécal. Adaptive importance sampling to accelerate training of a neural probabilistic language model. *IEEE Transactions on Neural Networks*, 19(4):713–722, 2008.

[2] Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

[3] Sebastian Caldas, Jakub Konečny, H Brendan McMahan, and Ameet Talwalkar. Expanding the reach of federated learning by reducing client resource requirements. *arXiv preprint arXiv:1812.07210*, 2018.

[4] Moses S Charikar. Similarity estimation techniques from rounding algorithms. In *Proceedings of the thiry-fourth annual ACM symposium on Theory of computing*, pages 380–388, 2002.

[5] Zachary Charles, Kallista Bonawitz, Stanislav Chiknavaryan, Brendan McMahan, et al. Federated select: A primitive for communication-and memory-efficient federated learning. *arXiv preprint arXiv:2208.09432*, 2022.

[6] Beidi Chen, Zichang Liu, Binghui Peng, Zhaozhuo Xu, Jonathan Lingjie Li, Tri Dao, Zhao Song, Anshumali Shrivastava, and Christopher Re. MONGOOSE: A learnable LSH framework for efficient neural network training. In *International Conference on Learning Representations (ICLR)*, 2021.

[7] Beidi Chen, Tharun Medini, James Farwell, Charlie Tai, Anshumali Shrivastava, et al. Slide: In defense of smart algorithms over hardware acceleration for large-scale deep learning systems. *Proceedings of Machine Learning and Systems*, 2:291–306, 2020.

[8] Wei-Ning Chen, Ayfer Özgür, and Peter Kairouz. The poisson binomial mechanism for secure and private federated learning. *arXiv preprint arXiv:2207.09916*, 2022.

[9] Gary Cheng, Zachary Charles, Zachary Garrett, and Keith Rush. Does federated dropout actually work? In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 3387–3395, 2022.

[10] Shabnam Daghaghi, Nicholas Meisburger, Mengnan Zhao, and Anshumali Shrivastava. Accelerating slide deep learning on modern cpus: Vectorization, quantizations, memory optimizations, and more. *Proceedings of Machine Learning and Systems*, 3:156–166, 2021.

[11] Mayur Datar, Nicole Immorlica, Piotr Indyk, and Vahab S Mirrokni. Locality-sensitive hashing scheme based on p-stable distributions. In *Proceedings of the twentieth annual symposium on Computational geometry*, pages 253–262, 2004.

[12] Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. In *International Conference on Learning Representations*, 2018.

[13] Chaoyang He, Songze Li, Jinhyun So, Xiao Zeng, Mi Zhang, Hongyi Wang, Xiaoyang Wang, Praneeth Vepakomma, Abhishek Singh, Hang Qiu, et al. Fedml: A research library and benchmark for federated machine learning. *arXiv preprint arXiv:2007.13518*, 2020.

[14] Peter Kairouz, H Brendan McMahan, Brendan Avent, Aurélien Bellet, Mehdi Bennis, Arjun Nitin Bhagoji, Kallista Bonawitz, Zachary Charles, Graham Cormode, Rachel Cummings, et al. Advances and open problems in federated learning. *Foundations and Trends® in Machine Learning*, 14(1–2):1–210, 2021.

[15] Tian Li, Maziar Sanjabi, Ahmad Beirami, and Virginia Smith. Fair resource allocation in federated learning. In *International Conference on Learning Representations*, 2019.

[16] Bill Yuchen Lin, Chaoyang He, Zihang Zeng, Hulin Wang, Yufen Huang, Mahdi Soltanolkotabi, Xiang Ren, and Salman Avestimehr. Fednlp: A research platform for federated learning in natural language processing. *arXiv preprint arXiv:2104.08815*, 2021.

[17] Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Artificial intelligence and statistics*, pages 1273–1282. PMLR, 2017.

[18] Tharun Kumar Reddy Medini, Qixuan Huang, Yiqiu Wang, Vijai Mohan, and Anshumali Shrivastava. Extreme classification in log memory using count-min sketch: A case study of amazon search with 50m products. *Advances in Neural Information Processing Systems*, 32, 2019.

[19] Stephen Merity, Nitish Shirish Keskar, and Richard Socher. Regularizing and optimizing lstm language models. *arXiv preprint arXiv:1708.02182*, 2017.

[20] Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. Squad: 100,000+ questions for machine comprehension of text. *arXiv preprint arXiv:1606.05250*, 2016.

[21] Sashank J Reddi, Zachary Charles, Manzil Zaheer, Zachary Garrett, Keith Rush, Jakub Konečnỳ, Sanjiv Kumar, and Hugh Brendan McMahan. Adaptive federated optimization. In *International Conference on Learning Representations*, 2020.

[22] Nicola Rieke, Jonny Hancox, Wenqi Li, Fausto Milletari, Holger R Roth, Shadi Albarqouni, Spyridon Bakas, Mathieu N Galtier, Bennett A Landman, Klaus Maier-Hein, et al. The future of digital health with federated learning. *NPJ digital medicine*, 3(1):1–7, 2020.

[23] Tara N Sainath, Yanzhang He, Arun Narayanan, Rami Botros, Weiran Wang, David Qiu, Chung-Cheng Chiu, Rohit Prabhavalkar, Alexander Gruenstein, Anmol Gulati, et al. Improving the latency and quality of cascaded encoders. In *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 8112–8116. IEEE, 2022.

[24] Anshumali Shrivastava and Ping Li. Improved asymmetric locality sensitive hashing (alsh) for maximum inner product search (mips). *arXiv preprint arXiv:1410.5410*, 2014.

[25] Hakim Sidahmed, Zheng Xu, Ankush Garg, Yuan Cao, and Mingqing Chen. Efficient and private federated learning with partially trainable networks. *arXiv preprint arXiv:2110.03450*, 2021.

[26] Ryan Spring and Anshumali Shrivastava. A new unbiased and efficient class of lsh-based samplers and estimators for partition function computation in log-linear models. *arXiv preprint arXiv:1703.05160*, 2017.

[27] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

[28] Sagar M Waghmare, Hang Qi, Huizhong Chen, Mikhail Sirotenko, and Tomer Meron. Efficient image representation learning with federated sampled softmax. *arXiv preprint arXiv:2203.04888*, 2022.

[29] Jianyu Wang, Zachary Charles, Zheng Xu, Gauri Joshi, H Brendan McMahan, Maruan Al-Shedivat, Galen Andrew, Salman Avestimehr, Katharine Daly, Deepesh Data, et al. A field guide to federated optimization. *arXiv preprint arXiv:2107.06917*, 2021.

[30] Zhuang Wang, Zhaozhuo Xu, Xinyu Wu, Anshumali Shrivastava, and TS Eugene Ng. Dragonn: Distributed randomized approximate gradients of neural networks. In *International Conference on Machine Learning*, pages 23274–23291. PMLR, 2022.

[31] Zhaozhuo Xu, Beidi Chen, Chaojian Li, Weiyang Liu, Le Song, Yingyan Lin, and Anshumali Shrivastava. Locality sensitive teaching. *Advances in Neural Information Processing Systems*, 34:18049–18062, 2021.

[32] Zhaozhuo Xu, Zhao Song, and Anshumali Shrivastava. Breaking the linear iteration cost barrier for some well-known conditional gradient methods using maxip data-structures. *Advances in Neural Information Processing Systems*, 34:5576–5589, 2021.

[33] Tien-Ju Yang, Dhruv Guliani, Françoise Beaufays, and Giovanni Motta. Partial variable training for efficient on-device federated learning. In *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 4348–4352. IEEE, 2022.

[34] Timothy Yang, Galen Andrew, Hubert Eichner, Haicheng Sun, Wei Li, Nicholas Kong, Daniel Ramage, and Françoise Beaufays. Applied federated learning: Improving google keyboard query suggestions. *arXiv preprint arXiv:1812.02903*, 2018.

[35] Haoran You, Chaojian Li, Pengfei Xu, Yonggan Fu, Yue Wang, Xiaohan Chen, Richard G Baraniuk, Zhangyang Wang, and Yingyan Lin. Drawing early-bird tickets: Toward more efficient training of deep networks. In *International Conference on Learning Representations, 2019*, 2020.

[36] Binhang Yuan, Cameron R Wolfe, Chen Dun, Yuxin Tang, Anastasios Kyrillidis, and Chris Jermaine. Distributed learning of fully connected neural networks using independent subnet training. *Proceedings of the VLDB Endowment*, 15(8):1581–1590, 2022.

Appendix

A   Visualization of the Hash Table

In this section, we visualize the bucket in the hash table we built for Stack Overflow dataset. We showcase the tokens of three buckets from a hash table as below. Here we set the $K = 4$ (see Section 3.1).

1. java, python, ruby, spring, tomcat, gcc, swift, println, opencv, openssl, activerecord, gdb, clang, webforms, rpc, i18n, nunit, llvm, msvc, apt, filenotfoundexception, openjdk, teardown, rejection

2. problems, ways, issues, questions, great, solutions, tutorials, major, bugs, conventions, viable, disadvantages, strategies, interactions, measures, useful, considerable, findings, documentations, sensors, reaction, brilliant, orthogonal

3. change, go, define, modify, ask, perform, manage, determine, accept, reset, combine, maintain, bring, evaluate, optimize, customize, jump, automate, preserve, terminate, associate, buy, pip, synchronize, eat, mutate, assemble, recalculate, optimise, dotnet, check-in

We observe that the first bucket is a programming language bucket. It contains "java", "python" and related platforms such as "opencv". In the second bucket, we observe that there are similar tokens such as "great", "brilliant" and "useful". Also the "issue" means similar to "questions" and "bugs". In the third bucket, there is a set of synonyms, such as "change", "modify" and "reset." To sum up, the hash table is able to group the relative tokens in the same bucket and we can look them up with a query.