# Memorization or Extraction? Auditing LLM-Based Recovery of Scientific Assumptions

## Abstract

We audit whether benchmarks for LLM-based recovery of scientific assumptions measure corpus-grounded extraction or pretraining memorization. Using author-defined targets for 10 historical AI breakthroughs (frozen 4-case protocol plus 6 post-hoc stress cases) and a "field-wide paradigmatic assumption" prompt, GPT-4o's top-10 extractions cover the target in 6/10 cases under a generous any-of-top-$K$ criterion—an upper bound that a 10-rater study corroborates for only $\sim$0.19 of sampled top-ranked pairs (human–rule $\kappa$=0.70, $\alpha$=0.634). Controlled stress tests structure the diagnosis: a no-corpus control (field name only) still scores 4/4 on the primary shifts (memorization dominates), while a wrong-corpus control collapses to 0/12 across all $4\times3$ cross-pairings (corpus *can* be causally read); a five-LLM canonical sweep (GPT-4o 4/4, Qwen 2/4, Claude 1/4, Llama-3.1 1/4, Mistral 0/4) shows the gap is model-specific format compliance, not closed-vs-open; a Min-K% Prob cross-check actually mis-ranks synthetic non-members as more contaminated than real pre-shift papers, motivating the behavioral framing; and synthetic/niche controls are mixed (causal in 1 of 3 synthetic scenarios, one shows corpus *harm*). We release an *audit kit* — five factorable controls (no-corpus, wrong-corpus, pair-level precision, $\geq$2-LLM, multi-seed; $\sim$\$15) — as a reusable benchmark-validity probe, with all artifacts anonymized.

## 1 Introduction

LLMs are increasingly used to mine scientific literature: extracting latent claims, locating research gaps, and surfacing the assumptions that papers take for granted (Wang et al., 2024; Baek et al., 2025; Si et al., 2025; Pu et al., 2024; Hu et al., 2024; Kargupta et al., 2026). Such systems raise an evaluation question that NLP research has been sharpening through work on benchmark contamination and pretraining-data leakage (Roberts et al., 2023; Golchin and Surdeanu, 2024; Magar and Schwartz, 2022; Sainz et al., 2023; Shi et al., 2024; Duan et al., 2024; Oren et al., 2024; Dong et al., 2024): when an LLM correctly identifies a finding from a relevant corpus, did it *extract* that finding from the text we provided, or did it *recall* it from pretraining? This knowledge-vs-context confound is endemic to any LLM-based scientific text mining benchmark whose targets are well-attested in pretraining data.

We study the confound in a concrete instantiation: *retrospective assumption recovery*, where an LLM is asked to identify, from pre-breakthrough literature, the foundational assumption that the breakthrough later violated. Three landmark AI advances each violated a previously-uncontested assumption: Transformers (Vaswani et al., 2017) broke the assumption that sequential processing requires recurrence; diffusion models (Ho et al., 2020) broke the assumption that generation requires adversarial training; ViT (Dosovitskiy et al., 2021) broke the assumption that vision requires convolutions. If these assumptions were so central to their fields, can they be identified retrospectively from pre-shift literature? And if so, does a successful identification reflect corpus extraction, or pretraining recall?

This paper investigates these questions through a controlled benchmark. We find that a simple prompt framing change — asking for "field-wide paradigmatic assumptions" rather than paper-specific claims — substantially improves assumption recovery (§5.2). But we also find that a no-corpus control achieves comparable results (§5.3), revealing that standard retrospective benchmarks on famous breakthroughs are deceptively easy to solve via memorization. Both findings are important: the prompt framing effect is real and measurable, but its practical value requires evaluation on cases where pretraining knowledge is insufficient.

**Contributions.**

1. A *benchmark for assumption recovery* — 10 historical AI breakthroughs with author-defined target assumptions (initially frozen for 4 primary cases, then extended post-hoc), multiple negative controls, and all artifacts released.

2. A *diagnostic analysis* revealing that (a) field-wide prompt framing raises target similarity by +0.21 on $N = 3$ categories with corpus held fixed (a post-hoc comparison, not the pre-registered ablation, and not claimed to generalize); (b) the benchmark is largely solvable without corpus input on famous breakthroughs (no-corpus 4/4) yet collapses under a wrong-corpus control (0/12 across all $4 \times 3$ cross-pairings), so the model *can* integrate corpus content — though presence is neither necessary nor reliably beneficial (1 of 3 synthetic scenarios shows corpus harm); (c) results are highly model-sensitive across five LLMs (GPT-4o 4/4 / Qwen 2/4 / Claude 1/4 / Llama-3.1-8B 1/4 / Mistral 0/4); we hypothesise that model-specific format compliance with the matcher template plays a major role though raw capability differences cannot be fully isolated (App. P); (d) success is limited to explicitly stated assumptions; and (e) simple retrieval baselines are weaker (TF-IDF/BM25 2/4 vs GPT-4o 4/4), popularity does not predict recovery ($\rho = -0.64$), and confidence is not a useful selection signal (gap only 0.025).

3. An *honest characterization of limitations* — including the memorization confound, format-metric coupling, and the gap between retrospective recovery and prospective utility.

## 2   Related Work

**LLMs for scientific literature mining and idea generation.**   Recent systems apply LLMs to scientific discovery (see Shahhosseini et al., 2026 for a creativity-centered survey): AI Scientist (Lu et al., 2024) proposes end-to-end automated research pipelines; ResearchAgent (Baek et al., 2025) iteratively refines ideas using reviewer feedback; SciMON (Wang et al., 2024) retrieves inspirations from literature; IdeaSynth (Pu et al., 2024) supports iterative idea refinement via literature-grounded critique; Nova (Hu et al., 2024) generates ideas by iterative planning and retrieval; and Idea-Catalyst (Kargupta et al., 2026) abstracts research bottlenecks into domain-agnostic form for cross-domain inspiration. Si et al. (Si et al., 2025) show LLM-generated ideas are rated more novel but less feasible than expert ideas. These systems primarily *generate* ideas conditional on retrieved context; our work probes whether LLMs can *surface* the shared assumptions that retrieved contexts already presuppose. The Artificial Hivemind finding (Jiang et al., 2025) — that aligned LLMs converge onto homogeneous outputs — motivates explicitly surfacing those assumptions.

**Benchmark contamination.**   A growing body of NLP work documents how frontier LLMs memorize evaluation material during pretraining (Roberts et al., 2023; Golchin and Surdeanu, 2024; Magar and Schwartz, 2022; Sainz et al., 2023). More recent contamination-detection tools use membership-inference signals: Min-K% Prob (Shi et al., 2024) detects whether a text was in training by thresholding on the probability of its rarest tokens; Duan et al. (Duan et al., 2024) systematize MIAs for pretraining data; Oren et al. (Oren et al., 2024) provide statistical tests for benchmark contamination; Dong et al. (Dong et al., 2024) survey leakage detection across evaluation benchmarks. Where token-probability MIAs ask whether a specific text was seen during pretraining, our no-corpus and synthetic-literature controls (§5.3) ask the parallel *behavioral* question: does the benchmark score survive removing the corpus? The two methodologies are orthogonal — ours requires only black-box prompting and is applicable to API-only models — and we view them as complementary lenses on the same pretraining-data confound. We cross-validate our benchmark against Min-K% Prob on the same pre-shift corpora using 3 OSS models with token-logprob access (Appendix L): the token-level MIA actually *mis-ranks* synthetic GPT-generated non-member abstracts as *more* member-like than the real pre-2020 papers in all 3 models. This result is best read as a lower bound on MIA's discriminative power between GPT-generated and pre-2020 archival text *at this scale* — not a universal MIA-limitation claim — since the synthetic baseline is itself GPT-generated and shares stylistic distribution with the OSS models' pretraining data. The behavioral no-corpus control yields a clean uniform $4/4$ memorization signal at $N = 10$; the two contamination signals can therefore disagree, and on this benchmark the behavioral lens is direction-correct.

**TRIZ, computational creativity, and meta-science.**   TRIZ provides structured methodol-

ogy for overcoming contradictions (Altshuller, 1984) and has been coupled to LLMs for inventive ideation (Jiang and Luo, 2024); Boden's framework (Boden, 2004) distinguishes combinatorial, exploratory, and transformational creativity (Schapiro et al., 2025); Kuhn's paradigm shifts (Kuhn, 1962) describe how scientific frameworks change. Our extraction protocol targets the assumptions whose violation characterizes paradigm shifts, though the present paper establishes only that certain historically salient assumptions can be *recovered* under particular prompting conditions.

## 3 Method

The extraction protocol has a single validated component: a field-wide paradigmatic-assumption prompt run over a pre-shift paper corpus, producing confidence-ranked assumptions that are then compared (via embedding similarity) to an author-defined target assumption. The design is deliberately minimal. An optional TRIZ-inspired hypothesis-diversification step exists in our implementation but does not improve retrospective recall (Appendix I) and we do not include it in the main pipeline.

**Field-wide assumption extraction.** For each paper in the pre-shift corpus, a language model extracts up to 10 paradigmatic assumptions. The critical design choice is *field-wide paradigmatic framing*: the prompt instructs the model to identify beliefs shared across the entire subfield that the paper takes for granted — not the paper's own design choices. The prompt (Appendix B): (1) distinguishes field-wide paradigmatic assumptions from paper-specific details; (2) enforces "[X] is necessary/required/essential for [Y]" format; (3) categorizes into five types (architectural, training, data, theoretical, evaluation); and (4) contains *no few-shot examples* in the main results, reducing prompt-leakage concerns (a variant with examples is tested in ablation, §F).

Each assumption includes a text description, confidence score (0–1), and category label. For Claude extraction across 60 papers, this yields ~600 raw assumptions that cluster semantically into ~60 reoccurring themes (which the paper previously described, imprecisely, as "~90% redundancy"). We emphasize that this is *semantic* clustering: exact-string deduplication on the raw assumption text leaves nearly every extraction intact (e.g., GPT-4o

Table 1: Primary paradigm shifts and pre-shift corpora.

| Paradigm | Year | Year Guard | Target Assumption |
|---|---|---|---|
| Transformer | 2017 | $\leq$2016 | Recurrence is necessary for sequence modeling |
| Diffusion | 2020 | $\leq$2019 | Adversarial training for high-quality generation |
| ICL | 2020 | $\leq$2019 | Fine-tuning is necessary for task adaptation |
| ViT | 2020 | $\leq$2019 | Conv. layers are necessary for vision |

on 15 papers returns 147–150 unique strings out of ~150). The assumption-convergence claim therefore holds only after semantic normalization, and we report both statistics explicitly in Appendix A.

**Ranking.** Assumptions are ranked by extraction confidence. A multi-agent debate system (Advocate/Critic/Judge) was implemented for optional filtering in prospective evaluation (Appendix H).

## 4 Experimental Setup

**Protocol freeze.** The initial 4-primary-shift protocol (target assumptions, metrics, corpora, baselines) was frozen before experiments, recorded with a SHA-256 hash. The 10-case extension and additional diagnostics were developed post-hoc as stress tests and are reported transparently as such.

**Benchmark cases.** We evaluate on 10 historical AI breakthroughs spanning two classes: (i) *paradigm shifts*—Transformer (Vaswani et al., 2017), Diffusion (Ho et al., 2020), GAN (Goodfellow et al., 2014), ViT (Dosovitskiy et al., 2021), ICL (Brown et al., 2020)—and (ii) *methodological breakthroughs*—ResNet (He et al., 2016), BatchNorm (Ioffe and Szegedy, 2015), Dropout (Srivastava et al., 2014), Word2Vec (Mikolov et al., 2013), BERT (Devlin et al., 2019). The primary benchmark uses 4 shifts with 60-paper corpora; the main result uses GPT-4o with a clean prompt on 15-paper subsets across all 10 cases. Table 1 shows the 4 primary shifts.

For each breakthrough, target assumptions and 2–3 aliases were authored based on canonical descriptions from survey papers, frozen before extraction experiments. This is a limitation: independent annotation would strengthen validity. Corpora were collected from OpenAlex (Priem et al., 2022) with strict year guards and verified for zero leakage.

**Metrics.** *Primary:* Soft-Recall@$K$ — a candidate matches the target if cosine similarity (OpenAI text-embedding-3-small) $\geq$ 0.65 against

Table 2: Main results — GPT-4o clean prompt (no few-shot examples, 15 papers/paradigm). Rank = position in confidence-ordered extraction list.

| Paradigm | Year | Best Sim | Conf. Rank | R@5 | R@10 |
|---|---|---|---|---|---|
| **Transformer** | 2017 | 0.674 | **1** | ✓ | ✓ |
| **Diffusion** | 2020 | 0.759 | **2** | ✓ | ✓ |
| **ICL** | 2020 | 0.702 | **3** | ✓ | ✓ |
| **ViT** | 2020 | 0.676 | **5** | ✓ | ✓ |
| **BatchNorm** | 2015 | 0.727 | **7** | × | ✓ |
| **GAN** | 2014 | 0.657 | **10** | × | ✓ |
| ResNet | 2015 | 0.597 | >20 | × | × |
| Word2Vec | 2013 | 0.633 | >20 | × | × |
| Dropout | 2014 | 0.604 | >20 | × | × |
| BERT | 2018 | 0.544 | >20 | × | × |
| **Total** | | | | **4/10** | **6/10** |

Figure 1: Confound tree (top-down): the headline 6/10 with-corpus result is dominated by pretraining memorization (no-corpus 4/4 on primary shifts); corpus grounding is demonstrably causal only in one synthetic scenario; on niche cases corpus quality determines whether corpus helps; and cross-model comparison reveals severe format-compliance confound. Each leaf references a specific result in §5.3–§5.4.

Table 3: Diagnostic comparison on 4 primary shifts.

| Method | Trans. | Diff. | ICL | ViT | R@10 |
|---|---|---|---|---|---|
| Random | × | × | × | × | 0/4 |
| Heuristic | × | × | × | × | 0/4 |
| Vanilla LLM (single-call) | ✓ | × | × | × | 1/4 |
| SCAM (no TRIZ) | ✓ | ✓ | × | ✓ | 3/4 |
| Extraction only (Claude, no TRIZ) | ✓ | ✓ | × | ✓ | 3/4 |
| **Unbox (GPT-4o, clean)** | ✓ | ✓ | ✓ | ✓ | **4/4** |

any alias. A rule-based structured-matching simulation with two automated annotators (strict / moderate labelers operationalized as keyword-pattern rules; Appendix E) on 80 pairs yields inter-labeler $\kappa = 0.97$ and threshold 0.65 has perfect precision with moderate recall (F1 = 0.73) against that simulated consensus. We emphasize that these are automated labelers *simulating* human structured matching, not independent human annotators; an independent human-expert study is left for future work. *Secondary:* Mean Rank of the highest-similarity assumption.

**Baselines.** Random (sentence extraction), Heuristic (keyword matching), Vanilla LLM (single-call, same prompt), and SCAM (same prompt + corpus, 5-sample majority vote, no TRIZ).

## 5 Results

### 5.1 Main Result

Figure 1 summarizes the battery of controls that structure the paper: the headline with-corpus result is qualified by a no-corpus control that largely matches it on famous shifts, a synthetic-literature scenario where corpus grounding is causal, and a niche benchmark where corpus value depends on corpus quality. Table 2 then presents the main with-corpus numbers: GPT-4o with a clean prompt (no few-shot examples) on 15-paper subsets.

The protocol matches the target in the top-10 in **6/10 cases** (R@10 = 0.60) and top-5 in 4/10 (R@5 = 0.40). The 6 successes share a common property: their broken assumptions are widely and explicitly stated in the "X is necessary for Y" format. The 4 failures involve assumptions that are implicit, rarely articulated, or domain-specific in phrasing.

### 5.2 Ablations and Baselines

**Diagnostic method comparison.** Table 3 compares methods on the 4 primary shifts. Note: entries differ in model, corpus size, and prompt variant — this is diagnostic, not a controlled head-to-head.

SCAM (same prompt, 5-sample majority) and extraction-only (same prompt, no TRIZ, no majority voting) achieve identical recall on Claude (3/4), confirming the field-wide extraction prompt — not any downstream aggregation or transformation — is the validated component. The optional TRIZ transformation produces near-disjoint hypothesis framings (Jaccard < 0.01; Appendix I) but does not improve recall.

All entries in Table 3 are soft-scored at threshold 0.65 for comparability (`scripts/reevaluate_with_soft_matching.py`); the Vanilla LLM

Table 4: Prompt ablation (Soft-R@10, 3 primary shifts). Values: best cosine similarity.

| Condition | Prompt | Trans. | Diff. | ViT | Avg R@10 |
|---|---|---|---|---|---|
| A | Paper-specific | ✗ (.52) | ✗ (.65) | ✗ (.56) | 0.00 |
| B | Field-wide | ✓ (.80) | ✓ (.82) | ✓ (.76) | **1.00** |

Table 5: No-corpus memorization control (GPT-4o, 4 primary shifts).

| Condition | Trans. | Diff. | ICL | ViT | R@5 | Avg Sim |
|---|---|---|---|---|---|---|
| With corpus (15 papers) | ✓ | ✓ | ✓ | ✓ | 4/4 | 0.729 |
| No corpus, field name only | ✓ | ✓ | ✓ | ✓ | 4/4 | 0.755 |

Table 6: Corpus-alignment ablation (GPT-4o, clean prompt, seed=42). A *wrong* corpus does not merely fail to help — it actively destroys the recovery that pre-training alone (no corpus) achieves. The $4/4 \to 0/12$ collapse across all $4 \times 3$ cross-pairings is direct evidence that corpus content causally enters extraction.

| Condition | R@10 | Avg best sim |
|---|---|---|
| With corpus (aligned, 4 primary) | 4/4 | 0.729 |
| No corpus (field name, 4 primary) | 4/4 | 0.755 |
| Wrong corpus (12 cross-pairings) | **0/12** | **0.41** |

Table 7: Synthetic literature control: 3 fictional fields with planted assumptions.

| Fictional Field | With Corpus | No Corpus |
|---|---|---|
| Chromatic Signal Processing | **rank 1** (0.954) | rank 1 (0.742) |
| Neuromorphic Memory Arch. | **rank 2** (0.958) | ✗ rank 27 (0.683) |
| Adaptive Topology Networks | ✗ rank 32 (0.707) | rank 7 (0.726) |

single-call baseline is $0/4$ under its native exact match and $1/4$ under soft match (Transformer succeeds via "Sequential processing requires recurrence", sim 0.703).

**Prompt ablation.** We compare field-wide vs paper-specific prompt framing on 3 primary shifts (Claude, 60-paper corpora):

Field-wide framing achieves 3/3 vs 0/3, with +0.21 average similarity improvement (95% CI: [0.17, 0.28]). The corpus files are identical between conditions, so the +0.21 reflects prompt framing alone on these $N = 3$ categories; this is a post-hoc comparison (not the pre-registered ablation set, which targeted TRIZ operators) and we do not claim it generalizes beyond the tested categories.

**SCAM baseline.** SCAM (5-sample majority vote, same prompt, no TRIZ) achieves identical recall to Unbox (0.75 each on 4 primary shifts with Claude). This confirms extraction protocol design is the validated component.

### 5.3 Memorization and Negative Controls

**No-corpus control.** We run GPT-4o with the clean prompt but *no paper text* — only the field name:

The no-corpus condition achieves **4/4 recall** with *higher* average similarity (0.755 vs 0.729), confirming that GPT-4o retrieves known breakthroughs from pretraining knowledge. The corpus provides a ranking benefit (avg confidence rank 2.75 with corpus) but is not necessary for recovery on well-known shifts.

**Wrong-corpus control.** To probe whether corpus content actively steers extraction or is simply ignored when present, we extract with each primary target against a *different* field's corpus, exhaustively enumerating all 12 cross-pairings ($4 \times 3$; scripts/run_wrong_corpus_12.py, 15 papers

each, GPT-4o clean prompt, seed=42). **All 12 pairings fail to recover the target**: R@10 = 0/12, best similarity 0.37–0.46 (avg 0.41), conf-rank = undefined (no candidate clears threshold) in every pair — well below both the with-corpus baseline (4/4, avg sim 0.729) and the no-corpus baseline (4/4, avg sim 0.755). The model does not simply rank pretraining knowledge above corpus content: when the corpus is *wrong*, the corpus actively wrenches extraction away from the correct target. Combined with the synthetic-literature result (Scenario 2: rank 2 with corpus vs rank 27 without), this confirms that the model integrates corpus content rather than retrieving solely from pretraining. The headline "memorization dominates" framing must therefore be qualified: pretraining-only retrieval succeeds on famous breakthroughs precisely *because* the supplied corpus is aligned with what the model already knows. Substitute a misaligned corpus and the extraction collapses. The contrast in Table 6 is, with synthetic Scenario 2, the cleanest causal evidence in the paper: *absence* of a corpus leaves pretraining recall intact (no-corpus 4/4), but *presence* of a wrong corpus overrides it (wrong-corpus 0/12). All 12 pairings are individually consistent (no single pair drives the result; per-pair sims in experiments/wrong_corpus_12/summary.json).

**Synthetic literature control.** To eliminate memorization entirely, we generate synthetic abstracts for 3 fictional fields with planted target assumptions:

In Scenario 2, corpus input is essential: no-corpus fails (rank 27) while with-corpus succeeds

(rank 2, sim 0.958). This is the cleanest single-scenario evidence that extraction can recover assumptions *from corpus content* rather than pretraining memory, since the fictional field has no pretraining history. Scenarios 1 and 3, however, show no effect and *corpus harm* respectively (Table 7): the causal-evidence base is $N=1$ and we therefore claim only that corpus content *can* be causal, not that it reliably helps.

**Niche subfield control.** We test on 8 less-famous breakthroughs (MoE, Neural ODE, Lottery Ticket, SimCLR, LoRA, FlashAttention, DPO, KAN). With-corpus extraction achieves 1/8 R@10 (Neural ODE at rank 10); no-corpus achieves 2/7 (Lottery Ticket at rank 9, LoRA at rank 2; KAN no-corpus incomplete due to quota exhaustion). The aggregate difference is not statistically significant (one-sided Fisher's exact $p \approx 0.5$ on the 7 complete paradigms), so we do not claim corpus-grounding is uniformly counterproductive. The pattern is mixed: corpus helps on the single genuinely niche case (Neural ODE — continuous-depth networks, less likely memorized), but for moderately well-known niche cases (LoRA, Lottery Ticket) no-corpus retrieves the target at much higher rank while with-corpus buries it at rank 19 or 75, likely because OpenAlex keyword search ingests adjacent-but-wrong papers that dilute extraction. For flash-attention and DPO both conditions fail. The niche benchmark therefore does not refute corpus value; it documents that corpus value depends on both assumption obscurity and corpus quality.

## 5.4 Diagnostic Analyses

**Retrieval baselines.** TF-IDF and BM25 (filtering corpus sentences for *necessary/required/essential*) each achieve 2/4 on primary shifts, succeeding where the target is lexically explicit (Diffusion, ICL) but failing where it is implicit (Transformer, ViT). GPT-4o achieves 4/4, with the advantage concentrated on sparsely stated assumptions.

**Popularity–performance correlation.** Spearman $\rho$ between citations and best similarity is $-0.636$: ResNet ($\sim$200k citations) and BERT ($\sim$80k) fail, while less-cited breakthroughs succeed. Recovery depends on whether the target is explicitly stated in "X is necessary for Y" format, not on fame.

**Error analysis.** For the 4 failures (ResNet, Word2Vec, Dropout, BERT): ResNet's target concept (skip connections/gradient flow) appears in zero of 150 extractions — an extraction-coverage failure. BERT's top-1 extraction is about particle physics, revealing OpenAlex corpus contamination. Failures cannot be detected from surface statistics (assumption length, confidence are near-identical to successes). Each of the 4 failures is attributable to a distinct, audit-kit-detectable confound (Appendix N): coverage gap (ResNet), domain phrasing (Word2Vec), implicit assumption (Dropout), and corpus contamination (BERT).

**Confidence calibration.** Across 6 successful paradigms, the confidence gap between top-1 (avg 0.992) and the hit rank (avg 0.967) is only 0.025 — confidence cannot discriminate targets from distractors.

**Cross-LLM extension (open-source).** To probe whether the GPT-4o vs Claude gap (§G) reflects model-specific format compliance or a more general closed-vs-open divide, we extend the comparison to three open-source 7–8B models (Llama-3.1-8B-Instruct, Qwen-2.5-7B-Instruct, Mistral-7B-Instruct-v0.3) run locally via vLLM under *identical* prompt, 15-paper subsets, temperature=0, and seed=42 (`scripts/run_oss_llm_extraction.py`; canonical evaluation via the same OpenAI text-embedding-3-small / 0.65-threshold pipeline). Table 8 reports the canonical numbers. The five-model spread (GPT-4o 4/4 down to Mistral 0/4) further fragments the closed-vs-open framing: Claude (closed) and Llama-3.1-8B (open) both land at 1/4, Qwen-2.5-7B (open) at 2/4 is the strongest open-source comparator, and Mistral-7B (open) at 0/4 is the weakest. The gap is therefore not strictly closed-vs-open. We hypothesise that model-specific format compliance with the matcher's "X is necessary for Y" template plays a major role, but raw capability, instruction-tuning quality, and contamination level all fit the data; this experiment alone cannot isolate format compliance from these alternatives. We address this directly with a format-relaxed matcher ablation in Appendix G.

**Human validation of rule-based matching.** We validate the embedding-similarity matcher against 10 independent, ML-literate raters blind to condition and rank, on the pre-registered 72-pair instrument (+8 blind attention checks;

Table 8: Cross-LLM recall on the 4 primary shifts under matched prompts and decoding (same canonical pipeline: text-embedding-3-small, threshold 0.65, confidence-ordered ranks).

| Model | Trans. | Diff. | ICL | ViT | R@5 | Avg Sim |
|---|---|---|---|---|---|---|
| GPT-4o (closed) | ✓ | ✓ | ✓ | ✓ | 4/4 | 0.703 |
| Claude Sonnet 4 (closed) | ✗ | ✓ | ✗ | ✗ | 1/4 | 0.658 |
| Llama-3.1-8B-Instruct (open)[†] | ✗ | ✗ | ✗ | ✓ | 1/4 | 0.563 |
| Qwen-2.5-7B-Instruct (open) | ✗ | ✗ | ✓ | ✓ | 2/4 | 0.705 |
| Mistral-7B-Instruct-v0.3 (open) | ✗ | ✗ | ✗ | ✗ | 0/4 | 0.581 |

[†]Llama-3.1-8B weights accessed via the NousResearch un-gated mirror of `meta-llama/Llama-3.1-8B-Instruct` (identical weights).

`scripts/sample_annotation_pairs.py`, seed 42). Raters score 1–5; the *pre-registered* binary match is score $\geq 4$. The study is internally reliable: Krippendorff's $\alpha = 0.634$ (interval; Krippendorff, 2018), mean pairwise Cohen's $\kappa = 0.555$ (binary; Cohen, 1960), and 0.99 attention-check pass (79/80). Applying the *same* rule-based matcher (TEXT-EMBEDDING-3-SMALL, cosine $\geq 0.65$) to the identical 72 pairs, human-majority vs. rule-based agreement is Cohen's $\kappa = 0.702$ (substantial; 0.92 raw agreement). The matcher is *not* more lenient than humans — it accepts slightly fewer pairs (rule 0.14 vs. human 0.19 match rate) — so the human study *substantiates* the matcher and replaces the earlier program-vs-program $\kappa = 0.97$ with a genuine human $\kappa = 0.702$. Per-condition, however, the matcher and humans disagree on direction: the matcher rates no-corpus pairs marginally above with-corpus (rule 0.21 vs 0.17, consistent with the memorization confound), while humans rate with-corpus pairs *twice* as high as no-corpus (humans 0.33 vs 0.17). Aggregate agreement remains substantial ($\kappa=0.70$), but the human pair-level signal — taken on its own — supports corpus benefit at this sample even though the matcher does not; we report both rather than collapse them. The honest caveat is at the *aggregate* level: both humans and the matcher mark only $\sim$0.19 of sampled top-ranked extractions as pairwise matches, whereas headline Recall@K counts a paradigm recovered if *any* of the top-$K$ clears threshold. The headline is thus a generous *recovery* criterion, not pairwise precision; the relative confound structure (the paper's contribution) is unaffected. See Table 9.

## 5.5 Statistical Summary

**Fisher's exact test.** GPT-4o 4/4 vs Vanilla LLM 1/4 on primary shifts: one-sided $p = 0.07$, not significant at $\alpha = 0.05$. The small $N$ inherently limits power.

Table 9: Human validation (10 independent raters, 72 stratified pairs +8 attention checks; pre-registered binary match = score $\geq 4$). Human-majority vs. rule-based agreement is substantial ($\kappa = 0.702$); the matcher is not more permissive than humans.

| Quantity | Value |
|---|---|
| Krippendorff's $\alpha$ (interval, 1–5) | 0.634 |
| Mean pairwise Cohen's $\kappa$ (inter-human, binary) | 0.555 |
| Attention-check pass rate (score $\leq 2$) | 0.99 |
| Human vs. rule Cohen's $\kappa$ (binary, 72 pairs) | 0.702 |
| Human vs. rule raw agreement | 0.92 |
| Rule match rate / human match rate | 0.14 / 0.19 |
| Human match rate — with-corpus | 0.33 (8/24) |
| Human match rate — no-corpus | 0.17 (4/24) |
| Human match rate — Claude | 0.08 (2/24) |

**Bootstrap / Wilson CIs.** GPT-4o R@10 $= 6/10$ has Wilson 95% CI $[0.31, 0.83]$; R@5 $= 4/10$ has Wilson 95% CI $[0.17, 0.69]$; avg best similarity (all 10 paradigms) $= 0.657$, bootstrap 95% CI $[0.619, 0.695]$; ablation B–A difference $+0.217$ CI $[0.170, 0.280]$. The headline is therefore a point estimate; formal hypothesis testing is reserved for the wrong-corpus $4/4\rightarrow0/12$ collapse (Bernoulli all-zero against an expected 0.4–0.8).

**Effect size.** Prompt framing yields Cohen's $d \approx 3.80$ on three categories — large but unstable given $N = 3$.

**Threshold robustness.** The 6 successes have similarities 0.657–0.759 (above 0.65); the 4 failures have 0.544–0.633 (below). The clean separation supports the 0.65 threshold for TEXT-EMBEDDING-3-SMALL; Appendix K reports calibrated thresholds for TEXT-EMBEDDING-3-LARGE (0.50) and `all-MiniLM-L6-v2` (0.65), under which primary R@10 stays at $4/4$ and all-paradigm R@10 spans 6–8/10 across the three embedders.

**Audit-kit recommendations.** The five controls used in this paper — (i) a no-corpus baseline, (ii) at least one wrong-corpus pairing, (iii) pair-level precision alongside any-of-top-$K$ recall, (iv) $\geq 2$ cross-LLM models, and (v) multi-seed or sensitivity-range reporting for closed-model APIs — factor cleanly and run together for $\sim\$15$ of API credits on our 4 primary shifts. We recommend them as a default validity probe for LLM-based scientific-text-mining benchmarks (full per-item rationale and decision rules in Appendix J; release scripts in scripts/; structural cross-domain transfer outlined in Appendix M).

## 6 Discussion

The central tension in our findings is between a genuine prompt-framing effect and pervasive memorization confounds. Field-wide framing produces a consistent +0.21 similarity improvement, and GPT-4o matches 6/10 targets. Yet the no-corpus control (4/4 on primary shifts) shows that for well-known breakthroughs, the model can surface assumptions from pretraining alone. Two controls resolve the tension in the other direction: the wrong-corpus ablation (4/4 with no corpus or an aligned corpus, but 0/4 under a misaligned corpus; Table 6) and synthetic Scenario 2 (rank 2 with corpus vs rank 27 without) together show corpus content *can* causally enter extraction — the model can read the corpus, though it does not reliably help (the wrong-corpus result is single-run on 4 pairings, and only 1 of 3 synthetic scenarios is a clean causal case; another shows corpus harm).

**Memorization confound.** The 10 primary breakthroughs tested are among the most famous in AI. We cannot fully disentangle corpus-based extraction from pretraining retrieval. The niche control (1/8 with-corpus, 2/7 no-corpus) shows that on less-memorized cases the corpus sometimes helps (Neural ODE) and sometimes hurts (LoRA, Lottery Ticket where OpenAlex retrieves noisy papers), so corpus value is not established as a general property of the protocol.

**Metric-format coupling.** The "X is necessary for Y" format couples prompt, output, and metric, creating circular evaluation. GPT-4o's stronger format compliance (vs Claude's more diverse outputs) likely explains its ranking advantage rather than deeper paradigm understanding.

**Human validation substantiates the matcher.** A 10-rater study ($\alpha = 0.634$, attention-check 99%; §5.4) gives human-vs-rule $\kappa = 0.70$ (92% raw); the matcher is *not* more permissive than humans (rule 0.14 vs human 0.19). Per-condition the two diverge: humans rate with-corpus twice as high as no-corpus, the matcher does not (Table 9), qualifying rather than overturning the memorization story. The aggregate $\sim$0.15–0.19 pairwise match rate bounds the headline: Recall@K is a recovery criterion, not pairwise precision.

**Model sensitivity.** On identical prompts and corpora, GPT-4o achieves 4/4 and Claude 1/4. Claude's individual extractions reach higher raw similarity (0.774 vs 0.729, Table 15) but at much worse confidence ranks; under the canonical top-$K$ pipeline the order flips (GPT-4o 0.703 vs Claude 0.658, Table 8). The metric thus rewards format compliance over extraction quality.

**Small sample size.** With $N = 10$, statistical power is limited (Fisher $p = 0.07$). Bootstrap CIs are correspondingly wide.

**Prospective utility.** Prospective evaluation (Appendix H) relies entirely on LLM judges ($\alpha = 0.34$–$0.47$). Human expert evaluation remains necessary.

## 7 Conclusion

We audited LLM-based recovery of paradigmatic assumptions on 10 historical AI breakthroughs (frozen 4-case protocol + 6 post-hoc cases). Three findings: **(1)** field-wide prompt framing raises target similarity by +0.21 (CI [0.17, 0.28]) on $N{=}3$ with identical corpora, and GPT-4o matches 6/10 in the extended setting; **(2)** memorization dominates (no-corpus 4/4 on primary), but corpus content *can* be causally read (wrong-corpus collapses to 0/12 across all $4{\times}3$ cross-pairings; synthetic Scenario 2 rank 2 vs 27) — the causal evidence is narrow (1 of 3 synthetic scenarios; one shows corpus harm); **(3)** design choices are confounded — the "X is necessary for Y" format couples prompt/output/metric, model selection dramatically affects ranking, and success is limited to explicitly stated assumptions. We release the audit kit — wrong-corpus pairings, 80-pair human-validation instrument, canonical evaluator, multi-seed driver, Min-K% probe — as an instrument other LLM scientific-text-mining benchmarks can apply to their own metrics. Empirical cross-domain validation is left to future work

(Appendix M); full manifest, reproduction walk-through, and what-we-dropped notes are in Appendices A, S, R.

## Limitations

This paper is deliberately scoped as a *diagnostic* of retrospective assumption-recovery benchmarks, and its claims should be read within the following limits.

**Construct validity and author bias.** Target assumptions and aliases are *author-defined* from canonical descriptions rather than independently annotated, introducing a selection/confirmation bias: the authors who designed the prompt also fixed what counts as a correct recovery. We mitigate this by freezing the 4 primary targets before experiments (SHA-256 hash) and by an independent 10-rater human-validation study (§5.4, Krippendorff's $\alpha = 0.634$), but the bias is reduced, not eliminated. *The 10-rater study validates the similarity matcher, not the targets themselves*; an independent expert target-validity study is the single highest-impact follow-up and is in preparation. The previously reported $\kappa = 0.97$ was agreement between *two deterministic rule-based programs*, not human raters; the human study supersedes it with a genuine human-vs-rule $\kappa = 0.70$ (substantial, 92% agreement) and shows the matcher is *not* more permissive than humans.

**Synthetic non-member baseline for MIA.** The 45 synthetic abstracts used as the Min-K% Prob non-member control (Appendix L) were generated by a GPT-family model and therefore share stylistic distribution with the OSS models' pretraining text far more than pre-2020 archival papers do. The observed negative real-vs-synth gap (95% CI strictly below 0 in all 3 models) is therefore an *upper bound on MIA's discriminative power between GPT-style and pre-2020 archival text at this scale*, not a universal MIA-limitation claim. A non-GPT synth baseline (e.g., generated by Llama itself) would tighten the bound.

**Statistical power and run variance.** The benchmark has $N = 10$ breakthroughs (4 pre-registered, 6 post-hoc stress cases). The primary comparison is not significant at $\alpha = 0.05$ (Fisher's exact $p = 0.07$) and bootstrap confidence intervals are wide; the prompt ablation rests on $N = 3$ categories. Closed-model extractions (GPT-4o, Claude) are single-seed API calls and `text-embedding-3-small` is a versioned, drift-prone API; we make *no claim of statistical superiority* and treat all relative numbers as descriptive of one canonical run. To bound API-level run variance we re-ran the with-corpus, no-corpus, and wrong-corpus conditions on the 4 primary shifts under 3 seeds (1, 2, 42; `scripts/run_multiseed_variance.py`; same prompts/threshold/embedding model). The contested claims are seed-stable: **no-corpus 4/4 across all 3 seeds** and **wrong-corpus 0/4 across all 3 seeds** (best-sim 0.36–0.42). With-corpus is slightly less stable at this re-run (4/4 on seeds 1 and 2; 3/4 on seed 42, with ViT's best-cosine 0.648 just below the 0.65 threshold so no candidate matches), corroborating the API/model-drift caveat. The full per-seed scatter is in Appendix O. The relative structure (with-corpus $\approx$ no-corpus $\gg$ wrong-corpus) holds across seeds.

**Run variance.** Closed-model (GPT-4o, Claude) extractions are single-seed API calls; we cannot report repeated-run variance for them. Open models were run at temperature 0 with a fixed seed but still as single runs.

**Confounds not fully separable.** We cannot fully disentangle corpus-grounded extraction from pretraining recall: corpus grounding is demonstrably causal only in one synthetic scenario and one genuinely niche case (Neural ODE), and *scenario-dependent* — 1 of 3 synthetic scenarios shows no corpus effect and another shows corpus *harm*, so causal corpus contribution is not a general property of the protocol. Even the niche and synthetic controls do not guarantee *zero* memorization (niche targets may be partially memorized, and synthetic fields only approximate novelty); the "X is necessary for Y" format couples prompt, output, and matcher; and recovery is highly model-sensitive (a five-LLM sweep spans 4/4 to 0/4 on identical inputs, each a single run).

**Scope.** The corpus, targets, and breakthroughs are English-language AI/ML; we make no claims about other languages, disciplines, or non-archival literature. The protocol is *not* validated as a prospective discovery method — the prospective pilot relies entirely on LLM judges (Appendix H) and human expert evaluation remains future work.

## Ethics Statement

The experiments use only public scientific metadata (paper titles/abstracts from OpenAlex, CC0) and contain *no* personally identifying information. The human-validation study (§5.4) involved 10 voluntary, adult, ML-literate annotators from the authors' professional network who were informed of the task and intended use, consented, could withdraw at any time, and rated only public extracted/target text pairs (no sensitive data, no personal information collected beyond ML-literacy). The task — anonymous Likert rating of non-sensitive public text — is minimal-risk and exempt from IRB review under standard common-rule criteria; participation was voluntary with a small honorarium or acknowledgment offered. Raw per-annotator returns are withheld; only anonymized aggregate statistics (annotation/g1_results.json, R01–R10) are released. An anonymised demographic summary of the 10 raters is in Appendix T. LLM extractions are derivative works subject to the respective providers' terms. Tools that suggest research directions risk homogenizing inquiry via the Artificial Hivemind effect (Jiang et al., 2025); we mitigate this by reporting ranked lists (preserving diversity), conditioning extraction on specific corpora (different contexts surface different assumptions), and releasing open methodology and reproduction scripts. Computational cost is modest — API calls plus minutes of single-GPU vLLM inference — with a correspondingly small carbon footprint. We foresee no dual-use or vulnerable-population harms.

## References

Genrich Altshuller. 1984. *Creativity as an Exact Science: The Theory of the Solution of Inventive Problems*. Gordon and Breach.

Jinheon Baek, Sujay Kumar Jauhar, Silviu Cucerzan, and Sung Ju Hwang. 2025. ResearchAgent: Iterative research idea generation over scientific literature with large language models. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL)*. ArXiv:2404.07738.

Margaret A. Boden. 2004. *The Creative Mind: Myths and Mechanisms*, 2nd edition. Routledge.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, and 1 others. 2020. Language models are few-shot learners. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 33, pages 1877–1901.

Jacob Cohen. 1960. A coefficient of agreement for nominal scales. *Educational and Psychological Measurement*, 20(1):37–46.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics (NAACL)*, pages 4171–4186.

Yihong Dong, Xue Jiang, Huanyu Liu, Zhi Jin, Bin Gu, Mengfei Yang, and Ge Li. 2024. Generalization or memorization: Data contamination and trustworthy evaluation for large language models. In *Findings of the Association for Computational Linguistics: ACL*.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. 2021. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations (ICLR)*.

Michael Duan, Anshuman Suri, Niloofar Mireshghallah, Sewon Min, Weijia Shi, Luke Zettlemoyer, Yulia Tsvetkov, Yejin Choi, David Evans, and Hannaneh Hajishirzi. 2024. Do membership inference attacks work on large language models? In *Conference on Language Modeling (COLM)*.

Shahriar Golchin and Mihai Surdeanu. 2024. Time travel in LLMs: Tracing data contamination in large language models. In *International Conference on Learning Representations (ICLR)*.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. 2014. Generative adversarial nets. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 27.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. 2016. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 770–778.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. 2020. Denoising diffusion probabilistic models. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 33, pages 6840–6851.

Xiang Hu, Hongyu Fu, Jinge Wang, Yifeng Wang, Zhikun Li, Renjun Xu, Yu Lu, Yaochu Jin, Lili Pan, and Zhenzhong Lan. 2024. Nova: An iterative planning and search approach to enhance novelty and diversity of LLM generated ideas. *arXiv preprint arXiv:2410.14255*.

Sergey Ioffe and Christian Szegedy. 2015. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *Proceedings of the 32nd International Conference on Machine Learning (ICML)*, pages 448–456.

Liwei Jiang, Yuanjun Chai, Margaret Li, Mickel Liu, Raymond Fok, Nouha Dziri, Yulia Tsvetkov, Maarten Sap, Alon Albalak, and Yejin Choi. 2025. Artificial hivemind: The open-ended homogeneity of language models (and beyond). In *Advances in Neural Information Processing Systems (NeurIPS)*. Best Paper Award. arXiv:2510.22954.

Shuo Jiang and Jianxi Luo. 2024. AutoTRIZ: Artificial ideation with TRIZ and large language models. *arXiv preprint arXiv:2403.13002*.

Priyanka Kargupta, Shuhaib Mehri, Dilek Hakkani-Tur, and Jiawei Han. 2026. Sparking scientific creativity via LLM-driven interdisciplinary inspiration. *arXiv preprint arXiv:2603.12226*.

Klaus Krippendorff. 2018. *Content Analysis: An Introduction to Its Methodology*, 4th edition. Sage.

Thomas S. Kuhn. 1962. *The Structure of Scientific Revolutions*. University of Chicago Press.

Chris Lu, Cong Lu, Robert Tjarko Lange, Jakob Foerster, Jeff Clune, and David Ha. 2024. The AI scientist: Towards fully automated open-ended scientific discovery. *arXiv preprint arXiv:2408.06292*.

Inbal Magar and Roy Schwartz. 2022. Data contamination: From memorization to exploitation. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 157–165.

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S. Corrado, and Jeff Dean. 2013. Distributed representations of words and phrases and their compositionality. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 26.

Yonatan Oren, Nicole Meister, Niladri Chatterji, Faisal Ladhak, and Tatsunori Hashimoto. 2024. Proving test set contamination in black-box language models. In *International Conference on Learning Representations (ICLR)*.

Jason Priem, Heather Piwowar, and Richard Orr. 2022. OpenAlex: A fully-open index of scholarly works, authors, venues, institutions, and concepts. *arXiv preprint arXiv:2205.01833*.

Kevin Pu, K. J. Kevin Feng, Tovi Grossman, Tom Hope, Bhavana Dalvi Mishra, Matt Latzke, Jonathan Bragg, Joseph Chee Chang, and Pao Siangliulue. 2024. IdeaSynth: Iterative research idea development through evolving and composing idea facets with literature-grounded feedback. *arXiv preprint arXiv:2410.04025*.

Manley Roberts, Himanshu Thakur, Christine Herlihy, Colin White, and Samuel Dooley. 2023. Data contamination through the lens of time. *arXiv preprint arXiv:2310.10628*.

Oscar Sainz, Jon Ander Campos, Iker García-Ferrero, Julen Etxaniz, Oier Lopez de Lacalle, and Eneko Agirre. 2023. NLP evaluation in trouble: On the need to measure LLM data contamination for each benchmark. In *Findings of the Association for Computational Linguistics: EMNLP*.

Samuel Schapiro, Jonah Black, and Lav R. Varshney. 2025. Transformational creativity in science: A graphical theory. In *Proceedings of the International Conference on Computational Creativity (ICCC)*.

Fatemeh Shahhosseini, Arash Mariorioyad, Ali Momen, Mahdieh Soleymani Baghshah, Mohammad Hossein Rohban, and Shaghayegh Haghjooy Javanmard. 2026. Large language models for scientific idea generation: A creativity-centered survey. *arXiv preprint arXiv:2511.07448*.

Weijia Shi, Anirudh Ajith, Mengzhou Xia, Yangsibo Huang, Daogao Liu, Terra Blevins, Danqi Chen, and Luke Zettlemoyer. 2024. Detecting pretraining data from large language models. In *International Conference on Learning Representations (ICLR)*.

Chenglei Si, Diyi Yang, and Tatsunori Hashimoto. 2025. Can LLMs generate novel research ideas? A large-scale human study with 100+ NLP researchers. In *International Conference on Learning Representations (ICLR)*. ArXiv:2409.04109.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. 2014. Dropout: A simple way to prevent neural networks from overfitting. *Journal of Machine Learning Research*, 15(1):1929–1958.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 30.

Qingyun Wang, Doug Downey, Heng Ji, and Tom Hope. 2024. SciMON: Scientific inspiration machines optimized for novelty. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (ACL)*. ArXiv:2305.14259.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. 2023. Judging LLM-as-a-judge with MT-bench and chatbot arena. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 36.

## A Artifact Manifest (How to Read this Supplement)

The anonymized supplement is organized around a single source of truth for every number in the paper. All headline results come from experiments/canonical_evaluation.json, produced by the confidence-order evaluator scripts/canonical_evaluator.py. An offline *consistency-check* script scripts/reproduce_paper_tables.py re-reads the frozen artifacts and asserts every headline number against them without API calls (73/73 checks); it verifies the paper matches the stored artifacts but does *not* regenerate them — recomputation requires the OpenAI embedding API and is single-run. Table 10 maps each paper table/claim to its source file, generating script, and canonical result. A *quarantined* stale artifact, experiments/gpt4o_clean_prompt/summary_STALE_similarity_reranked.json, is retained in the supplement for audit only and is explicitly not used for any paper number.

**Scope of the protocol freeze.** Only the initial 4-primary-shift protocol (Transformer, Diffusion, ICL, ViT with the target-assumption mapping and soft-matching threshold) is covered by the SHA-256-hashed freeze in evidence/protocol_freeze.json. The 6-case extension (ResNet, GAN, Word2Vec, Dropout, BatchNorm, BERT), retrieval baselines, contamination/calibration/error diagnostics, and synthetic/niche controls were developed post-hoc; their scripts and artifacts are released, but they are reported transparently as stress tests, not as pre-registered claims.

**Target-assumption construction.** Targets and 2–3 aliases per breakthrough are defined in data/paradigm_shift_mapping.json and authored by the paper's authors from canonical descriptions in survey papers and original breakthrough papers. These are *author-defined targets*, not independently annotated ground truth. Note this is distinct from the matcher-validation study (§5.4), which tests whether the *similarity matcher* agrees with humans, not whether the author-defined *targets* are themselves canonical; an independent human-expert study of target correctness remains future work.

**Stale and failed artifacts.** experiments/gpt4o_clean_prompt/summary_STALE_

similarity_reranked.json contains an earlier run that re-sorted by cosine similarity instead of confidence order; retained in the supplement only for audit trail, not used for paper claims. Quota-failed runs are moved to experiments/failed_runs/ and are similarly not used for any paper number.

**Compute and cost.** Extraction and evaluation total approximately \$15–\$30 USD in API credits across all experiments (Anthropic + OpenAI). No GPU compute is required. Typical wall-clock per paradigm: 3–10 minutes.

## B Clean Extraction Prompt (Main Results)

The prompt used for the main GPT-4o results (Table 2). No few-shot examples are included.

```
You are an expert at identifying the
    foundational, field-wide assumptions
that academic papers inherit from their
    broader research community.

Your task is NOT to find this specific
    paper's design choices. Instead,
identify the **paradigmatic assumptions
    ** -- beliefs shared across the
entire subfield that this paper takes
    for granted without questioning.
These are assumptions so deeply
    ingrained that the research
    community
treats them as self-evident truths.

These are NOT what we want:
- Paper-specific implementation details
    ("we use Adam optimizer with lr
    =0.001")
- Narrow technical choices ("batch size
    of 32 is sufficient")
- Obvious truisms ("more data helps")

For each assumption, phrase it as a
    general declarative statement about
what the field believes is NECESSARY,
    REQUIRED, or ESSENTIAL.
Use the pattern: "[X] is necessary/
    required/essential for [Y]".

Categories: architectural, training,
    data, theoretical, evaluation

Return ONLY valid JSON. Limit to top 10
    assumptions, ranked by how
foundational they are to the entire
    field (not just this paper).
```

## C Paper-Specific Prompt (Ablation)

```
You are an expert at identifying
    implicit assumptions in academic
    papers.
```

Table 10: Artifact manifest: every paper number → source file → generating script.

| Paper artifact | Source file | Generating script |
| --- | --- | --- |
| Table 2 (10-case main) | experiments/canonical_evaluation.json | scripts/canonical_evaluator.py |
| Prompt ablation (+0.21 sim) | experiments/ablation/summary.json | scripts/run_ablation_study.py |
| No-corpus 4/4 primary | experiments/no_corpus_control/summary.json | scripts/run_no_corpus_control.py |
| Wrong-corpus 0/4 (4 pairings, GPT-4o) | experiments/wrong_corpus_control/summary.json | scripts/run_wrong_corpus_control.py |
| Synthetic (rank 2 vs 27) | experiments/synthetic_benchmark/summary.json | scripts/run_synthetic_benchmark.py |
| Niche 1/8 with-corpus, 2/7 no-corpus | experiments/niche_benchmark/summary.json | scripts/run_niche_benchmark.py |
| TF-IDF/BM25 2/4 | experiments/simple_baselines/summary.json | scripts/run_simple_baselines.py |
| Spearman $\rho = -0.64$ | experiments/contamination/summary.json | scripts/run_contamination_analysis.py |
| Error analysis (ResNet 0/150; BERT PDF) | experiments/error_analysis/summary.json | scripts/run_error_analysis.py |
| Confidence gap 0.025 | experiments/calibration/summary.json | scripts/run_calibration_analysis.py |
| Cross-model 4/4 vs 1/4 | experiments/claude_clean_15paper/summary.json + experiments/canonical_evaluation.json | scripts/run_gpt4o_clean_all10.py |
| SCAM baseline comparison | experiments/baselines/scam/summary.json | scripts/run_retrospective_baselines.py |
| Rule-based matching simulation ($\kappa = 0.97$) | evidence/human_annotation_results.json | scripts/run_rulebased_match_simulation.py |
| Protocol freeze (SHA-256) | evidence/protocol_freeze.json | frozen pre-registration |
| Prospective pilot (LLM-judge) | experiments/prospective/summary.json | scripts/evaluate_prospective.py |

```
Read the following paper text and
    identify the implicit assumptions
(assumptions not explicitly stated but
    underlying the work).
For each assumption:
1. State it clearly and concisely
2. Provide a confidence score (0.0-1.0)
3. Categorize it (architectural/training
    /data/theoretical/evaluation)
Return ONLY valid JSON. Limit to top 10
    assumptions.
```

The critical difference: the paper-specific prompt asks for assumptions *of this paper*, while the field-wide prompt asks for assumptions *of the entire subfield*.

## D  Per-Category Analysis Details

Using Claude Sonnet 4 with the field-wide prompt (with few-shot examples) on 60-paper corpora:

**Transformer (pre-2017).** 32 unique assumptions extracted. Target "Recurrent connections are necessary for effective sequence modeling" at rank 10 (sim = 0.80). With GPT-4o (Table 2): confidence rank 1 (sim = 0.674).

**Diffusion (pre-2020).** "Adversarial training is necessary for high-quality generative modeling" at rank 1 (sim = 0.82) under the Claude 60-paper few-shot extraction; with GPT-4o (Table 2): confidence rank 2 (sim = 0.759). Eight of top 10 are adversarial training variations.

**ViT (pre-2020).** "Convolutional inductive biases are necessary for effective visual feature learning" at rank 1 (sim = 0.76). Top 5 all center on convolutional necessity.

**ICL (pre-2020).** Initial corpus (domain adaptation papers): sim = 0.62, below threshold. After reinforcing with fine-tuning papers: rank 10 (sim = 0.74). GPT-4o succeeds without reinforcement (rank 3, sim = 0.702) — partly Claude-specific failure.

**Corpus composition effect.** The ICL recovery reveals that corpus composition directly determines which assumptions are extractable. Pre-shift corpora should be representative of the paradigm, not just temporally filtered.

**Successful extractions (GPT-4o, canonical pipeline).** Table 11 shows the top-matched extraction at the recovery rank for each of the 6 successes. The extracted strings are semantically close paraphrases of the targets, with cosine $\in [0.657, 0.759]$.

Table 11: Successful target recoveries (6 of 10). For each paradigm, the extraction at the confidence rank that first cleared the 0.65 threshold, with cosine similarity to the closest target alias.

| Paradigm | rank/sim | Extraction at recovery rank |
|---|---|---|
| Transformer | 1 / .67 | Recurrent neural networks are necessary for modeling sequential data |
| Diffusion | 2 / .76 | Adversarial training is necessary for learning generative models |
| ICL | 3 / .70 | Fine-tuning pre-trained models is necessary for adapting them to tasks |
| ViT | 5 / .68 | Convolutional neural networks are necessary for image-based tasks |
| BatchNorm | 7 / .73 | Proper initialization is essential for training deep neural networks |
| GAN | 10 / .66 | Efficient representation of probability distributions is essential |

## E Sensitivity Analysis and Threshold Validation

**Threshold robustness.** Soft-R@10 across thresholds 0.50–0.85:

Table 12: Threshold-AUC robustness (Soft-R@10 area under threshold sweep 0.50–0.85): Unbox accumulates $1.9\times$ the AUC of Vanilla LLM.

| Method | AUC (0.50–0.85) | Ratio |
|---|---|---|
| Vanilla LLM | 0.1250 | $1.0\times$ |
| **Unbox** | **0.2375** | **$1.9\times$** |

At F1-optimal threshold (0.50): both achieve R@10 = 1.00, but Unbox at higher similarity (avg 0.79 vs 0.60). At conservative threshold (0.65): Unbox = 0.75, Vanilla = 0.25.

**Rule-based structured-matching simulation (not human raters).** Two automated labelers (strict and moderate keyword-pattern programs, `scripts/run_rulebased_match_simulation.py`) on 80 pairs yield inter-labeler $\kappa = 0.97$ (98.75% agreement). This is a structured metric-validation simulation, *not* independent human annotation; we report it only to probe threshold stability under a second deterministic labeler:

At 0.65, the matcher achieves perfect precision but moderate recall — reported results are conservative lower bounds.

Table 13: Soft-matching threshold sweep against the rule-based labelers (80 pairs): at 0.65 precision is perfect with $F_1=0.73$; reported headline numbers are conservative lower bounds.

| Threshold | Precision | Recall | F1 |
|---|---|---|---|
| 0.50 | 0.79 | 1.00 | 0.88 |
| 0.55 | 0.82 | 0.88 | 0.85 |
| 0.60 | 0.87 | 0.77 | 0.82 |
| **0.65** | **1.00** | **0.58** | **0.73** |
| 0.70 | 1.00 | 0.42 | 0.59 |

**Corpus size effect.** 15- vs 60-paper runs (Claude): rank stable for Diffusion and ViT (rank 1 both), worsens for Transformer ($7 \rightarrow 10$) as competing assumptions dilute ranking.

## F Few-Shot Leakage Test

Table 14: Few-shot leakage test (15 papers, 4 primary shifts).

| Condition | Description | Avg Best Sim | R@10 |
|---|---|---|---|
| Original | All 4 examples | 0.785 | 2/4 |
| Leave-one-out | Target removed | 0.781 | 2/4 |
| **No examples** | **All removed** | **0.823** | **2/4** |
| Cross-domain | Non-AI examples | 0.782 | 3/4 |

With no examples, the model achieves the *highest* average similarity (0.823, including 0.921 for Transformer). The extraction protocol works through field-wide framing, not example copying.

## G Cross-Model Comparison

Controlled comparison: same clean prompt, same 15-paper corpus. Note that the Avg Sim column here is the *raw best similarity across all ∼150 extractions per paradigm* (from the per-model 15-paper summaries) rather than the canonical top-$K$-by-confidence pipeline used in Table 8; the two numbers therefore differ by methodology, not by re-running the experiment. The canonical top-$K$ averages are GPT-4o 0.703 and Claude 0.658 (Table 8); reporting both highlights the rank-vs-similarity inversion.

Claude's individual extractions achieve higher raw similarity to the target (0.774 vs 0.729) but at much worse confidence-ordered ranks; under the canonical top-$K$ pipeline that ranking penalty flips the order (GPT-4o 0.703 > Claude 0.658, Table 8). GPT-4o's format compliance concentrates confidence on "X is necessary for Y" patterns — better aligned with the benchmark metric, not necessarily reflecting deeper understanding.

Table 15: Cross-model raw best similarity. Avg Sim = mean over the 4 primary shifts of the highest cosine similarity achieved by *any* extraction (regardless of confidence rank). GPT-4o values reproduce the quarantined `summary_STALE_similarity_reranked.json` artifact, retained for cross-reference; the canonical (top-$K$-by-confidence) average is 0.703 (Table 8).

| Model | Trans. | Diff. | ICL | ViT | R@5 | Avg Sim |
|---|---|---|---|---|---|---|
| Claude Sonnet 4 | ✗ (rk 26) | ✓ (rk 1) | ✗ (rk 35) | ✗ (rk 11) | 1/4 | 0.774 |
| GPT-4o | ✓ (rk 1) | ✓ (rk 2) | ✓ (rk 3) | ✓ (rk 5) | 4/4 | 0.729 |

Figure 2: Cross-LLM Soft-R@5 per primary paradigm, canonical pipeline (text-embedding-3-small, threshold 0.65). The 5-model spread (GPT-4o 4/4 down to Mistral 0/4) fragments any closed-vs-open framing and exposes model-specific format-compliance interactions with the matcher template.

**Format-relaxed matcher ablation.** To test how much of the 5-LLM gap is ranking artifact vs raw extraction recall, we recount each model's primary matches under a relaxed criterion: did *any* of the top-20 confidence-ranked extractions clear the 0.65 threshold, regardless of confidence rank? Table 16 shows the spread under R@10 (the headline criterion) and under the relaxed any-rank-in-top-20 criterion (`scripts/run_format_relaxed_matcher.py`).

Table 16: Format-relaxed matcher ablation. "Any rank" = any extraction in top-20-by-confidence clears the 0.65 threshold (regardless of rank). The spread is essentially preserved: Claude gains 1 match (1→2), but GPT-4o stays at 4, Llama at 2, Qwen at 3, Mistral at 0 — the gap is not primarily a ranking artifact.

| Model | R@5 | R@10 | any rank in top-20 |
|---|---|---|---|
| GPT-4o | 4 | 4 | 4 |
| Claude Sonnet 4 | 1 | 1 | 2 |
| Llama-3.1-8B | 1 | 2 | 2 |
| Qwen-2.5-7B | 2 | 3 | 3 |
| Mistral-7B | 0 | 0 | 0 |

The any-rank spread $[4, 2, 2, 3, 0]$ differs from the R@10 spread $[4, 1, 2, 3, 0]$ by exactly one match for Claude only; format-compliance with the matcher template explains *at most one match (Claude)* of the gap. The residual GPT-4o vs Mistral gap (4 vs 0) is in raw extraction recall, not in ranking. The §5.4 "format-compliance" framing is therefore a partial explanation; raw capability differences are not excluded.

# H  Prospective Pilot (Exploratory)

We apply Unbox to 4 current AI paradigms (autoregressive LLMs, RLHF, scaling laws, self-attention). From 12 seed assumptions, 35 hypotheses are generated via TRIZ. Five LLM judge personas evaluate the top 12:

Table 17: Prospective pilot (5 LLM judge personas, top-12 hypotheses). Moderate inter-judge agreement ($\alpha = 0.34$–$0.47$) reflects legitimate disagreement on creative evaluation; this section is exploratory only.

| Dimension | Avg Score (1–10) | Krippendorff's $\alpha$ |
|---|---|---|
| Novelty | 5.4 | 0.43 |
| Feasibility | 5.9 | 0.34 |
| Impact | 7.0 | 0.37 |
| Clarity | 6.5 | 0.47 |
| **Composite (mean of per-dim avgs)** | **6.2** (95% CI: [5.7, 7.0]) | — |

Moderate agreement ($\alpha = 0.34$–$0.47$) reflects legitimate disagreement on creative evaluation. Impact is consistently highest, suggesting hypotheses target important problems. A blinded human expert evaluation is in preparation. LLM-as-judge (Zheng et al., 2023) cannot substitute for expert assessment; this section is exploratory only.

# I  Optional TRIZ-Inspired Diversification (Not Validated)

An early version of this work included a TRIZ-inspired diversification step (`src/constraint_breaker.py`) that transforms each extracted assumption through three operators: NEGATE, RELAX, INVERT. On the 4 primary shifts with Claude, extraction-only and extraction + TRIZ achieve identical soft-R@10 (0.75); on the 4-primary GPT-4o clean-prompt run, the target is already in the top-10 in $4/4$ cases without TRIZ. TRIZ transformations *do* produce near-disjoint hypothesis framings (Jaccard $< 0.01$), which may have prospective value, but the prospective pilot (App. H) is LLM-judge only and inconclusive. We retain the implementation in the supplement for future work but do not include TRIZ in the main pipeline or claim it as a contribution.

## J  Audit-Kit Checklist for LLM-Based Assumption-Recovery Benchmarks

This checklist formalises the five recommendations of §5.5. Each item names the confound it isolates, the minimum experimental footprint that exposes it, and the canonical-pipeline parameter set that drives the cost. All five together cost approximately $15 of API credits on our 4 primary shifts.

1. **No-corpus baseline.** Re-run the protocol with only the field name (no paper text). Confound exposed: pretraining memorisation. Minimum footprint: one extraction per paradigm (no corpus). *Decision rule:* if no-corpus $R@K \geq$ with-corpus $R@K - 1$, treat the headline as memorisation-dominated.

2. **Wrong-corpus pairing.** Re-run with a target-/corpus mismatch (target field $A$ but corpus from field $B \neq A$). Confound exposed: corpus being ignored when present. Minimum footprint: at least one cross-pair. *Decision rule:* if wrong-corpus $R@K \approx$ with-corpus $R@K$, the corpus is not causally read; the headline is not a corpus-grounded extraction result.

3. **Pair-level precision alongside any-of-top-$K$ recall.** Sample $N \geq 50$ stratified (extraction, target)-pair candidates and label each as match / non-match. Confound exposed: the gap between "$K$th extraction clears threshold" and "top extraction matches". *Decision rule:* report both; recall@$K$ can hit 6/10 from pair-level precision as low as 0.19 (this paper).

4. **Cross-LLM evaluation ($\geq 2$ models).** Repeat the canonical pipeline with $\geq 2$ architecturally distinct models (e.g. closed-API + open-weights, or two different open-weights families). Confound exposed: format compliance vs. extraction quality. *Decision rule:* if $R@K$ spreads by $\geq 2$ across models on identical prompts and corpora, the metric is rewarding format compliance.

5. **Repeated-run or sensitivity bound.** For closed-model API extractions (which are single-seed by default), report either multi-seed variance ($\geq 3$ seeds) or a temperature / prompt-perturbation sensitivity range. Confound exposed: silent API or prompt drift. *Decision rule:* if the per-seed $R@K$ range exceeds $\pm 1$ paradigm, treat individual numbers as descriptive of one run, not as a stable point estimate.

**Adopting the kit.** The five controls factor: a benchmark author can run them independently as their corpus and compute permit. We release the four scripts (`scripts/run_no_corpus_control.py`, `scripts/run_wrong_corpus_control.py`, `scripts/sample_annotation_pairs.py`, `scripts/run_multiseed_variance.py`) so adoption is a path edit rather than a re-implementation.

## K  Cross-Embedding Sensitivity

The canonical pipeline reports $R@K$ at threshold 0.65 against the TEXT-EMBEDDING-3-SMALL embedder. To bound how much of the headline depends on that embedder choice, we re-evaluate the *same* GPT-4o extractions against two alternatives without any new LLM calls: OpenAI TEXT-EMBEDDING-3-LARGE and the open-weights `all-MiniLM-L6-v2` (sentence-transformers). For each embedder we sweep thresholds $\{0.50, 0.55, 0.60, 0.65, 0.70, 0.75\}$ and report the threshold at which primary $R@10$ saturates.

Table 18: Cross-embedding sensitivity (re-evaluation of identical GPT-4o extractions). At each embedder's calibrated threshold, primary $R@10$ stays at $4/4$ and all-paradigm $R@10$ spans 6–8/10.

| Embedder | Thr. (cal.) | Primary R@10 | All R@10 |
|---|---|---|---|
| text-embedding-3-small (baseline) | 0.65 | 4/4 | 6/10 |
| text-embedding-3-large | 0.50 | 4/4 | 8/10 |
| all-MiniLM-L6-v2 | 0.65 | 4/4 | 7/10 |

Two observations: (i) TEXT-EMBEDDING-3-LARGE produces a tighter cosine distribution; at the baseline threshold of 0.65 its primary $R@10$ drops to $2/4$, but at the F1-calibrated threshold 0.50 it recovers to $4/4$ and additionally promotes 2 of the previously failing paradigms (all $R@10 = 8/10$). (ii) `all-MiniLM-L6-v2` matches the baseline threshold 0.65 directly and lands at $4/4/7/10$ — the result is therefore not specific to OpenAI embeddings. The qualitative conclusions of §5.1–§5.4 (primary $4/4$, no-corpus $4/4$, wrong-corpus $0/4$) are therefore embedder-robust once the threshold is calibrated for each embedder; the embedder-specific 0.65 choice in the main pipeline controls only the absolute all-paradigm count between 6 and 8. Detailed numbers in `experiments/cross_embedding/summary.json`.

Figure 3: Threshold sweep across 3 embedders. Primary R@10 plateaus at $4/4$ for all three embedders once the threshold is moved off the baseline 0.65 (which is calibrated for TEXT-EMBEDDING-3-SMALL); the all-paradigm count varies between 6 and 8 depending on embedder, not the qualitative conclusion.

Figure 4: Per-paper Min-K%(20) Prob distribution: 240 real pre-shift papers (blue) vs 45 GPT-generated synthetic non-members (orange). In all three OSS models the synthetic non-member distribution sits *above* (less negative than) the real distribution, the opposite of what a naive contamination reading predicts.

## L  Membership-Inference Cross-Check (Min-K% Prob)

We test whether a token-level membership-inference attack (MIA) can detect the same contamination that the behavioral no-corpus control surfaces. For each of the 3 OSS models that expose token logprobs (Llama-3.1-8B, Qwen-2.5-7B, Mistral-7B; scripts/run_minkpct_mia.py) we feed every paper in the 4 pre-shift corpora through the model in prefill mode, take the bottom $20\%$ of per-token logprobs, and average them (Shi et al., 2024). The same statistic is computed on the 45 *synthetic* (definitely non-member) abstracts from §5.3 as a baseline.

Table 19: Min-K%(20) Prob on the 4 pre-shift corpora (real, $n$=240 papers) vs 45 synthetic abstracts (definitely non-member, GPT-generated). Higher (less negative) = more probable = MIA's contamination signal. *Synthetic abstracts are ranked more member-like than real pre-shift papers under all 3 OSS models*; the gap is statistically negative (95% bootstrap CI strictly below 0) for each model, exposing a stylistic-familiarity confound that defeats the naive MIA reading.

| Model | Real ($n$=240) | Synth ($n$=45) | Gap | 95% CI |
|---|---|---|---|---|
| Llama-3.1-8B | $-6.50$ | $-6.02$ | $-0.47$ | $[-0.59, -0.35]$ |
| Qwen-2.5-7B | $-6.24$ | $-6.00$ | $-0.24$ | $[-0.39, -0.10]$ |
| Mistral-7B | $-6.10$ | $-5.96$ | $-0.15$ | $[-0.27, -0.02]$ |

The gap is *negative* in all 3 models (Figure 4): the 45 GPT-generated synthetic abstracts — guaranteed not in any model's pretraining — look *more* member-like to Min-K% Prob than the actual pre-shift corpora do. *Important caveat:* these synthetic abstracts were themselves generated by a GPT-family model and therefore share stylistic distribution with the OSS models' pretraining text

far more than pre-2020 archival papers do. The result should be read as a *lower bound on MIA's discriminative power between GPT-style and pre-2020 archival text at this scale*, not as a universal indictment of Min-K% Prob. With that scope, the finding is still informative: a naive "Min-K% high $\Rightarrow$ in training" reading on this benchmark would mis-call the synthetic non-members as contaminated, while the behavioral no-corpus control — a uniform $4/4$ recovery on the same 4 paradigms — gives the direction-correct signal. We view the two modalities as complementary lenses; this paper's empirical observation is that they can disagree at $N = 10$ and that the behavioral lens is the one that works here. A non-GPT synth baseline (e.g., generated by Llama itself) would tighten the bound and is left to future work. Detailed numbers in experiments/mia_minkpct/.

## M  Cross-Domain Applicability of the Audit Kit

The five audit-kit controls (Appendix J) make no assumption specific to AI/ML literature: they only require (i) a pre-shift corpus, (ii) an author- or expert-defined target assumption, and (iii) a black-box LLM. Direct adaptations to other scientific domains:

**Structural biology pre-AlphaFold (2021).** Target assumption: "Multiple sequence alignment is necessary for accurate protein structure prediction." Pre-shift corpus: CASP12–CASP13 method papers ($\leq$2018). The five controls apply unchanged; the no-corpus baseline tests whether "alignment-based"

patterns are already memorised by frontier LLMs from broader biology literature.

**Compressed sensing pre-Donoho/Candès (2006).** Target: "Nyquist-rate sampling is necessary for exact signal recovery." Pre-shift corpus: signal-processing literature ≤2005. Wrong-corpus pairing: signal-processing target against information-theory corpus (a tight cross-pair).

**NLP pre-Transformer (2017) but *not* pre-BERT.** Target: "Recurrent connections are necessary for sequence modelling." Pre-shift corpus: ≤2016 NLP architecture papers (the configuration already used in this paper's main results). This shows the audit kit is self-applicable as a stress test: a benchmark builder can re-run the kit on their own benchmark to detect confounds before reporting headlines.

**Note on this paper's footprint.** We do not run the cross-domain demos above; the audit-kit cost (∼$15 + 1–2 hours per domain on 4 primary cases) is what we estimate other domains would incur. We list these adaptations to support the "benchmark-validity probe" framing in §5.5 and to ground the toolkit's reusability claim.

## N   Failure Mode Taxonomy and Concrete Examples

Each of the 4 R@10 failures (§5.4 Error analysis) is attributable to a distinct, audit-kit-detectable confound, not to a generic limitation of the protocol. Table 20 maps each failure to the kit control that would have surfaced it.

Table 20: Failure mode taxonomy: each of the 4 R@10 failures has a distinct, kit-detectable root cause.

| Paradigm | Failure mode | Audit-kit signal |
|---|---|---|
| ResNet | Coverage gap (target absent in 150 extractions) | Extraction-keyword check on top-$N$ |
| Word2Vec | Domain phrasing ("symbolic semantics") | Cross-embedding sensitivity (App. K) |
| Dropout | Implicit assumption (no explicit "necessary" frame) | Threshold sweep / soft-R@10 AUC |
| BERT | Corpus contamination (OpenAlex retrieved physics paper) | Corpus keyword-precision audit |

**Concrete failure examples.** For each failure, the top extraction in confidence order and the author-defined target illustrate why semantic similarity drops below threshold:

- **ResNet**. *Target*: "Deep networks must process information through sequential layers without shortcuts." *Top-1 extraction*: "Convolutional neural networks (CNNs) are essential for extracting powerful features for visual recognition tasks" (conf = 1.00; best-sim across top-20 = 0.597, below the 0.65 threshold). Cause: the broken assumption (depth-without-shortcuts) is not lexicalised in any pre-2016 paper; the corpus is saturated with CNN-necessity statements.
- **Word2Vec**. *Target*: "Word meaning requires symbolic or hand-crafted feature representations." *Top-1*: "Distributional similarity is necessary for estimating meaning similarity" (conf = 1.00; best-sim across top-20 = 0.633, below the 0.65 threshold). Pre-shift papers already articulate the distributional alternative as *necessary*; only negation-aware matching would recognise this as expressing the same assumption being broken.
- **Dropout**. *Target*: "All neurons should be active during training for optimal learning." *Top-1*: "Deep neural networks are essential for modern speech recognition systems" (conf = 0.95; best-sim across top-20 = 0.604, below the 0.65 threshold). The OpenAlex keyword search retrieves application-domain papers rather than papers articulating the all-neurons-active assumption; an explicit "necessary" frame for the broken assumption is largely absent from the pre-shift corpus.
- **BERT**. *Target*: "Language model pre-training must be left-to-right (autoregressive)." *Top-1*: "Parton distribution functions (PDFs) are essential for predicting outcomes in high-energy particle collisions" (conf = 1.00; best-sim across top-20 = 0.544, below the 0.65 threshold). Cause: OpenAlex keyword search for "BERT" returned a particle-physics paper; this is a corpus-construction artifact rather than an extraction limitation.

## O   Multi-Seed Variance

## P   Per-Paradigm Rank Heatmap

Figure 5: Per-paradigm best-cosine across 3 seeds (1, 2, 42) for the with-corpus (blue) and no-corpus (green) cells, plus all 4 wrong-corpus pairings (red ×). The behavioural conclusions are seed-stable: no-corpus and wrong-corpus cells are identical R@10 across seeds; with-corpus drops the ViT cell of seed 42 just below the dashed 0.65 threshold (the 4/4/3 multi-seed bound in Limitations).

Figure 6: Confidence rank of the (best-matching) target assumption per paradigm and LLM. Lower = better; "—" = no extraction cleared the 0.65 similarity threshold. The matrix makes the per-paradigm spread (6/10 paradigms recovered by GPT-4o, only 1 by Mistral) and the cross-model confound (Diffusion is the only paradigm matched by all five models) directly visible.

## Q    Pre-Registered Protocol Snapshot

The 4-primary-shift protocol was frozen with a SHA-256 hash in `evidence/protocol_freeze.json` before any extraction was run. The hashed contents (verbatim, anonymised) are:

```
protocol_id      = "unbox-4primary-v1"
paradigms        = ["transformer","diffusion","icl
    ","vit"]
year_guards      = {transformer:<=2016, diffusion
    :<=2019,
                    icl:<=2019, vit:<=2019}
target_assumptions = (author-defined; aliases 2--3
    per paradigm,
                    stored in data/
                       paradigm_shift_mapping.
                       json)
soft_match       = "cosine >= 0.65 vs any alias"
embedding_model  = "text-embedding-3-small"
primary_metric   = "Soft-Recall@K for K in
    {5,10,20}"
```

```
extraction_model = "Claude Sonnet 4" (initial), "GPT
    -4o" (canonical)
prompt_variant   = "field-wide paradigmatic" (clean,
    no few-shot)
papers_per_paradigm = 15 (canonical) / 60 (extended)
seed             = 42 ; temperature = 0
```

Everything outside this snapshot — the 6-case extension, retrieval baselines, contamination diagnostics, calibration, error analysis, synthetic/niche controls, cross-LLM sweep, cross-embedding probe, MIA cross-check, multi-seed variance, wrong-corpus pairings (4 and 12), and the audit-kit recommendations — is *post-hoc*. We label every such result transparently as a stress test or extension in its respective section.

## R    What We Tried and Dropped

**Similarity-reranked output.** An earlier pipeline (`experiments/gpt4o_clean_prompt/summary_STALE_similarity_reranked.json`) re-sorted extractions by cosine similarity to the target instead of by extraction confidence. This inflates R@K by construction (the highest-similarity extraction is always at rank 1 by definition) and we therefore quarantine it; the canonical pipeline uses confidence ordering only.

**TRIZ-inspired diversification.** Section I describes the TRIZ pipeline (negate / relax / invert). It produced near-disjoint hypothesis framings but did not improve retrospective recall (extraction-only and extraction+TRIZ both achieve 0.75 R@10 on the 4 primary shifts with Claude). We retained the implementation but dropped TRIZ from the main pipeline.

**Early no-corpus prompt variant.** An initial no-corpus probe handed the model the field name plus the publication year (e.g. "Transformer (2017)"). This leaked the breakthrough date and inflated no-corpus recall above the corpus-grounded baseline. We replaced it with the field-name-only variant used throughout the paper (`scripts/run_no_corpus_control.py`, `FIELD_NAMES_NO_YEAR`); both variants are released in the artefact for transparency.

**Rule-based 80-pair simulation as "human" agreement.** Earlier versions reported $\kappa = 0.97$ from two deterministic keyword-pattern labelers (`scripts/run_rulebased_match_simulation.py`) as a human-annotation result. This was a simulation, not human annotation, and is now reported as such in §5.4 and Appendix E; the

10-rater human study (§5.4, $\kappa = 0.70$) supersedes it.

## S Reproduction Walkthrough

The single command `make reproduce-tables` runs `scripts/reproduce_paper_tables.py`, which performs 73 offline assertions against the frozen JSON artefacts (no API calls). Categories and counts:

- *Table 2 main 10-case* (32 assertions: 10 paradigms $\times$ 3 metrics + 2 aggregate)
- *TF-IDF / BM25 retrieval baselines* (2)
- *Contamination Spearman correlations* (2)
- *Calibration: gap 0.025, monotonicity 10/10* (2)
- *Error analysis: ResNet 0/150, BERT keywords absent* (2)
- *Synthetic 3 fields with rank 1 / 2 / 32* (1)
- *Wrong-corpus 4 pairings 0/4 and 12 pairings 0/12* (6)
- *Synthetic Scenario-2 with-corpus rank 2 vs no-corpus 27* (2)
- *Cross-LLM primary R@5 per model (5 sources)* (5)
- *Niche subfield 1/8 with-corpus, 2/7 no-corpus* (2)
- *Human validation: $\alpha$=0.634, $\kappa$=0.702, AC 79/80* (4)
- *Cross-embedding primary R@10 4/4 at calibrated threshold* (4)
- *Min-K% real-synth gap negative + 95% CI strict-negative per model* (6)
- *Multi-seed variance per-seed R@10* (3)

The full breakdown is in `scripts/reproduce_paper_tables.py`; each `check()` call corresponds to one assertion. If any number in the paper is wrong relative to the stored artefact the script prints which value is expected vs. what was found and exits non-zero. A new contributor can therefore verify the paper's full numerical content in seconds against the supplement.

## T Rater Demographics

The 10-rater human validation panel (R01–R10; raw identities withheld) was drawn from the authors' professional network. Self-reported ML experience distribution at the time of the rating task (anonymous Likert form, no IRB-grade survey instrument): $\geq 5$ *years* (3 raters), *2–5 years* (5 raters), *1–2 years* (2 raters). All raters held at least a bachelor's degree in a computational field and reported familiarity with the "X is necessary for Y" assumption-recovery format used in the rating instrument. No personally identifying information beyond R01–R10 mappings is released; the raw rater CSVs are deliberately not included in the supplement (only the anonymised aggregate `annotation/g1_results.json` is). Participation was voluntary with a small honorarium or acknowledgment offered.