Clustering Effect of Adversarial Robust Models

Abstract

Adversarial robustness has received increasing attention along with the study of
adversarial examples. So far, existing works show that robust models not only
outperform under comprehensive adversarial attack evaluations but also boost the
performance in some downstream tasks. However, the underlying mechanism
of adversarial robustness is still not clear. In this paper, we explore adversarial
robustness from the perspective of linear components, and find that there exist
some statistical properties for comprehensively robust models. Specifically, robust
models show obvious hierarchical clustering effect on their linear sub-networks,
when removing or replacing all non-linear components (*e.g.*, batch normalization,
maximum pooling or activation layers). Based on these observations, we propose a
novel understanding of adversarial robustness and apply it on more tasks including
robustness boosting and domain adaption. Experimental evaluations show an
overall improvement and demonstrate the superiority of our proposed clustering
strategy.

1 Introduction

Nowadays, deep neural networks (DNNs) have shown a strong learning capacity through a huge
number of parameters and diverse structures [19, 28, 11, 2]. Meanwhile, adversary has raised increas-
ing security concerns on DNNs due to the observation of adversarial examples (*i.e.* the examples
mislead a classifier when crafted with human imperceptible but carefully designed perturbations)
[13]. Adversarial robustness and defense techniques have thus become crucial for deep learning,
yet many adversarial defense techniques are found with deficiencies such as obfuscated gradient
[3]. Up to now, the widely accepted techniques to improve adversarial robustness are adversarial
training variants [23], by training a DNN after data augmentation with the worst-case adversarial
examples. Recent study has found that not only do robust models show moderate robustness under
vast attacks, but also they can surprisingly boost the downstream tasks (*e.g.*, domain adaption task
with subpopulation shift) [30].

However, the underlying mechanism of adversarial robustness is still not clear. Existing studies have
explored adversary on some specific components of DNNs, such as batch normalization [12], skip
connection [31] or activation layers [14], which yield some enlightening understanding. On the other
hand, despite variation in DNNs' structure, the components can be roughly divided into linear and
non-linear ones. The non-linear components tend to be instance-wise. For example, adversarial and
benign examples tend to present different patterns on activation [4]. In contrast, for those linear
components, once the optimization is done and model evaluation mode is activated, they are shared
and fixed independently from inputs. Nowadays, the intrinsic relationship of adversary with linearity
has been studied. Some ascribes the adversary to linear accumulation of perturbations from inputs to
final outputs, dubbed 'accidental steganography' [13]. Some show that linear backward propagation
enhances adversarial transferability [31, 14]. Nevertheless, such mentioned linearity analyses are all

(a) VGG16-STD   (b) VGG16-AT   (c) VGG16-AT+C   (d) Class Hierarchy

Figure 1: Correlation matrices C of VGG-16 on CIFAR-10: a) 'STD' and b) 'AT' indicate standard and adversarial training, c) 'AT+C' indicates applying hierarchical clustering in adversarial training. Robust models tend to show clustering effect aligned with d) the class hierarchy of CIFAR-10, which is enhanced in c) our clustering adversarially trained model.

on the original non-linear models, which hinders a deeper understanding on linearity directly. Further essential exploration is encouraged.

In this paper, we thus study adversarial robustness on the statistical regularity of linear components. We provide a novel insight on adversarial robustness by showing the clustering effect well aligned with *class hierarchy*. As shown in Fig. 1(d), given a data set, superclasses are defined by grouping semantically similar subclasses together to form a hierarchy, *e.g.*, in CIFAR-10, 'Cat' and 'Dog' represent different subclasses/fine labels, despite both being the same superclasses/coarse labels, 'Animal'. Based on this, we conduct backward propagation on linear sub-networks of robust and non-robust DNNs (through adversarial/standard training respectively) to extract the corresponding implicit linear expression. In this fashion, we could obtain a $D_{\text{input}} \times D_{\text{output}}$ linear matrix W, which is extracted from inputs to predictive outputs. D_{input} represents for the dimension of one input data, specifically defined as width $\times$ height $\times$ channel. D_{output} represents for the dimension of one output vector, which is also the number of classes. We further study the correlation of vectors in W by matrix C, whose shape is $D_{\text{output}} \times D_{\text{output}}$. The details of W and C are introduced in Sec. 3.2. Then we find that robust models tend to show hierarchical clustering effect in correlation matrix C, which is surprisingly consistent with class hierarchy. For example, in Fig. 1 on CIFAR-10, the fine labels (0,1,8,9) belong to 'Non-animal', others belong to 'Animal'. The matrix C of robust model shows block clustering: values are close to '+1' in the two superclasses (0,1,8,9) and (2,3,4,5,6,7), and values are close to '-1' across these two superclasses. Such clustering effect is enhanced by our clustering regularization penalty in Fig. 1(c). This phenomenon could be semantically explained as subclasses from the same superclass share more feature similarities. Such hierarchical clustering effect can give a novel and insightful explanation on the superiority of robust models in some observed downstream tasks, as they can extract more semantic and representative features. To further confirm our findings, we enhance the hierarchical clustering effect in both adversarial robustness and downstream tasks, *e.g.*, domain adaption proposed in [30, 29]. The improvements of experimental results demonstrate that the superiority of robust models is closely related to their hierarchical classification capability. Our contributions are summarized as follows:

- To the best of our knowledge, we are the first to systematically analyze the statistical regularity of adversarially robust models (through adversarial training) compared to non-robust models (through standard training) on their linear sub-networks.

- We present an intriguing phenomenon of hierarchical clustering effect in robust models, and provide a novel yet insightful understanding of adversarial robustness. The clustering effect aligned with class hierarchy demonstrates more semantic and representative feature extraction capacity of robust models, which benefits a lot in various tasks.

- Based on the observations, we propose a plugged-in hierarchical clustering training strategy to generally enhance adversarial robustness and investigate some intriguing adversarial attack findings. Besides adversarial-related study, we further explore some downstream tasks with the understanding of hierarchical clustering, *e.g.*, domain adaption with subpopulation shift. Experimental results show that the clustering effect and hierarchical classification learned by robust model benefits the task as well.

2 Related Work

2.1 Adversarial Attack and Defense

Attack Given a clean example $\boldsymbol{x}$, its true label y, a DNN model $\mathcal{F}$ with parameters θ and its loss function $\mathcal{L}$, the goal of adversarial attack is to find an adversarial example $\boldsymbol{x}'$ that is close to clean example on pixel level but can fool $\mathcal{F}$ to give an incorrect prediction. Fast Gradient Sign Method (FGSM) [13] adds perturbations on clean example $\boldsymbol{x}$ by one step with step size ϵ:

$$\boldsymbol{x}' = \boldsymbol{x} + \epsilon \mathrm{sign}(\nabla_{\boldsymbol{x}} \mathcal{L}(\mathcal{F}(\boldsymbol{x}, \theta), y)). \tag{1}$$

Projected Gradient Descent (PGD) [23] adds perturbations on clean example $\boldsymbol{x}$ by K steps with smaller step size α. After every step (k-th) attack, adversarial example is projected into the ϵ-ball around clean example (function Π):

$$\boldsymbol{x}^k = \Pi(\boldsymbol{x}^{k-1} + \alpha \mathrm{sign}(\nabla_{\boldsymbol{x}} \mathcal{L}(\mathcal{F}(\boldsymbol{x}^{k-1}, \theta), y))). \tag{2}$$

There are other attack techniques, such as white-box CW [6], black-box $\mathcal{N}$Attack [21] and adaptive AutoAttack [9].

Defense Many adversarial defense techniques have been proposed since then, such as input pre-processing [18], defensive distillation [24], model compression [10] and adversarial training [23], etc. Among them, adversarial training variants are assumed to be most effective in comprehensive attack evaluations. They solve a min-max problem as:

$$\min_{\theta} \max_{\boldsymbol{x}' \in \mathcal{B}_\epsilon(\boldsymbol{x})} \mathcal{L}(\mathcal{F}(\boldsymbol{x}', \theta), y). \tag{3}$$

The inner maximum problem often generates adversarial examples by FGSM or PGD, while the outer minimum problem optimizes the worst-case loss. Some defense technique improves robustness through class-wise feature clustering [1], which is different from ours through instance-wise feature clustering defined in Sec. 4.1 Eq. 11.

2.2 Linearity Exploration in Adversary

Besides attack or defense techniques, the cause and understanding of adversary are studied. The linearity is one essential perspective with no doubt. Previous studies attribute the existing of adversarial examples to the linearity of DNNs [13] and observe the adversarial transferability enhancement on more linear models [31, 14]. Some works study linearity from another perspective by focusing on the properties of weight layers, *e.g.*, their norms, variances and orthogonality. L_p norm regularization works by pulling examples far away from the decision boundary, which comes as the side-effect of adversarial robustness [32, 17]. Spectral norm [7, 26] is useful in adversarial defense, which is defined as $\sigma_i = \frac{\|w_i \boldsymbol{x}\|_2}{\|\boldsymbol{x}\|_2}$ and is used to constrain the Lipschiz constant of a DNN $\mathcal{F}$ on $\boldsymbol{x}$ (assuming Lipschiz continuous):

$$\|\mathcal{F}(\boldsymbol{x} + \delta) - \mathcal{F}(\boldsymbol{x})\|_2 \leq \sigma \|\boldsymbol{x}\|_2 \leq \prod \sigma_i \|\boldsymbol{x}\|_2. \tag{4}$$

The weight scale shifting issue is also discussed in adversary [22], that is, scale of weights can be shifted between layers without changing the input-output function specified by the network, which could affect the capacity to regularize models. Then one weight scale shift invariant regularization is proposed and improves adversarial robustness. Moreover, the orthogonality could help improve generalization and adversarial robustness [5, 7] by inducing uncorrelated features. However, these experiments are all conducted on the original non-linear models instead of the linear components directly, which hinders a deeper understanding on linearity.

3 Observations on Linear Components

The robust models perform completely differently from non-robust ones especially under comprehensive adversarial attacks. However, the statistical regularity on linear components of these robust models is yet under little exploration. Different from related works, we explore linear components directly. To be specific, we extract a weight matrix expression of linear sub-networks, estimating the linear propagation from inputs to outputs.

3.1 Extracting a Linear Weight Matrix

Given a DNN $\mathcal{F}$ composed of L linear layers and non-linear components, the output $y = \mathcal{F}(\boldsymbol{x})$ could be expressed as

$$y = g_L(w_L \times g_{L-1}(w_{L-1} \times \ldots g_1(w_1 \times \boldsymbol{x} + b_1) \cdots + b_{L-1}) + b_L), \tag{5}$$

where g_i is a series of non-linear components (*e.g.*, activation function ReLUs), w_i and b_i are the expressions of linear ones. Then a corresponding linear sub-network of this original one could be extracted with the same weights and architectures, yet it removes activation function (*e.g.*, ReLU layers) and batch normalization layers, and further replaces maximum pooling layers with average pooling layers. This output of linear network $y_{\text{linear}} = \mathcal{F}_{\text{linear}}(\boldsymbol{x})$ is expressed as

$$y_{\text{linear}} = w_L \times (w_{L-1} \times \ldots(w_1 \times \boldsymbol{x} + b_1)\ldots + b_{L-1}) + b_L. \tag{6}$$

Thus in $\mathcal{F}_{\text{linear}}$, each input $\boldsymbol{x}$ is multiplied by an instance-agnostic total weight

$$W = w_L \times w_{L-1} \times \ldots w_1 + \sum_{i,j} b_i \ldots \times w_j \ldots. \tag{7}$$

However, such total weight expression W in DNNs is difficult to compute directly, because the multiplication of convolution layers is infeasible. Instead, we propose to compute W by applying backward propagation on the linear sub-network. To be specific, given a random input $\boldsymbol{x}$ and a pre-trained DNN $\mathcal{F}$, W is computed as the gradient propagated on linear sub-network $\mathcal{F}_{\text{linear}}$ following Algorithm 1.

Algorithm 1 Extracting the Linear Weight Matrix W

Input: A random input $\boldsymbol{x}$, a pre-trained DNN model $\mathcal{F}$ with D_{output} classes
Output: Weight matrix W
   Get the corresponding linear sub-network $\mathcal{F}_{\text{linear}}$ from $\mathcal{F}$
   Conduct forward propagation as: $y_{\text{linear}} = \mathcal{F}_{\text{linear}}(\boldsymbol{x})$
   for i in range(D_{output}) **do**
      $y_{\text{linear}}[i]$.backward()
      $W[:,i] = \boldsymbol{x}$.grad
   end for
   return W

3.2 Observation 1: Weight Clustering Effect

As indicated, though instance-wise performance varies on one specific DNN with non-linear components, it shares the same linear sub-network (*i.e.* parameters and linear structures) and thus the same implicit weight matrix W. As the implicit matrix W could estimate linear output scores y_{linear} of any input $\boldsymbol{x}$ when forward propagating on the linear sub-network, it hints some class-wise linear amplifications. After extracting W with shape $D_{\text{input}} \times D_{\text{output}}$, we further explore the correlation across classes by normalizing weight vectors in W (to avoid the class-wise scale variance) and computing a correlation matrix C following

$$C_{i,j} = \frac{W_i^T}{\|W_i^T\|_2} \times \frac{W_j}{\|W_j\|_2}. \tag{8}$$

In such fashion, the matrix C, whose shape is $D_{\text{output}} \times D_{\text{output}}$, has all elements in [-1, 1]. $C(i,j)$ represents for cosine value of two weight vectors corresponding to class i and j on linear sub-networks, which also represents for the correlation of class-wise weight vectors. If the element $C(i,j)$ is close to 1, it means that i-th and j-th class-wise weight vectors are strongly positive correlated in the linear weight space, which also demonstrates that class i and j are more likely to be positively related with each other.

Datasets and Setups Beside Fig. 1, we show more clustering effect across data sets using STL-10 [8] and two reconstructed data sets CIFAR-20 and ImageNet-10, composed of 20/10 subclasses from 4/2 superclasses in CIFAR-100 and TinyImageNet [27]. The details of constructed data sets are in Appendix Table 1. For robust models, we adversarially train ResNet-18 [15] using PGD-10

(a) STL-AT (b) CIFAR10-AT (c) CIFAR20-AT (d) ImageNet10-AT

(e) STL-STD (f) CIFAR10-STD (g) CIFAR20-STD (h) ImageNet10-STD

Figure 3: Correlation weight matrix C of ResNet-18 on different data sets. 'AT' indicates adversarial training. 'STD' indicates standard training. Robust models tend to show weight clustering effect aligned with class hierarchy.

($\epsilon = 8/255$ and step size $2/255$) with a random start. The non-robust models are standard trained. Both models are trained for 200 epochs using SGD with momentum 0.9, weight decay 2e-4, and initial learning rate 0.1 which is divided by 10 at the 75-th and 90-th epoch. All experiments in this paper is run with one GPU 1080x.

Result Analysis We plot the correlation matrix C in Fig. 3. Similar to Fig. 1 on CIFAR-10, the similar block clustering effect is observed on robust models and aligns well with class hierarchy. To be specific, in Fig. 3(a) and 3(b) on STL-10, fine labels (0,2,8,9) belong to 'Non-animal', others belong to 'Animal', and the matrix C of robust model shows block clustering: values close to '+1' in the two superclasses (0,2,8,9) and (1,3,4,5,6,7), values close to '-1' across these two superclasses. Such phenomena hint the fundamental connection of adversarial robustness with weight clustering effect. That is, subclasses in the same superclass are positively related to each other, which is in contrast with those in different superclasses. This hierarchical classification property is more semantic with data sets, demonstrating that robust model has a better representative feature extraction capacity and thus outperforms a standard model in various tasks.

3.3 Observation 2: Feature Clustering Effect

(a) CIFAR10-AT (b) CIFAR10-STD

Figure 2: Feature distance matrix E of ResNet-18 on CIFAR-10. 'AT' indicates adversarial training. 'STD' indicates standard training. Robust models show feature clustering effect aligned with class hierarchy, which is similar to C.

Besides the weight clustering effect, we further analyze the feature clustering effect by evaluating a class-wise feature distance matrix D of original non-linear DNNs on CIFAR-10 following Eq. 10. Given data pairs $(\boldsymbol{x}_i, y_i)$, their features $\boldsymbol{z}_i$, we compute the class-wise feature centers $\boldsymbol{Z}_j$ for class j following

$$\boldsymbol{Z}_j = \text{mean } \boldsymbol{z}_i \cdot \mathbb{1}(y_i = j) \qquad (9)$$

$E(a, b)$ represents the distance of class-wise feature centers $\boldsymbol{Z}_a$ and $\boldsymbol{Z}_b$, which is normalized with the largest class-wise distances for a better visualization.

$$E(a, b) = \frac{\|\boldsymbol{Z}_a - \boldsymbol{Z}_b\|_2}{\max\limits_{c, c \neq a} \|\boldsymbol{Z}_a - \boldsymbol{Z}_c\|_2}. \qquad (10)$$

Result Analysis We adopt the same basic setting as Sec. 3.2, and find a similar clustering effect in Fig. 2. That is, the centers of subclasses in the same superclass lie closer to each other in feature space. The feature clustering effect also aligns well with class hierarchy. Such effect further confirm our understanding that robust models learn a better feature extraction even in their original non-linear feature space, where features are more semantic and hierarchical.

4 Explorations with Clustering Effect

4.1 Adversarial Exploration

We have observed the block clustering in both linear weight correlation matrix C and non-linear feature distance matrix E. In this section, we further conduct extensive experiments to explore such an intriguing clustering effect along with other adversarial phenomena. The experiments are designed from two perspectives, 1) adversarial robustness enhancement and 2) attack confusion matrix study. The results show that adversarial robustness could be improved by enhancing the hierarchical clustering effect, and attack success rates are highly related to class hierarchy as well.

4.1.1 Adversarial Robustness Enhancement

We apply the clustering effect as a penalty to improve adversarial robustness. Given any unknown data set, we first extract its class hierarchy from a pre-trained robust model, *e.g.*, trained by adversarial training. To be specific, we compute matrices W and C following Sec. 3.2. We then formulate C to an approximate matrix C_{op} with all items set to '-1' or '+1', *i.e.* in C_{op}, subclasses in the same superclass block have values '+1', else have values '-1'. With the extracted class hierarchy, a regularization loss is designed to minimize outputs within the same superclass. Take the data set CIFAR-10 for example, subclasses are divided into (0,1,8,9) and (2,3,4,5,6,7) in C_{op}. The regularization loss is defined in Eq. 11. The hierarchical instance-wise clustering training strategy is proposed following Algorithm 2.

$$
\begin{aligned}
F_0 &= \mathbb{E}_x \mathcal{F}(\boldsymbol{x})_i \cdot \mathbb{1}(i = 0, 1, 8, 9) \\
F_1 &= \mathbb{E}_x \mathcal{F}(\boldsymbol{x})_j \cdot \mathbb{1}(j = 2, 3, 4, 5, 6, 7) \\
\mathcal{L}_{\mathrm{reg}}(\boldsymbol{x}) &= \sum_{i=0,1,8,9} \|\mathcal{F}(\boldsymbol{x})_i - F_0\|_2 + \sum_{j=2,3,4,5,6,7} \|\mathcal{F}(\boldsymbol{x})_j - F_1\|_2.
\end{aligned}
\tag{11}
$$

Algorithm 2 Robustness Improvement by Enhancing the Hierarchical Clustering Effect

---

Input: A random input $\boldsymbol{x}$, a pre-trained robust DNN model $\mathcal{F}$ (*e.g.*, on CIFAR-10)
Output: Robustness Enhanced Model $\mathcal{F}$
    Compute the weight correlation matrix C following Algorithm 1 and Eq. 8
    Compute an approximate matrix C_{op} with all items '+1/-1' based on C and extract class hierarchy
    Compute regularization loss $\mathcal{L}_{\mathrm{reg}}(\boldsymbol{x})$ with feature clusters following Eq. 11
    Retrain $\mathcal{F}$ from scratch using the original robust loss $\mathcal{L}(\boldsymbol{x}, y)$ (*e.g.*, adversarial training loss) added with $\mathcal{L}_{\mathrm{reg}}$
    return $\mathcal{F}$

Datasets and Setups We adversarially train a robust ResNet-18 on CIFAR-10. The basic training setting is the same with Sec. 3.2. The PGD-20 attack is applied with $\epsilon = 8/255$ and step size 0.003.

Results Analysis Although the main exploration of clustering effect is studied not only in robustness improvement, we conduct comprehensive robustness evaluations following the state-of-the-art attack list or strategy, with an adaptive AutoAttack [9]. We find that the clustering enhancement actually boosts adversarial robustness in Table 1 for both best and last checkpoints. For black-box attacks, the surrogate model is a standard trained VGG-16. $\mathcal{N}$Attack is conducted on 1,000 random test data and with a maximum query 20,000. Note that, the improvement against AutoAttack is 1.31%, which shows that the clustering alignment with coarse labels learned by robust models could indeed boost adversarial robustness. An interesting phenomenon is that when enhancing clustering effect, both natural and robust accuracies are improved because the clustering effect improves feature representation. The natural accuracy by standard training improves as well (from 92.75% to 93.54%) with a clustering effect. Therefore, the trade-off between adversarial robustness and natural accuracy still exists. In addition, we count the training time of two models (AT and AT+**C**). The AT model costs 191.20s per epoch, while the AT+**C** model costs 193.66s, using one GPU 1080X and batch size 128 of ResNet-18 on CIFAR-10. The time cost slightly increases with the clustering regularization, which is negligible. More results are shown in Appendix Table 8.

4.1.2 Attack Confusion Matrix

To further analyze how class hierarchy matters in adversary, we evaluate the attack confusion matrix M of adversarial examples in Fig. 4, whose shape is $D_{\mathrm{output}} \times D_{\mathrm{output}}$. $M(i, j)$ is defined as attack

Table 1: Robustness (accuracy (%) on various attacks) on CIFAR-10, based on the best/last checkpoint of ResNet-18. 'AT' indicates adversarial training. '**+C**' indicates applying our hierarchical instance-wise clustering training strategy. The best results are **boldfaced**.

Defense		White-box				Black-box			Adaptive
		Natural	FGSM	PGD-20	CW_∞	PGD-20	CW_∞	$\mathcal{N}$Attack	AutoAttack
AT	Best	84.20	63.32	50.12	50.97	81.80	84.80	48.21	46.58
	Last	84.27	60.46	46.50	48.97	79.13	**79.87**	45.05	41.90
AT+C	Best	**85.43**	**64.11**	**52.54**	**52.72**	**82.27**	**85.22**	**50.51**	**47.21**
	Last	**85.53**	**62.11**	**47.78**	**49.95**	**80.21**	78.98	**47.51**	**43.21**

(a) UNTARGET-AT   (b) UNTARGET-STD   (c) TARGET-AT   (d) TARGET-STD

Figure 4: Attack confusion matrix M under different settings. 'AT'/'STD' indicate adversarial/standard training. Robust models tend to show clustering effect aligned with class hierarchy.

success rate (ASR) of adversarial examples being attacked from the ground-truth label i to the target label j.

Datasets and Setups We train robust and non-robust ResNet-18s on CIFAR-10. The basic setting is the same with Sec. 3.2. The PGD-20 attack is applied with $\epsilon = 8/255$ and step size 0.003. For the target attack, target labels are set as the other 9 classes except for the ground-truth one.

Results Analysis Experimental results show that the attack confusion matrix M performs in another blocking pattern especially on robust models, which is well-aligned with class hierarchy as well as the weight correlation matrix C and the feature distance matrix E. That is, the difficulty in attacking robust models shows distinguishing performance for subclasses in or out of the same superclass. For example, against untarget PGD-20 attack in Fig. 4(a), the ASRs on adversarially trained ResNet-18 show that classes in (2,3,4,5,6,7) are easier to be attacked from one to other. However, the ASRs could decline to almost zero from one superclass (0,1,8,9) to the other (2,3,4,5,6,7). Different superclasses are harder to attack especially on robust models, demonstrating that the hierarchical classification capacity is enhanced by adversarial robustness. Such phenomenon is also consistent with our hierarchical clustering observations on robust models.

4.2 Domain Adaption Exploration

Recent study shows that robust models tend to perform better in downstream tasks, especially domain adaption with subpopulation shift [30]. However, further analyses are insufficient. We study from two perspectives, 1) verifying how robust models outperform in domain adaption with different settings and 2) exploring a further improvement by enhancing the clustering effect. Specifically, we randomly divide a hierarchical data set into source data and target data according to their subclasses. That is, source and target data share the same superclass yet different subclasses, dubbed subpopulation shift. In the training phase, we use fine labels of source data and map fine labels to coarse ones. In such a fashion, the model returns fine and coarse labels. Only coarse label is evaluated in the test phase as the target test data has different fine labels from source data. Both coarse and fine accuracies are evaluated on source domain. We enhance the feature clustering effect by a penalty loss defined in Sec. 4.1 Eq. 11. To better utilize hierarchical features extracted by pre-trained models, we also finetune parameters on target data to achieve a further improvement. Different models, different constructed data sets and different adversarial training settings (*i.e.* adversarial robustness levels) are evaluated and analyzed.

4.2.1 Different Models

Datasets and Setups The data set CIFAR-100 is composed of 20 superclasses, and each superclass is composed of 5 subclasses. Based on that, we construct our own data sets by randomly sampling from CIFAR-100, *e.g.*, our default CIFAR-20 is composed of 20 subclasses from 4 superclasses. The

details of all constructed data sets are shown in Appendix Table 1. We adversarially train ResNet-18, DenseNet-121 [16], and AlexNet [20] with PGD. If not specifically mentioned, PGD-5 is adopted (5 steps, step size 1/255, ϵ=2/255). The robust/non-robust ResNet-18 and DenseNet-121 are trained with SGD [25] and a initial learning rate 0.1. The robust/non-robust AlexNet are trained with SGD and a initial learning rate 0.01. The learning rates decay with a factor of 0.1 at the 75 and 90 epoch. Other hyper-parameters are the same with Sec. 3.2. Moreover, we finetune the pre-trained models on target data for 20 epochs with a learning rate 0.01.

Results Analysis We evaluate the models on our default CIFAR-20. As shown in Table 2, when comparing the coarse accuracies on target and source data, robust models tend to decline less than non-robust ones. Take pre-trained ResNet-18s for example, the coarse accuracy on robust model directly declines by 5.44% (from 87.94% to 82.50%) but declines by 10.18% (from 90.93% to 80.75%) on non-robust model. When considering finetuned models, the superiority of robust models outstands. For example, the coarse accuracy on finetuned robust ResNet-18 increases by 6.46% (from 87.94% to 94.40%) while increases by 3.32% (from 90.93% to 94.25%) on finetuned non-robust ResNet-18. When applying the clustering penalty defined in Eq. 11, coarse accuracy is improved by 2.25% on robust ResNet-18 (from 82.50% to 84.75%) even without finetuning. Experimental results demonstrate that features extracted by robust models have a non-trivial impact on domain adaptation. Such superiority keeps consistent when finetuning with the feature centers of target training data. Thus our understanding is confirmed that a better hierarchical classification learned by robust models benefits a lot in downstream domain adaption task.

Table 2: Accuracy (%) on CIFAR-20 across various models. 'Coarse' and 'Fine' indicate the ground-truth labels are coarse or fine respectively. 'FT' indicates the pre-trained models are finetuned on target data. 'R' indicates robust models (by adversarial training). 'NR' indicates non-robust models (by standard training). '+C' indicates robust models with an enhanced clustering effect defined in Eq. 11.

		Source Domain		Target Domain	
		Coarse	Fine	Coarse	Coarse-FT
AlexNet	NR	85.50	65.37	71.75	86.70
	R	84.75	64.50	**72.75**	**87.50**
	R+C	90.68	65.56	**75.25**	**89.25**
ResNet-18	NR	90.93	70.62	80.75	94.25
	R	87.94	68.75	**82.50**	**94.40**
	R+C	88.25	69.62	**84.75**	**94.75**
DenseNet-121	NR	92.31	73.56	77.25	95.50
	R	90.18	72.87	**81.00**	**95.75**
	R+C	91.37	73.87	**85.25**	**96.50**

4.2.2 Different Data Sets

Datasets and Setups For CIFAR-100, we randomly select 4 to 6 superclasses, select 4 subclasses from each superclass for training and apply the left one for test. We also select 5 superclasses, select 3 subclasses from each superclass for training and apply the left 2 subclasses for test. When selecting 4 superclasses and 4 subclasses, we typically design two extreme data set construction methods, *i.e.* the most different and similar data set. The 'different' 4 superclasses are selected as index 1, 2, 5, 14 (fish, flowers, household electrical devices, people). The 'similar' 4 superclasses are selected as index 8, 11, 12, 16, which are all animals. The reconstructed data set ImageNet-20 is composed of 20 subclasses from 4 superclasses in TinyImageNet. The details of datasets are in Appendix Table 2. We conduct experiments on ResNet-18s in this section.

Results Analysis As shown in Fig. 5, we find that experimental results on different data sets show different yet consistent performances: robust models show great superiority on those more hierarchical data sets, which can be boosted with an enhanced clustering effect. *e.g.*, In Fig. 5(a), our constructed data sets from CIFAR-100 and TinyImageNet show superiority with robustness and an enhanced clustering. Moreover, a better class hierarchy of data set enhances domain adaption tasks. For example, orange points (*i.e.* the 'different' data set) in both two subfigures in Fig. 5(b) tend to present lower source accuracies yet higher target accuracies, especially compared with lightseagreen points (*i.e.* the 'random' data set). For 'similar' data sets, because the class hierarchy is not obvious, target accuracy drops a lot. However, the royalblue start point (*i.e.* 'R+C' version model trained on 'similar' data set) still achieves the highest target accuracies among three models trained on 'similar' data set. We show the specific numerical results in Appendix Table 4 and 6.

(a)   (b)

Figure 5: Comparisons of target accuracy across different data sets. Different colors indicate different data set construction methods. Different shapes indicate different training methods, *i.e.* adversarial or standard training. Circle indicates non-robust model (NR), square and start indicate robust model without/with an enhanced clustering effect (R/R+C) respectively. Pentagon, diamond and octagon indicate finetuning NR/R/R+C models respectively. The legend in format $A * B$: A indicates the number of selected superclasses, B indicates the number of selected subclasses from each superclass for training. The points located in left and upper represent for better performances as they have lower source accuracies yet higher target accuracies.

4.2.3 Different Robustness Settings

Datasets and Setups We evaluate ResNet-18s with different robustness settings (*i.e.* different PGDs in adversarial training) on random CIFAR-4⋆4 defined in Appendix Table 2. The PGD details are given in Appendix Table 3.

Figure 6: Comparisons of target accuracy across different adversarial robustness levels (*i.e.* different adversarial training settings). Different colors indicate different PGD attack settings in adversarial training. Circle and square indicate robust model without/with an enhanced clustering effect (R/R+C). Pentagon and diamond indicate finetuning R/R+C model respectively. The points located in left and upper represent for better performances as they have lower source accuracies yet higher target accuracies.

Results Analysis As shown in Fig. 6, we could observe a trade-off between adversarial robustness and accuracies on target data. For example, in the polylines of both two subfigures, purple points show higher accuracies on target data than brown ones. However, brown points are of better robustness as their accuracies on source data are much lower. Royalblue points show the relatively bad performance on target data yet the best performance on source data. The phenomena demonstrate a trade-off between robustness and domain adaption performances. The better performance on target domain could only be achieved with both robustness and moderate accuracies on source data. Furthermore, robust model with an enhanced clustering effect has significantly results than the original robust model. We show the specific numerical results in Appendix Table 5. In addition, the time costs results with different robustness settings are shown in Appendix Table 7.

5 Conclusions

In this paper, we provide a novel view of linear model exploration by extracting an implicit linear matrix expression. Then we surprisingly find an intriguing clustering effect on adversarially robust models, which is well-aligned with class hierarchy. Based on such observations, we first give an insightful explanation and understanding of robust models, which have a better capacity in extracting more representative features and semantic information. Extensive experiments show that enhancing the hierarchical clustering effect not only improves model robustness, but also benefits other downstream domain adaption task. Overall, our observations and findings motivate a deeper understanding on adversarial robustness.

References

[1] Motasem Alfarra, Juan C Pérez, Adel Bibi, Ali Thabet, Pablo Arbeláez, and Bernard Ghanem. Clustr: Clustering training for robustness. *arXiv e-prints*, pages arXiv–2006, 2020.

[2] Dario Amodei, Sundaram Ananthanarayanan, Rishita Anubhai, Jingliang Bai, Eric Battenberg, Carl Case, Jared Casper, Bryan Catanzaro, Qiang Cheng, Guoliang Chen, et al. Deep speech 2: End-to-end speech recognition in english and mandarin. *ICML*, pages 173–182, 2016.

[3] Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. *ICML*, 2019.

[4] Yang Bai, Yuyuan Zeng, Yong Jiang, Shu-Tao Xia, Xingjun Ma, and Yisen Wang. Improving adversarial robustness via channel-wise activation suppressing. *ICLR*, 2021.

[5] Nitin Bansal, Xiaohan Chen, and Zhangyang Wang. Can we gain more from orthogonality regularizations in training deep networks? *Advances in Neural Information Processing Systems*, 31:4261–4271, 2018.

[6] Nicholas Carlini and David Wagner. Defensive distillation is not robust to adversarial examples. *arXiv:1607.04311*, 2016.

[7] Moustapha Cissé, Piotr Bojanowski, Edouard Grave, Yann Dauphin, and Nicolas Usunier. Parseval networks: Improving robustness to adversarial examples. *ICML*, 2017.

[8] Adam Coates, Andrew Ng, and Honglak Lee. An analysis of single-layer networks in unsupervised feature learning. *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics*, 15:215–223, 11–13 Apr 2011.

[9] Francesco Croce and Matthias Hein. Reliable evaluation of adversarial robustness with an ensemble of diverse parameter-free attacks. *ICML*, 2020.

[10] Nilaksh Das, Madhuri Shanbhogue, Shang-Tse Chen, Fred Hohman, Siwei Li, Li Chen, Michael E Kounavis, and Duen Horng Chau. Compression to the rescue: Defending from adversarial attacks across modalities. *KDD*, 2018.

[11] Li Deng, Geoffrey Hinton, and Brian Kingsbury. New types of deep neural network learning for speech recognition and related applications: An overview. *2013 IEEE international conference on acoustics, speech and signal processing*, pages 8599–8603, 2013.

[12] Angus Galloway, Anna Golubeva, Thomas Tanay, Medhat Moussa, and Graham W Taylor. Batch normalization is a cause of adversarial vulnerability. *ICML Workshop*, 2019.

[13] Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *ICLR*, 2015.

[14] Yiwen Guo, Qizhang Li, and Hao Chen. Backpropagating linearly improves transferability of adversarial examples. *NeurIPS*, 2020.

[15] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. *CoRR*, abs/1512.03385, 2015.

[16] G. Huang, Z. Liu, L. Van Der Maaten, and K. Q. Weinberger. Densely connected convolutional networks. *CVPR*, pages 2261–2269, 2017.

[17] Daniel Jakubovitz and Raja Giryes. Improving dnn robustness to adversarial attacks using jacobian regularization. *ECCV*, September 2018.

[18] Xiaojun Jia, Xingxing Wei, Xiaochun Cao, and Hassan. Foroosh. Comdefend: An efficient image compression model to defend adversarial examples. *CVPR*, 2019.

[19] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Advances in neural information processing systems*, 25:1097–1105, 2012.

[20] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Advances in Neural Information Processing Systems*, 25:1097–1105, 2012.

[21] Yandong Li, Lijun Li, Liqiang Wang, Tong Zhang, and Boqing Gong. Nattack: Learning the distributions of adversarial examples for an improved black-box attack on deep neural networks. *ICML*, 2019.

[22] Ziquan Liu, Yufei Cui, and Antoni B Chan. Improve generalization and robustness of neural networks via weight scale shifting invariant regularizations. *arXiv preprint arXiv:2008.02965*, 2020.

[23] Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *ICLR*, 2018.

[24] Nicolas Papernot, Patrick McDaniel, Xi Wu, Somesh Jha, and Ananthram Swami. Distillation as a defense to adversarial perturbations against deep neural networks. *S&P*, 2016.

[25] Ning Qian. On the momentum term in gradient descent learning algorithms. *Neural networks*, 12(1):145–151, 1999.

[26] Kevin Roth, Yannic Kilcher, and Thomas Hofmann. Adversarial training generalizes data-dependent spectral norm regularization. *arXiv 1906.01527*, 2019.

[27] Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael S. Bernstein, Alexander C. Berg, and Fei-Fei Li. Imagenet large scale visual recognition challenge. *CoRR*, abs/1409.0575, 2014.

[28] Tara N Sainath, Abdel-rahman Mohamed, Brian Kingsbury, and Bhuvana Ramabhadran. Deep convolutional neural networks for lvcsr. *2013 IEEE international conference on acoustics, speech and signal processing*, pages 8614–8618, 2013.

[29] Hadi Salman, Andrew Ilyas, Logan Engstrom, Ashish Kapoor, and Aleksander Madry. Do adversarially robust imagenet models transfer better? *arXiv preprint arXiv:2007.08489*, 2020.

[30] Shibani Santurkar, Dimitris Tsipras, and Aleksander Madry. Breeds: Benchmarks for subpopulation shift. *ICLR*, 2021.

[31] Dongxian Wu, Yisen Wang, Shu-Tao Xia, James Bailey, and Xingjun Ma. Rethinking the security of skip connections in resnet-like neural networks. *ICLR*, 2020.

[32] Ziang Yan, Yiwen Guo, and Changshui Zhang. Deep defense: Training dnns with improved adversarial robustness. *Advances in Neural Information Processing Systems*, 31:419–428, 2018.