Do We Need Neural Collapse? Learning Diverse Features for Fine-grained and Long-tail Classification

Abstract

Feature extractors *learned* from supervised training of deep neural networks have demonstrated superior performance over *handcrafted* ones. Recently, it is shown that such learned features have a *neural collapse* property, where within-class features collapse to the class mean and different class means are maximally separated. This paper examines the neural collapse property in the context of fine-grained classification tasks, where a feature extractor pretrained from a classification task with *coarse* labels is used for generating features for a downstream classification task with *fine-grained* labels. We argue that the within-class feature collapse is an undesirable property for fine-grained classification. Hence, we introduce a geometric arrangement of features called the *maximal-separating-cone*, where within-class features lie in a cone of nontrivial radius instead of collapsing to the class mean, and cones of different classes are maximally separated. We present a technique based on classifier weight and training loss design to produce such an arrangement. Experimentally we demonstrate an improved fine-grained classification performance with a feature extractor pretrained by our method. Moreover, our technique also provides benefits for classification on data with long-tail distribution over classes. Our work may motivate future efforts on the design of better geometric arrangement of deep features.

1 Introduction

The extraction of *features* or *representations* from image, language, and speech data in their raw forms is a problem of fundamental interest in machine learning. For classification tasks, a standard approach in classical machine learning is to handcraft a feature extractor that maps from the input to the feature space (Lowe, 2004), and learn a classifier on the features from labeled datasets. The effectiveness of this approach relies critically on the quality of the feature extractor, the design of which often requires meticulous and onerous work of human and domain experts. With the success of deep learning, methods based on *learned* instead of handcrafted feature extractors have become very popular. In such approaches, feature extractors are parameterized with a deep neural network and trained jointly with a linear classifier on the features using a labeled dataset. Such an approach not only requires less human expertise, but also exhibits better empirical performance compared to handcrafted feature extractors (Krizhevsky et al., 2017). Moreover, deep features extractors obtained from a pre-training classification task can be used for downstream tasks by simply training a task-specific classifier, which often offers good empirical performance (Yosinski et al., 2014).

Despite great empirical success, a mathematical understanding of deep feature extractors have been largely missing. Towards understanding the properties of deep features, a recent line of work studies features extracted at the terminal phrase of training a deep classification model. They show that the geometry of such features have a simple and elegant form:

- Within each class, the features are maximally concentrated and collapse to the class mean.
- Across different classes, the features are maximally separated. Namely, the distance between each pair of class means is the same and that distance is at the maximum.

This phenomenon is called *Neural Collapse* ($\mathcal{NC}$) in Papyan et al. (2020). The occurrence and prevalence of $\mathcal{NC}$ is verified empirically through experiments with a variety of datasets and network

Figure 1: Fine-grained classification with $\mathcal{NC}$ vs. diverse features. We train a ResNet32 on CIFAR-20, which contains 20 coarse classes, and use the features for classification on CIFAR-100, which contains 100 fine-grained class labels of the 20 coarse classes. The plots provide a visualization of randomly sampled features from three selected coarse classes (enclosed in dashed circles), each with two selected fine-grained classes (shown with different colors). Our visualization uses the technique of Müller et al. (2019). (a) With cross-entropy (CE) loss, within-class features collapse and fine-grained classes are less distinguishable. (b) With our method (i.e., Hinge CE), within-class features are diverse and fine-grained classes are more distinguishable.

architectures (Han et al., 2021). Motivated by such an observation, recent work provided theoretical analysis of deep features under the so-called *unconstrained feature models* (Mixon et al., 2020; Fang et al., 2021), where the features are considered to be free optimization variables for the reason that deep neural networks have sufficient expressive power to produce any features for any training dataset. In particular, Lu & Steinerberger (2020); Weinan & Wojtowytsch (2020); Mixon et al. (2020); Graf et al. (2021); Fang et al. (2021); Ji et al. (2021); Tirer & Bruna (2022) show that $\mathcal{NC}$ solutions are global optimal solutions for the nonconvex objective functions. Moreover, Zhu et al. (2021); Zhou et al. (2022) show that such nonconvex problems have a benign global landscape hence $\mathcal{NC}$ can be easily obtained by standard training algorithms. The study of $\mathcal{NC}$ arguably brings us a better understanding of the properties of the deep features. Nonetheless, existing study does not provide an answer to the following question:

Is Neural Collapse the desired property for deep features?

Contribution. We provide a study of whether $\mathcal{NC}$ is the desired property for deep features by considering a specific learning task. In particular, we consider the fine-grained classification task, where a deep learning model is first pretrained on a classification dataset with *coarse* class labels, and use the features extracted from such a model for a downstream classification task with *fine-grained* classes. For example, the pretraining task contains a coarse class, say *flower*, that contains all variants of flowers, while the fine-grained task may give each variant of flower a different class label. If $\mathcal{NC}$ occurs hence all features for the coarse class collapse to the class mean, then such features do not distinguish between different fine-grained classes hence cannot be used to successfully perform fine-grained classification. This simple thought experiment demonstrates that $\mathcal{NC}$ is not a desired property for fine-grained classification.

Motivated by the observation above, we argue that deep features extracted during pretraining should not have the $\mathcal{NC}$ property for the task of fine-grained classification. Instead, the features for each pretraining class should be *diverse* to a certain extent, so that variation within the class is preserved and can benefit fine-grained classification. To realize this idea, we introduce a geometric arrangement of deep features called the *maximal-separating-cone* (MSC), where features of each class lie inside a *cone* with a nontrivial radius (i.e. instead of collapsing to class mean as in $\mathcal{NC}$), and the axes of the cones are maximally separated. See Figure 2 for an illustration. To obtain such an arrangement, we present a technique based on the simple idea that, if a feature lies inside its cone, then its loss is set to be a constant by a hinge function. Figure 1 provides a comparison of $\mathcal{NC}$ features and our MSC features for fine-grained classification with CIFAR-20 and CIFAR-100. The contribution of this work is summarized as follows.

- We design a MSC arrangement of deep features where within-class features are diverse within a cone instead of collapsing to the class mean (as in $\mathcal{NC}$).

- We present a generic technique based on the design of classifier weight and training loss function to obtain MSC features.

Figure 2: Conceptual illustration of features obtained from deep learning based classification models. Each ball represents a feature vector for an input in the training set. (Left) Neural collapse features obtained by standard training (Section 2.2), where within each class, all features collapse to the class mean. (Right) Maximal-separating-cone features that our method obtains (Section 3.1), where within each class, the features lie in a cone and the axes of the cones are maximally separated.

- We conduct experiments on fine-grained classification to demonstrate the effectiveness of our method. We also provide ablation study to justify the design of each component in our method.
- Aside from fine-grained classification, we demonstrate that our method also improves the performance for classification with training data that has imbalanced number of samples for different classes (i.e., long-tail data).

2 BACKGROUND

In this section, we start by reviewing the basics of deep learning based classification in Section 2.1, where a feature extractor parameterized by a deep neural network and a linear classifier on the features are jointly learned from a training dataset. Then, Section 2.2 explains $\mathcal{NC}$ which characterizes the features and classifier obtained from training a deep learning based classification model.

2.1 DEEP LEARNING BASED CLASSIFICATION

Consider the classification task where the goal is to predict the label $y \in [K] \doteq \{1, \ldots, K\}$ for an input $\boldsymbol{x} \in \mathbb{R}^n$, where K is the number of classes. With deep learning based classification, this is typically achieved by training a model with the following optimization objective:

$$\min_{\boldsymbol{\theta}, \boldsymbol{W}, \boldsymbol{b}} \frac{1}{N} \sum_{i=1}^{N} \mathcal{L}\big([v_{i1}, \ldots, v_{iK}], y_i\big), \ \text{ s.t. } \ \boldsymbol{u}_i = f(\boldsymbol{x}_i, \boldsymbol{\theta}), \ \ v_{ik} = \langle \boldsymbol{u}_i, \boldsymbol{w}_k \rangle + b_k, \tag{1}$$

where $\{\boldsymbol{x}_i, y_i\}_{i=1}^{N}$ is a training dataset of input-label pairs. In above, $f(\cdot, \boldsymbol{\theta}) : \mathbb{R}^n \to \mathbb{R}^m$ is the feature extractor implemented as a deep neural network with trainable parameters $\boldsymbol{\theta}$. The output $\boldsymbol{u}_i$ of the feature extractor is referred to as the feature of $\boldsymbol{x}_i$. The other two optimization variables in (1), namely $\boldsymbol{W} = [\boldsymbol{w}_1, \ldots, \boldsymbol{w}_K] \in \mathbb{R}^{m \times K}$ and $\boldsymbol{b} = [b_1, \ldots, b_K] \in \mathbb{R}^K$, are parameters of a linear classifier. The vector $[v_{i1}, \ldots, v_{iK}]$ is often referred to as the *logit* vector for data $\boldsymbol{x}_i$. The loss function $\mathcal{L}(\cdot, \cdot)$ is defined on the logits and the label. One of the most popular choice of $\mathcal{L}(\cdot, \cdot)$ is the cross-entropy (CE) loss:

$$\mathcal{L}_{\text{CE}}\big([v_{i1}, \ldots, v_{iK}], y_i\big) \doteq -\log\left(\frac{\exp(v_{i,y_i})}{\exp(v_{i,y_i}) + \sum_{k \neq y_i} \exp(v_{ik})}\right). \tag{2}$$

2.2 NEURAL COLLAPSE ($\mathcal{NC}$)

$\mathcal{NC}$ is a phenomenon for the features obtained at terminal phase of training a deep learning based classification model (Papyan et al., 2020). Let $(\boldsymbol{\theta}^*, \boldsymbol{W}^*, \boldsymbol{b}^*)$ be the solution to (1). Then, $\mathcal{NC}$ states that the learned features $\{\boldsymbol{u}_i^* \doteq f(\boldsymbol{x}_i, \boldsymbol{\theta}^*)\}_{i=1}^{N}$ have the following properties (see also Figure 2(a)).

(i) $\mathcal{NC}$**1: Within-class Variability Collapse.** For each class $k \in [K]$, the features $\{\boldsymbol{u}_i^* \mid i : y_i = k\}$ collapse to the class mean $\boldsymbol{\mu}_k^* \doteq \frac{\sum_{i:y_i=k} \boldsymbol{u}_i^*}{\sum_{i:y_i=k} 1}$.

(ii) $\mathcal{NC}$**2: Between-class Maximal Separation.** Let $\boldsymbol{\mu}_G^* = \frac{1}{K} \sum_{k=1}^{K} \boldsymbol{\mu}_k^*$ be the global mean. Then, the class means after subtracting the global mean, i.e., $\{\boldsymbol{\mu}_k^* - \boldsymbol{\mu}_G^* \mid k \in [K]\}$ are maximally distant

and located on a sphere centered at origin. More precisely, they form a simplex equiangular tight frame (Simplex ETF) up to a rotation and scaling:

$$[\boldsymbol{\mu}_1^* - \boldsymbol{\mu}_G^*, \ldots, \boldsymbol{\mu}_K^* - \boldsymbol{\mu}_G^*] = s \boldsymbol{U} \boldsymbol{W}_{\text{ETF}}, \tag{3}$$

where $s > 0$ is an arbitrary scaling and $\boldsymbol{U} \in \mathbb{R}^{m \times K}$ is an arbitrary rotation (i.e., orthonormal matrix)[1] of the Simplex ETF. In above, $\boldsymbol{W}_{\text{ETF}}$ is a matrix that defines a Simplex ETF:

$$\boldsymbol{W}_{\text{ETF}} \doteq \sqrt{\frac{K}{K-1}} \left(\mathbf{I}_K - \frac{1}{K} \mathbf{1}_K \mathbf{1}_K^T\right) \tag{4}$$

where $\mathbf{I}_K \in \mathbb{R}^{K \times K}$ is an identity matrix and $\mathbf{1}_K \in \mathcal{R}^K$ is a vector of all ones. It can be verified that the angle between any pair of class means after subtracting the global mean is the same:

$$\arccos\left(\frac{\langle \boldsymbol{\mu}_k^* - \boldsymbol{\mu}_G^*, \ \boldsymbol{\mu}_{k'}^* - \boldsymbol{\mu}_G^* \rangle}{\|\boldsymbol{\mu}_k^* - \boldsymbol{\mu}_G^*\|_2 \cdot \|\boldsymbol{\mu}_{k'}^* - \boldsymbol{\mu}_G^*\|_2}\right) = \boldsymbol{\theta}_K \doteq \arccos\left(-\frac{1}{K-1}\right), \forall k, k' \in [K], k \neq k'. \tag{5}$$

Aside from the learned features, $\mathcal{NC}$ also states the following two properties hold for the classifier.

(iii) $\mathcal{NC}$**3: Self-duality between Feature and Classifier.** The classifier weight $\boldsymbol{W}^* = [\boldsymbol{w}_1^*, \ldots, \boldsymbol{w}_K^*]$ satisfies $\boldsymbol{w}_k^* = C \cdot (\boldsymbol{\mu}_k^* - \boldsymbol{\mu}_G^*)$, where C is a scalar independent of k.

(iv) $\mathcal{NC}$**4: Nearest Class Mean Classifier.** The class label for a test data $\boldsymbol{x}$ is determined by a nearest class mean classifier: $\arg\min_{k \in [K]} \|f(\boldsymbol{x}, \boldsymbol{\theta}^*) - \boldsymbol{\mu}_k^*\|_2$.

Theoretical studies of the $\mathcal{NC}$ phenomenon are often conducted with the unconstrained feature models (UFMs). The idea of UFMs is that, since performing an analysis of a multi-layer nonlinear neural network $f(.)$ is difficult, we treat $f(.)$ as a model that can produce any set of features given any set of inputs. Hence, the features $\{\boldsymbol{u}_i\}_{i=1}^K$ can be treated as free optimization variables, which allows us to peel off the network $f(.)$ and consider the following optimization problem[2]

$$\min_{\{\boldsymbol{u}_i\}_{i=1}^N, \boldsymbol{W}, \boldsymbol{b}} \frac{1}{N} \sum_{i=1}^N \mathcal{L}\big([v_{i1}, \ldots, v_{iK}], y_i\big), \ \text{ s.t. } v_{ik} = \langle \boldsymbol{u}_i, \boldsymbol{w}_k \rangle + b_k. \tag{6}$$

Under certain assumptions, it can be shown that all global solutions to (6) satisfy $\mathcal{NC}$ and that such an optimization problem has a benign global landscape (Zhu et al., 2021).

3 METHOD

In this section, we start by presenting an arrangement of features described by their geometric properties in Section 3.1, where within-class features are diverse within a cone. Then, Section 3.2 introduces our method for obtaining such an arrangement by the design of classifier and loss function.

3.1 A MAXIMAL-SEPARATING-CONE (MSC) ARRANGEMENT

As explained in Section 2.2, a standard deep learning based classification produces features with an arrangement described by $\mathcal{NC}$, where within-class variability converges to zero (i.e., $\mathcal{NC}$1) and between-class separation is maximized (i.e., $\mathcal{NC}$2) (see Figure 2(a)). Here we introduce an arrangement of features where within-class features are allowed to be diverse. As briefly explained in the introduction, within-class diversity is a desirable property for fine-grained classification.

Definition 1 (Maximal-Separating-Cone Arrangement)**.** *The set of features $\{\boldsymbol{u}_i\}_{i=1}^N \subseteq \mathbb{R}^m$ is said to have a maximal-separating-cone (MSC) arrangement with respect to (w.r.t.) the set of labels $\{y_i\}_{i=1}^N \subseteq [K]$ with angle $\tau > 0$ if there exist a collection of vectors $\{\boldsymbol{\beta}_k\}_{k=1}^K \subseteq \mathbb{R}^m$ with $\{\boldsymbol{\beta}_k\}_{k=1}^K$ forming a Simplex ETF, such that for all i, k that satisfies $y_i = k$, it has*

$$\frac{\langle \boldsymbol{u}_i, \ \boldsymbol{\beta}_k \rangle}{\|\boldsymbol{u}_i\|_2 \cdot \|\boldsymbol{\beta}_k\|_2} \geq \cos \tau. \tag{7}$$

The MSC arrangement has a simple geometric description (see Figure 2(b)). In words, it requires that features associated with each class lies in a cone. Moreover, the cones have the properties that 1) their axes form a Simplex ETF, hence different classes are sufficiently separated, and that 2) their angular radius is $\tau > 0$, hence within-class features do not collapse to a single point as in $\mathcal{NC}$.

---

[1]We assume that the feature space dimension m is greater or equal to the number of classes K.

[2]A regularization term is often added to the optimization variables. We omit it to simplify the discussion.

3.2 Inducing MSC Features via Classifier and Loss Design

We obtain MSC features by training a deep neural network with the following optimization problem:

$$\min_{\boldsymbol{\theta}} \frac{1}{N} \sum_{i=1}^{N} \mathcal{L}\Big([v_{i1}, \ldots, v_{iK}], y_i\Big), \ \text{s.t.} \ \boldsymbol{u}_i = f(\boldsymbol{x}_i, \boldsymbol{\theta}), \ v_{ik} = h(\boldsymbol{u}_i, y_i, \boldsymbol{w}_k, b_k),$$
$$\boldsymbol{W} \doteq [\boldsymbol{w}_1, \ldots, \boldsymbol{w}_K] = \boldsymbol{W}_{\text{ETF}}, \ \text{and} \ \boldsymbol{b} \doteq [b_1, \ldots, b_K] = \boldsymbol{0}, \tag{8}$$

where $h(\cdot)$ is defined in (9) and $\boldsymbol{W}_{\text{ETF}}$ is a Simplex ETF matrix defined in (4). The problem in (8) differs from (1) in two aspects, which we explain below.

Fixed Classifier. Instead of learning the classifier weights $\boldsymbol{W}$ and $\boldsymbol{b}$ from training data, we fix them as constant model parameters in (8). In particular, $\boldsymbol{W}$ is fixed as a Simplex ETF matrix $\boldsymbol{W}_{\text{ETF}}$.[3] The idea is that we would like the columns of $\boldsymbol{W}$ to be the axes of the cones in MSC arrangement, which are required to form a Simplex ETF according to Definition 1. For the parameter $\boldsymbol{b}$, we simply fix it to be a zero vector, which makes the design of method for obtaining MSC features easier.

Hinge Loss. The second difference in (8) is that the logits are set as $v_{ik} = h(\boldsymbol{u}_i, y_i, \boldsymbol{w}_k, b_k)$ with $h(.)$ being a hinge function defined below:

$$h(\boldsymbol{u}_i, y_i, \boldsymbol{w}_k, b_k) = \begin{cases} h^+(\boldsymbol{u}_i, y_i, \boldsymbol{w}_k, b_k) \doteq \min\{\langle \boldsymbol{w}_k, \boldsymbol{u}_i \rangle, \text{stop-grad}(\|\boldsymbol{u}_i\|_2) \cos \tau^+\}, & \text{if } k = y_i, \\ h^-(\boldsymbol{u}_i, y_i, \boldsymbol{w}_k, b_k) \doteq \max\{\langle \boldsymbol{w}_k, \boldsymbol{u}_i \rangle, \text{stop-grad}(\|\boldsymbol{u}_i\|_2) \cos \tau^-\}, & \text{if } k \neq y_i, \end{cases} \tag{9}$$

where τ^+ and τ^- are two hyper-parameters. If $\tau^+ = 0$ and $\tau^- = \pi$, we obtain $h(\boldsymbol{u}_i, y_i, \boldsymbol{w}_k, b_k) = \langle \boldsymbol{w}_k, \boldsymbol{u}_i \rangle + b_i$ which is the logit function used in (8). The idea of designing (9) is explained below.

- For the logit v_{ik} corresponding to the positive class, i.e., when $k = y_i$, we define $v_{ik} = \langle \boldsymbol{w}_k, \boldsymbol{u}_i \rangle$, which is the typically used logit in (8), when the angle between $\boldsymbol{w}_k$ and $\boldsymbol{u}_i$ is greater than τ^+[4]. Otherwise, we define the logit to be $v_{ik} = \text{stop-grad}(\|\boldsymbol{u}_i\|_2) \cos \tau^+$, with stop-grad() denotes an operation to stop the backpropagation of gradient; thereby making the logit independent of network parameters $\boldsymbol{\theta}$.
- For logits v_{ik} corresponding to the negative classes, i.e., when $k \neq y_i$, we define $v_{ik} = \langle \boldsymbol{w}_k, \boldsymbol{u}_i \rangle$, which is the typically used logit in (8), if the angle between $\boldsymbol{w}_k$ and $\boldsymbol{u}_i$ is smaller than τ^-. Otherwise, we define $v_{ik} = \text{stop-grad}(\|\boldsymbol{u}_i\|_2) \cos \tau^-$, so that the logits becomes independent of network parameters $\boldsymbol{\theta}$.

By setting $\tau^+ = \tau$, the logit v_{ik} for the positive class is independent of network parameters $\boldsymbol{\theta}$ when $\boldsymbol{u}_i$ lies in its corresponding cone in an MSC. Similarly, using the fact that the pairwise angular distance of vectors in a Simplex ETF with K vectors is the same and is given by $\boldsymbol{\theta}_K$ (see (5)), by setting $\tau^- = \theta_K - \tau$, the logits v_{ik} for the negative classes are independent of $\boldsymbol{\theta}$ when $\boldsymbol{u}_i$ lies in its corresponding cone in an MSC. Combining the cases above, we readily obtain the following result.

Theorem 1. *Consider (8) with $\tau^+ = \boldsymbol{\theta}_K - \tau^- = \tau$. If the set of features $\{\boldsymbol{u}_i\}_{i=1}^N$ satisfy the MSC arrangement w.r.t. $\{y_i\}_{i=1}^N$ with angle τ, then the gradient of the objective w.r.t. $\boldsymbol{\theta}$ is zero.*

From Theorem 1, if the features already have an MSC arrangement, then the network $f()$ will no longer be updated and hence the features will not collapse to their corresponding class centers.

4 Experiments

In this section, we demonstrate the empirical performance of our approach. In particular, we focus on two applications: (i) *Fine-grained classification*, where the goal is to illustrate the benefit of diverse features learned during pre-training for fine-grained downstream classification, and (ii) *Long-tail classification*, where we apply our approach to improve the performance on tail classes.

For our approach, we train feature extractors $f()$ by solving the optimization problem in (8) with $\mathcal{L}$ being the CE loss in (2) and $f()$ being different variants of ResNet (He et al., 2016) depending

---

[3]This design choice was previously made in Zhu et al. (2021), with the idea that since $\mathcal{NC}$ occurs at convergence, simply fixing $\boldsymbol{W}$ to be a a Simplex ETF should not hurt performance while may accelerate training.
[4]Here we use the fact that $\|\boldsymbol{w}_k\|_2 = 1$ by the constraint in (8).

Table 1: Performance comparison of transfer learning using linear evaluation on nine downstream image classification datasets. We report the Top-1 accuracy (%) where the **first** and the second high results are highlighted. Our approach, HingeCE, improves the transfer learning accuracy consistently and reaches the highest mean accuracy on several datasets. Symbols † & * here indicate the results reported in Chen et al. (2020) and Kornblith et al. (2021) respectively.

Approach	Food	Cifar10	Cifar100	Birdsnap	SUN	Car	Aircraft	Pet	Flower	Mean
SimCLR†	68.4	90.6	71.6	37.4	58.8	50.3	50.3	83.6	91.2	66.9
CE*	74.6	**92.4**	**76.9**	55.4	62.0	60.3	60.7	92.0	94.0	74.3
Smooth*	72.7	91.6	75.2	53.6	61.6	54.8	58.9	**92.9**	91.9	72.6
CE+ETF	73.4	91.0	73.0	55.1	65.3	60.1	59.9	92.0	95.8	74.0
Smooth+ETF	70.5	90.6	71.4	54.6	64.7	58.8	59.0	90.2	94.3	72.7
HingeCE (Ours)	**74.9**	92.3	76.6	**55.8**	**68.2**	**62.2**	**61.2**	92.2	**97.8**	**75.7**

on the dataset and application. We refer to our method as *HingeCE*. Since the last two layers of (all variants of) ResNets is a ReLU activation followed by a pooling, the extracted features are constrained to have non-negative entries, hence cannot satisfy an MSC arrangement. Therefore, we add a fully connected layer with the same input and output dimensions[5] on top of ResNets as the feature extractor $f()$, such that the output feature is theoretically defined over $\mathbb{R}^m$. The choice of hyper-parameters τ^+ and τ^-, as well as additional analysis, are discussed in Section 5.

4.1 FINE-GRAINED CLASSIFICATION

Experimental Setup. For this setup, we follow Kornblith et al. (2021) and first pre-train a ResNet-50 model (He et al., 2016) on ImageNet ILSVRC 2012 dataset (Russakovsky et al., 2015). The outputs of ResNet-50 are then used as features for the downstream tasks. More specifically, after pre-training, we fix the pre-trained feature extractor and only learn a linear classifier for each of the nine different downstream natural image classification tasks through L_2-regularized multinomial logistic regression. The downstream datasets are Food (Bossard et al., 2014), CIFAR10 & CIFAR100 (Krizhevsky et al., 2009), Birdsnap (Berg et al., 2014), Sun (Xiao et al., 2010), Car (Krause et al., 2013), Aircraft (Maji et al., 2013), Pet (Parkhi et al., 2012) and Flower (Nilsback & Zisserman, 2008). Most of these datasets concern recognition on fine-grained classes (see Appendix A for more details). The primary goal of this experiment is to demonstrate that *diverse features* in pre-training enables better downstream fine-grained classification.

Results. The results for fine-grained classification are summarized in Table 1. We consider several baselines to evaluate our performance gain. We use CE to denote the baseline which jointly learns the classifier and the feature extractor from scratch by minimizing CE loss $\mathcal{L}_{CE}$ during pre-training. Another natural baseline is CE+ETF, where the learnable classifier in CE is replaced with a fixed Simplex ETF. To have a fair comparison with our HingeCE which also uses fixed Simplex ETF as the classifier but uses an additional linear layer, we also add such a layer for CE+ETF. Hence, HingeCE and CE+ETF are the same in terms of architecture of feature extractor and using fixed Simplex ETF classifier, with the only difference being the choice of loss function for network training.

Additionally, following Kornblith et al. (2021), we use label-smoothed variants of the baselines above as additional baselines (e.g. Smooth+ETF). In particular, we modify the target distribution t as follows $t' = t(1-\alpha) + \alpha/K$ where α determines the weighting of the original and uniform targets and K is the number of classes in Eq. 8. We set α as 0.1 and mean linear evaluation accuracy drops from 94.3% to 92.6% (Row$_{(2,3)}$ of Table 1) when a classifier is jointly learned and from 94.0% to 92.7% (Row$_{(4,5)}$ of Table 1) when a Simplex ETF is used. We first note that CE+ETF achieves similar or competitive accuracy in linear evaluation as well as the accuracy on ImageNet (pre-training) test set when compared to CE (Row$_{(1,2)}$ of Table 3), indicating that using Simplex ETF as classifier does not impact the transferability of deep learning features. Finally, with our approach HingeCE, we mitigate the degree of collapse by maintaining diversity within each class, and observe substantial performance boost over the baselines on both transfer learning (Row$_{(5,6)}$ of Table 1) and test accuracy on ImageNet (Row$_{(2,3)}$ of Table 3). Also, in contrast to self-supervision approaches (e.g.

---

[5]For CIFAR100-LT classification using ResNet-32, the number of class $K = 100$ is greater than the feature dimension $m = 64$ which violates the constraint of $m \geq K$ for constructing a Simplex ETF in (4). In this particular case we set the output dimension to be 128.

Table 2: Performance comparison on long-tail datasets. We report Top-1 accuracy (%) and the **best** accuracy is highlighted. Our implementation is based upon Menon et al. (2020). Symbol *: the accuracy on is 38.4% when the feature dimension $m = 64$ and is 39.5% when $m = 128$. To ensure Simplex ETF constraint holds, for CIFAR100-LT, we increase the feature dimension to 128.

Approach	CIFAR10-LT	CIFAR100-LT	ImageNet-LT
Focal (Lin et al., 2017)	70.4	38.4	-
LADM (Cao et al., 2019)	73.4	39.6	-
M2M (Kim et al., 2020)	79.1	43.5	-
OLTR (Liu et al., 2019)	-	-	32.2
cRT (Kang et al., 2019)	-	-	47.3
FCL (Kang et al., 2020)	-	-	49.8
KCL (Kang et al., 2020)	77.6	42.8	51.5
TSC (Li et al., 2022)	79.7	43.8	**52.4**
Logit Adjusted (Menon et al., 2020)	77.7	43.9	51.1
CE (Menon et al., 2020)	72.8	38.4*	46.9
CE+ETF	77.3	42.6	48.1
HingeCE (Ours)	**80.4** ($\uparrow$ 2.9)	**46.2** ($\uparrow$ 3.6)	50.8 ($\uparrow$ 2.7)

SimCLR) which aim to learn diverse features, our method can provide both discriminative power and feature diversity, thereby, yielding better transfer learning performance.

4.2 LONG-TAIL CLASSIFICATION

Experimental Setup. For long-tail classification, we conduct experiments on three popular long-tail benchmarks: CIFAR10-LT, CIFAR100-LT (Krizhevsky et al., 2009), and ImageNet-LT (Russakovsky et al., 2015). CIFAR10-LT and CIFAR100-LT are derived from CIFAR10 and CIFAR100 with the number of samples per class ranges from 5000 to 50 and 500 to 5, respectively. ImageNet-LT is derived from ImageNet and contains 1000 classes. The number of samples per class ranges from 1280 to 5. Based on the number of training samples per class, we group the classes into two categories: *major class* which have more than 50 samples, and *minor classes* with less than 50 samples. In our method, we tune a τ^+ for the minor classes and simply use $\tau^+ = 0$ (which is equivalent to using $\langle \boldsymbol{w}_k, \boldsymbol{u}_i \rangle$ as logits) for the major classes.

Results. In addition to standard baselines, we also compare our approach with state-of-the-art long-tail classification methods. The results are summarized in Table 2. Using Simplex ETF as classifier, CE+ETF already yields improved performance when compared to CE (Row$_{(10,11)}$ of Table 2) as class centers are predefined and maximally separated while the centers of minor classes may not be well-learned (Fang et al., 2021). For CIFAR100-LT, even though the test accuracy improved from 38.4% to 39.5% by increasing feature dimension from 64 to 128, a larger gain in test accuracy (from 39.5% to 42.6%) was obtained through the use of Simplex ETF. Note that the performance gain using CE+ETF on ImageNet-LT is relatively minor compared to CIFAR-related datasets. On the other hand, by preserving the diversity of each class, our HingeCE considerably improves the performance on all three datasets yielding state-of-the-art performance on a few datasets and is competitive on the rest. Note that TSC (Li et al., 2022) and KCL (Kang et al., 2020) use two-stage training involving supervised contrastive learning (SCL) to improve the performance on long-tail classification, which is complementary to our approach. Nonetheless, even without SCL, we obtain better or competitive results. We believe our results can be further improved using SCL and additional hyperparameter tuning.

5 DISCUSSION

Choice of Hyper-parameters. τ^+ and τ^- are two hyper-parameters of our method introduced in Equation 9. Here we plot the cosine similarities between each feature on ImageNet train set with its positive class center and rest of the negative class centers during the training process, and present the results in Figure 3(a) and (b), respectively. It can be observed that the mean cosine similarity with positive class centers is around 0.46, which is perhaps larger than expected (since if all features collapse completely to class mean, then this value should be one). Moreover, the similarity with

(a) Cosine similarity with positive class centers.

(b) Cosine similarity with negative class centers.

(c) Transfer learning accuracy.

Figure 3: (a, b) Cosine similarity of each feature with its corresponding positive (in (a)) and negative (in (b)) class centers averaged over all features obtained with CE+ETF. (c) Transfer learning accuracy on Flower dataset as a function of $\tau^+ \in [0, \frac{17}{36}\pi]$ with $\tau^- = \pi$ during ImageNet pretraining with HingeCE.

negative class centers remains close to zero during the entire training process. Hence, the negative logits have small impact on the value of the CE loss and for simplicity we set $\tau^- = \pi$ (i.e., use $\langle \boldsymbol{w}_k, \boldsymbol{u}_i \rangle$ as logits). In the following we examine the effect of τ^+.

Figure 3(c) demonstrates the effect of τ^+ for fine-grained classification on Flower dataset. It can be seen that with a small value of τ^+, HingeCE does not have a significant effect. This is aligned with the observation in Figure 3(a). When τ^+ is increased to the range of $\frac{11}{36}\pi \leq \tau^+ \leq \frac{5}{12}\pi$, the accuracy increases considerably and is not sensitive to the choice of τ^+ within that range.

For all results in Table 1 & 3, the value of τ^+ is fixed to $\frac{13}{36}\pi$. Since this choice works fairly well across various settings, hyper-parameter tuning for our method is very easy. Finally, while this fixed choice works well, we find empirically without reporting the details here that additional hyper-parameter tuning can further improve the final performance.

Approach	Accuracy (%)
CE	76.5
CE+ETF	76.3
HingeCE	77.4

Figure 4: The (a) numerical rank and (b) NC1 metric among features on the ImageNet training set with different thresholds τ^+ for h^+.

Table 3: Top-1 test accuracy on ImageNet.

Measuring Diversity. To measure the diversity of features, we use $\mathcal{NC}1$, defined through between-class and within-class covariance matrices, and numerical rank, defined as the ratio of squared nuclear norm and squared Frobenius norm for features of each class averaged over all classes. The definition of these two measures can be found in e.g., Zhou et al. (2022). In Figure 4, we plot $\mathcal{NC}_1$ and numerical rank as a function of τ^+. It can be seen that both measures increases with τ^+, showing that our method indeed improves feature diversity.

Pre-training Performance. While designed for improving the performance of downstream fine-grained classification task, we show in Table 3 that our method improves the performance on the test set of ImageNet as well.

Per-class Analysis for Long-tail Classification. We evaluate the performance gain of our method on major vs minor classes in long-tail classification, and report the results in Figure 5. Specifically, Figure 5(a) & (b) shows that the benefit of our method is mainly on the minor classes. Figure 5(c) demonstrates the effect of τ^+ on major and minor classes separately. It can be seen that setting τ^+ to be in the range of $\frac{7}{36}\pi \leq \tau^+ \leq \frac{1}{4}\pi$ provides a notable gain for minor classes. In addition, setting τ^+ to be in the range of $\frac{1}{12}\pi \leq \tau^+ \leq \frac{11}{90}\pi$ (which is a range with lower values than that of the minor classes) provides a gain for major classes. This may imply that the optimal threshold τ^+ should be dependant upon the number of training samples in each class. Hence, while the results in Table 2 are obtained from using the same τ^+ in all minor classes and another τ^+ for all major classes, which is a choice made to simplify the study, the performance may be improved with a more careful choice of τ^+ for individual classes.

<table>
<tr><td>(a) Test Accuracy.</td><td>(b) Relative gain.</td><td>(c) Transfer learning accuracy.</td></tr>
</table>

Figure 5: On CIFAR100-LT, for each class, we calculate (a) test accuracy and (b) relative performance gain (the class with a larger index on x-axis has less training data) and the performance on minor class are mostly improved. Then, we apply our approach on the major and minor classes separately and adjust the threshold τ^+. In (c), we observe that the best testing accuracy is reached when our approach is applied on minor classes and the threshold is around $\frac{1}{6}\pi \leq \tau^+ \leq \frac{5}{18}\pi$.

6 RELATED WORK

Transfer Learning is a pipeline where a feature extractor trained on ImageNet (Russakovsky et al., 2015) is directly used to extract features for downstream tasks (Kornblith et al., 2019). While literature on transfer learning abounds, most related to ours include Kornblith et al. (2021) which show a trade-off between pretraining and downstream performance. In particular, while many techniques such as label smoothing produces better class separation and within class feature collapsing (Müller et al., 2019) hence improves the performance on ImageNet pre-training task, the features become less transferable and produce worse downstream performance. Our result shows that by introducing diversity via our HingeCE method, performance on both pretraining and fine-grained classification tasks can be improved.

Neural Collapse is a phenomenon reported in Papyan et al. (2020) for deep models fully trained on a balanced dataset in classification tasks. It simplifies the deep model by considering the last-layer features and the classifier as independent variables, and subsequent works theoretically demonstrated phenomenon of $\mathcal{NC}$ under Cross-Entropy (Wojtowytsch & Weinan, 2020; Lu & Steinerberger, 2020; Graf et al., 2021; Fang et al., 2021) or Mean Squared Error (Mixon et al., 2022; Rangamani & Banburski-Fahey, 2022; Poggio & Liao, 2020) losses. Since the classifier weight forms a Simplex ETF in $\mathcal{NC}$, Zhu et al. (2021) shows that fixing the classifier as a Simplex ETF during training can achieve similar performance. While the minimized diversity may hurt the adaptation performance to new classes (Kornblith et al., 2019), the Simplex ETF has been shown to be useful for continual learning (Wu et al., 2021) and long-tail learning (Li et al., 2022; Yang et al., 2022).

Long-tail Learning with imbalance of data distribution is a common real-world scenario. Deep learning models tend to perform well on major classes (Zhang et al., 2021) with a lower accuracy on minor classes. To address the issue, an intuitive strategy is to explicitly re-sample the training data (Ando & Huang, 2017) which usually hurts performance on major classes (Kang et al., 2019). Alternative methods include re-weighting the loss for different classes Byrd & Lipton (2019); Cui et al. (2019) or re-adjusting the logits (Menon et al., 2020; Cao et al., 2019) during training. Meanwhile, several regularization techniques such as weight-normalization (Kang et al., 2019) and loss modification (Iranmehr et al., 2019) can be applied, but they can be sensitive to the selection of optimizer and may not reach a balanced error (Menon et al., 2020).

7 CONCLUSION

In this paper, we examine the Neural Collapse phenomenon of deep learning feature extractors and argue that the lack of within-class diversity implies an undesirable property for fine-grained classification task. To address that, we introduce a geometric arrangement of features with within-class diversity, and present a method called HingeCE based on the classifier and loss function design. Empirically we show that HingeCE is substantially better than or competitive to the state-of-the-art methods for fine-grained classification and long-tail classification tasks.

REFERENCES

Shin Ando and Chun Yuan Huang. Deep over-sampling framework for classifying imbalanced data. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pp. 770–785. Springer, 2017.

Thomas Berg, Jiongxin Liu, Seung Woo Lee, Michelle L Alexander, David W Jacobs, and Peter N Belhumeur. Birdsnap: Large-scale fine-grained visual categorization of birds. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2011–2018, 2014.

Lukas Bossard, Matthieu Guillaumin, and Luc Van Gool. Food-101–mining discriminative components with random forests. In *European conference on computer vision*, pp. 446–461. Springer, 2014.

Jonathon Byrd and Zachary Lipton. What is the effect of importance weighting in deep learning? In *International Conference on Machine Learning*, pp. 872–881. PMLR, 2019.

Kaidi Cao, Colin Wei, Adrien Gaidon, Nikos Arechiga, and Tengyu Ma. Learning imbalanced datasets with label-distribution-aware margin loss. *Advances in neural information processing systems*, 32, 2019.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pp. 1597–1607. PMLR, 2020.

Yin Cui, Menglin Jia, Tsung-Yi Lin, Yang Song, and Serge Belongie. Class-balanced loss based on effective number of samples. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 9268–9277, 2019.

Cong Fang, Hangfeng He, Qi Long, and Weijie J Su. Exploring deep neural networks via layer-peeled model: Minority collapse in imbalanced training. *Proceedings of the National Academy of Sciences*, 118(43):e2103091118, 2021.

Florian Graf, Christoph Hofer, Marc Niethammer, and Roland Kwitt. Dissecting supervised constrastive learning. In *International Conference on Machine Learning*, pp. 3821–3830. PMLR, 2021.

XY Han, Vardan Papyan, and David L Donoho. Neural collapse under mse loss: Proximity to and dynamics on the central path. *arXiv preprint arXiv:2106.02073*, 2021.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Arya Iranmehr, Hamed Masnadi-Shirazi, and Nuno Vasconcelos. Cost-sensitive support vector machines. *Neurocomputing*, 343:50–64, 2019.

Wenlong Ji, Yiping Lu, Yiliang Zhang, Zhun Deng, and Weijie J Su. An unconstrained layer-peeled perspective on neural collapse. *arXiv preprint arXiv:2110.02796*, 2021.

Bingyi Kang, Saining Xie, Marcus Rohrbach, Zhicheng Yan, Albert Gordo, Jiashi Feng, and Yannis Kalantidis. Decoupling representation and classifier for long-tailed recognition. *arXiv preprint arXiv:1910.09217*, 2019.

Bingyi Kang, Yu Li, Sa Xie, Zehuan Yuan, and Jiashi Feng. Exploring balanced feature spaces for representation learning. In *International Conference on Learning Representations*, 2020.

Jaehyung Kim, Jongheon Jeong, and Jinwoo Shin. M2m: Imbalanced classification via major-to-minor translation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 13896–13905, 2020.

Simon Kornblith, Jonathon Shlens, and Quoc V Le. Do better imagenet models transfer better? In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 2661–2671, 2019.

Simon Kornblith, Ting Chen, Honglak Lee, and Mohammad Norouzi. Why do better loss functions lead to less transferable features? *Advances in Neural Information Processing Systems*, 34: 28648–28662, 2021.

Jonathan Krause, Jia Deng, Michael Stark, and Li Fei-Fei. Collecting a large-scale dataset of fine-grained cars. 2013.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Communications of the ACM*, 60(6):84–90, 2017.

Alex Krizhevsky et al. Learning multiple layers of features from tiny images. 2009.

Tianhong Li, Peng Cao, Yuan Yuan, Lijie Fan, Yuzhe Yang, Rogerio S Feris, Piotr Indyk, and Dina Katabi. Targeted supervised contrastive learning for long-tailed recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6918–6928, 2022.

Tsung-Yi Lin, Priya Goyal, Ross Girshick, Kaiming He, and Piotr Dollár. Focal loss for dense object detection. In *Proceedings of the IEEE international conference on computer vision*, pp. 2980–2988, 2017.

Ziwei Liu, Zhongqi Miao, Xiaohang Zhan, Jiayun Wang, Boqing Gong, and Stella X Yu. Large-scale long-tailed recognition in an open world. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 2537–2546, 2019.

David G Lowe. Distinctive image features from scale-invariant keypoints. *International journal of computer vision*, 60(2):91–110, 2004.

Jianfeng Lu and Stefan Steinerberger. Neural collapse with cross-entropy loss. *arXiv preprint arXiv:2012.08465*, 2020.

Subhransu Maji, Esa Rahtu, Juho Kannala, Matthew Blaschko, and Andrea Vedaldi. Fine-grained visual classification of aircraft. *arXiv preprint arXiv:1306.5151*, 2013.

Aditya Krishna Menon, Sadeep Jayasumana, Ankit Singh Rawat, Himanshu Jain, Andreas Veit, and Sanjiv Kumar. Long-tail learning via logit adjustment. In *International Conference on Learning Representations*, 2020.

Dustin G Mixon, Hans Parshall, and Jianzong Pi. Neural collapse with unconstrained features. *arXiv preprint arXiv:2011.11619*, 2020.

Dustin G Mixon, Hans Parshall, and Jianzong Pi. Neural collapse with unconstrained features. *Sampling Theory, Signal Processing, and Data Analysis*, 20(2):1–13, 2022.

Rafael Müller, Simon Kornblith, and Geoffrey E Hinton. When does label smoothing help? *Advances in neural information processing systems*, 32, 2019.

Maria-Elena Nilsback and Andrew Zisserman. Automated flower classification over a large number of classes. In *2008 Sixth Indian Conference on Computer Vision, Graphics & Image Processing*, pp. 722–729. IEEE, 2008.

Vardan Papyan, XY Han, and David L Donoho. Prevalence of neural collapse during the terminal phase of deep learning training. *Proceedings of the National Academy of Sciences*, 117(40): 24652–24663, 2020.

Omkar M Parkhi, Andrea Vedaldi, Andrew Zisserman, and CV Jawahar. Cats and dogs. In *2012 IEEE conference on computer vision and pattern recognition*, pp. 3498–3505. IEEE, 2012.

Tomaso Poggio and Qianli Liao. Explicit regularization and implicit bias in deep network classifiers trained with the square loss. *arXiv preprint arXiv:2101.00072*, 2020.

Akshay Rangamani and Andrzej Banburski-Fahey. Neural collapse in deep homogeneous classifiers and the role of weight decay. In *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 4243–4247. IEEE, 2022.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *International journal of computer vision*, 115(3):211–252, 2015.

Tom Tirer and Joan Bruna. Extended unconstrained features model for exploring deep neural collapse. *arXiv preprint arXiv:2202.08087*, 2022.

E Weinan and Stephan Wojtowytsch. On the emergence of tetrahedral symmetry in the final and penultimate layers of neural network classifiers. *arXiv preprint arXiv:2012.05420*, 2020.

Stephan Wojtowytsch and E Weinan. On the emergence of tetrahedral symmetry in the final and penultimate layers of neural network classifiers. *arXiv preprint arXiv:2012.05420*, 2020.

Ziyang Wu, Christina Baek, Chong You, and Yi Ma. Incremental learning via rate reduction. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 1125–1133, 2021.

Jianxiong Xiao, James Hays, Krista A Ehinger, Aude Oliva, and Antonio Torralba. Sun database: Large-scale scene recognition from abbey to zoo. In *2010 IEEE computer society conference on computer vision and pattern recognition*, pp. 3485–3492. IEEE, 2010.

Yibo Yang, Liang Xie, Shixiang Chen, Xiangtai Li, Zhouchen Lin, and Dacheng Tao. Do we really need a learnable classifier at the end of deep neural network? *arXiv preprint arXiv:2203.09081*, 2022.

Jason Yosinski, Jeff Clune, Yoshua Bengio, and Hod Lipson. How transferable are features in deep neural networks? *Advances in neural information processing systems*, 27, 2014.

Yifan Zhang, Bingyi Kang, Bryan Hooi, Shuicheng Yan, and Jiashi Feng. Deep long-tailed learning: A survey. *arXiv preprint arXiv:2110.04596*, 2021.

Jinxin Zhou, Xiao Li, Tianyu Ding, Chong You, Qing Qu, and Zhihui Zhu. On the optimization landscape of neural collapse under mse loss: Global optimality with unconstrained features. *arXiv preprint arXiv:2203.01238*, 2022.

Zhihui Zhu, Tianyu Ding, Jinxin Zhou, Xiao Li, Chong You, Jeremias Sulam, and Qing Qu. A geometric analysis of neural collapse with unconstrained features. *Advances in Neural Information Processing Systems*, 34:29820–29834, 2021.

A   FINGRAINED TRANSFER DATASET

The downstream datasets are Food (Food-101) (Bossard et al., 2014) with 101 finegrained classes of food, CIFAR10 & CIFAR100 (Krizhevsky et al., 2009), Birdsnap (Berg et al., 2014) with 500 finegrained classes regarding bird species, Sun (SUN-397) (Xiao et al., 2010) with 397 scene categories, Car (Stanford Cars) (Krause et al., 2013) with 196 finegrained class of car models, Aircraft (Maji et al., 2013) with 120 finegrained classes of aircraft models, Pet (Oxford IIIT Pets) (Parkhi et al., 2012) with 37 finegrained classes of dog & cat, and Flower (Oxford IIIT Flowers) (Nilsback & Zisserman, 2008) with 102 finegrained classes regarding flower species. Food(Bossard et al., 2014) contains 101 finegrained classes For all datasets, we follow Kornblith et al. (2021) and use the official train-test split for linear evaluation training. Then, we report the top-1 accuracy for Food, CIFAR10, CIFAR100, Birdsnap, SUN and Cars; and mean per-class accuracy for Aircraft, Pets, Flowers.

Figure 6: Visualization comparison ImageNet (pre-train) and Flower (Transfer learning). Comparing with baseline CE, by applying HingeCE, as the features are more diverse on pre-train dataset ((b) vs. (a)), the features for finegrained classes more separable ((d) vs. (c)), which then facilitate the finegrained recognition in transfer learning.

Visualization on fingrained classes.   As shown in Figure 6, we provide a visualization on three coarse classes for ImageNet and three Flower separately. All of the classes are randomly selected. Comparing Figure 6(a,b), applying our approach HingeCE can preserve more diversity within each coarse class. Then, from Figure 6(c,d), the features of finegrained classes can be more separable.