PRIVACY IMPLICATIONS OF SHUFFLING

ABSTRACT

LDP deployments are vulnerable to inference attacks as an adversary can link the noisy responses to their identity and subsequently, auxiliary information using the *order* of the data. An alternative model, shuffle DP, prevents this by shuffling the noisy responses uniformly at random. However, this limits the data learnability – only symmetric functions (input order agnostic) can be learned. In this paper, we strike a balance and show that systematic shuffling of the noisy responses can thwart specific inference attacks while retaining some meaningful data learnability. To this end, we propose a novel privacy guarantee, d_σ-privacy, that captures the privacy of the order of a data sequence. d_σ-privacy allows tuning the granularity at which the ordinal information is maintained, which formalizes the degree the resistance to inference attacks trading it off with data learnability. Additionally, we propose a novel shuffling mechanism that can achieve d_σ-privacy and demonstrate the practicality of our mechanism via evaluation on real-world datasets.

1 INTRODUCTION

Differential Privacy (DP) and its local variant (LDP) are the most commonly accepted notions of data privacy. LDP has the significant advantage of not requiring a trusted centralized aggregator, and has become a popular model for commercial deployments, such as those of Microsoft (Ding et al., 2017), Apple (Greenberg, 2016), and Google (Erlingsson et al., 2014; Fanti et al., 2015; Bittau et al., 2017b). Its formal guarantee asserts that an adversary cannot infer the value of an individual's private input by observing the noisy output. However in practice, a vast amount of *public auxiliary information*, such as address, social media connections, court records, property records, income and birth dates (La Corte, 2019), is available for every individual. An adversary, with access to such auxiliary information, *can* learn about an individual's private data from several *other* participants' noisy responses. We illustrate this as follows.

> **Problem.** An analyst runs a medical survey in Alice's community to investigate how the prevalence of a highly contagious disease changes from neighborhood to neighborhood. Community members report a binary value indicating whether they have the disease.

Next, consider the following two data reporting strategies.

> **Strategy 1.** Each data owner passes their data through an appropriate randomizer (that flips the input bit with some probability) in their local devices and reports the noisy output to the untrusted data analyst.

> **Strategy 2.** The noisy responses from the local devices of each of the data owners are collected by an intermediary trusted shuffler which dissociates the device IDs (metadata) from the responses and uniformly randomly shuffles them before sending them to the analyst.

Strategy 1 corresponds to the standard LDP deployment model (for example, Apple and Microsoft's deployments). Here *the order of the noisy responses is informative of the identity of the data owners* – the noisy response at index 1 corresponds to the first data owner and so on. Thus, the noisy responses can be directly linked with its associated device/account ID and subsequently, auxiliary information. This puts Alice's data under the threat of inference attacks. For instance, an adversary[1] may know the home addresses of the participants and use this to identify the responses of all the individuals from Alice's household. Being highly infectious, all or most of them will have the same true value (0 or 1). So, the adversary can reliably infer Alice's value by taking a simple majority vote of her and her household's noisy responses. Note that this does not violate the LDP guarantee since the inputs are appropriately randomized when observed in isolation. Additionally, on account of being

---

[1]The analyst and the adversary could be same, we refer to them separately for the ease of understanding.

Figure 1: Demonstration of how our proposed scheme thwarts inference attacks at different granularities. Fig. 1a depicts the original sensitive data (such as income bracket) with eight color-coded labels. The position of the points represents public information (such as home address) used to correlate them. There are three levels of granularity: warm vs. cool clusters, blue vs. green and red vs. orange crescents, and light vs. dark within each crescent. Fig. 1b depicts $\epsilon = 2.55$ LDP. Fig. 1c and 1d correspond to our scheme, each with $\alpha = 1$ (privacy parameter, Def. 4.3). The former uses a smaller distance threshold (r_1, used to delineate the granularity of grouping – see Sec. 4.2) that mostly shuffles in each crescent. The latter uses a larger distance threshold (r_2) that shuffles within each cluster. Figures in the bottom row demonstrate an inference attack (uses Gaussian process correlation) on all four cases. We see that LDP reveals almost the entire dataset (Fig. 1f) while uniform shuffling prevents all classification (1i). However, the granularity can be controlled with our scheme (Figs. 1g, 1h).

public, the auxiliary information is known to the adversary (and analyst) *a priori* – no mechanism can prevent their disclosure. For instance, any attempts to include Alice's address as an additional feature of the data and then report via LDP is *futile* – the adversary would simply discard the reported noisy address and use the auxiliary information about the exact addresses to identify the responses of her household members. We call such threats *inference attacks* – recovering an individual's private input using all or a subset of other participants' noisy responses. It is well known that protecting against inference attacks that rely on underlying data correlations is beyond the purview of DP (Kifer & Machanavajjhala, 2014; Tschantz et al., 2020).

Strategy 2 corresponds to the recently introduced shuffle DP model, such as Google's Prochlo (Bittau et al., 2017b). Here, the noisy responses are completely anonymized – the adversary cannot identify which LDP responses correspond to Alice and her household. Under such a model, only information that is completely order agnostic (i.e., symmetric functions that can be computed over just the *bag* of values, such as aggregate statistics) can be extracted. Consequently, the analyst also fails to accomplish their original goal as all the underlying data correlation is destroyed.

Thus, we see that the two models of deployment for LDP present a trade-off between vulnerability to inference attacks and scope of data learnability. In fact, as demonstrated in Kifer & Machanavajjhala (2011), it is impossible to defend against *all* inference attacks while simultaneously maintaining utility for learning. In the extreme case that the adversary knows *everyone* in Alice's community has the same true value (but not which one), no mechanism can prevent revelation of Alice's datapoint short of destroying all utility of the dataset. This then begs the question: ***Can we formally suppress specific inference attacks targeting each data owner while maintaining some meaningful learnability of the private data?*** Referring back to our example, can we thwart attacks inferring Alice's data using specifically her households' responses and still allow the medical analyst to learn its target trends? Can we offer this to every data owner participating?

In this paper, we strike a balance and propose a generalized shuffle framework that meets the utility requirements of the above analyst while formally protecting data owners against inference attacks. Our solution is based on the key insight: *the order of the data acts as the proxy for the identity of data owners* as illustrated above. The granularity at which the ordering is maintained formalizes resistance to inference attacks while retaining some meaningful learnability of the private data. Specifically, we guarantee each data owner that their data is shuffled together with a carefully chosen group of other data owners. Revisiting our example, consider uniformly shuffling the responses from Alice's household and her immediate neighbors. Now an adversary cannot use her household's responses to predict her value any better than they could with a random sample of responses from this group. In the same way that LDP prevents reconstruction of her datapoint using specifically *her* noisy response, this scheme prevents reconstruction of her datapoint using specifically *her households'* responses. The real challenge is offering such guarantees *equally* to *every* data owner. Bob, Alice's

neighbor, needs his households' responses shuffled in with his neighbors, as does Luis who is a neighbor of Bob but *not* of Alice. Thus, we have n data owners with n distinct, overlapping groups. Our scheme supports arbitrary groupings (overlapping or not), introducing a diverse and tunable class of privacy/utility trade-offs which is not attainable with either LDP or uniform shuffling alone. For the above example, our scheme can formally protect each data owner from inference attacks using specifically their household, while still learning how disease prevalence changes across the neighborhoods of Alice's community.

This work offers two key contributions to the machine learning privacy literature:

- **Novel privacy guarantee.** We propose a novel privacy definition, d_σ-privacy that captures the privacy of the *order* of a data sequence (Sec. 4.2) and formalizes the degree of resistance against inference attacks (Sec. 4.3). d_σ-privacy allows assigning an arbitrary group, G_i, to each data owner, $\mathsf{DO}_i, i \in [n]$. For instance, the groups can represent individuals in the same age bracket, 'friends' on social media, or individuals living in each other's vicinity (as in case of Alice in our example). Recall that the order is informative of the data owner's identity. Intuitively, d_σ-privacy protects DO_i from inference attacks that arise from knowing the *identity* of the members of their group G_i (Sec. 4.3). Additionally, this grouping determines a threshold of learnability – any learning that is order agnostic within a group (disease prevalence in a neighborhood – the data analyst's goal in our example) is utilitarian and allowed; whereas analysis that involves identifying the values of individuals within a group (disease prevalence within specific households – the adversary's goal) is regarded as a privacy threat and protected against. See Fig. 1 for a toy demonstration of how our guarantee allows *tuning the granularity at which trends can be learned*.

- **Novel shuffle framework.** We propose a novel mechanism that shuffles the data systematically and achieves d_σ-privacy. This provides a generalized shuffle framework that interpolates between no shuffling (LDP) and uniform random shuffling (shuffle model) in terms of protection against inference attacks and data learnability.

2 RELATED WORK

The shuffle model of DP (Bittau et al., 2017a; Cheu et al., 2019; Erlingsson et al., 2019) differs from our scheme as follows. These works (1) study DP benefits of shuffling whereas we study the inferential privacy benefits, and (2) only study uniformly random shuffling where ours generalizes this to tunable, non-uniform shuffling (see App. A.15).

A steady line of work has studied inferential privacy (Kasiviswanathan & Smith, 2014; Kifer & Machanavajjhala, 2011; Ghosh & Kleinberg, 2016; Dalenius, 1977; Dwork & Naor, 2010; Tschantz et al., 2020). Our work departs from those in that we focus on *local* inferential privacy and do so via the new angle of shuffling.

Older works such as k-anonymity (Sweeney, 2002), l-diversity Machanavajjhala et al. (2007), Anatomy (Xiao & Tao, 2006) and others (Wong et al., 2010; Tassa et al., 2012; Xue et al., 2012; Choromanski et al., 2013; Doka et al., 2015) have studied the privacy risk of non-sensitive auxiliary information or 'quasi identifiers'. These works (1) focus on the setting of dataset release, whereas we focus on dataset collection, and (2) do not offer each data owner formal inferential guarantees, whereas we do. The De Finetti attack (Kifer, 2009) shows how shuffling schemes are vulnerable to inference attacks that correlate records to recover the original permutation of sensitive attributes. A strict instance of our privacy guarantee can thwart such attacks (at the cost of no utility, App. A.3).

3 BACKGROUND

Notations. Boldface (such as $\mathbf{x} = \langle x_1, \cdots, x_n \rangle$) denotes a data sequence (ordered list); normal font (such as x_1) denotes individual values and $\{\cdot\}$ represents a multiset or bag of values.

3.1 LOCAL DIFFERENTIAL PRIVACY

The local model consists of a set of data owners and an untrusted data aggregator (analyst); each individual perturbs their data using a LDP algorithm (randomizers) and sends it to the analyst. The LDP guarantee is formally defined as

Definition 3.1. [Local Differential Privacy, LDP Warner (1965); Evfimievski et al. (2003); Kasiviswanathan et al. (2008)] A randomized algorithm $\mathcal{M} : \mathcal{X} \to \mathcal{Y}$ is ϵ-locally differentially private (or ϵ-LDP), if for any pair of private values $x, x' \in \mathcal{X}$ and any subset of output,

$$\Pr\big[\mathcal{M}(x) \in \mathcal{W}\big] \leq e^\epsilon \cdot \Pr\big[\mathcal{M}(x') \in \mathcal{W}\big] \tag{1}$$

The shuffle model is an extension of the local model where the data owners first randomize their inputs. Additionally, an intermediate trusted shuffler applies a *uniformly random permutation* to

all the noisy responses before the analyst can view them. The anonymity provided by the shuffler requires less noise than the local model for achieving the same privacy.

3.2 MALLOWS MODEL

A permutation of a set S is a bijection $S \mapsto S$. The set of permutations of $[n], n \in \mathbb{N}$ forms a symmetric group S_n. As a shorthand, we use $\sigma(\mathbf{x})$ to denote applying permutation $\sigma \in \mathrm{S}_n$ to a data sequence $\mathbf{x}$ of length n. Additionally, $\sigma(i), i \in [n], \sigma \in \mathrm{S}_n$ denotes the value at index i in σ and σ^{-1} denotes its inverse. For example, if $\sigma = (1\ 3\ 5\ 4\ 2)$ and $\mathbf{x} = \langle 21, 33, 45, 65, 67 \rangle$, then $\sigma(\mathbf{x}) = \langle 21, 45, 67, 65, 33 \rangle$, $\sigma(2) = 3, \sigma(3) = 5$ and $\sigma^{-1} = (1\ 5\ 2\ 4\ 3)$.

Mallows model is a popular probabilistic model for permutations (MALLOWS, 1957). The mode of the distribution is given by the reference permutation σ_0 – the probability of a permutation increases as we move 'closer' to σ_0 as measured by rank distance metrics, such as the Kendall's tau distance (Def. A.2). The dispersion parameter θ controls how fast this increase happens.

Definition 3.2. For a dispersion parameter θ, a reference permutation $\sigma_o \in \mathrm{S}_n$, and a rank distance measure $\delta : \mathrm{S}_n \times \mathrm{S}_n \mapsto \mathbb{R}$, $\mathbb{P}_{\Theta, \delta}(\sigma : \sigma_0) = \frac{1}{\psi(\theta, \delta)} e^{-\theta \delta(\sigma, \sigma_0)}$ is the Mallows model where $\psi(\theta, \delta) = \sum_{\sigma \in \mathrm{S}_n} e^{-\theta \delta(\sigma, \sigma_0)}$ is a normalization term and $\sigma \in \mathrm{S}_n$.

4 DATA PRIVACY AND SHUFFLING

In this section, we present d_σ-privacy and a shuffling mechanism capable of achieving the d_σ-privacy guarantee.

Figure 2: Trusted shuffler mediates on $\mathbf{y}$

4.1 PROBLEM SETTING

In our problem setting, we have n data owners $\mathsf{DO}_i, i \in [n]$ each with a private input $x_i \in \mathcal{X}$ (Fig. 2). The data owners first randomize their inputs via a ϵ-LDP mechanism to generate $y_i = \mathcal{M}(x_i)$. Additionally, just like in the shuffle model, we have a trusted shuffler. It mediates upon the noisy responses $\mathbf{y} = \langle y_1, \cdots, y_n \rangle$ to obtain the final output sequence $\mathbf{z} = \mathcal{A}(\mathbf{y})$ ($\mathcal{A}$ corresponds to Alg. 1) which is sent to the untrusted data analyst. The shuffler can be implemented via trusted execution environments (TEE) just like Google's Prochlo. Next, we formally discuss the notion of order and its implications.

Definition 4.1. (Order) The order of a sequence $\mathbf{x} = \langle x_1, \cdots, x_n \rangle$ refers to the indices of its set of values $\{x_i\}$ and is represented by permutations from S_n.

When the noisy response sequence $\mathbf{y} = \langle y_1, \cdots, y_n \rangle$ is represented by the identity permutation $\sigma_I = (1\ 2\ \cdots\ n)$, the value at index 1 corresponds to DO_1 and so on. Standard LDP releases the identity permutation w.p. 1. The output of the shuffler, $\mathbf{z}$, is some permutation of the sequence $\mathbf{y}$, i.e.,
$$\mathbf{z} = \sigma(\mathbf{y}) = \langle y_{\sigma(1)}, \cdots, y_{\sigma(n)} \rangle$$
where σ is determined via $\mathcal{A}(\cdot)$. For example, for $\sigma = (4\ 5\ 2\ 3\ 1)$, we have $\mathbf{z} = \langle y_4, y_5, y_2, y_3, y_1 \rangle$ which means that the value at index 1 (DO_1) now corresponds to that of DO_4 and so on.

4.2 DEFINITION OF d_σ-PRIVACY

Inferential risk captures the threat of an adversary who infers DO_i's private x_i using all or a subset of other data owners' released y_j's. Since we cannot prevent all such attacks and maintain utility, our aim is to formally limit *which data owners* can be leveraged in inferring DO_i's private x_i. To make this precise, each DO_i may choose a corresponding group, $G_i \subseteq [n]$, of data owners.

d_σ-privacy guarantees that y_j values originating from a data owner's group G_i are shuffled together. In doing so, the LDP values corresponding to subsets of DO_i's group $I \subset G_i$ cannot be reliably identified, and thus cannot be singled out to make inferences about DO_i's x_i. If Alice's group includes her whole neighborhood, LDP data originating from her household cannot be singled out to recover her private x_i.

Figure 3: An example social media connectivity graph $\mathbf{t}_{e.g}$

Any choice of grouping $\mathcal{G} = \{G_1, G_2, \ldots, G_n\}$ can be accommodated under d_σ-privacy. Each data owner may choose a group large enough to hide anyone they feel sufficient risk from. We outline two systematic approaches to assigning groups as follows:

- Let $\mathbf{t} = \langle t_1, \cdots, t_n \rangle, t_i \in \mathcal{T}$ denote some public auxiliary information about each individual. DO_i's group, G_i, could consist of all those DO_j's who are similar to DO_i w.r.t. the public auxiliary information t_i, t_j according to some distance measure $d : \mathcal{T} \times \mathcal{T} \to \mathbb{R}$. Here, we define

'similar' as being under a threshold[2] $r \in \mathbb{R}$ such that $G_i = \{j \in [n] \big| d(t_i, t_j) \leq r\}, \forall i \in [n]$. For example, $d(\cdot)$ can be Euclidean distance if $\mathcal{T}$ corresponds to geographical locations, thwarting inference attacks leveraging one's household or immediate neighbors. If $\mathcal{T}$ represents a social media connectivity graph, $d(\cdot)$ can measure the path length between two nodes, thwarting inference attacks using specifically one's close friends. For the example social media connectivity graph depicted in Fig. 3, assuming distance metric path length and $r = 2$, the groups are defined as $G_1 = \{1, 7, 8, 2, 5, 6\}, G_2 = \{2, 1, 7, 5, 6, 3\}$ and so on.

- Alternatively, the data owners might opt for a group of a specific size $r < n$. Collecting private data from a social media network, we may set $r = 50$, where each G_i is encouraged to include the 50 data owners DO_i interacts with most frequently.

Intuitively, d_σ-privacy protects DO_i against inference attacks that leverages correlations at a finer granularity than G_i. In other words, under d_σ-privacy, one subset of k data owners $\subset G_i$ (e.g. household) is no more useful for targeting x_i than any other subset of k data owners $\subset G_i$ (e.g. some combination of neighbors). This leads to the following key insight for the formal privacy definition.

Key Insight. Formally, our privacy goal is to prevent the leakage of ordinal information from within a group. We achieve this by systematically *bounding the dependence of the mechanism's output on the relative ordering (of data values corresponding to the data owners) within each group*.
First, we introduce the notion of neighboring permutations.

Definition 4.2. (Neighboring Permutations) Given a group assignment $\mathcal{G}$, two permutations $\sigma, \sigma' \in \mathrm{S}_n$ are defined to be neighboring w.r.t. a group $G_i \in \mathcal{G}$ (denoted as $\sigma \approx_{G_i} \sigma'$) if $\sigma(j) = \sigma'(j) \; \forall j \notin G_i$.

Neighboring permutations differ only in the indices of its corresponding group G_i. For example, $\sigma = (\underline{1}\,\underline{2}\,4\,5\,\underline{7}\,\underline{6}\,\underline{10}\,\underline{3}\,8\,9)$ and $\sigma' = (\underline{7}\,\underline{3}\,4\,5\,\underline{6}\,\underline{2}\,\underline{1}\,\underline{10}\,8\,9)$ are neighboring w.r.t G_1 (Fig. 3) since they differ only in $\sigma(1), \sigma(2), \sigma(5), \sigma(6), \sigma(7)$ and $\sigma(8)$. We denote the set of all neighboring permutations as

$$\mathrm{N}_{\mathcal{G}} = \{(\sigma, \sigma') | \sigma \approx_{G_i} \sigma', \exists G_i \in \mathcal{G}\} \qquad (2)$$

Now, we formally define d_σ-privacy as follows.

Definition 4.3 (d_σ-privacy). For a given group assignment $\mathcal{G}$ on a set of n entities and a privacy parameter $\alpha \in \mathbb{R}_{\geq 0}$, a randomized mechanism $\mathcal{A} : \mathcal{Y}^n \mapsto \mathcal{V}$ is $(\alpha, \mathcal{G})$-d_σ private if for all $\mathbf{y} \in \mathcal{Y}^n$ and neighboring permutations $\sigma, \sigma' \in \mathrm{N}_{\mathcal{G}}$ and any subset of output $O \subseteq \mathcal{V}$, we have

$$\Pr[\mathcal{A}(\sigma(\mathbf{y})) \in O] \leq e^\alpha \cdot \Pr[\mathcal{A}(\sigma'(\mathbf{y})) \in O] \qquad (3)$$

$\sigma(\mathbf{y})$ and $\sigma'(\mathbf{y})$ are defined to be *neighboring sequences*.

d_σ-privacy states that, for any group G_i, the mechanism is (almost) agnostic of the order of the data within the group. Even after observing the output, an adversary cannot learn about the relative ordering of the data within any group. Thus, two neighboring sequences are indistinguishable to an adversary. An important property of d_σ-privacy is that post-processing computations does not degrade privacy. Additionally, when applied multiple times, the privacy guarantee degrades gracefully. Both the properties are analogous to DP and are presented in App. A.4.

Note. Any data sequence $\mathbf{x} = \langle x_1, \cdots, x_n \rangle$ can be viewed as a two-tuple, $(\{x\}, \sigma)$, where $\{x\}$ denotes the *bag* of values and $\sigma \in S_n$ denotes the corresponding indices of the values which represents the *order* of the data. The ϵ-LDP protects the bag of data values, $\{x\}$, while d_σ-privacy protects the order, σ. Thus, the two privacy guarantees cater to orthogonal parts of a data sequence (see Thm. 4.2). Also, $\alpha = \infty \, (0), r = 0 \, (n)$ represents the standard LDP (shuffle DP) setting.

4.3 PRIVACY IMPLICATIONS

The group assignment $\mathcal{G}$ delineates a threshold of learnability which determines the privacy/utility tradeoff as follows.

- **Learning allowed (Analyst's goal)**. d_σ-privacy can answer queries that are order agnostic within groups, such as aggregate statistics of a group. In Alice's case, the analyst can estimate the disease prevalence in her neighborhood.

- **Learning disallowed (Adversary's goal)**. Adversaries cannot identify (noisy) values of individuals within any group. While they may learn the disease prevalence in Alice's neighborhood, they cannot determine the prevalence within her household and use that to recover her value x_i.

To make this precise, we first formalize the privacy implications of the d_σ guarantee in the standard Bayesian framework, typically used for studying inferential privacy. Next, we formalize the privacy provided by the combination of LDP and d_σ guarantees by way of a decision theoretic adversary.

---

[2] We could also have different thresholds, r_i, for every data owner, DO_i.

Bayesian Adversary. Consider a Bayesian adversary with any prior $\mathcal{P}$ on the joint distribution of noisy responses, $\Pr_{\mathcal{P}}[\mathbf{y}]$, which models their beliefs on the correlation between the participants (such as the correlation between Alice and her households' disease status). Their goal is to infer DO_i's private input x_i. As with early DP works (Dwork et al., 2006), we consider an *informed* adversary. Here, the adversary knows (1) the sequence (assignment) of noisy values outside G_i, $\mathbf{y}_{\overline{G}_i}$, and (2) the (unordered) bag of noisy values in G_i, $\{y_{G_i}\}$. d_σ-privacy bounds the prior-posterior odds gap on x_i for such as informed adversary as follows:

Theorem 4.1. *For a given group assignment $\mathcal{G}$ on a set of n data owners, if a shuffling mechanism $\mathcal{A} : \mathcal{Y}^n \mapsto \mathcal{Y}^n$ is $(\alpha, \mathcal{G})$-$d_\sigma$private, then for each data owner $\mathsf{DO}_i, i \in [n]$,*

$$\max_{\substack{i \in [n] \\ a,b \in \mathcal{X}}} \left| \log \frac{\Pr_{\mathcal{P}}[x_i = a | \mathbf{z}, \{y_{G_i}\}, \mathbf{y}_{\overline{G}_i}]}{\Pr_{\mathcal{P}}[x_i = b | \mathbf{z}, \{y_{G_i}\}, \mathbf{y}_{\overline{G}_i}]} - \log \frac{\Pr_{\mathcal{P}}[x_i = a | \{y_{G_i}\}, \mathbf{y}_{\overline{G}_i}]}{\Pr_{\mathcal{P}}[x_i = b | \{y_{G_i}\}, \mathbf{y}_{\overline{G}_i}]} \right| \leq \alpha$$

for a prior distribution $\mathcal{P}$, where $\mathbf{z} = \mathcal{A}(\mathbf{y})$ and $\mathbf{y}_{\overline{G}_i}$ is the noisy sequence for data owners outside G_i. See App A.5 for the proof and further discussion on the semantic meaning of the above guarantee.

Decision Theoretic Adversary. Here, we analyse the privacy provided by the combination of LDP and d_σ guarantees. Consider a decision theoretic adversary who aims to identify the noisy responses, $\{z_I\}$, that originated from a specific subset of data owners, $I \subset G_i$ (such as the members of Alice's household). We denote the adversary by a (possibly randomized) function mapping from the output $\mathbf{z}$ sequence to a set of k indices, $\mathcal{D}_{Adv} : \mathcal{Y}^n \rightarrow [n]^k$, where $k = |I|$. These k indices, $H \in [n]^k$, represent the elements of $\mathbf{z}$ that $\mathcal{D}_{Adv}$ believes originated from the data owners in I. $\mathcal{D}_{Adv}$ wins if $> k/2$ of the chosen indices indeed originated from I, i.e, $|\sigma(H) \cap I| > k/2$, where $z_i = y_{\sigma(i)}$ and $\sigma(H) = \{\sigma(i) : i \in H\}$. $\mathcal{D}_{Adv}$ loses if most of H did not originate from I, i.e., $|\sigma(H) \cap I| \leq k/2$. We choose the above adversary because this re-identification is a key step in carrying out inference attacks – in failing to reliably re-identify the noisy values originating from I, one cannot make inferences on x_i specifically from the subset $I \subset G_i$.

Theorem 4.2. *For $\mathcal{A}(\mathcal{M}(\mathbf{x})) = \mathbf{z}$ where $\mathcal{M}(\cdot)$ is ϵ-LDP and $\mathcal{A}(\cdot)$ is α - $d_\sigma$private, we have*

$$\Pr[\mathcal{D}_{Adv} \text{ loses}] \geq \lfloor \frac{r - k}{k} \rfloor e^{-(2k\epsilon + \alpha)} \cdot \Pr[\mathcal{D}_{Adv} \text{ wins}]$$

for any input subgroup $I \subset G_i, r = |G_i|$ and $k < r/2$.

The adversary's ability to re-identify the $\{z_I\}$ values comes partially from the *bag of values* (quantified by ϵ) and partially from the *order* (quantified by α). We highlight two implications of this fact.

- When ϵ is small ($\ll 1$), an adversary's ability to re-identify the noisy values $\{z_I\}$ originating from I may very well be dominated by α. For instance, if $\epsilon = 0.2$ and $k = 5$, the adversary's advantage is dominated by α for any $\alpha > 2$. When using LDP alone (no shuffling), $\alpha = \infty$ and the adversary can exactly recover which values came from Alice's household. As such, even a moderate α value (obtained via d_σ-privacy) significantly reduces the ability to re-identify the values.

- When the loss is dominated by ϵ ($2k\epsilon \gg \alpha$), the above expression allows us to disentangle the *source of privacy loss*. In this regime, adversaries get most of their advantage from the bag of values released, not from the order of the release. That is, even if $\alpha = 0$ (uniform random shuffling), participants still suffer a large risk of re-identification simply due to the noisy values being reported. Thus, no shuffling mechanism can prevent re-identification in this regime.

Discussion. In spirit, DP does not guarantee protection against recovering DO_i's private x_i value. It guarantees that – had a user not participated (or equivalently submitted a false value x_i') – the adversary would have about the same ability to learn their true value, potentially from the responses of other data owners. In other words, the choice to participate is unlikely to be responsible for the disclosure of x_i. Similarly, d_σ-privacy does not prevent disclosure of x_i. By requiring indistinguishability of neighboring permutations, it guarantees that – had the data owners of any group G_i completely swapped identities – the adversary would have about the same ability to learn x_i. So most likely, Alice's household is not uniquely responsible for a disclosure of her x_i: had her household swapped identities with any of her neighbors, the adversary would probably draw the same conclusion on x_i. Or, as detailed in Thm.4.2, an adversary cannot reliably resolve which $\{z\}$ values originated from Alice's household, so they cannot draw conclusions based on her household's responses. In a nutshell,

- Inference attacks can recover a data owner DO_i's private data x_i from the responses of other data owners. The order of the data acts as the proxy for the data owner's identity which can aid an adversary in corralling the subset of other data owners who correlate with DO_i (required to make a reliable inference of x_i).

- DP alleviates concerns that DO_i's choice to share data (y_i) will result in disclosure of x_i, and d_σ-privacy alleviates concerns that $\overline{\mathsf{DO}_i\text{'s group's } (G_i)}$ choice to share their identity will result in disclosure of x_i.

4.4 d_σ-PRIVATE SHUFFLING MECHANISM

We now describe our novel shuffling mechanism that can achieve d_σ-privacy. In a nutshell, our mechanism samples a permutation from a suitable Mallows model and shuffles the data sequence accordingly. We can characterize the d_σ-privacy guarantee of our mechanism in the same way as that of the DP guarantee of classic mechanisms (Dwork & Roth, 2014) – with variance and sensitivity. Intuitively, a larger dispersion parameter $\theta \in \mathbb{R}$ (Def. 3.2) reduces randomness over permutations, increasing utility and increasing (worsening) the privacy parameter α. The maximum value of θ for a given α guarantee depends on the sensitivity of the rank distance measure $\mathfrak{d}(\cdot)$ over all neighboring permutations $N_\mathcal{G}$. Formally, we define the sensitivity as

$$\Delta(\sigma_0 : \mathfrak{d}, \mathcal{G}) = \max_{(\sigma, \sigma') \in N_\mathcal{G}} |\mathfrak{d}(\sigma_0\sigma, \sigma_0) - \mathfrak{d}(\sigma_0\sigma', \sigma_0)|,$$

the maximum change in distance $\mathfrak{d}(\cdot)$ from the reference permutation σ_0 for any pair of neighboring permutations $(\sigma, \sigma') \in N_\mathcal{G}$ permuted by σ_0. The privacy parameter of the mechanism is then proportional to its sensitivity $\alpha = \theta \cdot \Delta(\sigma_0 : \mathfrak{d}, \mathcal{G})$.

Algorithm 1: d_σ-private Shuffling Mech.

Input: LDP sequence $\mathbf{y} = \langle y_1, \cdots, y_n \rangle$;
       Public aux. info. $\mathbf{t} = \langle t_1, \cdots t_n \rangle$;
       Dist. threshold r; Priv. param. α;

Output: $\mathbf{z}$ - Shuffled output sequence;

1   $\mathcal{G} = ComputeGroupAssignment\,(\mathbf{t}, r)$;
2   Construct graph $\mathbb{G}$ with
     a) vertices $V = \{1, 2, \cdots, n\}$
     b) edges $E = \{(i,j) : j \in G_i, G_i \in \mathcal{G}\}$
3   $root = \arg\max_{i \in [n]} |G_i|$;
4   $\sigma_0 = \mathsf{BFS}(\mathbb{G}, root)$;
5   $\Delta = ComputeSensitivity(\sigma_0, \mathcal{G})$
6   $\theta = \alpha/\Delta$;
7   $\hat{\sigma} \sim \mathbb{P}_{\theta, \mathfrak{d}}(\sigma_0)$;
8   $\sigma^* = \sigma_0^{-1}\hat{\sigma}$;
9   $\mathbf{z} = \langle y_{\sigma^*(1)}, \cdots y_{\sigma^*(n)} \rangle$;
10   Return $\mathbf{z}$;

Given $\mathcal{G}$ and a reference permutation σ_0, the sensitivity of a rank distance measure $\mathfrak{d}(\cdot)$ depends on the *width*, $\omega_\mathcal{G}^\sigma$, which measures how 'spread apart' the members of any group of $\mathcal{G}$ are in σ_0:

$$\omega_{G_i}^\sigma = \max_{(j,k) \in G_i \times G_i} \left|\sigma^{-1}(j) - \sigma^{-1}(k)\right|, i \in [n]; \qquad \omega_\mathcal{G}^\sigma = \max_{G_i \in \mathcal{G}} \omega_{G_i}^\sigma$$

For example, for $\sigma = (1\,3\,7\,8\,6\,4\,5\,2\,9\,10)$ and $G_1 = \{1, 7, 8, 2, 5, 6\}$, $\omega_{G_1}^\sigma = |\sigma^{-1}(1) - \sigma^{-1}(2)| = 7$. The sensitivity is an increasing function of the width. For instance, for Kendall's τ distance $\mathfrak{d}_\tau(\cdot)$ we have $\Delta(\sigma_0 : \mathfrak{d}_\tau, \mathcal{G}) = \omega_\mathcal{G}^{\sigma_0}(\omega_\mathcal{G}^{\sigma_0} + 1)/2$.

If a reference permutation clusters the members of each group closely together (low width), then the groups are more likely to permute within themselves. This has two benefits. First, for the same θ (θ is an indicator of utility as it determines the dispersion of the sampled permutation), a lower value of width gives lower α (better privacy). Second, if a group is likely to shuffle within itself, it will have better (η, δ)-preservation – a novel utility metric, we propose, for a shuffling mechanism. Intuitively, a mechanism is (η, δ)-preserving w.r.t a subset of indices $S \subset [n]$ if at least $\eta\%$ of its indices are shuffled within itself with probability $(1 - \delta)$. The rationale behind this metric is that it captures the utility of the learning allowed by d_σ-privacy – if S is equal to some group $G \in \mathcal{G}$, high (η, δ)-preservation allows overall statistics of G to be captured since $\eta\%$ of the correct data values remain preserved. We present the formal discussion in App. A.7.

Unfortunately, minimizing $\omega_\mathcal{G}^\sigma$ is an NP-hard problem (Thm. A.3 in App. A.9). Instead, we estimate the optimal σ_0 using the following heuristic[3] approach based on a graph breadth first search.

Algorithm Description. Alg. 1 above proceeds as follows. We first compute the group assignment, $\mathcal{G}$, based on the public auxiliary information and desired threshold r following discussion in Sec. 4.2 (Step 1). Then we construct σ_0 with a breadth first search (BFS) graph traversal.
We translate $\mathcal{G}$ into an undirected graph (V, E), where the vertices are indices $V = [n]$ and two indices i, j are connected by an edge if they are both in some group (Step 2). Next, σ_0 is computed via a breadth first search traversal (Step 4) – if the k-th node in the traversal is i, then $\sigma_0(k) = i$. The rationale is that neighbors of i (members of G_i) would be traversed in close succession. Hence, a neighboring node j is likely to be traversed at some step h near k which means $|\sigma_0^{-1}(i) - \sigma_0^{-1}(j)| = |h - k|$ would be small (resulting in low width). Additionally, starting from the node with the highest degree (Steps 3-4) which corresponds to the largest group in $\mathcal{G}$ (lower bound for $\omega_\mathcal{G}^\sigma$ for any σ) helps to curtail the maximum width in σ_0.

---

[3] The heuristics only affect σ_0 (and utility). Once σ_0 is fixed, Δ is computed exactly as discussed above.

This is followed by the computation of the dispersion parameter, θ, for our Mallows model (Steps 5-6). Next, we sample a permutation from the Mallows model (Step 7) $\hat{\sigma} \sim \mathbb{P}_\theta(\sigma : \sigma_0)$ and we apply the inverse reference permutation to it, $\sigma^* = \sigma_0^{-1}\hat{\sigma}$ to obtain the desired permutation for shuffling. Recall that $\hat{\sigma}$ is (most likely) close to σ_0, which is unrelated to the original order of the data. σ_0^{-1} therefore brings σ^* back to a shuffled version of the original sequence (identity permutation σ_I). Note that since Alg. 1 is publicly known, the adversary/analyst knows σ_0. Hence, even in the absence of this step from our algorithm, the adversary/analyst could perform this anyway. Finally, we permute $\mathbf{y}$ according to σ^* and output the result $\mathbf{z} = \hat{\sigma}(\mathbf{y})$ (Steps 9-10).

Theorem 4.3. *Alg. 1 is $(\alpha, \mathcal{G})$-d_σ private where $\alpha = \theta \cdot \Delta(\sigma_0 : \mathfrak{d}, \mathcal{G})$.*

The proof is in App. A.11. Note that Alg. 1 provides the same level of privacy (α) for any two group assignment $\mathcal{G}, \mathcal{G}'$ as long as they have the same sensitivity, i.e, $\Delta(\sigma_0 : \mathfrak{d}_\tau, \mathcal{G}) = \Delta(\sigma_0 : \mathfrak{d}_\tau, \mathcal{G}')$. This leads to the following theorem which generalizes the privacy guarantee for any group assignment.

Theorem 4.4. *Alg. 1 satisfies $(\alpha', \mathcal{G}')$-d_σ privacy for any group assignment $\mathcal{G}'$ with $\alpha' = \alpha \frac{\Delta(\sigma_0 : \mathfrak{d}, \mathcal{G}')}{\Delta(\sigma_0 : \mathfrak{d}, \mathcal{G})}$ (proof in App. A.12.)*

Note. Producing σ^* is completely data ($\mathbf{y}$) independent. It only requires access to the public auxiliary information $\mathbf{t}$. Hence, Steps $1 - 6$ can be performed in a pre-processing phase and do not contribute to the actual running time. See App. A.10 for an illustration of Alg. 1 and runtime analysis.

5 EVALUATION

(a) *PUDF*: Attack   (b) *Twitch*: Attack   (c) *PUDF*: Learnability   (d) *Twitch*: Learnability

Figure 4: Our scheme interpolates between standard LDP (orange line) and uniform shuffling (blue line) in both privacy and data learnability. All plots increase group size along x-axis (except (d)). (a) → (b): The fraction of participants vulnerable to an inferential attack. (c) → (d): The accuracy of a calibration model trained on $\mathbf{z}$ predicting the distribution of LDP outputs at any point $t \in \mathcal{T}$, such as the distribution of medical insurance types used specifically in the Houston area (not possible when uniformly shuffling across Texas).

The previous sections describe how our shuffling framework interpolates between standard LDP and uniform random shuffling. We now experimentally evaluate this asking the following two questions –

Q1. Does the Alg. 1 mechanism protect against realistic inference attacks?
Q2. How well can Alg. 1 tune a model's ability to learn trends within the shuffled data, i.e., tune *data learnability*?

We evaluate on four datasets. We are not aware of any prior work that provides comparable local inferential privacy. Hence, we baseline our mechanism with the two extremes: standard LDP and uniform random shuffling. For concreteness, we detail our procedure with the *PUDF* dataset (PUD) (license), which comprises $n \approx 29\text{k}$ psychiatric patient records from Texas. Each data owner's sensitive value x_i is their medical payment method, which is reflective of socioeconomic class (such as medicaid or charity). Public auxiliary information $t \in \mathcal{T}$ is the hospital's geolocation. Such information is used for understanding how payment methods (and payment amounts) vary from town to town for insurances in practice (Eric Lopez, 2020). Uniform shuffling across Texas precludes such analyses. Standard LDP risks inference attacks, since patients attending hospitals in the same neighborhood have similar socioeconomic standing and use similar payment methods, allowing an adversary to correlate their noisy y_i's. To trade these off, we apply Alg. 1 with $d(\cdot)$ being distance (km) between hospitals, $\alpha = 4$ and Kendall's τ rank distance measure for permutations.

Our inference attack predicts DO_i's x_i by taking a majority vote of the z_j values of the 25 data owners within r^* of t_i and who are most similar to DO_i w.r.t some additional privileged auxiliary information $t_j^p \in \mathcal{T}_p$. For PUDF, this includes the 25 data owners who attended hospitals that are within r^* km of DO_i's hospital, and are most similar in payment amount t_j^p. Using an $\epsilon = 2.5$ randomized response mechanism, we resample the LDP sequence $\mathbf{y}$ 50 times, and apply Alg. 1's chosen permutation to

each, producing 50 $\mathbf{z}$'s. We then mount the majority vote attack on each x_i for each $\mathbf{z}$. If the attack on a given x_i is successful across $\geq 90\%$ of these LDP trials, we mark that data owner as vulnerable – although they randomize with LDP, there is a $\geq 90\%$ chance that a simple inference attack can recover their true value. We record the fraction of vulnerable data owners as ρ. We report 1-standard deviation error bars over 10 trials.

Additionally, we evaluate *data learnability* – how well the underlying statistics of the dataset are preserved across $\mathcal{T}$. For *PUDF*, this means training a model on the shuffled $\mathbf{z}$ to predict the distribution of payment methods used near, for instance, $t_i = $ Houston for DO_i. For this, we train a calibrated model, $\mathtt{Cal} : \mathcal{T} \to \mathcal{D}_x$, on the shuffled outputs where $\mathcal{D}_x$ is the set of all distributions on the domain of sensitive attributes $\mathcal{X}$. We implement $\mathtt{Cal}$ as a gradient boosted decision tree (GBDT) model (Friedman, 2001) calibrated with Platt scaling (Niculescu-Mizil & Caruana, 2005). For each location t_i, we treat the empirical distribution of x_i values within r^* as the ground truth distribution at t_i, denoted by $\mathcal{E}(t_i) \in \mathcal{D}_x$. Then, for each t_i, we measure the Total Variation error between the predicted and ground truth distributions $\mathrm{TV}\big(\mathcal{E}(t_i), \mathtt{Cal}_r(t_i)\big)$. We then report $\lambda(r)$ – the average TV error for distributions predicted at each $t_i \in \mathbf{t}$ normalized by the TV error of naively guessing the uniform distribution at each t_i. With standard LDP, this task can be performed relatively well at the risk of inference attacks. With uniformly shuffled data, it is impossible to make geographically localized predictions unless the distribution of payment methods is identical in every Texas locale.

We additionally perform the above experiments on the following three datasets

- *Twitch* (Rozemberczki et al., 2019). This dataset, gathered from the *Twitch* social media platform, includes a graph of $\approx 9K$ edges (mutual friendships) along with node features. The user's history of explicit language is private $\mathcal{X} = \{0, 1\}$. $\mathcal{T}$ is a user's mutual friendships, i.e. t_i is the i'th row of the graph's adjacency matrix. We do not have any $\mathcal{T}_P$ here and select the 25 neighbors randomly.

- *Syn*. This is a synthetic dataset of size $20K$ which can be classified at three granularities – 8-way, 4-way and 2-way (Fig. 1a shows a scaled down version of the dataset). The eight color labels are private $\mathcal{X} = [8]$; the 2D-positions are public $\mathcal{T} = \mathbb{R}^2$. For learnability, we measure the accuracy of 8-way, 4-way and 2-way GBDT models trained on $\mathbf{z}$ on an equal sized test set at each r.

- *Adult* (Dua & Graff, 2017). This dataset is derived from the 1994 Census and has $\approx 33K$ records. Whether DO_i's annual income is $\geq 50k$ is considered private, $\mathcal{X} = \{\geq 50k, < 50k\}$. $\mathcal{T} = [17, 90]$ is age and $\mathcal{T}_P$ is the individual's marriage status. Due to lack of space figures are in App. A.14.2.

Experimental Results.

Q1. Our formal guarantee on the inferential privacy loss (Thm. 4.1) is described w.r.t to a 'strong' adversary (with access to $\{y_{G_i}\}, \mathbf{y}_{\overline{G}_i}$). Here, we test how well does our proposed scheme (Alg. 1) protect against inference attacks on real-world datasets without any such assumptions. Additionally, to make our attack more realistic, the adversary has access to extra privileged auxiliary information $\mathcal{T}_P$ which is *not used* by Alg. 10. Fig. 4a$\to$ 4b show that our scheme significantly reduces the attack efficacy. For instance, ρ is reduced by $2.7X$ at the attack distance threshold r^* for *PUDF*.

Additionally, ρ for our scheme varies from that of LDP[4] (minimum privacy) to uniform shuffle (maximum privacy) with increasing r (equivalently group size as in Fig. 4b) thereby spanning the entire privacy spectrum. As expected, ρ decreases with decreasing privacy parameter α (Fig. 8b).

Q2. Fig.4c $\to$ 4d show that λ varies from that of LDP (maximum learnability) to that of uniform shuffle (minimum learnability) with increasing r (equivalently, group size), thereby providing tunability. Interestingly, for *Adult* our scheme reduces ρ by $1.7X$ at the same λ as that of LDP for $r = 1$ (Fig. 8c). Fig. 5 shows that the distance threshold r defines the granularity at which the data can be classified. LDP allows 8-way classification while uniform shuffling allows none. The granularity of classification can be tuned by our scheme – r_8, r_4 and r_2 mark the thresholds for 8-way, 4-way and 2-way classifications, respectively.

Figure 5: *Syn*: Learnability

6 CONCLUSION

We have proposed a new privacy definition, d_σ-privacy that casts new light on the inferential privacy benefits of shuffling and a novel shuffling mechanism to achieve the same.

---

[4]Our scheme gives lower ρ than LDP at $r = 0$ because the resulting groups are non-singletons. For instance, for PUDF, G_i includes all individuals with the same zipcode as DO_i.

7 ETHIS STATEMENT

It is the aim of this paper to formalize the enhanced privacy guarantees offered by shuffling, to provide intuition of what those formal guarantees semantically offer to data owners, and to demonstrate an algorithm + experiments which offer these guarantees while meeting analyst utility requirements. We feel that all of these aims as well as the public datasets used are ethical.

8 REPRODUCIBILITY STATEMENT

The majority of this paper formalizes a novel perspective on the privacy guarantees achieved by shuffling (i.e. randomizing the order of the data as opposed to the values). Detailed proofs as well as intuitive discussions are provided in the Appendix. All datasets are public. A `.zip` file demonstrating code of each experiment has been uploaded as supplementary material.

REFERENCES

Hospital discharge data public use data file. `https://www.dshs.state.tx.us/THCIC/Hospitals/Download.shtm`.

Derangement. `https://en.wikipedia.org/wiki/Derangement`.

Simonetti N. Vazacopoulos A. Balas, E. Job shop scheduling with setup times, deadlines and precedence constraints. *J Sched*, 11:253–262, 2008. URL `https://doi.org/10.1007/s10951-008-0067-7`.

Victor Balcer and Albert Cheu. Separating local shuffled differential privacy via histograms. In *ITC*, 2020.

Borja Balle, James Bell, Adrià Gascón, and Kobbi Nissim. The privacy blanket of the shuffle model. In Alexandra Boldyreva and Daniele Micciancio (eds.), *Advances in Cryptology – CRYPTO 2019*, pp. 638–667, Cham, 2019. Springer International Publishing. ISBN 978-3-030-26951-7.

R. Bassily, A. Groce, J. Katz, and A. Smith. Coupled-worlds privacy: Exploiting adversarial uncertainty in statistical data privacy. In *2013 IEEE 54th Annual Symposium on Foundations of Computer Science*, pp. 439–448, 2013. doi: 10.1109/FOCS.2013.54.

Raghav Bhaskar, Abhishek Bhowmick, Vipul Goyal, Srivatsan Laxman, and Abhradeep Thakurta. Noiseless database privacy. In Dong Hoon Lee and Xiaoyun Wang (eds.), *Advances in Cryptology – ASIACRYPT 2011*, pp. 215–232, Berlin, Heidelberg, 2011. Springer Berlin Heidelberg. ISBN 978-3-642-25385-0.

Andrea Bittau, Úlfar Erlingsson, Petros Maniatis, Ilya Mironov, Ananth Raghunathan, David Lie, Mitch Rudominer, Ushasree Kode, Julien Tinnes, and Bernhard Seefeld. Prochlo: Strong privacy for analytics in the crowd. In *Proceedings of the 26th Symposium on Operating Systems Principles*, SOSP '17, pp. 441–459, New York, NY, USA, 2017a. Association for Computing Machinery. ISBN 9781450350853. doi: 10.1145/3132747.3132769. URL `https://doi.org/10.1145/3132747.3132769`.

Andrea Bittau, Úlfar Erlingsson, Petros Maniatis, Ilya Mironov, Ananth Raghunathan, David Lie, Mitch Rudominer, Ushasree Kode, Julien Tinnes, and Bernhard Seefeld. Prochlo: Strong privacy for analytics in the crowd. In *Proceedings of the 26th Symposium on Operating Systems Principles*, SOSP '17, pp. 441–459, New York, NY, USA, 2017b. ACM. ISBN 978-1-4503-5085-3. doi: 10.1145/3132747.3132769. URL `http://doi.acm.org/10.1145/3132747.3132769`.

Rui Chen, Benjamin C. Fung, Philip S. Yu, and Bipin C. Desai. Correlated network data publication via differential privacy. *The VLDB Journal*, 23(4):653–676, August 2014. ISSN 1066-8888. doi: 10.1007/s00778-013-0344-8. URL `https://doi.org/10.1007/s00778-013-0344-8`.

Albert Cheu, Adam Smith, Jonathan Ullman, David Zeber, and Maxim Zhilyaev. Distributed differential privacy via shuffling. In Yuval Ishai and Vincent Rijmen (eds.), *Advances in Cryptology – EUROCRYPT 2019*, pp. 375–403, Cham, 2019. Springer International Publishing. ISBN 978-3-030-17653-2.

Krzysztof M Choromanski, Tony Jebara, and Kui Tang. Adaptive anonymity via b-matching. *Advances in Neural Information Processing Systems*, 26:3192–3200, 2013.

Tore Dalenius. Towards a methodology for statistical disclosure control. *Statistik Tidskrift*, 15: 429–444, 1977.

Bolin Ding, Janardhan Kulkarni, and Sergey Yekhanin. Collecting telemetry data privately. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 30*, pp. 3571–3580. Curran Associates, Inc., 2017. URL http://papers.nips.cc/paper/6948-collecting-telemetry-data-privately.pdf.

Jean-Paul Doignon, Aleksandar Pekeč, and Michel Regenwetter. The repeated insertion model for rankings: Missing link between two subset choice models. *Psychometrika*, 69(1):33–54, March 2004. ISSN 1860-0980. doi: 10.1007/BF02295838. URL https://doi.org/10.1007/BF02295838.

Katerina Doka, Mingqiang Xue, Dimitrios Tsoumakos, and Panagiotis Karras. k-anonymization by freeform generalization. In *Proceedings of the 10th ACM Symposium on Information, Computer and Communications Security*, pp. 519–530, 2015.

Dheeru Dua and Casey Graff. UCI machine learning repository, 2017. URL http://archive.ics.uci.edu/ml.

Cynthia Dwork and Moni Naor. On the difficulties of disclosure prevention in statistical databases or the case for differential privacy. January 2010.

Cynthia Dwork and Aaron Roth. The algorithmic foundations of differential privacy. *Found. Trends Theor. Comput. Sci.*, pp. 211–407, August 2014. ISSN 1551-305X.

Cynthia Dwork, Frank McSherry, Kobbi Nissim, and Adam Smith. *Calibrating Noise to Sensitivity in Private Data Analysis*, volume 3876. March 2006. ISBN 978-3-540-32731-8. URL https://www.microsoft.com/en-us/research/publication/calibrating-noise-to-sensitivity-in-private-data-analysis/.

Gary Claxton Eric Lopez. Comparing private payer and medicare payment rates for select inpatient hospital services. *Kaiser Family Foundation*, Jul 2020.

Úlfar Erlingsson, Vasyl Pihur, and Aleksandra Korolova. Rappor: Randomized aggregatable privacy-preserving ordinal response. In *CCS*, 2014.

Úlfar Erlingsson, Vitaly Feldman, Ilya Mironov, Ananth Raghunathan, Kunal Talwar, and Abhradeep Thakurta. Amplification by shuffling: From local to central differential privacy via anonymity. In *Proceedings of the Thirtieth Annual ACM-SIAM Symposium on Discrete Algorithms*, SODA '19, pp. 2468–2479, USA, 2019. Society for Industrial and Applied Mathematics.

Alexandre Evfimievski, Johannes Gehrke, and Ramakrishnan Srikant. Limiting privacy breaches in privacy preserving data mining. In *Proceedings of the Twenty-second ACM SIGMOD-SIGACT-SIGART Symposium on Principles of Database Systems*, PODS '03, pp. 211–222, New York, NY, USA, 2003. ACM. ISBN 1-58113-670-6. doi: 10.1145/773153.773174. URL http://doi.acm.org/10.1145/773153.773174.

Giulia Fanti, Vasyl Pihur, and Úlfar Erlingsson. Building a rappor with the unknown: Privacy-preserving learning of associations and data dictionaries, 2015.

Vitaly Feldman, Audra McMillan, and Kunal Talwar. Hiding among the clones: A simple and nearly optimal analysis of privacy amplification by shuffling, 2020.

Jerome H Friedman. Greedy function approximation: a gradient boosting machine. *Annals of statistics*, pp. 1189–1232, 2001.

Johannes Gehrke, Edward Lui, and Rafael Pass. Towards privacy for social networks: A zero-knowledge based definition of privacy. In *Proceedings of the 8th Conference on Theory of Cryptography*, TCC'11, pp. 432–449, Berlin, Heidelberg, 2011. Springer-Verlag. ISBN 9783642195709.

Johannes Gehrke, Michael Hay, Edward Lui, and Rafael Pass. Crowd-blending privacy. In Reihaneh Safavi-Naini and Ran Canetti (eds.), *Advances in Cryptology – CRYPTO 2012*, pp. 479–496, Berlin, Heidelberg, 2012. Springer Berlin Heidelberg. ISBN 978-3-642-32009-5.

Joseph Geumlek and Kamalika Chaudhuri. Profile-based privacy for locally private computations. In *IEEE International Symposium on Information Theory, ISIT 2019, Paris, France, July 7-12, 2019*, pp. 537–541. IEEE, 2019. doi: 10.1109/ISIT.2019.8849549. URL https://doi.org/10.1109/ISIT.2019.8849549.

Arpita Ghosh and Robert Kleinberg. Inferential privacy guarantees for differentially private mechanisms. *CoRR*, abs/1603.01508, 2016. URL http://arxiv.org/abs/1603.01508.

Andy Greenberg. Apple's 'differential privacy' is about collecting your data—but not *your* data. *Wired*, Jun 13 2016.

Krzysztof Grining and Marek Klonowski. Towards extending noiseless privacy: Dependent data and more practical approach. In *Proceedings of the 2017 ACM on Asia Conference on Computer and Communications Security*, ASIA CCS '17, pp. 546–560, New York, NY, USA, 2017. Association for Computing Machinery. ISBN 9781450349444. doi: 10.1145/3052973.3052992. URL https://doi.org/10.1145/3052973.3052992.

Xi He, Ashwin Machanavajjhala, and Bolin Ding. Blowfish privacy: Tuning privacy-utility trade-offs using policies. In *Proceedings of the 2014 ACM SIGMOD International Conference on Management of Data*, SIGMOD '14, pp. 1447–1458, New York, NY, USA, 2014. Association for Computing Machinery. ISBN 9781450323765. doi: 10.1145/2588555.2588581. URL https://doi.org/10.1145/2588555.2588581.

S. Kasiviswanathan and A. Smith. On the 'semantics' of differential privacy: A bayesian formulation. *J. Priv. Confidentiality*, 6, 2014.

S. P. Kasiviswanathan, H. K. Lee, K. Nissim, S. Raskhodnikova, and A. Smith. What can we learn privately? In *2008 49th Annual IEEE Symposium on Foundations of Computer Science*, pp. 531–540, 2008. doi: 10.1109/FOCS.2008.27.

Yusuke Kawamoto and Takao Murakami. Differentially private obfuscation mechanisms for hiding probability distributions. *CoRR*, abs/1812.00939, 2018. URL http://arxiv.org/abs/1812.00939.

Daniel Kifer. Attacks on privacy and deFinetti's theorem. In *Proceedings of the 2009 ACM SIGMOD International Conference on Management of data*, SIGMOD '09, pp. 127–138, Providence, Rhode Island, USA, June 2009. Association for Computing Machinery. ISBN 978-1-60558-551-2. doi: 10.1145/1559845.1559861. URL https://doi.org/10.1145/1559845.1559861.

Daniel Kifer and Ashwin Machanavajjhala. No free lunch in data privacy. In *Proceedings of the 2011 ACM SIGMOD International Conference on Management of Data*, SIGMOD '11, pp. 193–204, New York, NY, USA, 2011. Association for Computing Machinery. ISBN 9781450306614. doi: 10.1145/1989323.1989345. URL https://doi.org/10.1145/1989323.1989345.

Daniel Kifer and Ashwin Machanavajjhala. Pufferfish: A framework for mathematical privacy definitions. *ACM Trans. Database Syst.*, 39(1), January 2014. ISSN 0362-5915. doi: 10.1145/2514689. URL https://doi.org/10.1145/2514689.

Rachel La Corte. Supreme court: State employee birthdates are public record. https://apnews.com/article/c1ff652f271947b2884dfe1216a11bc2/, 2019.

Katrina Ligett, Charlotte Peale, and Omer Reingold. Bounded-Leakage Differential Privacy. In Aaron Roth (ed.), *1st Symposium on Foundations of Responsible Computing (FORC 2020)*, volume 156 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pp. 10:1–10:20, Dagstuhl, Germany, 2020. Schloss Dagstuhl–Leibniz-Zentrum für Informatik. ISBN 978-3-95977-142-9. doi: 10.4230/LIPIcs.FORC.2020.10. URL https://drops.dagstuhl.de/opus/volltexte/2020/12026.

Changchang Liu, Supriyo Chakraborty, and Prateek Mittal. Dependence makes you vulnberable: Differential privacy under dependent tuples. In *NDSS*. The Internet Society, 2016. URL `http://dblp.uni-trier.de/db/conf/ndss/ndss2016.html#LiuMC16`.

Ashwin Machanavajjhala, Daniel Kifer, Johannes Gehrke, and Muthuramakrishnan Venkitasubramaniam. L-diversity: Privacy beyond k-anonymity. *ACM Transactions on Knowledge Discovery from Data*, 1(1):3–es, March 2007. ISSN 1556-4681. doi: 10.1145/1217299.1217302. URL `https://doi.org/10.1145/1217299.1217302`.

C. L. MALLOWS. NON-NULL RANKING MODELS. I. *Biometrika*, 44(1-2):114–130, 06 1957. ISSN 0006-3444. doi: 10.1093/biomet/44.1-2.114. URL `https://doi.org/10.1093/biomet/44.1-2.114`.

Alexandru Niculescu-Mizil and Rich Caruana. Predicting good probabilities with supervised learning. In *Proceedings of the 22nd international conference on Machine learning*, pp. 625–632, 2005.

Benedek Rozemberczki, Carl Allen, and Rik Sarkar. Multi-scale attributed node embedding. *arXiv preprint arXiv:1909.13021*, 2019. URL `http://snap.stanford.edu/data/twitch-social-networks.html`.

Shuang Song, Yizhen Wang, and Kamalika Chaudhuri. Pufferfish privacy mechanisms for correlated data. In *Proceedings of the 2017 ACM International Conference on Management of Data*, SIGMOD '17, pp. 1291–1306, New York, NY, USA, 2017. Association for Computing Machinery. ISBN 9781450341974. doi: 10.1145/3035918.3064025. URL `https://doi.org/10.1145/3035918.3064025`.

Latanya Sweeney. Achieving k-anonymity privacy protection using generalization and suppression. *International Journal of Uncertainty, Fuzziness and Knowledge-Based Systems*, 10(5):571–588, October 2002. ISSN 0218-4885. doi: 10.1142/S021848850200165X. URL `https://doi.org/10.1142/S021848850200165X`.

Tamir Tassa, Arnon Mazza, and Aristides Gionis. k-concealment: An alternative model of k-type anonymity. *Trans. Data Priv.*, 5(1):189–222, 2012.

M. C. Tschantz, S. Sen, and A. Datta. Sok: Differential privacy as a causal property. In *2020 IEEE Symposium on Security and Privacy (SP)*, pp. 354–371, 2020. doi: 10.1109/SP40000.2020.00012.

Stanley L Warner. Randomized response: A survey technique for eliminating evasive answer bias. *Journal of the American Statistical Association*, 60 60, no. 309:63–69, 1965.

Wai Kit Wong, Nikos Mamoulis, and David Wai Lok Cheung. Non-homogeneous generalization in privacy preserving data publishing. In *Proceedings of the 2010 ACM SIGMOD International Conference on Management of data*, pp. 747–758, 2010.

Xiaokui Xiao and Yufei Tao. Anatomy: Privacy and Correlation Preserving Publication. January 2006.

Mingqiang Xue, Panagiotis Karras, Chedy Raïssi, Jaideep Vaidya, and Kian-Lee Tan. Anonymizing set-valued data by nonreciprocal recoding. In *Proceedings of the 18th ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 1050–1058, 2012.

Bin Yang, Issei Sato, and Hiroshi Nakagawa. Bayesian differential privacy on correlated data. In *Proceedings of the 2015 ACM SIGMOD International Conference on Management of Data*, SIGMOD '15, pp. 747–762, New York, NY, USA, 2015. Association for Computing Machinery. ISBN 9781450327589. doi: 10.1145/2723372.2747643. URL `https://doi.org/10.1145/2723372.2747643`.

Wanrong Zhang, Olga Ohrimenko, and Rachel Cummings. Attribute privacy: Framework and mechanisms, 2020.

T. Zhu, P. Xiong, G. Li, and W. Zhou. Correlated differential privacy: Hiding information in non-iid data set. *IEEE Transactions on Information Forensics and Security*, 10(2):229–242, 2015. doi: 10.1109/TIFS.2014.2368363.

A APPENDIX

A.1 BACKGROUND CNTD.

A.2 LOCAL INFERENTIAL PRIVACY

Local inferential privacy captures what information a Bayesian adversary Kifer & Machanavajjhala (2014), with some prior, can learn in the LDP setting. Specifically, it measures the largest possible ratio between the adversary's posterior and prior beliefs about an individual's data after observing a mechanism's output .

Definition A.1. (Local Inferential Privacy Loss Kifer & Machanavajjhala (2014)) Let $\mathbf{x} = \langle x_1, \cdots, x_n \rangle$ and let $\mathbf{y} = \langle y_1, \cdots, y_n \rangle$ denote the input (private) and output sequences (observable to the adversary) in the LDP setting. Additionally, the adversary's auxiliary knowledge is modeled by a prior distribution $\mathcal{P}$ on $\mathbf{x}$. The inferential privacy loss for the input sequence $\mathbf{x}$ is given by

$$\mathbb{L}_{\mathcal{P}}(\mathbf{x}) = \max_{\substack{i \in [n] \\ a,b \in \mathcal{X}}} \left(\log \frac{\Pr_{\mathcal{P}}[\mathbf{y}|x_i = a]}{\Pr_{\mathcal{P}}[\mathbf{y}|x_i = b]} \right) = \max_{\substack{i \in [n] \\ a,b \in \mathcal{X}}} \left(\left| \log \frac{\Pr_{\mathcal{P}}[x_i = a|\mathbf{y}]}{\Pr_{\mathcal{P}}[x_i = b|\mathbf{y}]} - \log \frac{\Pr_{\mathcal{P}}[x_i = a]}{\Pr_{\mathcal{P}}[x_i = b]} \right| \right) \quad (4)$$

Bounding $\mathbb{L}_{\mathcal{P}}(\mathbf{x})$ would imply that the adversary's belief about the value of any x_i does not change by much even after observing the output sequence $\mathbf{y}$. This means that an informed adversary does not learn much about the individual i's private input upon observation of the entire private dataset $\mathbf{y}$.

Here we define two rank distance measures

Definition A.2 (Kendall's τ Distance). For any two permutations, $\sigma, \pi \in \mathrm{S}_n$, the Kendall's τ distance $\delta_\tau(\sigma, \pi)$ counts the number of pairwise disagreements between σ and π, i.e., the number of item pairs that have a relative order in one permutation and a different order in the other. Formally,

$$\delta_\tau(\sigma, \pi) = \Big| \big\{ (i,j) : i < j, \big[\sigma(i) > \sigma(j) \wedge \pi(i) < \pi(j) \big]$$

$$\vee \big[\sigma(i) < \sigma(j) \wedge \pi(i) > \pi(j) \big] \big\} \Big| \quad (5)$$

For example, if $\sigma = (1\ 2\ 3\ 4\ 5\ 6\ 7\ 8\ 9\ 10)$ and $\pi = (1\ 2\ 3\ \underline{6}\ 5\ \underline{4}\ 7\ 8\ 9\ 10)$, then $\delta_\tau(\sigma, \pi) = 3$.

Next, Hamming distance measure is defined as follows.

Definition A.3 (Hamming Distance). For any two permutations, $\sigma, \pi \in \mathrm{S}_n$, the Hamming distance $\delta_H(\sigma, \pi)$ counts the number of positions in which the two permutations disagree. Formally,

$$\delta_H(\sigma, \pi) = \Big| \big\{ i \in [n] : \sigma(i) \neq \pi(i) \big\} \Big|$$

Repeating the above example, if $\sigma = (1\ 2\ 3\ 4\ 5\ 6\ 7\ 8\ 9\ 10)$ and $\pi = (1\ 2\ 3\ \underline{6}\ 5\ \underline{4}\ 7\ 8\ 9\ 10)$, then $\delta_H(\sigma, \pi) = 2$.

A.3 d_σ-PRIVACY AND THE DE FINETTI ATTACK

We now show that a strict instance of d_σ privacy is sufficient for thwarting any de Finetti attack Kifer (2009) on individuals. The de Finetti attack involves a Bayesian adversary, who, assuming some degree of correlation between data owners, attempts to recover the true permutation from the shuffled data. As written, the de Finetti attack assumes the sequence of sensitive attributes and side information $(x_1, t_1), \ldots, (x_n, t_n)$ are *exchangeable*: any ordering of them is equally likely. By the de Finetti theorem, this implies that they are i.i.d. conditioned on some latent measure θ. To balance privacy with utility, the $\mathbf{x}$ sequence is non-uniformly randomly shuffled w.r.t. the $\mathbf{t}$ sequence producing a shuffled sequence $\mathbf{z}$, which the adversary observes. Conditioning on $\mathbf{z}$ the adversary updates their posterior on θ (i.e. posterior on a model predicting $x_i|t_i$), and thereby their posterior predictive on the true $\mathbf{x}$. The definition of privacy in Kifer (2009) holds that the adversary's posterior beliefs are close to their prior beliefs by some metric on distributions in $\mathcal{X}$, $\delta(\cdot, \cdot)$:

$$\delta\Big(\Pr[x_i], \Pr[x_i|\mathbf{z}] \Big) \leq \alpha$$

We now translate the de Finetti attack to our setting. First, to align notation with the rest of the paper we provide privacy to the sequence of LDP values $\mathbf{y}$ since we shuffle those instead of the $\mathbf{x}$ values as

in Kifer (2009). We use max divergence (multiplicative bound on events used in DP) for δ:
$$\Pr[y_i \in O] \leq e^\alpha \Pr[y_i \in O|\mathbf{z}]$$
$$\Pr[y_i \in O|\mathbf{z}] \leq e^\alpha \Pr[y_i \in O]$$
which, for compactness, we write as
$$\Pr[y_i \in O] \approx_\alpha \Pr[y_i \in O|\mathbf{z}] \quad . \tag{6}$$
We restrict ourselves to shuffling mechanisms, where we only randomize the order of sensitive values. By learning the unordered values $\{y\}$ alone, an adversary may have arbitrarily large updates to its posterior (e.g. if all values are identical), breaking the privacy requirement above. With this in mind, we assume the adversary already knows the unordered sequence of values $\{y\}$ (which they will learn anyway), and has a prior on permutations σ allocating values from that sequence to individuals. We then generalize the de Finetti problem to an adversary with an *arbitrary* prior on the true permutation σ, and observes a randomize permutation σ' from the shuffling mechanism. We require that the adversary's prior belief that $\sigma(i) = j$ is close to their posterior belief for all $i, j \in [n]$:
$$\Pr[\sigma \in \Sigma_{i,j}] \approx_\alpha \Pr[\sigma \in \Sigma_{i,j}|\sigma'] \quad \forall i, j \in [n], \forall \sigma' \in S_n \quad , \tag{7}$$
where $\Sigma_{i,j} = \{\sigma \in S_n : \sigma(i) = j\}$, the set of permutations assigning element j to DO_i. Conditioning on any unordered sequence $\{y\}$ with all unique values, the above condition is necessary to satisfy Eq. equation 6 for events of the form $O = \{y_i = a\}$, since $\{y_i = a\} = \{\Sigma_{i,j}\}$ for some $j \in [n]$. For any $\{y\}$ with repeat values, it is sufficient since $\Pr[y_i = a]$ is the sum of probabilities of disjoint events of the form $\Pr[\sigma \in \Sigma_{i,k}]$ for various $k \in [n]$ values.

We now show that a strict instance of d_σ-privacy satisfies Eq. equation 7. Let $\widehat{\mathcal{G}}$ be any group assignment such that at least one $G_i \in \widehat{\mathcal{G}}$ includes all data owners, $G_i = \{1, 2, \ldots, n\}$.

Property 1. *A $(\widehat{\mathcal{G}}, \alpha)$-$d_\sigma$-private shuffling mechanism $\sigma' \sim \mathcal{A}$ satisfies*
$$\Pr[\sigma \in \Sigma_{i,j}] \approx_\alpha \Pr[\sigma \in \Sigma_{i,j}|\sigma']$$
for all $i, j \in [n]$ and all priors on permutations $\Pr[\sigma]$.

Proof.

Lemma 1. *For any prior $\Pr[\sigma]$, Eq. equation 7 is equivalent to the condition*
$$\frac{\sum_{\hat{\sigma} \in \overline{\Sigma}_{i,j}} \Pr[\hat{\sigma}] \Pr[\sigma'|\hat{\sigma}]}{\sum_{\hat{\sigma} \in \Sigma_{i,j}} \Pr[\hat{\sigma}] \Pr[\sigma'|\hat{\sigma}]} \approx_\alpha \frac{\sum_{\hat{\sigma} \in \overline{\Sigma}_{i,j}} \Pr[\hat{\sigma}]}{\sum_{\hat{\sigma} \in \Sigma_{i,j}} \Pr[\hat{\sigma}]} \tag{8}$$
where the set $\overline{\Sigma}_{i,j}$ is the complement of $\Sigma_{i,j}$.

Under grouping $\hat{\mathcal{G}}$, every permutation $\sigma_a \in \Sigma_{i,j}$ neighbors every permutation $\sigma_b \in \overline{\Sigma}_{i,j}$, $\sigma_a \approx_{\hat{\mathcal{G}}} \sigma_b$, for any i, j. By the definition of d_σ-privacy, we have that for any observed permutation σ' output by the mechanism:
$$\Pr[\sigma'|\sigma = \sigma_a] \approx_\alpha \Pr[\sigma'|\sigma = \sigma_b] \quad \forall \sigma_a \in \Sigma_{i,j}, \sigma_b \in \overline{\Sigma}_{i,j}, \sigma' \in S_n \quad .$$
This implies Eq. 8. Thus, $(\widehat{\mathcal{G}}, \alpha)$-$d_\sigma$-privacy implies Eq. 8, which implies Eq. 7, thus proving the property. $\qquad\square$

Using Lemma 1, we may also show that this strict instance of d_σ-privacy is *necessary* to block all de Finetti attacks:

Property 2. *A $(\widehat{\mathcal{G}}, \alpha)$-$d_\sigma$-private shuffling mechanism $\sigma' \sim \mathcal{A}$ is necessary to satisfy*
$$\Pr[\sigma \in \Sigma_{i,j}] \approx_\alpha \Pr[\sigma \in \Sigma_{i,j}|\sigma']$$
for all $i, j \in [n]$ and all priors on permutations $\Pr[\sigma]$.

Proof. If our mechanism $\mathcal{A}$ is not $(\widehat{\mathcal{G}}, \alpha)$-$d_\sigma$-private, then for some pair of true (input) permutations $\sigma_a \neq \sigma_b$ and some released permutation $\sigma' \sim \mathcal{A}$, we have that
$$\Pr[\sigma'|\sigma_b] \geq e^\alpha \Pr[\sigma'|\sigma_a] \quad .$$
Under $\hat{\mathcal{G}}$, all permutations neighbor each other, so $\sigma_a \approx_{\hat{\mathcal{G}}} \sigma_b$. Since $\sigma_a \neq \sigma_b$, then for some $i, j \in [n]$, $\sigma_a \in \Sigma_{i,j}$ and $\sigma_b \in \overline{\Sigma}_{i,j}$: one of the two permutations assigns some j to some DO_i and the other does not. Given this, we may construct a bimodal prior on the true σ that assigns half its probability mass to σ_a and the rest to σ_b,
$$\Pr[\sigma_a] = \Pr[\sigma_b] = \frac{1}{2} \quad .$$

Therefore, for released permutation σ', the RHS of Eq. 8 is 1, and the LHS is

$$\frac{\sum_{\hat{\sigma} \in \overline{\Sigma}_{i,j}} \Pr[\hat{\sigma}] \Pr[\sigma'|\hat{\sigma}]}{\sum_{\hat{\sigma} \in \Sigma_{i,j}} \Pr[\hat{\sigma}] \Pr[\sigma'|\hat{\sigma}]} = \frac{1/2 \Pr[\sigma'|\sigma_b]}{1/2 \Pr[\sigma'|\sigma_a]}$$

$$\geq e^{\alpha} \quad ,$$

violating Eq. 8, thus violating Eq. 7, and failing to prevent de Finetti attacks against this bimodal prior. $\qquad\square$

Ultimately, unless we satisfy d_σ-privacy shuffling the entire dataset, there exists some prior on the true permutation $\Pr[\sigma]$ such that after observing the shuffled $\mathbf{z}$ permuted by σ', the adversary's posterior belief on one permutation is larger than their prior belief by a factor $\geq e^{\alpha}$. If we suppose that the set of values $\{y\}$ are all distinct, this means that for some $a \in \{y\}$, the adversary's belief that $y_i = a$ is signficantly larger after observing $\mathbf{z}$ than it was before.

Now to prove Lemma 1:

Proof.

$$\Pr[\sigma \in \Sigma_{i,j}] \approx_{\alpha} \Pr[\sigma \in \Sigma_{i,j}|\sigma']$$

$$\Pr[\sigma \in \Sigma_{i,j}] \approx_{\alpha} \frac{\Pr[\sigma'|\sigma \in \Sigma_{i,j}] \Pr[\sigma \in \Sigma_{i,j}]}{\sum_{\hat{\sigma} \in S_n} \Pr[\hat{\sigma}] \Pr[\sigma'|\hat{\sigma}]}$$

$$\sum_{\hat{\sigma} \in S_n} \Pr[\hat{\sigma}] \Pr[\sigma'|\hat{\sigma}] \approx_{\alpha} \Pr[\sigma'|\sigma \in \Sigma_{i,j}]$$

$$\sum_{\hat{\sigma} \in S_n} \Pr[\hat{\sigma}] \Pr[\sigma'|\hat{\sigma}] \approx_{\alpha} \Pr[\sigma \in \Sigma_{i,j}]^{-1} \sum_{\hat{\sigma} \in \Sigma_{i,j}} \Pr[\hat{\sigma}] \Pr[\sigma'|\hat{\sigma}]$$

$$\sum_{\hat{\sigma} \in \Sigma_{i,j}} \Pr[\hat{\sigma}] \Pr[\sigma'|\hat{\sigma}] + \sum_{\hat{\sigma} \in \overline{\Sigma}_{i,j}} \Pr[\hat{\sigma}] \Pr[\sigma'|\hat{\sigma}] \approx_{\alpha} \Pr[\sigma \in \Sigma_{i,j}]^{-1} \sum_{\hat{\sigma} \in \Sigma_{i,j}} \Pr[\hat{\sigma}] \Pr[\sigma'|\hat{\sigma}]$$

$$\sum_{\hat{\sigma} \in \overline{\Sigma}_{i,j}} \Pr[\hat{\sigma}] \Pr[\sigma'|\hat{\sigma}] \approx_{\alpha} \sum_{\hat{\sigma} \in \Sigma_{i,j}} \Pr[\hat{\sigma}] \Pr[\sigma'|\hat{\sigma}]\Big(\frac{1}{\Pr[\sigma \in \Sigma_{i,j}]} - 1\Big)$$

$$\frac{\sum_{\hat{\sigma} \in \overline{\Sigma}_{i,j}} \Pr[\hat{\sigma}] \Pr[\sigma'|\hat{\sigma}]}{\sum_{\hat{\sigma} \in \Sigma_{i,j}} \Pr[\hat{\sigma}] \Pr[\sigma'|\hat{\sigma}]} \approx_{\alpha} \frac{\sum_{\hat{\sigma} \in \overline{\Sigma}_{i,j}} \Pr[\hat{\sigma}]}{\sum_{\hat{\sigma} \in \Sigma_{i,j}} \Pr[\hat{\sigma}]}$$

$\qquad\square$

As such, a strict instance of d_σ-privacy can defend against any de Finetti attack (i.e. for any prior $\Pr[\sigma]$ on permutations), wherein at least one group $G_i \in \mathcal{G}$ includes all data owners. Furthermore, it is necessary. This makes sense. In order to defend against any prior, we need to significantly shuffle the entire dataset. Without a restriction of priors as in Pufferfish Kifer & Machanavajjhala (2014), the de Finetti attack (i.e. uninformed Bayesian adversaries) is an indelicate metric for evaluating the privacy of shuffling mechanisms: to achieve significant privacy, we must sacrifice all utility. This in many regards is reminiscent of the no free lunch for privacy theorem established in Kifer & Machanavajjhala (2011). As such, there is a need for more flexible privacy definitions for shuffling mechanisms.

A.4 ADDITIONAL PROPERTIES OF d_σ-PRIVACY

Lemma 2 (Convexity). *Let $\mathcal{A}_1, \ldots \mathcal{A}_k : \mathcal{Y}^n \mapsto \mathcal{V}$ be a collection of k $(\alpha, \mathcal{G})$-$d_\sigma$private mechanisms for a given group assignment $\mathcal{G}$ on a set of n entities. Let $\mathcal{A} : \mathcal{Y}^n \mapsto \mathcal{V}$ be a convex combination of these k mechanisms, where the probability of releasing the output of mechanism $\mathcal{A}_i$ is p_i, and $\sum_{i=1}^{k} p_i = 1$. $\mathcal{A}$ is also $(\alpha, \mathcal{G})$-$d_\sigma$private w.r.t. $\mathcal{G}$.*

Proof. For any $(\sigma, \sigma') \in \mathrm{N}_{\mathcal{G}}$ and $\mathbf{y} \in \mathcal{Y}$:

$$\Pr[\mathcal{A}(\sigma(\mathbf{y})) \in O] = \sum_{i=1}^{k} p_i \Pr[\mathcal{A}_i(\sigma(\mathbf{y})) \in O]$$

$$\leq e^{\alpha} \sum_{i=1}^{k} p_i \Pr[\mathcal{A}_i(\sigma'(\mathbf{y})) \in O]$$

$$= \Pr[\mathcal{A}(\sigma'(\mathbf{y})) \in O]$$

$\square$

Theorem A.1 (Post-processing). *Let $\mathcal{A} : \mathcal{Y}^n \mapsto \mathcal{V}$ be $(\alpha, \mathcal{G})$-$d_\sigma$private for a given group assignment $\mathcal{G}$ on a set of n entities. Let $f : \mathcal{V} \mapsto \mathcal{V}'$ be an arbitrary randomized mapping. Then $f \circ \mathcal{A} : \mathcal{Y}^n \mapsto \mathcal{V}'$ is also $(\alpha, \mathcal{G})$-$d_\sigma$private.*

Proof. Let $g : \mathcal{V} \to \mathcal{V}'$ be a deterministic, measurable function. For any output event $\mathcal{Z} \subset \mathcal{V}'$, let $\mathcal{W}$ be its preimage:
$\mathcal{W} = \{v \in \mathcal{V} | g(v) \in \mathcal{Z}\}$. Then, for any $(\sigma, \sigma') \in \mathrm{N}_{\mathcal{G}}$,

$$\Pr\Big[g\Big(\mathcal{A}(\sigma(\mathbf{y}))\Big) \in \mathcal{Z}\Big] = \Pr\Big[\mathcal{A}(\sigma(\mathbf{y})) \in \mathcal{W}\Big]$$

$$\leq e^{\alpha} \cdot \Pr\Big[\mathcal{A}(\sigma'(\mathbf{y})) \in \mathcal{W}\Big]$$

$$= e^{\alpha} \cdot \Pr\Big[g\Big(\mathcal{A}(\sigma'(\mathbf{y}))\Big) \in \mathcal{Z}\Big]$$

This concludes our proof because any randomized mapping can be decomposed into a convex combination of measurable, deterministic functions Dwork & Roth (2014), and as Lemma 2 shows, a convex combination of $(\alpha, \mathcal{G})$-$d_\sigma$private mechanisms is also $(\alpha, \mathcal{G})$-$d_\sigma$private. $\square$

Theorem A.2 (Sequential Composition). *If $\mathcal{A}_1$ and $\mathcal{A}_2$ are $(\alpha_1, \mathcal{G})$- and $(\alpha_2, \mathcal{G})$-$d_\sigma$private mechanisms, respectively, that use independent randomness, then releasing the outputs $(\mathcal{A}_1(\mathbf{y}), \mathcal{A}_2(\mathbf{y}))$ satisfies $(\alpha_1 + \alpha_2, \mathcal{G})$-$d_\sigma$privacy.*

Proof. We have that $\mathcal{A}_1 : \mathcal{Y}^n \to \mathcal{V}'$ and $\mathcal{A}_1 : \mathcal{Y}^n \to \mathcal{V}''$ each satisfy d_σ-privacy for different α values. Let $\mathcal{A} : \mathcal{Y}^n \to (\mathcal{V}' \times \mathcal{V}'')$ output $(\mathcal{A}_1(\mathbf{y}), \mathcal{A}_2(\mathbf{y}))$. Then, we may write any event $\mathcal{Z} \in (\mathcal{V}' \times \mathcal{V}'')$ as $\mathcal{Z}' \times \mathcal{Z}''$, where $\mathcal{Z}' \in \mathcal{V}'$ and $\mathcal{Z}'' \in \mathcal{V}''$. We have for any $(\sigma, \sigma') \in \mathrm{N}_{\mathcal{G}}$,

$$\Pr[\mathcal{A}(\sigma(\mathbf{y})) \in \mathcal{Z}] = \Pr[(\mathcal{A}_1(\sigma(\mathbf{y})), \mathcal{A}_2(\sigma(\mathbf{y}))) \in \mathcal{Z}]$$

$$= \Pr[\{\mathcal{A}_1(\sigma(\mathbf{y})) \in \mathcal{Z}'\} \cap \{\mathcal{A}_2(\sigma(\mathbf{y})) \in \mathcal{Z}''\}]$$

$$= \Pr[\{\mathcal{A}_1(\sigma(\mathbf{y})) \in \mathcal{Z}'\}] \Pr[\{\mathcal{A}_2(\sigma(\mathbf{y})) \in \mathcal{Z}''\}]$$

$$\leq e^{\alpha_1 + \alpha_2} \Pr[\{\mathcal{A}_1(\sigma'(\mathbf{y})) \in \mathcal{Z}'\}] \Pr[\{\mathcal{A}_2(\sigma'(\mathbf{y})) \in \mathcal{Z}''\}]$$

$$= e^{\alpha_1 + \alpha_2} \cdot \Pr[\mathcal{A}(\sigma'(\mathbf{y})) \in \mathcal{Z}]$$

$\square$

A.5   PROOF FOR THM. 4.1

Theorem 4.1 *For a given group assignment $\mathcal{G}$ on a set of n data owners, if a shuffling mechanism $\mathcal{A} : \mathcal{Y}^n \mapsto \mathcal{Y}^n$ is $(\alpha, \mathcal{G})$-$d_\sigma$private, then for each data owner $DO_i, i \in [n]$,*

$$\max_{\substack{i \in [n] \\ a, b \in \mathcal{X}}} \left| \log \frac{\Pr_{\mathcal{P}}[x_i = a | \mathbf{z}, \{y_{G_i}\}, \mathbf{y}_{\overline{G}_i}]}{\Pr_{\mathcal{P}}[x_i = b | \mathbf{z}, \{y_{G_i}\}, \mathbf{y}_{\overline{G}_i}]} - \log \frac{\Pr_{\mathcal{P}}[x_i = a | \{y_{G_i}\}, \mathbf{y}_{\overline{G}_i}]}{\Pr_{\mathcal{P}}[x_i = b | \{y_{G_i}\}, \mathbf{y}_{\overline{G}_i}]} \right| \leq \alpha$$

for a prior distribution $\mathcal{P}$, where $\mathbf{z} = \mathcal{A}(\mathbf{y})$ and $\mathbf{y}_{\overline{G}_i}$ is the noisy sequence for data owners outside G_i.

Proof. We prove the above by bounding the following equivalent expression for any $i \in [n]$ and $a, b \in \mathcal{X}$.

$$\frac{\Pr_{\mathcal{P}}[\mathbf{z}|x_i = a, \{y_{G_i}\}, \mathbf{y}_{\overline{G}_i}]}{\Pr_{\mathcal{P}}[\mathbf{z}|x_i = b, \{y_{G_i}\}, \mathbf{y}_{\overline{G}_i}]}$$

$$= \frac{\int \Pr_{\mathcal{P}}[\mathbf{y}|x_i = a, \{y_{G_i}\}, \mathbf{y}_{\overline{G}_i}] \Pr_{\mathcal{A}}[\mathbf{z}|\mathbf{y}] d\mathbf{y}}{\int \Pr_{\mathcal{P}}[\mathbf{y}|x_i = b, \{y_{G_i}\}, \mathbf{y}_{\overline{G}_i}] \Pr_{\mathcal{A}}[\mathbf{z}|\mathbf{y}] d\mathbf{y}}$$

$$= \frac{\sum_{\sigma \in S_r} \Pr_{\mathcal{P}}[\sigma(\mathbf{y}_{G_i}^*)|x_i = a, \mathbf{y}_{\overline{G}_i}] \Pr_{\mathcal{A}}[\mathbf{z}|\sigma(\mathbf{y}_{G_i}^*), \mathbf{y}_{\overline{G}_i}]}{\sum_{\sigma \in S_r} \Pr_{\mathcal{P}}[\sigma(\mathbf{y}_{G_i}^*)|x_i = b, \mathbf{y}_{\overline{G}_i}] \Pr_{\mathcal{A}}[\mathbf{z}|\sigma(\mathbf{y}_{G_i}^*), \mathbf{y}_{\overline{G}_i}]}$$

$$\leq \max_{\{\sigma, \sigma' \in S_r\}} \frac{\Pr_{\mathcal{A}}[\mathbf{z}|\sigma(\mathbf{y}_{G_i}^*), \mathbf{y}_{\overline{G}_i}]}{\Pr_{\mathcal{A}}[\mathbf{z}|\sigma'(\mathbf{y}_{G_i}^*), \mathbf{y}_{\overline{G}_i}]}$$

$$\leq \max_{\{\sigma, \sigma' \in N_{G_i}\}} \frac{\Pr_{\mathcal{A}}[\mathbf{z}|\sigma(\mathbf{y})]}{\Pr_{\mathcal{A}}[\mathbf{z}|\sigma'(\mathbf{y})]}$$

$$\leq e^\alpha$$

The second line simply marginalizes out the full noisy sequence $\mathbf{y}$. The third line reduces this to a sum over permutations of of $\mathbf{y}_{G_i}$, where $r = |G_i|$ and $\mathbf{y}_{G_i}^*$ is any fixed permutation of values $\{y_{G_i}\}$. This is possible since we are given the values outside the group, $\mathbf{y}_{\overline{G}_i}$, and the unordered set of values inside the group, $\{y_{G_i}\}$. Note that the permutations σ written here are possible permutations of the LDP input, not permutations output by the mechanism applied to the input as sometimes written in other parts of this document.

The fourth line uses the fact that the numerator and denominator are both convex combinations of $\Pr_{\mathcal{A}}[\mathbf{z}|\sigma(\mathbf{y}_{G_i}^*), \mathbf{y}_{\overline{G}_i}]$ over all $\sigma \in S_r$.

The fifth line uses the fact that for any $\mathbf{y}_{\overline{G}_i}$,

$$(\sigma(\mathbf{y}_{G_i}^*), \mathbf{y}_{\overline{G}_i}) \approx_{G_i} (\sigma'(\mathbf{y}_{G_i}^*), \mathbf{y}_{\overline{G}_i}) \,.$$

This allows a further upper bound over all neighboring sequences w.r.t. G_i, and thus over any permutation of $\mathbf{y}_{\overline{G}_i}$, as long as it is the same in the numerator and denominator. $\square$

Discussion The above Bayesian analysis measures what can be learned about DO_i's x_i from observing the private release $\mathbf{z}$ relative to some other known information (the conditioned information). Under d_σ-privacy, we condition on the bag of LDP values in Alice's group $\{y_{G_i}\}$ as well as the sequence (order and value) of LDP values outside her group $\mathbf{y}_{\overline{G}_i}$. This implies that releasing the shuffled sequence $\mathbf{z}$ cannot provide much more information about Alice's x_i than would releasing the LDP values outside her neighborhood (her group) and the unordered bag of LDP values inside her neighborhood, regardless of the adversary's prior knowledge $\mathcal{P}$. This is a communicable guarantee: if Alice feels comfortable with the data collection knowing that her entire neighborhood's responses will be uniformly shuffled together (including those of her household), then she ought to be comfortable with d_σ-privacy. Now, we have to provide this guarantee to Bob, a neighbor of Alice, as well as Luis, a neighbor of Bob but *not* of Alice. Thus, Bob, Alice and Luis have *distinct* and *overlapping* groups (neighborhoods). Hence, the trivial solution of uniformly shuffling the noisy responses of every group separately does not work in this case. d_σ-privacy, however, offers the above guarantee to each user (knowing that their entire neighborhood is *nearly* uniformly shuffled) while still maintaining utility (estimate disease prevalence within neighborhoods). Semantically, this is very powerful, since it implies that the noisy responses specific to one's household cannot be leveraged to infer one's disease state x_i.

A.6 PROOF OF THEOREM 4.2

Theorem 4.2

For $\mathcal{A}(\mathcal{M}(\mathbf{x})) = \mathbf{z}$ where $\mathcal{M}(\cdot)$ is ϵ-LDP and $\mathcal{A}(\cdot)$ is α - d_σ private, we have

$$\Pr[\mathcal{D}_{Adv} \text{ loses}] \geq \lfloor \frac{r - k}{k} \rfloor e^{-(2k\epsilon + \alpha)} \cdot \Pr[\mathcal{D}_{Adv} \text{ wins}]$$

for any input subgroup $I \subset G_i, r = |G_i|$ and $k < r/2$.

Proof. We first focus on deterministic adversaries and then expand to randomized adversaries afterwards using the fact that randomized adversaries are mixtures of deterministic ones.

Our adversary $\mathcal{D}_{Adv}$ is then defined by a deterministic decision function $\eta : \mathcal{Y}^n \to [n]^k$. Upon observing $\mathbf{z}$, $\eta(\mathbf{z})$ selects k elements in $\mathbf{z}$ which it believes originated from $I \subset G_i$.

In the following, let $\Pr_{\mathbf{z}}$ be the probability of events conditioned on the shuffled output sequence $\mathbf{z}$, where randomness is over the ϵ-LDP mechanism $\mathcal{M}$ and the α-d_σ-private shuffling mechanism $\mathcal{A}$. [5]

The adversary wins if it reidentifies $> \frac{k}{2}$ of the LDP values originating from I. Let $H = \eta(\mathbf{z})$ be the indices of elements in $\mathbf{z}$ selected by η. Let $W = \{\sigma \in S^n : |\sigma(H) \cap I| > \frac{k}{2}\}$ be the set of permutations where the adversary wins and let $L = \{\sigma \in S^n : \sigma(H) \cap I| \leq \frac{k}{2}\}$ be the set of permutations where the adversary loses.

$$\Pr_{\mathbf{z}}[\eta(\mathbf{z}) \text{ wins}] = \Pr_{\mathbf{z}}[\sigma \in W]$$

$$\Pr_{\mathbf{z}}[\eta(\mathbf{z}) \text{ loses}] = \Pr_{\mathbf{z}}[\sigma \in L]$$

where σ is the shuffling permutation produced by $\mathcal{A}$, $\mathbf{z} = \sigma(\mathbf{y})$ i.e. $z_i = y_{\sigma(i)}$. Concretely, this is equivalent to DO_i releasing $\mathsf{DO}_{\sigma(i)}$'s LDP response. Since the permutation and LDP outputs are randomized, many subgroups of size k in G_i could have produced the LDP values $(z_{H_1}, \ldots, z_{H_k})$ and then been mapped to H by a permutation. Concretely, there is a reasonable probability that Alice's household output the LDP values of another k-member household in her neighborhood and they output her household's LDP values. In the worst case, this is $e^{-2k\epsilon}$ less likely than without swapping values, by group DP guarantees. Since both households are part of the same group G_i, the permutation that maps her household to elements H in the output is close in probability to that which maps the other household to elements H in the output. As such, we have in the worst case a $e^{-(2k\epsilon+\alpha)}$ reduction in probability of the other household having swapped LDP values with Alice's and permuting to subset H.

The above provides intuition on how we could get the same output $\mathbf{z}$ many different ways, and how Alice's household could or could not contribute to elements H. It does not, however, explain why an adversary who is given output $\mathbf{z}$ has limited advantage in choosing a subset H such that they recover *most* of Alice's household's values. We formalize this fact as follows.

We may rewrite the probabilities of winning or losing by marginalizing out all possible LDP sequences $\mathbf{y}$. Conditioning on the output sequence $\mathbf{z}$, the only possible LDP sequences $\mathbf{y}$ are permutations of $\mathbf{z}$. Note that the probability of any sequence $\mathbf{y}$ is determined by the input $\mathbf{x}$ and the LDP mechanism $\mathcal{M}$:

$$\Pr_{\mathbf{z}}[\eta(\mathbf{z}) \text{ loses}] = \Pr_{\mathbf{z}}[\sigma \in W]$$

$$= \sum_{\sigma \in W} \Pr[\mathcal{A}(\mathbf{x}) = \mathbf{y} = \sigma^{-1}(\mathbf{z})] \Pr[\sigma|\mathbf{y}] / \Pr[\mathbf{z}]$$

Note that $\Pr_{\mathbf{z}}[\sigma|\mathbf{y}] = \Pr_{\mathbf{z}}[\sigma]$ for the mallows mechanism, which chooses its permutations independently of $\mathbf{y}$. Now consider when $\eta(\mathbf{z})$ loses. By similar arguments as above:

$$\Pr_{\mathbf{z}}[\eta(\mathbf{z}) \text{ loses}] = \Pr_{\mathbf{z}}[\sigma \in L]$$

$$= \sum_{\sigma \in L} \Pr[\mathcal{A}(\mathbf{x}) = \mathbf{y} = \sigma^{-1}(\mathbf{z})] \Pr[\sigma|\mathbf{y}] / \Pr[\mathbf{z}]$$

The odds of losing versus winning is given by

$$\frac{\Pr_{\mathbf{z}}[\eta(\mathbf{z}) \text{ loses}]}{\Pr_{\mathbf{z}}[\eta(\mathbf{z}) \text{ wins}]} = \frac{\sum_{\sigma' \in L} \Pr\left[\mathcal{A}(\mathbf{x}) = \mathbf{y} = \sigma'^{-1}(\mathbf{z})\right] \Pr[\sigma'|\mathbf{y}]}{\sum_{\sigma \in W} \Pr[\mathcal{A}(\mathbf{x}) = \mathbf{y} = \sigma^{-1}(\mathbf{z})] \Pr[\sigma|\mathbf{y}]}$$

We now show that for each σ in the denominator, we may construct $m = \lfloor \frac{r-k}{k} \rfloor$ distinct permutations σ' in the numerator that are close in probability to it.

Lemma 3. *For every $\sigma \in W$ there exists a set of $m = \lfloor \frac{r-k}{k} \rfloor$ permutations, $E(\sigma)$, such that*

---

[5]As an abuse of notation, we assume the output space of the LDP randomizers, $\mathcal{Y}$, have outcomes with non-zero measure e.g. randomized response. The following analysis can be expanded to continuous outputs (with outcomes of zero measure) by simply replacing the output sequence $\mathbf{z} \in \mathcal{Y}^n$ with an output event $\mathbf{Z} \subseteq \mathcal{Y}^n$.

1. $E(\sigma) \subseteq L$

2. $\sigma^{-1} \approx_{G_i} \sigma'^{-1}$

3. $E(\sigma_a) \cap E(\sigma_b) = \emptyset$ *for any pair* $\sigma_a, \sigma_b \in W$

4. $\Pr\left[\mathcal{A}(\mathbf{x}) = \mathbf{y} = \sigma^{-1}(\mathbf{z})\right] \leq e^{2k\epsilon} \Pr\left[\mathcal{A}(\mathbf{x}) = \mathbf{y} = \sigma'^{-1}(\mathbf{z})\right]$ *for any* $\mathbf{x} \in \mathcal{X}^n$ *and any* $\mathbf{z} \in \mathcal{Y}^n$

Proof. Given $\sigma \in W$, we construct $E(\sigma)$ by first taking the inverse σ^{-1}. Recall that, since $\sigma \in W$, we have that $|\sigma^{-1}(I) \cap H| > \frac{k}{2}$. ($\sigma^{-1}(i) = j$ could be interpreted as data owner i's LDP value will be output at position j). We then divide the remainder of the group $G_i \backslash I$ into m disjoint subsets of size k each, $J_1, J_2, \ldots, J_m$. These represent the other distinct subsets of size k that Alice's household could swap LDP values with. We then produce m permutations, $\sigma_1'^{-1}, \ldots, \sigma_m'^{-1}$, by making $\sigma_i'^{-1}(I) = \sigma^{-1}(J_i)$ and $\sigma_i'^{-1}(J_i) = \sigma^{-1}(I)$ (preserving order within those subsets) and $\sigma'^{-1} = \sigma^{-1}$ everywhere else.

On the first point, we know that every $\sigma' \in E(\sigma)$ is also in L. We know this because $\sigma_i'^{-1}(I) = \sigma^{-1}(J_i)$. Since $\sigma \in W$, we have that $|\sigma^{-1}(J_i) \cap H| < \frac{k}{2}$ since $|\sigma^{-1}(I) \cap H| \geq \frac{k}{2}$ and $I \cap J_i = \emptyset$ by definition. Thus, $|\sigma_i'^{-1}(I) \cap H| < \frac{k}{2}$, so $|\sigma_i'(H) \cap I| < \frac{k}{2}$ and $\sigma_i' \in L$.

On the second point, we know that the inverse permutations are neighboring $\sigma^{-1} \approx_{G_i} \sigma'^{-1}$ simply by construction – they only differ on elements in G_i.

On the third point, we know that the sets $E(\sigma_a)$ and $E(\sigma_b)$ are distinct since we can map any permutation $\sigma' \in E(\sigma_a)$ uniquely back to σ_a for any $\sigma_a \in W$. We do so by taking its inverse σ'^{-1}, finding which subset J_i has majority elements from H i.e. $|\sigma'^{-1}(J_i) \cap H| > \frac{k}{2}$. Swap elements back: $\sigma'^{-1}(J_i)$ with $\sigma'^{-1}(I)$. Invert back to σ_a.

On the fourth point, we know that $\sigma^{-1}(\mathbf{z})$ and $\sigma'^{-1}(\mathbf{z})$ differ on at most $2k$ indices. As such, by group DP guarantees, we know that their probabilities must be close to a factor of $e^{-2k\epsilon}$ regardless of $\mathbf{z}$ and $\mathbf{x}$. $\qquad\square$

Using the above Lemma we may bound the odds of losing vs. winning.

$$\frac{\Pr_{\mathbf{z}}[\eta(\mathbf{z}) \text{ loses}]}{\Pr_{\mathbf{z}}[\eta(\mathbf{z}) \text{ wins}]} = \frac{\sum_{\sigma' \in L} \Pr\left[\mathcal{A}(\mathbf{x}) = \mathbf{y} = \sigma'^{-1}(\mathbf{z})\right] \Pr[\sigma'|\mathbf{y}]}{\sum_{\sigma \in W} \Pr[\mathcal{A}(\mathbf{x}) = \mathbf{y} = \sigma^{-1}(\mathbf{z})] \Pr[\sigma|\mathbf{y}]}$$

$$\geq \frac{\sum_{\sigma \in W} \sum_{\sigma' \in E(\sigma)} \Pr\left[\mathcal{A}(\mathbf{x}) = \mathbf{y} = \sigma'^{-1}(\mathbf{z})\right] \Pr[\sigma'|\mathbf{y}]}{\sum_{\sigma \in W} \Pr[\mathcal{A}(\mathbf{x}) = \mathbf{y} = \sigma^{-1}(\mathbf{z})] \Pr[\sigma|\mathbf{y}]}$$

$$\geq \min_{\sigma \in W} \frac{\sum_{\sigma' \in E(\sigma)} \Pr\left[\mathcal{A}(\mathbf{x}) = \mathbf{y} = \sigma'^{-1}(\mathbf{z})\right] \Pr[\sigma'|\mathbf{y}]}{\Pr[\mathcal{A}(\mathbf{x}) = \mathbf{y} = \sigma^{-1}(\mathbf{z})] \Pr[\sigma|\mathbf{y}]}$$

$$\geq \lfloor \frac{r-k}{k} \rfloor e^{-(2k\epsilon+\alpha)}$$

where the last line follows from the fourth point of the above Lemma (for the $2k\epsilon$ term) and the fact that the inverse permutations $\sigma'^{-1}, \sigma^{-1}$ are neighboring (second point of the Lemma) so the probabilities of the mechanism to produce σ vs. σ' to reach $\mathbf{z}$ from these neighboring permutations must be close by a factor of e^α.

Since the above holds for any $\mathbf{z}$ and $\mathbf{x}$, the bound holds on average across all outcomes $\mathbf{z}$, thus

$$\Pr[\eta \text{ loses}] \geq \lfloor \frac{r-k}{k} \rfloor e^{-(2k\epsilon+\alpha)} \cdot \Pr[\eta \text{ wins}]$$

for any deterministic adversary with decision function η. Finally, we may write any probabilistic adversary as mixture of decision functions. By convexity (same argument used in Lemma 2), the above bound still holds. As such,

$$\Pr[\mathcal{D}_{Adv} \text{ loses}] \geq \lfloor \frac{r-k}{k} \rfloor e^{-(2k\epsilon+\alpha)} \cdot \Pr[\mathcal{D}_{Adv} \text{ wins}]$$

$\square$

A.7 Utility of Shuffling Mechanism

We now introduce a novel metric, (η, δ)-preservation, for assessing the utility of any shuffling mechanism. Let $S \subseteq [n]$ correspond to a set of indices in $\mathbf{y}$. The metric is defined as follows.

Definition A.4. ((η, δ)-preservation) A shuffling mechanism $\mathcal{A} : \mathcal{Y}^n \mapsto \mathcal{Y}^n$ is defined to be (η, δ)-preserving ($\eta, \delta \in [0, 1]$) w.r.t to a given subset $S \subseteq [n]$, if
$$\Pr\left[|S_\sigma \cap S| \geq \eta \cdot |S|\right] \geq 1 - \delta, \sigma \in S_n \tag{9}$$
where $\mathbf{z} = \mathcal{A}(\mathbf{y}) = \sigma(\mathbf{y})$ and $S_\sigma = \{\sigma(i) | i \in S\}$.

For example, consider $S = \{1, 4, 5, 7, 8\}$. If $\mathcal{A}(\cdot)$ permutes the output according to $\sigma = (5\,3\,2\,6\,7\,9\,8\,1\,4\,10)$, then $S_\sigma = \{5, 6, 7, 8, 1\}$ which preserves 4 or 80% of its original indices. This means that for any data sequence $\mathbf{y}$, at least η fraction of its data values corresponding to the subset S overlaps with that of shuffled sequence $\mathbf{z}$ with high probability $(1 - \delta)$. Assuming, $\{y_S\} = \{y_i | i \in S\}$ and $\{z_S\} = \{z_i | i \in S\} = \{y_{\sigma(i)} | i \in S\}$ denotes the set of data values corresponding to S in data sequences $\mathbf{y}$ and $\mathbf{z}$ respectively, we have $\Pr\left[|\{y_S\} \cap \{z_S\}| \geq \eta \cdot |S|\right] \geq 1 - \delta, \forall \mathbf{y}$. For example, let S be the set of individuals from Nevada. Then, for a shuffling mechanism that provides $(\eta = 0.8, \delta = 0.1)$-preservation to S, with probability $\geq 0.9, \geq 80\%$ of the values that are reported to be from Nevada in $\mathbf{z}$ are genuinely from Nevada. The rationale behind this metric is that it captures the utility of the learning allowed by d_σ-privacy – if S is equal to some group $G \in \mathcal{G}$, (η, δ) preservation allows overall statistics of G to be captured. Note that this utility metric is *agnostic of both the data distribution and the analyst's query*. Hence, it is a conservative analysis of utility which serves as a lower bound for learning from $\{z_S\}$. We suspect that with the knowledge of the data distribution and/or the query, a tighter utility analysis is possible.

A formal utility analysis of Alg. 10 is presented in App. A.13. Empirical evaluation of (η, δ) - preservation is presented in App. A.14.

A.8 Discussion on Properties of Mallows Mechanism

Property 3. *For group assignment $\mathcal{G}$, a mechanism $\mathcal{A}(\cdot)$ that shuffles according to a permutation sampled from the Mallows model $\mathbb{P}_{\theta, \mathbf{\delta}}(\cdot)$, satisfies $(\alpha, \mathcal{G})$-$d_\sigma$privacy where*
$$\Delta(\sigma_0 : \mathbf{\delta}, \mathcal{G}) = \max_{(\sigma, \sigma') \in N_\mathcal{G}} |\mathbf{\delta}(\sigma_0 \sigma, \sigma_0) - \mathbf{\delta}(\sigma_0 \sigma', \sigma_0)|$$

and

$$\alpha = \theta \cdot \Delta(\sigma_0 : \mathbf{\delta}, \mathcal{G})$$
We refer to $\Delta(\sigma_0 : \mathbf{\delta}, \mathcal{G})$ as the sensitivity of the rank-distance measure $\mathbf{\delta}(\cdot)$

Proof. Consider two permutations of the initial sequence $\mathbf{y}$, $\sigma_1(\mathbf{y}), \sigma_2(\mathbf{y})$ that are neighboring w.r.t. some group $G_i \in \mathcal{G}$, $\sigma_1 \approx_{G_i} \sigma_2$. Additionally consider any fixed released shuffled sequence $\mathbf{z}$. Let Σ_1, Σ_2 be the set of permutations that turn $\sigma_1(\mathbf{y}), \sigma_2(\mathbf{y})$ into $\mathbf{z}$, respectively:
$$\Sigma_1 = \{\sigma \in S_n : \sigma\sigma_1(\mathbf{y}) = \mathbf{z}\}$$
$$\Sigma_2 = \{\sigma \in S_n : \sigma\sigma_2(\mathbf{y}) = \mathbf{z}\} \quad .$$
In the case that $\{y\}$ consists entirely of unique values, Σ_1, Σ_2 will each contain exactly one permutation, since only one permutation can map $\sigma_i(\mathbf{y})$ to $\mathbf{z}$.

Lemma 4. *For each permutation $\sigma_1' \in \Sigma_1$ there exists a permutation in $\sigma_2' \in \Sigma_2$ such that*
$$\sigma_1' \approx_{G_i} \sigma_2' \quad .$$

Proof follows from the fact that — since only the elements $j \in G_i$ differ in $\sigma_1(\mathbf{y})$ and $\sigma_2(\mathbf{y})$ — only those elements need to differ to achieve the same output permutation. In other words, we may define σ_1', σ_2' at all inputs $i \notin G_i$ identically, and then define all inputs $i \in G_i$ differently as needed. As such, they are neighboring w.r.t. G_i.

Recalling that Alg. 1 applies σ_0^{-1} to the sampled permutation, we must sample $\sigma_0\sigma_1'$ (for some $\sigma_1' \in \Sigma_1$) for the mechanism to produce $\mathbf{z}$ from $\sigma_1(\mathbf{y})$. Formally, since $\sigma_1'\sigma_1(\mathbf{y}) = \mathbf{z}$ we must sample $\sigma_0\sigma_1'$ to get $\mathbf{z}$ since we are going to apply σ_0^{-1} to the sampled permutation.

$$\Pr\left[\mathcal{A}(\sigma_1(\mathbf{y})) = \mathbf{z}\right] = \mathbb{P}_{\theta,\delta}(\sigma_0\sigma', \sigma' \in \Sigma_1 : \sigma_0)$$

$$\Pr\left[\mathcal{A}(\sigma_2(\mathbf{y})) = \mathbf{z}\right] = \mathbb{P}_{\theta,\delta}(\sigma_0\sigma', \sigma' \in \Sigma_2 : \sigma_0)$$

Taking the odds, we have

$$\frac{\mathbb{P}_{\theta,\delta}(\sigma_0\sigma', \sigma' \in \Sigma_1 : \sigma_0)}{\mathbb{P}_{\theta,\delta}(\sigma_0\sigma'', \sigma'' \in \Sigma_2 : \sigma_0)} = \frac{\sum_{\sigma' \in \Sigma_1} \mathbb{P}_{\Theta,\delta}(\sigma_0\sigma' : \sigma_0)}{\sum_{\sigma'' \in \Sigma_2} \mathbb{P}_{\Theta,\delta}(\sigma_0\sigma'' : \sigma_0)}$$

$$= \frac{\sum_{\sigma' \in \Sigma_1} e^{-\theta\delta(\sigma_0\sigma', \sigma_0)}}{\sum_{\sigma'' \in \Sigma_2} e^{-\theta\delta(\sigma_0\sigma'', \sigma_0)}}$$

$$\leq \frac{e^{-\theta\delta(\sigma_0\sigma_a, \sigma_0)}}{e^{-\theta\delta(\sigma_0\sigma_b, \sigma_0)}}$$

$$\leq e^{\theta|\delta(\sigma_0\sigma_a, \sigma_0) - \delta(\sigma_0\sigma_b, \sigma_0)|}$$

$$\leq e^{\theta\Delta}$$

where

$$\sigma_a = \arg\max_{\sigma' \in \Sigma_1} e^{-\theta\delta(\sigma_0\sigma', \sigma_0)} \text{ and}$$

$$\sigma_a = \arg\min_{\sigma'' \in \Sigma_2} e^{-\theta\delta(\sigma_0\sigma'', \sigma_0)} .$$

Therefore, setting $\alpha = \theta \cdot \Delta$, we achieve $(\alpha, \mathcal{G})$-$d_\sigma$privacy. $\qquad\square$

Property 4. *The sensitivity of a rank-distance is an increasing function of the width $\omega_{\mathcal{G}}^{\sigma_0}$. For instance, for Kendall's τ distance $\delta_\tau(\cdot)$, we have $\Delta(\sigma_0 : \delta_\tau, \mathcal{G}) = \frac{\omega_{\mathcal{G}}^{\sigma_0}(\omega_{\mathcal{G}}^{\sigma_0}+1)}{2}$.*

To show the sensitivity of Kendall's τ, we make use of its triangle inequality.

Proof. Recall from the proof of the previous property that the expression $\delta(\sigma, \sigma_0) = \delta(\sigma_0\sigma, \sigma_0)$, where δ is the actual rank distance measure e.g. Kendall's τ. As such, we require that

$$\left|\delta(\sigma_0\sigma_a, \sigma_0) - \delta(\sigma_0\sigma_b, \sigma_0)\right| \leq \frac{\omega_{\mathcal{G}}^{\sigma_0}(\omega_{\mathcal{G}}^{\sigma_0} + 1)}{2}$$

for any pair of permutations $(\sigma_a, \sigma_b) \in N_{\mathcal{G}}$.

For any group $G_i \in \mathcal{G}$, let $W_i \subseteq n$ represent the smallest contiguous subsequence of indices in σ_0 that contains all of G_i.

For instance, if $\sigma_0 = [2, 4, 6, 8, 1, 3, 5, 7]$ and $G_i = \{2, 6, 8\}$, then $W_i = \{2, 4, 6, 8\}$. Then the group width width is $\omega_i = |W_i| - 1 = 3$. Now consider two permutations neighboring w.r.t. G_i, $\sigma_a \approx_{G_i} \sigma_b$, so only the elements of G_i are shuffled between them. We want to bound

$$\left|\delta(\sigma_0\sigma_a, \sigma_0) - \delta(\sigma_0\sigma_b, \sigma_0)\right|$$

For this, we use a pair of triangle inequalities:

$$\delta(\sigma_0\sigma_a, \sigma_0\sigma_b) \geq \delta(\sigma_0\sigma_a, \sigma_0) - \delta(\sigma_0\sigma_b, \sigma_0) \quad \& \quad \delta(\sigma_0\sigma_a, \sigma_0\sigma_b) \geq \delta(\sigma_0\sigma_b, \sigma_0) - \delta(\sigma_0\sigma_a, \sigma_0)$$

so,

$$\left|\delta(\sigma_0\sigma_a, \sigma_0) - \delta(\sigma_0\sigma_b, \sigma_0)\right| \leq \delta(\sigma_0\sigma_a, \sigma_0\sigma_b)$$

Since $\sigma_0\sigma_a$ and $\sigma_0\sigma_b$ only differ in the contiguous subset W_i, the largest number of discordant pairs between them is given by the maximum Kendall's τ distance between two permutations of size $\omega_i + 1$:

$$\left|\delta(\sigma_0\sigma_a, \sigma_0\sigma_b)\right| \leq \frac{\omega_i(\omega_i + 1)}{2}$$

Since $\omega_{\mathcal{G}}^{\sigma_0} \geq \omega_i$ for all $G_i \in \mathcal{G}$, we have that

$$\Delta(\sigma_0 : \delta, \mathcal{G}) \leq \frac{\omega_{\mathcal{G}}^{\sigma_0}(\omega_{\mathcal{G}}^{\sigma_0} + 1)}{2}$$

$\qquad\square$

A.9 Hardness of Computing The Optimum Reference Permutation

Theorem A.3. *The problem of finding the optimum reference permutation, i.e., $\sigma_0 = \arg\min_{\sigma \in S_n} \omega_{\mathcal{G}}^{\sigma}$ is NP-hard.*

Proof. We start with the formal representation of the problem as follows.

Optimum Reference Permutation Problem. Given n subsets $\mathcal{G} = \{G_i \in 2^{[n]}, i \in [n]\}$, find the permutation $\sigma_0 = \arg\min_{\sigma \in S_n} \omega_{\mathcal{G}}^{\sigma}$.

Now, consider the following job-shop scheduling problem.

Job Shop Scheduling. There is one job J with n operations $o_i, i \in [n]$ and n machines such that o_i needs to run on machine M_i. Additionally, each machine has a sequence dependent processing time p_i. Let S be the sequence till There are n subsets $S_i \subseteq [n]$, each corresponding to a set of operations that need to occur in contiguous machines, else the processing times incur penalty as follows. Let p_i denote the processing time for the machine running the i-th operation scheduled. Let $\mathbb{S}_i$ be the prefix sequence with i schedulings. For instance, if the final scheduling is 1 3 4 5 9 8 10 6 7 2 then $\mathbb{S}_4 = 1345$. Additionally, let $P_{\mathbb{S}_i}^j$ be the shortest subsequence such of $\mathbb{S}_i$ such that it contains all the elements in $S_j \cap \{\mathbb{S}_i\}$. For example for $S_1 = \{3, 5, 7\}$, $P_{\mathbb{S}_4}^1 = 345$.

$$p_i = \max_{i \in [n]}(|P_{\mathbb{S}_i}^j| - |S_j \cap \{\mathbb{S}_i\}|) \tag{10}$$

The objective is to find a scheduling for J such that it minimizes the makespan, i.e., the completion time of the job. Note that $p_n = \max_i p_i$, hence the problem reduces to minimizing p_n.

Lemma 5. *The aforementioned job shop scheduling problem with sequence-dependent processing time is NP-hard.*

Proof. Consider the following instantiation of the sequence-dependent job shop scheduling problem where the processing time is given by $p_i = p_{i-1} + w_{kl}, p_1 = 0$ where $\mathbb{S}_i[i-1] = k$, $\mathbb{S}_i[i] = l$ and $w_{ij}, j \in S_i$ represents some associated weight. This problem is equivalent to the travelling salesman problem (TSP) Balas (2008) and is therefore, NP-hard. Thus, our aforementioned job shop scheduling problem is also clearly NP-hard. □

Reduction: Let the n subsets S_i correspond to the groups in $\mathcal{G}$. Clearly, minimizing $\omega_{\mathcal{G}}^{\sigma}$ minimizes p_n. Hence, the optimal reference permutation gives the solution to the scheduling problem as well.

□

A.10 Illustration of Alg. 1

We now provide a small-scale step-by-step example of how Alg. 1 operates.

Fig. 6a is an example of a grouping $\mathcal{G}$ on a dataset of $n = 8$ elements. The group of DO_i includes i and its neighbors. For instance, $G_8 = \{8, 3, 5\}$. To build a reference permutation, Alg. 1 starts at the index with the largest group, $i = 5$ (highlighted in purple), with $G_5 = \{5, 2, 3, 8, 4\}$. As shown in Figure 6b, the σ_0 is then constructed by following a BFS traversal from $i = 5$. Each $j \in G_5$ is visited, queuing up the neighbors of each $j \in G_5$ that haven't been visited along the way, and so on. The algorithm completes after the entire graph has been visited.

The goal is to produce a reference permutation in which the width of each group in the reference permutation ω_i is small. In this case, the width of the largest group G_5 is as small as it can be $\omega_5 = 5 - 1 = 4$. However, the width of $G_4 = \{4, 5, 7\}$ is the maximum possible since $\sigma^{-1}(5) = 1$ and $\sigma^{-1}(7) = 8$, so $\omega_4 = 7$. This is difficult to avoid when the maximum group size is large as compared to the full dataset size n. Realistically, we expect n to be significantly larger, leading to relatively smaller groups.

With the reference permutation in place, we compute the sensitivity:

$$\Delta(\sigma_0 : \delta, \mathcal{G}) = \frac{\omega_4(\omega_4 + 1)}{2}$$
$$= 28$$

(a) Group graph

$\sigma_0(1)$	$\sigma_0(2)$	$\sigma_0(3)$	$\sigma_0(4)$	$\sigma_0(5)$	$\sigma_0(6)$	$\sigma_0(7)$	$\sigma_0(8)$
5	**2**	**3**	**8**	**4**	**1**	**6**	**7**

	queue 0	2	3	8	4	1	6	7
pos'n	1	3	8	4	1	6	7	
	2	8	4	1	6	7		
	3	4	1	6				

(b) BFS reference permutation σ_0

Figure 6: Illustration of Alg. 1

Which lets us set $\theta = \frac{\alpha}{28}$ for any given α privacy value. To reiterate, lower θ results in more randomness in the mechanism.

We then sample the permutation $\hat{\sigma} = \mathbb{P}_{\theta, \boldsymbol{\delta}}(\sigma_0)$. Suppose

$$\hat{\sigma} = [3\ 2\ 5\ 4\ 8\ 1\ 7\ 6]$$

Then, the released $\mathbf{z}$ is given as

$$\mathbf{z} = \sigma^* = \sigma^{-1}\hat{\sigma}(\mathbf{y})$$

$$= [y_1\ y_2\ y_5\ y_8\ y_3\ y_7\ y_6\ y_4]$$

One can think of the above operation as follows. What was 5 in the reference permutation ($\sigma_0(1) = 5$) is 3 in the sampled permutation ($\hat{\sigma}(1) = 3$). So, index 5 corresponding to DO_5 now holds DO_3's noisy data y_3. As such, we shuffle mostly between members of the same group, and minimally between groups.

The runtime of this mechanism is dominated by the Repeated Insertion Model sampler Doignon et al. (2004), which takes $\mathcal{O}(n^2)$ time. It is very possible that there are more efficient samplers available, but RIM is a standard and simple to implement for this first proposed mechanism. Additionally, the majority of this is spent computing sampling parameters which can be stored in advanced with $\mathcal{O}(n^2)$ memory. Furthermore, sampling from a Mallows model with some reference permutation σ_0 is equivalent to sampling from a Mallows model with the identity permutation and applying it to σ_0. As such, permutations may be sampled in advanced, and the runtime is dominated by computation of σ_0 which takes $\mathcal{O}(|V| + |E|)$ time (the number of veritces and edges in the graph).

A.11 Proof of Thm. 4.3

Theorem 4.3 *Alg. 1 is $(\alpha, \mathcal{G})$-d_σ private.*

Proof. The proof follows from Prop. 3. Having computed the sensitivity of the reference permutation σ_0, Δ, and set $\theta = \alpha/\Delta$, we are guaranteed by Property 3 that shuffling according to the permutation $\hat{\sigma}$ guarantees $(\alpha, \mathcal{G})$-d_σ privacy.

$\square$

.

A.12 Proof of Thm. 4.4

Theorem 4.4 *Alg. 1 satisfies $(\alpha', \mathcal{G}')$-d_σ privacy for any group assignment $\mathcal{G}'$ where $\alpha' = \alpha \frac{\Delta(\sigma_0 : \delta, \mathcal{G}')}{\Delta(\sigma_0 : \delta, \mathcal{G})}$*

Proof. Recall from Property 3 that we satisfy $(\alpha, \mathcal{G})$ d_σ-privacy by setting $\theta = \alpha/\Delta(\sigma_0 : \delta, \mathcal{G})$. Given alternative grouping $\mathcal{G}'$ with sensitivity $\Delta(\sigma_0 : \delta, \mathcal{G}')$, this same mechanism provides

$$
\begin{aligned}
\alpha' &= \frac{\theta}{\Delta(\sigma_0 : \delta, \mathcal{G}')} \\
&= \frac{\alpha/\Delta(\sigma_0 : \delta, \mathcal{G})}{\Delta(\sigma_0 : \delta, \mathcal{G}')} \\
&= \alpha \frac{\Delta(\sigma_0 : \delta, \mathcal{G}')}{\Delta(\sigma_0 : \delta, \mathcal{G})}
\end{aligned}
$$

$\square$

A.13 Formal Utility Analysis of Alg. 1

Theorem A.4. *For a given set $S \subset [n]$ and Hamming distance metric, $\delta_H(\cdot)$, Alg. 1 is (η, δ)-preserving for $\delta = \frac{1}{\psi(\theta, \delta_H)} \sum_{h=2k+1}^{n} (e^{-\theta \cdot h} \cdot c_h)$ where $k = \lceil (1 - \eta) \cdot |S| \rceil$ and c_h is the number of permutations with hamming distance h from the reference permutation that do not preserve $\eta\%$ of S and is given by*

$$
c_h = \sum_{j=k+1}^{\max(l_s, \lfloor h/2 \rfloor)} \binom{l_s}{j} \cdot \binom{n - l_s}{j} \cdot \left[\sum_{i=0}^{\min(l_s - j, h - 2j)} \binom{l_s - j}{i} \right.
$$

$$
\left. \cdot \binom{i + j}{j} \cdot f(i, j) \cdot \binom{n - l_s - j}{h - 2j - i} \cdot f(h - 2j - i, j)! \right]
$$

$$
f(i, 0) = !i, \ f(0, q) = q!
$$

$$
f(i, j) = \sum_{q=0}^{\min(i, j)} \left[\binom{i}{q} \cdot \binom{j}{j - q} \cdot j! \cdot f(i - q, q) \right]
$$

$$
l_s = |S|, k = (1 - \eta) \cdot l_s, !n = \lfloor \frac{n!}{e} + \frac{1}{2} \rfloor
$$

Proof. Let $l_s = |S|$ denote the size of the set S and $k = \lceil (1 - \eta) \cdot l_S \rceil$ denote the maximum number of correct values that can be missing from S. Now, for a given permutation $\sigma \in S_n$, let h denote its Hamming distance from the reference permutation σ_0, i.e, $h = \delta_H(\sigma, \sigma_0)$. This means that σ and σ_0 differ in h indices. Now, h can be analysed in the the following two cases,

Case I. $h \leq 2k + 1$

For $(1 - \eta)$ fraction of indices to be removed from S, we need at least $k + 1$ indices from S to be replaced by $k + 1$ values from outside S. This is clearly not possible for $h \leq 2k + 1$. Hence, here $c_h = 0$.

Case II. $h > 2k$

For the following analysis we consider we treat the permutations as strings (multi-digit numbers are treated as a single string character). Now, Let $\mathbb{S}_{\sigma_0}$ denote the non-contiguous substring of σ_0 such that it consists of all the elements of S, i.e.,

$$|\mathbb{S}| = l_S \tag{11}$$

$$\forall i \in [l_S], \mathbb{S}_{\sigma_0}[i] \in S \tag{12}$$

Let $\mathbb{S}_\sigma$ denote the substring corresponding to the positions occupied by $\mathbb{S}_{\sigma_0}$ in σ. Formally,

$$|\mathbb{S}_\sigma| = l_S \tag{13}$$

$$\forall i \in [l_S], \mathbb{S}_{\sigma_0}[i] = \sigma(\sigma_0^{-1}(\mathbb{S}_{\sigma_0}[i])) \tag{14}$$

For example, for $\sigma_0 = (1\ 2\ 3\ 5\ 4\ 7\ 8\ 10\ 9\ 6), \sigma = (1\ 3\ 2\ 7\ 8\ 5\ 4\ 6\ 10\ 9)$ and $S = \{2, 4, 5, 8\}$, we have $\mathbb{S}_{\sigma_0} = 2548$ and $S_\sigma = 3784$ where $h = \delta_H(\sigma, \sigma_0) = 9$. Let $\{\mathbb{S}_\sigma\}$ denote the set of the elements of string $\mathbb{S}_\sigma$. Let A be the set of characters in $\mathbb{S}_\sigma$ such that they do not belong to S, i.e, $A = \{\mathbb{S}_\sigma[i] | \mathbb{S}_\sigma[i] \notin S, i \in [l_S]\}$. Let B be the set of characters in $\mathbb{S}_\sigma$ that belong to S but differ from $\mathbb{S}_{\sigma_0}$ in position, i.e., $B = \{\mathbb{S}_\sigma[i] | \mathbb{S}_\sigma[i] \in S, \mathbb{S}_\sigma[i] \neq \mathbb{S}_{\sigma_0}[i], i \in [l_S]\}$. Additionally, let $C = S - \{\mathbb{S}_\sigma\}$. For instance, in the above example, $A = \{3, 7\}, B = \{4, 8\}, C = \{2, 5\}$. Now consider an initial arrangement of $p + m$ distinct objects that are subdivided into two types – p objects of Type A and m objects of Type B. Let $f(p, m)$ denote the number of permutations of these $p + m$ objects such that the m Type B objects can occupy any position but no object of Type A can occupy its original position. For example, for $f(p, 0)$ this becomes the number of derangements der denoted as $!p = \lfloor \frac{p!}{e} + \frac{1}{2} \rfloor$. Therefore, $f(|B|, |A|)$ denotes the number of permutations of $\mathbb{S}_\sigma$ such that $\delta_H(\mathbb{S}_{\sigma_0}, \mathbb{S}_\sigma) = |A| + |B|$. This is because if elements of B are allowed to occupy their original position then this will reduce the Hamming distance.

Now, let $\bar{\mathbb{S}}_\sigma$ ($\bar{\mathbb{S}}_{\sigma_0}$) denote the substring left out after extracting from $\mathbb{S}_\sigma$ ($\mathbb{S}_{\sigma_0}$) from σ (σ_0). For example, $\bar{\mathbb{S}}_\sigma = 1256109$ and $\bar{\mathbb{S}}_{\sigma_0} = 1371096$ in the above example. Let D be the set of elements outside of S and A that occupy different positions in $\bar{\mathbb{S}}_\sigma$ and $\bar{\mathbb{S}}_{\sigma_0}$ (thereby contributing to the hamming distance), i.e., $D = \{\bar{\mathbb{S}}_{\sigma_0[i]} | \bar{\mathbb{S}}_{\sigma_0[i]} \notin S, \bar{\mathbb{S}}_{\sigma_0[i]} \neq \bar{\mathbb{S}}_{\sigma[i]}, i \in [n - l_S]\}$. For instance, in the above example $D = \{9, 6, 10\}$. Hence, $h = \delta_H(\sigma, \sigma_0) = |A| + |B| + |C| + |D|$ and clearly $f(|D|, |C|)$ represents the number of permutations of $\bar{\mathbb{S}}_\sigma$ such that $\delta_H(\bar{\mathbb{S}}_\sigma, \bar{\mathbb{S}}_{\sigma_0}) = |C| + |D|$. Finally, we have

$$c_h = \sum_{j=k+1}^{\max(l_s, \lfloor h/2 \rfloor)} \underbrace{\binom{l_s}{j}}_{\substack{\text{\# ways of selecting set } C}} \cdot \underbrace{\binom{n - l_s}{j}}_{\substack{\text{\# ways of selecting set } A}} \cdot \Bigg[$$

$$\sum_{i=0}^{\min(l_s - j, h - 2j)} \underbrace{\binom{l_s - j}{i}}_{\substack{\text{\# ways of selecting set } B}} \cdot f(i, j)$$

$$\cdot \underbrace{\binom{n - l_s - j}{h - 2j - i}}_{\substack{\text{\# ways of selecting set } D}} \cdot f(h - 2j - i, j) \Bigg]$$

Now, for $f(i, j)$ let E be the set of original positions of Type A that are occupied by Type B objects in the resulting permutation. Additionally, let F be the set of the original positions of Type B objects that are still occupied by some Type B object. Clearly, Type B objects can occupy these $|E| + |F| = m$ in any way they like. However, the type A objects can only result in $f(p - q, q)$ permutations. Therefore, $f(p, m)$ is given by the following recursive function

$$f(p, 0) = !p$$

$$f(0, m) = m!$$

$$f(p, m) = \sum_{q=0}^{\min p, m} \Bigg(\underbrace{\binom{p}{q}}_{\substack{\text{\# ways of selecting set } E}} \cdot \underbrace{\binom{m}{m - q}}_{\substack{\text{\# ways of selecting set } F}}$$

$$\cdot m! \cdot f(p - q, q) \Bigg)$$

Thus, the total probability of failure is given by

$$\delta = \frac{1}{\psi(\theta, \boldsymbol{\delta}_H)} \sum_{h=2k+2}^{n} \left(e^{-\theta \cdot h} \cdot c_h \right) \tag{15}$$

$\square$

A.14 ADDITIONAL EXPERIMENTAL DETAILS

A.14.1 EVALUATION OF (η, δ)-PRESERVATION

Figure 7: (η, δ)-Preservation Analysis

In this section, we evaluate the characteristics of the (η, δ)-preservation for Kendall's τ distance $\mathfrak{d}_\tau(\cdot, \cdot)$.

Each sweep of Fig. 7 fixes $\delta = 0.01$, and observes η. We consider a dataset of size $n = 10K$ and a subset S of size l_S corresponding to the indices in the middle of the reference permutation σ_0 (the actual value of the reference permutation is not significant for measuring preservation). For the rest of the discussion, we denote the width of a permutation by ω for notational brevity. For each value of the independent axis, we generate 50 trials of the permutation σ from a Mallows model with the appropriate θ (given the ω and α parameters). We then report the largest η (fraction of subset preserved) that at least 99% of trials satisfy.

In Fig. 7a, we see that preservation is highest for higher α and increases gradually with declining width ω and increasing subset size l_s.

Fig. 7b demonstrates that preservation declines with increasing width. Δ increases quadratically with width ω for $\mathfrak{d}_\tau$, resulting in declining θ and increasing randomness. We also see that larger subset sizes result in a more gradual decline in η. This is due to the fact that the worst-case preservation (uniform random shuffling) is better for larger subsets. i.e. we cannot do worse than 80% preservation for a subset that is 80% of indices.

Finally, Fig. 7c demonstrates how preservation grows rapidly with increasing subset size. For large widths, we are nearly uniformly randomly permuting, so preservation will equal the size of the subset relative to the dataset size. For smaller widths, we see that preservation offers diminishing returns as we grow subset size past some critical l_s. For $\omega = 30$, we see that subset sizes much larger than a quarter of the dataset gain little in preservation.

A.14.2 ADULT DATASET

Figure 8: Adult dataset experiments

A.15 ADDITIONAL RELATED WORK

In this section, we discuss the relevant existing work.

The anonymization of noisy responses to improve differential privacy was first proposed by Bittau et al. Bittau et al. (2017a) who proposed a principled system architecture for shuffling. This model was formally studied later in Erlingsson et al. (2019); Cheu et al. (2019). Erlingsson et al. Erlingsson et al. (2019) showed that for arbitrary ϵ-LDP randomizers, random shuffling results in privacy amplification. Cheu et al. Cheu et al. (2019) formally defined the shuffle DP model and analyzed the privacy guarantees of the binary randomized response in this model. The shuffle DP model differs from our approach in two ways. First, it focuses completely on the DP guarantee. The privacy amplification is manifested in the from of a lower ϵ (roughly a factor of $\sqrt{n}$) when viewed in an alternative DP model known as the central DP model. Erlingsson et al. (2019); Cheu et al. (2019); Balle et al. (2019); Feldman et al. (2020); Bittau et al. (2017a); Balcer & Cheu (2020). However, our result caters to local inferential privacy. Second, the shuffle model involves an uniform random shuffling of the entire dataset. In contrast, our approach the granularity at which the data is shuffled is tunable which delineates a threshold for the learnability of the data.

A steady line of work has sudied the inferential privacy setting Kasiviswanathan & Smith (2014); Kifer & Machanavajjhala (2011); Ghosh & Kleinberg (2016); Dalenius (1977); Dwork & Naor (2010); Tschantz et al. (2020). Kifer et al. Kifer & Machanavajjhala (2011) formally studied privacy degradation in the face of data correlations and later proposed a privacy framework, Pufferfish Kifer & Machanavajjhala (2014); Song et al. (2017); He et al. (2014), for analyzing inferential privacy. Subsequently, several other privacy definitions have also been proposed for the inferential privacy setting Liu et al. (2016); Yang et al. (2015); Chen et al. (2014); Zhu et al. (2015); Bassily et al. (2013). For instance, Gehrke et al. proposed a zero-knowledge privacy Gehrke et al. (2011; 2012) which is based on simulation semantics. Bhaskar et al. proposed noiseless privacy Bhaskar et al. (2011); Grining & Klonowski (2017) by restricting the set of prior distributions that the adversary may have access to. A recent work by Zhang et al. proposes attribute privacy Zhang et al. (2020) which focuses on the sensitive properties of a whole dataset. In another recent work, Ligett et al. study a relaxation of DP that accounts for mechanisms that leak some additional, bounded information about the database Ligett et al. (2020). Some early work in local inferential privacy include profile-based privacy Geumlek & Chaudhuri (2019) by Gehmke et al. where the problem setting comes with a graph of data generating distributions, whose edges encode sensitive pairs of distributions that should be made indistinguishable. In another work by Kawamoto et al., the authors propose distribution privacy Kawamoto & Murakami (2018) – local differential privacy for probability distributions. The major difference between our work and prior research is that we provide local inferential privacy through a new angle – data shuffling.

Finally, older works such as k-anonymity Sweeney (2002), l-diversity Machanavajjhala et al. (2007), and Anatomy Xiao & Tao (2006) and other Wong et al. (2010); Tassa et al. (2012); Xue et al. (2012); Choromanski et al. (2013); Doka et al. (2015) have studied the privacy risk of non-sensitive auxiliary information, or 'quasi identifiers' (QIs). In practice, these works focus on the setting of dataset release, where we focus on dataset collection. As such, QIs can be manipulated and controlled, whereas we place no restriction on the amount or type of auxiliary information accessible to the adversary, nor do we control it. Additionally, our work offers each individual formal inferential guarantees against informed adversaries, whereas those works do not. We emphasize this last point since formalized guarantees are critical for providing meaningful privacy definitions. As established by Kifer and Lin in *An Axiomatic View of Statistical Privacy and Utility* (2012), privacy definitions ought to at least satisfy post-processing and convexity properties which our formal definition does.