PROFESSOR X: MANIPULATING EEG BCI WITH INVISIBLE AND ROBUST BACKDOOR ATTACK

ABSTRACT

While electroencephalogram (EEG) based brain-computer interface (BCI) has been widely used for medical diagnosis, health care, and device control, the safety of EEG BCI has long been neglected. In this paper, we propose **Professor X**, an invisible and robust "mind-controller" that can arbitrarily manipulate the outputs of EEG BCI through backdoor attack, to alert the EEG community of the potential hazard. However, existing EEG attacks mainly focus on single-target class attacks, and they either require engaging the training stage of the target BCI, or fail to maintain high stealthiness. Addressing these limitations, Professor X exploits a three-stage clean label poisoning attack: **1)** selecting one trigger for each class; **2)** learning optimal injecting EEG electrodes and frequencies strategy with reinforcement learning for each trigger; **3)** generating poisoned samples by injecting the corresponding trigger's frequencies into poisoned data for each class by linearly interpolating the spectral amplitude of both data according to previously learned strategies. Experiments on datasets of three common EEG tasks demonstrate the effectiveness and robustness of Professor X, which also easily bypasses existing backdoor defenses. Code will be released soon.

1 INTRODUCTION

Electroencephalogram (EEG) is a neuroimaging technology to record of the spontaneous electrical activity of the brain. EEG-based brain-computer interface (BCI) has been widely used in medical diagnosis (Ahmad et al., 2022), healthcare (Jafari et al., 2023), and device control (Lorach et al., 2023; Altaheri et al., 2023). While most EEG community researchers devote themselves to advancing the performance of EEG BCI, the safety of EEG BCI has long been neglected. Inspired by Professor X[1], a superhuman with the ability to control other's minds, we wonder whether a malicious adversary can arbitrarily manipulate the outputs of EEG BCI like him. It will be severely dangerous if so. Backdoor attack (BA), where an adversary injects a backdoor into a model to control its outputs for inference samples with a particular trigger, offers a feasible approach (Doan et al., 2022).

However, designing an effect and stealthy BA for EEG modality is not trivial for three difficulties, resulting in three questions. **D1**: Low signal-to-noise ratio (SNR) and heterogeneity in EEG format (*i.e.*, the montage and sampling rate of EEG recordings) are major obstacles. **Q1**: How to develop a generalizable BA for various EEG tasks (usually have different EEG formats)? **D2**: Previous studies demonstrated for different EEG tasks, different critical EEG electrodes and frequencies strongly related to the performance of EEG BCI (Parvez & Paul, 2014; Jana & Mukherjee, 2021; Baig et al., 2020; Herman et al., 2008), indicating that the trigger-injection strategy (*i.e.*, which electrodes and frequencies to inject triggers) inevitably affects the performance of BA. **Q2**: How to find the optimal strategy for different EEG tasks? **D3**: Certain classes of EEG have specific morphology that can easily be identified by human experts, *e.g.*, in epilepsy detection, the EEG during the ictal phase contains more spike/sharp waves than those during the normal state phase (Blume et al., 1984). **Q3**: How to maintain the consistency of the label and the morphology?

The first BA for EEG modality is demonstrated in Fig 1 (a), where the narrow period pulse (NPP) signals are added as the trigger for single-target class attacks (Meng et al., 2023; Jiang et al., 2023b). To generate invisible triggers, the adversarial loss is applied to learn a spatial filter as the trigger

---

[1]https://en.wikipedia.org/wiki/Professor_X

Figure 1: (a) The payloads of the existing backdoor attacks. (b) The payloads of Professor X, which can arbitrarily manipulate the outputs of EEG BCI models.(c)-(e) The framework of Professor X: (c) The trigger selection and EEG data distribution from the view of manifold learning. (d) Learning optimal electrodes and frequencies injection strategies. (e) The generation process.

function (Meng et al., 2024). Recently, some BA for time series (EEG signal is a kind of time series) adopt generative adversarial net (GAN) to produce poisoned data (Ding et al., 2022; Jiang et al., 2023c). However, there is rich information in the frequency domain of EEG (Arroyo & Uematsu, 1992; Kostyunina & Kulikov, 1996; Salinsky et al., 1991; Muthukumaraswamy, 2013). No matter whether these BA are stealthy or not, they all inject unnatural perturbation in the temporal domain, which will inevitably bring unnatural frequency into the real EEG frequency domain.

In this paper, we propose a novel backdoor attack framework **Professor X** to address **Q1**, which injects triggers in the frequency domain and is generalizable to various EEG tasks. Specifically, Professor X is a three-stage clean label poisoning attack demonstrated in Fig 1 (c-e): **1**): selecting c triggers from c classes. Since these triggers is all real EEG, their frequency are all real, the poisoned EEG (injected with triggers' frequency) is real, as shown in Fig 2(b). **2**): learning optimal injecting strategy for each trigger with reinforcement learning to enhance the performance of EEG BA, addressing **Q2**. **3**): generating poisoned data by injecting each trigger's frequency into clean data whose class is the same as the trigger's class, which does not introduce any unreal frequency from other EEG types and maintains the consistency of the label and morphology, addressing **Q3**.

The main contributions of this paper are summarized below:

- We propose a novel backdoor attack for EEG BCI called **Professor X**, which can attack arbitrary class while preserving stealthiness without engaging the training stage .
- To the best of our knowledge, it is the first work that considers the efficacy of different EEG electrodes and frequencies in EEG backdoor attacks.
- Extensive experiments on three EEG BCI datasets demonstrate the effectiveness of Professor X and the robustness against several common preprocessing and backdoor defenses.

2 RELATED WORK

2.1 BACKDOOR ATTACKS

Backdoor attacks has been deeply investigated in image processing filed (Weber et al., 2023; Yu et al., 2023; Yuan et al., 2023). BadNets (Gu et al., 2019) is the first BA, where the adversary maliciously control models to misclassify the input images contain suspicious patches to a target class. Other non-stealthy attacks include blended (Chen et al., 2017) and sinusoidal strips based (Barni et al.,

2019). To achieve higher stealthiness, some data poisoning BA were developed, including shifting color spaces (Jiang et al., 2023a), warping (Nguyen & Tran, 2020b), regularization (Li et al., 2020) and frequency-based (Zeng et al., 2021; Wang et al., 2022; Hammoud & Ghanem, 2021; Hou et al., 2023; Feng et al., 2022; Gao et al., 2024). Other stealthy attacks (Nguyen & Tran, 2020a; Doan et al., 2021) generate invisible trigger patterns by adversarial loss, which requires the control of the model's training process. To attack multi-target class with high stealthiness, Marksman backdoor (Doan et al., 2022) generates sample-specific triggers by co-training target model and trigger generation model, needing fully control of the training stage. Moreover, generating trigger patterns with a neural network for each sample is time-consuming and unable to use in real-time systems.

2.2 BACKDOOR ATTACKS FOR EEG BCI

Figure 2: t-SNE visualization.

Recently, the EEG-based BCIs have shown to be vulnerable to BA (Meng et al., 2023; Jiang et al., 2023b; Meng et al., 2024). The NPP signals are added to clean EEG to generate non-stealthy poisoned samples in (Meng et al., 2023; Jiang et al., 2023b), which significantly modifies the spectral distribution (as shown in Fig 2 (a)) and results in low stealthiness. From the view of manifold learning in Fig 1 (a), NPP-added EEG are fake data. To generate more stealthy poisoned data which stay in the real data boundary. The adversarial loss has been applied backdoor EEG BCI (Meng et al., 2024) and time series (Ding et al., 2022; Jiang et al., 2023c). BackTime proposed to generate trigger patterns for each input data using a bi-level optimization Lin et al. (2024). But these methods can only attack a single target class and require controlling the training process of the backdoor/surrogate models, requiring knowledge of targe model. Meng *et.al.* tried to achieve multi-target attacks with adding different types of signals to clean EEG, *i.e.*, NPP, sawtooth, sine, and chirp (Meng et al., 2023). However, these signals are not stealthy in both the temporal and frequency domain.

Different from the EEG BA in the temporal domain, we firstly propose to attack in the frequency domain. Our attack is **1)** more stealthy than NPP-based attack, **2)** faster than other trigger generation attack, and **3)** more practical as requiring no control of the target models. Compared to those frequency-based BAs for image, our attack introduces reinforcement learning to find the optimal injection strategy and design two novel rewards for enhancing the stealthiness and robustness.

It is worth noting that the adversarial attack (AA) Zhang & Wu (2019); Liu et al. (2021) is different from BA. AA tries to make the target model misclassify by adding invisible perturbation to input, which acts in the inference stage. BA tries to inject backdoor into target model in the training stage.

2.3 BACKDOOR DEFENSES

To cope with the security problems of backdoor attacks, several categories of defensive methods have been developed. Neural Cleanse (Wang et al., 2019) is a trigger reconstruction based methods. If the reconstructed trigger pattern is significantly small, the model is identified as a backdoor model. Assuming the trigger is still effective when a triggered sample is combining with a clean sample, STRIP (Gao et al., 2019) detects the backdoor model by feeding the combined samples into the model to see if the predictions are still with low entropy. Spectral Signature (Tran et al., 2018) detects the backdoor model based on the latent representations. Fine-Pruning (Liu et al., 2018) erases the backdoor by pruning the model.

Besides the above defenses designed for backdoor attacks, there are some common EEG pre-processing methods, such as bandstop filtering and down-sampling, should be considered when designing a practical robust backdoor attack for EEG BCI in the real-world scene.

3 METHODOLOGY

3.1 EEG BCI BACKDOOR ATTACKS AND THREAT MODEL

Multi-target BA. The main notations in this paper are listed in Table 7. Under the supervised learning setting, a classifier f is learned using a labeled training set $\mathcal{S} = \{(x_1, y_1), ..., (x_N, y_N)\}$ to map $f : \mathcal{X} \to \mathcal{C}$, where $x_i \in \mathcal{X}$ and $y_i \in \mathcal{C}$. The attacker in single target class backdoor attacks aims to learn a classifier f behaves as follows:

$$f(x_i) = y_i, \ \ f(\mathcal{T}(x_i)) = c_{tar}, \ \ c_{tar} \in \mathcal{C}, \ \forall (x_i, y_i) \in \mathcal{S}, \tag{1}$$

where $\mathcal{T}: \mathcal{X} \to \mathcal{X}$ is the trigger function and c_{tar} is the target label. For multi-target class backdoor attacks, the trigger function has an extra parameter c_i, which manipulates the behavior of f flexibly:

$$f(x_i) = y_i, \quad f(\mathcal{T}(c_i, x_i)) = c_i, \quad \forall c_i \in \mathcal{C}, \forall (x_i, y_i) \in \mathcal{S}. \tag{2}$$

Threat Model. We consider a malicious data provider, who generates a small number of poisoned samples (labeled with the target class) and injects them into the original dataset. A victim developer collects this poisoned dataset and trains his model, which will be infected a backdoor.

3.2 REINFORCEMENT LEARNING FOR OPTIMAL TRIGGER-INJECTION STRATEGIES

The learning of the injecting electrodes set $\mathcal{M}_e^{c_i}$ and frequencies set $\mathcal{M}_f^{c_i}$ for each selected trigger in class c_i can be formulated as a non-convex optimization problem. Under this optimization framework, the strategy generator function learn the optimal $\mathcal{M}_e^{c_i}$ and $\mathcal{M}_f^{c_i}$ for each EEG trigger to implement Professor X on target EEG BCI f, which is supposed to have a high clean accuracy (CA) on the clean data and attack success rate (ASR) on the poisoned data:

$$\underset{\mathcal{M}_e^{c_i}, \mathcal{M}_f^{c_i}}{\arg\min} \mathbb{E}_{(x_i, y_i) \sim \mathcal{D}}[\mathcal{L}(f(x_i), y_i) + \lambda \mathcal{L}(f(\mathcal{T}(x_i, x_{c_i}^t, \alpha, \mathcal{M}_e^{c_i}, \mathcal{M}_f^{c_i})), c_i)], \tag{3}$$

where λ is a hyper-parameter to balance CA and ASR, and $\mathcal{T}$ is the poisoned data generation function. However, it is infeasible to find the optimal injecting strategy for each trigger in a large searching space, *e.g.*, if injecting half of the 62 electrodes, there are $\binom{62}{31} \approx 4.65 \times 10^{17}$ cases for deciding $\mathcal{M}_e^{c_i}$. Reinforcement learning (RL) is an appropriate method, whose objective of RL is to find a sampler π to maximize the expect of the reward function. The details are presented in Algorithm 1.

$$\pi^* = \arg\max_\pi \mathbb{E}_{\tau \sim \pi(\tau)}[R(\tau)]$$
$$= \arg\max_\pi \sum_\tau [R(\tau) \cdot p_\pi(\tau)]$$
$$= \arg\max_\pi \sum_\tau [R(\tau) \cdot \rho_0(s_1) \cdot \tag{4}$$
$$\prod_{t=1}^{T-1} \pi(a_t|s_t) \cdot \mathcal{P}(s_{t+1}|s_t, a_t)],$$

where $R(\tau)$ is reward function of a trajectory $\tau = (s_1, a_1, r_1, \ldots s_T)$, the s_i, a_i, r_i means the state, action, and reward at time i. The ρ_0 indicates the sampler of initial state. In our settings, the action (strategy) do not affect the state (trigger), which allows us to simplify Eq 4 by removing the states s_i:

$$\pi^* = \arg\max_\pi \sum_\tau [R(\tau) \cdot \prod_{t=1}^{T-1} \pi(a_t)]. \tag{5}$$

Furthermore, since only a particular strategy of each trigger matters, we replace the $R(\tau)$ with $R(a_t)$ and select the a_t whose $R(a_t)$ is the

---

Algorithm 1 Professor X's Strategy Optimization

Input: (1) dataset $\mathcal{S} = \{\mathcal{D}_{train}, \mathcal{D}_{test}, \mathcal{D}_p\}$,
    (2) trigger EEG x_c^t, policy network π_θ^c,
    (3) iterations K to update π_θ^c,
    (4) poisoning function $\mathcal{T}$ (in section 3.3)
Output: learned strategies $\mathcal{M}_e^c$ and $\mathcal{M}_f^c$.
1: Initialize parameters θ, $j \leftarrow 0$, $R_{best} \leftarrow 0$
2: **repeat**
3:    Sample two strategies: $\hat{\mathcal{M}}_e^c, \hat{\mathcal{M}}_f^c \leftarrow \pi_\theta(x_c^t)$
4:    Initialize poisoning set $\mathcal{S}_p \leftarrow \{\}$
5:    **for** each $(x_i, y_i) \in \mathcal{D}_p$ **do**
6:      **if** $y_i == c$ **then**
7:        $x_i^p \leftarrow \mathcal{T}(x, x_c^t, \alpha, \hat{\mathcal{M}}_e^c, \hat{\mathcal{M}}_f^c)$
8:        $\mathcal{S}_p \leftarrow \mathcal{S}_p + x_i^p$
9:      **end if**
10:   **end for**
11:   Train an EEG BCI on the set $\{\mathcal{D}_{train}, \mathcal{S}_p\}$
12:   Calculate CA and ASR on $\mathcal{D}_{test}$
13:   $R_t(\hat{\mathcal{M}}_e^{c_i}, \hat{\mathcal{M}}_f^{c_i}) \leftarrow$ CA $+ \lambda$ ASR $+ \mu \operatorname{dis}(\hat{\mathcal{M}}_f^{c_i}) + \nu \min(\hat{\mathcal{M}}_f^{c_i})$
14:   $\hat{g} \leftarrow \mathbb{E}_t[R_t(a_t) \cdot \nabla_\theta \log \pi_\theta]$
15:   Update θ with gradient $\hat{g}$: $\theta \leftarrow \theta + \eta \hat{g}$
16:   **if** $R_t(\hat{\mathcal{M}}_e^{c_i}, \hat{\mathcal{M}}_f^{c_i}) > R_{best}$ **then**
17:     $R_{best} \leftarrow R_t(\hat{\mathcal{M}}_e^{c_i}, \hat{\mathcal{M}}_f^{c_i})$
18:     $\mathcal{M}_e^c \leftarrow \hat{\mathcal{M}}_e^c, \mathcal{M}_f^c \leftarrow \hat{\mathcal{M}}_f^c$
19:   **end if**
20:   $j \leftarrow j + 1$
21: **until** $j = K$
22: **return** $\mathcal{M}_e^c, \mathcal{M}_f^c$

---

biggest as the optimal strategy. Here, an RL algorithm called policy gradient (Sutton et al., 1999) is adopted to learn an agent (*i.e.*, policy network $\pi_\theta^{c_i}$ with parameters θ) to find the optimal strategy for each trigger from class c_i. After removing the state s_t and replacing $R(\tau)$, the gradient estimator is:

$$\hat{g} = \nabla_\theta \mathbb{E}_{\tau \sim \pi_\theta(\tau)}[R(\tau)] = \sum_\tau [R(a_t) \cdot \nabla p_{\pi_\theta}(a_t)] = \mathbb{E}_t[R_t(a_t) \cdot \nabla_\theta \log \pi_\theta], \tag{6}$$

where a_t and R_t is the action and estimator of the reward function at timestep t. The expectation $\mathbb{E}_t$ indicates the empirical average. Here, $a_t = \{\mathcal{M}_e^{c_i}, \mathcal{M}_f^{c_i}\}$. The parameters of $\pi_\theta^{c_i}$ are updated by $\theta_{t+1} = \theta_t + \eta \hat{g}$, η is the learning rate. We run the RL for K steps and take the best a_t as the strategy.

Specifically, the agent has two output vectors $v_1 \in \mathbb{R}^E, v_2 \in \mathbb{R}^F$, where E and F is the number of EEG electrodes and frequencies. The electrodes and frequencies are in $\mathcal{M}_e^{c_i}$ and $\mathcal{M}_f^{c_i}$ only if the corresponding positions in v_1 and v_2 have Top-k values, k is γE for electrodes and βF for frequencies, where $\gamma, \beta \in (0, 1]$ are hyperparameters.

Besides the CA and ASR, two other important concerns should be considered: **C1:** Robustness against common EEG preprocessig-based defenses. For instance, if a BA's trigger is injected into frequency band 50-60Hz, the BA will fail when EEG is filtered by a 50Hz low pass filter. Thus, scattering the injection positions in various frequency can effectively evade from specific frequency filter preprocessing. **C2:** Stealthiness against human perceptions. Since high frequency are related to environmental noise, injecting higher frequencies is more invisible (Gliske et al., 2016). Therefore, we design two novel loss functions to address **C1** and **C2**, DIS for scattering injection positions and HF for injecting higher frequencies. The whole reward function R_t can be formulated follows:

$$R_t(a_t) = R_t(\mathcal{M}_e^{c_i}, \mathcal{M}_f^{c_i}) = \text{CA} + \lambda \, \text{ASR} + \mu \, \text{dis}(\mathcal{M}_f^{c_i}) + \nu \min(\mathcal{M}_f^{c_i}), \quad (7)$$

where the $\mathcal{M}_f^{c_i}$ indicates the set of all injecting frequency positions, and $\text{dis}()$ calculates the minimal distance between each pair of positions. Thus, $\text{dis}(\mathcal{M}_f^{c_i})$ is the discrete (DIS) loss, and $\min(\mathcal{M}_f^{c_i})$ is the high frequency (HF) loss, which can scatter the injection positions in various frequency bands and inject as high frequencies as possible. The $\lambda, \mu, \nu \in \mathbb{R}$ are hyperparameters.

3.3 Poisoned Data Generation in the Frequency Domain

After selecting the C triggers from each class and learning the strategy for each trigger, the poisoned data are generated by injecting these triggers into clean data with the corresponding strategies. As shown in Fig 1(c), given a clean data $x_i \in \mathcal{D}_p$ with label c_i, and a trigger data $x_{c_i}^t$, let $\mathcal{F}^A$ and $\mathcal{F}^P$ be the amplitude and phase components of the fast Fourier transform (FFT) result of a EEG signals, we denote the amplitude and phase spectrum of x_i and $x_{c_i}^t$ as:

$$\mathcal{A}_{x_i} = \mathcal{F}^A(x_i), \mathcal{A}_{x_{c_i}^t} = \mathcal{F}^A(x_{c_i}^t), \\ \mathcal{P}_{x_i} = \mathcal{F}^P(x_i), \mathcal{P}_{x_{c_i}^t} = \mathcal{F}^P(x_{c_i}^t). \quad (8)$$

The new poisoned amplitude spectrum $\mathcal{A}_{x_i}^P$ is produced by linearly interpolating $\mathcal{A}_{x_i}$ and $\mathcal{A}_{x_{c_i}^t}$. In order to achieve this, we produce a binary mask $\mathcal{M}^{c_i} \in \mathbb{R}^{E \times F} = 1_{(j,k)}, j \in \mathcal{M}_e^{c_i}, k \in$

Algorithm 2 Frequency Injection of Professor X: $\mathcal{T}(x, x_c^t, \alpha, \mathcal{M}_e^c, \mathcal{M}_f^c)$

Input: (1) clean EEG x, trigger EEG x_c^t from class c, interpolating ratio α,
    (2) learned strategies $\mathcal{M}_e^c, \mathcal{M}_f^c$.
Output: the poisoned EEG x^p.
1:   $\mathcal{M}^c \leftarrow$ a zero matrix with the shape of $E \times F$
2:   **for** each $i \in \mathcal{M}_e^c$ **do**
3:      **for** each $j \in \mathcal{M}_f^c$ **do**
4:         $\mathcal{M}^c[i, j] \leftarrow 1$
5:      **end for**
6:   **end for**
7:   $\mathcal{A}_x, \mathcal{P}_x, \mathcal{A}_{x_c^t} \leftarrow \mathcal{F}^A(x), \mathcal{F}^P(x), \mathcal{F}^A(x_c^t)$
8:   $\mathcal{A}_x^P \leftarrow [(1 - \alpha)\mathcal{A}_x + \alpha\mathcal{A}_{x_c^t}] \odot \mathcal{M}^c + \mathcal{A}_x \odot (1 - \mathcal{M}^c)$
9:   $x^p \leftarrow \mathcal{F}^{-1}(\mathcal{A}_x^P, \mathcal{P}_x)$
10: **return** x^p

$\mathcal{M}_f^{c_i}$, whose value is 1 for all positions corresponding to elements in both electrode and frequency strategies and 0 elsewhere. Denoting $\alpha \in (0, 1]$ as the linear interpolating ratio, the new poisoned amplitude spectrum can be computed as follows, where $\odot$ indicates Hadamard product:

$$\mathcal{A}_{x_i}^P = [(1 - \alpha)\mathcal{A}_{x_i} + \alpha\mathcal{A}_{x_{c_i}^t}] \odot \mathcal{M}^{c_i} + \mathcal{A}_{x_i} \odot (1 - \mathcal{M}^{c_i}). \quad (9)$$

Finally, we adopt the injected poisoned amplitude spectrum $\mathcal{A}_{x_i}^P$ and the clean phase spectrum $\mathcal{P}_{x_i}$ to get the poisoned data by inverse FFT $\mathcal{F}^{-1}$: $x_i^p = \mathcal{F}^{-1}(\mathcal{A}_{x_i}^P, \mathcal{P}_{x_i})$. The detailed procedure is written in Algorithm 2. By generating x_i^p through this frequency injection approach, we obtain a subset $\mathcal{S}_p = \{x_1^p, ..., x_M^p\}$, which will combine with $\mathcal{D}_{train}$ to form the whole traing dataset $\mathcal{S}$. The EEG BCI model f is then trained with $\mathcal{S}$ to obtain the ability of behvaing as equation 2.

4 Experiment Settings

4.1 Datasets

We demonstrate the effectiveness and generalizability of the proposed Professor X backdoor through comprehensive experiments on three EEG datasets. Some meta information is displayed in Table 1,

where can be seen that these datasets vary significantly in tasks, electrode numbers, montages, and sampling rates. More details about preprocessing are illustrated in Appendix D. Our goal is to develop a task-agnostic and format-agnostic BA method for EEG BCI. Hence, these elaborately chosen datasets can effectively validate the generalizability of each BA method.

Table 1: Meta information of the three datasets

Dataset	# Class	# Subject	# Electrode	Sampling Rate	Montage
Emotion Recognition	3	15	62	200 Hz	unipolar
Motor Imagery	4	9	22	250 Hz	unipolar
Epilepsy Detection	4	23	23	256 Hz	bipolar

Emotion Recognition (ER) Dataset. SEED (Zheng & Lu, 2015) is a discrete EEG emotion dataset studying three types of emotions: happy, neutral, and sad. SEED collected EEG from 15 subjects.

Motor Imagery (MI) Dataset. BCIC-IV-2a (Brunner et al., 2008) dataset recorded EEG from 9 subjects while they were instructed to imagine four types of movements: left hand, right hand, feet, and tongue.

Epilepsy Detection (ED) Dataset. CHB-MIT (Shoeb & Guttag, 2010) is an epilepsy dataset required from 23 patients. We cropped and resampled the CHB-MIT dataset to build an ED dataset with four types of EEG: ictal, preictal, postictal, and interictal phase EEG.

4.2 BASELINES

Non-stealthy Baselines. As mentioned in previous sections, to the best of our knowledge, Professor X is the first work that studies multi-trigger and multi-target class (MT) backdoor in EEG BCI. For comparison, we design several baseline approaches which can be divided into two main groups: non-stealthy and stealthy. Non-stealthy attacks contains **PatchMT** and **PulseMT**. For a benign EEG segment $x \in \mathbb{R}^{E \times T}$. PatchMT is a multi-trigger and MT extension of BadNets (Gu et al., 2019) where we fill the first βT timepoints of a EEG segments with a constant number, *e.g.*, $\{0.1, 0.3, 0.5\}$ for three-class task. PulseMT is a multi-trigger and MT extension of NPP-based backdoor attacks (Meng et al., 2023) where we use NPP signals with different amplitudes, *e.g.*, $\{-0.8, -0.3, 0.3, 0.8\}$ for different target classes.

Stealthy Baselines. Previous works generate stealthy poisioned samples by controlling the training stage and can only attack single target class (Meng et al., 2024; Ding et al., 2022; Jiang et al., 2023c). As they control the training of target model, it is unfair to directly compare their methods with Professor X. There is no stealthy MT BA for EEG. Thus, we design two MT stealthy attacks baselines: **CompMT** and **AdverMT**. CompMT generates poisoned samples for different target classes by compressing the amplitude of EEG with different ratios, *e.g.*, $\{-0.1, 0, 0.1\}$ for three-class task. AdverseMT is a multi-trigger and MT extension of adversarial filtering based attacks (Meng et al., 2024), where we using a local model trained only on $\mathcal{S}_p$ to generate different spatial filters $\mathbf{W}_i^*$ for different target classes, then we apply these spatial filters to generate poisoned samples. More details are written in Appendix E.

4.3 EXPERIMENTAL SETUP

We follow the poisoning attack setting as the previous works (Meng et al., 2023) and consider three widely-used EEG BCIs for classifier f: EEGNet (Lawhern et al., 2018), DeepCNN (Schirrmeister et al., 2017), and LSTM (Tsiouris et al., 2018). We use a cross-validation setting to evaluate all BAs, each EEG dataset $\mathcal{D}$ is divided into three parts: training set $\mathcal{D}_{train}$, poisoning set $\mathcal{D}_p$, and test set $\mathcal{D}_{test}$. Specifically, for a dataset contains n subjects, we select one subject's data as $\mathcal{D}_p$ one by one, and the remaining $n-1$ subjects to perform leave-one-subject-out (LOSO) cross-validation, *i.e.*, one of the subjects as $\mathcal{D}_{test}$, and the remaining $n-2$ subjects as $\mathcal{D}_{train}$ (one of the subjects in $\mathcal{D}_{train}$ is chosen to be validation set). In summary, for a dataset contains n subjects, there are $n(n-1)$ runs to validate each EEG BCI backdoor attack method. A poisoned subset $\mathcal{S}_p$ of M ($M < N$) examples is generated based on $\mathcal{D}_p$. Then $\mathcal{S}_p$ is combined with $\mathcal{D}_{train}$ to acquire $\mathcal{S} = \{\mathcal{S}_p, \mathcal{D}_{train}\}$. The poisoning ratio is defined as : $\rho = M/N$.

Table 2: The clean accuraciy and attack success rate for each target class with 40% poisoning rate. The best results are in **bold** and the second best are underlined. (M1: TimesNet, M2: EEG-Conformer)

Dataset	Method	Emotion Recognition					Motor Imagery						Epilepsy Detection					
		Clean	ASR	0	1	2	Clean	ASR	0	1	2	3	Clean	ASR	0	1	2	3
EEGNet	No Attack	0.477	0.333	-	-	-	0.327	0.250	-	-	-	-	0.508	0.250	-	-	-	-
	PatchMT	0.492	0.382	0.577	0.232	0.337	0.283	0.824	0.866	0.880	0.787	0.762	0.460	0.549	0.532	0.430	0.388	0.845
	PulseMT	0.463	0.778	0.844	0.509	0.981	0.270	0.825	0.947	0.656	0.758	0.938	0.439	0.810	0.853	0.745	0.729	0.913
	CompMT	0.443	0.385	0.099	0.377	0.678	0.269	0.865	0.530	0.997	0.983	0.948	0.437	0.547	0.261	0.280	0.714	0.933
	AdverMT	0.457	0.334	0.276	0.330	0.396	0.257	0.243	0.316	0.192	0.230	0.235	0.413	0.250	0.326	0.264	0.200	0.210
	Professor X	**0.535**	**0.857**	0.831	**0.791**	0.949	**0.323**	**1.000**	**0.999**	**1.000**	**1.000**	**0.999**	**0.477**	**0.944**	**0.930**	**0.954**	**0.921**	**0.970**
DeepCNN	No Attack	0.497	0.333	-	-	-	0.301	0.250	-	-	-	-	0.443	0.250	-	-	-	-
	PatchMT	0.481	0.342	0.248	0.323	0.453	0.276	0.704	0.638	0.977	0.774	0.425	0.431	0.729	0.416	**0.890**	0.719	0.892
	PulseMT	0.450	0.596	**0.815**	0.334	0.638	0.261	0.829	0.764	0.968	0.819	0.765	0.405	**0.885**	**0.872**	0.862	**0.861**	**0.943**
	CompMT	0.461	0.427	0.473	0.473	0.336	0.286	0.887	0.638	0.982	0.946	0.980	0.446	0.538	0.196	0.466	0.571	0.918
	AdverMT	0.367	0.388	0.298	0.453	0.412	0.245	0.247	0.320	0.221	0.196	0.240	0.396	0.275	0.354	0.218	0.227	0.301
	Professor X	**0.534**	**0.832**	0.732	**0.865**	**0.901**	**0.315**	**1.000**	**1.000**	**1.000**	**1.000**	**0.999**	**0.469**	0.828	0.725	0.839	0.845	0.904
LSTM	No Attack	0.506	0.333	-	-	-	0.264	0.250	-	-	-	-	0.462	0.250	-	-	-	-
	PatchMT	0.509	0.368	0.311	0.392	0.401	0.261	0.429	0.395	0.296	0.386	0.639	0.450	0.513	0.500	0.437	0.417	0.700
	PulseMT	0.511	0.824	0.883	0.645	0.943	**0.265**	0.533	0.787	0.327	0.282	0.737	0.451	0.804	**0.845**	0.769	0.709	0.895
	CompMT	0.484	0.490	0.272	0.269	0.929	0.260	0.548	0.219	0.511	0.523	0.940	**0.455**	0.435	0.194	0.217	0.490	0.840
	AdverMT	0.367	0.415	0.472	0.453	0.321	0.239	0.271	0.308	0.215	0.247	0.312	0.432	0.268	0.367	0.232	0.198	0.275
	Professor X	**0.519**	**0.954**	**0.998**	0.868	**0.996**	0.264	**0.966**	**0.987**	**0.988**	**0.901**	**0.986**	0.444	**0.865**	0.795	**0.833**	**0.857**	**0.975**
M1	Professor X	0.485	0.960	0.961	0.926	0.993	0.276	0.997	0.999	0.998	0.999	0.992	0.373	0.986	0.985	0.986	0.995	0.976
M2	Professor X	0.475	0.894	0.842	0.904	0.935	0.935	0.996	0.999	1.000	0.987	0.999	0.419	0.944	0.958	0.970	0.887	0.964

For all methods, we train the classifiers using the Adam optimizer with learning rate of 0.001. The batch size is 32 and the number of epochs is 100. For all datasets and baselines, the interpolating ratio $\alpha = 0.8$, the frequency poisoning ratio $\beta = 0.1$, the electrode poisoning ratio $\gamma = 0.5$. For the reinforcement learning, we train π_θ networks $K = 250$ epochs using the Adam optimizer with learning rate of 0.01. The hyperparameters in advantage function is set to $\lambda = 2$, $\mu = 0.3$, and $\nu = 0.005$. More details of the experimental setup can be found in Appendix E.

5 EXPERIMENTAL RESULTS

5.1 EFFECTIVENESS OF PROFESSOR X

This section presents the attack success rates of Professor X and baselines. To evaluate the performance in the multi-trigger multi-payload scenario, for each test sample $(x, y) \in \mathcal{D}_{test}$, we enumerate all possible target labels $c_i \in \mathcal{C}$ including the true label y and inject the trigger to activate the backdoor. The attack is successful only when the backdoor classifier f correctly predicts c_i for each poisoned input x with a target label c_i.

5.1.1 ATTACK PERFORMANCE

The CA (Clean) and ASR (Attack) for each class of all attack methods on three EEG tasks with three EEG BCI models are presented in Table 2. The AdverMT, designed for single-target attack, fails to attacks multiple target classes. While PulseMT achieves the second best on ER and ED dataset, CompMT achieves the second best on the MI dataset, indicating that these baselines are less generalizable. Our Professor X significantly outperforms baselines at almost all cases ($p < 0.05$) except attacking DeepCNN on the ED dataset, having ASRs above 0.8 on three datasets and even achieving an ASR of 1.000 on the MI dataset. Moreover, our attack is also effective on the SOTA time-reries classification model TimesNet (M1) (Wu et al., 2023) and Transformer-based model EEG-Conformer (M2) (Song et al., 2022). These results demonstrate that our Professor X is effective across different EEG tasks and EEG models, showcasing it's generalizability.

5.1.2 PERFORMANCE OF THE REINFORCEMENT LEARNING: POLICY GRADIENT

Displaying in Table 3, the performance of the policy gradient was compared with other common optimazation algorithms, including genetic algorithm (GA) (Katoch et al., 2021) and random selection (The search space is too large for performing grid search as explained in Section 3.2). It can be observed that the policy gradient outperforms GA while only spending 16% training time of GA. We plot the learning curve of RL in Appendix G.3, which demonstrates that RL learns well strategies within 50 epochs, i.e., only trains 50 backdoor models and saves lots of time. It is worth mentioning

that the random algorithm achieves not bad results, proving that our methods can be applied without RL if some performance drop is acceptable.

Table 3: Clean and attack performance with with different trigger search optimization algorithms, the poisoning rate is set to 10%. The target model is EEGNet.

Dataset Method	Emotion			Motor Imagery			Epilepsy		
	Clean	Attack	Time ↓	Clean	Attack	Time ↓	Clean	Attack	Time ↓
Random	0.520	0.771	-	0.291	0.857	-	0.501	0.721	-
Genetic Algorithm	0.516	0.826	15.2h	0.302	1.000	10.0h	0.492	0.862	30.5h
Policy Gradient	0.535	0.857	2.5h	0.323	1.000	1.8h	0.477	0.944	5.2h

5.1.3 PERFORMANCE OF LEARNED MASK STRATEGIES ON OTHER TARGET MODELS

We demonstrate that the injecting strategies learned on a EEG classifier f can be used to attack other EEG classifiers $\hat{f}$. In other words, Professor X can still be effective when the adversary has no knowledge of the target models $\hat{f}$. To perform the experiments, we use the strategy learned with a classifier f, then generate poisoned samples to attack another classifier $\hat{f}$ whose network is different from f. Table 4 shows the performance difference, it can be observed that the difference is relatively small in most of the cases, demonstrating the transferability of the injecting strategy learned with reinforcement learning.

Table 4: Clean and attack performance on other models. Red values represent the decreasing performance in attacks with f is the same as $\hat{f}$. Blue values mean increments or unchanged .

Models	f : EEGNet				f : DeepCNN				f : LSTM			
	$\hat{f}$: DeepCNN		$\hat{f}$: LSTM		$\hat{f}$: EEGNet		$\hat{f}$: LSTM		$\hat{f}$: EEGNet		$\hat{f}$: DeepCNN	
Datasets	Clean	Attack	Clean	Attack	Clean	Attack	Clean	Attack	Clean	Attack	Clean	Attack
Emotion	0.458	0.781	0.485	0.938	0.516	0.813	0.490	0.936	0.516	0.863	0.497	0.779
	0.026	0.051	0.034	0.016	0.019	0.044	0.029	0.018	0.019	0.006	0.037	0.053
Motor	0.316	1.000	0.265	0.946	0.309	1.000	0.264	0.972	0.306	1.000	0.306	1.000
	0.001	0.000	0.001	0.020	0.014	0.000	0.000	0.006	0.017	0.000	0.009	0.000
Epilepsy	0.442	0.759	0.469	0.806	0.448	0.943	0.445	0.813	0.448	0.926	0.427	0.850
	0.027	0.069	0.025	0.059	0.029	0.001	0.001	0.052	0.029	0.018	0.042	0.022

5.1.4 ATTACK PERFORMANCE WITH DIFFERENT HYPERPARAMETERS

We investigate the influences of three different hyperparameters: poisoning rate ρ, frequency injection rate β, and electrode injection rate γ. The performance of attacking EEGNet on the ED dataset are displayed in Fig 3. It can be seen that the ASRs are positively correlated with poisoning rate. Note that it is non-trivial for multi-target class attack, thus the ASR is not high compared to the single class attack. Professor X outperforms other attacks in all cases and is robust to the change of β and γ.

Figure 3: Clean (/C) and attack (/B) performance with different poisoning or injection rates.

5.2 ROBUSTNESS OF PROFESSOR X

In this section, we evaluate the robustness of our Professor X against different EEG preprocessing method and various representative backdoor defenses.

5.2.1 ROBUSTNESS AGAINST EEG PREPROCESSING METHODS

To develop an EEG BCI, it is very common to preprocess the raw EEG signals, *e.g.*, 1) band-stop filtering and 2) down-sampling. An EEG backdoor attack is impractical in real scenarios if it is no longer effective when the target model is trained with the preprocessed poisoned EEG. Hence, we must take the robustness against preprocessing methods into account, which is widely ignored in the image backdoor attack field. The performance of each method facing different preprocessing methods are presented in Table 5. It can be observed that our Professor X is robust in all cases. However, when removing the DIS loss, the performance of Professor X decreases a lot after EEG preprocessing, especially facing the 30 Hz high-stop filtering preprocessing due to the HF loss that encourages the policy network learns to injecting high frequency.

Table 5: Clean and attack performance on three datasets after different EEG preprocessing methods. The target model is EEGNet. M w.o. DIS means removing the DIS loss in Professor X.

	Preprocessing	No defense		20 Hz low		30 Hz high		25% down		Average
	Method	Clean	Attack	Clean	Attack	Clean	Attack	Clean	Attack	ASR
ER	Professor X	0.535	0.857	0.512	0.829	0.463	0.892	0.518	0.908	0.876
	w/o DIS	0.506	0.859	0.492	0.816	0.466	0.333	0.498	0.807	0.652
MI	Professor X	0.323	1.000	0.285	1.000	0.329	1.000	0.321	1.000	1.000
	w/o DIS	0.298	1.000	0.264	1.000	0.322	0.250	0.284	0.990	0.746
ED	Professor X	0.497	0.944	0.492	0.914	0.494	0.856	0.516	0.818	0.920
	w/o DIS	0.515	0.250	0.477	0.864	0.508	0.250	0.510	0.249	0.454

5.2.2 ROBUSTNESS AGAINST NEURAL CLEANSE: TRIGGER INVERSION

Neural Cleanse (NC) (Wang et al., 2019) calculate a metric called Anomaly Index by reconstructing trigger pattern for each possible label. The Anomaly Index is positively correlated with the size of the reconstruction trigger. A model with Anomaly Index > 2 is considered to be backdoor-injected. We display the Anomaly Indexes of the clean models and the backdoor-injected model by Professor X in Fig 4. It can be seen that Professor X can easily bypass NC. The reconstructed trigger patterns on three datasets are presented in Appendix G.1.

Figure 4: Anomaly Index of three models on three datasets.

5.2.3 ROBUSTNESS AGAINST STRIP: INPUT PERTURBATION

We evaluate the robustness of Professor X against STRIP (Gao et al., 2019), which perturbs the input EEG and calculates the entropy of the predictions of these perturbed EEG data. Based on the assumption that the trigger is still effective after perturbation, the entropy of backdoor input tends to be lower than that of the clean one. The results are plotted in Fig 5, it can be seen that the entropy distributions of the backdoor and clean samples are similar.

Figure 5: Performance against STRIP on three datasets, the target model is EEGNet.

5.2.4 ROBUSTNESS AGAINST SPECTRAL SIGNATURE: LATENT SPACE CORRELATION

Spectral Signature (Tran et al., 2018) detects the backdoor samples by statistical analysis of clean data and backdoor data in the latent space. Following the same experimental settings in (Tran et al.,

2018), we randomly select 5,000 clean samples and 500 Professor X backdoor samples and plot the histograms of the correlation scores in Fig 6. There is no clear separation between these two sets of samples, showing the stealthiness of Professor X backdoor samples in the latent space.

Figure 6: Performance against Spectral Signature on three datasets, the target model is EEGNet.

5.2.5 ROBUSTNESS AGAINST FINE-PRUNING

We evaluate the robustness of Professor X against Fine-Pruning (Liu et al., 2018), a model analysis based defense which finds a classifier's low-activated neurons given a small clean dataset. Then it gradually prunes these low-activated neurons to mitigate the backdoor without affecting the CA. We can observe from Fig 7 that the ASR drops considerably small when pruning ratio is less than 0.7, suggesting that the Fine-Pruning is ineffective against Professor X.

Figure 7: Performances of EEGNet against Fine-Pruning on three datasets.

5.3 VISUALIZATION OF BACKDOOR ATTACK SAMPLES

To evade from human perception (**C2** in Section 3.2), we design to obatin injecting strategies with HF loss. It can be seen from the bottom row of Fig 8 that Professor X (with HF loss) generates stealthy poisoned EEG, which is almost the same as the clean EEG, demonstrating the **High Stealthiness**. More visualization on three datasets are presented in Appendix G.2.

Figure 8: The Clean EEG (Blue), Trigger-injected EEG (Orange) and the Residual (Red) of the ED dataset. (*x*-axis: timepoints, *y*-axis: amplitude.)

5.4 STEALTHINESS AGAINST DETECTION

To verify that the trigger of Professor X are invisible, we employ anomaly detection methods, GDN (Deng & Hooi, 2021) and USAD (Audibert et al., 2020). Specifically, for each dataset, we train anomaly detection methods on the clean test set $\mathcal{D}_{test}$ and then record the F1-score and the Area under the ROC Curve (ROC-AUC) on the set $= \mathcal{S}_p \cup \mathcal{D}_p$. The experimental results are presented in Table 6. The ROC-AUC is around 0.5 and F1-score is either around 0.5 or near 0 across all datasets, indicating that the detection results are nearly random guess. These strongly demonstrates the stealthiness of Professor X.

Table 6: Results of anomaly detection.

Anomaly Detection	ER		MI		ED	
	F1	AUC	F1	AUC	F1	AUC
GDN	0.50	0.50	0.50	0.51	0.50	0.50
USAD	0.00	0.51	0.00	0.51	0.00	0.50

6 CONCLUSION

In this paper, we proposed Professor X, a novel EEG backdoor for manipulating EEG BCI, where the adversary can arbitrarily control the output for any input samples. To the best of our knowledge, Professor X is the first method that considers which EEG electrodes and frequencies to be injected for different EEG tasks and formats. We specially design the reward function in RL to enhance the robustness and stealthiness. Experimental results showcase the effectiveness, robustness, and generalizability of Professor X. This work alerts the EEG community of the potential danger of the vulnerability of EEG BCI against BA and calls for defensive studies for EEG modality. It is worth noting that Professor X can also be applied for protecting intellectual properties of EEG datasets and BCI models, offering a concealed and harmless approach to add authors' watermark (backdoor can be regarded as watermark), indicating the real-world application of Professor X.

REFERENCES

Ijaz Ahmad, Xin Wang, Mingxing Zhu, Cheng Wang, Yao Pi, Javed Ali Khan, Siyab Khan, Oluwarotimi Williams Samuel, Shixiong Chen, Guanglin Li, et al. EEG-based epileptic seizure detection via machine/deep learning approaches: a systematic review. *Computational Intelligence and Neuroscience*, 2022, 2022.

Hamdi Altaheri, Ghulam Muhammad, Mansour Alsulaiman, Syed Umar Amin, Ghadir Ali Altuwaijri, Wadood Abdul, Mohamed A Bencherif, and Mohammed Faisal. Deep learning techniques for classification of electroencephalogram (EEG) motor imagery (MI) signals: A review. *Neural Computing and Applications*, 35(20):14681–14722, 2023.

Santiago Arroyo and Sumio Uematsu. High-frequency eeg activity at the start of seizures. *Journal of Clinical Neurophysiology*, 9(3):441–448, 1992.

Julien Audibert, Pietro Michiardi, Frédéric Guyard, Sébastien Marti, and Maria A Zuluaga. Usad: Unsupervised anomaly detection on multivariate time series. In *Proceedings of the 26th ACM SIGKDD international conference on knowledge discovery & data mining*, pp. 3395–3404, 2020.

Muhammad Zeeshan Baig, Nauman Aslam, and Hubert PH Shum. Filtering techniques for channel selection in motor imagery EEG applications: a survey. *Artificial Intelligence Review*, 53(2): 1207–1232, 2020.

Mauro Barni, Kassem Kallas, and Benedetta Tondi. A new backdoor attack in cnns by training set corruption without label poisoning. In *2019 IEEE International Conference on Image Processing (ICIP)*, pp. 101–105. IEEE, 2019.

Warren T Blume, G Bryan Young, and John F Lemieux. EEG morphology of partial epileptic seizures. *Electroencephalography and Clinical Neurophysiology*, 57(4):295–302, 1984.

Clemens Brunner, Robert Leeb, Gernot Müller-Putz, Alois Schlögl, and Gert Pfurtscheller. BCI competition 2008–graz data set A. *Institute for Knowledge Discovery (Laboratory of Brain-Computer Interfaces), Graz University of Technology*, 16:1–6, 2008.

Xinyun Chen, Chang Liu, Bo Li, Kimberly Lu, and Dawn Song. Targeted backdoor attacks on deep learning systems using data poisoning. *arXiv preprint arXiv:1712.05526*, 2017.

Ailin Deng and Bryan Hooi. Graph neural network-based anomaly detection in multivariate time series. In *Proceedings of the AAAI conference on artificial intelligence*, volume 35, pp. 4027–4035, 2021.

Daizong Ding, Mi Zhang, Yuanmin Huang, Xudong Pan, Fuli Feng, Erling Jiang, and Min Yang. Towards backdoor attack on deep learning based time series classification. In *2022 IEEE 38th International Conference on Data Engineering (ICDE)*, pp. 1274–1287. IEEE, 2022.

Khoa Doan, Yingjie Lao, Weijie Zhao, and Ping Li. Lira: Learnable, imperceptible and robust backdoor attacks. In *Proceedings of the IEEE/CVF international conference on computer vision (ICCV)*, pp. 11966–11976, 2021.

Khoa D Doan, Yingjie Lao, and Ping Li. Marksman backdoor: Backdoor attacks with arbitrary target class. *Advances in Neural Information Processing Systems (NeurIPS)*, 35:38260–38273, 2022.

Yu Feng, Benteng Ma, Jing Zhang, Shanshan Zhao, Yong Xia, and Dacheng Tao. Fiba: Frequency-injection based backdoor attack in medical image analysis. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 20876–20885, 2022.

Yansong Gao, Change Xu, Derui Wang, Shiping Chen, Damith C Ranasinghe, and Surya Nepal. STRIP: A defence against trojan attacks on deep neural networks. In *Proceedings of the 35th Annual Computer Security Applications Conference*, pp. 113–125, 2019.

Yudong Gao, Honglong Chen, Peng Sun, Junjian Li, Anqing Zhang, Zhibo Wang, and Weifeng Liu. A dual stealthy backdoor: From both spatial and frequency perspectives. In *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, volume 38, pp. 1851–1859, 2024.

Stephen V Gliske, Zachary T Irwin, Kathryn A Davis, Kinshuk Sahaya, Cynthia Chestek, and William C Stacey. Universal automated high frequency oscillation detector for real-time, long term eeg. *Clinical Neurophysiology*, 127(2):1057–1066, 2016.

Tianyu Gu, Kang Liu, Brendan Dolan-Gavitt, and Siddharth Garg. BadNets: Evaluating backdooring attacks on deep neural networks. *IEEE Access*, 7:47230–47244, 2019.

Hasan Abed Al Kader Hammoud and Bernard Ghanem. Check your other door! creating backdoor attacks in the frequency domain. *arXiv preprint arXiv:2109.05507*, 2021.

Pawel Herman, Girijesh Prasad, Thomas Martin McGinnity, and Damien Coyle. Comparative analysis of spectral approaches to feature extraction for EEG-based motor imagery classification. *IEEE Transactions on Neural Systems and Rehabilitation Engineering*, 16(4):317–326, 2008.

Ruitao Hou, Teng Huang, Hongyang Yan, Lishan Ke, and Weixuan Tang. A stealthy and robust backdoor attack via frequency domain transform. *World Wide Web (WWW)*, 26(5):2767–2783, 2023.

Mahboobeh Jafari, Afshin Shoeibi, Marjane Khodatars, Sara Bagherzadeh, Ahmad Shalbaf, David López García, Juan M Gorriz, and U Rajendra Acharya. Emotion recognition in EEG signals using deep learning methods: A review. *Computers in Biology and Medicine*, pp. 107450, 2023.

Ranjan Jana and Imon Mukherjee. Deep learning based efficient epileptic seizure prediction with EEG channel optimization. *Biomedical Signal Processing and Control*, 68:102767, 2021.

Wenbo Jiang, Hongwei Li, Guowen Xu, and Tianwei Zhang. Color backdoor: A robust poisoning attack in color space. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 8133–8142, 2023a.

Xue Jiang, Lubin Meng, Siyang Li, and Dongrui Wu. Active poisoning: efficient backdoor attacks on transfer learning-based brain-computer interfaces. *Science China Information Sciences*, 66(8): 182402, 2023b.

Yujing Jiang, Xingjun Ma, Sarah Monazam Erfani, and James Bailey. Backdoor attacks on time series: A generative approach. In *2023 IEEE Conference on Secure and Trustworthy Machine Learning (SaTML)*, pp. 392–403. IEEE, 2023c.

Sourabh Katoch, Sumit Singh Chauhan, and Vijay Kumar. A review on genetic algorithm: past, present, and future. *Multimedia tools and applications*, 80:8091–8126, 2021.

MB Kostyunina and MA Kulikov. Frequency characteristics of eeg spectra in the emotions. *Neuroscience and Behavioral Physiology*, 26(4):340–343, 1996.

Vernon J Lawhern, Amelia J Solon, Nicholas R Waytowich, Stephen M Gordon, Chou P Hung, and Brent J Lance. EEGNet: a compact convolutional neural network for EEG-based brain–computer interfaces. *Journal of Neural Engineering*, 15(5):056013, 2018.

Shaofeng Li, Minhui Xue, Benjamin Zi Hao Zhao, Haojin Zhu, and Xinpeng Zhang. Invisible backdoor attacks on deep neural networks via steganography and regularization. *IEEE Transactions on Dependable and Secure Computing*, 18(5):2088–2105, 2020.

Xiao Lin, Zhining Liu, Dongqi Fu, Ruizhong Qiu, and Hanghang Tong. Backtime: Backdoor attacks on multivariate time series forecasting. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024. URL https://openreview.net/forum?id=Kl13lipxTW.

Kang Liu, Brendan Dolan-Gavitt, and Siddharth Garg. Fine-pruning: Defending against backdooring attacks on deep neural networks. In *International Symposium on Research in Attacks, Intrusions, and Defenses*, pp. 273–294. Springer, 2018.

Zihan Liu, Lubin Meng, Xiao Zhang, Weili Fang, and Dongrui Wu. Universal adversarial perturbations for CNN classifiers in EEG-based BCIs. *Journal of Neural Engineering*, 18(4):0460a4, 2021.

Henri Lorach, Andrea Galvez, Valeria Spagnolo, Felix Martel, Serpil Karakas, Nadine Intering, Molywan Vat, Olivier Faivre, Cathal Harte, Salif Komi, et al. Walking naturally after spinal cord injury using a brain–spine interface. *Nature*, 618(7963):126–133, 2023.

Lubin Meng, Xue Jiang, Jian Huang, Zhigang Zeng, Shan Yu, Tzyy-Ping Jung, Chin-Teng Lin, Ricardo Chavarriaga, and Dongrui Wu. EEG-based brain-computer interfaces are vulnerable to backdoor attacks. *IEEE Transactions on Neural Systems and Rehabilitation Engineering*, 2023.

Lubin Meng, Xue Jiang, Xiaoqing Chen, Wenzhong Liu, Hanbin Luo, and Dongrui Wu. Adversarial filtering based evasion and backdoor attacks to EEG-based brain-computer interfaces. *Information Fusion*, pp. 102316, 2024.

Suresh D Muthukumaraswamy. High-frequency brain activity and muscle artifacts in meg/eeg: a review and recommendations. *Frontiers in human neuroscience*, 7:138, 2013.

Tuan Anh Nguyen and Anh Tran. Input-aware dynamic backdoor attack. *Advances in Neural Information Processing Systems (NeurIPS)*, 33:3454–3464, 2020a.

Tuan Anh Nguyen and Anh Tuan Tran. Wanet-imperceptible warping-based backdoor attack. In *International Conference on Learning Representations (ICLR)*, 2020b.

Mohammad Zavid Parvez and Manoranjan Paul. EEG signal classification using frequency band analysis towards epileptic seizure prediction. In *16th Int'l Conf. Computer and Information Technology*, pp. 126–130. IEEE, 2014.

MC Salinsky, BS Oken, and L Morehead. Test-retest reliability in eeg frequency analysis. *Electroencephalography and clinical neurophysiology*, 79(5):382–392, 1991.

Robin Tibor Schirrmeister, Jost Tobias Springenberg, Lukas Dominique Josef Fiederer, Martin Glasstetter, Katharina Eggensperger, Michael Tangermann, Frank Hutter, Wolfram Burgard, and Tonio Ball. Deep learning with convolutional neural networks for EEG decoding and visualization. *Human Brain Mapping*, 38(11):5391–5420, 2017.

Ali H Shoeb and John V Guttag. Application of machine learning to epileptic seizure detection. In *Proceedings of the 27th International Conference on Machine Learning (ICML)*, pp. 975–982, 2010.

Yonghao Song, Qingqing Zheng, Bingchuan Liu, and Xiaorong Gao. EEG conformer: Convolutional transformer for EEG decoding and visualization. *IEEE Transactions on Neural Systems and Rehabilitation Engineering*, 31:710–719, 2022.

Richard S Sutton, David McAllester, Satinder Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. *Advances in Neural Information Processing Systems (NeurIPS)*, 12, 1999.

Brandon Tran, Jerry Li, and Aleksander Madry. Spectral signatures in backdoor attacks. *Advances in Neural Information Processing Systems (NeurIPS)*, 31, 2018.

Kostas M Tsiouris, Vasileios C Pezoulas, Michalis Zervakis, Spiros Konitsiotis, Dimitrios D Koutsouris, and Dimitrios I Fotiadis. A long short-term memory deep learning network for the prediction of epileptic seizures using eeg signals. *Computers in biology and medicine*, 99:24–37, 2018.

Bolun Wang, Yuanshun Yao, Shawn Shan, Huiying Li, Bimal Viswanath, Haitao Zheng, and Ben Y Zhao. Neural Cleanse: Identifying and mitigating backdoor attacks in neural networks. In *2019 IEEE Symposium on Security and Privacy (S&P)*, pp. 707–723. IEEE, 2019.

Tong Wang, Yuan Yao, Feng Xu, Shengwei An, Hanghang Tong, and Ting Wang. An invisible black-box backdoor attack through frequency domain. In *European Conference on Computer Vision (ECCV)*, pp. 396–413. Springer, 2022.

Maurice Weber, Xiaojun Xu, Bojan Karlaš, Ce Zhang, and Bo Li. Rab: Provable robustness against backdoor attacks. In *2023 IEEE Symposium on Security and Privacy (S&P)*, pp. 1311–1328. IEEE, 2023.

Haixu Wu, Tengge Hu, Yong Liu, Hang Zhou, Jianmin Wang, and Mingsheng Long. Timesnet: Temporal 2d-variation modeling for general time series analysis. In *The Eleventh International Conference on Learning Representations*, 2023. URL `https://openreview.net/forum?id=ju_Uqw384Oq`.

Yi Yu, Yufei Wang, Wenhan Yang, Shijian Lu, Yap-Peng Tan, and Alex C Kot. Backdoor attacks against deep image compression via adaptive frequency trigger. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 12250–12259, 2023.

Zenghui Yuan, Pan Zhou, Kai Zou, and Yu Cheng. You are catching my attention: Are vision transformers bad learners under backdoor attacks? In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 24605–24615, 2023.

Yi Zeng, Won Park, Z Morley Mao, and Ruoxi Jia. Rethinking the backdoor attacks' triggers: A frequency perspective. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 16473–16481, 2021.

Xiao Zhang and Dongrui Wu. On the vulnerability of cnn classifiers in eeg-based bcis. *IEEE Transactions on Neural Systems and Rehabilitation Engineering*, 27(5):814–825, 2019.

Wei-Long Zheng and Bao-Liang Lu. Investigating critical frequency bands and channels for EEG-based emotion recognition with deep neural networks. *IEEE Transactions on Autonomous Mental Development*, 7(3):162–175, 2015.

A   KEY SYMBOLS OF PROFESSOR X

In this section, we list all the key symbols used in our paper in Table 7.

Table 7: Key symbols.

Symbol	Definition
x_i	The input data
y_i	The input data's label
x_c^t	The randomly selected trigger from class c (with label c)
x_i^p	The poisoned data of input data x_i
c_{tar}	The target class in the single target class backdoor attacks
E	The number of electrodes of an EEG segment
F	The number of frequency points of an EEG segment after FFT
T	The number of time points of an EEG segment
N	The number of the data points in the training subset
M	The number of the data points in the poisoning subset
α	The interpolating ratio of trigger and clean data
β	The ratio of injection time/frequency points to total time/frequency points
γ	The ratio of injection electrodes to total electrodes
λ	The hyperparameter to balance the ASR reward in reinforcement learning
μ	The hyperparameter to balance the DIS loss in reinforcement learning
ν	The hyperparameter to balance the HF loss in reinforcement learning
ρ	The ratio of the size of the poisoning subset to that of the training set
$\pi_\theta^{c_i}$	The policy network for the selected trigger from class c_i with parameter θ)
θ	The parameter of the policy network
ρ_0	The sampler of initial state
s_i	The state at time point i in reinforcement learning
a_i	The action at time point i in reinforcement learning
r_i	The reward at time point i in reinforcement learning
τ	The trajectory of the whole decision made by policy network
$\hat{g}$	The gradient estimator of a reward taken by a trajectory
η	The learning rate for training policy network
R	The reward function of a trajectory or a single action
K	The iteration numbers of reinforcement learning
$\mathcal{X}$	The distribution of input data
$\mathcal{C}$	The distribution of label/class
$\mathcal{M}_e^{c_i}$	The injecting electrodes set of the selected trigger from class c_i
$\mathcal{M}_f^{c_i}$	The injecting frequencies set of the selected trigger from class c_i
$\mathcal{M}^{c_i}$	The binary mask of the selected trigger from class c_i
$\mathcal{S}$	The set of labeled training data
$\mathcal{T}$	The trigger-injection function
$\mathcal{L}$	The loss function used for training a classifier
$\mathcal{D}$	The dataset used for training a classifier
$\mathcal{D}_{train}$	The subset of $\mathcal{S}$ used for training the target model
$\mathcal{D}_{test}$	The subset of $\mathcal{S}$ used for testing the target model
$\mathcal{D}_p$	The subset of $\mathcal{S}$ used for poisoning the target model
$\mathcal{S}_p$	The set of generated poisoned data using the subset $\mathcal{D}_p$
$\mathcal{F}$	The fast Fourier transform
$\mathcal{A}_x$	The amplitude of data x after FFT
$\mathcal{P}_x$	The phase of data x after FFT
f	The target classifier model
$\hat{f}$	The target model in the trigger transfer experiments

B LIMITATIONS

Our Professor X is a backdoor attack in the frequency domain, which requires to transform the EEG signals into frequency domain through fast Fourier transform (FFT) and return to temporal domain through inverse FFT (iFFT). The operation of FFT and iFFT in the trigger injection function are a little more time-consuming compared to other backdoor attack directly in the temporal domain, like PatchMT Gu et al. (2019) and PulseMT Meng et al. (2023). Future effort will be devoted into the faster implementation of FFT and iFFT, for example, taking the advantage of modern GPUs.

It is a little more time-consuming for the reinforcement learning to acquire the optimal strategies for each trigger. However, we can obtain a general injecting strategy for each EEG BCI tasks, which can achieve a relatively good performance without reinforcement learning, as we can see from Table 4 that random injection strategy has an acceptable performance.

C BROADER IMPACTS

With the rapid development of techniques, EEG BCIs gain a wide range of applications from health care to human-computer interaction. Some companies like Neuralink adopt the EEG BCI to assist paralytic patients helping themselves in daily lives. However, if the EEG BCI is backdoor attacked by Professor X, which allows the attacker to arbitrarily control BCI's outputs, the BCI users may fall into tremendous fatal troubles. For instance, one paralytic patient controls his/her wheelchair by EEG BCI, the attacker can manipulate the wheelchair to run down a steep staircase. For an epileptic patient, the attacker can let all the output be Normal State, even when the patient is experiencing an epileptic seizure. This paper reveals the severe danger faced by EEG BCIs, demonstrating the possibility that someone can maliciously manipulate the outputs of EEG BCIs with arbitrary target class.

Professor X can also be used for positive purposes, like protecting intellectual property of EEG dataset and EEG models with watermarking. As our Professor X has a very small impact of the clean accuracy, and the poisoning approach is clean label poisoning, Professor X is a fantastic method for watermarking EEG dataset and models.

For a company that provides EEG dataset, it can select different EEG triggers for different customs to generate poisoned data and inject into the dataset provided to customs who buy the dataset. As a result, the company have the information of which trigger is corresponding to which customs, e.g., trigger x is in the dataset provided to custom X, trigger y is in the dataset provided to custom Y. If an EEG model from a company which didn't buy dataset is detected having this watermark (backdoor) with trigger x, the company knows that the custom X leaked the dataset. Similarly, if an EEG model is detected having this watermark (backdoor) with trigger y, the company knows that the custom Y leaked the dataset.

D DATASETS AND PREPROCESSING

In this section, we introduce the three datasets used in our experiments, and explain the preprocessing. We elaborately selected these three datasets because of three reasons: **1)** They cover three different EEG tasks that are important and common in EEG BCI field; **2)** The EEG formats of these datasets vary significantly; **3)** The EEG tasks are all multi class classification tasks, that is, the number of categories is more than two. Experiments on these three datasets can validate the efficacy, manipulating performance, and generalizability of each BA methods as much as possible.

D.1 EMOTION RECOGNITION (ER)

The SJTU Emotion EEG Dataset (SEED) was incoporated as the representative dataset of emotion recogniton tasks Zheng & Lu (2015). It consists of EEG recordings from 15 subjects watching 15 emotional video clips with three repeated session each on different days. Each video clip is supposed to evoke one of the three target emotions: positive, neutral, and negative. The EEG signals were acquired by the 62-channel electrode cap at a sampling rate of 1000 Hz. We performed below preprocessing procedures for the 62-channel EEG signals: 1) Down-sampling from 1000 Hz to 200

Hz, 2) Band-pass filtering at 0.3-50 Hz, 3) Segmenting EEG signals into 1-second (200 timepoints), obtaining 3394 EEG segments in each session for each subject.

D.2 MOTOR IMAGERY (MI)

We employ the BCIC-IV-2a as a representative dataset of MI classification tasks Brunner et al. (2008). It contains EEG recordings in a four-class motor-imagery task from nine subjects with two repeated session each on different days. During the task, the subjects were instructed to imagine four types of movements (*i.e.*, right hand, left hand, feet, and tongue) for four seconds. Each session consists of a total of 288 trials with 72 trials for each type of the motor imagery. The EEG signals were recorded by 22 Ag/AgCl EEG electrodes in a sampling rate of 250 Hz. We segment the 22-channel EEG signals into 1-second segments, resulting in totally 1152 EEG data for each subject.

D.3 EPILEPSY DETECTION (ED)

The CHB-MIT, one of the largest and most used public datasets for epilepsy, is adopted as a representative dataset of ED tasks Shoeb & Guttag (2010). It recorded 877.39 hours of multi-channel EEG in a sampling rate of 256 Hz from 23 pediatric patients with intractable seizures. However, as the montages (*i.e.*, the number and the places of electrodes) of EEG signals vary significantly among different subjects' recordings, we select to use only the EEG recordings with the same 23 channels (see Appendix A) and discard other channels or the recordings don't have all these 23 channels. Due to the purpose is to test whether the backdoor attack works on the ED task, not to study the epilepsy EEG classification, we segment part of the CHB-MIT dataset to form a four-class ED dataset (*i.e.*, the preictal, ictal, postictal, and interictal phases). Specifically, for a ictal phase EEG recording of t_i seconds from $[s_i, e_i]$ timepoints, we segment the $[s_i - t_i, e_i]$ EEG as the preictal phase, the $[e_i, e_i + t_i]$ EEG as the postictal phase, and another t_i seconds EEG recordings as the interictal phase which satisfying there is no ictal phase within half an hour before or after. Then we segment the 23-channel EEG signals into 1-second segments, consequently, there are 41336 segments left in total from all subjects, 10334 for each phase. As the imbalanced amount of data across different subjects, we separate these 41336 segments into 10 groups and treat the ten groups as 10 subjects.

E IMPLEMENTATION DETAILS

E.1 EXPERIMENT COMPUTING RESOURCES

We use two servers for conducting our experiments. A server with one Nvidia Tesla V100 GPU is used for running reinforcement learning, the CUDA version is 12.3. Another server with four Nvidia RTX 3090 GPUs is used for running the backdoor attacks, the CUDA version is 11.4.

E.2 DETAILS OF BASELINE METHODS

In our Professor X backdoor attacks, for an EEG segment $x_i \in \mathbb{R}^{E \times T}$, we modify the βF frequency-points and γE electrodes of a EEG segments with a constant number.

There are four baseline methods in our study for multi-target backdoor attacks, two of them are non-stealthy attacks (**PatchMT** and **PulseMT**) and two are stealthy attacks (**CompressMT** and **AdverseMT**). In order to achieve a fair comparison, we modify only first γE electrodes for all baseline attack methods. For the non-stealthy attacks, which are all on the temporal domains, we modify βT timepoints of EEG signals. For the stealthy attacks, there is no constraint of the numbers of the modify timepoints as these attacks achieve stealthiness in another way.

For each baseline method, we try our best to find out the best performance, as demonstrated below. We promise that we did not maliciously lower the performances of the baseline methods.

E.2.1 PATCHMT

PatchMT is a multi-trigger and MT extension of BadNets Gu et al. (2019) where we fill the first βT timepoints and γE electrodes of a EEG segments with a constant number. Specifically, for an EEG segment $x_i \in \mathbb{R}^{E \times T}$, we set the first γE electrodes and the first βT timepoints of the EEG segment

to a constant number. We normalize the EEG segment $x_i \in \mathbb{R}^{E \times T}$ to let $\mathbf{x}_i$'s mean is 0 and std is 1. Then set the first γE electrodes and the first βT timepoints of $\mathbf{x}_i$ to a different constant number for different class. The constant number for each class of $\{0, 1, 2, 3\}$ for four classes, and $\{-0.1, 0.0, 1.0\}$ for three classes. Finally, denormalize $\mathbf{x}_i$ to original signal x_i's scale to generate x_i^p.

Although we try our best to find the best performance of PatchMT, and BadNets Gu et al. (2019) is really efficient in image backdoor attacks, PatchMT cannot have satisfactory results in EEG BCI attack.

E.2.2 PULSEMT

For PulseMT, we met the same questions as the PatchMT: how to identify the amplitude of each NPP signal for each class? If the numbers are too large then normal EEG signals, it will be unfair. If the numbers are too small, the efficacy of PulseMT is too negative.

We normalize the EEG segment $x_i \in \mathbb{R}^{E \times T}$ to let $\mathbf{x}_i$'s mean is 0 and std is 1. The constant amplitude for each class of $\{-0.8, -0.3, 0.3, 0.8\}$. Finally, denormalize $\mathbf{x}_i$ to original signal x_i's scale to generate x_i^p.

E.2.3 COMPRESSMT

Compressing the amplitude of EEG signals in the temporal domain will not change the morphology and the frequency distribution of EEG signals, thus obtaining stealthiness. For three-class Emotion datasets, the compress rate is $\{0.8, 0.6, 0.4\}$. For four-class Motor Imagery and Epilepsy datasets, the compress rate is $\{0.8, 0.6, 0.4, 0.2\}$.

E.2.4 ADVERSEMT

AdverseMT is another stealthy EEG backdoor attacks, which is the multi-trigger and multi-target extension of adversarial spatial filter attacks Meng et al. (2024), in wihch, for EEG segment $x_i \in \mathbb{R}^{E \times T}$, it learns an Spatial Filter $\mathbf{W} \in \mathbb{R}^{E \times E}$ by the adversarial loss to let the model f misclassify x_i:

$$\min_{\mathbf{W}} \mathbb{E}_{(x_i, y_i) \sim \mathcal{D}}[-\mathcal{L}_{CE}(\mathbf{W}x_i, y_i) + \alpha \mathcal{L}_{MSE}(\mathbf{W}x_i, x_i)], \tag{10}$$

However, the original version of Meng et al. (2024) requires the access to all training dataset $\mathcal{D}$ and the control of the training process of the model f. We modify the AdverseMT to only access to the training dataset $\mathcal{D}_{train}$. Note that the adversarial loss dose not have the special design for multi-target backdoor attacks, we only run the process c times for obtaining c spatial filters for different classes. So the poisoned subset are $\mathcal{S}_p = \{(\mathbf{W}_0(x), 0), (\mathbf{W}_1(x), 1), (\mathbf{W}_2(x), 2), (\mathbf{W}_3(x), 3)\}$.

E.3 REINFORCEMENT LEARNING POLICY NETWORK ARCHITECTURE

Here, we design a concise but effective convolutional neural networks as the our policy network, which is defined as belows:

Table 8: The Architecture of Policy Network

Layer	In	Out	Kernel	Stride
Conv2d	1	32	(1, 3)	(1, 1)
BatchNorm2d				
ELU				
AvgPool2d				(1,2)
Conv2d	32	64	(1, 3)	(1, 1)
BatchNorm2d				
ELU				
AvgPool2d				(1,2)
AdaptiveAvgPool2d				(1, 1)
Flatten				
Linear	64	256		

E.4 TARGET EEG BCIS' NETWORK ARCHITECTURE

Three mostly-used EEG BCI models in real-world applications are investigated in our experiments, covering convolutional neural network (CNN) and recurrent neural network (RNN): 1) EEGNet (Lawhern et al., 2018), 2) DeepCNN (Schirrmeister et al., 2017), 3) LSTM Tsiouris et al. (2018). Below we detail the architecture of each network. The EEGNet and DeepCNN are almost the same as the original paper (modified a little for cross-subject setting), LSTM comprises an embedding layer, a one-layer LSTM and a linear classifiers.

EEGNet is a compact and concise convolutional network for EEG BCI, having been proven to be effective in a variety of EEG fields with only 3 convolutional layers. DeepCNN is a little bit deeper than EEGNet, which comprises 4 blocks, 5 convolutional layers in total. The LSTM written by us, as demonstrated in Table 11, is a very shallow network. Our goal is to develop a model-agnostic BA method for EEG modality.

Table 9: The Architecture of EEGNet

Layer	Kernel	Input Size	Output Size
$16 \times$ Conv1d	$(C, 1)$	$C \times T$	$16 \times 1 \times T$
BatchNorm		$16 \times 1 \times T$	$16 \times 1 \times T$
Transpose		$16 \times 1 \times T$	$1 \times 16 \times T$
Dropout	0.25	$1 \times 16 \times T$	$1 \times 16 \times T$
$4 \times$ Conv2d	(2×32)	$1 \times 16 \times T$	$4 \times 16 \times T$
BatchNorm		$4 \times 16 \times T$	$4 \times 16 \times T$
Maxpool2D	(2,4)	$4 \times 16 \times T$	$4 \times 8 \times T/4$
Dropout	0.25	$4 \times 8 \times T/4$	$4 \times 8 \times T/4$
$4 \times$ Conv2d	(8×4)	$4 \times 8 \times T/4$	$4 \times 8 \times T/4$
BatchNorm		$4 \times 8 \times T/4$	$4 \times 8 \times T/4$
Maxpool2D	(2,4)	$4 \times 8 \times T/4$	$4 \times 4 \times T/16$
Dropout	0.25	$4 \times 4 \times T/16$	$4 \times 4 \times T/16$
Softmax Regression		$4 \times 4 \times T/16$	Class Number

Table 10: The Architecture of DeepCNN

Layer	Kernel	Input Size	Output Size
$F_1 \times$ Conv1d	$(1, 32)$	$C \times T$	$F_1 \times C \times T$
BatchNorm		$F_1 \times 1 \times T$	$F_1 \times 1 \times T$
$F_1 \times$ Conv1d	$(C, 1)$	$F_1 \times C \times T$	$F_1 \times 1 \times T$
BatchNorm		$F_1 \times 1 \times T$	$F_1 \times 1 \times T$
MaxPooling	(1,2)	$F_1 \times 1 \times T$	$F_1 \times 1 \times T/2$
Dropout	0.25	$F_1 \times 1 \times T/2$	$F_1 \times 1 \times T/2$
$F_2 \times$ Conv2d	(1×10)	$F_1 \times 1 \times T/2$	$F_2 \times 1 \times T/2$
BatchNorm		$F_2 \times 1 \times T/2$	$F_2 \times 1 \times T/2$
Maxpool2D	(1,2)	$F_2 \times 1 \times T/2$	$F_2 \times 1 \times T/4$
Dropout	0.25	$F_2 \times 1 \times T/4$	$F_2 \times 1 \times T/4$
$F_3 \times$ Conv2d	(1×10)	$F_2 \times 1 \times T/4$	$F_3 \times 1 \times T/4$
BatchNorm		$F_3 \times 1 \times T/4$	$F_3 \times 1 \times T/4$
Maxpool2D	(1,4)	$F_3 \times 1 \times T/4$	$F_3 \times 1 \times T/16$
Dropout	0.25	$F_3 \times 1 \times T/16$	$F_3 \times 1 \times T/16$
$F_4 \times$ Conv2d	(1×4)	$F_3 \times 1 \times T/16$	$F_4 \times 1 \times T/16$
BatchNorm		$F_4 \times 1 \times T/16$	$F_4 \times 1 \times T/16$
Maxpool2D	(1,4)	$F_4 \times 1 \times T/16$	$F_4 \times 1 \times T/64$
Dropout	0.25	$F_4 \times 1 \times T/64$	$F_4 \times 1 \times T/64$
Softmax Regression		$F_4 \times 1 \times T/64$	Class Number

Table 11: The Architecture of LSTM, n is the embedding size.

Layer	Input Size	Output Size
Linear	$C \times T$	$n \times T$
ReLU		
Linear	$n \times T$	$n \times T$
LSTM	$n \times T$	$n \times T$
Softmax Regression	$n \times T$	Class Number

F ATTACK PERFORMANCE OF PROFESSOR X

F.1 DIFFERENT POISONING RATES

We present the performance of each backdoor attacks' performance under different poisoning rates in Table 12. We can see that our Professor X outperforms other baseline at all poisoning rates, demonstrating the superiority of Professor X. Note that the performance of Professor X on the MI dataset is significantly robust to low poisoning rates, i.e., ASR of 1.000 when $\rho = 0.05$.

F.2 HYPERPARAMETER ANALYSIS: FREQUENCY AND ELECTRODES INJECTION RATIO

We present the performance of each backdoor attacks performance under different rates in Table 13 and Table 14. It can be observed with the increment of β and γ, the attack performance increases. Because the trigger is bigger in clean EEG data.

F.3 HYPERPARAMETER ANALYSIS IN REINFORCEMENT LEARNING

We applied the following reward function to acquire the optimal mask strategies for each triggers:

$$Q_t = \text{CA} + \lambda \, \text{ASR} + \mu \, \text{dis}(\mathcal{M}_f^{c_i}) + \nu \min(\mathcal{M}_f^{c_i}), \tag{11}$$

where the first part means the clean accuracy, the second part means the attack success rate, the third part is aiming to scatter the injection positions in various frequency bands, and the fourth part is aiming to inject as high frequencies in EEG signals as possible. Here, we give a simple example to demonstrate the reward function. For an 10 timepoints long EEG segment x_i, $\widetilde{x}_i = \mathcal{F}(x_i)$. If the $\mathcal{M}_f^{c_i} = \{2, 3, 5, 7, 9\}$, because the minimal distance between each pair in $\mathcal{M}_f^{c_i}$ is $|2 - 3| = 1$, thus $\text{dis}(\mathcal{M}_f^{c_i}) = 1$. The $\min(\mathcal{M}_f^{c_i})$ means the lowest position in $\mathcal{M}_f^{c_i}$, thus $\min(\mathcal{M}_f^{c_i}) = 2$.

The analysis of the λ are presented in Table 15. When λ increase, the Attack performance increases while the Clean performance declines slightly.

Table 15: Clean (/C) and attack (/B) performance with ASR's hyperparameter λ, $\mu = 0.3, \nu = 0.005$

	Dataset	Emotion		Motor Imagery		Epilepsy	
	Method	Clean	Attack	Clean	Attack	Clean	Attack
0.5	Professor X	$0.542_{\pm 0.03}$	$0.847_{\pm 0.04}$	$0.327_{\pm 0.02}$	$1.000_{\pm 0.01}$	$0.500_{\pm 0.04}$	$0.922_{\pm 0.04}$
1.0	Professor X	$0.537_{\pm 0.02}$	$0.855_{\pm 0.03}$	$0.325_{\pm 0.02}$	$1.000_{\pm 0.01}$	$0.482_{\pm 0.03}$	$0.935_{\pm 0.05}$
2	Professor X	$0.535_{\pm 0.03}$	$0.857_{\pm 0.02}$	$0.323_{\pm 0.02}$	$1.000_{\pm 0.01}$	$0.477_{\pm 0.04}$	$0.944_{\pm 0.02}$

Table 12: Clean (/C) and attack (/B) performance with different poisoning rates for Professor X and other baseline methods. The target model is EEGNet for all cases.

ρ	Dataset	Emotion		Motor Imagery		Epilepsy	
	Method	Clean	Attack	Clean	Attack	Clean	Attack
0.05	PatchMT	0.390	0.333	0.281	0.791	0.449	0.365
	PulseMT	0.488	0.337	0.275	0.788	0.473	0.397
	ComprsMT	0.448	0.313	0.269	0.754	0.449	0.329
	Professor X	0.491	0.566	0.321	1.000	0.460	0.667
0.10	PatchMT	0.443	0.334	0.279	0.785	0.452	0.400
	PulseMT	0.445	0.394	0.281	0.796	0.486	0.591
	ComprsMT	0.509	0.323	0.270	0.778	0.446	0.337
	Professor X	0.541	0.718	0.320	1.000	0.452	0.734
0.15	PatchMT	0.455	0.335	0.285	0.805	0.439	0.414
	PulseMT	0.438	0.514	0.280	0.787	0.447	0.669
	ComprsMT	0.488	0.332	0.275	0.792	0.461	0.374
	Professor X	0.528	0.805	0.322	1.000	0.460	0.781
0.20	PatchMT	0.481	0.334	0.277	0.816	0.461	0.451
	PulseMT	0.447	0.555	0.285	0.810	0.451	0.692
	ComprsMT	0.470	0.347	0.270	0.795	0.458	0.394
	Professor X	0.538	0.773	0.321	1.000	0.447	0.799
0.25	PatchMT	0.487	0.335	0.281	0.820	0.444	0.483
	PulseMT	0.466	0.701	0.275	0.815	0.431	0.684
	ComprsMT	0.493	0.335	0.269	0.800	0.462	0.427
	Professor X	0.551	0.836	0.325	1.000	0.447	0.834
0.30	PatchMT	0.459	0.343	0.280	0.809	0.440	0.496
	PulseMT	0.486	0.810	0.272	0.816	0.451	0.716
	ComprsMT	0.499	0.331	0.269	0.825	0.455	0.481
	Professor X	0.526	0.829	0.320	1.000	0.451	0.756
0.35	PatchMT	0.437	0.341	0.285	0.805	0.448	0.510
	PulseMT	0.437	0.767	0.275	0.837	0.482	0.757
	ComprsMT	0.473	0.347	0.265	0.851	0.446	0.517
	Professor X	0.489	0.763	0.321	1.000	0.453	0.910
0.40	PatchMT	0.490	0.345	0.283	0.824	0.460	0.549
	PulseMT	0.454	0.771	0.270	0.825	0.439	0.443
	ComprsMT	0.464	0.361	0.269	0.865	0.437	0.450
	Professor X	0.528	0.849	0.323	1.000	0.477	0.944

Table 13: Clean (/C) and attack (/B) performance with frequency injection rate β, $\gamma = 0.5$

β	Dataset	Emotion		Motor Imagery		Epilepsy	
	Method	Clean	Attack	Clean	Attack	Clean	Attack
0.05	PatchMT	0.411	0.334	0.272	0.801	0.476	0.499
	PulseMT	0.464	0.752	0.265	0.800	0.505	0.670
	Professor X	0.522	0.744	0.319	0.999	0.482	0.923
0.10	PatchMT	0.431	0.363	0.283	0.824	0.482	0.540
	PulseMT	0.460	0.795	0.270	0.825	0.486	0.704
	Professor X	0.522	0.813	0.323	1.000	0.500	0.944
0.15	PatchMT	0.413	0.371	0.275	0.821	0.464	0.587
	PulseMT	0.449	0.701	0.271	0.821	0.477	0.632
	Professor X	0.532	0.848	0.322	0.998	0.477	0.947
0.20	PatchMT	0.390	0.377	0.271	0.829	0.479	0.644
	PulseMT	0.434	0.769	0.270	0.819	0.484	0.606
	Professor X	0.529	0.882	0.325	0.999	0.486	0.950
0.25	PatchMT	0.406	0.385	0.267	0.835	0.491	0.673
	PulseMT	0.491	0.705	0.275	0.832	0.478	0.566
	Professor X	0.519	0.865	0.328	0.999	0.486	0.941
0.30	PatchMT	0.417	0.382	0.269	0.831	0.464	0.706
	PulseMT	0.425	0.708	0.273	0.844	0.488	0.592
	Professor X	0.521	0.862	0.330	0.999	0.495	0.940
0.35	PatchMT	0.435	0.373	0.270	0.841	0.475	0.734
	PulseMT	0.423	0.621	0.276	0.839	0.479	0.589
	Professor X	0.527	0.850	0.332	0.998	0.496	0.947
0.40	PatchMT	0.438	0.378	0.271	0.843	0.469	0.751
	PulseMT	0.481	0.624	0.272	0.845	0.485	0.592
	Professor X	0.521	0.893	0.330	0.999	0.501	0.951
0.45	PatchMT	0.460	0.385	0.266	0.844	0.481	0.742
	PulseMT	0.429	0.633	0.277	0.856	0.499	0.601
	Professor X	0.519	0.877	0.325	0.999	0.492	0.962
0.50	PatchMT	0.423	0.386	0.263	0.840	0.480	0.752
	PulseMT	0.459	0.514	0.273	0.851	0.492	0.610
	Professor X	0.528	0.893	0.329	1.000	0.497	0.970

Table 14: Clean (/C) and attack (/B) performance with electrodes injection rate γ, $\beta = 0.1$

γ	Dataset	Emotion		Motor Imagery		Epilepsy	
	Method	Clean	Attack	Clean	Attack	Clean	Attack
0.10	PatchMT	0.431	0.334	0.268	0.795	0.470	0.529
	PulseMT	0.425	0.498	0.269	0.802	0.502	0.717
	ComprsMT	0.407	0.349	0.271	0.805	0.482	0.656
	Professor X	0.489	0.485	0.235	0.367	0.499	0.814
0.20	PatchMT	0.473	0.335	0.271	0.805	0.464	0.599
	PulseMT	0.469	0.707	0.270	0.816	0.502	0.737
	ComprsMT	0.465	0.363	0.268	0.812	0.514	0.704
	Professor X	0.481	0.709	0.235	0.367	0.486	0.860
0.30	PatchMT	0.423	0.343	0.272	0.803	0.486	0.613
	PulseMT	0.488	0.767	0.273	0.814	0.506	0.749
	ComprsMT	0.451	0.398	0.271	0.811	0.494	0.700
	Professor X	0.500	0.743	0.235	0.367	0.490	0.883
0.40	PatchMT	0.453	0.343	0.270	0.812	0.478	0.525
	PulseMT	0.467	0.786	0.271	0.816	0.498	0.688
	ComprsMT	0.443	0.361	0.270	0.820	0.506	0.634
	Professor X	0.491	0.767	0.235	0.367	0.478	0.912
0.50	PatchMT	0.431	0.363	0.270	0.813	0.472	0.552
	PulseMT	0.460	0.795	0.269	0.819	0.471	0.710
	ComprsMT	0.430	0.366	0.269	0.821	0.503	0.640
	Professor X	0.522	0.813	0.235	0.367	0.477	0.944
0.60	PatchMT	0.452	0.377	0.267	0.819	0.480	0.549
	PulseMT	0.460	0.808	0.269	0.823	0.490	0.672
	ComprsMT	0.459	0.368	0.271	0.826	0.499	0.534
	Professor X	0.488	0.828	0.235	0.367	0.495	0.950
0.70	PatchMT	0.443	0.368	0.272	0.812	0.497	0.525
	PulseMT	0.437	0.809	0.270	0.821	0.459	0.716
	ComprsMT	0.456	0.366	0.273	0.835	0.492	0.571
	Professor X	0.527	0.853	0.235	0.367	0.489	0.955
0.80	PatchMT	0.461	0.383	0.268	0.821	0.479	0.573
	PulseMT	0.456	0.771	0.267	0.829	0.488	0.699
	ComprsMT	0.431	0.383	0.270	0.833	0.488	0.475
	Professor X	0.539	0.865	0.235	0.367	0.489	0.960
0.90	PatchMT	0.439	0.400	0.271	0.817	0.478	0.540
	PulseMT	0.461	0.811	0.269	0.823	0.494	0.694
	ComprsMT	0.459	0.389	0.274	0.836	0.490	0.309
	Professor X	0.520	0.824	0.235	0.367	0.489	0.970
1.00	PatchMT	0.430	0.370	0.267	0.823	0.476	0.526
	PulseMT	0.456	0.794	0.271	0.829	0.482	0.716
	ComprsMT	0.453	0.376	0.269	0.830	0.490	0.334
	Professor X	0.532	0.846	0.235	0.367	0.491	0.978

G MORE VISUALIZATION RESULTS

In this section, we plot the reconstructed triggers and masks on three datasets in Section G.1, then plot more visualizations of backdoor samples in Section G.2, and plot the learning curve of our reinforcement learning in Section G.3.

G.1 NEURAL CLEANSE: RECONSTRUCTION TRIGGER PATTERNS

Here, we present more visualization in Figure 9, Figure 10, and Figure 11 of the reconstructed trigger patterns and mask patterns for each possible label on three dataset (*i.e.*, the CHB-MIT dataset, the BCIC-IV-2a dataset and the SEED dataset) the target model is EEGnet. It can be observed that the reconstructed trigger patterns and mask patterns of the clean models and Professor X backdoor-injected models are very similar to each other. Thus, our Professor X backdoor attack can easily bypass the defense of Neural Cleanse.

Figure 9: The reconstructed trigger patterns and mask patterns for each possible class in the CHB-MIT dataset. The results in the left column are reconstructed based on the clean model, the results in the right column are reconstructed based on the backdoor model. The EEG segments in the CHB-MIT dataset have 23 electrodes and 256 timepoints.

Figure 10: The reconstructed trigger patterns and mask patterns for each possible class in the MI dataset. The results in the left column are reconstructed based on the clean model, the results in the right column are reconstructed based on the backdoor model. The EEG segments in the MI dataset have 22 electrodes and 250 timepoints.

Figure 11: The reconstructed trigger patterns and mask patterns for each possible class in the ER dataset (i.e., SEED dataset). The results in the left column are reconstructed based on the clean model, the results in the right column are reconstructed based on the backdoor model. The EEG segments in the SEED dataset have 62 electrodes and 200 timepoints.

G.2 VISUALIZATION OF BACKDOOR ATTACK SAMPLES

We present more visualization of the backdoor attack samples generated by our Professor X on three datasets in Fig 12, 13, and 14. The x-axis is the timepoints, the y-axis is the normalized amplitude. Top row: w.o. HF loss; Bottom row: with HF loss. Each column indicates each possible class.

Figure 12: The Clean EEG (Blue), Trigger-injected EEG (Orange) and the Residual (Red) of the ER dataset.

Figure 13: The Clean EEG (Blue), Trigger-injected EEG (Orange) and the Residual (Red) of the MI dataset.

Figure 14: The Clean EEG (Blue), Trigger-injected EEG (Orange) and the Residual (Red) of the ED dataset.

G.3 VISUALIZATION OF LEARNING CURVES OF REINFORCEMENT LEARNING

We present the visualization of the learning curves of the reinforcement learning of three dataset in Fig 15. We can see the effectiveness of our reinforcement, which converged within 50 epochs on the ER dataset, that is, only trained 50 backdoor models with different injection strategies. Our RL is more effective on the MI dataset and ED dataset, which finds a good strategy within less 10 epochs. Our RL is robust when learning strategies for different triggers as demonstrated in Fig 15(c) and (d), where the learning curves are quite similar when RL is performing on different triggers.

Figure 15: The learning curves of RL on three datasets. The right column is the curve we sort the (Clean Accuracy and Attack Success Rate) (ACC,ASR) according to the ASR. The backdoor models are all EEGNet.