On the Statistical Efficiency of Reward-Free Exploration in Non-Linear RL

Abstract

We study reward-free reinforcement learning (RL) under general non-linear function approximation, and establish sample efficiency and hardness results under various standard structural assumptions. On the positive side, we propose the RFO-LIVE (Reward-Free OLIVE) algorithm for sample-efficient reward-free exploration under minimal structural assumptions, which covers the previously studied settings of linear MDPs (Jin et al., 2020b), linear completeness (Zanette et al., 2020b) and low-rank MDPs with unknown representation (Modi et al., 2021). Our analyses indicate that the *explorability* or *reachability* assumptions, previously made for the latter two settings, are not necessary statistically for reward-free exploration. On the negative side, we provide a statistical hardness result for both reward-free and reward-aware exploration under linear completeness assumptions when the underlying features are unknown, showing an exponential separation between low-rank and linear completeness settings.

1 Introduction

Designing a reward function which faithfully captures the task of interest remains a central practical hurdle in reinforcement learning (RL) applications. To address this, a series of recent works (Jin et al., 2020a; Zhang et al., 2020b; Wang et al., 2020a; Zanette et al., 2020b; Qiu et al., 2021) investigate the problem of reward-free exploration, where the agent initially interacts with its environment to collect experience ("online phase"), that enables it to perform *offline learning* of near optimal policies for any reward function from a potentially pre-specified class ("offline phase"). Reward-free exploration also provides a basic form of multitask RL, enabling zero-shot generalization, across diverse rewards, and provides a useful primitive in tasks such as representation learning (Agarwal et al., 2020; Modi et al., 2021). So far, most of the study of reward-free RL has focused on tabular and linear function approximation settings, in sharp contrast with the literature on reward-aware RL, where abstract structural conditions identify when general function approximation can be used in a provably sample-efficient manner (Jiang et al., 2017; Jin et al., 2021; Du et al., 2021).

In this paper, we seek to bridge this gap and undertake a systematic study of reward-free RL in a model-free setting with general function approximation. We devise an algorithm, RFOLIVE, which is nontrivially adapted from its reward-aware counterpart (Jiang et al., 2017), and provide polynomial sample complexity guarantees under general conditions that significantly relax the assumptions needed by prior reward-free RL works. Our results produce both algorithmic contributions and important insights about the tractability of reward-free RL, as we summarize below (see also Table 1).

Algorithmic contribution: beyond linearity A unique challenge in reward-free RL is that the agent must exhaustively explore the environment during the online phase, since it does not know which states will be rewarding in the offline phase. A natural idea to tackle this challenge is to deploy a reward-aware RL "base algorithm" with the **0** reward function, since this algorithm must explore

	Setting	Reference
1	Linear MDP	Wang et al. (2020c)
2	Linear completeness + explorability	Zanette et al. (2020b)
3	Completeness + Q-type B-E dimension	**Theorem 1**
4	Completeness + V-type B-E dimension + small $|\mathcal{A}|$	**Theorem 3**
5	Low-rank MDP ($\phi^* \in \Phi$) + small $|\mathcal{A}|$ + reachability	Modi et al. (2021)
6	Linear completeness ($\phi^* \in \Phi$) + small $|\mathcal{A}|$ + explorability + reachability + reward-aware	**Theorem 5** (intractable)

Table 1: Summary of our results and comparisons to most closely related works in reward-free exploration. Blue arrows represent implication ($A \to B$ means B is a consequence of and hence weaker condition than A), and the red assumptions are what prior works need that are avoided by us. For linear settings, the true feature ϕ^* is assumed known unless otherwise specified (e.g., in Rows 5 & 6, ϕ^* is unknown but belongs to a feature class Φ). "B-E" stands for (low) Bellman Eluder dimension (Jin et al., 2021). Row 6 has many assumptions, which make it strong since it is a negative result.

to certify that there is indeed no reward. Prior works adopt this idea with optimistic value-iteration (VI) approaches, which use proxy reward functions to drive the agent to new states. However these optimistic methods rely heavily on linearity assumptions to construct the proxy reward and it is difficult to extend them to general function approximation. Instead of using optimistic VI, our basic building block is the OLIVE[1] algorithm of Jiang et al. (2017), a constraint-gathering and elimination algorithm that is a central workhorse for reward-aware RL with general function approximation. In the online phase of RFOLIVE, we run this algorithm with the **0** reward function, and we save the set of constraints gathered (in the form of *separated* datasets) for use in the offline phase.

Algorithmic contribution: novel offline module Prior works for reward-free RL typically use regression approaches (Ernst et al., 2005; Chen and Jiang, 2019; Jin et al., 2020b) in the offline phase, e.g., FQI (Modi et al., 2021; Zanette et al., 2020b), or its optimistic variants (Zhang et al., 2020b; Wang et al., 2020a). In the offline phase of RFOLIVE, rather than relying on regression, we enforce the constraints gathered in the online phase, which amounts to eliminating functions that have large average Bellman errors on state-distributions visited in the online phase. This generic elimination scheme does not rely on tabular or linear structures and allows us to move beyond these assumptions to obtain reward-free guarantees in much more general settings.

Implications: positive results The major assumptions that enable our sample complexity guarantees are Bellman-completeness (Assumption 2) and low Bellman Eluder dimension (Definition 5 and Definition 7); see Rows 3 and 4 in Table 1. These conditions significantly relax prior assumptions that specialize to linear function approximation. Furthermore, prior works require *explorability/reachability* assumptions, which, roughly speaking, assert that every direction in the feature space can be visited with sufficient probability. These assumptions are often not needed in reward-aware RL but suspected to be necessary for reward-free settings. Our results do not depend on such assumptions, showing that they are not necessary for sample-efficient reward-free exploration either.

Implications: negative results We develop lower bounds, showing that some of the structural assumptions made here are not easily relaxed further. While the settings of linear completeness with known features (Row 3), and low-rank MDPs with unknown features (Row 4) are both independently tractable, we show a hardness result against learning under linear completeness when the features are unknown, even under a few additional assumptions (Row 6).

Taken together, our results take a significant step in bridging the sizeable gap in our understanding of reward-aware and reward-free settings and bring the two closer to an equal footing.

Related work In recent years, we have seen a wide range of results for reward-aware RL under general function approximation (Jiang et al., 2017; Dann et al., 2018; Sun et al., 2019; Wang et al., 2020d; Jin et al., 2021; Du et al., 2021). These works develop statistically efficient algorithms

---

[1]We use the Q-type and V-type versions of OLIVE from Jin et al. (2021) as their structural assumption of low Bellman Eluder dimension subsumes the low Bellman rank assumption in Jiang et al. (2017) (see Proposition 3).

using structural assumptions on the function class. Despite their generality, a trivial extension to the reward-free setting incurs an undesirable linear dependence on the size of the reward class.

There also exists a line of research on reward-free RL in various settings: tabular MDPs (Jin et al., 2020a; Zhang et al., 2020b; Kaufmann et al., 2021; Ménard et al., 2021; Yin and Wang, 2021; Wu et al., 2022), MDPs with linear structure (Wang et al., 2020a; Zhang et al., 2021b; Zanette et al., 2020b; Huang et al., 2021; Wagenmaker et al., 2022), kernel MDPs (Qiu et al., 2021), block/low-rank MDPs (Misra et al., 2020; Agarwal et al., 2020; Modi et al., 2021), multi-agent setting (Bai and Jin, 2020; Liu et al., 2021). Many of these results can be subsumed by ours.

Our offline module uses average Bellman error constraints, which is related to a line of work in offline RL (Xie and Jiang, 2020; Jiang and Huang, 2020; Chen and Jiang, 2022; Zanette and Wainwright, 2022). However, there is only one dataset in the standard offline RL setting, and these works form multiple average Bellman error constraints using an additional helper class for reweighting, and need to impose additional realizability or even completeness-type assumptions on such a class. In contrast, we naturally collect *multiple* datasets in the online phase, and do not require a parametric class for reweighting during offline learning.

2 Preliminaries

Markov Decision Processes (MDPs) We consider a finite horizon episodic Markov decision process (MDP) defined as $M = (\mathcal{X}, \mathcal{A}, P, H)$, where $\mathcal{X}$ is the state space, $\mathcal{A}$ is the action space, $P = (P_0, \ldots, P_{H-1})$ with $P_h : \mathcal{X} \times \mathcal{A} \to \Delta(\mathcal{X})$ is the transition dynamics, and H is the number of timesteps in each episode. If the number of actions is finite, we denote the cardinality $|\mathcal{A}|$ by K. In each episode, an agent generates a trajectory $\tau = \{x_0, a_0, x_1, \ldots, x_{H-1}, a_{H-1}, x_H\}$ by taking a sequence of actions $a_0, \ldots, a_{H-1}$, where x_0 is a fixed starting state and $x_{h+1} \sim P_h(\cdot \mid x_h, a_h)$. For simplicity, we will use $a_{i:j}$ to denote $a_i, \ldots, a_j$ and use the notation $[H]$ to refer to $\{0, 1, \ldots, H-1\}$. We use the notation π to denote a collection of H (deterministic) policy functions $\pi = (\pi_0, \ldots, \pi_{H-1})$, where $\pi_h : \mathcal{X} \to \mathcal{A}$. For any $h \in [H]$ with $h' > h$, we use the notation $\pi_{h:h'}$ to denote the policies $(\pi_h, \pi_{h+1} \ldots, \pi_{h'})$. For any policy π and reward function[2] $R = (R_0, \ldots, R_{H-1})$ with $R_h : \mathcal{X} \times \mathcal{A} \to [0, 1]$, we define the policy-specific action-value (or Q-) function as $Q_{R,h}^\pi(x, a) = \mathbb{E}_\pi[\sum_{h'=h}^{H-1} R(x_{h'}, a_{h'}) \mid x_h = x, a_h = a]$ and state-value function as $V_{R,h}^\pi(x) = \mathbb{E}_\pi[Q_{R,h}^\pi(x, a_h) \mid x_h = x, a_h \sim \pi]$. We also use $v_R^\pi = V_{R,0}^\pi(x_0)$ to denote the expected return of policy π. For any fixed reward function R, there exists a policy π_R^* such that $v_R^* = V_{R,h}^{\pi_R^*}(x) = \sup_\pi V_{R,h}^\pi(x)$ for all $x \in \mathcal{X}$ and $h \in [H]$, where v_R^* denotes the optimal expected return under R. We use $\mathcal{T}_h^R$ to denote the reward-dependent Bellman operator: $\forall f : \mathcal{X} \times \mathcal{A} \to [0, B]$, $(\mathcal{T}_h^R f)(x, a) := R_h(x, a) + \mathbb{E}[\max_{a' \in \mathcal{A}} f(x', a') \mid x' \sim P_h(\cdot | x, a)]$ and similarly define $\mathcal{T}_h^\mathbf{0}$ for the zero reward $\mathbf{0}$. The optimal action-value function (under reward R) Q_R^* satisfies the Bellman optimality equation $Q_{R,h}^* = \mathcal{T}_h^R Q_{R,h+1}^*, \forall h \in [H]$.

Reward-free RL with function approximation We study reward-free RL with value function approximation, wherein, the agent is given a function class $\mathcal{F} = \mathcal{F}_0 \times \ldots \times \mathcal{F}_{H-1}$ where $\mathcal{F}_h : \mathcal{X} \times \mathcal{A} \to [0, H-h-1], \forall h \in [H]$.[3] Without the loss of generality, we assume $\mathbf{0} \in \mathcal{F}_h, \forall h \in [H]$ and $f_H \equiv \mathbf{0}$. We use $V_{f,h}$ to denote the state-value function induced by f, i.e., $V_{f,h}(x) = \max_a f_h(x, a)$ and $\pi_f(x)$ as its greedy policy, i.e., $\pi_{f,h}(x) = \text{argmax}_a f_h(x, a)$. When these functions take x_h as input and there is no confusion, we may drop the subscript h and use $V_f(x_h)$ and $\pi_f(x_h)$.

In reward-free RL, the agent is given access to a reward class $\mathcal{R}$, but the specific reward function is only selected after the agent finishes interacting with the environment. Specifically, the agent operates in two phases: an *online* phase where it explores the given MDP M to collect a dataset of trajectories $\mathcal{D}$ without the reward information, and an *offline* phase, where it uses the collected dataset $\mathcal{D}$ to optimize for any revealed reward function $R \in \mathcal{R}$.

Our goal is to investigate the statistical efficiency of reward-free RL with general non-linear function approximation: how many trajectories does the agent need to collect in the online phase such that in the offline phase, with probability at least $1 - \delta$, for any $R \in \mathcal{R}$, it can compute a near-optimal

---

[2]We study the deterministic reward and initial state for simplicity. Our results easily extend to random ones.
[3]Since $\mathcal{F}$ only captures the reward-independent part, w.l.o.g., we assume $\mathcal{F}_h : \mathcal{X} \times \mathcal{A} \to [0, H - h - 1]$.

policy π_R satisfying $v_R^{\pi_R} \geq v_R^* - \varepsilon$? We measure the statistical efficiency in terms of the structural complexity of function class $\mathcal{F}$, reward class $\mathcal{R}$, horizon H, accuracy ε and failure probability δ.

As structural assumptions, we assume the function class $\mathcal{F}$ is realizable and complete. Realizability requires that the optimal function Q_R^* belongs to the reward-appended class $\mathcal{F} + R$, which is natural in the reward-free setting where the agent uses $\mathcal{F}$ to capture reward-independent information. Completeness requires the Bellman backups of the reward-independent class $\mathcal{F}_{h+1}$ and the reward-dependent class $\mathcal{F}_{h+1} + R_{h+1}$ belong to $\mathcal{F}_h$.

Assumption 1 (Realizability of the function class). *We assume $\forall R \in \mathcal{R}, h \in [H]$, we have $Q_{R,h}^* \in \mathcal{F}_h + R_h$, where $\mathcal{F}_h + R_h = \{f_h + R_h : f_h \in \mathcal{F}_h\}$.*

Assumption 2 (Completeness). *We assume $\forall h \in [H], \mathcal{T}_h^{\mathbf{0}} \mathcal{F}_{h+1}, \mathcal{T}_h^{\mathbf{0}}(\mathcal{F}_{h+1} + \mathcal{R}_{h+1}) \subseteq \mathcal{F}_h$.[4] More specifically, $\forall h \in [H], f_{h+1} \in \mathcal{F}_{h+1}, R_{h+1} \in \mathcal{R}_{h+1}$, we have $\mathcal{T}_h^{\mathbf{0}} f_{h+1}, \mathcal{T}_h^{\mathbf{0}}(f_{h+1} + R_{h+1}) \in \mathcal{F}_h$.*

Next we define the covering number, which measures the statistical capacities of function classes.

Definition 1 (ε-covering number, e.g., Wainwright (2019)). *We use $\mathcal{N}_{\mathcal{F}}(\varepsilon)$ to denote the ε-covering number of a set $\mathcal{F} = \mathcal{F}_0 \times \ldots \times \mathcal{F}_{H-1}$ under metric $\sigma(f, f') = \max_{h \in [H]} \|f_h - f_h'\|_\infty$ for $f, f' \in \mathcal{F}$. We define it as $\mathcal{N}_{\mathcal{F}}(\varepsilon) = \min |\mathcal{F}_{cover}|$ such that $\mathcal{F}_{cover} \subseteq \mathcal{F}$ and for any $f \in \mathcal{F}$, there exists $f' \in \mathcal{F}_{cover}$ that satisfies $\sigma(f, f') \leq \varepsilon$. For the reward class $\mathcal{R}$, $\mathcal{N}_{\mathcal{R}}(\varepsilon)$ is defined in the same way.*

Finally, as our guarantees depend on Bellman Eluder (BE) dimensions—which are structural properties of the MDP that enable sample-efficient exploration—we will need the following definitions (see Russo and Van Roy, 2013; Jin et al., 2021) which the later definitions of BE dimensions will build on.

Definition 2 (ε-independence between distributions). *Let $\mathcal{F}'$ be a function class defined on $\mathcal{X}$, and $\nu, \mu_1, \ldots, \mu_n$ be probability measures over $\mathcal{X}$. We say ν is ε-independent of $\{\mu_i\}_{i=1}^n$ w.r.t. $\mathcal{F}'$ if $\exists f' \in \mathcal{F}'$ s.t. $\sqrt{\sum_{i=1}^n (\mathbb{E}_{\mu_i}[f'])^2} \leq \varepsilon$, but $|\mathbb{E}_\nu[f']| > \varepsilon$.*

Definition 3 (Distributional Eluder (DE) dimension). *Let $\mathcal{F}'$ be a function class defined on $\mathcal{X}$, and Γ be a family of probability measures over $\mathcal{X}$. The DE dimension $d_{DE}(\mathcal{F}', \Gamma, \varepsilon)$ is the length of the longest sequence $\{\rho_i\}_{i=1}^n \subseteq \Gamma$ s.t. $\exists \varepsilon' \geq \varepsilon$ where ρ_i is ε'-independent of $\{\rho_j\}_{j=1}^{i-1}, \forall i = 1, \ldots, n$.*

We also introduce the notation $\mathcal{D}_{\mathcal{F}} := \{\mathcal{D}_{\mathcal{F},h}\}_{h \in [H]}$, where $\mathcal{D}_{\mathcal{F},h}$ denotes the collection of all possible roll-in distributions at the h-th step generated by π_f for some $f \in \mathcal{F}$. Formally $\mathcal{D}_{\mathcal{F},h} := \{d_h^{\pi_f}\}_{f \in \mathcal{F}}$ where $d_h^{\pi_f}(x, a) = \mathbb{P}^{\pi_f}[x_h = x, x_h = a]$ is the state-action occupancy measure.

3 RFOLIVE algorithm and results

In this section, we describe our main algorithm RFOLIVE, a reward-free variant of OLIVE (Jiang et al., 2017; Jin et al., 2021).[5] The algorithmic template for RFOLIVE is shown in the pseudocode (Algorithm 1) and it can be instantiated with both Q-type and V-type versions of OLIVE from Jin et al. (2021). In the pseudocode, we use $\square$ as a placeholder for the respective Q/V-type definitions. For clarity, we will describe the Q-type RFOLIVE algorithm and its results in Section 3.1 and then state the differences for the V-type version and corresponding results in Section 3.2.

Before introducing our algorithm, we define the following average Bellman error:

Definition 4 (Average Bellman error). *We denote $\mathcal{E}^R$ as the average Bellman error under reward R:*

$$\mathcal{E}^R(f, \pi, \pi', h) = \mathbb{E}\left[f_h(x_h, a_h) - R_h(x_h, a_h) - V_f(x_{h+1}) \mid a_{0:h-1} \sim \pi, a_h \sim \pi'\right].$$

As shorthand, we use $\mathcal{E}_Q^R(f, \pi, h) = \mathcal{E}^R(f, \pi, \pi, h)$ to represent the Q-type Bellman error and $\mathcal{E}_V^R(f, \pi, h) = \mathcal{E}^R(f, \pi, \pi_f, h)$ to represent the V-type Bellman error (Jin et al., 2021). We use $\mathcal{E}^{\mathbf{0}}$ to represent the average Bellman errors under $\mathbf{0}$ reward.

---

[4]If we have $\mathbf{0} \in \mathcal{R}_h, \forall h \in [H]$, then Assumption 2 reduces to $\forall h \in [H], \mathcal{T}_h^{\mathbf{0}}(\mathcal{F}_{h+1} + \mathcal{R}_{h+1}) \subseteq \mathcal{F}_h$.

[5]Roughly speaking, V-type (Jiang et al., 2017) covers more settings of interest, but Q-type (Jin et al., 2021) avoids paying dependence on the number of actions K in some specialized settings such as linear MDPs.

Algorithm 1 RFOLIVE ($\mathcal{F}, \varepsilon, \delta$): Reward-Free OLIVE

Online phase, no reward information
1: Set $\varepsilon_{\text{actv}}, \varepsilon_{\text{elim}}, n_{\text{actv}}, n_{\text{elim}}$ according to Q-type/V-type and construct $\mathcal{F}_{\text{on}} = \mathcal{F} - \mathcal{F}$.
2: Initialize $\mathcal{F}^0 \leftarrow \mathcal{F}_{\text{on}}$ (Q-type) or $\mathcal{F}^0 \leftarrow \mathcal{Z}_{\text{on}}$, where $\mathcal{Z}_{\text{on}}$ is an $(\varepsilon_{\text{elim}}/64)$-cover of $\mathcal{F}_{\text{on}}$ (V-type)
3: **for** $t = 0, 1 \ldots$ **do**
4:     Choose function $f^t = \operatorname{argmax}_{f \in \mathcal{F}^t} V_f(x_0), \pi^t = \pi_{f^t}$.
5:     Collect n_{actv} trajectories $\{(x_0^{(i)}, a_0^{(i)}, \ldots, x_{H-1}^{(i)}, a_{H-1}^{(i)})\}_{i=1}^{n_{\text{actv}}}$ by following π^t for all $h \in [H]$
    and form estimates $\tilde{\mathcal{E}}^{\mathbf{0}}(f^t, \pi^t, \pi^t, h)$ for each $h \in [H]$ via Eq. (1).
6:     **if** $\sum_{h=0}^{H-1} \tilde{\mathcal{E}}^{\mathbf{0}}(f^t, \pi^t, \pi^t, h) \leq H\varepsilon_{\text{actv}}$ **then**
7:         Set $T = t$ and exit the loop.
8:     **end if**
9:     Pick any $h^t \in [H]$ for which $\tilde{\mathcal{E}}^{\mathbf{0}}(f^t, \pi^t, \pi^t, h^t) \geq \varepsilon_{\text{actv}}$.
10:     Set $\pi_{\text{est}} = \pi^t$ (Q-type) or $\pi_{\text{est}} = \text{Unif}(\mathcal{A})$, i.e., draw actions uniformly at random (V-type).
11:     Collect n_{elim} samples $\mathcal{D}^t = \{(x_{h^t}^{(i)}, a_{h^t}^{(i)}, x_{h^t+1}^{(i)})\}_{i=1}^{n_{\text{elim}}}$ where $a_{0:h^t-1} \sim \pi^t$ and $a_{h^t} \sim \pi_{\text{est}}$.
12:     For all $f \in \mathcal{F}^t$, compute estimate $\hat{\mathcal{E}}_{\square}^{\mathbf{0}}(f, \pi^t, h^t)$ via Eq. (2) (Q-type) or Eq. (4) (V-type).
13:     Update $\mathcal{F}^{t+1} = \{f \in \mathcal{F}^t : |\hat{\mathcal{E}}_{\square}^{\mathbf{0}}(f, \pi^t, h^t)| \leq \varepsilon_{\text{elim}}\}$.
14: **end for**
    Offline phase, the reward function $R = (R_0, \ldots, R_{H-1})$ is revealed.
15: Construct $\mathcal{F}_{\text{off}}(R) = \mathcal{F} + R$, set $\Pi_{\text{est}}^t = \{\pi^t\}$ (Q-type) or $\Pi_{\text{est}}^t = \Pi_{\text{on}} := \{\pi_f : f \in \mathcal{Z}_{\text{on}}\}$ (i.e.,
    the greedy policies induced by $\mathcal{Z}_{\text{on}}$) (V-type).
16: For each $t \in [T]$, $g \in \mathcal{F}_{\text{off}}(R)$, and $\pi \in \Pi_{\text{est}}^t$, compute estimate $\hat{\mathcal{E}}^R(g, \pi^t, \pi, h^t)$ via Eq. (3)
    (Q-type) or Eq. (5) (V-type).
17: Set $\mathcal{F}_{\text{sur}}(R) = \{g \in \mathcal{F}_{\text{off}}(R) : \forall t \in [T], \forall \pi \in \Pi_{\text{est}}^t, |\hat{\mathcal{E}}^R(g, \pi^t, \pi, h^t)| \leq \varepsilon_{\text{elim}}/2\}$.
18: Return $\hat{\pi} = \pi_{\hat{g}}$ where $\hat{g} = \operatorname{argmax}_{g \in \mathcal{F}_{\text{sur}}(R)} V_g(x_0)$.

3.1 Q-type RFOLIVE

Our algorithm, reward-free OLIVE (RFOLIVE) described in Algorithm 1, takes the function class $\mathcal{F}$, accuracy parameter ε and the failure probability δ as input. As we are in the reward-free setting, it operates in two phases: an online exploration phase where it collects a dataset without an explicit reward signal, and then, in the offline phase, computes a near-optimal policy after the reward function R is revealed. Below, we describe the two phases and the intuition behind the design.

Online exploration phase During the online phase, we first set elimination thresholds $\varepsilon_{\text{actv}}, \varepsilon_{\text{elim}}$ and sample sizes $n_{\text{actv}}, n_{\text{elim}}$ and construct the following function class $\mathcal{F}_{\text{on}}$ used in the online phase:

$$\mathcal{F}_{\text{on}} = \mathcal{F} - \mathcal{F} := \left\{ (f_0 - f_0', \ldots, f_{H-1} - f_{H-1}') : f_h, f_h' \in \mathcal{F}_h, \forall h \in [H] \right\}.$$

The details for specifying the parameters are deferred to Theorem 1 and Theorem 3. Subsequently, we simulate Q-type OLIVE with the function class $\mathcal{F}_{\text{on}}$ using the zero reward function $R = \mathbf{0}$ and the specified parameters. Similar to OLIVE, we maintain a version space $\mathcal{F}^t \subseteq \mathcal{F}_{\text{on}}$ of surviving functions after each iteration ($\mathcal{F}^0 = \mathcal{F}_{\text{on}}$). In each iteration, we first find the optimistic function $f^t \in \mathcal{F}^t$ (line 4) and set $\pi^t = \pi_{f^t}$. In line 5, we collect n_{actv} trajectories to estimate the Q-type average Bellman error $\tilde{\mathcal{E}}_Q^{\mathbf{0}}(f^t, \pi^t, h) = \tilde{\mathcal{E}}^{\mathbf{0}}(f^t, \pi^t, \pi^t, h)$ under zero reward:

$$\tilde{\mathcal{E}}^{\mathbf{0}}(f^t, \pi^t, \pi^t, h) = \frac{1}{n_{\text{actv}}} \sum_{i=1}^{n_{\text{actv}}} \left[f_h^t \left(x_h^{(i)}, a_h^{(i)} \right) - V_{f^t} \left(x_{h+1}^{(i)} \right) \right]. \tag{1}$$

If the elimination condition in line 6 is satisfied, then we terminate the online phase and otherwise, we pick a step h^t where the estimate $\tilde{\mathcal{E}}^{\mathbf{0}}(f^t, \pi^t, \pi^t, h^t) \geq \varepsilon_{\text{actv}}$ (line 9). We now collect n_{elim} trajectories using $a_{0:h^t} \sim \pi^t$ and set $\mathcal{D}^t$ as the transition tuples at step h^t. Using $\mathcal{D}^t$, we construct the Bellman error estimates $\hat{\mathcal{E}}_Q^{\mathbf{0}}(f, \pi^t, h^t)$ for all $f \in \mathcal{F}^t$ in line 12:

$$\hat{\mathcal{E}}_Q^{\mathbf{0}}(f, \pi^t, h^t) = \frac{1}{n_{\text{elim}}} \sum_{i=1}^{n_{\text{elim}}} \left[f_{h^t} \left(x_{h^t}^{(i)}, a_{h^t}^{(i)} \right) - V_f \left(x_{h^t+1}^{(i)} \right) \right]. \tag{2}$$

Finally, in line 13, we eliminate all the $f \in \mathcal{F}^t$ whose Bellman error estimate $\hat{\mathcal{E}}_{\mathrm{Q}}^{\mathbf{0}}(f, \pi^t, h^t) > \varepsilon_{\mathrm{elim}}$.

The online phase returns tuples $\{(h^t, \pi^t, \mathcal{D}^t)\}_{t=0}^{T-1}$ where T is the total number of iterations and each dataset $\mathcal{D}^t$ consists of n_{elim} transition tuples.

Offline elimination phase   In the offline phase, the reward function R is revealed, and we first construct the reward-appended function class $\mathcal{F}_{\mathrm{off}}(R) = \mathcal{F} + R := \{(f_0 + R_0, \ldots, f_{H-1} + R_{H-1}) : f_h \in \mathcal{F}_h, \forall h \in [H]\}$. Using the class $\Pi_{\mathrm{est}}^t = \{\pi^t\}$ from line 15 and the collected tuples $\{(h^t, \pi^t, \mathcal{D}^t)\}_{t=0}^{T-1}$, we estimate the reward-dependent average Bellman error (Definition 4) for all iterations $t \in [T]$ of the online phase:

$$\hat{\mathcal{E}}^R(g, \pi^t, \pi^t, h^t) = \frac{1}{n_{\mathrm{elim}}} \sum_{i=1}^{n_{\mathrm{elim}}} \left[g_h\left(x_h^{(i)}, a_h^{(i)}\right) - R_h\left(x_h^{(i)}, a_h^{(i)}\right) - V_g\left(x_{h+1}^{(i)}\right) \right]. \tag{3}$$

RFOLIVE eliminates all $g \in \mathcal{F}_{\mathrm{off}}(R)$ whose Bellman error estimates are large (line 17) and returns the optimistic function $\hat{g}$ from the surviving set.[6]

Remark   Similar to its counterparts in reward-aware general function approximation setting (Jiang et al., 2017; Dann et al., 2018; Jin et al., 2021; Du et al., 2021), RFOLIVE is in general not computationally efficient. We leave addressing computational tractability as a future direction.

3.1.1   Main results for Q-type RFOLIVE

We now present the theoretical guarantees of Q-type RFOLIVE. We start with introducing the Q-type Bellman Eluder (BE) dimension (Jin et al., 2021).

Definition 5 (Q-type BE dimension). *Let* $(I - \mathcal{T}_h^R)\mathcal{F} := \{f_h - \mathcal{T}_h^R f_{h+1} : f \in \mathcal{F}\}$ *be the set of Bellman differences of* $\mathcal{F}$ *at step* h, *and* $\Gamma = \{\Gamma_h\}_{h=0}^{H-1}$ *where* Γ_h *is a set of distributions over* $\mathcal{X} \times \mathcal{A}$. *The* ε-*BE dimension of* $\mathcal{F}$ *w.r.t.* Γ *is defined as* $\dim_{QBE}^R(\mathcal{F}, \Gamma, \varepsilon) := \max_h d_{DE}\left((I - \mathcal{T}_h^R)\mathcal{F}, \Gamma_h, \varepsilon\right)$.

We can now state our sample complexity result for Q-type RFOLIVE. To simplify presentation, we state the result here assuming parametric growth of the covering numbers, that is $\log(\mathcal{N}_{\mathcal{F}}(\varepsilon)) \leq d_{\mathcal{F}} \log(1/\varepsilon)$ and $\log(\mathcal{N}_{\mathcal{R}}(\varepsilon)) \leq d_{\mathcal{R}} \log(1/\varepsilon)$.

Theorem 1 (Q-type RFOLIVE, parametric case). *Fix* $\delta \in (0, 1)$. *Given a reward class* $\mathcal{R}$ *and a function class* $\mathcal{F}$ *that satisfies Assumption 1 and Assumption 2. With probability at least* $1 - \delta$, *for any* $R \in \mathcal{R}$, *Q-type* RFOLIVE *(Algorithm 1) outputs a policy* $\hat{\pi}$ *that satisfies* $v_R^{\hat{\pi}} \geq v_R^* - \varepsilon$. *The required number of episodes is*[7]

$$\tilde{O}\left(\left(H^7 d_{\mathcal{F}} + H^5 d_{\mathcal{R}}\right) d_{QBE}^2 \log(1/\delta)/\varepsilon^2\right)$$

where $d_{QBE} = \dim_{QBE}^{\mathbf{0}}(\mathcal{F} - \mathcal{F}, \mathcal{D}_{\mathcal{F} - \mathcal{F}}, \varepsilon/(4H))$.

The more general statement along with the specific values of $\varepsilon_{\mathrm{actv}}, \varepsilon_{\mathrm{elim}}, n_{\mathrm{actv}}, n_{\mathrm{elim}}$ are deferred to Appendix A.2, where we also present the proof. We remark that we only need the covering number of $\mathcal{R}$ to set these parameters and do not use any other information about the reward class.

We pause to compare Theorem 1 to the reward-aware case. First, our BE dimension involves the "difference" function class under zero reward as opposed to the original class with the given reward. As we will see, this difference is inconsequential for our examples of interest. Second, our sample complexity has an additional H^4 dependence because (a) we consider a different reward normalization from Jiang et al. (2017) and (b) we use a smaller threshold in the online phase to ensure sufficient exploration. Similar gaps in H factors between reward-free and reward-aware learning also appear in Wagenmaker et al. (2022). We also pay for the complexity of $\mathcal{R}$ in a lower order term, which is standard in reward-free RL (Zhang et al., 2020a; Modi et al., 2021). We believe that a similar adaptation of GOLF (Jin et al., 2021) for the reward-free setting may provide a sharper result with improved dependence on H and $\dim_{\mathrm{QBE}}$, analogously to the reward-aware setting.

---

[6]As a convention in our paper, g refers to reward-appended functions and f to reward-independent functions.

[7]The $\tilde{O}(\cdot)$ notation suppresses poly-logarithmic factors in its argument.

 ### 3.1.2 Q-type RFOLIVE for known representation linear completeness setting

219 Here, we instantiate the general guarantee of Q-type RFOLIVE to the linear completeness setting.[8]

220 **Definition 6** (Linear completeness setting (Zanette et al., 2020b))**.** *We call feature* $\phi^{\mathrm{lc}} =$
221 $(\phi_0^{\mathrm{lc}}, \ldots, \phi_{H-1}^{\mathrm{lc}})$ *with* $\phi_h^{\mathrm{lc}} : \mathcal{X} \times \mathcal{A} \to \mathbb{R}^{d_{\mathrm{lc}}}, \forall h \in [H]$ *a linearly complete feature, if for any* $B >$
222 $0, h \in [H-1]$ *and* $\forall f_{h+1} \in \mathcal{Q}_{h+1}(\{\phi^{\mathrm{lc}}\}, B)$ *we have:* $\min_{f_h \in \mathcal{Q}_h(\{\phi^{\mathrm{lc}}\}, B)} \|f_h - \mathcal{T}_h^{\mathbf{0}} f_{h+1}\|_\infty = 0$,
223 *where* $\mathcal{Q}_h(\{\phi^{\mathrm{lc}}\}, B) = \{\langle \phi_h^{\mathrm{lc}}, \theta_h \rangle : \|\theta_h\|_2 \le B\sqrt{d_{\mathrm{lc}}}\}$.

224 When the linearly complete feature (Definition 6) ϕ^{lc} is known, we can construct the function class
225 $\mathcal{F}(\{\phi^{\mathrm{lc}}\}) = \mathcal{F}_0(\{\phi^{\mathrm{lc}}\}, H-1) \times \ldots \times \mathcal{F}_{H-1}(\{\phi^{\mathrm{lc}}\}, 0)$, where $\mathcal{F}_h(\{\phi^{\mathrm{lc}}\}, B_h) = \{f_h(x_h, a_h) =$
226 $\langle \phi_h^{\mathrm{lc}}(x_h, a_h), \theta_h \rangle : \|\theta_h\|_2 \le B_h \sqrt{d_{\mathrm{lc}}}, \langle \phi_h^{\mathrm{lc}}(\cdot), \theta_h \rangle \in [0, B_h]\}$ consists of appropriately bounded
227 linear functions of ϕ^{lc}. It is easy to verify that $\mathcal{F}(\{\phi^{\mathrm{lc}}\})$ satisfies the assumptions in Theorem 1. This
228 gives us the following corollary. We defer the full statement and proof to Appendix A.3.

229 **Corollary 2** (Informal)**.** *Fix* $\delta \in (0, 1)$. *Consider an MDP* M *that satisfies linear completeness*
230 *(Definition 6) with known feature* ϕ^{lc}, *and the linear reward class* $\mathcal{R} = \mathcal{R}_1 \times \ldots \times \mathcal{R}_h$, *where*
231 $\mathcal{R}_h = \{\langle \phi_h^{\mathrm{lc}}, \eta_h \rangle : \|\eta_h\|_2 \le \sqrt{d_{\mathrm{lc}}}, \langle \phi_h^{\mathrm{lc}}(\cdot), \eta_h \rangle \in [0, 1]\}$. *With probability at least* $1 - \delta$, *for any*
232 $R \in \mathcal{R}$, *Q-type* RFOLIVE *(Algorithm 1) with* $\mathcal{F} = \mathcal{F}(\{\phi^{\mathrm{lc}}\})$ *outputs a policy* $\hat{\pi}$ *that satisfies*
233 $v_R^{\hat{\pi}} \ge v_R^* - \varepsilon$. *The required number of samples is* $\tilde{O}\left(H^8 d_{\mathrm{lc}}^3 \log(1/\delta)/\varepsilon^2\right)$.

234 The reward normalization above, called *explicit regularity* in Zanette et al. (2020b), is standard.
235 Compared to that work, our result implies that *explorability* is not necessary, which significantly
236 relaxes the existing assumptions for this setting. Our result can also be easily extended to handle
237 approximately linearly complete features (i.e., low inherent Bellman error). On the other hand, our
238 sample complexity bound is worse in H factors and our algorithm is not computationally efficient.

239 ## 3.2 V-type RFOLIVE

240 In this section, we describe the instantiation of RFOLIVE with V-type definitions. For V-type
241 RFOLIVE, we also assume that the action space is finite with size K.

242 **Online exploration phase** Instead of using $\mathcal{F}_{\mathrm{on}}$, we use its $(\varepsilon_{\mathrm{elim}}/64)$-cover $\mathcal{Z}_{\mathrm{on}}$ and maintain a
243 version space $\mathcal{F}^t$ across iterations.[9] Since the on-policy version of Q-type and V-type Bellman errors
244 are the same, the termination check in line 5 and line 6 are unchanged. If the algorithm does not
245 terminate in line 6, we again identify a deviation step h^t such that $\tilde{\mathcal{E}}_{\mathrm{V}}^{\mathbf{0}}(f^t, \pi^t, h^t) \ge \varepsilon_{\mathrm{actv}}$. Instead of
246 using π^t to collect trajectories, we use $a_{0:h^t-1} \sim \pi^t$ and choose a_{h^t} uniformly at random to collect
247 the dataset of n_{elim} transition tuples at step h^t. Compared to Q-type RFOLIVE, we estimate $\hat{\mathcal{E}}_{\mathrm{V}}^{\mathbf{0}}$ for
248 all f in line 12 using importance sampling (IS):

$$\hat{\mathcal{E}}_{\mathrm{V}}^{\mathbf{0}}(f, \pi^t, h^t) = \frac{1}{n_{\mathrm{elim}}} \sum_{i=1}^{n_{\mathrm{elim}}} \frac{\mathbf{1}[a_{h^t}^{(i)} = \pi_f(x_{h^t}^{(i)})]}{1/K} \left[f_{h^t}\left(x_{h^t}^{(i)}, a_{h^t}^{(i)}\right) - V_f\left(x_{h^t+1}^{(i)}\right) \right] \qquad (4)$$

249 Finally, in line 13, we eliminate all $f \in \mathcal{F}^t$ whose average Bellman error estimates are large.

250 **Offline elimination phase** In the offline phase, we consider the same reward-appended function
251 class $\mathcal{F}_{\mathrm{off}}(R)$ when reward $R \in \mathcal{R}$ is revealed. For V-type RFOLIVE, in line 15, we define the policy
252 class $\Pi_{\mathrm{est}}^t = \Pi_{\mathrm{on}}$ which consists of greedy policies with respect to all $f \in \mathcal{Z}_{\mathrm{on}}$. Using the dataset
253 $\mathcal{D}^t$, we estimate $\mathcal{E}^R(g, \pi^t, \pi', h^t)$ for all $g \in \mathcal{F}_{\mathrm{off}}(R), \pi' \in \Pi_{\mathrm{on}}, t \in [T]$ from its empirical version:

$$\hat{\mathcal{E}}^R(g, \pi^t, \pi', h^t) = \frac{1}{n_{\mathrm{elim}}} \sum_{i=1}^{n_{\mathrm{elim}}} \frac{\mathbf{1}[a_{h^t}^{(i)} = \pi'(x_h^{(i)})]}{1/K} \left[g_h(x_h^{(i)}, a_h^{(i)}) - R_h(x_h^{(i)}, a_h^{(i)}) - V_g(x_{h+1}^{(i)}) \right] \quad (5)$$

254 and eliminate invalid functions in line 17. Finally, we return the optimistic policy $\hat{\pi}$ from the surviving
255 set. Apart from estimating different average Bellman errors, the noticeable difference between Q-type
256 and V-type RFOLIVE is that the latter has an IS factor, which is used to correct the distribution to
257 some policy $\pi' \in \Pi_{\mathrm{on}}$ to witness the average Bellman error (Jiang et al., 2017).

---

[8]Zanette et al. (2020b) only define linear completeness for $B = 1$. It can be easily verified that it is equivalent for any choice of B. More discussion can be found in Appendix A.3.

[9]Following Jin et al. (2021), we call V-type OLIVE with the discretized class $\mathcal{Z}_{\mathrm{on}}$ for the ease of presentation.

3.2.1 Main results for V-type RFOLIVE

We now present the theoretical guarantee of V-type RFOLIVE. Firstly, we introduce the V-type Bellman Eluder (BE) dimension (Jin et al., 2021).

Definition 7 (V-type BE dimension). *Let $(I - \mathcal{T}_h^R)V_\mathcal{F} \subseteq (\mathcal{X} \rightarrow \mathbb{R})$ be the state-wise Bellman difference class of $\mathcal{F}$ at step h defined as $(I - \mathcal{T}_h^R)V_\mathcal{F} := \{x \mapsto (f_h - \mathcal{T}_h^R f_{h+1})(x, \pi_{f_h}(x)) : f \in \mathcal{F}\}$. Let $\Gamma = \{\Gamma_h\}_{h=0}^{H-1}$ where Γ_h is a set of distributions over $\mathcal{X}$. The V-type ε-BE dimension of $\mathcal{F}$ with respect to Γ is defined as $\dim_{VBE}^R(\mathcal{F}, \Gamma, \varepsilon) := \max_{h \in [H]} d_{DE}((I - \mathcal{T}_h^R)V_\mathcal{F}, \Gamma_h, \varepsilon)$.*

We now state the guarantee for V-type RFOLIVE, assuming polynomial covering number growth.

Theorem 3 (V-type RFOLIVE, parametric case). *Fix $\delta \in (0, 1)$. Given a reward class $\mathcal{R}$, a function class $\mathcal{F}$ that satisfies Assumption 1, Assumption 2. With probability at least $1 - \delta$, for any $R \in \mathcal{R}$, V-type RFOLIVE outputs a policy $\hat{\pi}$ that satisfies $v_R^{\hat{\pi}} \geq v_R^* - \varepsilon$. The required number of episodes is*

$$\tilde{O}\left(\left(H^7 d_\mathcal{F} + H^5 d_\mathcal{R}\right) d_{VBE}^2 K \log(1/\delta)/\varepsilon^2\right),$$

where $d_{VBE} = \dim_{VBE}^0(\mathcal{F} - \mathcal{F}, \mathcal{D}_{\mathcal{F}-\mathcal{F}}, \varepsilon/(8H))$.

The detailed proof and the specific values of $\varepsilon_{\text{actv}}, \varepsilon_{\text{elim}}, n_{\text{actv}}, n_{\text{elim}}$ are deferred to Appendix B.2. Our rate is again loose in H factors when compared with the reward-aware version. Compared with the Q-type version, here we also incur a dependence on $K = |\mathcal{A}|$, analogous to the reward-aware case.

3.2.2 V-type RFOLIVE for unknown representation low-rank MDPs

In this section, we instantiate our V-type RFOLIVE result to low-rank MDPs (Modi et al., 2021):

Definition 8 (Low-rank factorization). *A transition operator $P_h : \mathcal{X} \times \mathcal{A} \rightarrow \Delta(\mathcal{X})$ admits a low-rank decomposition of dimension d_{lr} if there exists $\phi^{\text{lr}} : \mathcal{X} \times \mathcal{A} \rightarrow \mathbb{R}^{d_{\text{lr}}}$ and $\mu^{\text{lr}} : \mathcal{X} \rightarrow \mathbb{R}^{d_{\text{lr}}}$ s.t. $\forall x, x' \in \mathcal{X}, a \in \mathcal{A} : P_h(x' \mid x, a) = \langle \phi^{\text{lr}}(x, a), \mu^{\text{lr}}(x') \rangle$, and additionally $\|\phi^{\text{lr}}(x, a)\|_2 \leq 1$ and $\forall f' : \mathcal{X} \rightarrow [0, 1]$, we have $\left\|\int f'(x)\mu^{\text{lr}}(x)dx\right\|_2 \leq \sqrt{d_{\text{lr}}}$. We say M is low-rank with embedding dimension d_{lr}, if for each $h \in [H]$, the transition operator P_h admits a rank-d_{lr} decomposition.*

Similar to Modi et al. (2021), we consider low-rank MDPs and a given realizable feature class Φ^{lr}:

Assumption 3 (Realizability of low-rank feature class). *We assume that a finite feature class $\Phi^{\text{lr}} = \Phi_0^{\text{lr}} \times \ldots \times \Phi_{H-1}^{\text{lr}}$ satisfies $\phi_h^{\text{lr}} \in \Phi_h^{\text{lr}}, \forall h \in [H]$. In addition, $\forall h \in [H], \phi_h \in \Phi_h^{\text{lr}}, \|\phi_h(\cdot)\|_2 \leq 1$.*

Similar to the linear completeness setting (Section 3.1.2), we construct $\mathcal{F}(\Phi^{\text{lr}}) = \mathcal{F}_0(\Phi^{\text{lr}}, H-1) \times \ldots \times \mathcal{F}_{H-1}(\Phi^{\text{lr}}, 0)$, where $\mathcal{F}_h(\Phi^{\text{lr}}, B_h) = \{f_h(x_h, a_h) = \langle \phi_h(x_h, a_h), \theta_h \rangle : \phi_h \in \Phi_h^{\text{lr}}, \|\theta_h\|_2 \leq B_h \sqrt{d_{\text{lr}}}, \langle \phi_h(\cdot), \theta_h \rangle \in [0, B_h]\}$. In Proposition 4, we show that the V-type Bellman Eluder dimension of $\mathcal{F}(\Phi^{\text{lr}}) - \mathcal{F}(\Phi^{\text{lr}})$ in this case is $\tilde{O}(d_{\text{lr}})$ which leads to the following corollary:

Corollary 4 (Informal, parametric case). *Fix $\delta \in (0, 1)$. Consider a low-rank MDP M of embedding dimension d_{lr} with a realizable feature class Φ^{lr} (Assumption 3) and a reward class $\mathcal{R}$. With probability at least $1 - \delta$, for any $R \in \mathcal{R}$, V-type RFOLIVE (Algorithm 1) with $\mathcal{F}(\Phi^{\text{lr}})$ outputs a policy $\hat{\pi}$ that satisfies $v_R^{\hat{\pi}} \geq v_R^* - \varepsilon$. The required number of episodes is*

$$\tilde{O}\left(\left(H^8 d_{\text{lr}}^3 \log(|\Phi^{\text{lr}}|) + H^5 d_{\text{lr}}^2 d_\mathcal{R}\right) K \log(1/\delta)/\varepsilon^2\right).$$

We defer the full statement and detailed proof of the corollary to Appendix B.3. In the low-rank MDP setting, Modi et al. (2021) propose a more computationally viable algorithm, but additionally require a reachability assumption. Our result shows that reachability is not necessary for statistically efficient, which opens an interesting avenue for designing an algorithm that is both computationally and statistically efficient without reachability. Moreover, our result significantly improves upon their sample complexity bound. Notice that here K shows up in our bound. As another corollary, in the linear MDP (Definition 8 plus ϕ^{lr} is known), Q-type RFOLIVE yields a K independent bound. The detailed corollary and proof can be found in Appendix A.4.

3.3 Intuition and proof sketch for RFOLIVE

To provide intuition, since we use **0** reward function when running OLIVE online, any policy π_f attains zero value (i.e., $V^{\pi_f}(x_0) = 0, \forall f \in \mathcal{F}_{\text{on}}$). By the policy loss decomposition lemma (Jiang

et al., 2017), the value error for the greedy policy, $V_f(x_0) - V^{\pi_f}(x_0)$, is small when the algorithm stops (line 6). Therefore, all $f \in \mathcal{F}_{\text{on}}$ which predict large values $V_f(x_0)$ must have been eliminated before OLIVE terminates. This implies that, in the online phase, we gather a diverse set of constraints (roll-in distributions π^t) that can witness the average Bellman error of functions in $\mathcal{F}_{\text{on}}$. In this sense, our algorithm focuses on function space elimination and does not try to reach all latent states or directions (Modi et al., 2021; Zanette et al., 2020b), which is the key conceptual difference that enables us to avoid reachability and explorability assumptions.

On the technical side, our analysis is also novel and distinct from the prior works. The most crucial part is to show that any bad $g \in \mathcal{F}_{\text{off}}(R)$ whose average Bellman error is large under the true reward R will be eliminated in the offline phase. To prove this, we construct $\tilde{f} \in \mathcal{F}_{\text{on}}$ that has the same average Bellman error as g and predicts a large positive value $V_{\tilde{f}}(x_0)$, which implies that it will be eliminated during the online phase. Finally, by our construction, the constraint used to eliminate $\tilde{f}$ directly witnesses the average Bellman error of g, thus ruling out g in the offline phase.

4 Hardness result for unknown representation linear completeness setting

In Section 3.1, we showed that Q-type RFOLIVE requires polynomial sample for reward-free RL in the known feature linear completeness setting. For low-rank MDPs, when given a realizable feature class, we showed V-type RFOLIVE is statistically efficient in Section 3.2. A natural next step is to relax the low-rank assumption on the MDP and show a sample efficiency result for the more general linear completeness and unknown feature case. However, below we state a hardness result which shows that a polynomial dependence on $|\Phi^{\text{lc}}|$ or $|\mathcal{X}|$, or exponential dependence on H is *unavoidable*. We first introduce the realizability of a linearly complete feature class.

Assumption 4 (Realizability of linearly complete feature class)**.** *We assume that there exists a finite candidate feature class $\Phi^{\text{lc}} = \Phi_0^{\text{lc}} \times \cdots \times \Phi_{H-1}^{\text{lc}}$, such that $\forall h \in [H]$, we have $\phi_h^{\text{lc}} \in \Phi_h^{\text{lc}}$. In addition, $\forall h \in [H], \phi_h \in \Phi_h^{\text{lc}}, \forall (x, a) \in \mathcal{X} \times \mathcal{A}$, we have $\|\phi_h(x, a)\|_2 \leq 1$.*

Below we state a hardness result for learning in the linear completeness setting with a realizable feature class (Assumption 4). A complete proof and more discussions are provided in Appendix C.

Theorem 5. *There exists a family of MDPs $\mathcal{M}$, reward class $\mathcal{R}$ and feature set Φ^{lc}, where $\forall M \in \mathcal{M}$, the (M, Φ^{lc}) pair satisfies the linear completeness assumption in Assumption 4, yet it is information-theoretically impossible for an algorithm to obtain a $\text{poly}\left(d_{\text{lc}}, H, \log(|\Phi^{\text{lc}}|), \log(|\mathcal{R}|), \frac{1}{\varepsilon}, \log(\frac{1}{\delta})\right)$ sample complexity for reward-free exploration with the given reward class $\mathcal{R}$.*

The hardness result in Theorem 5 is applicable to more general settings, as it also depicts a necessary exponential dependence using the same construction under linear completeness assumptions over a feature class for (i) learning with a generative model (or using a local access protocol, Hao et al. (2022)), (ii) reward-free learning with explorability (Zanette et al., 2020a) and reachability (Modi et al., 2021) assumptions and (iii) reward-aware learning as $\mathcal{R}$ is a known singleton class. Thus, the result highlights an exponential separation between the low-rank MDP and linear completeness assumptions by showing that linearly complete true feature $\phi^{\text{lc}} \in \Phi^{\text{lc}}$ is not sufficient for polynomial sample efficiency and additional assumptions are required to account for the unknown representation.

5 Conclusions and discussions

In this paper, we investigated the statistical efficiency of reward-free RL under general function approximation. Our positive results significantly relax the existing assumptions in the reward-free exploration framework. Our negative result shows the first sharp separation between low-rank MDP and the linear completeness settings with unknown representations. In addition, we provide an algorithm-specific counterexample in Appendix D that shows RFOLIVE can fail when the completeness assumption is violated. As realizability alone is sufficient for reward-aware RL (Jiang et al., 2017; Jin et al., 2021; Du et al., 2021), our results also elicit the further question:

Are completeness-type assumptions necessary for statistically efficient reward-free RL?

We conjecture that the answer is negative, and we believe that the hardness between reward-aware and reward-free RL has a deep connection to the sharp separation between realizability and completeness (Chen and Jiang, 2019; Wang et al., 2020b, 2021; Weisz et al., 2021, 2022; Foster et al., 2021).

References

Alekh Agarwal, Sham Kakade, Akshay Krishnamurthy, and Wen Sun. Flambe: Structural complexity and representation learning of low rank mdps. *Advances in Neural Information Processing Systems*, 2020.

Yu Bai and Chi Jin. Provable self-play algorithms for competitive reinforcement learning. In *International conference on machine learning*, pages 551–560. PMLR, 2020.

Jinglin Chen and Nan Jiang. Information-theoretic considerations in batch reinforcement learning. In *International Conference on Machine Learning*, 2019.

Jinglin Chen and Nan Jiang. Offline reinforcement learning under value and density-ratio realizability: the power of gaps. *arXiv preprint arXiv:2203.13935*, 2022.

Christoph Dann, Nan Jiang, Akshay Krishnamurthy, Alekh Agarwal, John Langford, and Robert E Schapire. On oracle-efficient pac rl with rich observations. In *Advances in Neural Information Processing Systems*, 2018.

Simon Du, Sham Kakade, Jason Lee, Shachar Lovett, Gaurav Mahajan, Wen Sun, and Ruosong Wang. Bilinear classes: A structural framework for provable generalization in rl. In *International Conference on Machine Learning*, pages 2826–2836. PMLR, 2021.

Damien Ernst, Pierre Geurts, and Louis Wehenkel. Tree-based batch mode reinforcement learning. *Journal of Machine Learning Research*, 6:503–556, 2005.

Dylan J Foster, Akshay Krishnamurthy, David Simchi-Levi, and Yunzong Xu. Offline reinforcement learning: Fundamental barriers for value function approximation. *arXiv preprint arXiv:2111.10919*, 2021.

Botao Hao, Nevena Lazic, Dong Yin, Yasin Abbasi-Yadkori, and Csaba Szepesvari. Confident least square value iteration with local access to a simulator. In *International Conference on Artificial Intelligence and Statistics*, pages 2420–2435. PMLR, 2022.

Jiawei Huang, Jinglin Chen, Li Zhao, Tao Qin, Nan Jiang, and Tie-Yan Liu. Towards deployment-efficient reinforcement learning: Lower bound and optimality. In *International Conference on Learning Representations*, 2021.

Nan Jiang and Alekh Agarwal. Open problem: The dependence of sample complexity lower bounds on planning horizon. In *Conference On Learning Theory*, pages 3395–3398. PMLR, 2018.

Nan Jiang and Jiawei Huang. Minimax value interval for off-policy evaluation and policy optimization. *Advances in Neural Information Processing Systems*, 33:2747–2758, 2020.

Nan Jiang, Akshay Krishnamurthy, Alekh Agarwal, John Langford, and Robert E Schapire. Contextual decision processes with low Bellman rank are PAC-learnable. In *International Conference on Machine Learning*, 2017.

Chi Jin, Akshay Krishnamurthy, Max Simchowitz, and Tiancheng Yu. Reward-free exploration for reinforcement learning. In *International Conference on Machine Learning*, 2020a.

Chi Jin, Zhuoran Yang, Zhaoran Wang, and Michael I Jordan. Provably efficient reinforcement learning with linear function approximation. In *Conference on Learning Theory*, 2020b.

Chi Jin, Qinghua Liu, and Sobhan Miryoosefi. Bellman eluder dimension: New rich classes of rl problems, and sample-efficient algorithms. *arXiv preprint arXiv:2102.00815*, 2021.

Emilie Kaufmann, Pierre Ménard, Omar Darwiche Domingues, Anders Jonsson, Edouard Leurent, and Michal Valko. Adaptive reward-free exploration. In *Algorithmic Learning Theory*, pages 865–891. PMLR, 2021.

Akshay Krishnamurthy, Alekh Agarwal, and John Langford. Pac reinforcement learning with rich observations. *Advances in Neural Information Processing Systems*, 29, 2016.

Qinghua Liu, Tiancheng Yu, Yu Bai, and Chi Jin. A sharp analysis of model-based reinforcement learning with self-play. In *International Conference on Machine Learning*, pages 7001–7010. PMLR, 2021.

Pierre Ménard, Omar Darwiche Domingues, Anders Jonsson, Emilie Kaufmann, Edouard Leurent, and Michal Valko. Fast active learning for pure exploration in reinforcement learning. In *International Conference on Machine Learning*, pages 7599–7608. PMLR, 2021.

Dipendra Misra, Mikael Henaff, Akshay Krishnamurthy, and John Langford. Kinematic state abstraction and provably efficient rich-observation reinforcement learning. In *International conference on machine learning*, 2020.

Aditya Modi, Nan Jiang, Ambuj Tewari, and Satinder Singh. Sample complexity of reinforcement learning using linearly combined model ensembles. In *Conference on Artificial Intelligence and Statistics*, 2020.

Aditya Modi, Jinglin Chen, Akshay Krishnamurthy, Nan Jiang, and Alekh Agarwal. Model-free representation learning and exploration in low-rank mdps. *arXiv preprint arXiv:2102.07035*, 2021.

Shuang Qiu, Jieping Ye, Zhaoran Wang, and Zhuoran Yang. On reward-free rl with kernel and neural function approximations: Single-agent mdp and markov game. In *International Conference on Machine Learning*, pages 8737–8747. PMLR, 2021.

Daniel Russo and Benjamin Van Roy. Eluder dimension and the sample complexity of optimistic exploration. *Advances in Neural Information Processing Systems*, 26, 2013.

Wen Sun, Nan Jiang, Akshay Krishnamurthy, Alekh Agarwal, and John Langford. Model-based rl in contextual decision processes: Pac bounds and exponential improvements over model-free approaches. In *Conference on learning theory*, pages 2898–2933. PMLR, 2019.

Masatoshi Uehara, Xuezhou Zhang, and Wen Sun. Representation learning for online and offline rl in low-rank mdps. In *International Conference on Learning Representations*, 2021.

Andrew Wagenmaker, Yifang Chen, Max Simchowitz, Simon S Du, and Kevin Jamieson. Reward-free rl is no harder than reward-aware rl in linear markov decision processes. *arXiv preprint arXiv:2201.11206*, 2022.

Martin J Wainwright. *High-dimensional statistics: A non-asymptotic viewpoint*, volume 48. Cambridge University Press, 2019.

Ruosong Wang, S. Simon Du, F. Lin Yang, and Ruslan Salakhutdinov. On reward-free reinforcement learning with linear function approximation. In *Advances in Neural Information Processing Systems*, 2020a.

Ruosong Wang, Dean P Foster, and Sham M Kakade. What are the statistical limits of offline rl with linear function approximation? *arXiv preprint arXiv:2010.11895*, 2020b.

Ruosong Wang, Ruslan Salakhutdinov, and Lin F Yang. Provably efficient reinforcement learning with general value function approximation. *arXiv:2005.10804*, 2020c.

Ruosong Wang, Russ R Salakhutdinov, and Lin Yang. Reinforcement learning with general value function approximation: Provably efficient approach via bounded eluder dimension. *Advances in Neural Information Processing Systems*, 33:6123–6135, 2020d.

Yuanhao Wang, Ruosong Wang, and Sham Kakade. An exponential lower bound for linearly realizable mdp with constant suboptimality gap. *Advances in Neural Information Processing Systems*, 34, 2021.

Gellért Weisz, Philip Amortila, and Csaba Szepesvári. Exponential lower bounds for planning in mdps with linearly-realizable optimal action-value functions. In *Algorithmic Learning Theory*, pages 1237–1264. PMLR, 2021.

Gellért Weisz, Csaba Szepesvári, and András György. Tensorplan and the few actions lower bound for planning in mdps under linear realizability of optimal value functions. In *International Conference on Algorithmic Learning Theory*, pages 1097–1137. PMLR, 2022.

Jingfeng Wu, Vladimir Braverman, and Lin Yang. Gap-dependent unsupervised exploration for reinforcement learning. In *International Conference on Artificial Intelligence and Statistics*, pages 4109–4131. PMLR, 2022.

Tengyang Xie and Nan Jiang. Q* approximation schemes for batch reinforcement learning: A theoretical comparison. In *Conference on Uncertainty in Artificial Intelligence*, pages 550–559. PMLR, 2020.

Ming Yin and Yu-Xiang Wang. Optimal uniform ope and model-based offline reinforcement learning in time-homogeneous, reward-free and task-agnostic settings. *Advances in neural information processing systems*, 34, 2021.

Andrea Zanette and Martin J Wainwright. Bellman residual orthogonalization for offline reinforcement learning. *arXiv preprint arXiv:2203.12786*, 2022.

Andrea Zanette, Alessandro Lazaric, Mykel Kochenderfer, and Emma Brunskill. Learning near optimal policies with low inherent bellman error. In *International Conference on Machine Learning*, pages 10978–10989. PMLR, 2020a.

Andrea Zanette, Alessandro Lazaric, Mykel J Kochenderfer, and Emma Brunskill. Provably efficient reward-agnostic navigation with linear value iteration. In *Advances in Neural Information Processing Systems*, 2020b.

Amy Zhang, Rowan McAllister, Roberto Calandra, Yarin Gal, and Sergey Levine. Learning invariant representations for reinforcement learning without reconstruction. *arXiv:2006.10742*, 2020a.

Weitong Zhang, Jiafan He, Dongruo Zhou, Amy Zhang, and Quanquan Gu. Provably efficient representation learning in low-rank markov decision processes. *arXiv preprint arXiv:2106.11935*, 2021a.

Weitong Zhang, Dongruo Zhou, and Quanquan Gu. Reward-free model-based reinforcement learning with linear function approximation. *Advances in Neural Information Processing Systems*, 34, 2021b.

Xuezhou Zhang, Yuzhe Ma, and Adish Singla. Task-agnostic exploration in reinforcement learning. *Advances in Neural Information Processing Systems*, 33, 2020b.