On Dropout, Overfitting, and Interaction Effects in Deep Neural Networks

Abstract

We examine Dropout through the perspective of *interactions*. Given N variables, there are $\mathcal{O}(N^2)$ possible pairwise interactions, $\mathcal{O}(N^3)$ possible 3-way interactions, i.e. $\mathcal{O}(N^k)$ possible interactions of k variables. Conversely, the probability of an interaction of k variables surviving Dropout at rate p is $\mathcal{O}((1-p)^k)$. In this paper, we show that these rates cancel, and as a result, Dropout selectively regularizes against learning higher-order interactions. We prove this new perspective analytically for Input Dropout and empirically for Activation Dropout. This perspective on Dropout has several practical implications: (1) higher Dropout rates should be used when we need stronger regularization against spurious high-order interactions, (2) caution must be used when interpreting Dropout-based feature saliency measures, and (3) networks trained with Input Dropout are biased estimators. We also compare Dropout to regularization via weight decay and early stopping and find that it is difficult to obtain the same regularization benefit for high-order interactions with these methods.

1 Introduction

Over the past decade, improvements in deep learning have produced remarkable increases in accuracy on a variety of domains. Many of these advances are the result of thoughtful engineering and empirical experimentation as opposed to theoretical analysis. Unfortunately, over-reliance on empiricism could hinder our community's future progress.

For example, Dropout was originally proposed to "reduce co-adaptation of features" (Hinton et al., 2012; Srivastava et al., 2014). This explanation is insufficient to help the community understand precisely what Dropout regularizes, when it helps, and how it can be improved. As a result, the deep learning community has developed many explanations of Dropout in terms of regularization on weights (e.g. Baldi & Sadowski (2013), Cavazza et al. (2018), and more discussed in Section 2). Unfortunately, these views of Dropout as a *weight* regularizer are insufficient: there are too many parameters in modern networks for parameter regularization to provide a useful heuristic. Thus, we view Dropout instead as a *function* regularizer.

In this paper, we explore the inductive bias of Dropout and ask how it helps neural networks (NNs) to generalize well. Deep neural networks (NNs) have the representational capacity to learn high-order interactions of the input features. Given N variables, there are $\mathcal{O}(N)$ possible main effects, $O(N^2)$ possible pairwise interactions, $\mathcal{O}(N^3)$ possible 3-way interactions, i.e. $\mathcal{O}(N^k)$ possible interactions of k input variables. Despite the exponentially increasing number of potential high-order interactions, NNs do not massively overfit by learning many spurious high-order interactions. Why? We show that Dropout contributes a regularization effect which helps NNs explore simple functions of lower-order interactions before considering functions of higher-order interactions. Dropout imposes this regularization by reducing the effective learning rate of interaction effects according to the number of variables in the interaction effect. As a result, Dropout encourages models to stay closer to additive models.

We first prove this fact theoretically before turning to empirical analysis. Our approach in both the theoretical and empirical analyses is to decompose the function estimated by a NN according to the weighted functional ANOVA (fANOVA) decomposition of Hooker (2004). This decomposition allows us to measure the strength of the interaction effects estimated under a variety of Dropout settings. As we show in this paper, more Dropout produces networks with weaker interaction effects.

Anonymized code to reproduce all figures is available at `https://github.com/dropout-intx/ICLR2021`.

Why Interaction Effects? In this paper, we propose a new view: Dropout is a regularizer of interaction effects. It is natural to ask *why should we care about interaction effects?* We choose this lens because (1) Interaction effects are a tractable heuristic for understanding and engineering deep learning systems which have too many weights to understand

individually, (2) the fANOVA has several convenient properties, including identifiability, for calculating interaction effects, (3) Dropout's main method of action is to regularize against *internal features and outputs which require simultaneous knowledge of several inputs*, i.e., interaction effects, and (4) this perspective has practical implications.

Practical Implications   While this paper is focused on *understanding* Dropout, our proposed view of Dropout as a regularizer of interactions is useful. For example, this view make it clear that Dropout induces a bias in the estimated NN both at training time and at test time, and thus Dropout should not be used for post-hoc explanations or saliency estimation. In addition, concisely describing the bias of Dropout gives a handle on which to *unbias* the model, and we look forward to future work in this direction.

2   RELATED WORK

In its original proposal, Dropout was motivated to prevent "complex co-adaptations in which a feature detector is only helpful in the context of several other specific feature detectors"(Hinton et al., 2012; Srivastava et al., 2014). While this explanation is certainly motivating, many questions remain: Is the expectation of the Dropout output the same as the model output without Dropout? Does Dropout change the trajectory of the model during optimization? These questions are important because Dropout has been used as a method for Bayesian uncertainty (Gal & Ghahramani, 2016; Gal et al., 2017; Chang et al., 2017b;a), which implicitly assume that Dropout does not bias the model's output. The use of Dropout as a tool for uncertainty quantification has been questioned due to its failure to separate aleotoric and epistemic sources of uncertainty (Osband, 2016) (i.e., the uncertainty does not decrease even as more data is gathered). In this paper we ask a separate question: Does Dropout treat all parts of an input function equivalently?

Significant work has focused on the effect of Dropout as a regularizer of weights(Baldi & Sadowski, 2013; Warde-Farley et al., 2013; Cavazza et al., 2018; Mianjy et al., 2018; Zunino et al., 2018), including its properties of structured shrinkage (Nalisnick et al., 2018) or adaptive regularization (Wager et al., 2013). However, weight regularization is of limited utility for modern-scale NNs, and can produce counter-intuitive results such as a negative regularization penalty (Helmbold & Long, 2017).

Instead of focusing on the influence of Dropout on parameters, we take a nonparametric view of NNs as function approximators and query the input-output change. Thus, our work is similar in spirit to Wan et al. (2013), which showed a linear relationship between keep probability and the Rademacher complexity of the model class. Our investigation finds that Dropout preferentially targets high-order interaction effects, resulting in learned models that generalize better by ignoring (or significantly down-weighting) high-order interaction effects that are typically spurious or difficult to learn correctly from limited training data.

3   PRELIMINARIES

3.1   FUNCTIONAL ANOVA AND PURE INTERACTION EFFECTS

In this paper, we use the concept of *pure interaction effects* from Lengerich et al. (2020). According to this definition, a pure interaction effect is variance explained by a group of variables u that *cannot* be explained by any subset of u. This definition is equivalent to the fANOVA decomposition of the overall function F: Given a density $w(X)$ and $\mathcal{F}^u \subset \mathcal{L}^2(\mathbb{R}^u)$ the family of allowable functions for variable set u, the weighted fANOVA (Hooker, 2004; 2007; Cuevas et al., 2004) decomposition of $F(X)$ is:

$$\{f_u(X_u)|u \subseteq [d]\} = \underset{\{g_u \in \mathcal{F}^u\}_{u \in [d]}}{\arg\min} \int \Big(\sum_{u \subseteq [d]} g_u(X_u) - F(X) \Big)^2 w(X)dX, \tag{1a}$$

where $[d]$ indicates the power set of d features, such that

$$\forall\, v \subseteq\, u, \quad \int f_u(X_u)g_v(X_v)w(X)dX = 0 \quad \forall\, g_v, \tag{1b}$$

i.e., each member f_u is orthogonal to the members which operate on any subset of u. An interaction effect f_u is of *order* k if $|u| = k$.

The fANOVA decomposition provides a unique decomposition for a given data distribution; thus, pure interaction effects can only be defined by simultaneously defining a data distribution. An example of this interplay between the data distribution and the interaction definition is shown in Figure B.2. As Lengerich et al. (2020) describe, the correct distribution to use is the data-generating distribution $p(x)$. In studies on real data, estimating $p(x)$ is one of the central challenges of machine learning; for this paper, we use simulation data for which we know $p(x)$.

Multiplication While multiplicative terms like $X_1 X_2$ are often used to encode "interaction effects", they are only *pure* interaction effects if X_1 and X_2 are uncorrelated and have mean zero. When the two variables are correlated, some portion of the variance in the outcome $X_1 X_2$ can be explained by main effects of each individual variable. Note, however, that correlation between two input variables does not imply an interaction effect on the outcome, and an interaction effect of two input variables on the outcome does not imply correlation between the variables.

4 ANALYSIS: DROPOUT REGULARIZES INTERACTION EFFECTS

Dropout operates by probabilistically setting values to zero (i.e. multiplying by a Bernoulli mask). For clarity, we call this "Input Dropout" if the perturbed values are input variables, and "Activation Dropout" if the perturbed values are activations of hidden nodes.

Input Dropout Performs Data Augmentation with Effect Shrinkage Exponential in Interaction Order Input Dropout is equivalent to augmenting the training dataset with samples drawn from a perturbed distribution:

Theorem 1. *Let* $\mathbb{E}[Y|X] = \sum_{u \in [d]} f_u(X_u)$ *with* $\mathbb{E}[Y] = 0$. *Then Input Dropout at rate* p *has*

$$\mathbb{E}[Y|X \odot M] = \sum_{u \in [d]} (1-p)^{|u|} f_u(X) \tag{2}$$

where M is the Dropout mask and $\odot$ is element-wise multiplication. This theorem shows that Input Dropout shrinks the conditional expectation of $Y|X \odot M$ toward the expectation of Y. Furthermore, Input Dropout preferentially targets high-order interactions: the scaling factor shrinks exponentially with $|u|$. Implications of this theorem are:

1. The distribution of training data is actually different for different levels of Input Dropout. NNs will converge to different optima based on the level of Input Dropout, i.e., Input Dropout introduces bias.

2. Input Dropout acts on the data distribution, not the model, so it has the same effect on learning regardless of the downstream net architecture.

3. Input Dropout affects higher-order interactions more than lower-order interactions, biasing the prediction of any model (regardless of whether or not the model was originally trained with Input Dropout).

Input Dropout Shrinks Gradients Exponentially with Effect Order

Theorem 2. *Let* ∇_u *be the gradient update for an interaction effect* u. *The expected concordance between the gradient with Input Dropout and the gradient without Input Dropout is:*

$$\mathbb{E}_M \left[\frac{\nabla_u(X_u, Y) \cdot \nabla_u(X_u \odot M, Y)}{\|\nabla_u(X_u, Y)\|} \right] = (1-p)^{|u|} \nabla_u(X_u, Y). \tag{3}$$

This theorem shows that Input Dropout shrinks the gradient update corresponding to each effect by an *effective learning rate* $r_p(k) = (1-p)^k$ which decays exponentially in the interaction order k. Implications of this theorem are:

1. The decreased learning rate persists throughout all training. Therefore, the disruption in the gradient signal will also interplay with other mechanisms of adaptive optimizers (e.g., early stopping or momentum).

2. The bias of training with Input Dropout could be undone by up-weighting the gradients of interaction effects.

4.1 SYMMETRY BETWEEN DROPOUT STRENGTH AND NUMBER OF INTERACTION EFFECTS

From N input features, there are $\binom{N}{k}$ distinct k-order interaction effects which could be estimated. Without any regularization, high-order interactions would dominate. However, as shown above, the effective learning rate of k-order interactions decays exponentially with k. This is a symmetry with $\binom{N}{k}$ (which is upper-bounded by N^k). As shown in Fig 1, the exponential growth of the hypothesis space $\mathcal{H}_k$ with interaction order is balanced by the exponential decay of the effective learning rate, provided strong regularization against spurious high-order interaction methods.

5 EXPERIMENTS

As shown above, Dropout does not simply add unbiased noise to the gradient updates; instead, Dropout exerts an unceasing force throughout the optimization process. This means that Dropout changes the steady-state optima of the model. We examine this behavior empirically for both Input Dropout and Activation Dropout by decomposing the effect estimated by a NN with the fANOVA.

(a) Full space.

(b) First four orders.

Figure 1: The growing hypothesis space of potential interaction effects is balanced against the effective learning rate imposed by Dropout. In this figure, we plot the product of the effective learning rate ($r_p(k)$) and the number of potential interaction effects of order k ($\mathcal{H}_k$) for a variety of Dropout rates p. In a, we plot these values on a log scale for the entire range of potential interaction orders for an input of 25 features. In b, we plot up to order 4 on a linear scale.

5.1 MEASURING INTERACTION EFFECTS IN TRAINED NEURAL NETWORKS

The function $\hat{F}(X)$ estimated by a NN can be decomposed as: $\hat{F}(X) = \sum_{u \in [d]} \hat{f}_u(X_u)$ by the fANOVA (Eq. 1b). We will use this decomposition to measure the interaction effects implicit in the NN. To approximate this decomposition, we repeatedly apply model distillation (Buciluă et al., 2006; Hinton et al., 2015) using the `XGBoost` software package (Chen & Guestrin, 2016). First, we train boosted stumps (`XGBoost` with max depth of 1) to approximate the output of the NN using only main effects of individual variables. We successively increase the maximum depth of trees (corresponding to an increase in the maximum order of interaction effect permitted). By training on the residuals of the previous model, we ensure that the estimated effects are orthogonal. In the remainder of this paper, we will refer to $\mathrm{Var}_X(\hat{f}_u(X))$ as the *effect size* of an estimated effect $\hat{f}_u$ [1]. For a demonstration of the accuracy and robustness of this procedure, please see the experiments performed in Appendix A. Given the extra space allowed for the camera-ready copy, we intend to include these experiments in the main text here.

5.2 DROPOUT REGULARIZES INTERACTIONS IN PURE NOISE DATA

In this experiment, we use a simulation setting in which there is no signal (so any estimated effects are spurious). This gives us a testbench to easily see the regularization strength of different levels of Dropout. Specially, we generate 1500 samples of 25 input features where $X_i \sim Unif(-1, 1)$ and $Y \sim N(0, 1)$. We optimize NNs with 3 hidden layers and ReLU nonlinearities and measure effect sizes as described in Sec. 5.1. In Fig. 2, we see the results for NNs with 32 units in each hidden layer. For this small network, both Activation and Input Dropout have strong regularizing effects on a neural net. Not only do they reduce the overall estimated effect size, both Activation and Input Dropout preferentially target higher-order interactions (e.g., the proportion of variance explained by low-order interactions monotonically increases as the Dropout Rate is increased for Figs. 2d,2e, and 2f. In Fig. E.3, we see results from the same experiment on NNs with 128 units in each hidden layer. For these larger networks, Activation Dropout has a minimal effect on regularizing away interaction effects (e.g., the proportion of variance explained by low-order interactions does not change significantly until a Dropout rate of 0.5 is reached in Fig. E.3d). However, as our analysis predicts, the effects of Input Dropout are just as strong for this larger network (Fig. E.3e) as they were for the smaller network.

5.3 MODIFIED 20-NEWSGROUPS DATA

This understanding of Dropout as a regularizer against high-order interaction effects suggests that Dropout should be used at higher rates where we would like to regularize against high-order interaction effects. To test this guideline, we design an experiment based on the classic 20-NewsGroups dataset [2]. This dataset contains documents from 20 different news organizations, leading to a natural 20-way classification task. To test our hypothesis about the mechanism of

---

[1]The fANOVA decomposition is identifiable for a given distribution of X; in our experiments, we will mainly use simulation data so that this decomposition can be computed with respect to the correct distribution.

[2]http://qwone.com/~jason/20Newsgroups/

Figure 2: In this experiment, we train fully-connected neural networks on a dataset of pure noise (details in Sec. 5.2). Displayed values are the (mean $\pm$ std. over 10 initializations) of the trained model's variance explained by each order of interaction effect. Activation and Input Dropout both significantly reduce the effect sizes of the learned high-order interactions. The top row of graphs (a–c) shows the absolute variance of the models for different values of Dropout — as Dropout grows, overfitting is reduced and the variance of the predictions converges towards zero. The middle row (d–f) shows the relative effect sizes of interactions, making it easier to see how the Dropout rate affects each degree of interaction. The bottom row (g–i) shows the effects normalized by their strength in the unregularized model to visualize the shrinkage effect of Dropout for each degree of interaction.

action for Dropout, we modify this dataset by adding k new features (each feature is IID $Unif(0, 1)$) and a 21st class which is the correct label if all of the k new features take on a value greater than 0.5. This modified dataset therefore has a strong k-way interaction effect, and as k grows, we would expect the optimal Dropout rate to be lower. Results are shown in Table 1. As predicted by our understanding of Dropout, indeed the optimal Dropout rate is lower for larger k.

k	Dropout Rate					
	0.0	0.125	0.25	0.375	0.5	0.625
1	0.52 ± 0.01	0.54 ± 0.01	0.54 ± 0.03	$\mathbf{0.57 \pm 0.02}$	0.55 ± 0.02	0.47 ± 0.02
2	0.39 ± 0.01	0.38 ± 0.03	$\mathbf{0.40 \pm 0.02}$	$\mathbf{0.40 \pm 0.01}$	0.38 ± 0.01	0.27 ± 0.02
3	0.39 ± 0.01	$\mathbf{0.41 \pm 0.01}$	$\mathbf{0.41 \pm 0.01}$	0.40 ± 0.02	0.40 ± 0.02	0.27 ± 0.04

Table 1: Test accuracies of the models trained on the modified 20-Newgroups datasets (Sec. 5.3). Reported values are (mean $\pm$ std) of the test accuracies over 5 experiments, with the best setting in each row bolded. Each row indicates k, the order of the added interaction effect. As k is increased, lower levels of Dropout tend to outperform. Different modifications of the dataset chnage the difficulty of the task, so the accuracy values are not comparable across rows.

5.4 DO OTHER REGULARIZERS PENALIZE INTERACTION EFFECTS?

Seeing that Dropout regularizes against interaction effects, it is natural to ask whether other effective regularizers of NNs also achieve better generalization by penalizing high-order interaction effects. Here, we examine early stopping and weight decay as potential regularizers of interaction effects. We find that neither of these regularization techniques specifically target interaction effects. However, because Dropout changes the effective learning rate of interaction effects, it can act in concert with early stopping to magnify the regularization against interaction effects.

5.4.1 EARLY STOPPING

It has long been known that the effective size of NNs increases over training epochs (Weigend, 1994), and recent work has supported this view that randomly-initialized NNs represent simple functions which are made more complex through training (De Palma et al., 2018; Nakkiran et al., 2019). Thus, it makes sense that early stopping can be extremely helpful for selecting generalizable models (Caruana et al., 2001; Prechelt, 1998).

To see how early stopping interplays with the Dropout-induced effective learning rates, we study the learned effects over the course of optimization. We generate 1500 samples of 25 input features where $X_i \sim Unif(-1, 1)$ and the target is generated according to one of three settings: (1) only main effects: $Y \sim N(\sin(X_0) + \cos(X_1), \sigma^2)$, (2) only pair effects: $Y \sim N(\sin(X_0)\cos(X_1), \sigma^2)$, and (3) only three-way effects: $Y \sim N(\sin(X_0)\cos(X_1)X_2, \sigma^2)$. We optimize fully-connected NNs on these data and measure effect sizes as described in Sec. 5.1. As shown in Fig. 3, the models with low settings of Dropout tend to massively overfit the data due to a reliance on spurious high-order interaction effects. Since Dropout slows down the learning of these spurious high-order effects, early stopping is doubly effective in combination with Dropout. In short, NNs tend to learn simple functions earlier (regardless of Dropout usage), and Dropout slows the learning of high-order interactions. As a result, early stopping reduces the complexity of the learned function and Dropout increases this effect by delaying learning high-order interactions.

5.4.2 WEIGHT DECAY

Another popular regularization mechanism is weight decay: placing an ℓ_2 penalty on the weights of the network. We study weight decay on the same data generator as we studied Dropout in Sec. 5.2. As the results in Fig. 4 show, strong weight decay (large values of λ) has a modest effect of regularizing against interaction effects. However, achieving the same practical benefit from weight decay as from Dropout is untenable due to the training instability that strong weight decay introduces: when weight decay was set larger than about 0.2 the NNs learned simple constant functions.

6 DISCUSSION AND IMPLICATIONS

In this paper, we examined a concrete mechanistic explanation of how Dropout works: by regularizing higher-order interactions. We see that Dropout does not introduce unbiased noise into learning — training with higher levels of Dropout produces models that are less likely to learn strong interaction effects. This explanation of Dropout has several implications for its use and crystallizes some of the conventional wisdom regarding how and when to use Dropout.

Figure 3: Learned interaction effects and model accuracies over training epochs. Each row corresponds to a different generator function described in Sec. 5.4.1; the top row has only true 1-way interactions, the middle row has only true 2-way interactions, and the bottom row has only true 3-way interactions. The models with low settings of Dropout tend to massively overfit the data due to a reliance on spurious high-order interaction effects. Since Dropout slows down the learning of these spurious high-order effects, early stopping is doubly effective in combination with Dropout.

6.1 DROPOUT FOR EXPLANATIONS

While Dropout has been used for measures of model confidence (Gal & Ghahramani, 2016; Gal et al., 2017) and to aid model interpretability (Chang et al., 2017b;a), it does not equally affect all effect that NNs might learn. This must be taken into consideration both when using Dropout to query what a model has learned and what patterns are or are not present in the data. For example, it has been reported that there are important 2^{nd} and 3^{rd} order interactions in the New York City Bike Share data (Tan et al., 2018), but using Dropout to examine a NN trained on this dataset may underweight these interaction effects. Thus one should be careful when using Dropout to interpret NNs, or interpreting what NNs trained with different Dropout rates tell us about patterns in the data.

6.2 SETTING DROPOUT RATE

The Dropout rate should be set according to the desired magnitude of the anti-interaction regularization effect. If the dataset is large or sufficient augmentation can be performed, lower rates of Dropout can be used or Dropout can be omitted entirely(Hernández-García & König, 2018).

In addition, it is often suggested to use larger Dropout rates in deeper layers than in initial layers (Ba & Frey, 2013). This conventional wisdom is now explained by the interaction view: initial layers are for representation learning which

(a) Total Effect Sizes   (b) Normalized Effect Sizes   (c) Rate of Decay

Figure 4: Strong weight decay can have a mild regularization effect against interaction effects; however, the regularization effect comparable to Dropout occurs at extremely strong weight decay for which training is very unstable.

requires interactions between input features, while deeper layers focus more on making predictions, a task which often depends more on summing evidence from multiple sources than on learning complex high-order interactions.

In CNNs, Dropout is typically used at lower rates than in fully-connected networks (Park & Kwak, 2016). The convolutional architecture creates constraints that prevent arbitrary high-order interactions of distant input features from being learned. In other words, convolutional nets create a strong bias for or against different kinds of interaction effects via architecture and thus depend less on a mechanism like Dropout to regularize interactions.

6.3 EXPLICITLY MODELING INTERACTION EFFECTS

In this investigation, we have seen that the main challenge of estimating interaction effects is the hypothesis space which grows exponentially with the order of the interaction effect. If we were able to hone down the hypothesis space by specifying a small number of interaction effects before looking at data, our models could efficiently learn the correct parameters for these few interactions from data. Several recent works have proposed to do this by explicitly modeling interaction effects in NNs. Of particular note is (Jayakumar et al., 2020), which proposed to explicitly use multiplicative interactions as a means of combining data modalities The authors found that many common architectures can be seen in the lens of multiplicative interactions, and these multiplicative interactions help in multitask problems (but hurt in standard MNIST/CIFAR problems). These works make sense given the difficulty of picking interaction effects from the exponentially-growing haystack of possible interactions: if we know a priori which high-order interactions exist, it is better to explicitly model them rather than hope the deep model learns them from data.

Another approach to explicitly model interaction effects is the Deep and Cross Network (Wang et al., 2017), which uses a two-part architecture consisting of a fully-connected network and a "cross" network in which each layer has its activation crossed with the vector of input variables before being transmitted to the next layer. This "cross" network increases the interaction order at every layer. Interestingly, the experiments of (Wang et al., 2017) (especially Fig. 3 within) show that the best-performing architecture has only a single cross layer – this is exactly what we would expect based on the amount of spurious interaction effects which the model is otherwise capable of learning.

Finally, we can see these experiments as another view on the success of CNNs: when interaction effects are important (such as in image recognition), it is important to make the form of expected interactions explicit. High-order interaction effects in the data are not strong enough to cut through the hypothesis space of all potential interaction effects, so explicitly encoding the form can make a tremendous difference in model accuracy.

7 CONCLUSIONS

In this paper, we have examined a concrete explanation of Dropout as a regularization against interaction effects. We have shown that the effective learning rate of interaction effects decreases exponentially with the order of the interaction effect, a crucial balance against the exponentially-growing number of potential interactions of k variables. Although Dropout can work in concert with weight decay and early stopping, these do not naturally achieve Dropout's regularization against high-order interactions. By reducing the tendency of NNs to learn spurious high-order interaction effects, Dropout helps to train models which generalize more accurately to test sets.

REFERENCES

Jimmy Ba and Brendan Frey. Adaptive dropout for training deep neural networks. In C. J. C. Burges, L. Bottou, M. Welling, Z. Ghahramani, and K. Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 26*, pp. 3084–3092. Curran Associates, Inc., 2013. URL http://papers.nips.cc/paper/5032-adaptive-dropout-for-training-deep-neural-networks.pdf.

Pierre Baldi and Peter J Sadowski. Understanding dropout. In *Advances in neural information processing systems*, pp. 2814–2822, 2013.

Cristian Buciluǎ, Rich Caruana, and Alexandru Niculescu-Mizil. Model compression. In *Proceedings of the 12th ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 535–541, 2006.

Rich Caruana, Steve Lawrence, and C Lee Giles. Overfitting in neural nets: Backpropagation, conjugate gradient, and early stopping. In *Advances in neural information processing systems*, pp. 402–408, 2001.

Jacopo Cavazza, Pietro Morerio, Benjamin Haeffele, Connor Lane, Vittorio Murino, and Rene Vidal. Dropout as a low-rank regularizer for matrix factorization. In *International Conference on Artificial Intelligence and Statistics*, pp. 435–444, 2018.

Chun-Hao Chang, Elliot Creager, Anna Goldenberg, and David Duvenaud. Interpreting neural network classifications with variational dropout saliency maps. In *NeurIPS Machine Learning in Computational Biology Workshop*, 2017a.

Chun-Hao Chang, Ladislav Rampasek, and Anna Goldenberg. Dropout feature ranking for deep learning models. *arXiv preprint arXiv:1712.08645*, 2017b.

Tianqi Chen and Carlos Guestrin. Xgboost: A scalable tree boosting system. *ArXiv*, abs/1603.02754, 2016.

Xi Cheng, Bohdan Khomtchouk, Norman Matloff, and Pete Mohanty. Polynomial regression as an alternative to neural nets. *CoRR*, abs/1806.06850, 2018. URL http://arxiv.org/abs/1806.06850.

Brent A Coull, David Ruppert, and MP Wand. Simple incorporation of interactions into additive models. *Biometrics*, 57(2):539–545, 2001.

Antonio Cuevas, Manuel Febrero, and Ricardo Fraiman. An anova test for functional data. *Computational statistics & data analysis*, 47(1):111–122, 2004.

Giacomo De Palma, Bobak Toussi Kiani, and Seth Lloyd. Deep neural networks are biased towards simple functions. *arXiv preprint arXiv:1812.10156*, 2018.

Ian A Delbridge, David S Bindel, and Andrew Gordon Wilson. Randomly projected additive gaussian processes for regression. *arXiv preprint arXiv:1912.12834*, 2019.

Paul HC Eilers and Brian D Marx. Flexible smoothing with b-splines and penalties. *Statistical science*, pp. 89–102, 1996.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *international conference on machine learning*, pp. 1050–1059, 2016.

Yarin Gal, Jiri Hron, and Alex Kendall. Concrete dropout. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 30*, pp. 3581–3590. Curran Associates, Inc., 2017. URL http://papers.nips.cc/paper/6949-concrete-dropout.pdf.

Andrew Gelman. Statistical modeling, causal inference, and social science, Mar 2018. URL https://statmodeling.stat.columbia.edu/2018/03/15/need-16-times-sample-size-estimate-interaction-estimate-main-effect/.

Trevor Hastie and Rob Tibshirani. *Generalized Additive Models*. Chapman and Hall/CRC, 1990.

David P Helmbold and Philip M Long. Surprising properties of dropout in deep networks. *The Journal of Machine Learning Research*, 18(1):7284–7311, 2017.

Alex Hernández-García and Peter König. Do deep nets really need weight decay and dropout? *arXiv preprint arXiv:1802.07042*, 2018.

Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

Geoffrey E Hinton, Nitish Srivastava, Alex Krizhevsky, Ilya Sutskever, and Ruslan R Salakhutdinov. Improving neural networks by preventing co-adaptation of feature detectors. *arXiv preprint arXiv:1207.0580*, 2012.

Giles Hooker. *Diagnostics and Extrapolation in Machine Learning*. Stanford University, 2004.

Giles Hooker. Generalized functional anova diagnostics for high-dimensional functions of dependent variables. *Journal of Computational and Graphical Statistics*, 16(3):709–732, 2007.

Siddhant M. Jayakumar, Jacob Menick, Wojciech M. Czarnecki, Jonathan Schwarz, Jack Rae, Simon Osindero, Yee Whye Teh, Tim Harley, and Razvan Pascanu. Multiplicative interactions and where to find them. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=rylnK6VtDH.

Benjamin Lengerich, Sarah Tan, Chun-Hao Chang, Giles Hooker, and Rich Caruana. Purifying interaction effects with the functional anova: An efficient algorithm for recovering identifiable additive models. In *International Conference on Artificial Intelligence and Statistics*, pp. 2402–2412, 2020.

Andrew C Leon and Moonseong Heo. Sample sizes required to detect interactions between two binary fixed-effects in a mixed-effects linear regression model. *Computational statistics & data analysis*, 53(3):603–608, 2009.

Yin Lou, Rich Caruana, and Johannes Gehrke. Intelligible models for classification and regression. In *Proceedings of the 18th ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 150–158. ACM, 2012.

Yin Lou, Rich Caruana, Johannes Gehrke, and Giles Hooker. Accurate intelligible models with pairwise interactions. In *Proceedings of the 19th ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 623–631. ACM, 2013.

Poorya Mianjy, Raman Arora, and Rene Vidal. On the implicit bias of dropout. *arXiv preprint arXiv:1806.09777*, 2018.

Preetum Nakkiran, Gal Kaplun, Dimitris Kalimeris, Tristan Yang, Benjamin L Edelman, Fred Zhang, and Boaz Barak. Sgd on neural networks learns functions of increasing complexity. *arXiv preprint arXiv:1905.11604*, 2019.

Eric Nalisnick, José Miguel Hernández-Lobato, and Padhraic Smyth. Dropout as a structured shrinkage prior. *arXiv preprint arXiv:1810.04045*, 2018.

Didrik Nielsen. Tree boosting with xgboost-why does xgboost win" every" machine learning competition? Master's thesis, NTNU, 2016.

Ian Osband. Risk versus uncertainty in deep learning: Bayes, bootstrap and the dangers of dropout. In *NIPS Workshop on Bayesian Deep Learning*, volume 192, 2016.

Sungheon Park and Nojun Kwak. Analysis on the dropout effect in convolutional neural networks. In *Asian Conference on Computer Vision*, pp. 189–204. Springer, 2016.

Lutz Prechelt. Early stopping-but when? In *Neural Networks: Tricks of the trade*, pp. 55–69. Springer, 1998.

Daniel Selsam, Matthew Lamm, Benedikt Bünz, Percy Liang, Leonardo de Moura, and David L Dill. Learning a sat solver from single-bit supervision. *arXiv preprint arXiv:1802.03685*, 2018.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: A simple way to prevent neural networks from overfitting. *Journal of Machine Learning Research*, 15:1929–1958, 2014. URL http://jmlr.org/papers/v15/srivastava14a.html.

Sarah Tan, Rich Caruana, Giles Hooker, Paul Koch, and Albert Gordo. Learning global additive explanations for neural nets using model distillation. *arXiv preprint arXiv:1801.08640*, 2018.

J Kenneth Tay and Robert Tibshirani. Reluctant additive modeling. *arXiv preprint arXiv:1912.01808*, 2019.

Yusuke Tsuzuku and Issei Sato. On the structural sensitivity of deep convolutional networks to the directions of fourier basis functions. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 51–60, 2019.

Stefan Wager, Sida Wang, and Percy S Liang. Dropout training as adaptive regularization. In *Advances in neural information processing systems*, pp. 351–359, 2013.

Li Wan, Matthew Zeiler, Sixin Zhang, Yann LeCun, and Rob Fergus. Regularization of neural networks using dropconnect. In Sanjoy Dasgupta and David McAllester (eds.), *Proceedings of the 30th International Conference on Machine Learning*, volume 28 of *Proceedings of Machine Learning Research*, pp. 1058–1066, Atlanta, Georgia, USA, 17–19 Jun 2013. PMLR. URL http://proceedings.mlr.press/v28/wan13.html.

MP Wand and John T Ormerod. Penalized wavelets: Embedding wavelets into semiparametric regression. *Electronic Journal of Statistics*, 5:1654–1717, 2011.

Haohan Wang, Xindi Wu, Zeyi Huang, and Eric P Xing. High-frequency component helps explain the generalization of convolutional neural networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8684–8694, 2020.

Ruoxi Wang, Bin Fu, Gang Fu, and Mingliang Wang. Deep & cross network for ad click predictions. In *Proceedings of the ADKDD'17*, pp. 12. ACM, 2017.

David Warde-Farley, Ian J Goodfellow, Aaron Courville, and Yoshua Bengio. An empirical analysis of dropout in piecewise linear networks. *arXiv preprint arXiv:1312.6197*, 2013.

Andreas Weigend. On overfitting and the effective number of hidden units. In *Proceedings of the 1993 connectionist models summer school*, volume 1, pp. 335–342, 1994.

Bodgan M Wilamowski, David Hunter, and Aleksander Malinowski. Solving parity-n problems with feedforward neural networks. In *Proceedings of the International Joint Conference on Neural Networks, 2003.*, volume 4, pp. 2546–2551. IEEE, 2003.

Dong Yin, Raphael Gontijo Lopes, Jon Shlens, Ekin Dogus Cubuk, and Justin Gilmer. A fourier perspective on model robustness in computer vision. In *Advances in Neural Information Processing Systems*, pp. 13255–13265, 2019.

Andrea Zunino, Sarah Adel Bargal, Pietro Morerio, Jianming Zhang, Stan Sclaroff, and Vittorio Murino. Excitation dropout: Encouraging plasticity in deep neural networks. *arXiv preprint arXiv:1805.09092*, 2018.

(a) 100 Samples   (b) 1000 Samples   (c) 10000 Samples

Figure A.1: Measuring the accuracy of the estimated interactions in NNs trained on simulation data of pure interactions of order 1, 2, or 3. Each pane shows results for a given number of samples used for model distillation. For small numbers of samples, the distillation procedure can over-estimate the variance contained by high-order interaction effects. For large numbers of samples, the distillation procedure accurately recovers the true interaction order. Error bars represent the variance of the estimate over 10 experimental runs.

A   ACCURACY OF FUNCTIONAL ANOVA DECOMPOSITION BY DISTILLATION

A critical step in our experimental framework is accurately calculating the fANVOA decomposition of the function estimated by the NN. Because the fANOVA captures a high-dimensional function as a sequence of lower-dimensional functions, each function is a constrained approximation of the function represented by the NN. Thus, we do not recommend always using model compression as a general-purpose explanation of NNs. However, in this paper we care about only a single aspect of the compressed models: approximation error of the NNs. From the NN function $\hat{F}(X)$, we estimate an additive model $\hat{f}_1(X) \in \mathcal{S}(\hat{F}, \mathcal{F}_1) = \arg\min_{f \in \mathcal{F}_1} \mathbb{E}_X \left[\mathcal{L}(f(X), \hat{F}(X)) \right]$ where $\mathcal{F}_1$ is the class of additive models and $\mathcal{L}$ is squared loss. The set of possible explanations $\mathcal{S}(\hat{F}, \mathcal{F}_1)$ may have more than one member; however, all of these explanations must have the same compression loss $\mathbb{E}_X \left[\mathcal{L}(f(X), \hat{F}(X)) \right]$. Since the only metric we are reporting about these models is the compression loss (how much of the variance of the NN *could* be explained by a model in $\mathcal{F}_1$), in this paper it does not matter which explanation in $\mathcal{S}(\hat{F}, \mathcal{F}_1)$ is chosen.

To empirically measure this approximation error, we test the distillation procedure using simulation data. Our goal in this experiment is to accurately fit a NN to a known function so that we can measure the approximation error of the distillation procedure against the known function encoded in the NN. For each run, we generate data according to $X \sim \text{Unif}(-1, 1)^5$, and train the NN to fit a function of pure k-order interactions (a multiplication of k uncorrelated features of X). In this way, the NN represents a function of pure k-order interactions and a perfect distillation procedure would assign 100% of the variance to the interactions of order k. Code for this simulation, with hardcoded values of hyperparameters, are available at the main repository.

In Fig. A.1, we show the results for distillation with various numbers of samples. In each pane, there are 4 bars which each represent a pure interaction of a different order. The height of the bars (and the corresponding colors) represent the normalized effect size estimated by the distillation procedure for each of these underlying interaction effects. In Fig. A.1a, only 100 samples are used to fit the distilled models; as a result, the distilled models underfit the NN's behavior and the implied effects of high-order interactions are exaggerated. When the number of samples is increased to 1000 (Fig. A.1b) or to 10000 (Fig. A.1c), the distillation procedure is increasingly accurate at recovering the true interaction order in the NN.

We have also run this experiment on data generated from a mixture of interaction effects and obtain similar recovery results.

B   INTERACTION EFFECTS

An example of the distribution changing the meaning of a pure interaction effect is shown in Fig. B.2.

Figure B.2: A toy example of decomposing a function into pure interaction and main effects. In each (a) and (b), there are four panes: (left) an overall function, (middle left) a pure interaction effect of X_1 and X_2, (middle right) a pure effect of X_1, and (right) a pure effect of X_2. In both a and b, the overall function is $Y = X_1 X_2$, but the decomposition changes based on the coefficient ρ of correlation between X_1 and X_2. For X_1 and X_2 uncorrelated, the multiplication is a pure interaction effect; for X_1 and X_2 correlated, much of the variance can be moved into effects of the individual variables. The decomposition is unique given the joint distribution of the three variables.

B.1 THE UNREASONABLE EFFECTIVENESS OF MODELS WITH FEW INTERACTION EFFECTS

Generalized additive models (GAMs) Hastie & Tibshirani (1990) are a restrictive model class which estimate functions of individual features, i.e., functions of the form $f(X_i, \ldots, X_p) = \sum_{i=1}^{p} g_i(X_i)$. There have been a large number of methods for estimating these functions, including functional forms such as splines, trees, wavelets, etc. (Eilers & Marx, 1996; Lou et al., 2012; Wand & Ormerod, 2011). While vanilla GAMs describe nonlinear relationships between each feature and the label, interactions are sometimes added to further capture relationships between multiple features and the label (Coull et al., 2001; Lou et al., 2013; Tay & Tibshirani, 2019).

In the age of deep learning, it is surprising that GAMs with a small number of added interaction effects could be state-of-the-art on any dataset with a moderately large number of samples. However, successful tree-based ensembles such as XGBoost (Chen & Guestrin, 2016) often require only a few interaction effects to win competitions (Nielsen, 2016). In certain cases, polynomial regression of order 2 can be competitive with fully-connected deep NNs (Cheng et al., 2018), and even generalized additive models have a surprising capability to approximate deep NNs (Tan et al., 2018). Similar phenomena have been observed for Gaussian Processes (Delbridge et al., 2019) and computer vision models (Yin et al., 2019; Wang et al., 2020; Tsuzuku & Sato, 2019). How are these models, which ignore the majority of interaction effects, so effective?

B.2 STATISTICAL (UN)RELIABILITY OF INTERACTION EFFECTS

One reason why models which ignore high-order interaction effects can perform so well is the tremendous difficulty that higher-order interaction effects present to learning algorithms. When trying to learn high-order interaction effects, we are stuck between a rock and a hard place: the number of possible interaction effects grows exponentially (the number of k-order interaction effects possible from N input features is $\binom{N}{k}$), while the the variance of an interaction effect grows with the interaction order (Leon & Heo, 2009). This quandry is intensified when the effect strength decreases with interaction order, which is reasonable for real data (Gelman, 2018). It is like searching for a needle in a haystack, but as we increase k, the haystack gets larger and the needle gets smaller. For large k, we are increasingly likely to select spurious effects rather than the true effect – at some point it is better to stop searching the haystack. Viewed this way, it is less surprising that in the absence of prior knowledge of which interaction effects are true, simple models are able to outperform large models.

B.3 PARITY AND INTERACTION EFFECTS

Interaction effects are intricately linked to a classically difficult function class: parity. In the case of two Boolean variables, a pure interaction effect is exactly a weighted XOR function and for continuous variables, pure interaction effects are a continuous analog of parity (Lengerich et al., 2020). Parity functions are notoriously difficult to learn with NNs (Wilamowski et al., 2003; Selsam et al., 2018). Does this suggest that NNs are already robust against interaction effects, and if so, why is the extra regularization of Dropout against interaction effects necessary?

It is important for us to distinguish between learning the *correct* interaction effect against learning a *spurious* interaction. Given N variables, there are $O(N)$ possible main effects, $O(N^2)$ possible pairwise interactions, $O(N^3)$ possible 3-way interactions, $O(N^4)$ possible 4-way interactions, etc. This exponential growth in the hypothesis space of interaction terms simultaneously increases the probability that a universal approximator would estimate *some* interaction effect while decreasing the probability that the same universal approximator selects the *correct* interaction effect. For this reason, it can be possible for model classes to struggle with accurate recovery of parity functions without being inherently biased against high-order interactions. As shown in Figure 1, the exponential growth in the number of potential interaction terms is balanced by the exponential decay in learning rate induced by Dropout. In this way, large NNs trained with Dropout can have the convenient property that they are *capable* of learning high-order interactions but will put off the difficult task of learning these high-order interactions until simpler functions have been thoroughly explored.

C PROOF OF THEOREM 1

Proof. Let $\mathbb{E}[Y|X] = \sum_{u \in [d]} f_u(X_u)$ and $\mathbb{E}[Y] = 0$. Then with Input Dropout,

$$\mathbb{E}[Y|X \odot M] = \sum_{u \in [d]} P(X \odot M = X) f_u(X_u) + \big(1 - P(X \odot M = X)\big) \mathbb{E}[f_u(X_u \odot M^+)] \tag{4a}$$

$$= \sum_{u \in [d]} (1-p)^{|u|} f_u(X_u) + \big(1 - (1-p)^{|u|}\big) \mathbb{E}[f_u(X_u \odot M^+)] \tag{4b}$$

$$= \sum_{u \in [d]} (1-p)^{|u|} f_u(X_u) + \big(1 - (1-p)^{|u|}\big) \int f_u(X_{u \setminus v}, X_v) dX_v \qquad \text{for some } v \in u \tag{4c}$$

$$= \sum_{u \in [d]} (1-p)^{|u|} f_u(X_u) \tag{4d}$$

where M^+ is drawn uniformly from the Dropout masks with at least one zero value and the final equality holds by the orthogonality condition of the fANOVA decomposition (Eq. 1b in the main text). □

D PROOF OF THEOREM 2

Proof.

$$\mathbb{E}_M\big[\frac{\nabla_u(X_u, Y) \cdot \nabla_u(X_u \odot M, Y)}{\|\nabla_u(X_u, Y)\|}\big] \tag{5a}$$

$$= (1-p)^{|u|} \nabla_u(X_u, Y) + \frac{1}{\|\nabla_u(X_u, Y)\|} \big(1 - (1-p)^{|u|}\big) \mathbb{E}_{M^+}[\nabla_u(X_u \odot M^+, Y)] \tag{5b}$$

$$= (1-p)^{|u|} \nabla_u(X_u, Y) \tag{5c}$$

where the final equation holds by the orthongonality of fANOVA. □

E ADDITIONAL EXPERIMENTS

Figure E.3 are results for experiments with various Dropout rates on a NN with 128 hidden units in each layer. These results are analogous to the results shown in Fig. 2 of the main text for a NN with 32 hidden units in each layer.

(a) Total Effect: Activation Dropout

(b) Total Effect: Input Dropout

(c) Total Effect: Input + Activation Dropout

(d) Normalized Effect: Activation Dropout

(e) Normalized Effect: Input Dropout

(f) Normalized Effect: Input + Activation

(g) Shrinkage: Activation Dropout

(h) Shrinkage: Input Dropout

(i) Shrinkage: Input + Activation Dropout

Figure E.3: In this experiment, we train fully-connected neural networks on a dataset of pure noise (details in Sec. 5.2). Displayed values are the (mean $\pm$ std. over 10 initializations) of the proportion of the trained model's variance explained by each order of interaction effect. All neural networks in this figure have 128 units in each hidden layer (compared to 32 units per layer in Figure 2), and we see that Activation Dropout has only a small impact, while Input Dropout significantly reduces the estimated effect sizes of the high-order interactions. As expected, increasing the size of the hidden layers from 32 in Figure 2 to 128 in this Figure decreases the impact of Activation Dropout on high-order interactions, but does not reduce the effectiveness of Input Dropout.