Rethinking Layer Redundancy: Calibration Matters More Than Search in LLM Depth Pruning

Abstract

Depth pruning improves the inference efficiency of large language models by removing Transformer blocks. Prior work typically treats layer redundancy as an inherent structural property of pretrained networks, emphasizing importance criteria and search algorithms to identify removable layers. In this study, we empirically investigate depth pruning from a functional perspective. Evaluating representative LLM families across diverse calibration configurations and multiple search algorithms, we show that different configurations produce different pruning patterns. Furthermore, under a fixed calibration configuration, complex search algorithms yield marginal performance improvements over simple one-shot methods, converging to similar pruned subsets. Overall, our results suggest that the calibration configuration plays a substantially larger role than the choice of search algorithm in shaping pruning patterns and calibration perplexity, while contributing comparably to variance in downstream reasoning accuracy. This indicates that future pruning efforts may benefit from prioritizing the calibration configuration over search complexity.

1 Introduction

Large Language Models (LLMs) achieve strong capabilities but incur substantial deployment cost due to their scale (Grattafiori et al., 2024; Yang et al., 2025). Among structured compression approaches, *depth pruning* removes entire Transformer blocks, reducing inference cost approximately proportionally to the number of removed layers (Men et al., 2025; Song et al., 2024). Prior work has mainly advanced depth pruning through importance criteria (Men et al., 2025; Zhang et al., 2026; Wee et al., 2025) and search algorithms (Song et al., 2024; Chen et al., 2025; Tang et al., 2025; Sieberling et al., 2025; Jansen et al., 2026). Many existing methods implicitly treat layer redundancy as an

intrinsic property of the pretrained model. For example, ShortGPT (Men et al., 2025) ranks layers using cosine similarity independent of downstream tasks. Similarly, similarity- and magnitude-based methods (Song et al., 2024; Chen et al., 2025) apply largely static layer rankings across calibration strategies. We refer to this perspective as the *structural view* of redundancy.

However, it remains unclear whether redundancy is truly invariant. In practice, layers identified as redundant under language modeling perplexity may remain critical for downstream reasoning tasks. This raises a natural question: *Is layer redundancy an intrinsic structural property of the pretrained model, or is it functionally determined by the calibration configuration used during pruning?* We define this calibration configuration as the (objective, data) pair used to evaluate layer importance. Specifically, we compute $\mathcal{L}(\mathcal{D}; \theta_0)$ and use the resulting score to identify redundant layers.

Rather than proposing a new pruning algorithm, we study this question through a controlled empirical analysis. We formulate depth pruning as a subset selection problem, seeking an optimal subset of layers S^* (with budget $|S| = M$) that minimizes degradation under a specific calibration configuration:

$$S^* = \arg \min_{|S|=M} \mathcal{L}\big(\mathcal{D}; f_{\theta_0 \odot \mathbf{m}_S}\big),$$

where $\mathbf{m}_S$ denotes the corresponding layer mask vector. We investigate how these optimal pruning solutions vary with the calibration configuration and search procedure. Under this *functional view*, redundancy is not static; rather, it strictly depends on how the calibration configuration is set. To isolate these effects, we compare seven search algorithms under two distinct calibration configurations across three LLM families: language modeling perplexity on C4 (Raffel et al., 2020), and a task likelihood margin (Wee et al., 2025) on commonsense

reasoning datasets (Hu et al., 2023).

Our experiments reveal three consistent observations. First, pruning patterns differ substantially across calibration criteria: perplexity-based pruning concentrates on contiguous mid-to-late layers, whereas task likelihood margin pruning produces more distributed removal patterns. Second, calibration perplexity and downstream reasoning accuracy show negative or weak rank correlations under perplexity pruning, whereas they positively correlate under task likelihood margin pruning. Third, under a fixed calibration configuration, complex search algorithms yield only marginal performance improvements over simple one-shot methods and tend to converge to similar sets of pruned layers. Together, these findings suggest that the calibration configuration determines layer redundancy far more than the choice of search algorithm.

Our contributions are threefold: First, we introduce and empirically examine a *functional view* of layer redundancy in LLM depth pruning, demonstrating that redundancy is dictated by the calibration configuration rather than being an intrinsic model property. Second, we show that computationally expensive search algorithms yield marginal improvements over simple one-shot pruning in calibration perplexity, and offer comparable variance in downstream reasoning accuracy, under a fixed calibration configuration. Third, we identify a systematic misalignment between calibration perplexity and downstream reasoning accuracy, illustrating that layer importance is inherently specific to the chosen calibration configuration.

2 Related Works

Pruning paradigms. Unstructured pruning (Sun et al., 2024; Frantar and Alistarh, 2023; Yun, 2024) achieves high sparsity but often requires specialized hardware for practical acceleration. In contrast, structured pruning removes architectural components directly, enabling immediate efficiency gains on standard hardware. Among these approaches, *depth pruning* removes entire Transformer blocks (Song et al., 2024), with inference cost scaling approximately with the number of retained layers.

Importance criteria. Prior work proposes various criteria for identifying redundant layers, including cosine similarity (Men et al., 2025), interlayer output similarity (Song et al., 2024), mutual information (Zhang et al., 2026), and prompt-

conditioned routing (Wee et al., 2025). Many of these methods implicitly treat layer redundancy as an intrinsic property of the pretrained model that can be captured through a suitable ranking criterion. In contrast, we examine whether redundancy instead depends on the calibration configuration used during pruning.

Metric–search confound in depth pruning. Most depth pruning frameworks combine an importance metric with a search procedure. One-shot (Men et al., 2025) and greedy iterative (Song et al., 2024) methods make local pruning decisions, motivating more global approaches such as evolutionary search (Tang et al., 2025; Sieberling et al., 2025; Huang et al., 2025b) and constrained binary optimization (Jansen et al., 2026) for the NP-hard subset selection problem (Natarajan, 1995). However, prior frameworks often introduce a new search strategy together with a new importance metric, making improvements difficult to attribute to either component individually. To address this metric–search confound, we compare one-shot pruning, greedy iterative pruning, beam search, evolutionary search, constrained binary optimization (Jansen et al., 2026), and fast-block-select (Zhang et al., 2026) under unified calibration configurations and evaluation settings. Our prior-guided genetic algorithm (GA) and Bayesian optimization (BO) variants are therefore used as controlled search procedures rather than standalone methodological contributions.

3 Depth Pruning as Subset Selection

3.1 Problem Formulation

Let f_{θ_0} denote a pretrained LLM with N Transformer blocks, indexed by $I \triangleq \{1, \ldots, N\}$. We assume access to a calibration dataset $\mathcal{D}$ and an evaluation objective $\mathcal{L}(\mathcal{D}; \theta)$. Together, we define the combination of $\mathcal{L}$ and $\mathcal{D}$ as the *calibration configuration*. Throughout this work, $\mathcal{L}$ is instantiated as either perplexity or a task likelihood margin loss (Wee et al., 2025). A pruning decision is represented by a subset $S \subseteq I$ of removed layers, with an induced mask vector $(\mathbf{m}_S)_i \triangleq \mathbb{1}[i \notin S]$. We denote by $f_{\theta_0 \odot \mathbf{m}_S}$ the resulting pruned model. Given a pruning budget M, depth pruning seeks a subset $S \subseteq I$ with $|S| = M$ that minimizes degradation under the calibration configuration:

$$S^\star = \arg \min_{\substack{S \subseteq I \\ |S| = M}} \mathcal{L}\big(\mathcal{D}; f_{\theta_0 \odot \mathbf{m}_S}\big). \qquad (1)$$

Equation (1) highlights that depth pruning is functionally determined by the calibration configuration, rather than solely by the intrinsic properties of the pretrained model.

3.2 Functional View of Layer Redundancy

We argue that layer redundancy is not an intrinsic property of the pretrained model θ_0, but depends on the tuple $(\theta_0, \mathcal{L}, \mathcal{D})$. Varying the calibration objective $\mathcal{L}$ or dataset $\mathcal{D}$ alters the importance of hidden-state perturbations, yielding different minimizers for Equation (1). Thus, a layer i is *functionally redundant* under a specific calibration configuration if it belongs to an optimal subset $S^\star$.

Prior work implicitly adopts a *structural view*, assuming redundant layers remain static across calibration configurations and yield a universal ranking. In contrast, our *functional view* treats redundancy as determined by the calibration configuration. This raises a testable hypothesis: if redundancy is structural, varying the configuration will preserve pruning patterns and downstream rankings. If functional, different configurations will induce distinct subsets of removable layers.

3.3 Non-additivity and search complexity

A known challenge in depth pruning is that the effect of removing multiple layers is generally non-additive. Define

$$\Delta(S) \triangleq \mathcal{L}\big(\mathcal{D}; f_{\theta_0 \odot \mathbf{m}_S}\big) - \mathcal{L}\big(\mathcal{D}; f_{\theta_0}\big).$$

For disjoint subsets $S_1, S_2 \subseteq I$, in general,

$$\Delta(S_1 \cup S_2) \neq \Delta(S_1) + \Delta(S_2),$$

because removing one layer perturbs the hidden-state distribution encountered by subsequent layers (Huang et al., 2025a). This non-additivity limits the reliability of local layer scores, traditionally motivating the use of complex, subset-level search algorithms (e.g., evolutionary search or Bayesian optimization). However, if redundancy is fundamentally configuration-specific, the calibration configuration itself may have a stronger impact on the final pruning outcome than the choice of search algorithm. To disentangle these two factors, our empirical study explicitly isolates the effect of the calibration configuration from the search procedure.

4 Experimental Setup

By independently varying the search algorithm and the calibration configuration, we isolate their re-spective contributions to $S^\star$. All evaluated datasets are publicly available NLP benchmarks.

4.1 Models and calibration

To investigate whether layer redundancy is structurally intrinsic or functionally determined by the calibration configuration, we evaluate three 8B-scale LLMs (LLaMA3, LLaMA3.1, and Qwen3) across two distinct calibration configurations for Equation (1): perplexity on C4 (Raffel et al., 2020) and a task likelihood margin on Commonsense 170k (Hu et al., 2023).

4.2 Search algorithms and configurations

We implement the seven search algorithms introduced in Section 2: one-shot, greedy iterative, beam search ($B = 5$), prior-guided GA (population 16, elitism 0.2, mutation 0.15, 10 generations), prior-guided BO (200 trials, 10 random initializations), CBO (Jansen et al., 2026), and fast-block-select (Zhang et al., 2026). Under each experimental condition, all procedures share an identical calibration configuration ($\mathcal{L}$ and $\mathcal{D}$).

Adaptations for controlled comparison. To integrate CBO (Jansen et al., 2026) and *fast block select* (Zhang et al., 2026) into our controlled study, we apply two lightweight adaptations. First, we replace their original scoring functions with our unified calibration metric. Second, for *fast block select*, we introduce a history-tracking mechanism that restores the best observed configuration to prevent performance regression during iterative refinement.

Layer-level prior for global search. Unlike iterative methods, global search algorithms (GA, BO) lack sequential context and yield poor solutions under random initialization. To ensure fair comparison, we initialize them with a shared *single-layer ablation prior* $\mathbf{s} \in \mathbb{R}^N$, where $s_i \triangleq \mathcal{L}\big(\mathcal{D}; f_{\theta_0 \odot \mathbf{m}_{\{i\}}}\big)$ for $i \in I$. Recomputed for each (configuration, model) pair, $\mathbf{s}$ biases the initial GA population and seeds the BO surrogate.

4.3 Pruning regimes

We examine two budgets $M \in \{7, 9\}$, spanning moderate to high compression of the roughly 32–40 blocks in each model. We range from regimes where one-shot is typically considered adequate ($M = 7$) to regimes where reconstruction error becomes more pronounced ($M = 9$).

Figure 1: Pruned layers selected by each search algorithm across models and $M \in \{7, 9\}$. **(a)** Task likelihood margin configuration (calibration data: Commonsense 170k). **(b)** Calibration perplexity configuration (calibration data: C4). Colored blocks indicate removed layers.

4.4 Evaluation protocols

We align our downstream evaluation settings with the respective calibration configurations. For models calibrated on perplexity, we report the perplexity on the test splits of WikiText-2 (Merity et al., 2017), C4 (Raffel et al., 2020), and LAM-BADA (Paperno et al., 2016). Conversely, for models calibrated using a task likelihood margin, we compute zero-shot accuracy on HellaSwag (Zellers et al., 2019), WinoGrande (Sakaguchi et al., 2019), ARC (Clark et al., 2018), PIQA (Bisk et al., 2020), and BoolQ (Clark et al., 2019) using the LM Evaluation Harness (Gao et al., 2024).

Implementation details. We conduct all experiments on NVIDIA A40 48GB GPUs. To construct the calibration dataset, we randomly sample 64 instances from the respective training splits, truncating each to a maximum sequence length of 2048 tokens. We report results based on a single fixed random seed for all algorithms. Detailed search times for each algorithm are provided in Section 5.2.

5 Layer Redundancy Analysis

From a functional perspective, we present three key observations: (i) calibration configurations reshape the resulting sets of pruned layers (Section 5.1); (ii) performance variance across search algorithms is smaller in language modeling perplexity but comparable in downstream reasoning accuracy relative to the variation induced by the configuration (Sec-

Figure 2: Trade-off between perplexity (log scale) and zero-shot average accuracy across search algorithms under two calibration configurations. Top row: $M = 7$ removed layers; bottom row: $M = 9$.

Figure 3: Rank correlation between perplexity and zero-shot average accuracy for seven search algorithms per (model, M) setting. Top row: $M = 7$ removed layers; bottom row: $M = 9$. **(a)** Task likelihood margin pruning. **(b)** Calibration perplexity pruning. Each panel reports Spearman ρ computed across the seven algorithms ($n = 7$).

tion 5.2); and (iii) calibration perplexity and downstream reasoning rankings show negative or weak correlations under perplexity pruning but positive correlations under task likelihood margin pruning (Section 5.3). These findings suggest that layer redundancy depends on the calibration configuration, rather than being an intrinsic structural property of the network.

(a) Perplexity pruning

M	Method	LLaMA3 8B				LLaMA3.1 8B				Qwen3 8B			
		W2	C4	LMB	Avg	W2	C4	LMB	Avg	W2	C4	LMB	Avg
0	Dense (Baseline)	6.14	8.31	16.11	10.18	6.24	8.37	16.21	10.27	9.71	13.65	23.56	15.64
7	One-shot	13.12	16.71	28.21	**19.35**	14.74	16.72	31.60	21.02	17.53	22.20	36.53	25.42
	Greedy iterative	13.12	16.70	29.88	19.90	13.10	16.58	29.64	19.77	15.55	19.92	33.70	23.06
	Beam (B=5)	13.12	16.70	29.88	19.90	13.10	16.58	29.64	19.77	15.55	19.92	33.70	23.06
	GA (P=16)	13.16	17.02	28.77	19.65	13.10	16.58	29.64	19.77	15.14	19.83	34.96	23.31
	BO (T=200)	13.12	16.71	28.21	**19.35**	13.32	16.67	28.78	**19.59**	15.23	20.15	33.32	**22.90**
	CBO	13.33	17.21	28.30	19.61	13.30	16.85	28.89	19.68	28.72	34.74	96.82	53.42
	Fast-block-select	17.40	19.47	30.78	22.55	13.66	16.84	30.16	20.22	17.19	22.94	37.45	25.86
9	One-shot	21.47	23.25	40.65	28.46	20.85	22.71	41.02	28.19	24.77	29.51	42.97	32.42
	Greedy iterative	20.16	22.18	42.92	28.42	34.77	21.71	93.28	49.92	19.78	23.97	38.92	**27.56**
	Beam (B=5)	18.27	21.98	38.22	26.16	17.88	21.28	37.35	**25.51**	19.78	23.97	38.92	**27.56**
	GA (P=16)	18.31	22.61	36.38	**25.77**	18.77	21.49	37.84	26.03	21.52	24.24	43.41	29.72
	BO (T=200)	18.27	21.98	38.22	26.16	22.42	21.33	55.56	33.10	19.15	23.62	39.96	27.58
	CBO	22.81	26.62	47.07	32.17	28.03	28.26	48.35	34.88	68.02	63.13	230.18	120.44
	Fast-block-select	45.43	23.57	69.81	46.27	29.91	22.36	54.62	35.63	24.77	29.51	42.97	32.42

(b) Task-likelihood margin pruning

M	Method	LLaMA3 8B				LLaMA3.1 8B				Qwen3 8B			
		W2	C4	LMB	Avg	W2	C4	LMB	Avg	W2	C4	LMB	Avg
0	Dense (Baseline)	6.14	8.31	16.11	10.18	6.24	8.37	16.21	10.27	9.71	13.65	23.56	15.64
7	One-shot	25.94	31.26	65.12	40.78	110.06	110.93	277.76	**166.25**	8,623.8	4,883.1	7,987.8	7,164.9
	Greedy iterative	43.56	40.75	78.57	54.29	645.59	724.36	600.24	656.73	541.35	708.45	1,732.2	993.99
	Beam (B=5)	196.24	262.31	376.36	278.30	1,292.3	1,431	1,387.5	1,370.3	541.35	708.45	1,732.2	993.99
	GA (P=16)	93.55	69.93	145.74	103.08	194.02	199.88	334.03	242.65	7,889.4	5,175.5	20,033	11,033
	BO (T=200)	19.25	19.72	35.39	**24.79**	217.04	305.88	335.38	286.10	219.58	197.63	359.27	258.83
	CBO	39.75	41.42	68.76	49.98	147.98	180.73	241.88	190.20	152.64	79.47	254.69	**162.27**
	Fast-block-select	25.94	31.26	65.12	40.78	110.06	110.93	277.76	**166.25**	8,623.8	4,883.1	7,987.8	7,164.9
9	One-shot	106.75	97.16	212.98	138.97	615.04	336.24	2,066.6	**1,006**	54,814	17,983	89,417	54,071
	Greedy iterative	58.98	57.92	124.10	**80.33**	1,152	1,001.5	1,370	1,174.5	588.35	807.86	1,503.6	966.6
	Beam (B=5)	434.87	474.15	616.99	508.67	5,540.1	3,264.3	6,394	5,066.1	588.35	807.86	1,503.6	966.6
	GA (P=16)	145.45	132.86	357.83	212.05	707.94	6,847.7	1,671.1	3,075.6	2,348.6	1,260.8	2,223.1	1,944.2
	BO (T=200)	85.64	86.60	141.03	104.42	12,726	3,903.3	11,891	9,506.6	42.05	45.83	96.08	**61.32**
	CBO	88.95	81.39	126.66	99.00	655.32	376.98	2,211.5	1,081.3	349.47	167.86	877.15	464.83
	Fast-block-select	106.75	97.16	212.98	138.97	615.04	336.24	2,066.6	**1,006**	54,814	17,983	89,417	54,071

Table 1: Perplexity ($\downarrow$) on WikiText-2 (W2), C4, and LAMBADA (LMB) across three 8B LLMs under two calibration configurations. **(a)** Pruning by calibration perplexity on C4. **(b)** Pruning by task-likelihood margin (TLM) loss on Commonsense 170k. Models are evaluated without fine-tuning. M denotes the number of removed layers. Lowest average perplexity (**Avg**) per (M, model) pair is in bold.

5.1 Configuration-driven pruning outcomes

Configurations reshape pruned layers. Figure 1 visualizes the removed layers under each calibration configuration. Perplexity pruning targets contiguous mid-to-late layers, with diverse search procedures (e.g., greedy iterative, GA, BO) converging to highly similar pruned layers on LLaMA models (mean pairwise Jaccard 0.63 across four (model, M) cells) but with substantially lower agreement on Qwen3 (0.36). In contrast, task likelihood margin pruning yields more distributed and search-dependent removals with comparable algorithm-level agreement across all three models (mean Jaccard 0.51). We report cell-level Jaccard values in Appendix A.2.

Convergence is not a prior artifact. The prior-guided GA and BO share the single-layer ablation prior (Section 4.2), but the convergence above is not an initialization artifact. First, it is dictated by the calibration configuration (Figure 1): the same procedures converge under perplexity but diverge under the task likelihood margin. Second, within the task likelihood margin cell, WikiText-2 perplexity varies by two to four orders of magnitude across procedures (Table 1), confirming substantial deviation from the prior.

5.2 Configuration-driven variance

Configurations dominate perplexity variance. We first examine how the calibration configuration affects language modeling perplexity (Table 1). Under a fixed (model, M) setting, altering the

Model	M	Method	Hella	Wino	ARC-E	ARC-C	PIQA	BoolQ	Avg
LLaMA3.1 8B	0	Dense (Baseline)	79.31	74.59	82.45	54.86	81.12	83.00	75.89
	7	One-shot	63.62	66.61	58.84	43.00	69.04	73.67	**62.47**
		Greedy iterative	60.19	64.48	59.39	40.27	70.51	71.04	60.98
		Beam search ($B=5$)	57.85	62.98	56.44	42.15	70.02	62.29	58.62
		GA ($P=16$)	64.01	63.61	54.25	40.10	70.78	63.94	59.45
		BO ($T=200$)	58.77	64.64	56.99	37.88	69.37	58.32	57.66
		CBO	60.48	66.22	58.80	41.04	70.57	53.49	58.43
		Fast-block-select	63.62	66.61	58.84	43.00	69.04	73.67	**62.47**
	9	One-shot	54.81	62.67	49.83	38.31	65.02	66.94	56.26
		Greedy iterative	55.94	63.69	50.17	36.43	68.44	64.83	56.58
		Beam search ($B=5$)	52.73	62.59	50.00	38.40	65.72	63.12	55.43
		GA ($P=16$)	50.26	64.09	50.63	38.57	66.21	52.08	53.64
		BO ($T=200$)	52.20	63.46	52.36	39.08	66.43	63.67	56.20
		CBO	55.04	62.12	49.66	37.71	67.19	68.29	**56.67**
		Fast-block-select	54.81	62.67	49.83	38.31	65.02	66.94	56.26
Qwen3 8B	0	Dense (Baseline)	74.94	67.72	80.93	56.66	77.69	86.57	74.09
	7	One-shot	46.08	58.48	55.26	38.82	62.68	71.04	55.39
		Greedy iterative	52.87	60.69	59.76	40.10	66.10	86.39	**60.99**
		Beam search ($B=5$)	52.87	60.69	59.76	40.10	66.10	86.39	**60.99**
		GA ($P=16$)	45.96	60.06	58.84	40.02	63.66	73.67	57.03
		BO ($T=200$)	54.52	58.01	60.90	38.40	65.67	81.50	59.83
		CBO	52.80	63.30	58.25	40.36	65.34	83.85	60.65
		Fast-block-select	46.08	58.48	55.26	38.82	62.68	71.04	55.39
	9	One-shot	41.52	60.93	51.73	34.90	61.59	69.11	53.30
		Greedy iterative	51.76	59.59	58.67	40.02	65.02	85.60	60.11
		Beam search ($B=5$)	51.76	59.59	58.67	40.02	65.02	85.60	60.11
		GA ($P=16$)	44.99	57.38	55.22	36.35	62.57	62.17	53.11
		BO ($T=200$)	57.16	60.30	61.45	39.16	66.81	78.84	**60.62**
		CBO	47.29	59.51	46.38	34.90	62.68	79.11	54.98
		Fast-block-select	41.52	60.93	51.73	34.90	61.59	69.11	53.30

Table 2: Zero-shot accuracy (↑) on HellaSwag (Hella), WinoGrande (Wino), ARC-Easy (ARC-E), ARC-Challenge (ARC-C), PIQA, and BoolQ for LLaMA3.1 and Qwen3 8B, pruned by minimizing the task likelihood margin on Commonsense 170k and evaluated without fine-tuning. M denotes the number of removed layers; the highest **Avg** per M is in bold. LLaMA3 8B results are in Appendix A.1.

Method	Time (s)	Average acc. (%)
One-shot	551	57.99
Greedy iterative	3,223	60.69
Beam search ($B=5$)	13,869	60.12
GA ($P=16$)	3,544	57.63
BO ($T=200$)	4,233	60.90
CBO	8,173	59.93
Fast-block-select	429	57.99

Table 3: Search time in seconds and average zero-shot accuracy (%) for LLaMA3 8B at $M=7$ under task likelihood margin pruning.

calibration configuration shifts the average perplexity by one to three orders of magnitude (e.g., $\sim 10^1 \to 10^4$ on Qwen3 8B, $M=9$, one-shot). Conversely, altering the search algorithm changes the average perplexity by less than one order of magnitude across most evaluated conditions.

Configuration does not dominate accuracy. This pattern does not extend to downstream accuracy (Tables 2, 4). Altering the configuration shifts average zero-shot accuracy by at most 5.76 points (Qwen3 8B, $M=9$, greedy iterative), whereas varying the search algorithm shifts it by up to 7.51 points (Qwen3 8B, $M=9$, task likelihood margin). Since search-induced and configuration-induced variances are comparable, calibration perplexity is a limited proxy for downstream reasoning under aggressive pruning.

Configurations reshape the trade-off. Figure 2 visualizes this trade-off: perplexity-pruned models cluster at low perplexity, while task likelihood margin pruning shifts models substantially along the perplexity axis without a comparable shift along the accuracy axis.

Search complexity offers limited gains. Table 3 shows that increasing search complexity yields limited accuracy improvements and occasionally degrades performance. One-shot pruning reaches

Model	M	Method	Hella	Wino	ARC-E	ARC-C	PIQA	BoolQ	Avg
	0	Dense (Baseline)	79.31	74.59	82.45	54.86	81.12	83.00	75.89
		One-shot	62.14	55.41	64.06	36.43	75.03	62.57	59.27
		Greedy iterative	61.83	56.91	57.24	33.11	73.29	60.37	57.12
		Beam search ($B = 5$)	61.83	56.91	57.24	33.11	73.29	60.37	57.12
	7	GA ($P = 16$)	61.83	56.91	57.24	33.11	73.29	60.37	57.12
		BO ($T = 200$)	62.03	57.46	63.51	36.01	74.05	53.33	57.73
		CBO	64.12	62.83	65.28	38.82	74.10	56.85	**60.33**
LLaMA3.1 8B		Fast-block-select	60.58	56.75	62.16	35.07	74.21	62.39	58.53
		One-shot	56.92	55.80	56.82	33.70	70.57	62.05	55.98
		Greedy iterative	55.97	53.04	58.29	34.30	70.78	61.99	55.73
		Beam search ($B = 5$)	56.02	58.88	57.24	34.30	71.76	47.92	54.35
	9	GA ($P = 16$)	57.13	56.91	59.13	33.96	71.87	50.28	54.88
		BO ($T = 200$)	55.09	56.83	58.38	34.30	71.98	61.68	**56.38**
		CBO	56.60	60.69	52.95	30.03	69.04	63.70	55.50
		Fast-block-select	56.14	54.62	58.00	32.17	70.78	61.68	55.57
	0	Dense (Baseline)	74.94	67.72	80.93	56.66	77.69	86.57	74.09
		One-shot	56.80	54.85	66.84	37.03	72.20	65.60	58.89
		Greedy iterative	59.06	59.04	64.77	41.30	72.63	69.48	61.05
		Beam search ($B = 5$)	59.06	59.04	64.77	41.30	72.63	69.48	61.05
	7	GA ($P = 16$)	56.74	55.64	63.30	37.29	71.82	74.59	59.90
		BO ($T = 200$)	58.82	57.38	65.19	38.82	73.29	59.69	58.87
		CBO	57.04	59.27	66.54	41.30	70.35	80.06	**62.43**
Qwen3 8B		Fast-block-select	51.48	54.46	61.74	36.09	71.11	61.56	56.07
		One-shot	50.56	51.93	58.84	34.04	69.86	63.09	54.72
		Greedy iterative	54.62	54.14	63.93	37.20	71.27	44.92	54.35
		Beam search ($B = 5$)	54.62	54.14	63.93	37.20	71.27	44.92	54.35
	9	GA ($P = 16$)	51.85	54.46	55.72	34.98	70.57	66.82	55.73
		BO ($T = 200$)	52.37	54.22	60.14	35.15	70.29	66.21	56.40
		CBO	43.93	53.20	53.41	33.53	63.76	67.28	52.52
		Fast-block-select	50.56	51.93	58.84	34.04	69.86	63.09	54.72

Table 4: Zero-shot accuracy (↑) of perplexity-pruned models on downstream reasoning tasks for LLaMA3.1 and Qwen3 8B. Each model is pruned by minimizing calibration perplexity on C4 and evaluated without fine-tuning. M denotes the number of removed layers. Highest average accuracy (**Avg**) per M is in bold. Results for LLaMA3 8B are provided in Appendix A.1.

57.99% accuracy in 550 seconds, while BO requires over 70 minutes for a gain of less than 3 points (60.90%). Beam search (13,869 seconds) and GA (∼1 hour) further underperform the greedy iterative approach and the one-shot baseline, respectively.

5.3 Perplexity-accuracy misalignment

Figure 3 reports Spearman correlations between perplexity and zero-shot accuracy across seven algorithms. Task likelihood margin pruning yields positive correlations across all six (model, M) settings (median $+0.55$, range $+0.20$ to $+0.78$), whereas perplexity pruning yields negative correlations in five of six settings (median -0.27, range -0.78 to $+0.11$). Section 5.2 shows orders-of-magnitude perplexity differences lack proportional accuracy differences, indicating perplexity is a limited proxy for downstream reasoning. Given the small sample size ($n = 7$), we consider these general trends, not statistically rigorous results.

6 Conclusion

We examine whether layer redundancy in LLM depth pruning is an intrinsic structural property or determined by the calibration configuration. By disentangling the calibration configuration from the search procedure across representative LLM families, diverse calibration configurations, and a wide array of search algorithms, we find strong evidence for the *functional view*. Specifically, different configurations induce different pruning patterns, and calibration perplexity rankings often fail to align with downstream reasoning accuracy. Furthermore, under a fixed calibration configuration, different search algorithms converge to similar pruned subsets. These results demonstrate that the calibration configuration dominates pruning patterns and calibration perplexity, with comparable effects on downstream reasoning accuracy.

Limitations

Our study primarily evaluates calibration perplexity and downstream reasoning accuracy under controlled depth pruning. Other capabilities, such as long-context reasoning or instruction-following, may exhibit different redundancy patterns. Additionally, our empirical analysis does not theoretically explain why distinct calibration configurations induce divergent pruning structures. We further note that the dominant effect of the calibration configuration holds for pruning patterns and calibration perplexity but not for downstream reasoning accuracy, where its effect is comparable to that of the search algorithm (Section 5.2)—an asymmetry suggesting that calibration perplexity is a limited proxy for downstream reasoning under aggressive depth pruning.

Four methodological limitations remain. First, because our calibration configurations vary the loss objective and data simultaneously (perplexity on C4 versus task likelihood margin on Commonsense 170k) without cross-controls, the observed differences reflect their joint effect. Second, since all evaluated search procedures rely on a shared single-layer ablation prior (Section 4.2), we lack random-initialization controls to fully isolate this prior's contribution. Third, although Section 3.3 demonstrates the non-additivity of multi-layer removal, subset-level search procedures (e.g., BO, beam search) do not consistently outperform simple one-shot pruning under our evaluated budgets. Fourth, computational costs restrict us to a single random seed per experimental setting. Consequently, we emphasize general trends—specifically, the variation induced by the calibration configuration relative to the search algorithm—rather than precise point estimates across seeds. Future work should extend this functional perspective to broader model coverage and evaluation settings, theoretically characterize configuration-dependent redundancy, and isolate these methodological factors.

Ethics Statement

This work presents a controlled empirical analysis of depth pruning strategies for large language models using publicly available datasets and benchmark tasks. No human participants, private information, or sensitive data are involved in our experiments. Because model compression can alter model behavior in ways that may not be fully reflected by perplexity or downstream reasoning evaluations, pruned models should be carefully validated before deployment in high-risk or safety-sensitive applications. In addition, our findings suggest that layer redundancy is closely tied to the calibration configuration, implying that pruning decisions should be made with awareness of the target deployment setting and evaluation criteria.

References

Yonatan Bisk, Rowan Zellers, Ronan Le Bras, Jianfeng Gao, and Yejin Choi. 2020. Piqa: Reasoning about physical commonsense in natural language. In *Thirty-Fourth AAAI Conference on Artificial Intelligence*.

Xinrui Chen, Hongxing Zhang, Fanyi Zeng, Yongxian Wei, Yizhi Wang, Xitong Ling, Guanghao Li, and Chun Yuan. 2025. Prune&comp: Free lunch for layer-pruned llms via iterative pruning with magnitude compensation. *arXiv preprint arXiv:2507.18212*.

Christopher Clark, Kenton Lee, Ming-Wei Chang, Tom Kwiatkowski, Michael Collins, and Kristina Toutanova. 2019. BoolQ: Exploring the surprising difficulty of natural yes/no questions. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 2924–2936. Association for Computational Linguistics.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. 2018. Think you have solved question answering? try arc, the ai2 reasoning challenge. *ArXiv*, abs/1803.05457.

Elias Frantar and Dan Alistarh. 2023. Sparsegpt: Massive language models can be accurately pruned in one-shot. In *ICML*, pages 10323–10337.

Leo Gao, Jonathan Tow, Baber Abbasi, Stella Biderman, Sid Black, Anthony DiPofi, Charles Foster, Laurence Golding, Jeffrey Hsu, Alain Le Noac'h, Haonan Li, Kyle McDonell, Niklas Muennighoff, Chris Ociepa, Jason Phang, Laria Reynolds, Hailey Schoelkopf, Aviya Skowron, Lintang Sutawika, and 5 others. 2024. The language model evaluation harness.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, and 1 others. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Zhiqiang Hu, Lei Wang, Yihuai Lan, Wanyu Xu, Ee-Peng Lim, Lidong Bing, Xing Xu, Soujanya Poria, and Roy Lee. 2023. LLM-adapters: An adapter family for parameter-efficient fine-tuning of large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Pro-*

cessing, pages 5254–5276, Singapore. Association for Computational Linguistics.

Weizhong Huang, Yuxin Zhang, Xiawu Zheng, Fei Chao, and Rongrong Ji. 2025a. Determining layer-wise sparsity for large language models through a theoretical perspective. In *Forty-second International Conference on Machine Learning*.

Weizhong Huang, Yuxin Zhang, Xiawu Zheng, Fei Chao, and Rongrong Ji. 2025b. Towards efficient automatic self-pruning of large language models. *arXiv preprint arXiv:2502.14413*.

David Jansen, Roman Rausch, David Montero, and Roman Orus. 2026. Block removal for large language models through constrained binary optimization. *arXiv preprint arXiv:2602.00161*.

Xin Men, Mingyu Xu, Qingyu Zhang, Qianhao Yuan, Bingning Wang, Hongyu Lin, Yaojie Lu, Xianpei Han, and Weipeng Chen. 2025. ShortGPT: Layers in large language models are more redundant than you expect. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 20192–20204, Vienna, Austria. Association for Computational Linguistics.

Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. 2017. Pointer sentinel mixture models. In *International Conference on Learning Representations*.

B. K. Natarajan. 1995. Sparse approximate solutions to linear systems. *SIAM Journal on Computing*, 24(2):227–234.

Denis Paperno, Germán Kruszewski, Angeliki Lazaridou, Ngoc Quan Pham, Raffaella Bernardi, Sandro Pezzelle, Marco Baroni, Gemma Boleda, and Raquel Fernandez. 2016. The LAMBADA dataset: Word prediction requiring a broad discourse context. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1525–1534, Berlin, Germany. Association for Computational Linguistics.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. 2020. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of machine learning research*, 21(140):1–67.

Keisuke Sakaguchi, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. 2019. Winogrande: An adversarial winograd schema challenge at scale. *arXiv preprint arXiv:1907.10641*.

Oliver Sieberling, Denis Kuznedelev, Eldar Kurtic, and Dan Alistarh. 2025. Evopress: Accurate dynamic model compression via evolutionary search. In *Forty-second International Conference on Machine Learning*.

Jiwon Song, Kyungseok Oh, Taesu Kim, Hyungjun Kim, Yulhwa Kim, and Jae-Joon Kim. 2024. Sleb: Streamlining llms through redundancy verification and elimination of transformer blocks. In *Proceedings of the 41st International Conference on Machine Learning*.

Mingjie Sun, Zhuang Liu, Anna Bair, and J Zico Kolter. 2024. A simple and effective pruning approach for large language models. In *The Twelfth International Conference on Learning Representations*.

Shengkun Tang, Oliver Sieberling, Eldar Kurtic, Zhiqiang Shen, and Dan Alistarh. 2025. Darwinlm: Evolutionary structured pruning of large language models. *arXiv preprint arXiv:2502.07780*.

Juyoung Wee, Minjae Park, and Jaeho Lee. 2025. Prompt-based depth pruning of large language models. In *International Conference on Machine Learning*.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, and 1 others. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

Juyoung Yun. 2024. Robust neural pruning with gradient sampling optimization for residual neural networks. In *2024 International Joint Conference on Neural Networks (IJCNN)*, pages 1–10.

Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. 2019. Hellaswag: Can a machine really finish your sentence? In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*.

Hao Zhang, Zhibin Zhang, Guangxin Wu, He Chen, Jiafeng Guo, and Xueqi Cheng. 2026. Mi-prun: Optimize large language model pruning via mutual information. *arXiv preprint arXiv:2601.07212*.

A Appendix

A.1 Results on LLaMA3 8B

We provide per-task zero-shot accuracy for LLaMA3 8B under both calibration configurations, supplementing the LLaMA3.1 8B and Qwen3 8B results in the main text. Table 6 reports performance under the task likelihood margin configuration, and Table 7 details the calibration perplexity configuration across HellaSwag, WinoGrande, ARC-Easy, ARC-Challenge, PIQA, and BoolQ. The observed patterns align with the findings reported in the main text.

A.2 Algorithm-level agreement

To quantify how strongly the seven search algorithms agree on which layers to remove under each calibration configuration, we compute three statistics over the seven pruned layer sets $\{S_1, \ldots, S_7\}$ per (model, M) cell. **Mean pairwise Jaccard** averages the $\binom{7}{2} = 21$ pairwise similarities $|S_i \cap S_j|/|S_i \cup S_j|$. **Range** reports the minimum and maximum pairwise Jaccard, capturing the spread of agreement across algorithm pairs. **Full overlap** is the ratio $|\bigcap_i S_i|/|\bigcup_i S_i|$, indicating how many layers are selected by all seven algorithms relative to the total set of layers ever selected. Table 5 reports the per-cell values that underlie the summary statistics in Section 5.1.

B Licenses and Terms of Use

All datasets and models used in this work are publicly available and used in compliance with their respective licenses and terms of use. We use them solely for non-commercial research purposes, consistent with their intended use.

Models. LLaMA3 8B (Grattafiori et al., 2024) is released under the Meta Llama 3 Community License Agreement. LLaMA3.1 8B (Grattafiori et al., 2024) is released under the Llama 3.1 Community License Agreement. Qwen3 8B (Yang et al., 2025) is released under the Apache 2.0 License.

Calibration datasets. C4 (Raffel et al., 2020) is released under the ODC-BY License, with the underlying Common Crawl content also subject to Common Crawl's terms of use. The Commonsense 170k dataset (Hu et al., 2023) is released under the ODC-BY License as part of the LLM-Adapters release; it aggregates the training splits of several commonsense reasoning benchmarks, whose original licenses also apply to the corresponding constituents.

Evaluation datasets. WikiText-2 (Merity et al., 2017) is released under the CC BY-SA License; the underlying Wikipedia content is also available under the GFDL. LAMBADA (Paperno et al., 2016) is released under the CC BY 4.0 License. HellaSwag (Zellers et al., 2019) is released under the MIT License. WinoGrande (Sakaguchi et al., 2019) is released under the CC BY 4.0 License. ARC-Easy and ARC-Challenge (Clark et al., 2018) are released under the CC BY-SA 4.0 License. PIQA (Bisk et al., 2020) is released under the Academic Free License (AFL) v3.0. BoolQ (Clark et al., 2019) is released under the CC BY-SA 3.0 License.

Model	M	Configuration	Mean	Range	Full overlap
LLaMA3 8B	7	Perplexity	0.557	[0.273, 1.000]	3/13 (0.231)
		Task likelihood margin	0.471	[0.167, 1.000]	2/15 (0.133)
	9	Perplexity	0.669	[0.385, 1.000]	4/13 (0.308)
		Task likelihood margin	0.488	[0.286, 1.000]	3/20 (0.150)
LLaMA3.1 8B	7	Perplexity	0.686	[0.400, 1.000]	4/10 (0.400)
		Task likelihood margin	0.410	[0.273, 1.000]	1/14 (0.071)
	9	Perplexity	0.592	[0.286, 0.800]	3/15 (0.200)
		Task likelihood margin	0.550	[0.286, 1.000]	3/15 (0.200)
Qwen3 8B	7	Perplexity	0.338	[0.000, 1.000]	0/19 (0.000)
		Task likelihood margin	0.599	[0.273, 1.000]	2/11 (0.182)
	9	Perplexity	0.388	[0.059, 1.000]	0/22 (0.000)
		Task likelihood margin	0.546	[0.286, 1.000]	3/14 (0.214)

Table 5: Pairwise Jaccard statistics over the seven pruned layer sets per (model, M) cell, under each calibration configuration. **Mean**: average of $\binom{7}{2} = 21$ pairwise Jaccard similarities. **Range**: minimum and maximum pairwise similarity. **Full overlap**: $|\bigcap_i S_i|/|\bigcup_i S_i|$, the ratio of layers selected by all seven algorithms to those selected by any algorithm. Higher values indicate stronger algorithm-level convergence on the same pruned subset under a fixed calibration configuration.

M	Method	Hella	Wino	ARC-E	ARC-C	PIQA	BoolQ	Avg
0	Dense (Baseline)	79.23	73.72	77.53	54.10	80.63	82.26	74.58
7	One-shot	59.23	64.80	56.23	35.58	69.37	62.72	57.99
	Greedy iterative	60.47	69.30	58.16	38.82	69.91	67.49	60.69
	Beam search ($B = 5$)	61.04	64.17	54.17	39.59	70.73	71.04	60.12
	GA ($P = 16$)	53.14	69.22	52.74	39.25	67.41	64.01	57.63
	BO ($T = 200$)	64.34	67.32	60.06	36.95	71.98	64.77	**60.90**
	CBO	59.63	66.54	54.00	36.35	69.97	73.09	59.93
	Fast-block-select	59.23	64.80	56.23	35.58	69.37	62.72	57.99
9	One-shot	46.63	60.14	46.55	34.39	64.15	63.18	52.51
	Greedy iterative	53.28	63.46	49.87	31.66	65.13	63.21	54.43
	Beam search ($B = 5$)	55.03	60.46	43.60	33.45	65.78	58.04	52.73
	GA ($P = 16$)	49.65	63.38	48.32	34.98	64.74	65.87	**54.49**
	BO ($T = 200$)	53.37	65.04	46.51	36.01	65.83	57.71	54.08
	CBO	51.86	62.75	47.01	34.56	62.73	64.22	53.85
	Fast-block-select	46.63	60.14	46.55	34.39	64.15	63.18	52.51

Table 6: Zero-shot accuracy (↑) of task likelihood margin-pruned LLaMA3 8B on downstream reasoning tasks. The model is pruned by minimizing the task likelihood margin loss on Commonsense 170k and evaluated without fine-tuning on HellaSwag (Hella), WinoGrande (Wino), ARC-Easy (ARC-E), ARC-Challenge (ARC-C), PIQA, and BoolQ. M denotes the number of removed layers. Highest average accuracy (**Avg**) per M is in bold.

M	Method	Hella	Wino	ARC-E	ARC-C	PIQA	BoolQ	Avg
0	Dense (Baseline)	79.23	73.72	77.53	54.10	80.63	82.26	74.58
7	One-shot	62.32	55.56	60.02	33.62	73.45	48.01	55.50
	Greedy iterative	61.60	59.12	54.92	33.87	73.56	58.65	56.95
	Beam search ($B = 5$)	61.60	59.12	54.92	33.87	73.56	58.65	56.95
	GA ($P = 16$)	63.56	61.64	60.27	35.75	73.23	43.18	56.27
	BO ($T = 200$)	62.32	55.56	60.02	33.62	73.45	48.01	55.50
	CBO	62.68	63.61	62.50	36.52	73.34	45.96	57.44
	Fast-block-select	63.86	59.35	57.74	34.30	71.82	62.32	**58.23**
9	One-shot	56.65	53.99	54.88	31.40	69.64	62.51	**54.84**
	Greedy iterative	57.56	58.48	49.37	31.40	69.31	62.45	54.76
	Beam search ($B = 5$)	57.28	57.30	50.17	33.02	69.31	44.25	51.89
	GA ($P = 16$)	55.56	56.20	55.47	32.42	70.78	43.00	52.24
	BO ($T = 200$)	57.28	57.30	50.17	33.02	69.31	44.25	51.89
	CBO	55.83	58.88	56.82	33.62	69.42	37.83	52.07
	Fast-block-select	55.68	53.51	54.55	31.66	70.35	61.99	54.62

Table 7: Zero-shot accuracy (↑) of perplexity-pruned LLaMA3 8B on downstream reasoning tasks. The model is pruned by minimizing calibration perplexity on C4 and evaluated on zero-shot benchmarks without fine-tuning. M denotes the number of removed layers. Highest average accuracy (**Avg**) per M is in bold.