Surprise Minimizing Multi-Agent Learning with Energy-based Models

Abstract

Multi-Agent Reinforcement Learning (MARL) has demonstrated significant success by virtue of collaboration across agents. Recent work, on the other hand, introduces *surprise* which quantifies the degree of change in an agent's environment. Surprise-based learning has received significant attention in the case of single-agent entropic settings but remains an open problem for fast-paced dynamics in multi-agent scenarios. A potential alternative to address surprise may be realized through the lens of free-energy minimization. We explore surprise minimization in multi-agent learning by utilizing the free energy across all agents in a multi-agent system. A temporal Energy-Based Model (EBM) represents an estimate of surprise which is minimized over the joint agent distribution. Our formulation of the EBM is theoretically akin to the minimum conjugate entropy objective and highlights suitable convergence towards minimum surprising states. We further validate our theoretical claims in an empirical study of multi-agent tasks demanding collaboration in the presence of fast-paced dynamics.

1 Introduction

The rise of RL has led to an increasing interest in the study of multi-agent systems (Lowe et al., 2017; Vinyals et al., 2019), commonly known as Multi-Agent Reinforcement Learning (MARL). In the case of partially observable settings, MARL enables the learning of policies with centralised training and decentralised control (Kraemer & Banerjee, 2016). This has proven to be useful for exploiting value-based methods which motivate collaboration across large number of agents. But how do agents behave in the presence of sudden environmental changes?

Consider the problem of autonomous driving wherein a *driver* (agent) autonomously operates a vehicle in real-time. The *driver* learns to optimize the reward function by maintaining constant speed and covering more distance in different traffic conditions. Whenever the vehicle approaches an obstacle, the *driver* acts to avoid it by utilizing the brake and directional steering commands. However, due to the fast-paced dynamics of the environment, say fast-moving traffic, the agent may abruptly encounter an obstacle (*a person running across the street*) which may result in a collision. Irrespective of the optimal action (*pushing of brakes*) executed by the agent, the vehicle may fail to evade the collision as a result of the abrupt temporal change.

Surprise minimization (Berseth et al., 2019) is a recent phenomenon observed in the case of single-agent RL methods which deals with environments consisting of rapidly changing states. In the case of model-based RL (Kaiser et al., 2019), surprise minimization is used as an effective planning tool in the agent's model (Berseth et al., 2019) whereas in the case of model-free RL, surprise minimization is witnessed as an intrinsic motivation (Achiam & Sastry, 2017; Macedo et al., 2004) or generalization problem (Chen, 2020). On the other hand, MARL does not account for surprise across agents as a result of which agents remain unaware of drastic changes in the environment (Macedo & Cardoso, 2005). Thus, surprise minimization in the case of multi-agent settings requires attention from a critical standpoint.

A potential pathway to treat surprising states may be realized in light of free-energy minimization. The free-energy principle depicts convergence to local niches and provides a general recipe for cognitive stability among agents. Through this lens, we unify surprise with free-energy in the multi-agent setting. We construct a temporal EBM which represents an estimate of surprise agents may face in the environment. All agents jointly minimize this estimate utilizing temporal difference

learning upon their value functions and the EBM. Our formulation of free-energy minimization is theoretically akin to minimizing the entropy in conjugate gradient space. This insight provides a suitable convergence result towards minimum surprising states (or niches) of the agent state distributions. In an empirical study of multi-agent tasks which present significant collaboration bottlenecks and fast-paced dynamics, we validate our theoretical claims and motivate the practical usage of EBMs in MARL.

2 RELATED WORK

Surprise Minimization: Despite the recent success of value-based methods (Mnih et al., 2016; Hessel et al., 2017) RL agents suffer from spurious state spaces and encounter sudden changes in trajectories. Quantitatively, surprise has been studied as a measure of deviation (Berseth et al., 2019; Chen, 2020) among states encountered by the agent during its interaction with the environment. While exploring (Burda et al., 2019; Thrun, 1992) the environment, agents tend to have higher deviation among states which is gradually reduced by gaining a significant understanding of state-action transitions. In the case of model-based RL, agents can leverage spurious experiences (Berseth et al., 2019) and plan effectively for future steps. On the other hand, in the case of model-free RL, surprise results in sample-inefficient learning (Achiam & Sastry, 2017). This is primarily addressed by making use of rigorous exploration strategies (Stadie et al., 2015; Lee et al., 2019). High-dimensional exploration further requires extrinsic feature engineering (Kulkarni et al., 2016) and meta models (Gupta et al., 2018). A suitable way to tackle high-dimensional dynamics is by utilizing surprise as a penalty on the reward (Chen, 2020). This leads to improved generalization for single-agent interactions (Ren et al., 2005). Our proposed approach is orthogonal to the aforesaid methods.

Energy-based Models: EBMs have been successfully implemented in single-agent RL methods (O'Donoghue et al., 2016; Haarnoja et al., 2017). These typically make use of Boltzmann distributions to approximate policies (Levine & Abbeel, 2014). Such a formulation results in the minimization of free energy within the agent. While policy approximation depicts promise in the case of unknown dynamics, inference methods (Toussaint, 2009) play a key role in optimizing goal-oriented behavior.

A second type of usage of EBMs follows the maximization of entropy (Ziebart et al., 2008). The maximum entropy framework (Haarnoja et al., 2018b) highlighted in Soft Q-Learning (SQL) (Haarnoja et al., 2017) allows the agent to obey a policy which maximizes its reward and entropy concurrently. Maximization of agent's entropy results in diverse and adaptive behaviors (Ziebart, 2010) which may be difficult to accomplish using standard exploration techniques (Burda et al., 2019; Thrun, 1992). The maximum entropy framework is akin to approximate inference in the case of policy gradient methods (Schulman et al., 2017). Such a connection between likelihood ratio gradient techniques and energy-based formulations leads to diverse and robust policies (Haarnoja, 2018) and their hierarchical extensions (Haarnoja et al., 2018a) which preserve the lower levels of hierarchies. In the case of MARL, EBMs have witnessed limited applicability as a result of the increasing number of agents and complexity within each agent (Buşoniu et al., 2010). While the probabilistic framework is readily transferable to opponent-aware multi-agent systems (Wen et al., 2019), cooperative settings consisting of coordination between agents require a firm formulation of energy which is scalable in the number of agents (Grau-Moya et al., 2018) and accounts for environments consisting of spurious states (Wei et al., 2018). Our theoretical formulation is motivated by these methods in literature.

3 PRELIMINARIES

3.1 MULTI-AGENT LEARNING

We review the cooperative MARL setup. The problem is modeled as a Dec-Partially Observable Markov Decision Process (POMDP) (Sutton & Barto, 2018) defined by the tuple $(\mathcal{S}, \mathcal{A}, r, N, P, Z, O, \gamma)$ where the state space $\mathcal{S}$ and action space $\mathcal{A}$ are discrete, $r : \mathcal{S} \times \mathcal{A} \to [r_{min}, r_{max}]$ presents the reward observed by agents $a \in N$ where N is the set of all agents, $P : \mathcal{S} \times \mathcal{S} \times \mathcal{A} \to [0, \infty)$ presents the unknown transition model consisting of the transition probability to the next state $s' \in \mathcal{S}$ given the current state $s \in \mathcal{S}$ and joint action $u \in \mathcal{A}$ at time step t and γ is the discount factor. We consider a partially observable setting in which each agent n draws individual observations $z \in Z$ according to the observation function $O(s, u) : \mathcal{S} \times \mathcal{A} \to Z$. We consider a joint policy $\pi_\theta(u|s)$ as a function of model parameters θ. Standard RL de-

fines the agent's objective to maximize the expected discounted reward $\mathbb{E}_{\pi_\theta}[\sum_{t=0}^T \gamma^t r(s_t, u_t)]$ as a function of the parameters θ. The joint action-value function for agents is represented as $Q(u, s; \theta) = \mathbb{E}_{\pi_\theta}[\sum_{t=1}^T \gamma^t r(s, u) | s = s_t, u = u_t]$ which is the expected sum of payoffs obtained in state s upon performing action u by following the policy π_θ. We denote the optimal policy π_θ^* such that $Q(u, s; \theta^*) \geq Q(u, s; \theta) \forall s \in S, u \in A$. In the case of multiple agents, the joint optimal policy can be expressed as the Nash Equilibrium (Nash, 1950) of the Stochastic Markov Game as $\pi^* = (\pi^{1,*}, \pi^{2,*}, ... \pi^{N,*})$ such that $Q(u^a, s; \theta^*) \geq Q(u^a, s; \theta) \forall s \in S, u \in A, a \in N$. Q-Learning is an off-policy, model-free algorithm suitable for continuous and episodic tasks. The algorithm uses semi-gradient descent to minimize the Temporal Difference (TD) error in Equation 1.

$$\mathbb{L}(\theta) = \mathbb{E}_{b \sim R}\left[\left(r + \gamma \max_{u' \in A} Q(u', s'; \theta^-) - Q(u, s; \theta)\right)^2\right] \tag{1}$$

where $y = r + \gamma \max_{u' \in A} Q(u', s'; \theta^-)$ is the TD target consisting of θ^- as the target parameters and b is the batch sampled from memory R.

3.2 Energy-based Models

EBMs (LeCun et al., 2006; 2007) have been successfully applied in the field of machine learning (Teh et al., 2003) and probabilistic inference (MacKay, 2002). A typical EBM $\mathcal{E}$ formulates the equilibrium probabilities (Sallans & Hinton, 2004) $P(v, h) = \frac{\exp\left(-\mathcal{E}(v,h)\right)}{\sum_{\hat{v},\hat{h}}[\exp\left(-\mathcal{E}(\hat{v},\hat{h})\right)]}$ via a Boltzmann distribution (Levine & Abbeel, 2014) where v and h are the values of the visible and hidden variables and $\hat{v}$ and $\hat{h}$ are all the possible configurations of the visible and hidden variables respectively. The probability distribution over all the visible variables can be obtained by summing over all possible configurations of the hidden variables. This is mathematically expressed in Equation 2.

$$P(v) = \frac{\sum_h \exp\left(-\mathcal{E}(v, h)\right)}{\sum_{\hat{v},\hat{h}} \exp\left(-\mathcal{E}(\hat{v}, \hat{h})\right)} \tag{2}$$

Here, $\mathcal{E}(v, h)$ is called the equilibrium free energy which is the minimum of the variational free energy and $\sum_{\hat{v},\hat{h}} \exp\left(-\mathcal{E}(\hat{v}, \hat{h})\right)$ is the partition function.

4 Energy-based Surprise Minimization

We begin by constructing surprise minimization as an energy-based problem in the temporal setting. The motivation behind an energy-based formulation stems from rapidly changing states as an undesired niche among agents in the case of partially-observed settings. To steer agents away from this niche, we further construct a method which incorporates the theoretical aspect of the study.

4.1 The Surprise Minimization Objective

To make analysis tractable towards valid function spaces and surprising states, we take into account two assumptions which form the central basis of surprise minimization among multiple agents.

> **Assumption 1.** (Completeness of value function space) *The space $\Pi : \mathcal{S} \times \mathcal{A}$ of all Q value functions $Q(s, u) \in \Pi, \ \forall s \in \mathcal{S}, \ \forall u \in \mathcal{A}$ is a nonempty complete metric space.*

Assumption 1 restricts the formulation of individual agent value functions Q_a to the nonempty complete metric space. A nonempty space confirms the presence of candidate functions Q_a lower bounded by the optimal function Q^*, i.e.- $Q_a \leq Q^*, \ \forall a \in N$ (Bertsekas & Tsitsiklis, 1995). The completeness counterpart, on the other hand, provisions a fixed interior **int** Π for optimization (Boyd & Vandenberghe, 2004).

Assumption 2. (Constant surprise at Equilibrium) *In the limit of convergence* $\lim_{\pi_a \to \pi^*}$ *to an optimal policy* π^*, *all agents* $a \in N$ *incur a finite surprise* $\zeta > 0$ *between consecutive states* s *and* s' *until termination state* s_T.

Assumption 2 is directly based on the constant and continuous temporal aspect of surprise minimization (Schwartenbeck et al., 2013; Friston, 2010). Corresponding to the lifetime of each agent $a \in N$, a desired ecological niche bakes in the optimal distribution of actions which correspond to minimum yet finite instantaneous surprise.

We formulate the energy-based objective consisting of surprise as a function of states s, joint actions u and deviation σ within states for each agent a. We call this function as the surprise value function $V_{\text{surp}}^a(s, u, \sigma)$ which serves as a mapping from agent and environment dynamics to surprise. Define an operator presented in Equation 3 which sums surprising configurations across all agents.

$$\mathcal{T}V_{\text{surp}}^a(s, u, \sigma) = \log \sum_{a=1}^{N} \exp\left(V_{\text{surp}}^a(s, u, \sigma)\right) \tag{3}$$

Remark 1. $\mathcal{T}V_{\text{surp}}^a(s, u, \sigma)$ *intuitively provides a global estimate of surprise. If all agents are equally likely to face a surprising state, then* $\mathcal{T}V_{\text{surp}}^a(s, u, \sigma)$ *captures their individual contributions.*

The formulation makes use of the soft-maximum operator (Asadi & Littman, 2017). The operator $\mathcal{T}V_{\text{surp}}^a(s, u, \sigma)$ is similar to prior energy formulations (Haarnoja et al., 2017) where the energy across different actions is evaluated. In our case, inference is carried out across all agents with actions as prior variables. However, in the special case of using an EBM as a Q-function, our approach suitable generalizes to the above methods (details in Appendix B).

Our choice of $\mathcal{T}V_{\text{surp}}^a(s, u, \sigma)$ is based on its unique mathematical properties which result in better convergence. Of these properties, the most useful result is that $\mathcal{T}$ forms a contraction on the surprise value function $V_{\text{surp}}^a(s, u, \sigma)$ indicating a guaranteed minimization of surprise within agents. This is formally stated in Theorem 1 while utilizing the completeness criterion of Assumption 1 which provides a tractable value function space. All proofs are deferred to Appendix A.

Theorem 1. *Given a surprise value function* $V_{\text{surp}}^a(s, u, \sigma) \; \forall a \in N$, *the energy operator* $\mathcal{T}V_{\text{surp}}^a(s, u, \sigma) = \log \sum_{a=1}^{N} \exp\left(V_{\text{surp}}^a(s, u, \sigma)\right)$ *forms a contraction on* $V_{\text{surp}}^a(s, u, \sigma)$.

Theorem 1 provides a suitable guarantee of $\mathcal{T}V_{\text{surp}}^a(s, u, \sigma)$ converging to a fixed point niche. The contraction result is directly based on Banach's fixed point property and suggests the generalization of convergence in any nonempty complete metric space (X, d) (Bertsekas & Tsitsiklis, 1995).

We now consider a weighted combination of $Q(s, u)$ with $\mathcal{T}V_{\text{surp}}^a(s, u, \sigma)$ wherein we denote β as a temperature parameter,

$$\hat{Q}(u, s; \theta) = Q(u, s; \theta) + \beta \log \sum_{a=1}^{N} \exp\left(V_{\text{surp}}^a(s, u, \sigma)\right) \tag{4}$$

Remark 2. *Equation 4 is an instance of value function regularization wherein the Q values are subject to a joint penalty while observing surprising states.*

Interestingly, upon considering the Legendre transform $f^*(x)$ (Boyd & Vandenberghe, 2004; Gao & Pavel, 2017) (convex conjugate function corresponding to the conjugate space $\mathcal{X}$ of a differentiable function $f(z)$) of $\mathcal{T}V_{\text{surp}}^a(s, u, \sigma)$, we obtain the following,

$$f^*(x) = \sup_{z \in \text{dom} f} \left(x^{\text{T}}z - f(z)\right) \; , \; f(z) = \mathcal{T}V_{\text{surp}}^a(s, u, \sigma) \tag{5}$$

$$f^*(x) = \sum_{x} x \log(x) \; , \; x = \nabla_z f(z) \in \mathcal{X} \tag{6}$$

Remark 3. *The Legendre Transform of $\mathcal{T}V^a_{\text{surp}}(s, u, \sigma)$ given by $f^*(x) = \sum_x x \log(x)$ when utilized as value function regularization $\hat{Q} = Q - f^*(x)$ corresponds to the minimum entropy formulation in conjugate space $\mathbb{E}_{\pi_\theta}\left[\sum_{t=0}^{T} \gamma^t(r(s_t, u_t) - \lambda\mathcal{H}(x))\right]$ for $x = \nabla_z f(z) \in \mathcal{X}$.*

Based on the above insight, minimizing entropy to express $\nabla_z f(z)$ in conjugate space is akin to minimizing uncertainty among all agents in the value function space Π. Intuitively, $\mathcal{H}(x)$ denotes the uncertainty for each agent $a \in N$ in the multi-agent population which is directly related to its ability of efficaciously interpreting the environment. Minimizing $\mathcal{H}(x)$ leads to an increase in the expressiveness of value function. This in turn, induces an expressive state visitation distribution which steers the agent away from sudden changes in its environment. Note that the setting does not minimize entropy in value function space which would stand contrary to the maximum entropy formulation Haarnoja et al. (2018b).

Figure 1 presents an intuitive illustration of the objective. The joint agent population aims to minimize surprise corresponding to minimum energy configurations. Agents collaborate in partially-observed worlds to attain a joint niche. This local niche implicitly corresponds to a fixed point of $\mathcal{T}V^a_{\text{surp}}(s, u, \sigma)$ on the energy landscape. Note that agents act locally with actions conditioned on their own action observation histories. It is by virtue of preconditioned values estimations that the surprise minimization scheme informs agents of joint surprise. Upon population's convergence to a suitable configuration, agents continue to experience minimum (yet finite) surprise arising from evironment dynamics.

Figure 1: Agent populations seek energy minima (in darker shade). This results in surprise minimization from high (■) to low energy (■) niches.

4.2 Surprise Minimization with Function Approximation

We utilize the above insights as surprise-based regularization in the TD learning setting. Upon replacing $Q(u, s; \theta)$ with $\hat{Q}(u, s, ; \theta)$ in the RL construction of Equation 1 one obtains the following,

$$L(\theta) = \mathbb{E}_{b \sim R}\left[\frac{1}{2}\left(\hat{y} - (Q(u, s; \theta) + \beta \log \sum_{a=1}^{N} \exp(V^a_{\text{surp}}(s, u, \sigma)))\right)^2\right]$$

where $\hat{y} = r + \gamma\max_{u'}Q(u', s'; \theta^-) + \beta \log \sum_{a=1}^{N} \exp(V^a_{\text{surp}}(s', u', \sigma'))$. This yields the following,

$$L(\theta) = \mathbb{E}_{b \sim R}\left[\frac{1}{2}\left(r + \gamma\max_{u'}Q(u', s'; \theta^-) + \beta E - Q(u, s; \theta)\right)^2\right] \tag{7}$$

Here, E is defined as the *surprise ratio*. The surprise value function $V^a_{\text{surp}}(s', u', \sigma')$ is expressed as the negative free energy and $\sum_{a=1}^{N} \exp(V^a_{\text{surp}}(s, u, \sigma))$ as the partition function of a conventional EBM described in Equation 2. Alternatively, $V^a_{\text{surp}}(s, u, \sigma)$ can be formulated as the negative free energy with $\sum_{a=1}^{N} \exp(V^a_{\text{surp}}(s', u', \sigma'))$ as the partition function. The TD objective incorporates the minimization of surprise across all agents as minimizing the energy in spurious states.

Remark 4. *The above formulation of βE can be realized as intrinsic motivation steering the agent towards subgoals with reduced surprise.*

The energy formulation E provides a tractable distribution over all surprising configurations in the state space $\mathcal{S}$. This guarantees convergence to minimum surprise at optimal policy π^* and is formally expressed in Theorem 2 (see Appendix C for a detailed convergence analysis).

> **Theorem 2.** *Upon agent's convergence to an optimal policy π^*, total energy of π^*, expressed by E^* will reach a thermal equilibrium consisting of minimum surprise among consecutive states s and s'.*

Theorem 2 demonstrates an intuitive convergence result of agent populations collaborating to reside in a mutual ecological niche (Friston, 2010). The multi-agent population with minimum surprise

exhibits the optimal policy π^* which results in minimum energy corresponding to each surprising state in the state distribution $\mathcal{S}$. Orthogonally, agents may continue to experience finite and constant surprise in the long-horizon while acting optimally to visit non-surprising and rewarding states. This presents surprise minimization as a secondary surrogate objective in MARL.

4.3 ENERGY-BASED MIXER (EMIX)

Figure 2: The EMIX architecture for learning surprise across global states.

Based on our theoretical analysis, we incorporate learning of surprise as global intrinsic motivation across all agents in the multi-agent system. A global estimate of surprise, following the energy operator $\mathcal{T}V^a_{\mathrm{surp}}(s, u, \sigma)$, is befitting from a computational perspective as well. An individual estimate of surprise for each agent may be intractable to obtain due to the non-stationarity of the environment. Instead, we seek to minimize surprise jointly across all agents using an expressive Energy-based MIXer (EMIX) architecture which is compatible with any multi-agent RL algorithm. Figure 2 illustrates our learning scheme.

Learning of surprise in the high-dimensional value function space is cumbersome with the number of actions scaling linearly in the number of agents. This imposes an inherent restriction to learn global surprise efficaciously across all agents at a given timestep. Towards this goal, EMIX encodes individual value functions Q_1, Q_2, ... Q_n corresponding to each agent using local value encoders. These encoders capture the local change in value functions arising over subsequent TD learning iterations (Wang et al., 2021). A global state encoder maps environment states s_1, s_2, ... s_T to a low dimensional representation. Further, a state deviation encoder encodes deviations across all states s_1, s_2, ... s_T within the given batch. Akin to a model-based method (Janner et al., 2019), the state deviation encoder accounts for uncertainty in an agent's state visitation distribution. Note that the encoder does not construct an explicit model of states, but only represents their variation in the agent's environment. This insight is essential to account for abrupt dynamics encountered by agents. Representations obtained from state and value function encoders are concatenated and compressed using a final surprise encoder which estimates a distribution of surprise values. The distribution implicitly represents the density of states wherein an agent may encounter most surprise. A value estimate $V^a_{\mathrm{surp}}(s, u, \sigma)$ sampled from the surprise distribution depicts the variational free energy configuration upon application of $\mathcal{T}$ which serves as global intrinsic motivation. Practical training of EMIX proceeds with backpropagation (Rumelhart et al., 1986) using gradient descent and the reparameterization trick (Kingma & Welling, 2014) for sampling of $V^a_{\mathrm{surp}}(s, u, \sigma)$.

Algorithm 1 Energy-based MIXer (EMIX)

1: Initialize ϕ, θ, $\theta_1^- ..., \theta_m^-$, agent and hypernetwork parameters.
2: Initialize learning rate α, temperature β and replay buffer $\mathcal{R}$.
3: **for** environment step **do**
4:      $u \leftarrow (u_1, u_2..., u_N)$
5:      $\mathcal{R} \leftarrow \mathcal{R} \cup \{(s, u, r, s')\}$
6:      **if** $|\mathcal{R}| >$ batch-size **then**
7:          **for** random batch **do**
8:              $Q_{tot}^\theta \leftarrow$ *Mixer-Network*$(Q_1, Q_2..., Q_N, s)$
9:              $Q_i^{\theta^-} \leftarrow$ *Target-Mixer*$_i(Q_1, Q_2..., Q_N, s'), \forall i = 1, 2.., m$
10:              Calculate σ and σ' using s and s'
11:              $V_{\text{surp}}^a(s, u, \sigma) \leftarrow$ *Surprise-Mixer*(s, u, σ)
12:              $V_{\text{surp}}^a(s', u', \sigma') \leftarrow$ *Target-Surprise-Mixer*(s', u', σ')
13:              $E \leftarrow \log \left(\frac{\sum_{a=1}^N \exp\left(V_{\text{surp}}^a(s', u', \sigma')\right)}{\sum_{a=1}^N \exp\left(V_{\text{surp}}^a(s, u, \sigma)\right)} \right)$
14:              Calculate $L(\theta)$ using E in Equation 7
15:              $\theta \leftarrow \theta - \alpha \nabla_\theta L(\theta)$
16:          **end for**
17:      **end if**
18:      **if** update-interval steps have passed **then**
19:          $\theta_i^- \leftarrow \theta, \forall i = 1, 2.., m$
20:      **end if**
21: **end for**

4.4 Practical Implementation

Algorithm 1 presents the EMIX framework (in green) combined with QMIX Rashid et al. (2018), an off-the-shelf MARL algorithm. The total Q-value Q_{tot}^θ is computed by the mixer network with its inputs as the Q-values of all the agents conditioned on s via the hypernetworks. Similarly, the target mixers approximate $Q_i^{\theta^-}$ conditioned on s'. In order to evaluate surprise within agents, we compute the standard deviations σ and σ' across all observations z and z' for each agent using s and s' respectively. The surprise value function, called the Surprise-Mixer, estimates surprise $V_{\text{surp}}^a(s, u, \sigma)$ conditioned on s, u and σ. The same computation is repeated using the Target-Surprise-Mixer for estimating surprise $V_{\text{surp}}^a(s', u', \sigma')$ within next-states in the batch. Application of the energy operator along the non-singleton agent dimension for $V_{\text{surp}}^a(s, u, \sigma)$ and $V_{\text{surp}}^a(s', u', \sigma')$ yields the energy ratio E which is used in Equation 7 to evaluate $L(\theta)$. We then use batch gradient descent to update parameters of the mixer θ. Target parameters θ_i^- are updated every $update - interval$ steps.

5 Experiments

Our experiments aim to evaluate the theoretical claims presented by EMIX along with its performance to prior MARL methods. Specifically, we aim to answer the following questions- (1) How does the provision of an EBM for surprise minimization compare to current MARL methods?, and (2) Does the algorithm validate the theoretical claims corresponding to its components?

5.1 Energy-based Surprise Minimization

We assess the validity of EMIX, when combined with QMIX, on multi-agent StarCraft II microman-agement scenarios (Samvelyan et al., 2019) as these consist of a larger number of agents with different action spaces. This in turn motivates a greater deal of coordination. Additionally, micromanagement scenarios in StarCraft II consist of multiple opponents which introduce a greater degree of surprise within consecutive states.

We compare our method to prior methods namely; (1) QMIX (Rashid et al., 2018), constituting of nonlinear value function factorization with monotonicity constraints; (2) Value Decomposition Networks (VDN) (Sunehag et al., 2018), consisting of linear additive factorization of Q function; (3) Counterfactual Multi-Agent Policy Gradients (COMA) (Foerster et al., 2017), which consist of

Scenarios	EMIX	SMiRL-QMIX	QMIX	VDN	COMA	IQL
2s_vs_1sc	90.33 ± 0.72	88.41 ± 1.31	89.19 ± 3.23	91.42 ± 1.23	**96.90 ± 0.54**	86.07 ± 0.98
2s3z	**95.40±0.45**	94.93±0.32	95.30±1.28	92.03±2.08	43.33±2.70	55.74±6.84
3m	**94.90±0.39**	93.94±0.22	93.43±0.20	94.58±0.58	84.75±7.93	94.79±0.50
3s_vs_3z	**99.58±0.07**	97.63±1.08	99.43±0.20	97.90±0.58	0.21±0.54	92.32±2.83
3s_vs_4z	**97.22±0.73**	0.24±0.11	96.01±3.93	94.29±2.13	0.00±0.00	59.75±12.22
3s_vs_5z	52.91±11.80	0.00±0.00	43.44±7.09	**68.51±5.60**	0.00±0.00	18.14±2.34
3s5z	**88.88±1.07**	88.53±1.03	88.49±2.32	63.58±3.99	0.25±0.11	7.05±3.52
8m	**94.47±1.38**	89.96±1.42	94.30±2.90	90.26±1.12	92.82±0.53	83.53±1.62
8m_vs_9m	**71.03±2.69**	69.90±1.94	68.28±2.30	58.81±4.68	4.17±0.58	28.48±22.38
10m_vs_11m	75.35±2.30	**77.85±2.02**	70.36±2.87	71.81±6.50	4.55±0.73	32.27±25.68
so_many_baneling	**95.87±0.16**	93.61±0.94	93.35±0.78	92.26±1.06	91.65±2.26	74.97±6.52
5m_vs_6m	**37.07±2.42**	33.27±2.79	34.42±2.63	35.63±3.32	0.52±0.13	14.78±2.72

Table 1: Comparison of success rate percentages between EMIX and prior MARL methods on StarCraft II micromanagement scenarios. EMIX is comparable to or improves over QMIX agent. In comparison to SMiRL-QMIX, EMIX demonstrates improved minimization of surprise. Results are averaged over 5 random seeds.

counterfactual actor-critic updates in a centralized critic; and (4) Independent Q Learning (IQL) (Tan, 1993), wherein each agent acts independent of other agents. (5) In order to compare our surprise minimization scheme against pre-existing mechanisms, we compare EMIX additionally to a model-free implementation of SMiRL (Berseth et al., 2019) in QMIX. We use the generalized version of SMiRL as it demonstrates reduced variance across batches (Chen, 2020). This implementation is denoted as SMiRL-QMIX for comparisons. Details related to the implementation of EMIX are presented in Appendix D.

Table 1 presents the comparison of success rate percentages between EMIX and prior MARL algorithms on 12 StarCraft II micromanagement scenarios. Corresponding to each scenario, algorithms demonstrating higher success rate values in comparison to other methods have their entries highlighted in **bold**. Out of the 12 scenarios considered, EMIX presents higher success rates on 9 of these scenarios depicting the suitability of the proposed approach. In cases of *so_many_baneling* and *5m_vs _6m* having large number of opponents and a greater level of surprise, EMIX aptly improves over prior methods.

When compared to QMIX, EMIX depicts improved success rates on all of the 12 scenarios. On comparing EMIX with SMiRL-QMIX, we note that EMIX demonstrates a higher average success rate. This highlights the suitability of the energy-based scheme in the case of a larger number of agents and complex environment dynamics for surprise minimization.

5.2 ABLATION STUDY

We now present the ablation study for the various components of EMIX. Our experiments aim to determine the effectiveness of the energy-based surprise minimization method. Additionally, we also aim to evaluate the utility of dual approximators for surprise estimation in accordance with the precept from RL literature (Hasselt et al., 2016; Fujimoto et al., 2018; Haarnoja et al., 2018b).

5.2.1 EMIX OBJECTIVE

To weigh the effectiveness of energy-based scheme, we ablate the energy operator $\mathcal{T}$ and only utilize V_{surp}^a. Since this implementation employs dual approximators $V_{\mathrm{surp},(i)}^a$ $i \in \{1, 2\}$ for stability, we call this implementation as TwinQMIX. Thus, we compare between QMIX, TwinQMIX and EMIX to assess the contributions of each of the proposed methods.

Figure 3: Ablations for each of EMIX's component. When compared to QMIX, EMIX and TwinQMIX depict improvements in performance and sample efficiency.

Figure 3 presents the comparison of average success rates for QMIX, TwinQMIX and EMIX on 3 different scenarios. Agents were evaluated for a total of 2 million timesteps with the lines in the plot indicating average success rates and the

shaded area as the deviation across 5 random seeds. In comparison to QMIX, TwinQMIX adds stability to the original objective by incorporating surprising estimates in the initial QMIX objective. On comparing TwinQMIX to EMIX we note that dual approximators play little role in improving convergence. Thus, the energy-based surprise minimization scheme is the main facet for significant performance improvement in the modified EMIX objective. This is demonstrated in the *5m_vs_6m* scenario wherein the EMIX implementation improves the performance of TwinQMIX in comparison to QMIX by utilizing a surprise-robust policy. In the case of *so_many _baneling* scenario which consists of a large number of opponents (27 banelings), EMIX tackles surprise effectively by preventing a significant drop in performance which is observed in cases of QMIX and TwinQMIX. We conjecture that this is a direct consequence of underestimations arising from $V^a_{\text{surp},(i)}$ estimates.

5.2.2 SURPRISE MINIMIZATION WITH TEMPERATURE

The importance of β can be validated by assessing its usage in surprise minimization. However, it is difficult to evaluate surprise minimization directly as surprise value function estimates $V^a_{\text{surp}}(s, u, \sigma)$ vary from state-to-state across different agents and thus, they present high variance during agent's learning. We instead observe the variation of E as it is a collection of surprise-based sample estimates across the batch. Additionally, E consists of prior samples $V^a_{\text{surp}}(s, u, \sigma)$ for $V^a_{\text{surp}}(s', u', \sigma')$ which makes inference across different agents tractable.

Figure 4: Variation of surprise minimization with temperature β. Learning of surprise is achieved by making use of a suitable value of temperature parameter ($\beta = 0.01$) which controls the stability in surprise minimization by utilizing E as intrinsic motivation.

Figure 4 presents the variation of Energy ratio E with the temperature parameter β during learning. We compare two stable variations of E at $\beta = 0.001$ and $\beta = 0.01$. The objective minimizes E over the course of learning and attains thermal equilibrium with minimum energy. Intuitively, equilibrium corresponds to convergence to optimal policy π^* which validates the claim in Theorem 2. With $\beta = 0.01$, EMIX presents improved convergence and surprise minimization for 5 out of the 6 considered scenarios, hence validating the suitable choice of β. On the other hand, a lower value of $\beta = 0.001$ does little to minimize surprise across agents.

6 DISCUSSION

In this paper, we presented an energy-based perspective towards surprise minimization in multi-agent RL. Towards this goal we introduce EMIX, an energy-based intrinsic motivation framework for surprise minimization in MARL algorithms. EMIX utilizes a temporal EBM to estimate and minimize surprise jointly across all agents. Our theoretical claims on the formulation of minimization of temporal energy with surprise are corroborated upon utilizing EMIX on a suite of challenging MARL tasks requiring significant collaboration under fast-paced dynamics.

While EMIX serves as a practical example of EBMs in cooperative MARL, it presents several new avenues for future work. We shed light on 3 such aspects,

(1) Provision of an energy-based model naturally raises the question of *how can we efficiently sample from the surprise distribution?* Advances in sampling methods depict promise towards this aspect.

(2) Although suitable for lower dimensions, the scalability of EBMs towards high dimensional action spaces remains an open question. We conjecture that the utility of density-based methods and generative models can address the scalability gap.

(3) Lastly, the extension of an EBM framework to opponent-aware and competitive MARL settings presents a suitable tangent for learning multi-agent roles. Provision of an EBM for learning minimum energy role configurations would do away with the need for multi-stage training and complex exploration strategies. We leave the aforesaid as potential directions for future work.

REFERENCES

Joshua Achiam and Shankar Sastry. Surprise-based intrinsic motivation for deep reinforcement learning, 2017.

Kavosh Asadi and Michael L Littman. An alternative softmax operator for reinforcement learning. In *International Conference on Machine Learning*, 2017.

Glen Berseth, Daniel Geng, Coline Devin, Dinesh Jayaraman, Chelsea Finn, and Sergey Levine. Smirl: Surprise minimizing rl in entropic environments. 2019.

Dimitri P Bertsekas. *Abstract dynamic programming*. Athena Scientific Nashua, NH, USA, 2018.

Dimitri P Bertsekas and John N Tsitsiklis. *Neuro-dynamic Programming*, volume 1. Athena Scientific, 1995.

Stephen Boyd and Lieven Vandenberghe. *Convex Optimization*. Cambridge University Press, 2004.

Yuri Burda, Harri Edwards, Deepak Pathak, Amos Storkey, Trevor Darrell, and Alexei A. Efros. Large-scale study of curiosity-driven learning. In *ICLR*, 2019.

Lucian Buşoniu, Robert Babuška, and Bart De Schutter. Multi-agent reinforcement learning: An overview. In *Innovations in multi-agent systems and applications-1*. 2010.

Jerry Zikun Chen. Reinforcement learning generalization with surprise minimization, 2020.

Jakob Foerster, Gregory Farquhar, Triantafyllos Afouras, Nantas Nardelli, and Shimon Whiteson. Counterfactual multi-agent policy gradients, 2017.

Karl Friston. The free-energy principle: a unified brain theory? *Nature reviews neuroscience*, 11(2): 127–138, 2010.

Scott Fujimoto, Herke van Hoof, and David Meger. Addressing function approximation error in actor-critic methods, 2018.

Bolin Gao and Lacra Pavel. On the properties of the softmax function with application in game theory and reinforcement learning. *arXiv preprint arXiv:1704.00805*, 2017.

Jordi Grau-Moya, Felix Leibfried, and Haitham Bou-Ammar. Balancing two-player stochastic games with soft q-learning. *arXiv preprint arXiv:1802.03216*, 2018.

Abhishek Gupta, Russell Mendonca, YuXuan Liu, Pieter Abbeel, and Sergey Levine. Meta-reinforcement learning of structured exploration strategies. In *Advances in Neural Information Processing Systems 31*. 2018.

Tuomas Haarnoja. *Acquiring Diverse Robot Skills via Maximum Entropy Deep Reinforcement Learning*. PhD thesis, UC Berkeley, 2018.

Tuomas Haarnoja, Haoran Tang, Pieter Abbeel, and Sergey Levine. Reinforcement learning with deep energy-based policies. *arXiv preprint arXiv:1702.08165*, 2017.

Tuomas Haarnoja, Kristian Hartikainen, Pieter Abbeel, and Sergey Levine. Latent space policies for hierarchical reinforcement learning. *arXiv preprint arXiv:1804.02808*, 2018a.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. *arXiv preprint arXiv:1801.01290*, 2018b.

Hado van Hasselt, Arthur Guez, and David Silver. Deep reinforcement learning with double q-learning. In *Proceedings of the Thirtieth AAAI Conference on Artificial Intelligence*, 2016.

Matteo Hessel, Joseph Modayil, Hado Van Hasselt, Tom Schaul, Georg Ostrovski, Will Dabney, Dan Horgan, Bilal Piot, Mohammad Azar, and David Silver. Rainbow: Combining improvements in deep reinforcement learning. *arXiv preprint arXiv:1710.02298*, 2017.

Michael Janner, Justin Fu, Marvin Zhang, and Sergey Levine. When to trust your model: Model-based policy optimization. In *Advances in Neural Information Processing Systems*, 2019.

Lukasz Kaiser, Mohammad Babaeizadeh, Piotr Milos, Blazej Osinski, Roy H Campbell, Konrad Czechowski, Dumitru Erhan, Chelsea Finn, Piotr Kozakowski, Sergey Levine, Afroz Mohiuddin, Ryan Sepassi, George Tucker, and Henryk Michalewski. Model-based reinforcement learning for atari, 2019.

Diederik P. Kingma and Max Welling. Auto-Encoding Variational Bayes. In *2nd International Conference on Learning Representations*, 2014.

Landon Kraemer and Bikramjit Banerjee. Multi-agent reinforcement learning as a rehearsal for decentralized planning. *Neurocomputing*, 190, 02 2016.

Tejas D Kulkarni, Karthik Narasimhan, Ardavan Saeedi, and Josh Tenenbaum. Hierarchical deep reinforcement learning: Integrating temporal abstraction and intrinsic motivation. In *Advances in neural information processing systems*, 2016.

Yann LeCun, Sumit Chopra, Raia Hadsell, M Ranzato, and F Huang. A tutorial on energy-based learning. *Predicting structured data*, 1, 2006.

Yann LeCun, Sumit Chopra, M Ranzato, and F-J Huang. Energy-based models in document recognition and computer vision. In *Ninth International Conference on Document Analysis and Recognition (ICDAR 2007)*, volume 1, 2007.

Lisa Lee, Benjamin Eysenbach, Emilio Parisotto, Eric Xing, Sergey Levine, and Ruslan Salakhutdinov. Efficient exploration via state marginal matching. *arXiv preprint arXiv:1906.05274*, 2019.

Sergey Levine and Pieter Abbeel. Learning neural network policies with guided policy search under unknown dynamics. In *Advances in Neural Information Processing Systems*, 2014.

Ryan Lowe, Yi Wu, Aviv Tamar, Jean Harb, Pieter Abbeel, and Igor Mordatch. Multi-agent actor-critic for mixed cooperative-competitive environments, 2017.

Luis Macedo and Amilcar Cardoso. The role of surprise, curiosity and hunger on exploration of unknown environments populated with entities. In *2005 portuguese conference on artificial intelligence*, 2005.

Luis Macedo, Rainer Reisezein, and Amilcar Cardoso. Modeling forms of surprise in artificial agents: empirical and theoretical study of surprise functions. In *Proceedings of the Annual Meeting of the Cognitive Science Society*, volume 26, 2004.

David J. C. MacKay. *Information Theory, Inference & Learning Algorithms*. Cambridge University Press, 2002.

Volodymyr Mnih, Adria Puigdomenech Badia, Mehdi Mirza, Alex Graves, Timothy Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In *International conference on machine learning*, 2016.

John F. Nash. Equilibrium points in n-person games. *Proceedings of the National Academy of Sciences*, 36(1), 1950.

Brendan O'Donoghue, Remi Munos, Koray Kavukcuoglu, and Volodymyr Mnih. Combining policy gradient and q-learning. *arXiv preprint arXiv:1611.01626*, 2016.

Tabish Rashid, Mikayel Samvelyan, Christian Schroeder de Witt, Gregory Farquhar, Jakob Foerster, and Shimon Whiteson. Qmix: Monotonic value function factorisation for deep multi-agent reinforcement learning. In *ICML 2018: Proceedings of the Thirty-Fifth International Conference on Machine Learning*, 2018.

Wei Ren, Randal W Beard, and Ella M Atkins. A survey of consensus problems in multi-agent coordination. In *Proceedings of the 2005, American Control Conference, 2005.*, 2005.

David E. Rumelhart, Geoffrey E. Hinton, and Ronald J. Williams. Learning Representations by Back-propagating Errors. *Nature*, 323:533–536, 1986.

Brian Sallans and Geoffrey E Hinton. Reinforcement learning with factored states and actions. *Journal of Machine Learning Research*, 5, 2004.

Mikayel Samvelyan, Tabish Rashid, Christian Schroeder de Witt, Gregory Farquhar, Nantas Nardelli, Tim G. J. Rudner, Chia-Man Hung, Philip H. S. Torr, Jakob Foerster, and Shimon Whiteson. The starcraft multi-agent challenge, 2019.

John Schulman, Xi Chen, and Pieter Abbeel. Equivalence between policy gradients and soft q-learning. *arXiv preprint arXiv:1704.06440*, 2017.

Philipp Schwartenbeck, Thomas FitzGerald, Ray Dolan, and Karl Friston. Exploration, novelty, surprise, and free energy minimization. *Frontiers in psychology*, 4:710, 2013.

Bradly C Stadie, Sergey Levine, and Pieter Abbeel. Incentivizing exploration in reinforcement learning with deep predictive models. *arXiv preprint arXiv:1507.00814*, 2015.

Peter Sunehag, Guy Lever, Audrunas Gruslys, Wojciech Marian Czarnecki, Vinicius Zambaldi, Max Jaderberg, Marc Lanctot, Nicolas Sonnerat, Joel Z. Leibo, Karl Tuyls, and Thore Graepel. Value-decomposition networks for cooperative multi-agent learning based on team reward. In *Proceedings of the 17th International Conference on Autonomous Agents and MultiAgent Systems*, AAMAS '18, pp. 2085–2087, 2018.

Richard S. Sutton and Andrew G. Barto. *Reinforcement Learning: An Introduction*. 2018.

Ming Tan. Multi-agent reinforcement learning: Independent vs. cooperative agents. In *In Proceedings of the Tenth International Conference on Machine Learning*, 1993.

Yee Whye Teh, Max Welling, Simon Osindero, and Geoffrey E Hinton. Energy-based models for sparse overcomplete representations. *Journal of Machine Learning Research*, 4, 2003.

Sebastian B Thrun. Efficient exploration in reinforcement learning. 1992.

Marc Toussaint. Robot trajectory optimization using approximate inference. In *Proceedings of the 26th annual international conference on machine learning*, 2009.

Oriol Vinyals, Igor Babuschkin, Wojciech Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David Choi, Richard Powell, Timo Ewalds, Petko Georgiev, Junhyuk Oh, Dan Horgan, Manuel Kroiss, Ivo Danihelka, Aja Huang, Laurent Sifre, Trevor Cai, John Agapiou, Max Jaderberg, and David Silver. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *Nature*, 575, 11 2019.

Tonghan Wang, Tarun Gupta, Anuj Mahajan, Bei Peng, Shimon Whiteson, and Chongjie Zhang. {RODE}: Learning roles to decompose multi-agent tasks. In *International Conference on Learning Representations*, 2021.

Ermo Wei, Drew Wicke, David Freelan, and Sean Luke. Multiagent soft q-learning. *arXiv preprint arXiv:1804.09817*, 2018.

Ying Wen, Yaodong Yang, Rui Luo, Jun Wang, and Wei Pan. Probabilistic recursive reasoning for multi-agent reinforcement learning. *arXiv preprint arXiv:1901.09207*, 2019.

Brian D Ziebart. Modeling purposeful adaptive behavior with the principle of maximum causal entropy. 2010.

Brian D Ziebart, Andrew L Maas, J Andrew Bagnell, and Anind K Dey. Maximum entropy inverse reinforcement learning. In *AAAI*, 2008.

A PROOFS

Theorem 1. *Given a surprise value function $V_{\text{surp}}^a(s, u, \sigma) \forall a \in N$, the energy operator $\mathcal{T}V_{\text{surp}}^a(s, u, \sigma) = \log \sum_{a=1}^N \exp\left(V_{\text{surp}}^a(s, u, \sigma)\right)$ forms a contraction on $V_{\text{surp}}^a(s, u, \sigma)$.*

Proof. We follow the process of (Asadi & Littman, 2017). Let us first define a norm on surprise values $||V_1 - V_2|| \equiv \max_{s,u,\sigma} |V_1(s, u, \sigma) - V_2(s, u, \sigma)|$. Suppose $\epsilon = ||V_1 - V_2||$,

$$\log \sum_{a=1}^N \exp\left(V_1(s, u, \sigma)\right) \leq \log \sum_{a=1}^N \exp\left(V_2(s, u, \sigma) + \epsilon\right)$$

$$= \log \sum_{a=1}^N \exp\left(V_1(s, u, \sigma)\right) \leq \log \exp\left(\epsilon\right) \sum_{a=1}^N \exp\left(V_2(s, u, \sigma)\right)$$

$$= \log \sum_{a=1}^N \exp\left(V_1(s, u, \sigma)\right) \leq \epsilon + \log \sum_{a=1}^N \exp\left(V_2(s, u, \sigma)\right)$$

$$= \log \sum_{a=1}^N \exp\left(V_1(s, u, \sigma)\right) - \log \sum_{a=1}^N \exp\left(V_2(s, u, \sigma)\right) \leq ||V_1 - V_2|| \qquad (8)$$

Similarly, using ϵ with $\log \sum_{a=1}^N \exp\left(V_1(s, u, \sigma)\right)$,

$$\log \sum_{a=1}^N \exp\left(V_1(s, u, \sigma) + \epsilon\right) \geq \log \sum_{a=1}^N \exp\left(V_2(s, u, \sigma)\right)$$

$$= \log \exp\left(\epsilon\right) \sum_{a=1}^N \exp\left(V_1(s, u, \sigma)\right) \geq \log \sum_{a=1}^N \exp\left(V_2(s, u, \sigma)\right)$$

$$= \epsilon + \log \sum_{a=1}^N \exp\left(V_1(s, u, \sigma)\right) \geq \log \sum_{a=1}^N \exp\left(V_2(s, u, \sigma)\right)$$

$$= ||V_1 - V_2|| \geq \log \sum_{a=1}^N \exp\left(V_2(s, u, \sigma)\right) - \log \sum_{a=1}^N \exp\left(V_1(s, u, \sigma)\right) \qquad (9)$$

Results in Equation 8 and Equation 9 prove that the energy operation is a contraction. $\qquad \square$

Theorem 2. *Upon agent's convergence to an optimal policy π^*, total energy of π^*, expressed by E^* will reach a thermal equilibrium consisting of minimum surprise among consecutive states s and s'.*

Proof. We begin by initializing a set of M policies $\{\pi_1, \pi_2..., \pi_M\}$ having energy ratios $\{E_1, E_2..., E_M\}$. Consider a policy π_1 with surprise value function V_1. E_1 can then be expressed as

$$E_1 = \log \left[\frac{\sum_{a=1}^N \exp\left(V_1^a(s', u', \sigma')\right)}{\sum_{a=1}^N \exp\left(V_1^a(s, u, \sigma)\right)} \right]$$

Invoking Assumption 2 for s and s', we can express $V_1^a(s', u', \sigma') = V_1^a(s, u, \sigma) + \zeta_1$ where ζ_1 is a constant. Using this expression in E_1 we get,

$$E_1 = \log \left[\frac{\sum_{a=1}^N \exp\left(V_1^a(s, u, \sigma) + \zeta_1\right)}{\sum_{a=1}^N \exp\left(V_1^a(s, u, \sigma)\right)} \right]$$

$$E_1 = \log \left[\frac{\exp\left(\zeta_1\right) \sum_{a=1}^N \exp\left(V_1^a(s, u, \sigma)\right)}{\sum_{a=1}^N \exp\left(V_1^a(s, u, \sigma)\right)} \right]$$

$$E_1 = \zeta_1$$

Similarly, $E_2 = \zeta_2, E_3 = \zeta_3..., E_M = \zeta_M$. Thus, the energy residing in policy π is proportional to the surprise between consecutive states s and s'. Clearly, an optimal policy π^* is the one with minimum surprise. Mathematically,

$$\pi^* \geq \pi_1, \pi_2..., \pi_M \implies \zeta^* \leq \zeta_1, \zeta_2..., \zeta_M$$
$$= \pi^* \geq \pi_1, \pi_2..., \pi_M \implies E^* \leq E_1, E_2..., E_M$$

Thus, proving that the optimal policy consists of minimum surprise at thermal equilibrium. $\square$

B CONNECTION BETWEEN EMIX AND SOFT Q-LEARNING

The Soft Q-Learning objective with $V_{\text{soft}}^{\theta^-}(s')$ and $Q_{\text{soft}}(u, s; \theta)$ as state and action value functions respectively is given by-

$$J_Q(\theta) = \mathbb{E}_{s,u \sim R}\left[\frac{1}{2}\left(r + \gamma \mathbb{E}_{s' \sim R}[V_{\text{soft}}^{\theta^-}(s')] - Q_{\text{soft}}(u, s; \theta)\right)^2\right]$$

$$= J_Q(\theta) = \mathbb{E}_{s,u \sim R}\left[\frac{1}{2}\left(r + \gamma \mathbb{E}_{s' \sim R}\left[\log \sum_{u \in A} \exp Q_{\text{soft}}(u', s'; \theta^-)\right] - Q_{\text{soft}}(u, s; \theta)\right)^2\right]$$

The gradient of this objective can be expressed as-

$$\nabla_\theta J_Q(\theta) = \mathbb{E}_{s,u \sim R}\left[\left(\left(r + \gamma \mathbb{E}_{s' \sim R}\left[\log \sum_{u \in A} \exp Q(u', s'; \theta^-)\right] - Q_{\text{soft}}(u, s; \theta)\right)\right)\nabla_\theta Q_{\text{soft}}(u, s; \theta)\right]$$
(10)

And the gradient of the EMIX objective is obtained as-

$$L(\theta) = \mathbb{E}_{s,u,s' \sim R}\left[\frac{1}{2}\left(r + \gamma \max_{u'} Q(u', s'; \theta^-) + \beta \log\left(\frac{\sum_{a=1}^N \exp\left(V_{\text{surp}}^a(s', u', \sigma')\right)}{\sum_{a=1}^N \exp\left(V_{\text{surp}}^a(s, u, \sigma)\right)}\right) - Q(u, s; \theta)\right)^2\right]$$

$$\nabla_\theta L(\theta) = \mathbb{E}_{s,u,s' \sim R}\left[\left(r + \gamma \max_{u'} Q(u', s'; \theta^-)\right.\right.$$
$$\left.\left. + \beta \log\left(\frac{\sum_{a=1}^N \exp\left(V_{\text{surp}}^a(s', u', \sigma')\right)}{\sum_{a=1}^N \exp\left(V_{\text{surp}}^a(s, u, \sigma)\right)}\right) - Q(u, s; \theta)\right)\right]\nabla_\theta Q(u, s; \theta) \quad (11)$$

Comparing Equation 10 to Equation 11 we notice that Soft Q-Learning and EMIX are related to each other as they utilize EBMs. Soft Q-Learning makes use of a discounted energy function which downweights the energy values over longer horizons. Actions consisting of lower energy configurations are given preference by making use of $Q_{\text{soft}}(u, s; \theta)$ as the negative energy. On the other hand, EMIX makes use of a constant energy function weighed by β which minimizes surprise-based energy between consecutive states. Both the objectives can be thought of as energy minimizing models which search for an optimal energy configuration. Soft Q-Learning searches for an optimal configuration in the action space whereas EMIX favours optimal behavior on spurious states. In fact, EMIX can be realized as a special case of Soft Q-Learning if the mixer agent utilizes an energy-based policy and attains thermal equilibrium. This leads us to express Theorem 3.

Theorem 3. *Given an energy-based policy π with its target function $V(s') = \log \sum_{u \in A} \exp Q(u', s'; \theta^-)$, the surprise minimization objective $L(\theta)$ reduces to the Soft Q-Learning objective $L(\theta_{\text{soft}})$ in the special case surprise absent between consecutive states, $\sum_{a=1}^N \exp\left(V_{\text{surp}}^a(s', u', \sigma')\right) = \sum_{a=1}^N \exp\left(V_{\text{surp}}^a(s, u, \sigma)\right)$.*

Proof. We know that the EMIX objective is given by-

$$L(\theta) = \mathbb{E}_{s,u,s' \sim R}\left[\frac{1}{2}\left(r + \gamma \max_{u'} Q(u'; s', \theta^-) + \beta \log\left(\frac{\sum_{a=1}^N \exp\left(V_{\text{surp}}^a(s', u', \sigma')\right)}{\sum_{a=1}^N \exp\left(V_{\text{surp}}^a(s, u, \sigma)\right)}\right) - Q(u, s; \theta)\right)^2\right]$$
(12)

Replacing the greedy policy term $\max_{u'} Q(u', s'; \theta^-)$ with the energy-based value function $V(s') = \log \sum_{u' \in A} \exp Q(u', s'; \theta^-)$, we get,

$$L(\theta) = \mathbb{E}_{s,u,s' \sim R} \left[\frac{1}{2} \left(r + \gamma \mathbb{E}_{s' \sim R}[V(s')] + \beta \log \left(\frac{\sum_{a=1}^{N} \exp\left(V_{\text{surp}}^a(s', u', \sigma')\right)}{\sum_{a=1}^{N} \exp\left(V_{\text{surp}}^a(s, u, \sigma)\right)} \right) - Q(u, s; \theta) \right)^2 \right] \tag{13}$$

$$= L(\theta) = \mathbb{E}_{s,u,s' \sim R} \left[\frac{1}{2} \left(r + \gamma \mathbb{E}_{s' \sim R} \left[\log \sum_{u' \in A} \exp Q(u', s'; \theta^-) \right] \right. \right.$$
$$\left. \left. + \beta \log \left(\frac{\sum_{a=1}^{N} \exp\left(V_{\text{surp}}^a(s', u', \sigma')\right)}{\sum_{a=1}^{N} \exp\left(V_{\text{surp}}^a(s, u, \sigma)\right)} \right) - Q(u, s; \theta) \right)^2 \right]$$

At thermal equilibrium, $\sum_{a=1}^{N} \exp\left(V_{\text{surp}}^a(s, u, \sigma)\right) = \sum_{a=1}^{N} \exp\left(V_{\text{surp}}^a(s', u', \sigma')\right)$,

$$= L(\theta) = \mathbb{E}_{s,u,s' \sim R} \left[\frac{1}{2} \left(r + \gamma \mathbb{E}_{s' \sim R} \left[\log \sum_{u' \in A} \exp Q(u', s'; \theta^-) \right] \right. \right.$$
$$\left. \left. + \beta \log \left(\frac{\sum_{a=1}^{N} \exp\left(V_{\text{surp}}^a(s', u', \sigma')\right)}{\sum_{a=1}^{N} \exp\left(V_{\text{surp}}^a(s', u', \sigma')\right)} \right) - Q(u, s; \theta) \right)^2 \right]$$

$$= L(\theta) = \mathbb{E}_{s,u,s' \sim R} \left[\frac{1}{2} \left(r + \gamma \mathbb{E}_{s' \sim R} \left[\log \sum_{u' \in A} \exp Q(u', s'; \theta^-) \right] + \beta \log(1) - Q(u, s; \theta) \right)^2 \right] \tag{14}$$

$$= L(\theta) = \mathbb{E}_{s,u,s' \sim R} \left[\frac{1}{2} \left(r + \gamma \mathbb{E}_{s' \sim R} \left[\log \sum_{u' \in A} \exp Q(u', s'; \theta^-) \right] - Q(u, s; \theta) \right)^2 \right] \tag{15}$$

Equation 15 represents the Soft Q-Learning objective, hence proving the result. $\qquad \square$

C CONVERGENCE ANALYSIS

We now analyze convergence of the surprise minimization scheme during policy optimization. For brevity, our notation denotes the modified Bellman operator as $\mathcal{B}$ obeying the standard assumptions of monotonicity and contraction (Bertsekas, 2018). Additionally, we consider the cumulative value $\hat{V}_k = r_k + G_k + \beta \log \sum_{a=1}^{N} \exp(V_{\text{surp},(k)}^a(s, u, \sigma))$ as the sum of state values $V_k = r_k + G_k$ and surprise energy values $\beta \log \sum_{a=1}^{N} \exp(V_{\text{surp},(k)}^a(s, u, \sigma))$ at k^{th} Bellman update.

Consider $\left\| V_k - V^* \right\|_2$ with V^* being the optimal value at convergence,

$$\left\| \hat{V}_k - V^* \right\|_2 \leq \left\| \mathcal{B}\hat{V}_{k-1} + \beta \log \sum_{a=1}^{N} \exp(V_{\text{surp},(k)}^a) - V^* \right\|_2 \tag{16}$$

$$\leq \left\| \mathcal{B}^2 \hat{V}_{k-2} + \beta \log \sum_{a=1}^{N} \exp(V_{\text{surp},(k-1)}^a) + \beta \log \sum_{a=1}^{N} \exp(V_{\text{surp},(k)}^a) - V^* \right\|_2 \tag{17}$$

$$\leq \left\| \mathcal{B}^2 \hat{V}_{k-2} + \beta \left(\log \sum_{a=1}^{N} \exp(V_{\text{surp},(k-1)}^a) + \log \sum_{a=1}^{N} \exp(V_{\text{surp},(k)}^a) \right) - V^* \right\|_2 \tag{18}$$

$$\leq \left\| \mathcal{B}^2 \hat{V}_{k-2} + \beta \left(\log \left[\sum_{a=1}^{N} \exp(V_{\text{surp},(k-1)}^a) \right] \left[\sum_{a=1}^{N} \exp(V_{\text{surp},(k)}^a) \right] \right) - V^* \right\|_2 \tag{19}$$

Thus, for k iterations, we have,

$$\leq \left\| \mathcal{B}^k V_0 + \beta \left(\log \prod_{i=1}^k \left[\sum_{a=1}^N \exp(V_{\text{surp},(i)}^a) \right] \right) - V^* \right\|_2 \tag{20}$$

$$= \left\| \mathcal{B}^k V_0 + \beta \left(\log \sum_{a=1}^N \left[\prod_{i=1}^k \exp(V_{\text{surp},(i)}^a) \right] \right) - V^* \right\|_2 \tag{21}$$

$$= \left\| \mathcal{B}^k V_0 + \beta \left(\log \sum_{a=1}^N \left[\exp(\sum_{i=1}^k V_{\text{surp},(i)}^a) \right] \right) - V^* \right\|_2 \tag{22}$$

Denoting $V_{\text{tot}}^a = \sum_{i=1}^k V_{\text{surp},(i)}^a$ and utilizing the Triangle Inequality, we get,

$$= \left\| \mathcal{B}^k V_0 - V^* \right\|_2 + \left\| \beta \left(\log \sum_{a=1}^N [\exp(V_{\text{tot}}^a)] \right) \right\|_2 \tag{23}$$

We now bound the two terms separately. Considering the first term and following the results of value iteration convergence (Bertsekas & Tsitsiklis, 1995),

$$\left\| \mathcal{B}^k V - V^* \right\|_2 \leq \gamma^k \left\| V - V^* \right\|_2 \tag{24}$$

$$= \gamma^k \left\| V + V_\mu - V_\mu - V^* \right\|_2 \tag{25}$$

wherein V_μ denotes an approximation to V. Utilizing the triangle inequality yields,

$$\leq \gamma^k \left\| V - V_\mu \right\|_2 + \gamma^k \left\| V_\mu - V^* \right\|_2 \tag{26}$$

The two terms are bounded using the convergence result of (Bertsekas, 2018).

$$= \gamma^k \sqrt{r_{\max}} + \gamma^k \sqrt{\frac{r_{\max} |\mathcal{S}|}{1 - \gamma}} \tag{27}$$

Now, considering the second term in Equation 23,

$$\leq \beta \left\| \log \sum_{a=1}^N \exp(V_{\text{tot}}^a) \right\|_2 \tag{28}$$

$$= \beta \left\| \log \sum_{a=1}^N \exp(V_{\text{tot}}^a) - \log \sum_{a=1}^N \exp(V_{\text{tot}}^*) + \log \sum_{a=1}^N \exp(V_{\text{tot}}^*) \right\|_2 \tag{29}$$

using the triangle inequality,

$$\leq \beta \left\| \log \sum_{a=1}^N \exp(V_{\text{tot}}^a) - \log \sum_{a=1}^N \exp(V_{\text{tot}}^*) \right\|_2 + \beta \left\| \log \sum_{a=1}^N \exp(V_{\text{tot}}^*) \right\|_2 \tag{30}$$

Since $\mathcal{T} = \log \sum_{a=1}^N \exp(V_{\text{tot}}^a)$ is a contraction following Theorem 1, for the first term we have,

$$\leq \beta \gamma \left\| V_{\text{tot}}^a - V_{\text{tot}}^* \right\|_2 + \beta \left\| \log \sum_{a=1}^N \exp(V_{\text{tot}}^*) \right\|_2 \tag{31}$$

The second term in the above relation is bounded due to the completeness assumption, $\left\| \log \sum_{a=1}^N \exp(V_{\text{tot}}^*) \right\|_2$.

$$\leq \beta \gamma \left\| V_{\text{tot}}^a - V_{\text{tot}}^* \right\|_2 + \beta \zeta \ , \ \zeta > 0 \tag{32}$$

Finally, combining Equation 27 and Equation 32 in Equation 23, we obtain the desired convergence bound.

$$\left\| V_k - V^* \right\|_2 \le \gamma^k \left(\sqrt{r_{\max}} + \sqrt{\frac{r_{\max}|\mathcal{S}|}{1-\gamma}} \right) + \beta \left(\gamma \left\| V^a_{\text{tot}} - V^*_{\text{tot}} \right\|_2 + \zeta \right) \tag{33}$$

While the first term in Equation 33 denotes the convergence of policy optimization, the second term indicates the bounded convergence of surprise to ecological niches with finite (yet nonzero) surprising elements. The policy optimization process converges at a geometric rate $\mathcal{O}(\gamma^k)$ towards its stable fixed points. The surprise minimization process, on the other hand, demonstrates an annealing behavior which depends on the temperature parameter β. Furthermore, convergence to stable fixed point V^a_{tot} is bounded in respect to each agents individual surprise values V^a_{tot}. This insight indicates that different agents converge towards different locally optimal values of surprise. Finally, the presence of constant ζ corroborates prior claims (Schwartenbeck et al., 2013; Friston, 2010) that agents continue to experience surprise irrespective of their convergence to minimum energy niches.

To further develop intuition for this claim, consider the special case wherein $\left\| V^a_{\text{tot}} - V^*_{\text{tot}} \right\|_2 \to 0$. Irrespective of global convergence among all agents, a finite yet small ζ continues to contribute to the upper bound of $\left\| V_k - V^* \right\|_2$.

D   IMPLEMENTATION DETAILS

D.1   MODEL SPECIFICATIONS

This section highlights model architecture for the surprise value function. At the lower level, the architecture consists of 3 independent networks called *state_net*, *q_net* and *surp_net*. Each of these networks consist of a single layer of 256 units with ReLU non-linearity as activations. Similar to the mixer-network, we use the ReLU non-linearity in order to provide monotonicity constraints across agents. Using a modular architecture in combination with independent networks leads to a richer extraction of joint latent transition space. Outputs from each of the networks are concatenated and are provided as input to the *main_net* consisting of 256 units with ReLU activations. The *main_net* yields a single output as the surprise value $V^a_{\text{surp}}(s, u, \sigma)$ which is reduced along the agent dimension by the energy operator. Alternatively, deeper versions of networks can be used in order to make the extracted embeddings increasingly expressive. However, increasing the number of layers does little in comparison to additional computational expense.

D.2   HYPERPARAMETERS

Table 2 presents hyperparameter values for EMIX. Value of β was tuned between 0.001 and 1 in intervals of 0.01 with best performance observed at $\beta = 0.01$. A total of 2 target Q-functions were used as the model is found to be robust to any greater values.

Hyperparameters	Values
batch size	$b = 32$
learning rate	$\alpha = 0.0005$
discount factor	$\gamma = 0.99$
target update interval	200 episodes
gradient clipping	10
exploration schedule	1.0 to 0.01 over 50000 steps
mixer embedding size	32
agent hidden size	64
temperature	$\beta = 0.01$
target Q-functions	2

Table 2: Hyperparameter values for EMIX agents