THE WORLD IS CHANGING:
FAIRNESS UNDER CORRELATION SHIFTS

ABSTRACT

Model fairness is an essential element for Trustworthy AI. While many techniques for model fairness have been proposed, most of them assume that the training and deployment data distributions are identical, which is often not true in practice. In particular, when the bias between labels and sensitive groups changes, the fairness of the trained model is directly influenced and can worsen. We make two contributions for solving this problem. First, we analytically show that existing in-processing fair algorithms have fundamental limits in accuracy and fairness. We introduce the notion of *correlation shifts*, which can explicitly capture the change of the above bias. Second, we propose a novel pre-processing step that samples the input data to reduce correlation shifts and thus enables the in-processing approaches to overcome their limitations. We formulate an optimization problem for adjusting the data ratio among labels and sensitive groups to reflect the shifted correlation. A key advantage of our approach lies in *decoupling* the roles of pre-processing and in-processing approaches: correlation adjustment via pre-processing and unfairness mitigation on the processed data via in-processing. Experiments show that our framework effectively improves existing in-processing fair algorithms w.r.t. accuracy and fairness, both on synthetic and real datasets.

1 INTRODUCTION

Model fairness is becoming indispensable in many AI applications to prevent discrimination against specific groups such as gender, race, or age (Feldman et al., 2015; Hardt et al., 2016). There are three prominent fairness approaches: pre-processing, where training data is debiased; in-processing, where model training is tailored for fairness; and post-processing, where the trained model's output is modified to satisfy fairness – see more related works discussed in Sec. 6.

While fairness in-processing approaches are commonly used to mitigate unfairness, most of them make the limiting assumption that the training and deployment data distributions are the same (Zafar et al., 2017a; Zhang et al., 2018; Roh et al., 2021). However, the two distributions are usually different, especially in terms of data biases (Wick et al., 2019; Maity et al., 2021). For example, a recent work shows that the bias amounts likely differ between previously collected data and recently collected data (Ding et al., 2021). Moreover, when the data bias changes, the fairness and accuracy of the trained model are now unpredictable at deployment, as the above assumption is broken.

In this work, we introduce the notion of *correlation shifts* between the label y and group attribute z in the data to systematically address the data bias changes. Although several works have been recently proposed to investigate fair training on different types of distribution shifts, including covariate and concept shifts (Singh et al., 2021; Mishler & Dalmasso, 2022), they usually do not explicitly consider bias changes between y and z. In comparison, we focus on correlation shifts, where the notion of correlation enables us to theoretically analyze the clear relationship between training data and the behaviors of fair training – see a more detailed comparison with other types of shifts in Sec. 6.

For fair training under correlation shifts, we first 1) analyze the fundamental accuracy and fairness limits of in-processing approaches using the notion of correlation in the data and then 2) design a novel pre-processing step to boost the performances of in-processing approaches under the correlation shifts. We show that existing in-processing fair algorithms are indeed limited by the training distribution and may perform poorly on the deployment distribution. In particular, a high (y, z)-correlation results in a poor accuracy-fairness tradeoff for any fair training. Therefore, as most in-processing fair algorithms

(a) A high-level workflow under correlation shifts.

(b) A toy example for illustrating the impact of correlation shifts (i.e., bias changes) on the trained classifier.

Figure 1: The central axis in the left figure represents the correlation between the label y and sensitive group attribute z. The correlation of training data is usually higher than that of deployment data. In Sec. 3, we show that the correlation determines the achievable performance of fair training. Thus, we first run our pre-processing and then apply existing fair algorithms on the processed data to address the correlation shift and improve the performances of fair training. Not addressing the correlation shift may result in reduced performance as shown in the right figure – see details in Sec. 2.

assume identical training and deployment distributions, there is no guarantee their performances on the training data carry over to the deployment data. Based on the theoretical analysis, we propose a pre-processing step for reducing the shifted correlation by taking samples of (y, z)-classes. Using a possible range of the shifted correlations, we solve an optimization problem that finds the new data ratio among (y, z)-classes to adjust the correlation for the shift, which gives in-processing approaches a better opportunity to perform well. The pre-processed data are then used as the input data of any fair algorithm.

A key advantage of our framework is *the decoupling of pre-processing and in-processing for unfairness mitigation* where the pre-processing adjusts the correlation while the in-processing performs the rest of the unfairness mitigation, as described in Figure 1a. We note that our pre-processing aims to boost the performances of in-processing approaches based on our theoretical analysis, whereas existing pre-processing approaches for fairness simply remove the bias in the data and are not designed to explicitly benefit the in-processing approaches – see Sec. 5.1 for details. Our framework thus takes the best of both worlds of pre- and in-processings where (1) pre-processing solves the data problems, and (2) in-processing performs its best on the improved data. Our framework is not only useful for improving the fairness of a single metric, but can also be extended to support multiple metrics.

In our experiments, we verify our theoretical results and demonstrate how our framework outperforms state-of-the-art pre-processing and in-processing baselines. Experiments on both synthetic and real-world datasets (COMPAS (Angwin et al., 2016) and AdultCensus (Kohavi, 1996)) show that our framework effectively improves the accuracy and fairness performances of the state-of-the-art in-processing approaches (Zafar et al., 2017a; Zhang et al., 2018; Roh et al., 2021) under correlation shifts. Also, our framework performs better than two-step baselines that first run an existing pre-processing approach (Kamiran & Calders, 2011) and then an in-processing approach. We also show that our framework is still beneficial when we do not know the exact range of the shifted correlations.

Summary of Contributions **(1)** We introduce the notion of correlation shifts, which is important to connect the data bias changes and behaviors of fair training. **(2)** Using the notion of correlation, we theoretically analyze that existing in-processing fair algorithms are limited by the training distribution and may perform poorly on the deployment distribution. **(3)** We propose a novel pre-processing step to boost the performances of fair in-processing approaches. **(4)** We demonstrate that our framework effectively improves the performances of the state-of-the-art fair algorithms under correlation shifts.

2 LIMITATIONS OF IN-PROCESSING APPROACHES

Most in-processing approaches for fairness assume that the training and deployment distributions are the same, which means that they assume the same level of bias as well. However, data bias may shift over time as confirmed by recent studies (Wick et al., 2019; Maity et al., 2021; Ding et al., 2021), which means that the deployment data may actually have a different bias than the training data.

In fair training, the data bias reflects the relationship between a label y and sensitive group attribute z. For example, if all positive labels are in the same group, the data can be considered highly biased. Conversely, if the labels are randomly assigned to all groups, the data can be considered unbiased.

A bias change in the deployment data may have an adverse affect on a trained model's performance. Figure 1b shows a toy example that illustrates how a fair classifier's performance is affected by a

bias change during deployment. Here, the bias can be expressed via correlation, and we discuss their relationship in Sec. 3. The training distribution is biased, where Group 2 has more positive labels than Group 1. On the other hand, in the deployment distribution, the bias decreases as the positive labels are equally distributed for each group. Suppose we train a fair classifier on the training data as shown on the left side where the DP fairness is perfect (i.e., $\Pr(\hat{y}=1)$ are the same for the groups), but the accuracy is not as a result. On the deployment data, the DP worsens while the accuracy still remains imperfect. The underlying problem is that the classifier was trained with a different bias in mind.

In the next section, we formalize the notion of bias change and provide a theoretical analysis and simulation results that explain the above observations with the following notation and fairness metrics.

Notation & Fairness Metrics   Let θ be the model weights, $x \in \mathbb{X}$ be the input feature to the model, $y \in \mathbb{Y}$ be the true label, and $\hat{y} \in \mathbb{Y}$ be the predicted label where $\hat{y}$ is a function of (x, θ). Let $z \in \mathbb{Z}$ be a sensitive group attribute, e.g., gender or race. We assume a binary setting ($\mathbb{Y} = \mathbb{Z} = \{0, 1\}$). We focus on the prominent group fairness metrics, demographic parity (DP) (Feldman et al., 2015) and equalized odds (EO) (Hardt et al., 2016), where DP is achieved when the positive prediction rates are the same for the groups (i.e., $\Pr(\hat{y}=1|z=1)= \Pr(\hat{y}=1|z=0)$) and EO is achieved when the label-wise accuracies are the same for the groups (i.e., $\Pr(\hat{y}=y|y=y, z=1)= \Pr(\hat{y}=y|y=y, z=0), \forall y \in \{0, 1\}$).

3   FAIR TRAINING UNDER CORRELATION SHIFTS

To systematically study the effects of data bias changes, we first analyze the achievable performances of fair training via a *correlation between y and z that can be used to explicitly measure data bias* (Sec. 3.1) and discuss the limitations of fair in-processings when this correlation shifts (Sec. 3.2). We define correlation as follows:

(y, z)**-correlation**   Data bias can be represented via the correlation between the label y and the sensitive group attribute z, where the correlation represents a statistical relationship between two random variables. We thus define *(y, z)-correlation* using Pearson's correlation coefficient (Rodgers & Nicewander, 1988) $\rho_{yz} = \frac{Cov(y,z)}{\sigma(y)\sigma(z)}$, which is known to effectively capture biases in real-world scenarios. Here, $Cov(\cdot)$ is the covariance, and $\sigma(\cdot)$ is the standard deviation. As we assume y and z are binary, we can express ρ_{yz} as follows (Cohen & Cohen, 1975):

$$\rho_{yz} = \frac{\Pr(y=1, z=1)\Pr(y=0, z=0) - \Pr(y=1, z=0)\Pr(y=0, z=1)}{\sqrt{\Pr(y=1)\Pr(y=0)\Pr(z=1)\Pr(z=0)}}.$$

3.1   ACHIEVABLE PERFORMANCE ANALYSIS VIA CORRELATION

We identify the fundamental accuracy and fairness limits of fair training based on the (y, z)-correlation of the data. We first analyze the most common case of improving the fairness w.r.t. a single fairness metric. We then extend our analysis to the more complicated case of improving the fairness w.r.t. multiple metrics, which is important for capturing various social contexts, but has been seldom studied in the literature. In both cases, we show that the (y, z)-correlation determines the achievable performance of fair training.

CASE 1 – Fair Training w.r.t. a Single Metric   When improving group fairness, fair training is known to face an accuracy-fairness tradeoff, where the accuracy is sacrificed to make the model fairer. Recently, Menon & Williamson (2018) investigate that the accuracy-fairness tradeoff w.r.t. demographic parity is affected by how much y and z are *aligned* in the data. For example, if the y and z values are identical for all examples, achieving high fairness may require low accuracy. In contrast, if y and z are randomly set, fairness and accuracy can be achieved together. The following proposition shows this previous work's result.

Proposition 1 (From Menon & Williamson (2018))**.** *(Informal) When a model is trained w.r.t. demographic parity, a high alignment between* y *and* z *leads to a worse accuracy-fairness tradeoff.*

For our purposes, we infer a similar relationship using (y, z)-correlation based on Proposition 1. The following lemma makes a connection between the (y, z)-correlation and the conditional probabilities of y given z under some conditions.

Lemma 2. *If the marginal probabilities of* y *and* z *(i.e.,* $\Pr(y = y)$ *and* $\Pr(z = z)$*) remain the same, the* (y, z)*-correlation* ρ_{yz} *is proportional to the difference between the conditional probabilities of* y *given different* z *values (i.e.,* $\Pr(y = 1|z = 1) - \Pr(y = 1|z = 0)$*).*

The proof for Lemma 2 can be found in Sec. A.1. By applying Lemma 2 to Proposition 1, we can infer that the (y, z)-correlation also determines the accuracy-fairness tradeoff under certain conditions. According to the previous work (Menon & Williamson, 2018), alignment is defined as how many examples in each group have a specific label. We can thus measure alignment as $\Pr(y = y|z = 1) + \Pr(y = y'|z = 0)$ where $y \neq y'$ and $y, y' \in \{0, 1\}$. Then, we can convert this term into the difference between the conditional probabilities of y given different z values, which is used in Lemma 2 – see details in Sec. A.2. As a result, we derive the following corollary, which shows that the (y, z)-correlation determines the achievable accuracy-fairness tradeoff.

Corollary 3. *When a model is trained w.r.t. demographic parity, and the marginal probabilities of* y *and* z *remain the same, the achievable accuracy-fairness tradeoff of the model is determined by the* (y, z)*-correlation. The higher the correlation, the worse the accuracy-fairness tradeoff.*

Remark 4. *We can relax the assumption that marginal probabilities are fixed in Corollary 3. When the marginal probabilities of* y *and* z *change up to* γ_y *and* γ_z*, respectively, Corollary 3 can be generalized as follows: the achievable accuracy-fairness tradeoff is determined by* $\rho_{y,z} \cdot \eta$*, where* $\rho_{y,z}$ *is the* (y, z)*-correlation and* $\eta \in [\sqrt{\frac{\Pr(y=1)-\gamma_y-(\Pr(y=1)+\gamma_y)^2}{\Pr(z=1)+\gamma_z-(\Pr(z=1)-\gamma_z)^2}}, \sqrt{\frac{\Pr(y=1)+\gamma_y-(\Pr(y=1)-\gamma_y)^2}{\Pr(z=1)-\gamma_z-(\Pr(z=1)+\gamma_z)^2}}]$*. Thus, the higher the* $\rho_{y,z} \cdot \eta$*, the worse the accuracy-fairness tradeoff. In our framework, we actually allow the marginal probabilities of* y *and* z *to change up to* γ_y *and* γ_z *– see details in Sec. 4.1.*

Simulation We now confirm our theoretical observations via a simulation – see details on the setting in Sec. B.1. The left plot in Figure 2 shows the accuracy-unfairness performances of classifiers on two synthetic datasets with low and high correlations when using DP for measuring fairness (the plot on the right will be explained later). We measure unfairness where a lower value indicates better fairness (i.e., perfectly fair when the value is 0) – see the exact metrics in Sec. 5. We generate various synthetic classifiers on the two datasets to show the full range of possible model performances. The blue dots (red crosses) are the classifiers on the dataset with low (high) correlation. As a result, low correlation results in better accuracy-fairness tradeoffs (i.e., close to the bottom right). We will discuss the black stars and squares in Sec. 3.2.

Figure 2: Simulation results of accuracy-unfairness (left: DP and right: DP & EO) performances of various classifiers on two synthetic datasets that have low and high (y, z)-correlations. The blue dots (red crosses) indicate the classifiers' performances on the low (high) correlation data. The lower the unfairness value, the better. For each dataset, we generate enough classifiers to show the full range of possible performances. As a result, low correlation enables classifiers to attain better accuracy-fairness tradeoffs (i.e., close to the bottom right), regardless of supporting single or multiple fairness metrics. Also, the optimal classifiers trained on high correlation data (black stars) have suboptimal performances on the low correlation data (black squares).

Remark 5. *We note that Corollary 3 does not necessarily apply for equalized odds (EO), which is achieved when the accuracies conditioned on the true label are the same for the groups. In theory, a perfect classifier can achieve perfect fairness w.r.t. EO, so the* (y, z)*-correlation does not determine the limits of the accuracy-fairness tradeoff w.r.t. EO. However, classifiers are not perfect in practice, and we empirically observe that higher* (y, z)*-correlation leads to a worse accuracy-fairness tradeoff w.r.t. EO as well – see the empirical results in Sec. B.2.*

CASE 2 – Fair Training w.r.t. Multiple Metrics Beyond the single metric scenario, we now extend our analysis to support multiple fairness metrics together. Although supporting multiple metrics is necessary to address fairness under various social contexts, most fairness works do not address this problem. A major challenge is that group fairness metrics are known to be mutually exclusive, which means that these metrics cannot be perfectly satisfied together, unless the data is completely unbiased (Barocas et al., 2019; Kleinberg et al., 2017). Interestingly, our (y, z)-correlation provides an opportunity to support multiple fairness metrics together as much as possible in a principled fashion. We focus on supporting two metrics and leave the support of more metrics as future work.

We first analyze when a model can improve both demographic parity (DP) and equalized odds (EO) to get hints on the relationship between the (y, z)-correlation and improving fairness w.r.t. two metrics. Here, we focus on the ε-fairness of both metrics, which is a relaxed version of perfect fairness (Barocas et al., 2019), where ε indicates the unfairness level of the model. For example, we can define ε-DP as $|\Pr(\hat{y} = 1|z = 1) - \Pr(\hat{y} = 1|z = 0)| \le \varepsilon$ and ε-EO as $|\Pr(\hat{y} = y|y = y, z = 1) - \Pr(\hat{y} = y|y = y, z = 0)| \le \varepsilon$. Note that $\varepsilon \in [0, 1]$ and a lower ε means higher fairness. The following proposition shows when a model can achieve both ε-DP and ε-EO.

Proposition 6 (ε-DP & ε-EO). *Let a model achieve both ε-DP and ε-EO. Then, the following inequality holds:* $|\Pr(y = y|z = z) - \Pr(y = y|z = z')| |\Pr(\hat{y} = y|y = y, z = z) - \Pr(\hat{y} = y|y = y', z = z)| \le 2\varepsilon, y \ne y', z \ne z', y, y', z, z' \in \{0, 1\}.$

The proof for Proposition 6 can be found in Sec. A.3. Here, the achievable fairness level ε is affected by the data bias, which is represented by the difference between the conditional probabilities of y given z (i.e., $|\Pr(y = y|z = z) - \Pr(y = y|z = z')|$). For example, if the data is highly biased, a model cannot achieve high fairness (i.e., low ε) unless the second term on the left side (i.e., $|\Pr(\hat{y} = y|y = y', z = z) - \Pr(\hat{y} = y|y = y, z = z)|$) decreases. However, the second term is related to the accuracy, where lowering it to zero causes the model to make random predictions or predictions that are all the same. Thus, Lemma 2 and Proposition 6 give the following corollary.

Corollary 7. *When a model is trained w.r.t. both DP and EO, and the marginal probabilities of* y *and* z *do not change, the achievable fairness of the model is determined by the* (y, z)*-correlation if the accuracy does not change. The higher the correlation, the lower the achievable fairness.*

Similar to the single-metric case, we confirm the theoretical result of supporting multiple metrics via the simulation in the right plot in Figure. 2. Again, we observe that low correlation enables classifiers to attain better accuracy-fairness tradeoffs. We also leave discussions for improving fairness w.r.t. another prominent metric called predictive parity (PP) (Berk et al., 2021) together with DP and EO in Secs. A.4 (ε-PP and ε-DP) and A.5 (ε-EO and ε-PP).

3.2 EFFECTS OF CORRELATION SHIFTS

As the performance ranges of fair training are different according to the data correlation, a fair classifier learned on some training data does not necessarily have optimal performance on deployment data with a different correlation. We say there is a *correlation shift* between two data distributions D_1 and D_2 when $|\rho_{yz}^{D_1} - \rho_{yz}^{D_2}| \ne 0$, where $\rho_{yz}^{D_i}$ indicates the (y, z)-correlation of D_i. Here, the correlation *shift* reflects the bias *change* between data distributions.

We revisit our previous simulation in Figure 2 that helps to understand how the correlation shifts affect fair training. We consider a correlation shift from a training distribution with high correlation to a deployment distribution with low correlation. We start from a few optimal classifiers trained on the high-correlated data, which are denoted as black stars. These classifiers unfortunately have suboptimal performances on the low-correlation deployment data (black squares). Hence, in-processing approaches that assume the same training and deployment data distributions lose the chance of achieving better fairness and accuracy in the deployment distribution under correlation shifts.

Based on our theoretical and simulation results, we design a pre-processing approach using (y, z)-correlation as a tuning knob to give existing in-processing approaches a better opportunity to achieve maximum accuracy and fairness performances in the following section.

4 FRAMEWORK

To improve the performance of fair training in the presence of correlation shifts, we propose a novel fair training framework that consists of two main parts: applying a pre-processing approach for reflecting the shifted correlation and utilizing any existing in-processing algorithms for fair training on top of the improved data. We first design an optimization problem for finding a new data distribution that follows the shifted correlation by adjusting the (y, z)-class ratios. Then, we explain our overall training process and extensions to support similar distributions.

4.1 OPTIMIZATION

We design an optimization that finds the best (y, z)-class ratios given a (y, z)-correlation ρ_{yz} by using Lemma 2, which shows that ρ_{yz} is proportional to the conditional probability difference under some

assumptions. Note that the conditional probability can be written using the class weights. Let the original data ratio of each (y=y, z=z)-class be $w_{y=y,z=y}$. Let the new data ratio be $w'_{y=y,z=y}$, which is required to satisfy the shifted correlation of the deployment data. Note that $\sum_{\forall y,z} w'_{y=y,z=z} = 1$. Also, let c be the correlation constant that is the difference between the conditional probabilities of y given z in the deployment data. Let $[\alpha, \beta]$ be the range of the correlation constant c (i.e., $c \in [\alpha, \beta]$). The range may be known in advance or constructed by using distribution estimation techniques (Huang et al., 2006; Zhang et al., 2013) for computing the shifted correlation and generating a range using its confidence interval. We use a relaxed version of the assumption in Lemma 2 where the marginal probabilities of y and z can change by up to γ_y and γ_z, respectively, as discussed in Remark 4. With these conditions, we set up a problem whose goal is to minimize the squared differences between the original and new data ratios to help reduce the information loss, similar to other pre-processing approaches (Zemel et al., 2013; Quadrianto et al., 2019):

$$\min_{w'} \sum_{\forall y,z} (w_{y=y,z=z} - w'_{y=y,z=z})^2$$

$$\text{s.t.} \quad \alpha \le \frac{w'_{y=1,z=1}}{w'_{y=1,z=1} + w'_{y=0,z=1}} - \frac{w'_{y=1,z=0}}{w'_{y=1,z=0} + w'_{y=0,z=0}} \le \beta,$$

$$|(w'_{y=1,z=1} + w'_{y=1,z=0}) - \text{Pr}_{\text{train}}(y=1)| \le \gamma_y, \quad |(w'_{y=1,z=1} + w'_{y=0,z=1}) - \text{Pr}_{\text{train}}(z=1)| \le \gamma_z,$$

$$\sum_{\forall y,z} w'_{y=y,z=z} = 1, \quad 0 \le w'_{y=y,z=z} \le 1, \quad \forall y \in \{0,1\}, z \in \{0,1\}$$

where $\text{Pr}_{\text{train}}(y=1)=w_{y=1,z=1}+w_{y=1,z=0}$ and $\text{Pr}_{\text{train}}(z=1) = w_{y=1,z=1}+w_{y=0,z=1}$. Note that when we know the exact shifted correlation value (i.e., $\alpha = \beta = c$), the first constraint can be rewritten as $w'_{y=1,z=1}/(w'_{y=1,z=1} + w'_{y=0,z=1}) - w'_{y=1,z=0}/(w'_{y=1,z=0} + w'_{y=0,z=0}) = c$.

The above optimization is a non-convex quadratically constrained quadratic problem (non-convex QCQP), where the objective is quadratic, and the first constraint is non-convex quadratic. However, the non-convex QCQP is known to be hard to solve (d'Aspremont & Boyd, 2003). Thus, we apply the semidefinite (SDP) relaxation, which is one of the convex relaxations known to give a reasonable lower bound of the optimal value of the original non-convex QCQP (Park & Boyd, 2017):

$$\min_{X,x} \mathbf{Tr}(XP_0) + q_0^T x$$

$$\text{s.t.} \ \mathbf{Tr}(XP_\alpha) \ge 0, \ \mathbf{Tr}(XP_\beta) \le 0,$$

$$|q_2^T x - \text{Pr}_{\text{train}}(y=1)| \le \gamma_y, \ |q_3^T x - \text{Pr}_{\text{train}}(z=1)| \le \gamma_z, \ q_4^T x = 1, \ 0 \le x_i \le 1 \ \forall i, \ \begin{bmatrix} X & x \\ x^T & 1 \end{bmatrix} \succeq 0$$

where $\mathbf{Tr}(\cdot)$ is the trace, $X = xx^T$, $x = \begin{bmatrix} x_1 & x_2 & x_3 & x_4 \end{bmatrix}^T = \begin{bmatrix} w'_{1,1} & w'_{1,0} & w'_{0,1} & w'_{0,0} \end{bmatrix}^T$, $q_0 = -2\begin{bmatrix} w_{1,1} & w_{1,0} & w_{0,1} & w_{0,0} \end{bmatrix}^T$, $q_2 = \begin{bmatrix} 1 & 0 & 1 & 0 \end{bmatrix}^T$, $q_3 = \begin{bmatrix} 1 & 1 & 0 & 0 \end{bmatrix}^T$, $q_4 = \begin{bmatrix} 1 & 1 & 1 & 1 \end{bmatrix}^T$, $P_0 = \text{diag}(\mathbf{1})$, $P_\alpha = \begin{bmatrix} 0 & -\alpha/2 & 0 & (1-\alpha)/2 \\ -\alpha/2 & 0 & (-1-\alpha)/2 & 0 \\ 0 & (-1-\alpha)/2 & 0 & -\alpha/2 \\ (1-\alpha)/2 & 0 & -\alpha/2 & 0 \end{bmatrix}$, and $P_\beta = \begin{bmatrix} 0 & -\beta/2 & 0 & (1-\beta)/2 \\ -\beta/2 & 0 & (-1-\beta)/2 & 0 \\ 0 & (-1-\beta)/2 & 0 & -\beta/2 \\ (1-\beta)/2 & 0 & -\beta/2 & 0 \end{bmatrix}$.

Details on the conversion are in Sec. A.6. Since the above SDP relaxation problem is now convex, we can solve it using convex optimization solvers (e.g., CVXPY (Diamond & Boyd, 2016)).

4.2 OVERALL TRAINING

We present the overall process for fair training under correlation shifts in Algorithm 1. The algorithm includes two main parts: pre-processing for reflecting the shifted correlation and in-processing for fair training on top of the improved data. We first find the new (y, z)-class ratio $w_{y,z}$ based on the SDP relaxation of our optimization, which can be solved using convex optimization solvers (e.g., CVXPY). We then calculate the sample-wise weights to ensure that the sample weight sum in each (y=y, z=z)-class is $w_{y=y,z=z} \cdot n$, where n is the total number of samples in the original training data. Within each (y=y, z=z)-class, all samples have the same weight. We then draw new data D' from the original training data via weighted sampling according to the sample-wise weights. Finally, we train a model using an in-processing fair algorithm f on D'.

Algorithm 1: Fair Training under Correlation Shifts

Input: training data D, original ratio $w_{y,z}$, correlation range $[\alpha, \beta]$, thresholds γ_y and γ_z, in-processing algorithm f

$w'_{y,z} = \texttt{SDPsolver}(w_{y,z}, \alpha, \beta, \gamma_y, \gamma_z)$

$d_j \leftarrow w'_{y=y,z=z}/w_{y=y,z=z}$,
$\quad \forall j \in \mathbb{I}_{(y,z)}, \forall (y,z) \in \mathbb{Y} \times \mathbb{Z}$

$\mathbf{d} = \{d_i\}_{i=1,\dots,n}$

(Optional) $\mathbf{d} = \texttt{MinDistChange}(D, w_{y,z}, w'_{y,z})$

Draw new data D' from D via weighted sampling w.r.t. $\mathbf{d}$

$\theta \leftarrow$ initial model parameters

for *each epoch* **do**: Update θ based on f on D'

Output: θ

In addition, using an optional step (`MinDistChange`), we can address the scenario where the pre-processing should minimally change the original training data, which is sometimes preferred in other applications (Kamiran & Calders, 2011). Details on this extension are in Sec. A.7.

5 EXPERIMENTS

We perform experiments to evaluate our framework. We use logistic regression in all experiments. We evaluate the models on separate test datasets and repeat all experiments with five different random seeds. We use CVXPY as a convex optimization solver. More detailed settings are in Sec. B.3.

Fairness metrics We focus on two prominent group fairness metrics: demographic parity (DP) (Feldman et al., 2015) and equalized odds (EO) (Hardt et al., 2016). We measure the fairness disparities (i.e., unfairness) among sensitive groups as follows: *DP disparity* = $\max_{z\in\mathbb{Z}}|\Pr(\hat{y}=1|z=z)-\Pr(\hat{y}=1)|$ and *EO disparity* = $\max_{z\in\mathbb{Z},y\in\mathbb{Y}}|\Pr(\hat{y}=y|z=z,y=y)-\Pr(\hat{y}=y|y=y)|$. When measuring the unfairness w.r.t. both DP and EO, we take the maximum of both disparities (i.e., $\max($*DP disp.*, *EO disp.*$)$). Note that lower disparity means better fairness.

Datasets We use a total of three datasets for training: one synthetic dataset and two real-world benchmark datasets. We generate the synthetic dataset using a method similar to Zafar et al. (2017a). The synthetic training dataset has 2,000 samples and consists of two non-sensitive attributes (x_1, x_2), one sensitive attribute z, and one label attribute y. Each sample (x_1, x_2, y) is drawn from Gaussian distributions, and z follows a biased distribution – see details in Sec. B.3. We also utilize two real datasets, ProPublica COMPAS (Angwin et al., 2016) and AdultCensus (Kohavi, 1996), and use the same pre-processing in IBM Fairness 360 (Bellamy et al., 2019). COMPAS and AdultCensus consist of 5,278 and 43,131 samples, and the labels indicate recidivism and each person's annual income, respectively. We use gender as the sensitive attribute. Also, we do not use any personal identifiers.

To construct test data representing the deployment distribution with shifted correlation, we use three methods: (1) re-sampling data within each (y, z)-class in the original test data, (2) modifying the z values while fixing the x and y distributions in the original test data (see details in Sec. B.3), and (3) utilizing a newly-collected data, where we train on the AdultCensus dataset (Kohavi, 1996), but test on a recent version of this dataset called ACSIncome (Ding et al., 2021). We show the results for the method of re-sampling in the main paper and leave the results for the other methods in Secs. B.6 & B.7. In Secs. 5.1 & 5.3, the correlation constant c (i.e., $\Pr(y=1|z=1)-\Pr(y=1|z=0)$) of the test data is 50% and 60% of c_{train}, respectively, where c_{train} is the correlation constant of the training data. In Secs. 5.2 & 5.4, c is set to 10% to 70% of c_{train}. In Sec. B.9, c is set to 110% to 150% of c_{train}.

Baselines We compare our framework with three types of baselines: (1) *vanilla (non-fair)* training using logistic regression, (2) *in-processing-only* training, and (3) *two-step* training that first runs an existing pre-processing algorithm and then an in-processing algorithm. For in-processing-only training, we use the following three approaches: Fairness Constraints (FC) (Zafar et al., 2017a;b), which adds an unfairness penalty term to the loss function; Adversarial Debiasing (AD) (Zhang et al., 2018), which adversarially trains a classifier with a fairness discriminator; and FairBatch (FB) (Roh et al., 2021), which adaptively adjusts batch ratios among groups to improve fairness. When we run in-processing approaches for multiple fairness metrics, we naturally extend each approach by combining the fairness constraints for different metrics – see details in Sec. B.3. For two-step training, we use a pre-processing algorithm called Reweighing (RW) (Kamiran & Calders, 2011) to debias the training data before running the above in-processing algorithms, where RW balances the data amounts across groups. We thus run the in-processing algorithms on the less-biased data by RW.

Hyperparameters We consider *three scenarios of knowing the range of the correlation constant c* in the test data. As discussed in Sec. 4.1, one can infer this range using distribution techniques (Huang et al., 2006; Zhang et al., 2013), which gives a confidence interval that can be used as the correlation constant range $[\alpha, \beta]$. **(1)** In Secs. 5.1, 5.2, and 5.4, we assume that the range indicates the exact c_{test} value (i.e., $\alpha = \beta = c_{\text{test}}$). **(2)** In Sec. B.8, we assume that the range is $c_{\text{test}} \pm x\%$. **(3)** In Sec. 5.3, we assume that the range is incorrect. We set both γ_y and γ_z to 0.1, which is a larger value than the actual marginal probability changes in the test data. We also test for the values of 0.2 and 0.3, and the overall trends remain the same. For all in-processing algorithms, we start from a candidate set and use cross-validation on the (pre-processed) training data to choose the hyperparameters that result in the best fairness while having an accuracy that best aligns with other results. Details are in Sec. B.3.

Table 1: Performances on the synthetic and COMPAS test datasets w.r.t. a single metric (DP) and multiple metrics (DP & EO). The test datasets are constructed via re-sampling from the original distribution. The correlation constant c of the test data is 50% of that of the training data. We compare our framework with three types of baselines: (1) non-fair training: LR; (2) in-processing-only training: FC (Zafar et al., 2017a;b), AD (Zhang et al., 2018), and FB (Roh et al., 2021); (3) two-step training: RW (Kamiran & Calders, 2011) + in-processings. Experiments are repeated five times.

| | Synthetic | | | | COMPAS | | | |
| | Single (DP) | | Multiple (DP & EO) | | Single (DP) | | Multiple (DP & EO) | |
Method	Acc.	Unfair.	Acc.	Unfair.	Acc.	Unfair.	Acc.	Unfair.
LR	$.865 \pm .000$	$.173 \pm .000$	$.865 \pm .000$	$.173 \pm .000$	$.660 \pm .000$	$.129 \pm .000$	$.660 \pm .000$	$.225 \pm .000$
FC	$.778 \pm .011$	$.038 \pm .013$	$.853 \pm .001$	$.075 \pm .002$	$.656 \pm .004$	$.050 \pm .021$	$.654 \pm .007$	$.137 \pm .034$
RW+FC	$.848 \pm .004$	$.079 \pm .003$	$.848 \pm .004$	$.082 \pm .002$	$.654 \pm .004$	$.068 \pm .039$	$.651 \pm .010$	$.124 \pm .031$
Ours+FC	$.849 \pm .002$	$\mathbf{.034 \pm .004}$	$.851 \pm .005$	$\mathbf{.060 \pm .003}$	$.657 \pm .008$	$\mathbf{.037 \pm .021}$	$.652 \pm .020$	$\mathbf{.106 \pm .038}$
AD	$.762 \pm .016$	$.032 \pm .011$	$.821 \pm .004$	$.068 \pm .003$	$.655 \pm .003$	$.054 \pm .015$	$.661 \pm .005$	$\mathbf{.111 \pm .035}$
RW+AD	$.845 \pm .002$	$.087 \pm .006$	$.847 \pm .003$	$.084 \pm .005$	$.657 \pm .005$	$.092 \pm .022$	$.655 \pm .007$	$.145 \pm .056$
Ours+AD	$.814 \pm .011$	$\mathbf{.017 \pm .006}$	$.842 \pm .009$	$\mathbf{.054 \pm .008}$	$.650 \pm .003$	$\mathbf{.045 \pm .008}$	$.664 \pm .006$	$.117 \pm .039$
FB	$.821 \pm .000$	$.048 \pm .000$	$.849 \pm .001$	$.091 \pm .005$	$.647 \pm .001$	$.038 \pm .013$	$.650 \pm .002$	$.187 \pm .019$
RW+FB	$.859 \pm .002$	$.055 \pm .003$	$.855 \pm .001$	$.071 \pm .008$	$.653 \pm .003$	$.094 \pm .016$	$.652 \pm .003$	$.197 \pm .020$
Ours+FB	$.836 \pm .001$	$\mathbf{.003 \pm .001}$	$.852 \pm .004$	$\mathbf{.058 \pm .001}$	$.648 \pm .004$	$\mathbf{.027 \pm .001}$	$.657 \pm .004$	$\mathbf{.130 \pm .014}$

5.1 ACCURACY AND FAIRNESS

We first compare the accuracy and fairness performances of our framework with baselines on the synthetic and COMPAS datasets in Table 1 – see performances on the AdultCensus dataset in Sec. B.4, which shows similar results. The test data has lower correlation than the training data. LR in the first row shows vanilla training without any fairness technique. Other baselines are clustered based on three in-processing approaches: FC, AD, and FB. For each in-processing approach X, applying our pre-processing (denoted as Ours + X) generally shows better fairness while achieving comparable or even better accuracies, either when supporting only DP or both DP and EO. The in-processing-only baselines mostly show worse fairness and accuracies compared to applying our approach, because the in-processing-only baselines are trained with different biases from test data distribution in mind. The baselines of applying RW before in-processing generally do not achieve high fairness compared to ours. The reason is that existing pre-processing approaches like RW simply mitigate data bias as much as possible, which is not always beneficial for the in-processing. In comparison, our approach takes a more principled approach by adjusting the bias according to the correlation shift with the purpose of improving the in-processing performance. We also present accuracy and fairness trade-off curves of the in-processing-only baseline and our approach in Sec. B.5.

We observe similar results when using the two other test settings explained above. One is to modify the z values while fixing the x and y distributions using the synthetic dataset (Sec. B.6). The other is to use two income datasets collected in the 1990s (i.e., AdultCensus) and 2010s (i.e., ACSIncome) for training and testing, respectively, where they have different (y, z)-correlation values (Sec. B.7).

5.2 VARYING THE CORRELATION OF THE TEST DATA

We compare the algorithm performances when varying the correlation of the test data. Figure 3a shows the accuracy and fairness performances of FB and Ours+FB. As the test data's correlation constant c varies from 10% to 70% of the training data's correlation constant, our pre-processing improves the accuracy and fairness of the in-processing algorithm. Interestingly, when the correlation of the test data differs significantly from the training data (i.e., close to 10%), the in-processing-only baseline (FB) shows worse fairness. We suspect that the baseline is mitigating a different type of bias than that of the test data. On the other hand, our pre-processing successfully enables the in-processing algorithm to achieve high fairness and accuracy (e.g., for a 10% test corr., the unfairness decreases from 0.108 to 0.003). We also expand the $[\alpha, \beta]$ range to be $[c_{\text{test}} - x\%, c_{\text{test}} + x\%]$ instead of a constant value in Sec. B.8 and observe similar results. In addition, we vary the correlation from 110% to 150% in Sec. B.9 where we show how our pre-processing enables in-processing to achieve high fairness.

5.3 MISSPECIFYING THE CORRELATION IN THE ALGORITHM

We also evaluate our approach when the shifted correlation is incorrectly specified. We set $\alpha = \beta = c_{\text{specified}}$, where $c_{\text{specified}} \neq c_{\text{test}}$. Figure 3b shows the performances of FB and Ours+FB when the true correlation of the test data is 60% correlation of the training data. Ours improves the in-processing-only baseline's accuracy for the entire range of considered correlations and improves fairness when the specified correlation is higher than 30%. Hence, our approach is still beneficial when the estimation error is within 10%.

(a) Varying the correlation of the test data.   (b) Varying the *specified* correlation in our algorithm.

Figure 3: Performances of FB and Ours+FB on the synthetic data while (a) varying the correlation of the test data to have 10% to 70% correlation of the training data and (b) varying the *specified* correlation in our algorithm to have 10% to 70% where the true correlation of the test data is 60%.

5.4 Minimizing the Distribution Change

We show the effects of the optional `MinDistChange` step in Algorithm 1, which finds possibly-different data sample weights within each (y, z)-class to minimize the overall distribution change between the training and pre-processed data. This optional step is useful when an application requires the pre-processing to minimally change the original training data. We find that the optional step generally reduces the Wasserstein distance between the training and pre-processed data distributions, while not sacrificing much of the final classifier's accuracy and fairness. More details are in Sec. B.10.

6 Related Work

As model fairness becomes essential for Trustworthy AI, various fairness definitions have been proposed to reflect legal and social requirements (Narayanan, 2018). Among the definitions, we focus on group fairness, which aims to not discriminate specific groups. There are three prominent group fairness metrics: demographic parity (Feldman et al., 2015), equalized odds (Hardt et al., 2016), and predictive parity (Berk et al., 2021). To support the fairness metrics, various fairness techniques have been proposed, which can be categorized into three prominent approaches: (1) pre-processing approaches (Kamiran & Calders, 2011; Zemel et al., 2013; Feldman et al., 2015; Choi et al., 2020), which debias, reweight, or generate training data, (2) in-processing approaches (Zafar et al., 2017a;b; Agarwal et al., 2018; Zhang et al., 2018; Cotter et al., 2019; Roh et al., 2020; 2021), which modify model training itself for fairness, and (3) post-processing approaches (Hardt et al., 2016; Pleiss et al., 2017; Chzhen et al., 2019), which manipulate only the model outputs without changing the training inside. Among the three categories, in-processing approaches are widely used for unfairness mitigation, but most of them assume that the training and deployment data distributions are the same.

More recently, there is a new focus to address bias changes in the data (Wick et al., 2019; Maity et al., 2021). Several studies (Wick et al., 2019; Ding et al., 2021) identify that the deployment data distribution can be different from the training data distribution, especially in terms of data biases. A recent study (Maity et al., 2021) theoretically analyzes the behavior of fair training under a change in bias called subpopulation shifts, where a specific group has fewer positively-labeled examples during training time compared to deployment time. Another study (Giguere et al., 2022) proposes a new test method to serve a fair model under another data distribution change called demographic shifts, where the subgroup distribution may change. In comparison, we analyze the fundamental accuracy and fairness limits of in-processing approaches by introducing the notion of correlation shifts and propose a pre-processing algorithm for assisting them.

Another line of research is to support multiple fairness metrics (Thomas et al., 2019; Zhao et al., 2020). Thomas et al. (2019) proposes a fairness testing framework that can support multiple metrics. Zhao et al. (2020) shows that EO can be achieved while preserving the original DP. In comparison, we analyze when a model can achieve both ε-DP and ε-EO.

7 Conclusion

We addressed the problem of model fairness in the presence of bias changes in the data. We first introduced the new notion of (y, z)-correlation for capturing bias and analyzed the accuracy and fairness limitations of existing in-processing approaches in the presence of correlation shifts. We then proposed a decoupling framework where pre-processing is used to adjust the correlation, and in-processing is used for unfairness mitigation. The pre-processing step adjusts the data ratio among (y, z)-classes to reflect the shifted correlation and can optionally minimize the distribution change of the training data as well. Experiments showed how our pre-processing enables existing in-processing approaches to achieve high fairness and accuracy under correlation shifts and outperform baselines.

REFERENCES

Alekh Agarwal, Alina Beygelzimer, Miroslav Dudík, John Langford, and Hanna M. Wallach. A reductions approach to fair classification. In *ICML*, pp. 60–69, 2018.

Julia Angwin, Jeff Larson, Surya Mattu, and Lauren Kirchner. Machine bias: There's software used across the country to predict future criminals. And its biased against blacks. ProPublica, 2016.

Solon Barocas, Moritz Hardt, and Arvind Narayanan. *Fairness and Machine Learning*. fairmlbook.org, 2019. http://www.fairmlbook.org.

Rachel K. E. Bellamy, Kuntal Dey, Michael Hind, Samuel C. Hoffman, Stephanie Houde, Kalapriya Kannan, Pranay Lohia, Jacquelyn Martino, Sameep Mehta, Aleksandra Mojsilovic, Seema Nagar, Karthikeyan Natesan Ramamurthy, John T. Richards, Diptikalyan Saha, Prasanna Sattigeri, Moninder Singh, Kush R. Varshney, and Yunfeng Zhang. AI fairness 360: An extensible toolkit for detecting and mitigating algorithmic bias. *IBM J. Res. Dev.*, 63(4/5):4:1–4:15, 2019.

Richard Berk, Hoda Heidari, Shahin Jabbari, Michael Kearns, and Aaron Roth. Fairness in criminal justice risk assessments: The state of the art. *Sociol. Methods Res.*, 50(1):3–44, 2021.

Kristy Choi, Aditya Grover, Trisha Singh, Rui Shu, and Stefano Ermon. Fair generative modeling via weak supervision. In *ICML*, 2020.

Evgenii Chzhen, Christophe Denis, Mohamed Hebiri, Luca Oneto, and Massimiliano Pontil. Leveraging labeled and unlabeled data for consistent fair binary classification. In *NeurIPS*, pp. 12760–12770. 2019.

Jacob Cohen and Patricia Cohen. Applied multiple regression/correlation analysis for the behavioral sciences. 1975.

Andrew Cotter, Heinrich Jiang, and Karthik Sridharan. Two-player games for efficient non-convex constrained optimization. In *ALT*, pp. 300–332, 2019.

Steven Diamond and Stephen Boyd. CVXPY: A Python-embedded modeling language for convex optimization. *Journal of Machine Learning Research*, 17(83):1–5, 2016.

Frances Ding, Moritz Hardt, John Miller, and Ludwig Schmidt. Retiring adult: New datasets for fair machine learning. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan (eds.), *NeurIPS*, 2021.

Alexandre d'Aspremont and Stephen Boyd. Relaxations and randomized methods for nonconvex qcqps. *EE392o Class Notes, Stanford University*, 1:1–16, 2003.

Michael Feldman, Sorelle A. Friedler, John Moeller, Carlos Scheidegger, and Suresh Venkatasubramanian. Certifying and removing disparate impact. In *SIGKDD*, pp. 259–268, 2015.

Stephen Giguere, Blossom Metevier, Yuriy Brun, Philip S. Thomas, Scott Niekum, and Bruno Castro da Silva. Fairness guarantees under demographic shift. In *ICLR*, 2022.

Clark R Givens and Rae Michael Shortt. A class of wasserstein metrics for probability distributions. *Michigan Math. J.*, 31(2):231–240, 1984.

Moritz Hardt, Eric Price, and Nati Srebro. Equality of opportunity in supervised learning. In *NeurIPS*, pp. 3315–3323, 2016.

Jiayuan Huang, Arthur Gretton, Karsten Borgwardt, Bernhard Schölkopf, and Alex Smola. Correcting sample selection bias by unlabeled data. *NIPS*, 19:601–608, 2006.

Faisal Kamiran and Toon Calders. Data preprocessing techniques for classification without discrimination. *Knowl. Inf. Syst.*, 33(1):1–33, 2011.

Jon M. Kleinberg, Sendhil Mullainathan, and Manish Raghavan. Inherent trade-offs in the fair determination of risk scores. In *ITCS*, pp. 43:1–43:23, 2017.

Ron Kohavi. Scaling up the accuracy of naive-bayes classifiers: A decision-tree hybrid. In *SIGKDD*, pp. 202–207, 1996.

Subha Maity, Debarghya Mukherjee, Mikhail Yurochkin, and Yuekai Sun. Does enforcing fairness mitigate biases caused by subpopulation shift? In *NeurIPS*, 2021.

Aditya Krishna Menon and Robert C Williamson. The cost of fairness in binary classification. In *FAT**, pp. 107–118, 2018.

Alan Mishler and Niccolò Dalmasso. Fair when trained, unfair when deployed: Observable fairness measures are unstable in performative prediction settings. *ArXiv*, 2022.

Arvind Narayanan. Translation tutorial: 21 fairness definitions and their politics. In *ACM FAccT*, volume 1170, 2018.

Jaehyun Park and Stephen Boyd. General heuristics for nonconvex quadratically constrained quadratic programming. *ArXiv*, 2017.

Gabriel Peyré and Marco Cuturi. Computational optimal transport: With applications to data science. *Found. Trends Mach. Learn.*, 11(5-6):355–607, 2019.

Geoff Pleiss, Manish Raghavan, Felix Wu, Jon M. Kleinberg, and Kilian Q. Weinberger. On fairness and calibration. In *NeurIPS*, pp. 5684–5693, 2017.

Novi Quadrianto, Viktoriia Sharmanska, and Oliver Thomas. Discovering fair representations in the data domain. In *CVPR*, pp. 8227–8236, 2019.

Joseph Lee Rodgers and W Alan Nicewander. Thirteen ways to look at the correlation coefficient. *The American Statistician*, 42(1):59–66, 1988.

Yuji Roh, Kangwook Lee, Steven Euijong Whang, and Changho Suh. FR-Train: A mutual information-based approach to fair and robust training. In *ICML*, pp. 8147–8157, 2020.

Yuji Roh, Kangwook Lee, Steven Euijong Whang, and Changho Suh. FairBatch: Batch selection for model fairness. In *ICLR*, 2021.

Harvineet Singh, Rina Singh, Vishwali Mhasawade, and Rumi Chunara. Fairness violations and mitigation under covariate shift. In *FAccT*, pp. 3–13, 2021.

Philip S Thomas, Bruno Castro da Silva, Andrew G Barto, Stephen Giguere, Yuriy Brun, and Emma Brunskill. Preventing undesirable behavior of intelligent machines. *Science*, 366(6468):999–1004, 2019.

Michael Wick, swetasudha panda, and Jean-Baptiste Tristan. Unlocking fairness: a trade-off revisited. In *NeurIPS*, 2019.

Muhammad Bilal Zafar, Isabel Valera, Manuel Gomez-Rodriguez, and Krishna P. Gummadi. Fairness constraints: Mechanisms for fair classification. In *AISTATS*, pp. 962–970, 2017a.

Muhammad Bilal Zafar, Isabel Valera, Manuel Gomez-Rodriguez, and Krishna P. Gummadi. Fairness beyond disparate treatment & disparate impact: Learning classification without disparate mistreatment. In *WWW*, pp. 1171–1180, 2017b.

Richard S. Zemel, Yu Wu, Kevin Swersky, Toniann Pitassi, and Cynthia Dwork. Learning fair representations. In *ICML*, pp. 325–333, 2013.

Brian Hu Zhang, Blake Lemoine, and Margaret Mitchell. Mitigating unwanted biases with adversarial learning. In *AIES*, pp. 335–340, 2018.

Fuzhen Zhang. *The Schur complement and its applications*, volume 4. Springer Science & Business Media, 2006.

Kun Zhang, Bernhard Schölkopf, Krikamol Muandet, and Zhikun Wang. Domain adaptation under target and conditional shift. In *ICML*, pp. 819–827, 2013.

Han Zhao, Amanda Coston, Tameem Adel, and Geoffrey J. Gordon. Conditional learning of fair representations. In *ICLR*, 2020.

A APPENDIX – THEORY

A.1 PROOF FOR LEMMA 2

Continuing from Sec. 3.1, we provide a proof for Lemma 2.

Proof. We denote the Pearson's correlation coefficient between y and z as ρ_{yz}. By definition, $\rho_{yz} = \frac{Cov(y,z)}{\sigma(y)\sigma(z)}$. For binary y and z, we can rewrite ρ_{yz} as follows (Cohen & Cohen, 1975):

$$\rho_{yz} = \frac{Cov(y,z)}{\sigma(y)\sigma(z)} = \frac{\Pr(y=1,z=1)\Pr(y=0,z=0) - \Pr(y=1,z=0)\Pr(y=0,z=1)}{\sqrt{\Pr(y=1)\Pr(y=0)\Pr(z=1)\Pr(z=0)}}$$

If the marginal probabilities of y and z (i.e., $\Pr(y=y)$ and $\Pr(z=z)$) remain the same,

$$
\begin{aligned}
\rho_{yz} &\propto \Pr(y=1,z=1)\Pr(y=0,z=0) - \Pr(y=1,z=0)\Pr(y=0,z=1) \\
&\propto \frac{\Pr(y=1,z=1)}{\Pr(z=1)}\frac{\Pr(y=0,z=0)}{\Pr(z=0)} - \frac{\Pr(y=1,z=0)}{\Pr(z=0)}\frac{\Pr(y=0,z=1)}{\Pr(z=1)} \\
&= \Pr(y=1|z=1)\Pr(y=0|z=0) - \Pr(y=1|z=0)\Pr(y=0|z=1) \\
&= \Pr(y=1|z=1)(1-\Pr(y=1|z=0)) - \Pr(y=1|z=0)(1-\Pr(y=1|z=1)) \\
&= \Pr(y=1|z=1) - \Pr(y=1|z=0) - \Pr(y=1|z=1)\Pr(y=1|z=0) + \Pr(y=1|z=0)\Pr(y=1|z=1) \\
&= \Pr(y=1|z=1) - \Pr(y=1|z=0).
\end{aligned}
$$

Therefore, if the marginal probabilities of y and z remain the same, the (y,z)-correlation ρ_{yz} is proportional to $\Pr(y=1|z=1) - \Pr(y=1|z=0)$, which is the difference between the conditional probabilities of y given different z values.

$\square$

A.2 THE ACCURACY-FAIRNESS TRADEOFF WHEN IMPROVING FAIRNESS W.R.T. A SINGLE METRIC

Continuing from Sec. 3.1, we show that the (y,z)-correlation determines the accuracy-fairness tradeoff under certain conditions by applying Lemma 2 to Proposition 1.

The previous work (Menon & Williamson, 2018) shows that a higher alignment between y and z leads to a worse accuracy-fairness tradeoff w.r.t. demographic parity – more details are described in Proposition 8 in Menon & Williamson (2018). According to the previous work, alignment is defined as how many examples in each group have a specific label. We can thus measure the alignment as $\Pr(y=1|z=1) + \Pr(y=0|z=0)$. Then, we can rewrite the equation as follows:

$$
\begin{aligned}
\text{alignment} &= \Pr(y=1|z=1) + \Pr(y=0|z=0) \\
&= \Pr(y=1|z=1) + (1 - \Pr(y=1|z=0)) \\
&= 1 + \Pr(y=1|z=1) - \Pr(y=1|z=0).
\end{aligned}
$$

By applying Lemma 2 to the above result, we observe that the alignment between y and z is proportional to $((y,z)$-correlation $+1)$ when the marginal distributions of y and z remain the same. Therefore, when a model is trained w.r.t. demographic parity and the marginal probabilities of y and z do not change, a higher (y,z)-correlation results in a worse accuracy-fairness tradeoff.

A.3 ε-DP & ε-EO

Continuing from Sec. 3.1, we provide a proof for Proposition 6.

Proof. A model achieves both ε-DP and ε-EO when the two inequalities $|\Pr(\hat{y}=y|z=z) - \Pr(\hat{y}=y|z=z')| \le \varepsilon$ (i.e., ε-DP) and $|\Pr(\hat{y}=y|y=y,z=z) - \Pr(\hat{y}=y|y=y,z=z')| \le \varepsilon$ (i.e., ε-EO) are satisfied, where $y \ne y', y, y' \in \{0,1\}$ and $z \ne z', z, z' \in \{0,1\}$.

By combining the law of total probability and ε-DP, we can get the following inequality:

$$-\varepsilon \leq \Pr(\hat{y} = y | z = z, y = y') \Pr(y = y' | z = z) + \Pr(\hat{y} = y | z = z, y = y) \Pr(y = y | z = z)$$
$$- \Pr(\hat{y} = y | z = z', y = y') \Pr(y = y' | z = z') - \Pr(\hat{y} = y | z = z', y = y) \Pr(y = y | z = z') \leq \varepsilon. \tag{1}$$

Also, ε-EO can be rewritten as follows:

$$-\varepsilon + \Pr(\hat{y} = y | z = z', y = y) \leq \Pr(\hat{y} = y | z = z, y = y) \leq \varepsilon + \Pr(\hat{y} = y | z = z', y = y). \tag{2}$$

By substituting Eq. 2 to Eq. 1, we can get the following inequality:

$$(-\varepsilon + \Pr(\hat{y} = y | z = z', y = y')) \Pr(y = y' | z = z) + (-\varepsilon + \Pr(\hat{y} = y | z = z', y = y)) \Pr(y = y | z = z)$$
$$- \Pr(\hat{y} = y | z = z', y = y') \Pr(y = y' | z = z') - \Pr(\hat{y} = y | z = z', y = y) \Pr(y = y | z = z')$$
$$\leq \Pr(\hat{y} = y | z = z, y = y') \Pr(y = y' | z = z) + \Pr(\hat{y} = y | z = z, y = y) \Pr(y = y | z = z) \tag{3}$$
$$- \Pr(\hat{y} = y | z = z', y = y') \Pr(y = y' | z = z') - \Pr(\hat{y} = y | z = z', y = y) \Pr(y = y | z = z')$$
$$\leq (\varepsilon + \Pr(\hat{y} = y | z = z', y = y')) \Pr(y = y' | z = z) + (\varepsilon + \Pr(\hat{y} = y | z = z', y = y)) \Pr(y = y | z = z)$$
$$- \Pr(\hat{y} = y | z = z', y = y') \Pr(y = y' | z = z') - \Pr(\hat{y} = y | z = z', y = y) \Pr(y = y | z = z').$$

By subtracting Eq. 2 from Eq. 3,

$$- \varepsilon + (-\varepsilon + \Pr(\hat{y} = y | z = z', y = y')) \Pr(y = y' | z = z) + (-\varepsilon + \Pr(\hat{y} = y | z = z', y = y)) \Pr(y = y | z = z)$$
$$- \Pr(\hat{y} = y | z = z', y = y') \Pr(y = y' | z = z') - \Pr(\hat{y} = y | z = z', y = y) \Pr(y = y | z = z')$$
$$\leq 0$$
$$\leq \varepsilon + (\varepsilon + \Pr(\hat{y} = y | z = z', y = y')) \Pr(y = y' | z = z) + (\varepsilon + \Pr(\hat{y} = y | z = z', y = y)) \Pr(y = y | z = z)$$
$$- \Pr(\hat{y} = y | z = z', y = y') \Pr(y = y' | z = z') - \Pr(\hat{y} = y | z = z', y = y) \Pr(y = y | z = z').$$

By rearranging the terms, we get the followings:

$$-2\varepsilon \leq (\Pr(\hat{y} = y | z = z', y = y') - \Pr(\hat{y} = y | z = z', y = y))(\Pr(y = y' | z = z) - \Pr(y = y' | z = z')) \leq 2\varepsilon$$
$$\Rightarrow -2\varepsilon \leq (\Pr(\hat{y} = y | z = z', y = y') - \Pr(\hat{y} = y | z = z', y = y))(1 - \Pr(y = y | z = z) - 1 + \Pr(y = y | z = z')) \leq 2\varepsilon.$$

Thus, we get the following inequality, which is in Proposition 6:

$$|\Pr(y = y | z = z) - \Pr(y = y | z = z')| \, |\Pr(\hat{y} = y | y = y, z = z) - \Pr(\hat{y} = y | y = y', z = z)| \leq 2\varepsilon.$$

$$\square$$

A.4 ε-PP & ε-DP

Continuing from Sec. 3.1, we consider fair training w.r.t. both predictive parity (PP) and demographic parity (DP). We can define ε-PP & ε-DP as follows:

$$-\varepsilon \leq \Pr(y = y | \hat{y} = y, z = 0) - \Pr(y = y | \hat{y} = y, z = 1) \leq \varepsilon \ \text{(i.e., } \varepsilon\text{-PP)}$$
$$-\varepsilon \leq \Pr(\hat{y} = y | z = 0) - \Pr(\hat{y} = y | z = 1) \leq \varepsilon \ \text{(i.e., } \varepsilon\text{-DP)}$$

Based on these definitions, we give a proposition for ε-PP and ε-DP:

Proposition 8 (ε-PP & ε-DP). *Let a model achieve both ε-PP and ε-DP. Then, the following inequality holds:*

$$\frac{|\Pr(y = y, \hat{y} = y | z = z) - \Pr(y = y, \hat{y} = y | z = z')|}{2\Pr(y = y | \hat{y} = y, z = z) + \Pr(\hat{y} = y | z = z) + \Pr(y = y | \hat{y} = y, z = z')} \leq \varepsilon, \ z \neq z', \ z, z' \in \mathbb{Z}, \ y \in \mathbb{Y}.$$

Proof. From ε-DP, we get

$$-\varepsilon + \Pr(\hat{y} = y | z = 1) \leq \Pr(\hat{y} = y | z = 0) \leq \varepsilon + \Pr(\hat{y} = y | z = 1). \tag{4}$$

From ε-PP, we get

$$-\varepsilon \leq \Pr(\hat{y} = y|z = 0)\frac{\Pr(z = 0)}{\Pr(\hat{y} = y, z = 0)}\frac{\Pr(y = y, \hat{y} = y, z = 0)}{\Pr(\hat{y} = y, z = 0)} - \Pr(\hat{y} = y|z = 1)\frac{\Pr(z = 1)}{\Pr(\hat{y} = y, z = 1)}\frac{\Pr(y = y, \hat{y} = y, z = 1)}{\Pr(\hat{y} = y, z = 1)} \leq \varepsilon.$$
$$(5)$$

By substituting Eq. 4 to Eq. 5, we can get the following inequality:

$$\{-\varepsilon + \Pr(\hat{y} = y|z = 1)\}\frac{\Pr(z = 0)}{\Pr(\hat{y} = y, z = 0)}\frac{\Pr(y = y, \hat{y} = y, z = 0)}{\Pr(\hat{y} = y, z = 0)} - \Pr(\hat{y} = y|z = 1)\frac{\Pr(z = 1)}{\Pr(\hat{y} = y, z = 1)}\frac{\Pr(y = y, \hat{y} = y, z = 1)}{\Pr(\hat{y} = y, z = 1)}$$
$$\leq \Pr(\hat{y} = y|z = 0)\frac{\Pr(z = 0)}{\Pr(\hat{y} = y, z = 0)}\frac{\Pr(y = y, \hat{y} = y, z = 0)}{\Pr(\hat{y} = y, z = 0)} - \Pr(\hat{y} = y|z = 1)\frac{\Pr(z = 1)}{\Pr(\hat{y} = y, z = 1)}\frac{\Pr(y = y, \hat{y} = y, z = 1)}{\Pr(\hat{y} = y, z = 1)}$$
$$(6)$$
$$\leq \{\varepsilon + \Pr(\hat{y} = y|z = 1)\}\frac{\Pr(z = 0)}{\Pr(\hat{y} = y, z = 0)}\frac{\Pr(y = y, \hat{y} = y, z = 0)}{\Pr(\hat{y} = y, z = 0)} - \Pr(\hat{y} = y|z = 1)\frac{\Pr(z = 1)}{\Pr(\hat{y} = y, z = 1)}\frac{\Pr(y = y, \hat{y} = y, z = 1)}{\Pr(\hat{y} = y, z = 1)}.$$

By subtracting Eq. 5 from Eq. 6,

$$-\varepsilon + \{-\varepsilon + \Pr(\hat{y}=y|z=1)\}\frac{\Pr(z = 0)}{\Pr(\hat{y} = y, z = 0)}\frac{\Pr(y = y, \hat{y} = y, z = 0)}{\Pr(\hat{y} = y, z = 0)} - \Pr(\hat{y}=y|z=1)\frac{\Pr(z = 1)}{\Pr(\hat{y} = y, z = 1)}\frac{\Pr(y = y, \hat{y} = y, z = 1)}{\Pr(\hat{y} = y, z = 1)}$$
$$\leq 0$$
$$\leq \varepsilon + \{\varepsilon + \Pr(\hat{y}=y|z=1)\}\frac{\Pr(z = 0)}{\Pr(\hat{y} = y, z = 0)}\frac{\Pr(y = y, \hat{y} = y, z = 0)}{\Pr(\hat{y} = y, z = 0)} - \Pr(\hat{y}=y|z=1)\frac{\Pr(z = 1)}{\Pr(\hat{y} = y, z = 1)}\frac{\Pr(y = y, \hat{y} = y, z = 1)}{\Pr(\hat{y} = y, z = 1)}.$$

By rearranging the terms, we get the following inequality:

$$-\varepsilon \cdot \frac{\Pr(z = 0)\Pr(y = y, \hat{y} = y, z = 0)}{(\Pr(\hat{y} = y, z = 0))^2} - \varepsilon$$
$$\leq \Pr(\hat{y} = y|z = 1)\{\frac{\Pr(z = 1)\Pr(y = y, \hat{y} = y, z = 1)}{(\Pr(\hat{y} = y, z = 1))^2} - \frac{\Pr(z = 0)\Pr(y = y, \hat{y} = y, z = 0)}{(\Pr(\hat{y} = y, z = 0))^2}\}$$
$$\leq \varepsilon \cdot \frac{\Pr(z = 0)\Pr(y = y, \hat{y} = y, z = 0)}{(\Pr(\hat{y} = y, z = 0))^2} + \varepsilon$$

which is rewritten as follows:

$$-\varepsilon \cdot \frac{\Pr(y = y|\hat{y} = y, z = 0) + \Pr(\hat{y} = y|z = 0)}{\Pr(\hat{y} = y|z = 0)}$$
$$\leq \Pr(\hat{y} = y|z = 1)\{\frac{\Pr(y = y|\hat{y} = y, z = 1)}{\Pr(\hat{y} = y|z = 1)} - \frac{\Pr(y = y|\hat{y} = y, z = 0)}{\Pr(\hat{y} = y|z = 0)}\}$$
$$\leq \varepsilon \cdot \frac{\Pr(y = y|\hat{y} = y, z = 0) + \Pr(\hat{y} = y|z = 0)}{\Pr(\hat{y} = y|z = 0)}.$$

By multiplying $\frac{\Pr(\hat{y}=y|z=0)}{\Pr(y=y|\hat{y}=y,z=0)+\Pr(\hat{y}=y|z=0)}$ for all terms in the above inequality, we can get

$$-\varepsilon \leq \frac{\Pr(\hat{y} = y|z = 0)\Pr(y = y|\hat{y} = y, z = 1) - \Pr(\hat{y} = y|z = 1)\Pr(y = y|\hat{y} = y, z = 0)}{\Pr(y = y|\hat{y} = y, z = 0) + \Pr(\hat{y} = y|z = 0)} \leq \varepsilon.$$
$$(7)$$

Let $A = \Pr(y = y|\hat{y} = y, z = 0) + \Pr(\hat{y} = y|z = 0)$. Since $-\varepsilon \leq \Pr(\hat{y} = y|z = 0) - \Pr(\hat{y} = y|z = 1) \leq \varepsilon$ (i.e., ε-DP), we can make another inequality from Eq. 7:

$$\frac{(-\varepsilon + \Pr(\hat{y} = y|z = 1))\Pr(y = y|\hat{y} = y, z = 1) - (\varepsilon + \Pr(\hat{y} = y|z = 0))\Pr(y = y|\hat{y} = y, z = 0)}{A}$$
$$\leq \frac{\Pr(\hat{y} = y|z = 0)\Pr(y = y|\hat{y} = y, z = 1) - \Pr(\hat{y} = y|z = 1)\Pr(y = y|\hat{y} = y, z = 0)}{A} \quad (8)$$
$$\leq \frac{(\varepsilon + \Pr(\hat{y} = y|z = 1))\Pr(y = y|\hat{y} = y, z = 1) - (-\varepsilon + \Pr(\hat{y} = y|z = 0))\Pr(y = y|\hat{y} = y, z = 0)}{A}.$$

By subtracting Eq. 7 and Eq. 8,

$$-\varepsilon + \frac{(-\varepsilon + \Pr(\hat{y}=y|z=1))\Pr(y=y|\hat{y}=y,z=1) - (\varepsilon + \Pr(\hat{y}=y|z=0))\Pr(y=y|\hat{y}=y,z=0)}{A}$$

$$\leq 0$$

$$\leq \varepsilon + \frac{(\varepsilon + \Pr(\hat{y}=y|z=1))\Pr(y=y|\hat{y}=y,z=1) - (-\varepsilon + \Pr(\hat{y}=y|z=0))\Pr(y=y|\hat{y}=y,z=0)}{A}.$$

Since $\Pr(\hat{y}=y|z=z)\Pr(y=y|\hat{y}=y,z=z) = \Pr(y=y,\hat{y}=y|z=z)$, we can rewritten the above inequality as follows:

$$-\varepsilon + \frac{-\varepsilon\{\Pr(y=y|\hat{y}=y,z=1) + \Pr(y=y|\hat{y}=y,z=0)\} + \Pr(y=y,\hat{y}=y|z=1) - \Pr(y=y,\hat{y}=y|z=0)}{A}$$

$$\leq 0$$

$$\leq \varepsilon + \frac{\varepsilon\{\Pr(y=y|\hat{y}=y,z=1) + \Pr(y=y|\hat{y}=y,z=0)\} + \Pr(y=y,\hat{y}=y|z=1) - \Pr(y=y,\hat{y}=y|z=0)}{A}.$$

Now, let $B = \Pr(y=y|\hat{y}=y,z=1) + \Pr(y=y|\hat{y}=y,z=0)$ and $C = \Pr(y=y,\hat{y}=y|z=1) - \Pr(y=y,\hat{y}=y|z=0)$. Then,

$$-\varepsilon + \frac{1}{A}(-\varepsilon \cdot B + C) \leq 0 \leq \varepsilon + \frac{1}{A}(\varepsilon \cdot B + C).$$

By arranging the terms,

$$-\varepsilon \cdot (1 + \frac{B}{A}) + \frac{C}{A} \leq 0 \leq \varepsilon \cdot (1 + \frac{B}{A}) + \frac{C}{A}$$

$$\implies -\varepsilon \leq \frac{-C}{A+B} \leq \varepsilon.$$

Therefore, we can conclude

$$\frac{|\Pr(y=y,\hat{y}=y|z=0) - \Pr(y=y,\hat{y}=y|z=1)|}{2\Pr(y=y|\hat{y}=y,z=0) + \Pr(\hat{y}=y|z=0) + \Pr(y=y|\hat{y}=y,z=1)} \leq \varepsilon.$$

If we reverse the z values in the derivation, we get the same formula with only the z value changed in the above expression. As a result, we get the following inequality, which is in Proposition 8:

$$\frac{|\Pr(y=y,\hat{y}=y|z=z) - \Pr(y=y,\hat{y}=y|z=z')|}{2\Pr(y=y|\hat{y}=y,z=z) + \Pr(\hat{y}=y|z=z) + \Pr(y=y|\hat{y}=y,z=z')} \leq \varepsilon, \ z \neq z', \ z,z' \in \mathbb{Z}, \ y \in \mathbb{Y}.$$

$$\square$$

Therefore, to make $\varepsilon = 0$, the numerator term $|\Pr(y=y,\hat{y}=y|z=z) - \Pr(y=y,\hat{y}=y|z=z')|$ should be zero. When $|\Pr(y=y,\hat{y}=y|z=z) - \Pr(y=y,\hat{y}=y|z=z')| = 0$, the following is satisfied: $(y,\hat{y}) \perp z$, which implies $y \perp z$ and $\hat{y} \perp z$. Here, $y \perp z$ indicates that $|\Pr(y=y|z=z) - \Pr(y=y|z=z')|$ is zero. As a result, perfectly satisfying PP and DP requires the data to be fully unbiased. We thus suspect that the achievable model fairness w.r.t. both PP and DP is affected by the (y,z)-correlation.

A.5 ε-EO & ε-PP

Continuing from Sec. 3.1, we consider fair training w.r.t. both equalized odds (EO) and predictive parity (PP). We can define ε-EO & ε-PP as follows:

$$-\varepsilon \leq \Pr(\hat{y}=y|y=y,z=0) - \Pr(\hat{y}=y|y=y,z=1) \leq \varepsilon \ \text{(i.e., } \varepsilon\text{-EO)}$$
$$-\varepsilon \leq \Pr(y=y|\hat{y}=y,z=0) - \Pr(y=y|\hat{y}=y,z=1) \leq \varepsilon \ \text{(i.e., } \varepsilon\text{-PP)}$$

Based on these definitions, we give a proposition for ε-EO and ε-PP:

Proposition 9 (ε-EO & ε-PP). *Let a model achieve both ε-EO and ε-PP. Then, the following inequality holds:*

$$\frac{\Pr(\hat{\mathbf{y}} = y | \mathbf{y} = y, \mathbf{z} = z')}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = z) + \Pr(\mathbf{y} = y, \mathbf{z} = z)} \cdot | \Pr(\mathbf{y} = y) - \Pr(\mathbf{y} = y | \mathbf{z} = z') \cdot \frac{\Pr(\hat{\mathbf{y}} = y)}{\Pr(\hat{\mathbf{y}} = y | \mathbf{z} = z')} | \leq \varepsilon, \; z \neq z', \; z, z' \in \mathbb{Z}, \; y \in \mathbb{Y}.$$

Proof. From ε-EO, we get

$$-\varepsilon + \Pr(\hat{\mathbf{y}} = y | \mathbf{y} = y, \mathbf{z} = 1) \leq \Pr(\hat{\mathbf{y}} = y | \mathbf{y} = y, \mathbf{z} = 0) \leq \varepsilon + \Pr(\hat{\mathbf{y}} = y | \mathbf{y} = y, \mathbf{z} = 1). \quad (9)$$

From ε-PP, we get

$$-\varepsilon \leq \Pr(\hat{\mathbf{y}} = y | \mathbf{y} = y, \mathbf{z} = 0)\frac{\Pr(\mathbf{y} = y, \mathbf{z} = 0)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 0)} - \Pr(\hat{\mathbf{y}} = y | \mathbf{y} = y, \mathbf{z} = 1)\frac{\Pr(\mathbf{y} = y, \mathbf{z} = 1)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 1)} \leq \varepsilon. \quad (10)$$

By substituting Eq. 9 to Eq. 10, we can get the following inequality:

$$(-\varepsilon + \Pr(\hat{\mathbf{y}} = y | \mathbf{y} = y, \mathbf{z} = 1))\frac{\Pr(\mathbf{y} = y, \mathbf{z} = 0)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 0)} - \Pr(\hat{\mathbf{y}} = y | \mathbf{y} = y, \mathbf{z} = 1)\frac{\Pr(\mathbf{y} = y, \mathbf{z} = 1)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 1)}$$

$$\leq \Pr(\hat{\mathbf{y}} = y | \mathbf{y} = y, \mathbf{z} = 0)\frac{\Pr(\mathbf{y} = y, \mathbf{z} = 0)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 0)} - \Pr(\hat{\mathbf{y}} = y | \mathbf{y} = y, \mathbf{z} = 1)\frac{\Pr(\mathbf{y} = y, \mathbf{z} = 1)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 1)} \quad (11)$$

$$\leq (\varepsilon + \Pr(\hat{\mathbf{y}} = y | \mathbf{y} = y, \mathbf{z} = 1))\frac{\Pr(\mathbf{y} = y, \mathbf{z} = 0)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 0)} - \Pr(\hat{\mathbf{y}} = y | \mathbf{y} = y, \mathbf{z} = 1)\frac{\Pr(\mathbf{y} = y, \mathbf{z} = 1)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 1)}.$$

By subtracting Eq. 10 from Eq. 11,

$$-\varepsilon + (-\varepsilon + \Pr(\hat{\mathbf{y}} = y | \mathbf{y} = y, \mathbf{z} = 1))\frac{\Pr(\mathbf{y} = y, \mathbf{z} = 0)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 0)} - \Pr(\hat{\mathbf{y}} = y | \mathbf{y} = y, \mathbf{z} = 1)\frac{\Pr(\mathbf{y} = y, \mathbf{z} = 1)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 1)}$$

$$\leq 0$$

$$\leq \varepsilon + (\varepsilon + \Pr(\hat{\mathbf{y}} = y | \mathbf{y} = y, \mathbf{z} = 1))\frac{\Pr(\mathbf{y} = y, \mathbf{z} = 0)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 0)} - \Pr(\hat{\mathbf{y}} = y | \mathbf{y} = y, \mathbf{z} = 1)\frac{\Pr(\mathbf{y} = y, \mathbf{z} = 1)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 1)}.$$

By rearranging the terms, we get the following inequality:

$$-\varepsilon \cdot \frac{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 0) + \Pr(\mathbf{y} = y, \mathbf{z} = 0)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 0)}$$

$$\leq \Pr(\hat{\mathbf{y}} = y | \mathbf{y} = y, \mathbf{z} = 1)\{\frac{\Pr(\mathbf{y} = y, \mathbf{z} = 0)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 0)} - \frac{\Pr(\mathbf{y} = y, \mathbf{z} = 1)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 1)}\}$$

$$\leq \varepsilon \cdot \frac{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 0) + \Pr(\mathbf{y} = y, \mathbf{z} = 0)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 0)}.$$

By multiplying $\frac{\Pr(\hat{\mathbf{y}}=y,\mathbf{z}=0)}{\Pr(\hat{\mathbf{y}}=y,\mathbf{z}=0)+\Pr(\mathbf{y}=y,\mathbf{z}=0)}$ for all terms in the inequality, we can get

$$-\varepsilon \leq \frac{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 0) \Pr(\hat{\mathbf{y}} = y | \mathbf{y} = y, \mathbf{z} = 1)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 0) + \Pr(\mathbf{y} = y, \mathbf{z} = 0)}\{\frac{\Pr(\mathbf{y} = y, \mathbf{z} = 0)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 0)} - \frac{\Pr(\mathbf{y} = y, \mathbf{z} = 1)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 1)}\} \leq \varepsilon$$

which is rewritten as follows:

$$-\varepsilon \leq \frac{\Pr(\hat{\mathbf{y}} = y | \mathbf{y} = y, \mathbf{z} = 1)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 0) + \Pr(\mathbf{y} = y, \mathbf{z} = 0)}\{\Pr(\mathbf{y} = y, \mathbf{z} = 0) - \frac{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 0)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 1)} \cdot \Pr(\mathbf{y} = y, \mathbf{z} = 1)\} \leq \varepsilon.$$

Since $\Pr(\mathbf{y} = y, \mathbf{z} = 0) = \Pr(\mathbf{y} = y) - \Pr(\mathbf{y} = y, \mathbf{z} = 1)$ by the total probability law,

$$-\varepsilon \leq \frac{\Pr(\hat{\mathbf{y}} = y | \mathbf{y} = y, \mathbf{z} = 1)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 0) + \Pr(\mathbf{y} = y, \mathbf{z} = 0)}\{\Pr(\mathbf{y} = y) - \Pr(\mathbf{y} = y, \mathbf{z} = 1) - \frac{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 0)}{\Pr(\hat{\mathbf{y}} = y, \mathbf{z} = 1)} \cdot \Pr(\mathbf{y} = y, \mathbf{z} = 1)\} \leq \varepsilon.$$

By arranging the terms,

$$-\varepsilon \le \frac{\Pr(\hat{y} = y | y = y, z = 1)}{\Pr(\hat{y} = y, z = 0) + \Pr(y = y, z = 0)}\{\Pr(y = y) - \Pr(y = y, z = 1) \cdot (1 + \frac{\Pr(\hat{y} = y, z = 0)}{\Pr(\hat{y} = y, z = 1)})\} \le \varepsilon$$

$$\Rightarrow -\varepsilon \le \frac{\Pr(\hat{y} = y | y = y, z = 1)}{\Pr(\hat{y} = y, z = 0) + \Pr(y = y, z = 0)}\{\Pr(y = y) - \Pr(y = y, z = 1) \cdot \frac{\Pr(\hat{y} = y)}{\Pr(\hat{y} = y, z = 1)}\} \le \varepsilon.$$

Therefore, we can conclude

$$\frac{\Pr(\hat{y} = y | y = y, z = 1)}{\Pr(\hat{y} = y, z = 0) + \Pr(y = y, z = 0)} \cdot |\Pr(y = y) - \Pr(y = y, z = 1) \cdot \frac{\Pr(\hat{y} = y)}{\Pr(\hat{y} = y, z = 1)}| \le \varepsilon.$$

If we reverse the z values in the derivation, we get the same formula with only the z value changed in the above expression. As a result, we get the following inequality, which is in Proposition 9:

$$\frac{\Pr(\hat{y} = y | y = y, z = z')}{\Pr(\hat{y} = y, z = z) + \Pr(y = y, z = z)} \cdot |\Pr(y = y) - \Pr(y = y | z = z') \cdot \frac{\Pr(\hat{y} = y)}{\Pr(\hat{y} = y | z = z')}| \le \varepsilon, \ z \ne z', \ z, z' \in \mathbb{Z}, \ y \in \mathbb{Y}.$$

$$\square$$

Therefore, $\varepsilon = 0$ when $\Pr(y = y) = \Pr(y = y | z = z')$ and $\Pr(\hat{y} = y) = \Pr(\hat{y} = y | z = z')$ (i.e., $y \perp z$ and $\hat{y} \perp z$). Here, satisfying both $y \perp z$ and $\hat{y} \perp z$ is the sufficient condition of perfectly satisfying EO and PP. Note that $y \perp z$ implies that the data is unbiased. We thus suspect that the achievable model fairness w.r.t. both EO and PP is affected by the (y, z)-correlation.

A.6 SEMIDEFINITE RELAXATION

Continuing from Sec. 4.1, we provide details of the semidefinite relaxation in our optimization.

Recall our original optimization as follows:

$$\min_{w'} \sum_{\forall y,z}(w_{y=y,z=z} - w'_{y=y,z=z})^2$$

$$\text{s.t. } \alpha \le \frac{w'_{y=1,z=1}}{w'_{y=1,z=1} + w'_{y=0,z=1}} - \frac{w'_{y=1,z=0}}{w'_{y=1,z=0} + w'_{y=0,z=0}} \le \beta,$$

$$|(w'_{y=1,z=1} + w'_{y=1,z=0}) - \Pr_{\text{train}}(y = 1)| \le \gamma_y,$$

$$|(w'_{y=1,z=1} + w'_{y=0,z=1}) - \Pr_{\text{train}}(z = 1)| \le \gamma_z,$$

$$\sum_{\forall y,z} w'_{y=y,z=z} = 1, \ 0 \le w'_{y=y,z=z} \le 1, \ \forall y \in \{0,1\}, z \in \{0,1\}$$

where $\Pr_{\text{train}}(y = 1) = w_{y=1,z=1} + w_{y=1,z=0}$ and $\Pr_{\text{train}}(z = 1) = w_{y=1,z=1} + w_{y=0,z=1}$.

As the above optimization is a non-convex quadratically constrained quadratic problem (non-convex QCQP), we now apply the semidefinite relaxation (SDP relaxation) (Park & Boyd, 2017). We first rewrite the above optimization using matrices:

$$\min_x \ x^T P_0 x + q_0^T x$$

$$\text{s.t. } x^T P_\alpha x \ge 0, \ x^T P_\beta x \le 0,$$

$$|q_2^T x - \Pr_{\text{train}}(y = 1)| \le \gamma_y,$$

$$|q_3^T x - \Pr_{\text{train}}(z = 1)| \le \gamma_z$$

$$q_4^T x = 1, \ 0 \le x_i \le 1 \ \forall i$$

where $x = [x_1 \ x_2 \ x_3 \ x_4]^T = [w'_{1,1} \ w'_{1,0} \ w'_{0,1} \ w'_{0,0}]^T$, $q_0 = -2[w_{1,1} \ w_{1,0} \ w_{0,1} \ w_{0,0}]^T$, $q_2 = [1 \ 0 \ 1 \ 0]^T$, $q_3 = [1 \ 1 \ 0 \ 0]^T$, $q_4 = [1 \ 1 \ 1 \ 1]^T$,

$$P_0 = \text{diag}(\mathbf{1}), \ P_\alpha = \begin{bmatrix} 0 & -\alpha/2 & 0 & (1-\alpha)/2 \\ -\alpha/2 & 0 & (-1-\alpha)/2 & 0 \\ 0 & (-1-\alpha)/2 & 0 & -\alpha/2 \\ (1-\alpha)/2 & 0 & -\alpha/2 & 0 \end{bmatrix}, \text{ and } P_\beta = \begin{bmatrix} 0 & -\beta/2 & 0 & (1-\beta)/2 \\ -\beta/2 & 0 & (-1-\beta)/2 & 0 \\ 0 & (-1-\beta)/2 & 0 & -\beta/2 \\ (1-\beta)/2 & 0 & -\beta/2 & 0 \end{bmatrix}.$$

As $x^T P x = \mathbf{Tr}(P(xx^T))$, we can get the following optimization:

$$\min_{X,x} \mathbf{Tr}(XP_0) + q_0^T x$$

$$\text{s.t. } \mathbf{Tr}(XP_\alpha) \geq 0, \ \mathbf{Tr}(XP_\beta) \leq 0$$

$$|q_2^T x - \Pr_{\text{train}}(y = 1)| \leq \gamma_y,$$

$$|q_3^T x - \Pr_{\text{train}}(z = 1)| \leq \gamma_z$$

$$q_4^T x = 1, \ \ 0 \leq x_i \leq 1 \ \ \forall i,$$

$$X = xx^T$$

where $\mathbf{Tr}(\cdot)$ is the trace and $X = xx^T$.

In the above optimization, the last constraint is non-convex. Thus, we relax the non-convex constraint $X = xx^T$ into $X - xx^T \succeq 0$, which is convex, and then use a Schur complement (Zhang, 2006) to get the final SDP form:

$$\min_{X,x} \mathbf{Tr}(XP_0) + q_0^T x$$

$$\text{s.t. } \mathbf{Tr}(XP_\alpha) \geq 0, \ \mathbf{Tr}(XP_\beta) \leq 0$$

$$|q_2^T x - \Pr_{\text{train}}(y = 1)| \leq \gamma_y,$$

$$|q_3^T x - \Pr_{\text{train}}(z = 1)| \leq \gamma_z$$

$$q_4^T x = 1, \ \ 0 \leq x_i \leq 1 \ \ \forall i,$$

$$\begin{bmatrix} X & x \\ x^T & 1 \end{bmatrix} \succeq 0.$$

When we solve the above SDP relaxation problem using convex optimization solvers, we set the 5×5-matrix A as the variable so as to indicate $\begin{bmatrix} X & x \\ x^T & 1 \end{bmatrix}$. Then, we get the solution $x = \begin{bmatrix} x_1 & x_2 & x_3 & x_4 \end{bmatrix}^T$ by taking the first four elements of the last vector in the resulting matrix A.

A.7 OPTIONAL STEP FOR MINIMIZING OVERALL DISTRIBUTION CHANGE

Continuing from Sec. 4.2, we explain the details on the optional step in Algorithm 1. We can use the optional step (`MinDistChange`) to find non-uniform data sample weights within each (y, z)-class that minimizes the overall distribution change in terms of the Wasserstein distance (Givens & Shortt, 1984), rather than using identical weights. In the optional step, we first divide the examples in each $(y=y, z=z)$-class into two sets $\{y=y, z=z, t=0\}$ and $\{y=y, z=z, t=1\}$ with equal numbers, where t is a specific feature that can be a criterion for dividing the examples. For example, we can find a median of a non-sensitive attribute x_1 and set $t = 0$ for an example if the x_1 value of the example is lower than the median of x_1. We set $t = 1$ otherwise. We then make a candidate set of partial weights $w'_{y=y,z=z,t=t}$ on each $(y=y, z=z, t=t)$-class, where $\sum w'_{y=y,z=z,t=t} = w'_{y=y,z=z}$. Note that we can extend t beyond the binary setting to find more detailed partial weights. For each partial weight candidate, we calculate the candidate sample-wise weights ($\mathbf{d}_{\text{tmp}}$) to ensure that the sample weight sum in each $(y=y, z=z, t=t)$-class is $w_{y=y,z=z,t=t} \cdot n$, where n is the total number of samples in the original training data. Then, we draw new data $\tilde{D}$ from the original training data D via weighted sampling according to $\mathbf{d}_{\text{tmp}}$. Then, we calculate the Wasserstein distance between $\tilde{D}$ and D via an optimal transport technique (Peyré & Cuturi, 2019). As a result, the algorithm returns the final sample-wise weights ($\mathbf{d}_{\text{min}}$) that result in the closest distribution from the original data.

B APPENDIX – EXPERIMENTS

B.1 SIMULATION SETTINGS

Continuing from Sec. 3.1, we explain the details of the simulation. The goal of the simulation is to confirm our theoretical observations by generating various synthetic classifiers that show the full

---

Algorithm 2: MinDistChange

Input: train data D, original ratio $w_{y,z}$, new ratio $w'_{y,z}$

In each (y=y, z=z)-class, divide the examples into two sets {y=y, z=z, t=0} and {y=y, z=z, t=1}
  with equal numbers

partials = $[0, 1/m, 2/m, ..., 1]$

$W_{y=y,z=z} \leftarrow []$, $\forall (y,z) \in \mathbb{Y} \times \mathbb{Z}$

for *each (y=y, z=z)-class* **do**

   for p in partials **do**

      $w'_{y=y,z=z,t=0} = w'_{y=y,z=z} \cdot p$

      $w'_{y=y,z=z,t=1} = w'_{y=y,z=z} \cdot (1-p)$

      Append $[w'_{y=y,z=z,t=0}, w'_{y=y,z=z,t=1}]$ to $W_{y=y,z=z}$

candidates $\leftarrow W_{y=1,z=1} \times W_{y=1,z=0} \times W_{y=0,z=1} \times W_{y=0,z=0}$

minD $\leftarrow$ an initial large value

for partial-weight in candidates **do**

   $d_j \leftarrow w'_{y=y,z=z,t=t}/(w_{y=y,z=z} \cdot 0.5), \forall j \in \mathbb{I}_{(y,z,t)}, \forall (y,z,t) \in \mathbb{Y} \times \mathbb{Z} \times \{0,1\}$

   $\mathbf{d}_{tmp} = \{d_i\}_{i=1,...,n}$

   Draw data $\tilde{D}$ from D via weighted sampling w.r.t. $\mathbf{d}_{tmp}$

   wassD $\leftarrow$ Calculate the Wasserstein distance between $\tilde{D}$ and D via optimal transport

   if *wassD < minD* **then**

      $\mathbf{d}_{min} = \mathbf{d}_{tmp}$

      minD = wassD

Output : $\mathbf{d}_{min}$

Figure 4: Accuracy-unfairness performances of fair training with FairBatch (Roh et al., 2021) on two synthetic data with different (y, z)-correlations. We measure fairness w.r.t. equalized odds (EO).

range of possible model performances. To this end, we generate 1000 data samples, where each sample has y and z features. We first set y and z to have a specific correlation. We then generate various synthetic classifiers that have different ŷ by varying the probability $\Pr(\hat{y} > 0)$ in each (y=y, z=z)-class. For each synthetic classifier, we measure the accuracy and fairness performances based on y, z, and the classifier's ŷ. We repeat the above procedures while varying y and z to have different correlations. As a result, we get the simulation results in Figure 2 by plotting all the classifier accuracy and fairness performances within each (y, z)-correlation.

B.2 EMPIRICAL OBSERVATIONS FOR EQUALIZED ODDS

Continuing from Sec. 3.1, we perform an experiment to observe that higher (y, z)-correlation leads to a worse accuracy-fairness tradeoff w.r.t. equalized odds (EO) in practice. Figure 4 shows the accuracy-unfairness performances of the logistic regression model trained using FairBatch (Roh et al., 2021) to improve EO on two synthetic datasets with low and high (y, z)-correlations. As a result, low correlation enables classifiers to attain better accuracy-fairness tradeoffs (i.e., close to the bottom right) w.r.t. EO. This experiment shows that the (y, z)-correlation indeed affects the accuracy-fairness tradeoff w.r.t. EO in practice.

Table 2: Performances on the AdultCensus test dataset. Other experimental settings are identical to those in Table 1.

	Single (DP)		Multiple (DP & EO)	
Method	Acc.	Unfair.	Acc.	Unfair.
LR	$.824 \pm .001$	$.074 \pm .002$	$.824 \pm .001$	$.074 \pm .002$
FC	$.805 \pm .013$	$.021 \pm .004$	$.807 \pm .013$	$.078 \pm .017$
RW+FC	$.810 \pm .004$	$.020 \pm .006$	$.810 \pm .008$	$.048 \pm .013$
Ours+FC	$.820 \pm .003$	$\mathbf{.005 \pm .002}$	$.805 \pm .014$	$\mathbf{.033 \pm .013}$
AD	$.777 \pm .022$	$\mathbf{.007 \pm .004}$	$.806 \pm .011$	$.052 \pm .004$
RW+AD	$.808 \pm .010$	$.025 \pm .007$	$.800 \pm .015$	$.035 \pm .003$
Ours+AD	$.803 \pm .009$	$\mathbf{.007 \pm .003}$	$.805 \pm .009$	$\mathbf{.033 \pm .003}$
FB	$.825 \pm .002$	$.017 \pm .001$	$.826 \pm .001$	$.049 \pm .001$
RW+FB	$.818 \pm .008$	$.020 \pm .005$	$.817 \pm .008$	$.071 \pm .010$
Ours+FB	$.824 \pm .001$	$\mathbf{.008 \pm .003}$	$.826 \pm .003$	$\mathbf{.037 \pm .012}$

B.3 OTHER EXPERIMENTAL SETTINGS

Continuing from Sec. 5, we provide more details on the experimental settings. The batch sizes of the synthetic, COMPAS, and AdultCensus datasets are 100, 200, and 2000, respectively. For the synthetic dataset, we use 2000 samples for the training dataset and 1000 samples for the test dataset. For the real datasets, we split the entire data into 4:1 for the training and test datasets. We set the learning rate to 0.0005. Our experiments are performed using PyTorch on a Linux server with Intel Xeon Silver 4210R CPUs and NVIDIA Quadro RTX 8000 GPUs.

We generate the synthetic training dataset with 2,000 samples and consists of two non-sensitive attributes (x_1, x_2), one sensitive attribute z, and one label attribute y. Each sample (x_1, x_2, y) is drawn from the following Gaussian distributions: $(x_1, x_2)|y = 0 \sim \mathcal{N}([-2; -2], [10, 1; 1, 3])$ and $(x_1, x_2)|y = 1 \sim \mathcal{N}([2; 2], [5, 1; 1, 5])$. For the sensitive attribute z, we generate a biased distribution: $\Pr(z = 1) = \Pr((x_1', x_2')|y = 1)/[\Pr((x_1', x_2')|y = 0) + \Pr((x_1', x_2')|y = 1)]$ where $(x_1', x_2') = (x_1 \cos(\pi/4) - x_2 \sin(\pi/4), x_1 \sin(\pi/4) + x_2 \cos(\pi/4))$.

When we construct the synthetic test dataset by modifying the z values while fixing the x and y distributions in the original test data, we change the k value in $(x_1', x_2') = (x_1 \cos(\pi/k) - x_2 \sin(\pi/k), x_1 \sin(\pi/k) + x_2 \cos(\pi/k))$.

To support multiple fairness metrics, we naturally extend each in-processing approach by combining the fairness constraints for different metrics via a tuning knob that adjusts the importance between each metric. Here, the fairness constraints are implemented differently in each algorithm. Fairness Constraints (FC) (Zafar et al., 2017a) adds each unfairness penalty term to the loss function. Thus, we extend FC by adding multiple penalty terms and adjust the importance between each penalty term by a tuning knob. Adversarial Debiasing (AD) (Zhang et al., 2018) utilizes a discriminator of each fairness metric for the adversarial training. Thus, we extend AD by adding multiple fairness discriminators and adjust the importance between each discriminator by adding a tuning knob in the classifier's loss function. FairBatch (FB) (Roh et al., 2021) solves a bilevel optimization that has an objective for minimizing a fairness disparity according to each fairness metric. Thus, we extend FB by minimizing the maximum of fairness disparities (e.g., $\max(DPdisp., EOdisp.)$) and adjust the importance between each disparity using a tuning knob.

B.4 ACCURACY AND FAIRNESS – ADULTCENSUS

Continuing from Sec. 5.1, we show the results on the AdultCensus dataset. Table 2 shows the accuracy and fairness performances of the algorithms on the AdultCensus test dataset w.r.t. a single metric (DP) and multiple metrics (DP & EO). Other setting are identical to Table 1. We observe consistent results where our framework improves accuracy and fairness of the in-processing-only baselines and also shows better fairness than the two-step baselines using RW.

Figure 5: Accuracy-fairness disparity trade-off curves of FB and Ours+FB on the synthetic data.

Table 3: Performances on the synthetic test dataset. The test dataset is constructed via modifying the z values of the original distribution. Other settings are identical to those in Table 1.

	Single (DP)		Multiple (DP & EO)	
Method	Acc.	Unfair.	Acc.	Unfair.
LR	$.871 \pm .000$	$.138 \pm .000$	$.871 \pm .000$	$.138 \pm .000$
FC	$.805 \pm .006$	$.040 \pm .005$	$.830 \pm .001$	$.119 \pm .003$
RW+FC	$.847 \pm .005$	$.047 \pm .007$	$.852 \pm .005$	$.053 \pm .004$
Ours+FC	$.831 \pm .003$	$\mathbf{.005 \pm .004}$	$.854 \pm .004$	$\mathbf{.052 \pm .002}$
AD	$.792 \pm .012$	$.048 \pm .009$	$.815 \pm .008$	$.133 \pm .006$
RW+AD	$.836 \pm .010$	$.042 \pm .008$	$.849 \pm .004$	$\mathbf{.054 \pm .004}$
Ours+AD	$.820 \pm .006$	$\mathbf{.005 \pm .003}$	$.847 \pm .002$	$.057 \pm .007$
FB	$.804 \pm .001$	$.051 \pm .002$	$.831 \pm .001$	$.128 \pm .002$
RW+FB	$.844 \pm .004$	$.036 \pm .003$	$.853 \pm .005$	$.057 \pm .011$
Ours+FB	$.824 \pm .002$	$\mathbf{.015 \pm .002}$	$.854 \pm .003$	$\mathbf{.054 \pm .003}$

B.5 ACCURACY AND FAIRNESS – TRADEOFF CURVES

Continuing from Sec. 5.1, we provide the accuracy-fairness disparity (DP) trade-off curves of FairBatch (FB) and Ours+FB on the the synthetic data in Figure 5. Our framework shows a better accuracy-fairness tradeoff compared to the in-processing approach (FB). FB shows an "inversed" curve, as it is trained with wrong biases in mind.

B.6 ACCURACY AND FAIRNESS – OTHER TEST DATA CONSTRUCTION: SYNTHETIC DATA

Continuing from Sec. 5.1, we compare the algorithm performances when using a different method to construct the test dataset of the synthetic-data experiment. Table 3 shows the accuracy and fairness performances on the synthetic dataset when constructing the test dataset by modifying z directly.

We again generate the synthetic dataset using a method similar to Zafar et al. (2017a). The synthetic dataset consists of two non-sensitive attributes (x_1, x_2), one sensitive attribute z, and one label attribute y. Each sample (x_1, x_2, y) is drawn from the following Gaussian distributions: $(x_1, x_2)|y = 0 \sim \mathcal{N}([-2; -2], [10, 1; 1, 3])$ and $(x_1, x_2)|y = 1 \sim \mathcal{N}([2; 2], [5, 1; 1, 5])$. For the sensitive attribute z, we generate a biased distribution: $\Pr(z = 1) = \Pr((x_1', x_2')|y = 1)/[\Pr((x_1', x_2')|y = 0) + \Pr((x_1', x_2')|y = 1)]$ where $(x_1', x_2') = (x_1 \cos(\pi/k) - x_2 \sin(\pi/k), x_1 \sin(\pi/k) + x_2 \cos(\pi/k))$. For the training dataset, we set k to 4. We then change the k value to generate the test dataset with 50% of the training data correlation.

As a result, we observe consistent results where our framework improves the accuracy and fairness performances of the in-processing-only baselines and generally shows better fairness than the two-step baselines using RW.

Table 4: Model performances on the ACSIncome test data (Ding et al., 2021) collected in the 2010s. The models are trained on the AdultCensus data (Kohavi, 1996) collected in the 1990s. Both datasets have labels that indicate each person's annual income.

	Single (DP)	
Method	Acc.	Unfair.
FC	$.646 \pm .013$	$.104 \pm .015$
Ours+FC	$.652 \pm .015$	$.090 \pm .017$
AD	$.637 \pm .031$	$.137 \pm .037$
Ours+AD	$.644 \pm .024$	$.060 \pm .039$
FB	$.643 \pm .007$	$.128 \pm .021$
Ours+FB	$.670 \pm .004$	$.098 \pm .002$

Figure 6: Performances of FB and Ours+FB on the synthetic data while varying the correlation of the test data c_{test} to have 10% to 70% correlation of the training data. We set the *specified* correlation range in our algorithm to $[\alpha, \beta] = [c_{\text{test}} - x\%, c_{\text{test}} + x\%]$, where $x \in \{10, 50, 100\}$.

B.7 Accuracy and Fairness – Other Test Data Construction: Real Data

Continuing from Sec. 5.1, we compare the algorithm performances when using a different method to construct the test dataset of the real-data experiment. Table 4 shows the accuracy and fairness performances when using the two income datasets collected in the 1990s (Kohavi, 1996) (i.e., AdultCensus dataset used in Sec. B.4) and 2010s (Ding et al., 2021) for training and testing, respectively. Here, the 1990s and 2010s datasets have the different (y, z)-correlation values 0.214 and 0.150, respectively. As a result, we observe consistent results where our framework improves the accuracy and fairness performances of the in-processing-only baselines.

B.8 Setting the Correlation Range to $c_{\text{TEST}} \pm x\%$

Continuing from Sec. 5.2, we evaluate our approach when $[\alpha, \beta] = [c_{\text{test}} - x\%, c_{\text{test}} + x\%]$. Figure 6 shows the accuracy and fairness performances of FB and Ours+FB, while varying the correlation constant c of the test data. Here, we set the *specified* correlation range in our algorithm to $[\alpha, \beta] = [c_{\text{test}} - x\%, c_{\text{test}} + x\%]$, where $x \in \{10, 50, 100\}$. When $x = 10\%$, we observe similar trends as in Figure 3a, where our framework improves the accuracy and fairness performances of the in-processing-only baselines. When $x = 100\%$ (i.e., the worst-case setting of $[\alpha, \beta]$), the accuracy and fairness performances of our framework converge to the in-processing-only baselines. When $x = 50\%$, the performances of our framework are in between those of when $x = 10\%$ and $x = 100\%$. There are two takeaways: 1) our framework successfully boosts the in-processing-only baseline performances when the $[\alpha, \beta]$ range is reasonable, and 2) even if we do not have any information about the correlation shift, our framework performs at least as well as the in-processing-only baselines.

B.9 Varying the Correlation of the Test Data: More Biases

Continuing from Sec. 5.2, we vary the correlation of the test data to have more biases than the training data. Figure 7 shows the accuracy and fairness performances of FB and Ours+FB, while varying the correlation constant c of the test data up to 150%. When the correlation increases more than 100% of that of the training data, the in-processing-only baseline (FB) cannot improve fairness because the training data does not capture the bias level in the test data. Hence, the in-processing-only baseline cannot be used in applications that require high fairness. On the other hand, our pre-processing

Figure 7: Performances of FB and Ours+FB on the synthetic data while varying the correlation of the test data to have 10% to 150% correlation of the training data.

enables the in-processing approach to achieve the high fairness that it may need, with some accuracy degradation.

B.10 USING THE OPTIONAL STEP

Continuing from Sec. 5.4, we show the results of when using the optional step using `MinDistChange` in Algorithm 1. This step finds possibly-different data sample weights within each (y, z)-class to minimize the overall distribution change between the training and pre-processed data. Figure 8 shows the Wasserstein distances between the original training data and pre-processed data when our algorithm uses either the basic or optional step, and the correlation constant c ranges from 10% to 70% of the training data's correlation. As a result, the optional step generally reduces the Wasserstein distance between the training and pre-processed data distributions, especially for smaller c values. In addition, Table 5 shows the performances on the synthetic test dataset when our algorithm uses either the basic step (Ours) or the optional step (Ours+Optional). As a result, when using the new data from the optional step as an input of the in-processing approaches, the final classifier's accuracy and fairness are not sacrificed much compared to using data from the basic step, while minimally changing the data distribution.

Figure 8: Wasserstein distances between the original training data and pre-processed data when our algorithm uses either the basic step or the optional step, while varying the target correlation to have 10% to 70% correlation of the training data.

Table 5: Performances on the synthetic test dataset. Other settings are identical to those in Table 1.

	Single (DP)	
Method	Acc.	Unfair.
Ours+FC	$.849 \pm .002$	$.034 \pm .004$
Ours+Optional+FC	$.830 \pm .003$	$.027 \pm .005$
Ours+AD	$.814 \pm .011$	$.017 \pm .006$
Ours+Optional+AD	$.808 \pm .007$	$.014 \pm .006$
Ours+FB	$.837 \pm .002$	$.003 \pm .002$
Ours+Optional+FB	$.842 \pm .002$	$.010 \pm .004$