Model-based Lifelong Reinforcement Learning with Bayesian Exploration

Abstract

We propose a model-based lifelong reinforcement-learning approach that estimates a hierarchical Bayesian posterior distilling the common structure shared across different tasks. The learned posterior combined with a sample-based Bayesian exploration procedure increases the sample efficiency of learning across a family of related tasks. We first derive an analysis of the relationship between the sample complexity and the initialization quality of the posterior in the finite MDP setting. We next scale the approach to continuous-state domains by introducing a Variational Bayesian Lifelong Reinforcement Learning algorithm that can be combined with recent model-based deep RL methods, and that exhibits backward transfer. Experimental results on several challenging domains show that our algorithms achieve both better forward and backward transfer performance than state-of-the-art lifelong RL methods.

1 Introduction

Reinforcement learning (RL) [42; 26] has been successfully applied to solve challenging individual tasks such as learning robotic control [11] and playing expert-level Go [38]. However, the typical RL setting assumes that the agent must solve exactly one task, which it has the opportunity to interact with repeatedly. In many real-world settings, an agent instead experiences a collection of distinct tasks that arrive sequentially throughout its operational lifetime; learning each new task from scratch is inefficient, but treating them all as a single task will fail. Therefore, recent research has focused on algorithms that enable agents to learn across multiple, sequentially posed tasks, leveraging knowledge from previous tasks to accelerate the learning of new tasks. This problem setting is known as *lifelong reinforcement learning* [7; 50; 25]. The key questions in lifelong RL research are: How can an algorithm exploit knowledge gained from past tasks to quickly adapt to new tasks (forward transfer), and how can data from new tasks help the agent perform better on previously learned tasks (backward transfer)?

We propose to address these problems by extracting the common structure existing in previously encountered tasks so that the agent can quickly learn the dynamics specific to the new tasks. We consider lifelong RL problems that can be modeled as hidden-parameter MDPs or *HiP-MDPs* [10; 27], where variations among the true task dynamics can be described by a set of hidden parameters. Our algorithm goes further than previous work in both lifelong learning and HiP-MDPs by **1)** Separately modeling epistemic and aleatory uncertainty over different levels of abstraction across the collection of tasks: the uncertainty captured by a world-model distribution describing the probability distribution over tasks, and the uncertainty captured by a task-specific model of the (stochastic) dynamics within a single task. To enable more accurate sequential knowledge transfer, we separate the learning process for these two quantities and maintain a hierarchical Bayesian posterior that approximates them. **2)**

Performing Bayesian exploration enabled by the hierarchical posterior: The method lets the agent act optimistically according to models sampled from the posterior, and thus increases sample efficiency.

Specifically, we propose a model-based lifelong RL approach with Bayesian exploration that estimates a Bayesian world-model posterior that distills the common structure of previous tasks, and then uses this between-task posterior as a within-task prior to learn a task-specific model in each subsequent task. The learned hierarchical posterior model combined with sample-based Bayesian exploration procedures can increase the sample efficiency of learning. We first derive an explicit performance bound that shows that the task-specific model requires fewer samples to become accurate as the world-model posterior approaches the true underlying world-model distribution for the discrete case. We further develop Variational Bayesian exploration for Lifelong RL (VBLRL), a more scalable version that uses variational inference to approximate the world-model distribution and leverages Bayesian Neural Networks (BNNs) to build the hierarchical Bayesian posterior. VBLRL provides a novel way to separately estimate different kinds of uncertainties in the HiP-MDP setting. Based on the same framework, we also propose a backward transfer version of VBLRL that is able to provide improvements for previously encountered tasks. Our experimental results on a set of challenging domains show that our algorithms achieve better both forward and backward transfer performance than state-of-the-art lifelong RL algorithms when given only limited interactions with each task.

2 Background

RL is the problem of maximizing the long-term expected reward of an agent interacting with an environment [42]. We usually model the environment as a Markov Decision Process or *MDP* [36], described by a five tuple: $\langle S, A, R, T, \gamma \rangle$, where S is a finite set of states; A is a finite set of actions; $R : S \times A \mapsto [0, 1]$ is a reward function, with a lower and upper bound of 0 and 1; $T : S \times A \mapsto \Pr(S)$ is a transition function, with $T(s'|s, a)$ denoting the probability of arriving in state $s' \in S$ after executing action $a \in A$ in state s; and $\gamma \in [0, 1)$ is a discount factor, expressing the agent's preference for delayed over immediate rewards.

An MDP is a suitable model for the task facing a single agent. In the lifelong RL setting, the agent instead faces a series of tasks $m_1, ..., m_n$, each of which can be modeled as an MDP: $\langle S^{(i)}, A^{(i)}, R^{(i)}, T^{(i)}, \gamma^{(i)} \rangle$. For lifelong RL problems, the performance of a specific algorithm is usually evaluated based on both forward transfer and backward transfer results [30]:

- *Forward transfer*: the influence that learning task t has on the performance in future task $k \succ t$.

- *Backward transfer*: the influence that learning task t has on the performance in earlier tasks $k \prec t$.

A key question in the lifelong setting is how the series of task MDPs are related; we model the collection of tasks as a HiP-MDP, where a family of tasks is generated by varying a latent task parameter ω drawn for each task according to the world-model distribution P_Ω. Each setting of ω specifies a unique MDP, but the agent neither observes ω nor has access to the function that generates the task family. The dynamics $T(s'|s, a; \omega_i)$ and reward function $R(r|s, a; \omega_i)$ for task i then depend on $\omega_i \in \Omega$, which is fixed for the duration of the task. The tasks are i.i.d. sampled from a fixed distribution and arrive one at a time. Similar settings are commonly used in other lifelong RL papers [31].

3 Related work

The first category of lifelong RL algorithms learns a single model that encourages transfer across tasks by modifying objective functions. EWC [28] imposes a quadratic penalty that pulls each weight back towards its old values by an amount proportional to its importance for performance on previously-learned tasks to avoid forgetting. There are several extensions of this work based on the core idea of modifying the form of the penalty [29; 53; 33]. Another category of lifelong RL methods uses multiple models with shared parameters and task-specific parameters to avoid or alleviate the catastrophic problem [5; 24; 31]. The drawback of this method is that it is hard to incorporate the knowledge learned from previous tasks during initial training on a new task [31]. Nagabandi et al. [32] introduce a model-based continual learning framework based on MAML, but they focus on discovering when new tasks were encountered without access to task indicators.

Published HiP-MDP methods use Gaussian Processes [10] or Bayesian neural networks [27] to find a single model that works for all tasks, which may trigger catastrophic forgetting [5; 24]. Meta-RL [47; 12] and multi-task RL [35; 43] settings also attempt to accelerate learning by transferring knowledge from different tasks. Some work employs the MAML framework with Bayesian methods to learn a stochastic distribution over initial parameters [51; 16; 13]. Other work uses the collected trajectories to infer the hidden parameter, which is taken as an additional input when computing the policy [37; 56; 14]. Our method, however, focuses on problems where the tasks arrive sequentially instead of having a large number of tasks available at the beginning of training. This sequential setting makes it hard to accurately infer the hidden parameters, but opens the door for algorithms that support backward transfer.

Some prior work uses Bayesian methods in RL to quantify uncertainty over initial MDP models [15; 1; 18]. Several algorithms start from the idea of sampling from a posterior over MDPs for Bayesian RL, maintaining Bayesian posteriors and sampling one complete MDP [41; 49] or multiple MDPs [2]. Instead of focusing on single-task RL, our algorithm aims to find a posterior over the common structure among multiple tasks. Wilson et al. [49] uses a hierarchical Bayesian infinite mixture model to learn a strong prior that allows the agent to rapidly infer the characteristics of a new environment based on previous tasks. However, it only infers the category label of a new MDP and only works in discrete settings.

4   Model-based Lifelong Reinforcement Learning

Our approach is built upon two main intuitions: First, transferring the transition model instead of policy/value function leads to more efficient usage of the data when "finetuning" on a new task. As we show empirically in Section 5.1, although some model-free lifelong RL algorithms perform better than the proposed model-based method in single-task cases, in lifelong RL setting of the same task type the model-based method is still able to achieve comparable/better performance with only half the amount of data. Secondly, with a model that is able to capture different levels of the uncertainty within HiP-MDPs, an agent can employ sample-based Bayesian exploration to further improve sample-efficiency.

The model underlying our approach is a hierarchical Bayesian posterior over task MDPs controlled by the hidden parameter ω. Intuitively, we maintain probability distributions that separately capture two categories of uncertainty within lifelong learning tasks: The *world-model posterior* $P(\omega)$ captures the epistemic uncertainty of the world-model distribution over all future and past tasks $m_1, \cdots, m_n$ controlled by the hidden parameter $\omega_1, \cdots, \omega_n \sim P_\Omega$. As the learner is exposed to more and more tasks, this posterior should converge to the world-model distribution P_Ω. The *task-specific posterior* $P(\omega_i)$ captures the epistemic uncertainty of the current task m_i (Throughout the paper we will often write i for simplicity.). As the learner is exposed to more and more transitions within the task, this posterior should approach the true distribution corresponding to ω_i, i.e. peaking at the true ω_i for this specific task i, leaving only the aleatoric uncertainty of transitions within the task, which is independent of other tasks. Each time the agent encounters a new task, we initialize the task-specific model using the world-model posterior and further train it with data collected only from the new task. One of our key insights here is that the sample complexity of learning a new task will decrease as the initial prior of task-specific model approaches the true underlying distribution of the transition function. Thus, the agent can learn new tasks faster by exploiting knowledge common to previous tasks, thereby exhibiting positive forward transfer.

Specifically, we model the task-specific posterior via the transition dynamics using $p(s^{t+1}, r^t | s^t, a^t; \omega_i)$. The task-specific posterior, given a new state–action pair from task i, can be rewritten via Bayes' rule:

$$P(\omega_i | D_i^t, a^t, s^{t+1}, r^t) = \frac{P(\omega_i | D_i^t) P(s^{t+1}, r^t | D_i^t, a^t; \omega_i)}{P(s^{t+1}, r^t | D_i^t, a^t)}, \tag{1}$$

where $D_i^t = \{s^1, a^1, \cdots, s^t\}$ is the agent's history of task i until time step t. The world-model posterior, given the new data from task i, can be rewritten as:

$$P(\omega | D_{1:i}) = \frac{P(\omega | D_{1:i-1}) P(D_i | D_{1:i-1}; \omega)}{P(D_i | D_{1:i-1})}, \tag{2}$$

where $D_{1:i}$ denotes the agent's history with all the experienced tasks $1 \sim i$ until current task i. In particular, each time when the agent faces a new task i and has not started updating its task specific

posterior yet (that is, $D_i^t = \varnothing$), we first use the world-model posterior to initialize the task-specific prior: $P(\omega_i|D_i^t) = P(\omega|D_{1:i})$. The world-model distribution aims to approximate the underlying P_Ω. The task-specific distribution aims to approximate the distribution that peaks at the true ω_i for this specific task i.

In Section 4.1, we derive a sample complexity bound in the finite MDP case which explicitly show how the distance between the distribution of a task's true transition model and our task-specific model's prior initialized by the parameters of the world-model posterior will affect the learning efficiency of a new task. Then, in Section 4.2 and 4.3 we extend our high-level idea to a scalable version that can be combined with recent model-based RL approaches and exhibits positive forward & backward transfer.

4.1 Sample Complexity Analysis

In this subsection, we consider the finite MDP setting and use a standard Bayesian exploration algorithm BOSS [2] as a single-task baseline. Note that BOSS creates optimism in the face of uncertainty as the agent can choose actions based on the highest performing transition of the K models sampled, which drives exploration. We included explanations of the finite MDP version of our algorithm BLRL (Bayesian Lifelong RL) based on BOSS in appendix C and simple experiments on Gridworlds in appendix K.

BLRL uses the world-model posterior $P(\omega|D_{1:i-1})$ learned from previous $i-1$ tasks to initialize (copy distribution) the task-specific prior of $P(\omega_i)$ of new task i, aiming to decrease the number of samples needed to learn an accurate task-specific posterior. Our analysis focuses on how the properties of the Bayesian prior affect the sample complexity of learning each specific task.

Let $\pi(\omega_i)$ denote the prior distribution on the parameter space Γ. We consider a set of transition-probability densities $p(\cdot|\omega_i) = p(s^{t+1}, r^t|s^t, a^t, \omega_i)$ indexed by ω_i, and the true underlying density q. We also denote the model family $\{p(\cdot|\omega_i) : \omega_i \in \Gamma\}$ by the same symbol Γ.

Lemma 4.1. *The task-specific posterior in Equation 1 can be regarded as the probability density $g(\omega_i)$ with respect to π that attains the infimum of:*

$$R_n(g) = \mathbb{E}_\pi g(\omega_i) \sum_{t=1}^{T} \ln \frac{q(s^{t+1}, r^t|D_i^t, a^t)}{p(s^{t+1}, r^t|D_i^t, a^t; \omega_i)} + D_{KL}(gd\pi||d\pi). \tag{3}$$

$\inf R_n(g)$ controls the complexity of the density estimation process for $g(\omega_i)$. Intuitively, Lemma 4.1 converts the Bayesian posterior into an information theoretical minimizer that allows us to further investigate the relationship between the properties of the Bayesian prior and the risk/complexity of attaining the posterior.

Proposition 4.2. *Define the **prior-mass radius** of the transition-probability densities as:*

$$d_\pi = \inf\{d : d \geq -\ln \pi(\{p \in \Gamma : D_{KL}(q||p) \leq d\})\}. \tag{4}$$

Intuitively, this quantity measures the distance between the Bayesian prior of the task-specific model and the true underlying task-specific distribution. Then, we adopt the same settings in Zhang [55]: $\forall \rho \in (0,1)$ and $\eta \geq 1$, let

$$\varepsilon_n = (1 + \frac{1}{n})\eta d_\pi + (\eta - \rho)\varepsilon_{upper,n}((\eta-1)/(\eta-\rho)), \tag{5}$$

*where $\varepsilon_{upper,n}$ is the **critical upper-bracketing radius** [55]. The decay rate of $\varepsilon_{upper,n}$ controls the consistency of the Bayesian posterior distribution [2]. Let $\rho = \frac{1}{2}$, we have for all states and actions, $h \geq 0$ and $\delta \in (0,1)$, with probability at least $1 - \delta$,*

$$\pi_n\Big(\Big\{p \in \Gamma : ||p - q||_1^2/2 \geq \frac{2\varepsilon_n + (4\eta - 2)h}{\delta/4}\Big\}\Big|X\Big) \leq \frac{1}{1 + e^{nh}}, \tag{6}$$

where $\pi_n(\omega_i)$ denotes the posterior distribution over ω after collecting n samples, X denotes the n collected samples. It functions the same as D_i^t in Equation 1.

Proof. See Appendix F. Instead of using the critical prior-mass radius $\varepsilon_{\pi,n}$ to describe certain characteristics of the Bayesian prior as in Corollary 5.2 of Zhang [55], we define and use the prior-mass radius d_π, which is independent of the sample size n and measures the distance between the prior and true distribution. $\qquad\square$

Similar to BOSS, for a new MDP $m^* \sim M$ with hidden parameters ω_{m^*}, we can define the Bayesian concentration sample complexity for the task-specific posterior: $f(s, a, \epsilon_0, \delta_0, \rho_0)$, as the minimum number u such that, if u IID transitions from (s, a) are observed, then, with probability at least $1 - \delta_0$,

$$Pr_{m \sim posterior}(||T(\cdot|s, a, \omega_m) - T(\cdot|s, a, \omega_{m^*})||_1 < \epsilon_0) \geq 1 - \rho_0. \tag{7}$$

Intuitively, the inequality means that for a model with the hidden parameter sampled from the learned posterior distribution, the probability that that it is within ϵ_0 far away from the true model is larger than $1 - \rho_0$.

Lemma 4.3. *Assume the posterior of each task is consistent (that is, $\varepsilon_{upper,n} = o(1)$) and set $\eta = 2$, then the Bayesian concentration sample complexity for the task-specific posterior $f(s, a, \epsilon, \delta, \rho) = O\left(\frac{d_\pi + \ln \frac{1}{\rho}}{\epsilon^2 \delta - d_\pi}\right)$.*

Proof (sketch). This bound can be derived by directly combining Lemma 4.2 and Equation 7. □

The above lemma suggests an upper bound of the Bayesian concentration sample complexity using the prior-mass radius. We can further combine this result with PAC-MDP theory [39] and derive the sample complexity of the algorithm for each new task.

Proposition 4.4. *For each new task, set the sample size $K = \Theta(\frac{S^2 A}{\delta} \ln \frac{SA}{\delta})$ and the parameters $\epsilon_0 = \epsilon(1 - \gamma)^2, \delta_0 = \frac{\delta}{SA}, \rho_0 = \frac{\delta}{S^2 A^2 K}$, then, with probability at least $1 - 4\delta$, $V^t(s^t) \geq V^*(s^t) - 4\epsilon_0$ in all but $\tilde{O}(\frac{S^2 A^2 d_\pi}{\delta \epsilon^3 (1-\gamma)^6})$ steps, where $\tilde{O}(\cdot)$ suppresses logarithmic dependence.*

Proof (sketch). The central part of the proof is Proposition 4.2 (detailed proof in appendix), and the remaining parts are exactly the same as those for BOSS. In general, the proof is based on the PAC-MDP theorem [40] combined with the new bound for the Bayesian concentration sample complexity we derived in Lemma 2. We use the same process in BOSS to verify the three required properties of PAC-MDP: optimism, accuracy, and learning complexity. For each new task, the main difference between BLRL and BOSS is that we use the world-model posterior to initialize the task-specific posterior, which results in a new sample complexity bound with d_π. □

The result formalizes how the sample complexity of the lifelong RL algorithm will change with respect to the initialization quality of the posterior: if we put a larger prior mass at a density close to the true q such that d_π is small, the sample efficiency of the algorithm will increase accordingly. In other words, the sample complexity of our algorithm drops proportionally to d_π, which is the distance between the Bayesian prior of the task-specific model initialized by the parameters of the world-model posterior and the true underlying task-specific distribution. We provide a illustrative example in the appendix N.

4.2 Variational Bayesian Lifelong RL

The intuition from the last section is that, if we initialize the task-specific distribution with a prior that is close to the true distribution, sample complexity will decrease accordingly. To scale our approach, we must find a efficient way to explicitly approximate these distributions. We propose a practical approximate algorithm, VBLRL, that uses neural networks and variational inference [21].

We choose Bayesian neural networks (BNN) to approximate the posterior. The intuition is that, in the context of stochastic outputs, BNNs naturally approximate the hierarchical Bayesian model since they also maintain a learnable distribution over their weights and biases [17; 23]. We use the uncertainty embedded in the weights and biases of networks to capture the epistemic uncertainty introduced by hidden parameters of different tasks, while we also set the outputs of the neural networks to be stochastic to capture the aleatory uncertainty within each specific task. In our case, the BNN weights and biases distribution $q(\omega; \phi)$ (a distribution over ω but parameterized by ϕ) can be modeled as fully factorized Gaussian distributions [3]:

$$q(\omega; \phi) = \prod_{j=1}^{|\Omega|} \mathcal{N}(\omega_j | \mu_j, \sigma_j^2), \tag{8}$$

where $\phi = \{\mu, \sigma\}$, and μ is the Gaussian's mean vector while σ is the covariance matrix diagonal.

We maintain a world-model BNN across all the tasks and a task-specific BNN for each task. The input for all the BNNs is a state–action pair, and the output are the mean and variance of the prediction for reward and next state. Then, the posterior distribution over the model parameters can be computed leveraging variational lower bounds [22; 23]:

$$\phi_t = \arg\min_{\phi} \left[D_{KL}[q(\omega;\phi)||p(\omega)] - \mathbb{E}_{\omega \sim q(\cdot;\phi)}[\log p(s^{t+1}, r^t|D^t, a^t; \omega)] \right], \tag{9}$$

where $p(\omega)$ represents the fixed prior distribution of ω, also recall that $D^t = \{s^1, a^1, r^1, \cdots, s^t\}$. In VBLRL, $p(\omega)$ for the task-specific distribution is initialized by the world-model distribution, while $p(\omega)$ of the world-model distribution is simply set to a Gaussian. (That could be improved with more informed task family knowledge.) The second term on the right hand side can be approximated through $\frac{1}{N}\sum_{i=1}^{N}\log p(s^{t+1}, r^t|D^t, a^t; \omega_i)$ with N samples from $\omega_i \sim q(\phi)$. This optimization can be performed in parallel for each s, keeping ϕ_{t-1} fixed. Details about our BNN structure can be found in appendix B.

Once we have the world-model as well as the task-specific posterior model, we can do posterior sampling to drive Bayesian exploration. Osband et al. [34] and Rakelly et al. [37] already show the benefit of posterior sampling for improving sample efficiency in single-task RL and meta-RL settings. Here, instead of sampling from the posterior of value functions or latent context representations, we directly sample from the posterior of the transition model and choose the optimal action based on the transition samples. Then we use the collected samples to update the posterior and do sampling again. The agent thus continually do Bayesian exploration and acts more and more optimally as the posterior distribution narrows.

We provide the framework of VBLRL in Figure 8. We employ our posterior knowledge models in the context of a model-based RL method. When encountering a new task, VBLRL first uses the model parameters (that is, $\{\mu, \sigma\}$ of weights and biases of BNN) from the general knowledge model to initialize the task-specific posterior network (directly copy parameters). We sample transitions from the task-specific posterior and select actions based on the generated transitions. The detailed algorithm is summarized in Algorithm 1. Specifically, for planning, at each step we begin by creating P particles from the current state $s_{\tau=t}^p = s_t \forall p$. Then, we sample N candidate action sequences $a_{t:t+T}$ from a learnable distribution. These two steps are the same as PETS [8]. Then we propagate the state–action pairs using the learned task-specific model $p_{m_i}(\cdot|s, a)$ (BNN) and use the cross entropy method [4] to update the sam-

Figure 1: Variational Bayesian Lifelong RL (VBLRL). "NN" is the network using fixed parameters sampled from the weight distribution of the task-specific BNN. When the agent does CEM planning, we let it propagate the state particles using several NNs that use different network parameters, all sampled from the BNN to achieve randomness in transitions.

pling distribution to make the sampled action sequences close to previous action sequences that achieved high reward. We further calculate the cumulative reward estimated (via the learned model) for previously sampled sequences and select the current action based on the mean of that distribution. By sampling from the task-specific posterior at each step, the agent explores in a temporally extended and diverse manner.

For each specific task, we use the task-specific BNN to plan during forward learning. They are updated with only the data from the current task thus avoid catastrophic forgetting in the forward transfer process. The world model is updated using the data from **all** the visited tasks. The intuition is to guide the two posteriors to separately learn two categories of uncertainty within lifelong learning tasks. The world-model posterior captures the epistemic uncertainty of the general knowledge distribution (shared across all tasks controlled by the hidden parameters) via the internal variance of world-model BNN. As the learner is exposed to more and more tasks, the posterior should converge to P_Ω. The task-specific posterior captures the epistemic uncertainty of the current task m_i, which comes from the aleatory uncertainty of the world model when generating ω_i for a new task, via the internal variance of task-specific BNN. We provide additional illustration in Appendix J. In general,

we used the world-model BNN to encode P_Ω over a family of tasks, and the task-specific BNN to encode $P(\omega_i)$, which should peak at the specific true ω_i sampled for the current task.

Note that in single-task cases, other CEM-based algorithms like PETS usually maintain a set of neural networks using the same training data, and sample action sequences from each of the neural nets to achieve randomness in transitions. However, in lifelong RL settings, it is unrealistic to maintain (≥ 30) models for each task encountered. Our usage of BNNs avoids such problems as we only have to train one neural network using the same data for each task, and we can sample an unlimited number of different action sequences to cover more possibilities as needed. In PETS, the epistemic uncertainty is estimated via the variance of the output mean of different neural networks, while, in VBLRL, it is estimated via the variance of the weights and biases distribution of the BNN.

4.3 Backward Transfer of Variational Bayesian Lifelong RL

In our lifelong RL setting, the agent interacts with each task for only a limited number of episodes and the task-specific model stops learning when the next task is initiated. As a result, there may exist portions of the transition dynamics in which model uncertainty remains high. However, as the world-model posterior continues to train on new tasks, it gathers more experience in the whole state space and can provide improved guesses concerning the "unknown" transition dynamics, even for previously encountered tasks.

Intuitively, the performance of an agent on one task has the potential to be further improved (positive backward transfer) if there exists a sufficiently large set of state–action transition pairs of which the task-specific model's predictions are not confident due to lack of data. In our algorithm, the aleatory uncertainty (irreducible chance in the outcome) is measured by the output variance of the prediction $\{\sigma_{r_\tau^p}, \sigma_{s_\tau^p}\}$, and the epistemic uncertainty (due to lack of experience) corresponds to the uncertainty of the output mean and variance (see Definition 1 below). Thus, a straightforward method to improve a previously learned task-specific model is to find the predictions it needs to make that have high epistemic uncertainty, and replace them with the predictions from the world-model posterior, which has lower epistemic uncertainty. If we only consider reward prediction, the quantity for measuring whether a task-specific/world model is sufficiently confident is as follows.

Definition 4.5. For a given state–action pair (s, a), we define the confidence level c of the predictions (reward) $r_\tau^p(s, a)$ from a task-specific/world model as:

$$c = -\frac{\sum_{p=1}^{P}(\mu_{r_\tau^p} - \overline{\mu}_{r_\tau^p})^2}{P-1} - \alpha * \frac{\sum_{p=1}^{P}(\sigma_{r_\tau^p} - \overline{\sigma}_{r_\tau^p})^2}{P-1}, \tag{10}$$

where P is the number of particles and α is a hyperparameter controlling the scale of the second term. A similar definition applies to the task-specific/world model's next-state prediction. Intuitively, c measures the uncertainty of the output mean and variance for each dynamic prediction. During CEM planning, we propagate each pair of P state particles with different network parameters thanks to the usage of BNN, resulting in P different $\{\mu_{r_\tau^p}, \sigma_{r_\tau^p}\}$. Thus we can further calculate the confidence level of current predictions based on these P pairs of output mean and variance.

We show the detailed backward transfer algorithm in Algorithm 2. Compared with the forward training version, the agent will also calculate the confidence level of the task-specific and general-knowledge model for each particular transition and compare the value of them when predicting the state particles. If the task-specific model is not confident enough for this state–action pair (i.e. $c_{m_i} < c_{wm}$), we will use the world-model to do the predictions instead.

5 Experiments

5.1 OpenAI Gym MuJoCo Domains

We evaluated the performance of VBLRL on HiP-MDP versions of several continuous control tasks from the Mujoco physics simulator [45], *HalfCheetah-gravity, HalfCheetah-bodyparts, Hopper-gravity, Hopper-bodyparts, Walker-gravity, Walker-bodyparts*, all of which are lifelong-RL benchmarks used in prior work [31]. For each of six different domains, the task-specific hidden parameters correspond to different gravity values or different sizes and masses of the simulated body parts. Details can be found in the appendix. Compared with prior work, we substantially reduced the

number of iterations that the agent can sample and train on: 100 iterations for each task and a horizon
of 100 (Halfcheetah) or 400 (Hopper & Walker) for each iteration. We used such settings to increase
the difficulty of lifelong learning and test the sample efficiency of lifelong RL algorithms, given that
it is hard for a single-task training algorithm to obtain a good policy within such limited number of
interactions with the environments. However, we show in appendix H and I that, as the agent is
exposed to more and more tasks, our lifelong learning agent is able to achieve similar performance to
that of more fully trained single-task agents while requiring far fewer per-task samples.

	VBLRL	T-HiP-MDP	LPG-FTW (2× samples)	EWC (2× samples)	Single-task MBRL
CG-Start	**160.68 ± 48.80**	126.95 ± 31.41	−81.59 ± 9.18	−3426.76 ± 827.99	−83.96 ± 60.10
CG-Train	**226.72 ± 26.53**	170.20 ± 39.92	−29.49 ± 11.03	−3440.66 ± 1007.50	−40.47 ± 10.68
CG-Back	**231.79 ± 23.49**	97.84 ± 22.04	−29.95 ± 11.64	−6672.33 ± 3748.63	/
CB-Start	**110.74 ± 41.96**	78.95 ± 18.43	−263.94 ± 40.80	−5016.93 ± 1708.10	−101.02 ± 39.11
CB-Train	**173.97 ± 78.26**	87.20 ± 9.42	−217.86 ± 42.82	−5454.52 ± 2145.82	−58.93 ± 33.24
CB-Back	**181.60 ± 67.50**	116.03 ± 17.35	−116.41 ± 65.64	−13889.31 ± 6851.05	/
HG-Start	268.11 ± 33.29	230.21 ± 30.75	305.63 ± 34.55	**306.79 ± 29.14**	18.62 ± 1.51
HG-Train	332.89 ± 23.68	285.87 ± 41.48	**352.10 ± 25.25**	345.47 ± 40.26	20.46 ± 1.77
HG-Back	**360.94 ± 7.71**	312.11 ± 55.45	347.07 ± 44.09	301.06 ± 114.11	/
HB-Start	193.27 ± 8.03	181.94 ± 12.97	**256.13 ± 69.68**	133.95 ± 27.61	19.12 ± 1.75
HB-Train	**296.34 ± 11.15**	227.50 ± 41.78	285.62 ± 78.18	139.01 ± 46.24	21.25 ± 2.67
HB-Back	**316.74 ± 20.72**	213.93 ± 75.95	281.99 ± 74.96	−384.27 ± 199.27	/
WG-Start	**248.97 ± 19.95**	217.94 ± 39.99	140.75 ± 67.64	163.61 ± 86.55	4.32 ± 0.23
WG-Train	**333.65 ± 26.73**	268.97 ± 36.26	166.00 ± 45.04	181.76 ± 97.42	210.41 ± 39.34
WG-Back	**364.18 ± 49.60**	173.33 ± 58.43	168.39 ± 94.19	216.09 ± 62.67	/
WB-Start	**222.88 ± 34.49**	220.07 ± 20.31	164.79 ± 10.31	164.00 ± 34.31	4.64 ± 0.23
WB-Train	**311.41 ± 16.30**	266.97 ± 26.72	165.75 ± 2.39	206.97 ± 41.40	196.42 ± 22.04
WB-Back	**317.82 ± 13.90**	229.10 ± 16.60	195.01 ± 49.25	152.94 ± 70.59	/

Table 1: Results on OpenAI Gym Mujoco domains. *CG* denotes **Cheetah-Gravity**, *CB* denotes
Cheetah-Bodyparts, *HG* denotes **Hopper-Gravity**, *HB* denotes **Hopper-Bodyparts**, *WG* denotes
Walker-Gravity, *WB* denotes **Walker-Bodyparts**.

We compared VBLRL against state-of-the-art lifelong RL methods LPG-FTW [31], EWC [28],
single-task model-based RL baseline (using the same BNN structure and planning procedures) as
well as T-HiP-MDP [27]. For a fair comparison, we further replaced the DDQN algorithm [46] used
in Killian et al.'s paper with CEM planning, and let the transition model also predict the reward for
each state–action pair. This modified baseline is similar to the single-model version of VBLRL (i.e.,
only using the world-model posterior). Moreover, LPG-FTW and EWC are built upon a relatively
simple policy gradient baseline, which does not perform as well as our model-based baseline in
the single-task setting within the same amount of interactions. Thus, we let them collect **twice the
amount of samples** each iteration compared to VBLRL. We show in Appendix H that, with such
modifications, in single-task settings the baselines achieve better or at least similar performance
compared to the single-task version of VBLRL.

The results are shown in Table 1 and Figure 7 in Appendix I. For all six domains, we report the
average performance of all the tasks at the beginning of training (**Start**) and after all training for
each new task (**Train**), as well as the average performance for all previous tasks after training for
a given number of tasks, which is our backward transfer test (**Back**). As shown in the results, our
VBLRL shows better performance on all three test stages of the HalfCheetah domain and Walker
domain, as well as better backward transfer performance on Hopper-gravity and Hopper-bodyparts
than the other three algorithms. Comparing Figure 6 and Figure 7, we find that, in the Hopper
domains, even though the single-task baseline used by LPG-FTW and EWC performed much better
than VBLRL after we let them collect **2×** samples each iteration, VBLRL still achieves comparable
performance with LPG-FTW and EWC in lifelong RL experiments, suggesting that VBLRL is
capable of making better use of the data in the lifelong learning setting. In the walker domains
where the single-task baselines achieved similar performance, VBLRL shows significantly better
performance than LPG-FTW/EWC in lifelong RL experiments. These comparisons also suggest
that VBLRL's lifelong learning performance may be further improved when combined with better
model-based deep RL algorithms, like Dreamer [20]. EWC fails in some of the tasks as it is hard to
directly learn a single shared policy that achieves good performance when the tasks are highly diverse.
T-HiP-MDP shows good results on some of the tasks because it is more sample-efficient in learning a
shared model across all the tasks and more easily captures the world-model uncertainty. However, it
cannot achieve as good performance as VBLRL as it is hard to model the task-specific uncertainty
using only one model across all tasks, which also leads to negative backward transfer performance on
tasks like Cheetah-Gravity. Comparing VBLRL's performance on the **Train** stage and **Back** stage,
we also find that it shows positive backward transfer results on most tasks, without showing patterns

of catastrophic forgetting. Overall, VBLRL's world-model posterior contributes to better forward transfer performance (**Start**), the learning of task-specific posterior contributes to better forward transfer training for each new task (**Train**), and the combination of these two posteriors guides the agent to achieve better backward transfer performance (**Back**).

5.2 Meta-world Domains

Meta-World [52] contains a suite of challenging evaluation benchmarks on a robotic SAWYER arm. We evaluated the performance of VBLRL as well as the baselines on two Meta-World task sets: Reach and Reach-Wall following the settings given by [54]. We used the v1 version of Meta-World, with state observations and dense versions of the reward functions. The hidden parameters in these cases are the goals we want the robot to reach, which controls the reward functions and are not included in the agent's observation space. We measured performance in terms of average cumulative rewards across tasks. As shown in Figure 2, VBLRL achieves

Figure 2: Average performance during training across all tasks. Left: Reach; Right: Reach-Wall.

significantly higher performance than the other baselines. VBLRL-Backward denotes VBLRL's average backward transfer performance on all the tasks and is higher than the final performance of VBLRL's forward training in both tasks, suggesting that our approach can achieve positive backward transfer. More experimental results can be found in our appendix.

5.3 Ablation Study

This section evaluates the essentiality of VBLRL's components. As shown in Figure 3 left, we tested different backward transfer strategy for VBLRL. Task-specific-Backward denotes the performance if directly using the learned task-specific model to do all the predictions without using world model. World-model-Backward denotes the performance if using world-model to do all the predictions without using each task-specific model. Compared to these baselines, VBLRL's backward transfer strategy achieves the best performance by combining these two kinds of models according to their confidence level. We also explored the in-

Figure 3: Ablation Study on Reach domain. Left: Backward transfer strategy; Right: Using Bayesian neural networks to model the task-specific posterior.

fluence of using a Bayesian neural network to model the task-specific model. As shown in the right side of the figure, using BNN enables faster adaptation to new tasks compared with using regular neural networks (VBLRL-Deterministic).

6 Conclusion

To improve sample efficiency in lifelong RL, our work proposed a model-based lifelong RL approach that distills shared knowledge from similar MDPs and maintains a Bayesian posterior to approximate the distribution derived from that knowledge. We gave a sample-complexity analysis of the algorithm in the finite MDP setting. Then, we extended our method to use variational inference, which scales better and supports backward and forward transfer. Our experimental results show that the proposed algorithms enable faster training on new tasks through collecting and transferring the knowledge learned from preceding tasks.

References

[1] Asmuth, J. and Littman, M. Learning is planning: Near Bayes-optimal reinforcement learning via Monte-Carlo tree search. In *UAI*, 2011.

[2] Asmuth, J., Li, L., Littman, M. L., Nouri, A., and Wingate, D. A Bayesian sampling approach to exploration in reinforcement learning. In *UAI 2009, Proceedings of the Twenty-Fifth Conference on Uncertainty in Artificial Intelligence, 2009*, pp. 19–26. AUAI Press, 2009.

[3] Blundell, C., Cornebise, J., Kavukcuoglu, K., and Wierstra, D. Weight uncertainty in neural networks. *CoRR*, abs/1505.05424, 2015.

[4] Botev, Z., Kroese, D. P., Rubinstein, R., and L'Ecuyer, P. Chapter 3 – the cross-entropy method for optimization. *Handbook of Statistics*, 31:35–59, 2013.

[5] Bou-Ammar, H., Eaton, E., Ruvolo, P., and Taylor, M. E. Online multi-task learning for policy gradient methods. In *ICML*, 2014.

[6] Brafman, R. I. and Tennenholtz, M. R-max - a general polynomial time algorithm for near-optimal reinforcement learning. 3(null), 2003. ISSN 1532-4435.

[7] Brunskill, E. and Li, L. Pac-inspired option discovery in lifelong reinforcement learning. In *ICML*, 2014.

[8] Chua, K., Calandra, R., McAllister, R., and Levine, S. Deep reinforcement learning in a handful of trials using probabilistic dynamics models. In *Advances in Neural Information Processing Systems 31: Annual Conference on Neural Information Processing Systems 2018, NeurIPS 2018*, pp. 4759–4770, 2018.

[9] des Combes, R. T., Bachman, P., and van Seijen, H. Learning invariances for policy generalization. In *6th International Conference on Learning Representations, ICLR 2018*. OpenReview.net, 2018.

[10] Doshi-Velez, F. and Konidaris, G. D. Hidden parameter markov decision processes: A semi-parametric regression approach for discovering latent task parametrizations. In *Proceedings of the Twenty-Fifth International Joint Conference on Artificial Intelligence, IJCAI 2016*, pp. 1432–1440. IJCAI/AAAI Press, 2016.

[11] Duan, Y., Chen, X., Houthooft, R., Schulman, J., and Abbeel, P. Benchmarking deep reinforcement learning for continuous control. In *ICML*, 2016.

[12] Finn, C., Abbeel, P., and Levine, S. Model-agnostic meta-learning for fast adaptation of deep networks. In *ICML*, 2017.

[13] Finn, C., Xu, K., and Levine, S. Probabilistic model-agnostic meta-learning. In *Advances in Neural Information Processing Systems 31: Annual Conference on Neural Information Processing Systems 2018, NeurIPS 2018*, pp. 9537–9548, 2018.

[14] Fu, H., Tang, H., Hao, J., Chen, C., Feng, X., Li, D., and Liu, W. Towards effective context for meta-reinforcement learning: an approach based on contrastive learning. In *Thirty-Fifth AAAI Conference on Artificial Intelligence, AAAI 2021*, pp. 7457–7465. AAAI Press, 2021.

[15] Ghavamzadeh, M., Mannor, S., Pineau, J., and Tamar, A. Convex optimization: Algorithms and complexity. *Foundations and Trends® in Machine Learning*, 8(5-6):359–483, 2015. ISSN 1935-8245.

[16] Grant, E., Finn, C., Levine, S., Darrell, T., and Griffiths, T. L. Recasting gradient-based meta-learning as hierarchical bayes. In *6th International Conference on Learning Representations, ICLR 2018*. OpenReview.net, 2018.

[17] Graves, A. Practical variational inference for neural networks. In *Advances in Neural Information Processing Systems 24: 25th Annual Conference on Neural Information Processing Systems 2011*, pp. 2348–2356, 2011.

[18] Guez, A., Silver, D., and Dayan, P. Efficient bayes-adaptive reinforcement learning using sample-based search. In *NIPS*, 2012.

[19] Haarnoja, T., Zhou, A., Abbeel, P., and Levine, S. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *Proceedings of the 35th International Conference on Machine Learning, ICML 2018*, pp. 1856–1865. PMLR, 2018.

[20] Hafner, D., Lillicrap, T. P., Ba, J., and Norouzi, M. Dream to control: Learning behaviors by latent imagination. *ArXiv*, abs/1912.01603, 2020.

[21] Hinton, G. E. and van Camp, D. Keeping the neural networks simple by minimizing the description length of the weights. In *Proceedings of the Sixth Annual ACM Conference on Computational Learning Theory, COLT 1993*, pp. 5–13. ACM, 1993.

[22] Hinton, G. E. and van Camp, D. Keeping the neural networks simple by minimizing the description length of the weights. In *COLT '93*, 1993.

[23] Houthooft, R., Chen, X., Duan, Y., Schulman, J., Turck, F. D., and Abbeel, P. VIME: variational information maximizing exploration. In *Advances in Neural Information Processing Systems 29: Annual Conference on Neural Information Processing Systems 2016*, pp. 1109–1117, 2016.

[24] Isele, D., Rostami, M., and Eaton, E. Using task features for zero-shot knowledge transfer in lifelong learning. In *Proceedings of the Twenty-Fifth International Joint Conference on Artificial Intelligence, IJCAI 2016*, pp. 1620–1626. IJCAI/AAAI Press, 2016.

[25] Isele, D., Rostami, M., and Eaton, E. Using task features for zero-shot knowledge transfer in lifelong learning. In *IJCAI*, 2016.

[26] Kaelbling, L. P., Littman, M. L., and Moore, A. W. Reinforcement learning: A survey. *J. Artif. Intell. Res.*, 4:237–285, 1996.

[27] Killian, T. W., Daulton, S., Doshi-Velez, F., and Konidaris, G. D. Robust and efficient transfer learning with hidden parameter markov decision processes. In *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017*, pp. 6250–6261, 2017.

[28] Kirkpatrick, J., Pascanu, R., Rabinowitz, N. C., Veness, J., Desjardins, G., Rusu, A. A., Milan, K., Quan, J., Ramalho, T., Grabska-Barwinska, A., Hassabis, D., Clopath, C., Kumaran, D., and Hadsell, R. Overcoming catastrophic forgetting in neural networks. *CoRR*, abs/1612.00796, 2016.

[29] Li, Z. and Hoiem, D. Learning without forgetting, 2017.

[30] Lopez-Paz, D. and Ranzato, M. Gradient episodic memory for continual learning. In *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017*, pp. 6467–6476, 2017.

[31] Mendez, J. A. M., Wang, B., and Eaton, E. Lifelong policy gradient learning of factored policies for faster training without forgetting. *ArXiv*, abs/2007.07011, 2020.

[32] Nagabandi, A., Finn, C., and Levine, S. Deep online learning via meta-learning: Continual adaptation for model-based rl. *ArXiv*, abs/1812.07671, 2019.

[33] Nguyen, C. V., Li, Y., Bui, T. D., and Turner, R. E. Variational continual learning, 2018.

[34] Osband, I., Blundell, C., Pritzel, A., and Roy, B. V. Deep exploration via bootstrapped dqn. In *NIPS*, 2016.

[35] Parisotto, E., Ba, L. J., and Salakhutdinov, R. Actor-mimic: Deep multitask and transfer reinforcement learning. In *4th International Conference on Learning Representations, ICLR 2016*, 2016.

[36] Puterman, M. L. *Markov Decision Processes—Discrete Stochastic Dynamic Programming*. John Wiley & Sons, Inc., 1994.

[37] Rakelly, K., Zhou, A., Finn, C., Levine, S., and Quillen, D. Efficient off-policy meta-reinforcement learning via probabilistic context variables. In *Proceedings of the 36th International Conference on Machine Learning, ICML 2019*, volume 97 of *Proceedings of Machine Learning Research*, pp. 5331–5340. PMLR, 2019.

[38] Silver, D., Schrittwieser, J., Simonyan, K., Antonoglou, I., Huang, A., Guez, A., Hubert, T., baker, L., Lai, M., Bolton, A., Chen, Y., Lillicrap, T., Hui, F., Sifre, L., Driessche, G. V. D., Graepel, T., and Hassabis, D. Mastering the game of go without human knowledge. *Nature*, 550:354–359, 2017.

[39] Strehl, A., Li, L., and Littman, M. Incremental model-based learners with formal learning-time guarantees. *ArXiv*, abs/1206.6870, 2006.

[40] Strehl, A. L., Li, L., and Littman, M. L. Reinforcement learning in finite mdps: Pac analysis. *J. Mach. Learn. Res.*, 10:2413–2444, 2009.

[41] Strens, M. J. A. A Bayesian framework for reinforcement learning. In *Proceedings of the Seventeenth International Conference on Machine Learning (ICML 2000)*, pp. 943–950, 2000.

[42] Sutton, R. S. and Barto, A. G. *Reinforcement Learning: An Introduction*. The MIT Press, 1998.

[43] Teh, Y. W., Bapst, V., Czarnecki, W. M., Quan, J., Kirkpatrick, J., Hadsell, R., Heess, N., and Pascanu, R. Distral: Robust multitask reinforcement learning. In *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017*, pp. 4496–4506, 2017.

[44] Thompson, W. R. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25:285–294, 1933.

[45] Todorov, E., Erez, T., and Tassa, Y. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems, IROS 2012*, pp. 5026–5033. IEEE, 2012.

[46] van Hasselt, H., Guez, A., and Silver, D. Deep reinforcement learning with double q-learning. In *Proceedings of the Thirtieth AAAI Conference on Artificial Intelligence,2016*, pp. 2094–2100. AAAI Press, 2016.

[47] Wang, J. X., Kurth-Nelson, Z., Tirumala, D., Soyer, H., Leibo, J. Z., Munos, R., Blundell, C., Kumaran, D., and Botvinick, M. Learning to reinforcement learn. *CoRR*, abs/1611.05763, 2016.

[48] Wang, T., Bao, X., Clavera, I., Hoang, J., Wen, Y., Langlois, E., Zhang, S., Zhang, G., Abbeel, P., and Ba, J. Benchmarking model-based reinforcement learning. *CoRR*, abs/1907.02057, 2019.

[49] Wilson, A., Fern, A., Ray, S., and Tadepalli, P. Multi-task reinforcement learning: A hierarchical Bayesian approach. In *Machine Learning, Proceedings of the Twenty-Fourth International Conference (ICML 2007), 2007*, volume 227 of *ACM International Conference Proceeding Series*, pp. 1015–1022. ACM, 2007.

[50] Wilson, A., Fern, A., Ray, S., and Tadepalli, P. Multi-task reinforcement learning: a hierarchical bayesian approach. In *ICML '07*, 2007.

[51] Yoon, J., Kim, T., Dia, O., Kim, S., Bengio, Y., and Ahn, S. Bayesian model-agnostic meta-learning. In *Advances in Neural Information Processing Systems 31: Annual Conference on Neural Information Processing Systems 2018, NeurIPS 2018*, pp. 7343–7353, 2018.

[52] Yu, T., Quillen, D., He, Z., Julian, R. C., Hausman, K., Finn, C., and Levine, S. Meta-world: A benchmark and evaluation for multi-task and meta reinforcement learning. *ArXiv*, abs/1910.10897, 2019.

[53] Zenke, F., Poole, B., and Ganguli, S. Continual learning through synaptic intelligence, 2017.

[54] Zhang, J., Wang, J., Hu, H., Chen, T., Chen, Y., Fan, C., and Zhang, C. Metacure: Meta reinforcement learning with empowerment-driven exploration. In *ICML*, 2021.

[55] Zhang, T. From -entropy to kl-entropy: Analysis of minimum information complexity density estimation. *Annals of Statistics*, 34:2180–2210, 2006.

[56] Zintgraf, L. M., Shiarlis, K., Igl, M., Schulze, S., Gal, Y., Hofmann, K., and Whiteson, S. Varibad: A very good method for bayes-adaptive deep RL via meta-learning. In *8th International Conference on Learning Representations, ICLR 2020*. OpenReview.net, 2020.