NEURAL ENSEMBLE SEARCH
FOR UNCERTAINTY ESTIMATION AND DATASET SHIFT

ABSTRACT

Ensembles of neural networks achieve superior performance compared to stand-alone networks not only in terms of predictive performance, but also uncertainty calibration and robustness to dataset shift. Diversity among networks is believed to be key for building strong ensembles, but typical approaches, such as *deep ensembles*, only ensemble different weight vectors of a fixed architecture. Instead, we propose two methods for constructing ensembles to exploit diversity among networks with *varying* architectures. We find the resulting ensembles are indeed more diverse and also exhibit better uncertainty calibration, predictive performance and robustness to dataset shift in comparison with deep ensembles on a variety of classification tasks.

1 INTRODUCTION

Automatically learning useful representations of data using deep neural networks has been successful across various tasks (Krizhevsky et al., 2012; Hinton et al., 2012; Mikolov et al., 2013). While some applications rely only on the predictions made by a neural network, many critical applications also require reliable predictive uncertainty estimates and robustness under the presence of dataset shift, that is, when the observed data distribution at deployment differs from the training data distribution. Examples include medical imaging (Esteva et al., 2017) and self-driving cars (Bojarski et al., 2016). However, several studies have shown that neural networks are not always robust to dataset shift (Ovadia et al., 2019; Hendrycks & Dietterich, 2019), nor do they exhibit calibrated predictive uncertainty, resulting in incorrect predictions made with high confidence (Guo et al., 2017).

Using an ensemble of networks rather than a stand-alone network improves both predictive uncertainty calibration and robustness to dataset shift. Ensembles also outperform approximate Bayesian methods (Lakshminarayanan et al., 2017; Ovadia et al., 2019; Gustafsson et al., 2020). Their success is usually attributed to the diversity among the base learners, however there are various definitions of diversity (Kuncheva & Whitaker, 2003; Zhou, 2012) without a consensus. In practice, ensembles are usually constructed by choosing a *fixed* state-of-the-art architecture and creating base learners by independently training random initializations of it. This is referred to as *deep ensembles* (Lakshminarayanan et al., 2017), a state-of-the-art method for uncertainty estimation.

However, as we show, base learners with varying network architectures make more diverse predictions. Therefore, picking a strong, fixed architecture for the ensemble's base learners neglects diversity in favor of base learner strength. This has implications for the ensemble performance, since both diversity and base learner strength are important. To overcome this, we propose *Neural Ensemble Search* (NES); a NES algorithm finds a set of diverse neural architectures that together form a strong ensemble. Note that, *a priori*, it is not obvious how to find diverse architectures that work well as an ensemble; one cannot randomly select them, since it is important to select strong ones, nor can one optimize them individually as that ignores diversity. By directly optimizing ensemble loss while maintaining independent training of base learners, a NES algorithm implicitly encourages diversity, without the need for explicitly defining diversity. In detail, our contributions are as follows:

1. We show that ensembles composed of varying architectures perform better than ensembles composed of a fixed architecture. We demonstrate that this is due to increased diversity among the ensemble's base learners (Sections 3 and 5).

2. Based on these findings and the importance of diversity, we propose two algorithms for Neural Ensemble Search: NES-RS and NES-RE. NES-RS is a simple random search based algorithm, and NES-RE is based on regularized evolution (Real et al., 2019). Both search algorithms seek performant ensembles with varying base learner architectures (Section 4).

3. With experiments on classification tasks, we evaluate the ensembles found by NES-RS and NES-RE from the point of view of both predictive performance and uncertainty calibration, comparing them to deep ensembles with fixed, optimized architectures. We find our ensembles outperform deep ensembles not only on in-distribution data but also during dataset shift (Section 5). The code for our experiments is available at: `https://anonymousfiles.io/ZaY1ccR5/`.

2   RELATED WORK

Ensemble Learning and Uncertainty Estimation.   Ensembles of neural networks (Hansen & Salamon, 1990; Krogh & Vedelsby, 1995; Dietterich, 2000) are commonly used to boost performance (Szegedy et al., 2015; Simonyan & Zisserman, 2015; He et al., 2016). In practice, strategies for building ensembles include the popular approach of independently training multiple initializations of the same network (i.e. *deep ensembles* (Lakshminarayanan et al., 2017)), training base learners on bootstrap samples of the training data (i.e. *bagging*) (Zhou et al., 2002), joint training with diversity-encouraging losses (Lee et al., 2015; Zhou et al., 2018; Webb et al., 2019) and using checkpoints during the training trajectory of a network (Huang et al., 2017; Loshchilov & Hutter, 2017). Much recent interest in ensembles has been due to their strong predictive uncertainty estimation (Lakshminarayanan et al., 2017), with extensive empirical studies (Ovadia et al., 2019; Gustafsson et al., 2020) observing that ensembles outperform other approaches for uncertainty estimation, notably including Bayesian methods (Gal & Ghahramani, 2016; Welling & Teh, 2011) and post-hoc calibration (Guo et al., 2017). Note He et al. (2020) draw a link between Bayesian methods and deep ensembles. We focus on deep ensembles as they provide state-of-the-art results in uncertainty estimation. Note that Ashukha et al. (2020) found many sophisticated ensembling techniques to be equivalent to a small-sized deep ensemble in terms of test performance.

AutoML.   AutoML (Hutter et al., 2018) is the process of automatically designing machine learning systems. Automatic ensemble construction is commonly used in AutoML (Feurer et al., 2015). Lévesque et al. (2016) use Bayesian optimization to tune non-architectural hyperparameters of an ensemble's base learners, relying on ensemble selection (Caruana et al., 2004). Specific to neural networks, AutoML also includes neural architecture search (NAS), the process of automatically designing network architectures (Elsken et al., 2019). Existing strategies using reinforcement learning (Zoph & Le, 2017), evolutionary algorithms (Real et al., 2019) or gradient-based methods (Liu et al., 2019) have demonstrated that NAS can find architectures that surpass hand-crafted ones.

Some recent research connects ensemble learning with NAS. Methods proposed by Cortes et al. (2017) and Macko et al. (2019) iteratively add (sub-)networks to an ensemble to improve the ensemble's performance. While our work focuses on generating a diverse and well-performing (in an ensemble) set of architectures while fixing how the ensemble is built from its base learners, the aforementioned works focus on how to build the ensemble. The search spaces considered by these works are also limited compared to ours: Cortes et al. (2017) consider fully-connected layers and Macko et al. (2019) only use NASNet-A (Zoph et al., 2018) blocks with varying depth and number of filters. All aforementioned works only focus on predictive performance and do not consider uncertainty estimation and dataset shift. Concurrent to our work, Wenzel et al. (2020) consider ensembles with base learners having varying hyperparameters using an approach similar to NES-RS. However, they focus on non-architectural hyperparameters such as L_2 regularization strength and dropout rates, keeping the architecture fixed. As in our work, they also consider predictive uncertainty calibration and robustness to shift, finding improvements over deep ensembles.

3   ENSEMBLES OF VARYING ARCHITECTURES ARE MORE DIVERSE

3.1   DEFINITIONS AND SET-UP

Let $\mathcal{D}_{\text{train}} = \{(\boldsymbol{x}_i, y_i) : i = 1, \ldots, N\}$ be the training dataset, where the input $\boldsymbol{x}_i \in \mathbb{R}^D$ and, assuming a classification task, the output $y_i \in \{1, \ldots, C\}$. We use $\mathcal{D}_{\text{val}}$ and $\mathcal{D}_{\text{test}}$ for the validation

and test datasets, respectively. Denote by f_θ a neural network with weights θ, so $f_\theta(\boldsymbol{x}) \in \mathbb{R}^C$ is the predicted probability vector over the classes for input $\boldsymbol{x}$. Let $\ell(f_\theta(\boldsymbol{x}), y)$ be the neural network's loss for data point $(\boldsymbol{x}, y)$. Given M networks $f_{\theta_1}, \ldots, f_{\theta_M}$, we construct the *ensemble F* of these networks by averaging the outputs, yielding $F(\boldsymbol{x}) = \frac{1}{M} \sum_{i=1}^{M} f_{\theta_i}(\boldsymbol{x})$.

In addition to the ensemble's loss $\ell(F(\boldsymbol{x}), y)$, we will also consider the *average base learner* loss and the *oracle ensemble's* loss. The average base learner loss is simply defined as $\frac{1}{M} \sum_{i=1}^{M} \ell(f_{\theta_i}(\boldsymbol{x}), y)$; we use this to measure the *average base learner strength*. Similar to Lee et al. (2015); Zhou et al. (2018), the oracle ensemble F_{OE} composed of base learners $f_{\theta_1}, \ldots, f_{\theta_M}$ is defined to be the function which, given an input $\boldsymbol{x}$, returns the prediction of the base learner with the smallest loss for $(\boldsymbol{x}, y)$, that is,

$$F_{\text{OE}}(\boldsymbol{x}) = f_{\theta_k}(\boldsymbol{x}), \quad \text{where} \quad k \in \operatorname*{argmin}_i \ell(f_{\theta_i}(\boldsymbol{x}), y).$$

Of course, the oracle ensemble can only be constructed if the true class y is known. We use the oracle ensemble loss as a measure of the *diversity* in base learner predictions. Intuitively, if base learners make diverse predictions for $\boldsymbol{x}$, the oracle ensemble is more likely to find some base learner with a small loss, whereas if all base learners make identical predictions, the oracle ensemble yields the same output as any (and all) base learners. Therefore, as a rule of thumb, *small oracle ensemble loss indicates more diverse base learner predictions*.

Proposition 3.1. Suppose ℓ is negative log-likelihood (NLL). Then, the oracle ensemble loss, ensemble loss, and average base learner loss satisfy the following inequality:

$$\ell(F_{\text{OE}}(\boldsymbol{x}), y) \le \ell(F(\boldsymbol{x}), y) \le \frac{1}{M} \sum_{i=1}^{M} \ell(f_{\theta_i}(\boldsymbol{x}), y).$$

We refer to Appendix A for a proof. Proposition 3.1 suggests that strong ensembles require not only strong average base learners (smaller upper bound), but also more diversity in their predictions (smaller lower bound). There is extensive theoretical work relating strong base learner performance and diversity with the generalization properties of ensembles (Hansen & Salamon, 1990; Zhou, 2012; Jiang et al., 2017; Bian & Chen, 2019; Goodfellow et al., 2016). Notably, Breiman (2001) showed that the generalization error of random forests depends on the strength of individual trees and the correlation between their mistakes.

3.2 VISUALIZING SIMILARITY IN BASE LEARNER PREDICTIONS

The fixed architecture used to build deep ensembles is typically chosen to be a strong stand-alone architecture, either hand-crafted or found by NAS. However, since ensemble performance depends not only on strong base learners but also on their diversity, optimizing the base learner's architecture and *then* constructing a deep ensemble neglects diversity in favor of strong base learner performance.

Having base learner architectures vary allows more diversity in their predictions. In this section, we provide empirical evidence for this by visualizing the base learners' predictions. Fort et al. (2019) found that base learners in a deep ensemble explore different parts of the function space by means of applying dimensionality reduction to their predictions. Building on this, we uniformly sample five architectures from the DARTS search space (Liu et al., 2019), train 20 initializations of each architecture on CIFAR-10 and visualize the similarity among the networks' predictions on the test dataset using t-SNE (Van der Maaten & Hinton, 2008). Experiment details are available in Section 5 and Appendix B.

Figure 1: t-SNE visualization: five different architectures, each trained with 20 different initializations.

As shown in Figure 1, we observe clustering of predictions made by different initializations of a fixed architecture, suggesting that base learners with varying architectures explore different parts of the function space. Moreover, we also visualize the predictions of base learners of two ensembles, each

of size $M = 30$, where one is a deep ensemble and the other has varying architectures (found by NES-RS which will be introduced in Section 4). Figure 11 shows more diversity in the ensemble with varying architectures than in the deep ensemble.

4   NEURAL ENSEMBLE SEARCH

In this section, we introduce *neural ensemble search* (NES). In summary, a NES algorithm optimizes the architectures of base learners in an ensemble to minimize ensemble loss.

Given a network $f : \mathbb{R}^D \to \mathbb{R}^C$, let $\mathcal{L}(f, \mathcal{D}) = \sum_{(\boldsymbol{x}, y) \in \mathcal{D}} \ell(f(\boldsymbol{x}), y)$ be the loss of f over dataset $\mathcal{D}$. Given a set of base learners $\{f_1, \ldots, f_M\}$, let `Ensemble` be the function which maps $\{f_1, \ldots, f_M\}$ to the ensemble $F = \frac{1}{M} \sum_{i=1}^{M} f_i$ as defined in Section 3 . To emphasize the architecture, we use the notation $f_{\theta, \alpha}$ to denote a network with architecture $\alpha \in \mathcal{A}$ and weights θ, where $\mathcal{A}$ is a search space (SS) of architectures. A NES algorithm aims to solve the following optimization problem:

$$\min_{\alpha_1, \ldots, \alpha_M \in \mathcal{A}} \mathcal{L}\left(\texttt{Ensemble}(f_{\theta_1, \alpha_1}, \ldots, f_{\theta_M, \alpha_M}), \mathcal{D}_{\text{val}}\right) \tag{1}$$
$$\text{s.t.} \quad \theta_i \in \operatorname*{argmin}_{\theta} \mathcal{L}(f_{\theta, \alpha_i}, \mathcal{D}_{\text{train}}) \qquad \text{for } i = 1, \ldots, M$$

Eq. 1 is difficult to solve for at least two reasons. First, we are optimizing over M architectures, so the search space is effectively $\mathcal{A}^M$, compared to it being $\mathcal{A}$ in typical NAS, making it more difficult to explore fully. Second, a larger search space also increases the risk of overfitting the ensemble loss to $\mathcal{D}_{\text{val}}$. A possible approach here is to consider the ensemble as a single large network to which we apply NAS, but joint training of an ensemble through a single loss has been empirically observed to underperform training base learners independently, specially for large neural networks (Webb et al., 2019). Instead, our general approach to solve Eq. 1 consists of two steps:

1. **Pool building**: build a *pool* $\mathcal{P} = \{f_{\theta_1, \alpha_1}, \ldots, f_{\theta_K, \alpha_K}\}$ of size K consisting of potential base learners, where each f_{θ_i, α_i} is a network trained independently on $\mathcal{D}_{\text{train}}$.

2. **Ensemble selection**: select M base learners $f_{\theta_1^*, \alpha_1^*}, \ldots, f_{\theta_M^*, \alpha_M^*}$ from $\mathcal{P}$ to form an ensemble which minimizes loss on $\mathcal{D}_{\text{val}}$. (We assume $K \geq M$.)

Step 1 reduces the options for the base learner architectures, with the intention to make the search more feasible and focus on strong architectures. Step 2 then selects a performant ensemble which implicitly encourages base learner strength *and* diversity. This procedure also ensures that the ensemble's base learners are trained independently. We propose using forward step-wise selection for step 2; that is, given the set of networks $\mathcal{P}$, we start with an empty ensemble and add to it the network from $\mathcal{P}$ which minimizes ensemble loss on $\mathcal{D}_{\text{val}}$. We repeat this without replacement until the ensemble is of size M. Let `ForwardSelect`$(\mathcal{P}, \mathcal{D}_{\text{val}}, M)$ denote the set of M base learners selected from $\mathcal{P}$ by this procedure.

Note that selecting the ensemble from $\mathcal{P}$ is a combinatorial optimization problem; a greedy approach such as `ForwardSelect` is nevertheless effective (Caruana et al., 2004), while keeping computational overhead low, given the predictions of the networks on $\mathcal{D}_{\text{val}}$. We also experimented with three other ensemble selection algorithms: (1) Starting with the best network by validation performance, add the next best network to the ensemble only if it improves validation performance, iterating until the ensemble size is M or all models have been considered.[1] (2) Select the top M networks by validation performance. (3) Forward step-wise selection *with* replacement. We typically found that these three performed comparatively or worse than our choice `ForwardSelect`.

We have not yet discussed the algorithm for building the pool in step 1; we propose two approaches, NES-RS (Section 4.1) and NES-RE (Section 4.2). NES-RS is a simple random search based algorithm, while NES-RE is based on regularized evolution (Real et al., 2019), a state-of-the-art NAS algorithm. Note that while gradient-based NAS methods have recently become popular, they are not naively applicable in our setting as the base learner selection component `ForwardSelect` is typically non-differentiable.

---

[1]This approach returns an ensemble of size at most M.

Figure 2: Illustration of one iteration of NES-RE. Network architectures are represented as colored bars of different lengths illustrating different layers and widths. Starting with the current population, ensemble selection is applied to select parent candidates, among which one is sampled as the parent. A mutated copy of the parent is added to the population, and the oldest member is removed.

4.1 NES with Random Search

In NAS, random search (RS) is a competitive baseline on carefully designed architecture search spaces (Li & Talwalkar, 2019; Yang et al., 2020; Yu et al., 2020). Motivated by its success and simplicity, we first introduce NES with random search (NES-RS). NES-RS builds the pool $\mathcal{P}$ by independently sampling architectures uniformly from the search space $\mathcal{A}$ (and training them). Since the architectures of networks in $\mathcal{P}$ vary, applying ensemble selection is a simple way to exploit diversity, yielding a performant ensemble. Algorithm 1 describes NES-RS in pseudocode.

Algorithm 1: NES with Random Search

Data: Search space $\mathcal{A}$; ensemble size M; comp. budget K; $\mathcal{D}_{\text{train}}, \mathcal{D}_{\text{val}}$.
1 Sample K architectures $\alpha_1, \ldots, \alpha_K$ independently and uniformly from $\mathcal{A}$.
2 Train each architecture α_i using $\mathcal{D}_{\text{train}}$, yielding a pool of networks $\mathcal{P} = \{f_{\theta_1, \alpha_1}, \ldots, f_{\theta_K, \alpha_K}\}$.
3 Select base learners $\{f_{\theta_1^*, \alpha_1^*}, \ldots, f_{\theta_M^*, \alpha_M^*}\} = \texttt{ForwardSelect}(\mathcal{P}, \mathcal{D}_{\text{val}}, M)$ by forward step-wise selection without replacement.
4 **return** ensemble $\texttt{Ensemble}(f_{\theta_1^*, \alpha_1^*}, \ldots, f_{\theta_M^*, \alpha_M^*})$

4.2 NES with Regularized Evolution

A more guided approach for building the pool $\mathcal{P}$ is using regularized evolution (RE) (Real et al., 2019). While RS has the benefit of simplicity, by sampling architectures uniformly, the resulting pool might contain many weak architectures, leaving few strong architectures for $\texttt{ForwardSelect}$ to choose between. Therefore, NES-RS might require a large pool in order to explore interesting parts of the search space. RE is an evolutionary algorithm used for NAS which explores the search space by evolving a *population* of architectures. In summary, RE starts with a randomly initialized fixed-size population of architectures. At each iteration, a subset of size m of the population is sampled, from which the best network by validation loss is selected as the parent. A mutated copy of the parent architecture, called the child, is trained and added to the population, and the oldest member of the population is removed, preserving the population size. This is iterated until the computational budget is reached, returning the *history*, i.e. all the networks evaluated during the search, from which the best model is chosen by validation loss.

Based on RE for NAS, we propose NES-RE to build the pool of potential base learners. NES-RE starts by randomly initializing a population $\mathfrak{p}$ of size P. At each iteration, we apply $\texttt{ForwardSelect}$ to the population to select an ensemble of size m, and we uniformly sample one base learner from the ensemble to be the parent. A mutated copy of the parent is added to $\mathfrak{p}$ and the oldest network is removed, as in regularized evolution. This process is repeated until the computational budget is reached, and the history is returned as the pool $\mathcal{P}$. See Algorithm 2 for pseudocode and Figure 2 for an illustration.

Also, note the distinction between the *population* and the *pool* in NES-RE: the population is evolved, whereas the pool is the set of all networks evaluated during evolution (i.e., the history) and is used post-hoc for selecting the ensemble, similar to Real et al. (2019). Moreover, $\texttt{ForwardSelect}$ is used both for selecting m parent candidates (line 4 in NES-RE) and choosing the final ensemble of size M (line 9 in NES-RE). In general, $m \neq M$.

Algorithm 2: NES with Regularized Evolution

Data: Search space $\mathcal{A}$; ensemble size M; comp. budget K; $\mathcal{D}_{\text{train}}, \mathcal{D}_{\text{val}}$; population size P; number of parent candidates m.

1 Sample P architectures $\alpha_1, \ldots, \alpha_P$ independently and uniformly from $\mathcal{A}$.

2 Train each architecture α_i using $\mathcal{D}_{\text{train}}$, and initialize $\mathfrak{p} = \mathcal{P} = \{f_{\theta_1, \alpha_1}, \ldots, f_{\theta_P, \alpha_P}\}$.

3 **while** $|\mathcal{P}| < K$ **do**

4   Select m parent candidates $\{f_{\widetilde{\theta}_1, \widetilde{\alpha}_1}, \ldots, f_{\widetilde{\theta}_m, \widetilde{\alpha}_m}\} = \texttt{ForwardSelect}(\mathfrak{p}, \mathcal{D}_{\text{val}}, m)$.

5   Sample uniformly a parent architecture α from $\{\widetilde{\alpha}_1, \ldots, \widetilde{\alpha}_m\}$.   // α stays in $\mathfrak{p}$.

6   Apply mutation to α, yielding child architecture β.

7   Train β using $\mathcal{D}_{\text{train}}$ and add the trained network $f_{\theta, \beta}$ to $\mathfrak{p}$ and $\mathcal{P}$.

8   Remove the oldest member in $\mathfrak{p}$.   // as done in RE (Real et al., 2019).

9 Select base learners $\{f_{\theta_1^*, \alpha_1^*}, \ldots, f_{\theta_M^*, \alpha_M^*}\} = \texttt{ForwardSelect}(\mathcal{P}, \mathcal{D}_{\text{val}}, M)$ by forward step-wise selection without replacement.

10 **return** ensemble $\texttt{Ensemble}(f_{\theta_1^*, \alpha_1^*}, \ldots, f_{\theta_M^*, \alpha_M^*})$

4.3 Ensemble Adaptation to Dataset Shift

Using deep ensembles is a common way of building a model robust to distributional shift relative to training data. In general, one may not know the type of distributional shift that occurs at test time. However, by using an ensemble, diversity in base learner predictions prevents the model from relying on one base learner's predictions which may not only be incorrect but also overconfident.

We assume that one does not have access to data points with test-time shift at training time, but one does have access to some validation data $\mathcal{D}_{\text{val}}^{\text{shift}}$ with a *validation* shift, which encapsulates one's belief about test-time shift. Crucially, test and validation shifts are disjoint. A simple way to adapt NES-RS and NES-RE to return ensembles robust to shift is by using $\mathcal{D}_{\text{val}}^{\text{shift}}$ instead of $\mathcal{D}_{\text{val}}$ whenever applying $\texttt{ForwardSelect}$ to select the final ensemble. In algorithms 1 and 2, this is in lines 3 and 9, respectively. Note that in line 4 of Algorithm 2, we can also replace $\mathcal{D}_{\text{val}}$ with $\mathcal{D}_{\text{val}}^{\text{shift}}$ when expecting test-time shift, however to avoid running NES-RE once for each of $\mathcal{D}_{\text{val}}, \mathcal{D}_{\text{val}}^{\text{shift}}$, we simply sample one of $\mathcal{D}_{\text{val}}, \mathcal{D}_{\text{val}}^{\text{shift}}$ uniformly at each iteration, in order to explore architectures that work well both in-distribution and during shift. See Appendices C.1.3 and B.4 for further discussion.

5 Experiments

We compare NES to deep ensembles on different choices of architecture search space (DARTS and NAS-Bench-201 (Dong & Yang, 2020) search spaces) and dataset (FMNIST, CIFAR-10, CIFAR-100, ImageNet-16-120 and Tiny ImageNet). For CIFAR-10/100 and Tiny ImageNet, we also consider dataset shifts proposed by Hendrycks & Dietterich (2019). The metrics used are: NLL, classification error and expected calibration error (ECE) (Guo et al., 2017; Naeini et al., 2015). Hyperparameter choices, experimental and implementation details are available in Appendix B. Unless stated otherwise, all evaluations are on the test dataset. Additional experimental results are in Appendix C.

Baselines. We compare the ensembles found by NES to the baseline of deep ensembles built using a fixed, optimized architecture. On the DARTS search space, the fixed architecture is either: (1) opti-

(a) No data shift   (b) Dataset shift: severity 5 (out of 5)

Figure 3: NLL vs. ensemble sizes on CIFAR-10, CIFAR-100 and Tiny ImageNet with and without respective dataset shifts (Hendrycks & Dietterich, 2019) over DARTS search space.

(a) No data shift   (b) Dataset shift: severity 5 (out of 5)

Figure 4: NLL vs. budget K on CIFAR-10/100 and Tiny ImageNet with and without respective dataset shifts over the DARTS search space. Ensemble size is fixed at $M = 10$.

mized by random search, called DeepEns (RS), (2) the architecture found using the DARTS algorithm, called DeepEns (DARTS) or (3) the architecture found using RE, called DeepEns (AmoebaNet). On the NAS-Bench-201 search space, instead of DeepEns (DARTS/AmoebaNet), we compare to DeepEns (GDAS), found using GDAS (Dong & Yang, 2019)[2], and DeepEns (Optimal), which uses the optimal architecture in the NAS-Bench-201 search space by validation loss. All base learners use the same training routine and have approximately the same model size for a given search space and dataset. See Appendix B for details and further discussion.

NLL on in-distribution and shifted data. Figures 3a and 4a show the NLL achieved by NES-RS, NES-RE and the baselines as functions of the ensemble size M and budget K respectively for in-distribution data. We find that NES algorithms consistently outperform deep ensembles across ensemble sizes, with NES-RE usually outperforming NES-RS. Next, we evaluate the robustness of the ensembles to dataset shift in Figures 3b and 4b. All base learners are trained on $\mathcal{D}_{\text{train}}$ without data augmentation with shifted examples. However, we use a shifted validation dataset, $\mathcal{D}_{\text{val}}^{\text{shift}}$, and a shifted test dataset, $\mathcal{D}_{\text{test}}^{\text{shift}}$. $\mathcal{D}_{\text{val}}^{\text{shift}}$ is built by applying a random *validation shift* to each datapoint in $\mathcal{D}_{\text{val}}$. $\mathcal{D}_{\text{test}}^{\text{shift}}$ is built similarly but using instead a disjoint set of *test shifts* applied to $\mathcal{D}_{\text{test}}$; see Appendix B and Hendrycks & Dietterich (2019) for details. The severity of the shift varies between 1-5. The fixed architecture used in the baseline DeepEns (RS) is selected based on its loss over $\mathcal{D}_{\text{val}}^{\text{shift}}$, but the DARTS and AmoebaNet architectures remain unchanged. As shown in Figures 3b and 4b, ensembles picked by NES-RS and NES-RE are more robust to dataset shift than all three baselines. Unsurprisingly, DeepEns (DARTS/AmoebaNet) perform poorly

Table 1: Classification error of ensembles for different shift severities. Best values and all values within 95% confidence interval are bold faced.

(a) Fixed $M = 10$.

Dataset	Shift Severity	Classif. error (%), $\mathcal{A}$ = DARTS search space				
		DeepEns (Amoe.)	DeepEns (DARTS)	DeepEns (RS)	NES-RS	NES-RE
C10	0	9.7	10.0	$10.8_{\pm 0.2}$	$\mathbf{9.4}_{\pm 0.1}$	$\mathbf{9.4}_{\pm 0.2}$
	3	25.6	26.3	$25.1_{\pm 0.7}$	$23.2_{\pm 0.2}$	$\mathbf{22.9}_{\pm 0.2}$
	5	42.7	42.9	$41.1_{\pm 0.9}$	$38.0_{\pm 0.2}$	$\mathbf{37.4}_{\pm 0.4}$
C100	0	31.6	30.9	$33.2_{\pm 1.2}$	$\mathbf{30.7}_{\pm 0.1}$	$\mathbf{30.4}_{\pm 0.4}$
	3	54.2	55.1	$54.8_{\pm 1.6}$	$\mathbf{49.8}_{\pm 0.1}$	$\mathbf{49.1}_{\pm 1.0}$
	5	68.5	68.5	$64.3_{\pm 3.2}$	$62.4_{\pm 0.2}$	$\mathbf{61.4}_{\pm 1.4}$
Tiny ImageNet	0	38.5	39.1	$\mathbf{37.5}_{\pm 0.3}$	$\mathbf{37.4}_{\pm 0.2}$	$\mathbf{37.0}_{\pm 0.6}$
	3	55.4	54.6	$53.8_{\pm 0.6}$	$53.0_{\pm 0.2}$	$\mathbf{52.7}_{\pm 0.2}$
	5	71.7	71.6	$70.5_{\pm 0.4}$	$\mathbf{69.9}_{\pm 0.2}$	$70.2_{\pm 0.1}$

(b) Fixed $M = 3$.

Dataset	Shift Severity	Classif. error (%), $\mathcal{A}$ = NAS-Bench-201 search space				
		DeepEns (GDAS)	DeepEns (Optimal)	DeepEns (RS)	NES-RS	NES-RE
C10	0	8.4	$\mathbf{7.2}$	$7.8_{\pm 0.2}$	$7.7_{\pm 0.1}$	$7.6_{\pm 0.1}$
	3	28.7	27.1	$28.3_{\pm 0.3}$	$\mathbf{22.0}_{\pm 0.2}$	$22.5_{\pm 0.1}$
	5	47.8	46.3	37.1	$\mathbf{32.5}_{\pm 0.2}$	$33.0_{\pm 0.5}$
C100	0	29.9	26.4	$26.3_{\pm 0.4}$	$\mathbf{23.3}_{\pm 0.3}$	$\mathbf{23.5}_{\pm 0.2}$
	3	60.3	54.5	$57.0_{\pm 0.9}$	$\mathbf{46.6}_{\pm 0.3}$	$46.7_{\pm 0.5}$
	5	75.3	69.9	$64.5_{\pm 0.0}$	$\mathbf{59.7}_{\pm 0.2}$	$60.0_{\pm 0.6}$
ImageNet-16-120	0	49.9	49.9	$50.5_{\pm 0.6}$	$48.1_{\pm 1.0}$	$\mathbf{47.9}_{\pm 0.4}$

compared to the other methods, as they are not optimized to deal with dataset shift, highlighting that highly optimized architectures can fail heavily under dataset shift.

Classification error and uncertainty calibration. We also assess the ensembles using classification error and expected calibration error (ECE). ECE measures the mismatch between the model's confidence and the corresponding achieved accuracy at different levels of confidence. As shown in Figure 5, ensembles found with NES tend to exhibit superior uncertainty calibration and are either competitive with or outperform deep ensembles for most shift severities. Notably, on CIFAR-10, ECE reduces by up to 40% compared to deep ensembles. Note that good uncertainty calibration is especially important when models are used during dataset shift. In terms of classification error, we find that ensembles built by NES consistently outperform deep ensembles, with reductions of up to 7 percentage points in error, shown in Table 1. As with NLL, NES-RE tends to outperforms NES-RS.

---

[2]We did not consider DARTS algorithm on NAS-Bench-201, since it returns degenerate architectures with poor performance on this space (Dong & Yang, 2020). GDAS, on the other hand, yields state-of-the-art performance on this space (Dong & Yang, 2020).

Figure 6: Average base learner loss and oracle ensemble loss (see Section 3 for definitions) on CIFAR-10/100 and Tiny ImageNet. Recall that small oracle ensemble loss generally corresponds to higher diversity. These findings are qualitatively consistent across datasets and also over shifted test data. See Appendix C.1.

Diversity and average base learner strength. To understand why ensembles found by NES algorithms outperform deep ensembles with fixed, optimized architectures, we view the ensembles through the lenses of the average base learner loss and oracle ensemble loss as defined in Section 3 and shown in Figure 6. Recall that *small oracle ensemble loss indicates higher diversity*. We see that NES finds ensembles with smaller oracle ensemble losses indicating greater diversity among base learners.

Figure 5: ECE vs. dataset shift severity on CIFAR-10, CIFAR-100 and Tiny ImageNet over the DARTS search space. No dataset shift is indicated as severity 0. Ensemble size is fixed at $M = 10$.

Unsurprisingly, the average base learner is occasionally weaker for NES as compared to DeepEns (RS). Despite this, the ensemble performs better (Figure 3), highlighting once again the importance of diversity.

Results on the NAS-Bench-201 search space. We also compare NES to deep ensembles for the NAS-Bench-201 search space, which has two benefits: this shows our findings are not specific to the DARTS search space, and NAS-Bench-201 is a search space for which all architectures' trained weights are available, which allows us to compare NES to the deep ensemble of the *optimal* architecture by validation loss. Results shown in Figure 7 compare the losses of the en-

Figure 7: Ensemble, average base learner and oracle ensemble NLL for ImageNet-16-120 on the NAS-Bench-201 search space. Ensemble size $M = 3$.

semble, average base learner and oracle ensemble. Interestingly, despite DeepEns (Optimal) having a significantly lower average base learner loss than other methods, the lack of diversity (as indicated by higher oracle ensemble loss) yields an ensemble which is outperformed by both NES algorithms.

6 CONCLUSION

We showed that ensembles with varying architectures are more diverse than ensembles with fixed architectures and argued that deep ensembles with fixed, optimized architectures neglect diversity. To this end, we proposed *Neural Ensemble Search*, which exploits diversity between base learners of varying architectures to find strong ensembles. We demonstrated empirically that NES-RE and NES-RS outperform deep ensembles in terms of both predictive performance and uncertainty calibration, for in-distribution data and also during dataset shift. We found that even NES-RS, a simple random search based algorithm, found ensembles capable of outperforming deep ensembles built with state-of-the-art architectures.

REFERENCES

Arsenii Ashukha, Alexander Lyzhov, Dmitry Molchanov, and Dmitry Vetrov. Pitfalls of in-domain uncertainty estimation and ensembling in deep learning. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=BJxI5gHKDr.

Yijun Bian and Huanhuan Chen. When does Diversity Help Generalization in Classification Ensembles? *ArXiv*, abs/1903.06236, 2019.

Mariusz Bojarski, Davide Del Testa, Daniel Dworakowski, Bernhard Firner, Beat Flepp, Prasoon Goyal, Lawrence D. Jackel, Mathew Monfort, Urs Muller, Jiakai Zhang, Xin Zhang, Jake Zhao, and Karol Zieba. End to End Learning for Self-Driving Cars. *CoRR*, abs/1604.07316, 2016.

Leo Breiman. Random forests. In *Machine Learning*, pp. 5–32, 2001.

Rich Caruana, Alexandru Niculescu-Mizil, Geoff Crew, and Alex Ksikes. Ensemble Selection from Libraries of Models. In *Proceedings of the Twenty-First International Conference on Machine Learning*, ICML '04, pp. 18, New York, NY, USA, 2004. Association for Computing Machinery. ISBN 1581138385. doi: 10.1145/1015330.1015432. URL https://doi.org/10.1145/1015330.1015432.

Patryk Chrabaszcz, Ilya Loshchilov, and Frank Hutter. A downsampled variant of imagenet as an alternative to the cifar datasets. *arXiv preprint arXiv:1707.08819*, 2017.

Corinna Cortes, Xavier Gonzalvo, Vitaly Kuznetsov, Mehryar Mohri, and Scott Yang. AdaNet: Adaptive Structural Learning of Artificial Neural Networks. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 874–883, International Convention Centre, Sydney, Australia, 06–11 Aug 2017. PMLR. URL http://proceedings.mlr.press/v70/cortes17a.html.

Thomas G. Dietterich. Ensemble Methods in Machine Learning. In *Multiple Classifier Systems*, pp. 1–15, Berlin, Heidelberg, 2000. Springer Berlin Heidelberg. ISBN 978-3-540-45014-6.

Xuanyi Dong and Yi Yang. Searching for a Robust Neural Architecture in Four GPU Hours. In *Computer Vision and Pattern Recognition (CVPR)*, pp. 1761–1770, 2019.

Xuanyi Dong and Yi Yang. Nas-bench-201: Extending the scope of reproducible neural architecture search. In *International Conference on Learning Representations (ICLR)*, 2020. URL https://openreview.net/forum?id=HJxyZkBKDr.

Thomas Elsken, Jan Hendrik Metzen, and Frank Hutter. Neural Architecture Search: A Survey. *Journal of Machine Learning Research*, 20(55):1–21, 2019.

Andre Esteva, Brett Kuprel, Roberto A. Novoa, Justin Ko, Susan M. Swetter, Helen M. Blau, and Sebastian Thrun. Dermatologist-level classification of skin cancer with deep neural networks. *Nature*, 542:115–, 2017.

Stefan Falkner, Aaron Klein, and Frank Hutter. BOHB: Robust and Efficient Hyperparameter Optimization at Scale. In *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 1437–1446, Stockholmsmässan, Stockholm Sweden, 10–15 Jul 2018. PMLR. URL http://proceedings.mlr.press/v80/falkner18a.html.

Matthias Feurer, Aaron Klein, Katharina Eggensperger, Jost Springenberg, Manuel Blum, and Frank Hutter. Efficient and robust automated machine learning. In *Advances in Neural Information Processing Systems 28*, pp. 2962–2970. Curran Associates, Inc., 2015.

Stanislav Fort, Huiyi Hu, and Balaji Lakshminarayanan. Deep Ensembles: A Loss Landscape Perspective. *ArXiv*, abs/1912.02757, 2019.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. volume 48 of *Proceedings of Machine Learning Research*, pp. 1050–1059, New York, New York, USA, 20–22 Jun 2016. PMLR. URL http://proceedings.mlr.press/v48/gal16.html.

Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep Learning*. MIT Press, 2016.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On Calibration of Modern Neural Networks. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 1321–1330, International Convention Centre, Sydney, Australia, 06–11 Aug 2017. PMLR. URL `http://proceedings.mlr.press/v70/guo17a.html`.

Fredrik K Gustafsson, Martin Danelljan, and Thomas B Schön. Evaluating Scalable Bayesian Deep Learning Methods for Robust Computer Vision. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, June 2020.

Lars K. Hansen and Peter Salamon. Neural network ensembles. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 12(10):993–1001, 1990.

Bobby He, Balaji Lakshminarayanan, and Yee Whye Teh. Bayesian deep ensembles via the neural tangent kernel. *arXiv preprint arXiv:2007.05864*, 2020.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep Residual Learning for Image Recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 770–778, 2016.

Dan Hendrycks and Thomas Dietterich. Benchmarking Neural Network Robustness to Common Corruptions and Perturbations. In *International Conference on Learning Representations*, 2019.

G. Hinton, L. Deng, D. Yu, G. E. Dahl, A. Mohamed, N. Jaitly, A. Senior, V. Vanhoucke, P. Nguyen, T. N. Sainath, and B. Kingsbury. Deep neural networks for acoustic modeling in speech recognition: The shared views of four research groups. *IEEE Signal Processing Magazine*, 29(6):82–97, 2012.

Gao Huang, Yixuan Li, Geoff Pleiss, Zhuang Liu, John Hopcroft, and Kilian Weinberger. Snapshot Ensembles: Train 1, get m for free. In *International Conference on Learning Representations*, 2017.

F. Hutter, L. Kotthoff, and J. Vanschoren (eds.). *Automated Machine Learning: Methods, Systems, Challenges*. Springer, 2018. In press, available at http://automl.org/book.

Zhengshen Jiang, Hongzhi Liu, Bin Fu, and Zhonghai Wu. Generalized Ambiguity Decompositions for Classification with Applications in Active Learning and Unsupervised Ensemble Pruning. In *AAAI*, pp. 2073–2079. AAAI Press, 2017.

Alex Krizhevsky, Vinod Nair, and Geoffrey Hinton. Cifar-10 (canadian institute for advanced research). 2009. URL `http://www.cs.toronto.edu/~kriz/cifar.html`.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet Classification with Deep Convolutional Neural Networks. In F. Pereira, C. J. C. Burges, L. Bottou, and K. Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 25*, pp. 1097–1105. Curran Associates, Inc., 2012.

Anders Krogh and Jesper Vedelsby. Neural Network Ensembles, Cross Validation, and Active Learning. In G. Tesauro, D. S. Touretzky, and T. K. Leen (eds.), *Advances in Neural Information Processing Systems 7*, pp. 231–238. MIT Press, 1995.

Ludmila Kuncheva and Chris Whitaker. Measures of Diversity in Classifier Ensembles and Their Relationship with the Ensemble Accuracy. *Machine Learning*, 51:181–207, 05 2003. doi: 10.1023/A:1022859003006.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and Scalable Predictive Uncertainty Estimation using Deep Ensembles. In *Advances in Neural Information Processing Systems 30*, pp. 6402–6413. Curran Associates, Inc., 2017.

Y. Le and X. Yang. Tiny imagenet visual recognition challenge. 2015.

Stefan Lee, Senthil Purushwalkam, Michael Cogswell, David Crandall, and Dhruv Batra. Why M Heads are Better than One: Training a Diverse Ensemble of Deep Networks. *arXiv e-prints*, art. arXiv:1511.06314, 2015.

Julien-Charles Lévesque, Christian Gagné, and Robert Sabourin. Bayesian hyperparameter optimization for ensemble learning. In *Proceedings of the Thirty-Second Conference on Uncertainty in Artificial Intelligence*, UAI'16, pp. 437–446, Arlington, Virginia, USA, 2016. AUAI Press. ISBN 9780996643115.

Liam Li and Ameet Talwalkar. Random Search and Reproducibility for Neural Architecture Search. In *UAI*, pp. 129. AUAI Press, 2019.

Hanxiao Liu, Karen Simonyan, and Yiming Yang. DARTS: Differentiable Architecture Search. In *International Conference on Learning Representations*, 2019.

Ilya Loshchilov and Frank Hutter. SGDR: Stochastic Gradient Descent with Warm Restarts. In *International Conference on Learning Representations*, 2017.

Vladimir Macko, Charles Weill, Hanna Mazzawi, and Javier Gonzalvo. Improving Neural Architecture Search Image Classifiers via Ensemble Learning. *ArXiv*, abs/1903.06236, 2019.

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. Distributed Representations of Words and Phrases and their Compositionality. In *Advances in Neural Information Processing Systems 26*, pp. 3111–3119. Curran Associates, Inc., 2013.

Mahdi Pakdaman Naeini, Gregory F. Cooper, and Milos Hauskrecht. Obtaining Well Calibrated Probabilities using Bayesian Binning. In *Proceedings of the Twenty-Ninth AAAI Conference on Artificial Intelligence*, AAAI'15, pp. 2901–2907. AAAI Press, 2015. ISBN 0262511290.

Yaniv Ovadia, Emily Fertig, Jie Ren, Zachary Nado, D. Sculley, Sebastian Nowozin, Joshua Dillon, Balaji Lakshminarayanan, and Jasper Snoek. Can you trust your model's uncertainty? Evaluating predictive uncertainty under dataset shift. In *Advances in Neural Information Processing Systems 32*, pp. 13991–14002. Curran Associates, Inc., 2019.

Esteban Real, Alok Aggarwal, Yanping Huang, and Quoc V. Le. Regularized Evolution for Image Classifier Architecture Search. In *AAAI*, pp. 4780–4789. AAAI Press, 2019. ISBN 978-1-57735-809-1.

Karen Simonyan and Andrew Zisserman. Very Deep Convolutional Networks for Large-Scale Image Recognition. In *International Conference on Learning Representations*, 2015.

Christian Szegedy, Wei Liu, Yangqing Jia, Pierre Sermanet, Scott Reed, Dragomir Anguelov, Dumitru Erhan, Vincent Vanhoucke, and Andrew Rabinovich. Going Deeper with Convolutions. In *Computer Vision and Pattern Recognition (CVPR)*, 2015.

Laurens Van der Maaten and Geoffrey Hinton. Visualizing data using t-SNE. *Journal of Machine Learning Research*, 9(2579-2605):85, 2008.

Andrew M. Webb, Charles Reynolds, Dan-Andrei Iliescu, Henry W. J. Reeve, Mikel Luján, and Gavin Brown. Joint Training of Neural Network Ensembles. *CoRR*, abs/1902.04422, 2019.

Max Welling and Yee Whye Teh. Bayesian learning via stochastic gradient langevin dynamics. In *Proceedings of the 28th International Conference on International Conference on Machine Learning*, ICML'11, pp. 681–688, Madison, WI, USA, 2011. Omnipress. ISBN 9781450306195.

Florian Wenzel, Jasper Snoek, Dustin Tran, and Rodolphe Jenatton. Hyperparameter ensembles for robustness and uncertainty quantification, 2020.

Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-MNIST: A Novel Image Dataset for Benchmarking Machine Learning Algorithms. *arXiv e-prints*, 2017.

Antoine Yang, Pedro M. Esperança, and Fabio M. Carlucci. NAS evaluation is frustratingly hard. In *International Conference on Learning Representations*, 2020.

Kaicheng Yu, Christian Sciuto, Martin Jaggi, Claudiu Musat, and Mathieu Salzmann. Evaluating the Search Phase of Neural Architecture Search. In *International Conference on Learning Representations*, 2020.

Tianyi Zhou, Shengjie Wang, and Jeff A Bilmes. Diverse Ensemble Evolution: Curriculum Data-Model Marriage. In *Advances in Neural Information Processing Systems 31*, pp. 5905–5916. Curran Associates, Inc., 2018.

Zhi-Hua Zhou. *Ensemble Methods: Foundations and Algorithms*. Chapman & Hall, 1st edition, 2012. ISBN 1439830037.

Zhi-Hua Zhou, Jianxin Wu, and Wei Tang. Ensembling neural networks: Many could be better than all. *Artificial Intelligence*, 137(1):239 – 263, 2002. ISSN 0004-3702. doi: https://doi.org/10.1016/S0004-3702(02)00190-X.

Barret Zoph and Quoc V Le. Neural Architecture Search with Reinforcement Learning. In *International Conference on Learning Representations*, 2017.

Barret Zoph, Vijay Vasudevan, Jonathon Shlens, and Quoc V Le. Learning Transferable Architectures for Scalable Image Recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 8697–8710, 2018.