Optimal Weak to Strong Learning

Abstract

The classic algorithm AdaBoost allows to convert a weak learner, that is an algorithm that produces a hypothesis which is slightly better than chance, into a strong learner, achieving arbitrarily high accuracy when given enough training data. We present a new algorithm that constructs a strong learner from a weak learner but uses less training data than AdaBoost and all other weak to strong learners to achieve the same generalization bounds. A sample complexity lower bound shows that our new algorithm uses the minimum possible amount of training data and is thus optimal. Hence, this work settles the sample complexity of the classic problem of constructing a strong learner from a weak learner.

1 Introduction

The field of boosting has been started from a classic question in learning theory asking whether classifiers that are just slightly better than random guessing can be used to create a classifier with arbitrarily high accuracy when given enough training data. This question was initially asked by Kearns and Valiant [14, 15] and ignited the line of research that eventually lead to the development of AdaBoost [6], the prototype boosting algorithm to date. AdaBoost carefully combines the predictions of several inaccurate classifiers trained with a focus on different parts of the training data to come up with a voting classifier that performs well everywhere.

We quantify the performance of an inaccurate learner by its *advantage* γ over random guessing. Said loosely, a γ-*weak learner* will correctly classify new data points with probability at least $1/2 + \gamma$. In contrast, given $0 < \varepsilon, \delta < 1$ and enough training data a *strong learner* outputs with probability $1 - \delta$ over the choice of the training data and possible random choices of the algorithm a hypothesis that correctly classifies new data points with probability at least $1 - \varepsilon$. The number of samples $m(\varepsilon, \delta)$ such that the learning algorithm achieves the desired accuracy and confidence levels is called the *sample complexity*. The sample complexity is the key metric for the performance of a strong learner and depends on the weak learner's advantage γ, the weak learner's flexibility measured in terms of the VC-dimension, as well as ε and δ. Essentially, a construction with low sample complexity makes the most out of the available training data.

AdaBoost [6] is the classic algorithm for constructing a strong learner from a γ-weak learner. If the weak learner outputs a hypothesis from a base set of hypotheses $\mathcal{H}$, then AdaBoost constructs a strong learner by taking a weighted majority vote among several hypotheses $h_1, \ldots, h_t$ from $\mathcal{H}$. Each of these hypotheses is obtained by invoking the γ-weak learning algorithm on differently weighted versions of a set of training samples S. The number of samples required by AdaBoost for strong learning depends both on the advantage γ of the weak learner and the complexity of the hypothesis set $\mathcal{H}$. If we let d denote the VC-dimension of $\mathcal{H}$, i.e. the cardinality of the largest set of data points $x_1, \ldots, x_d$ such that every classification of $x_1, \ldots, x_d$ can be realized by a hypothesis $h \in \mathcal{H}$, then it

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

is known that AdaBoost is a strong learner, which for error ε and failure probability δ, requires

$$O\left(\frac{d\ln(1/(\varepsilon\gamma))\ln(d/(\varepsilon\gamma))}{\varepsilon\gamma^2} + \frac{\ln(1/\delta)}{\varepsilon}\right), \tag{1}$$

samples. This sample complexity is state-of-the-art for producing a strong learner from a γ-weak learner. However, is this the best possible sample complexity? This is the main question we ask and answer in this work.

First, we present a new algorithm for constructing a strong learner from a weak learner and prove that it requires only

$$O\left(\frac{d}{\varepsilon\gamma^2} + \frac{\ln(1/\delta)}{\varepsilon}\right)$$

samples. In addition to improving over AdaBoost by two logarithmic factors, we complement our new algorithm by a lower bound, showing that any algorithm for converting a γ-weak learner to a strong learner requires

$$\Omega\left(\frac{d}{\varepsilon\gamma^2} + \frac{\ln(1/\delta)}{\varepsilon}\right)$$

samples. Combining these two results, we have a tight bound on the sample complexity of weak to strong learning. In the remainder of the section, we give a more formal introduction to weak and strong learning as well as present our main results and survey previous work.

1.1 Weak and strong learning

Consider a binary classification task in which there is an unknown concept $c : X \to \{-1, 1\}$ assigning labels to a ground set X. The goal is to learn or approximate c to high accuracy. Formally, we assume that there is an unknown but fixed data distribution $\mathcal{D}$ over X. A learning algorithm then receives a set S of i.i.d. samples $x_1, \ldots, x_m$ from $\mathcal{D}$ together with their labels $c(x_1), \ldots, c(x_m)$ and produces a hypothesis h with $h \approx c$ based on S and the labels. To measure how well h approximates c, it is assumed that a new data point x is drawn from the same unknown distribution $\mathcal{D}$, and the goal is to minimize the probability of mispredicting the label of x. We say that a learning algorithm is a weak learner if it satisfies the following:

Definition 1. *Let $C \subseteq X \to \{-1, 1\}$ be a set of concepts and $\mathcal{A}$ a learning algorithm. We say that $\mathcal{A}$ is a γ-weak learner for C, if there is a constant $\delta_0 < 1$ and an integer $m_0 \in \mathbb{N}$, such that for every distribution $\mathcal{D}$ over X and every concept $c \in C$, when given m_0 i.i.d. samples $S = x_1, \ldots, x_{m_0}$ from $\mathcal{D}$ together with their labels $c(x_1), \ldots, c(x_{m_0})$, it holds with probability at least $1 - \delta_0$ over the sample S and the randomness of $\mathcal{A}$, that $\mathcal{A}$ outputs a hypothesis $h : X \to \{-1, 1\}$ such that*

$$\mathcal{L}_{\mathcal{D}}(h) = \Pr_{x \sim \mathcal{D}}\left[h(x) \neq c(x)\right] \leq 1/2 - \gamma.$$

A γ-weak learner thus achieves an advantage of γ over random guessing when given m_0 samples. Note that $\mathcal{A}$ knows neither the distribution $\mathcal{D}$, nor the concrete concept $c \in C$ but achieves the advantage γ for all $\mathcal{D}$ and c. In contrast, a strong learner can obtain arbitrarily high accuracy:

Definition 2. *Let $C \subseteq X \to \{-1, 1\}$ be a set of concepts and $\mathcal{A}$ a learning algorithm. We say that $\mathcal{A}$ is a strong learner for C, if for all $0 < \varepsilon, \delta < 1$, there is some number $m(\varepsilon, \delta)$ such that for every distribution $\mathcal{D}$ over X and every concept $c \in C$, when given $m = m(\varepsilon, \delta)$ i.i.d. samples $S = x_1, \ldots, x_m$ from $\mathcal{D}$ together with their labels $c(x_1), \ldots, c(x_m)$, it holds with probability at least $1 - \delta$ over the sample S and the randomness of $\mathcal{A}$, that $\mathcal{A}$ outputs a hypothesis $h : X \to \{-1, 1\}$ such that*

$$\mathcal{L}_{\mathcal{D}}(h) = \Pr_{x \sim \mathcal{D}}\left[h(x) \neq c(x)\right] \leq \varepsilon.$$

The definition of a strong learner is essentially identical to the classic notion of (ε, δ)-PAC learning in the realizable setting. Unlike the γ-weak learner, we here require the learner to output a classifier with arbitrarily high accuracy (ε small) and confidence (δ small) when given enough samples S.

Kearns and Valiant [14, 15] asked whether one can always obtain a strong learner when given access only to a γ-weak learner for a $\gamma > 0$. This was answered affirmatively by Schapire [19] and is the

76 motivation behind the design of AdaBoost [6]. If we let $\mathcal{H}$ denote the set of hypotheses that a γ-weak
77 learner may output from, then AdaBoost returns a *voting* classifier $f(x) = \text{sign}(\sum_{i=1}^{t} \alpha_i h_i(x))$ where
78 each $h_i \in \mathcal{H}$ is the output of the γ-weak learner when trained on some carefully weighted version
79 of the training set S and each α_i is a real-valued weight. In terms of sample complexity $m(\varepsilon, \delta)$,
80 AdaBoost can be shown to require the number of samples stated in Eq. (1). There are several ways
81 to prove this. For instance, it can be argued that when given m samples, AdaBoost combines only
82 $t = O(\gamma^{-2} \ln m)$ hypotheses $h_1, \ldots, h_t$ from $\mathcal{H}$ in order to produce an f that perfectly classifies all
83 the training data S, i.e. $f(x_i) = c(x_i)$ for all $x_i \in S$. Using that the class $\mathcal{H}^t$ can generate at most
84 $O\left(\binom{m}{d}^t\right)$ distinct classifications of m points (i.e. its growth function is bounded by this), one can
85 intuitively invoke classic generalization bounds for PAC-learning in the realizable case to conclude
86 that the hypothesis f satisfies

$$\mathcal{L}_{\mathcal{D}}(f) \leq O\left(\frac{td \ln(m/d) + \ln(1/\delta)}{m}\right) = O\left(\frac{d \ln(m/d) \ln m}{\gamma^2 m} + \frac{\ln(1/\delta)}{m}\right) \qquad (2)$$

87 with probability at least $1 - \delta$ over S (and potentially the randomness of the weak learner). Using
88 $\mathcal{L}_{\mathcal{D}}(f) = \varepsilon$ and solving Eq. (2) for m gives the sample complexity stated in Eq. (1). This is the best
89 sample complexity bound of any weak to strong learner prior to this work.

90 Our main upper bound result is a new algorithm with better sample complexity than AdaBoost and
91 other weak to strong learners. It guarantees the following:

92 **Theorem 3.** *Assume we are given access to a γ-weak learner for some $0 < \gamma < 1/2$, using a base*
93 *hypothesis set $\mathcal{H} \subseteq X \rightarrow \{-1, 1\}$ of VC-dimension d. Then there is a universal constant $\alpha > 0$ and*
94 *an algorithm $\mathcal{A}$, such that $\mathcal{A}$ is a strong learner with sample complexity $m(\varepsilon, \delta)$ satisfying*

$$m(\varepsilon, \delta) \leq \alpha \cdot \left(\frac{d\gamma^{-2}}{\varepsilon} + \frac{\ln(1/\delta)}{\varepsilon}\right).$$

95 We remark that it is often required that a strong learner runs in polynomial time given a polynomial-
96 time weak learner. This is indeed the case for our new algorithm.

97 Next, we complement our algorithm from Theorem 3 by the following lower bound:

98 **Theorem 4.** *There is a universal constant $\alpha > 0$ such that for all integers $d \in \mathbb{N}$ and every*
99 $0 < \gamma < 1/80$, *there is a finite set X, a concept class $C \subset X \rightarrow \{-1, 1\}$ and a hypothesis set*
100 $\mathcal{H} \subseteq X \rightarrow \{-1, 1\}$ *of VC-dimension at most d, such that for every (ε, δ) with $0 < \varepsilon < 1$ and*
101 $0 < \delta < 1/3$, *there is a distribution $\mathcal{D}$ over X such that the following holds:*

102   *1. For every $c \in C$ and every distribution $\mathcal{D}'$ over X, there is an $h \in \mathcal{H}$ with*
103      $\Pr_{x \sim \mathcal{D}'}[h(x) \neq c(x)] \leq 1/2 - \gamma.$

104   *2. For any algorithm $\mathcal{A}$, there is a concept $c \in C$ such that $\mathcal{A}$ requires at least*

$$m \geq \alpha \cdot \left(\frac{d\gamma^{-2}}{\varepsilon} + \frac{\ln(1/\delta)}{\varepsilon}\right)$$

105   *samples S and labels $c(S)$ to guarantee $\mathcal{L}_{\mathcal{D}}(h_S) \leq \varepsilon$ with probability at least $1 - \delta$ over S,*
106   *where h_S is the hypothesis produced by $\mathcal{A}$ on S and $c(S)$.*

107 The first statement of Theorem 4 says that the concept class C can be γ-weakly learned. The second
108 point then states that any learner requires as many samples as our new algorithm. Moreover, the
109 lower bound does not require the algorithm to even use a γ-weak learner, nor does it need to run in
110 polynomial time for the lower bound to apply. Furthermore, the algorithm is even allowed to use the
111 full knowledge of the set C and the distribution $\mathcal{D}$. The only thing it does not know is which concept
112 $c \in C$ provides the labels $c(S)$ to the training samples.

113 In the next section, we present the overall ideas in our new algorithm, as well as a new generalization
114 bound for voting classifiers that is key to our algorithm. Finally, we sketch the main ideas in the lower
115 bound. Due to the space requirements, several proofs have been moved to the supplementary material.

1.2 Main ideas and voting classifiers

117 One of the key building blocks in our new algorithm are voting classifiers. To formally introduce
118 voting classifiers, define from a hypothesis set $\mathcal{H} \subseteq X \rightarrow \{-1, 1\}$ the set of all convex combination

119 $\Delta(\mathcal{H})$ of hypotheses in $\mathcal{H}$. That is, $\Delta(\mathcal{H})$ contains all functions f of the form $f(x) = \sum_{i=1}^{t} \alpha_i h_i(x)$
120 with $\alpha_i > 0$ and $\sum_i \alpha_i = 1$. AdaBoost can be thought of as producing a voting classifier $g(x) =$
121 $\text{sign}(f(x))$ for an $f \in \Delta(\mathcal{H})$ by appropriate normalization of the weights it uses.

122 Classic work on understanding the surprisingly high accuracy of AdaBoost introduced the notion
123 of *margins* [1]. For a function $f \in \Delta(\mathcal{H})$, and a sample x with label y, the margin of f on (x, y) is
124 $yf(x)$. Notice that the margin is positive if and only if $\text{sign}(f(x))$ correctly predicts the label y of x.
125 It was empirically observed that AdaBoost produces voting classifiers $g(x) = \text{sign}(f(x))$ where f
126 has large margins. This inspired multiple generalization bounds based on the margins of a voting
127 classifier, considering both the minimum and the k-th margin [11, 3, 2, 17, 18, 16]. The simplest
128 bound when all margins are assumed to be at least γ, is Breiman's min margin bound:

129 **Theorem 5** (Breiman [3]). *Let $c \in \mathcal{X} \to \{-1, 1\}$ be an unknown concept, $\mathcal{H} \subseteq \mathcal{X} \to \{-1, 1\}$ a*
130 *hypothesis set of VC-dimension d and $\mathcal{D}$ an arbitrary distribution over $\mathcal{X}$. With probability at least*
131 *$1 - \delta$ over a set of m samples $S \sim \mathcal{D}^m$, it holds for every voting classifier $g(x) = \text{sign}(f(x))$ with*
132 *$f \in \Delta(\mathcal{H})$ satisfying $c(x)f(x) \geq \gamma$ on all $x \in S$, that:*

$$\mathcal{L}_{\mathcal{D}}(g) = O\left(\frac{d \ln(m/d) \ln m}{\gamma^2 m}\right)$$

133 The resemblance to the generalization performance of AdaBoost in Eq. (2) is no coincidence. Indeed,
134 a small twist to AdaBoost, presented in the AdaBoost$_\nu^*$ algorithm [18], ensures that the voting
135 classifier produced by AdaBoost$_\nu^*$ from a γ-weak learner has all margins at least $\gamma/2$. This gives an
136 alternative way of obtaining the previous best sample complexity in Eq. (1). We remark that more
137 refined generalization bounds based on margins exist, such as the k-th margin bound by Gao and
138 Zhou [7] which is known to be near-tight [9]. These bounds take the whole sequence of margins
139 $c(x_i)f(x_i)$ of all samples $x_i \in S$ into account, not only the smallest. However, none of these bounds
140 leads to better generalization from a γ-weak learner.

141 We note that the notion of margins has not only been considered in the context of boosting algorithms
142 but also plays a key role in understanding the generalization performance of Support Vector Machines,
143 see e.g. the recent works [13, 10] giving tight SVM generalization bounds in terms of margins.

144 In our new algorithm, we make use of a voting classifier with good margins as a subroutine. Concretely,
145 we invoke AdaBoost$_\nu^*$ to obtain margins of at least $\gamma/2$ on all training samples. At first sight, this
146 seems to incur logarithmic losses, at least if the analysis by Breiman is tight. Moreover, Grønlund et al.
147 [8] proved a generalization lower bound showing that there are voting classifiers with margins γ on
148 all training samples, but where at least one of the logarithmic factors in the generalization bound must
149 occur. To circumvent this, we first notice that the lower bound only applies when m is sufficiently
150 larger than $d\gamma^{-2}$. We carefully exploit this loophole and prove a new generalization bound for voting
151 classifiers:

152 **Theorem 6.** *Let $c \in \mathcal{X} \to \{-1, 1\}$ be an unknown concept, $\mathcal{H} \subseteq \mathcal{X} \to \{-1, 1\}$ a hypothesis set of*
153 *VC-dimension d and $\mathcal{D}$ an arbitrary distribution over $\mathcal{X}$. There is a universal constant $\alpha > 0$, such*
154 *that with probability at least $1 - \delta$ over a set of $m \geq \alpha(d\gamma^{-2} + \ln(1/\delta))$ samples $S \sim \mathcal{D}^m$, every*
155 *voting classifier $g(x) = \text{sign}(f(x))$ with $f \in \Delta(\mathcal{H})$ satisfying $c(x)f(x) \geq \gamma$ on all $x \in S$ achieves*

$$\mathcal{L}_{\mathcal{D}}(g) \leq \tfrac{1}{200}.$$

156 The value $1/200$ is arbitrary and chosen to match the requirements in the proof of Theorem 3.
157 Notice how our new generalization bound avoids the logarithmic factors when aiming merely
158 at generalization error $1/200$. Breiman's bound would only guarantee that $d\gamma^{-2} \ln(1/\gamma) \ln(d/\gamma)$
159 samples suffice for such a generalization error. While the focus of previous work on generalization
160 bounds was not on the constant error case, we remark that any obvious approaches to modify the
161 previous proofs could perhaps remove the $\ln m$ factor but not the $\ln(m/d)$ factor. The $\ln(m/d)$ factor
162 turns into $\Theta(\ln(1/\gamma))$ when solving for m in $d \ln(m/d)/(\gamma^2 m) = 1/200$ and is insufficient for our
163 purpose.

164 With the new generalization bound on hand, we can now construct our algorithm for producing a
165 strong learner from a γ-weak learner. Here we use as template the sample optimal algorithm by
166 Hanneke [12] for PAC learning in the realizable case (which improved over a previous near-tight result
167 by Simon [20]). Given a training set S, his algorithm carefully constructs a number of sub-samples
168 $S_1, S_2, \ldots, S_k$ of S and trains a hypothesis h_i on each S_i using empirical risk minimization. As the
169 final classifier, he returns the voter $g(x) = \text{sign}\left((1/k) \sum_{i=1}^{k} h_i(x)\right)$.

For our new algorithm, we use Hanneke's approach to construct sub-samples $S_1, \ldots, S_k$ of a training set S. We then run AdaBoost$^*_\nu$ on each S_i to produce a voting classifier $g_i(x) = \text{sign}(f_i(x))$ for an $f_i \in \Delta(\mathcal{H})$ with margins $\gamma/2$ on all samples in S_i. We finally return the voter $h(x) = \text{sign}((1/k) \sum_{i=1}^k g_i(x))$. Our algorithm thus returns a majority of majorities. A lower bound by Grønlund et al. [8] shows the existence of a voting classifier with simultaneously large margins and a generalization error with an additional log-factor. It is thus conceivable that a simple majority vote is not sufficient and a majority of majorities is indeed necessary, although the lower bound only guarantees the *existence* of a 'bad' voter with good margins and not that *all* such voters are 'bad'.

To prove that our algorithm achieves the desired sample complexity $m(\varepsilon, \delta)$ claimed in Theorem 3, we then revisit Hanneke's proof and show that it suffices for his argument that the base learning algorithm (in his case empirical risk minimization, in our case AdaBoost$^*_\nu$) achieves an error of at most $1/200$ when given τ samples. If this is the case, then his proof can be modified to show that the final error of the output voter drops to $O(\tau/m)$. Plugging in the $\tau = \alpha(d\gamma^{-2} + \ln(1/\delta))$ from our new generalization bound in Theorem 6 completes the proof.

In the following, we start by proving our new generalization bound (Theorem 6) in Section 2. We then proceed in Section 3 to present our new algorithm and sketch the proof that it gives the guarantees in Theorem 3. Finally, in Section 4 we give the proof ideas of the lower bound in Theorem 4.

2   New margin-based generalization bounds for voting classifiers

In this section, we prove the new generalization bound stated in Theorem 6. For ease of notation, we write that $\mathcal{D}$ is a distribution over $\mathcal{X} \times \{-1, 1\}$ (and not just a distribution over $\mathcal{X}$) and implicitly assume that the label of each $x \in \mathcal{X}$ is $c(x)$ for the unknown concept c. Moreover, for a voting classifier $g(x) = \text{sign}(f(x))$ with $f \in \Delta(\mathcal{H})$, we simply refer to f as the voting classifier and just remark that one needs to take the sign to make a prediction. Finally, we think of the sample S as a set of pairs (x_i, y_i) with $x_i \in \mathcal{X}$ and $y_i = c(x_i) \in \{-1, 1\}$.

The key step in the proof of Theorem 6 is to analyze the generalization performance for a voting classifier obtained by combining randomly drawn hypotheses among the hypotheses $h_1, \ldots, h_t$ making up a voting classifier $f = \sum_i \alpha_i h_i$ from $\Delta(\mathcal{H})$. We then relate that to the generalization performance of f itself. Formally, we define a distribution $\mathcal{D}_{f,t}$ for every f and look at a random hypothesis from $\mathcal{D}_{f,t}$. We start by defining this distribution.

Let $f(x) = \sum_h \alpha_h h(x) \in \Delta(\mathcal{H})$ be a voting classifier. Let $\mathcal{D}_f$ be the distribution over $\mathcal{H}$ (the base hypotheses used in f) where h has probability α_h. Consider drawing t i.i.d. hypotheses $h'_1, \ldots, h'_t$ from $\mathcal{D}_f$ and then throwing away each h'_i independently with probability $1/2$. Let t' be the number of remaining hypotheses, denote them $h_1, \ldots, h_{t'}$, and let $g = \frac{1}{t'} \sum_{i=1}^{t'} h_i$. One can think of g as a sub-sampled version of f with replacement. Denote by $\mathcal{D}_{f,t}$ the distribution over g.

Key properties of $\mathcal{D}_{f,t}$.   In the following, we analyze how a random g from $\mathcal{D}_{f,t}$ behaves and show that while it behaves similar to f it produces with good probability predictions that are big in absolute value (even if $f(x) \approx 0$). The proofs of the following three lemmas are given in the supplementary material. First, we note that predictions made by a random g are often close to those made by f and then observe that g rarely makes predictions $g(x)$ that are small in absolute value.

Lemma 7. *For any $x \in \mathcal{X}$, any $f \in \Delta(\mathcal{H})$ and any $\mu > 0$:* $\Pr_{g \sim \mathcal{D}_{f,t}} [|f(x) - g(x)| \geq \mu] < 5e^{-\mu^2 t/32}$.

Lemma 8. *For any $x \in \mathcal{X}$, any $f \in \Delta(\mathcal{H})$ and any $\mu \geq 1/t$:* $\Pr_{g \sim \mathcal{D}_{f,t}} [|g(x)| \leq \mu] \leq 2\mu\sqrt{t}$.

Lemma 8 means that even if $f(x) \approx 0$ for an unseen sample, $g(x)$ will still be large with good probability. Thus we can think of g as having large margins (perhaps negative) also on unseen data. This is crucial for bounding the generalization error. The proof follows from an invocation of Erdős' improved Littlewood-Offord lemma [5].

As the last property, we look at the out-of-sample and in-sample error of a random g and start with relating the generalization error of f to that of a random g. To formalize this, define for any distribution $\mathcal{D}$, the loss $\mathcal{L}^t_{\mathcal{D}}(f) := \Pr_{(x,y) \sim \mathcal{D}, g \sim \mathcal{D}_{f,t}} [yg(x) \leq 0]$ and when writing $\mathcal{L}^t_S(f)$ we implicitly assume S to also denote the uniform distribution over all $(x, y) \in S$. We then have:

Lemma 9. *For any distribution $\mathcal{D}$ over $\mathcal{X} \times \{-1, 1\}$, any $t \geq 36$ and any voting classifier $f \in \Delta(\mathcal{H})$ for a hypothesis set $\mathcal{H} \subset \mathcal{X} \to \{-1, 1\}$, we have $\mathcal{L}_{\mathcal{D}}(f) \leq 3\mathcal{L}^t_{\mathcal{D}}(f)$.*

Moreover, if f has margins γ on all training samples $(x, y) \in S$, then g is correct on most of S provided that we set t big enough:

Lemma 10. *Let S be a set of m samples in $\mathcal{X} \times \{-1, 1\}$ and assume f is a voting classifier with $y f(x) \geq \gamma$ for all $(x, y) \in S$. For $t \geq 1024\gamma^{-2}$, we have $\mathcal{L}_S^t(f) \leq 1/1200$.*

Proof. By Lemma 7, it holds for all $(x, y) \in S$, that $|f(x) - g(x)| \geq \gamma$ with probability at most $5\exp\left(-\gamma^2 t/32\right) \leq 5e^{-32} \ll 1/1200$. Since $y f(x) \geq \gamma$, this implies $\text{sign}(g(x)) = \text{sign}(f(x)) = y$. $\square$

The last ingredient for the proof of Theorem 6 is to relate $\mathcal{L}_S^t(f)$ and $\mathcal{L}_\mathcal{D}^t(f)$. For the proof we use Lemma 8 to infer that with good probability $|g(x)| = \Omega(\gamma)$, i.e. has large absolute value. We use this to argue that $\text{sign}(g)$ often belongs to a class with small VC-dimension and then apply a growth-function argument to relate $\mathcal{L}_S^t(f)$ and $\mathcal{L}_\mathcal{D}^t(f)$. Formally, we prove the following lemma.

Lemma 11. *Let $\mathcal{D}$ be an arbitrary distribution over $\mathcal{X} \times \{-1, 1\}$ and let $\mathcal{H} \subset \mathcal{X} \to \{-1, 1\}$ be a hypothesis set of VC-dimension d. There is a universal constant $\alpha > 0$ such that for any $t \in \mathbb{N}$ and any $m \geq \alpha t d$, it holds that:*

$$\Pr_S\left[\sup_{f \in \Delta(\mathcal{H})} |\mathcal{L}_S^t(f) - \mathcal{L}_\mathcal{D}^t(f)| > \tfrac{1}{1200}\right] \leq \alpha \cdot \exp(-m/\alpha).$$

Before we prove Lemma 11, we show how to use it to prove Theorem 6. Since we are only aiming to prove the generalization of voting classifiers f with $y f(x) \geq \gamma$ for all samples $(x, y) \in S$, Lemma 10 tells us that such f have small $\mathcal{L}_S^t(f)$ when $t \geq 1024\gamma^{-2}$. We thus fix $t = 1024\gamma^{-2}$ and get that $\mathcal{L}_S^t(f) \leq 1/1200$ from Lemma 10. By Lemma 11, with probability at least $1 - \alpha \exp(-m/\alpha)$ over the sample S, we have for all $f \in \Delta(\mathcal{H})$ that $|\mathcal{L}_S^t(f) - \mathcal{L}_\mathcal{D}^t(f)| \leq 1/1200$ and thus $\mathcal{L}_\mathcal{D}^t(f) \leq 1/600$. Finally, Lemma 9 gives us that $\mathcal{L}_\mathcal{D}(f) \leq 3\mathcal{L}_\mathcal{D}^t(f)$ for all $f \in \Delta(\mathcal{H})$. Together we thus have $\mathcal{L}_\mathcal{D}^t(f) \leq 1/600 \Rightarrow \mathcal{L}_\mathcal{D}(f) \leq 1/200$ for any $m \geq \alpha t d \geq \alpha' d\gamma^{-2}$ where $\alpha' > 0$ is a universal constant. By observing that $\alpha \exp(-m/\alpha) < \delta$ for $m \geq \alpha \ln(\alpha/\delta)$, this completes the proof of Theorem 6. What remains is thus to prove Lemma 11 which we do in the remainder of this section.

2.1 Relating $\mathcal{L}_S^t(f)$ and $\mathcal{L}_\mathcal{D}^t(f)$

The last remaining step to show Theorem 6 is thus to relate $\mathcal{L}_S^t(f)$ to $\mathcal{L}_\mathcal{D}^t(f)$, i.e. to prove Lemma 11. In the proof, we rely on the classic approach for showing generalization for classes $\mathcal{H}$ of bounded VC-dimension and introduce a *ghost* set that only exists for the sake of analysis. In addition to the sample S, we thus consider a *ghost* set S' of another m i.i.d. samples from $\mathcal{D}$. This allows us to prove:

Lemma 12. *For $m \geq 2400^2$ any t and any f, it holds that:*

$$\Pr_S\left[\sup_{f \in \Delta(\mathcal{H})} |\mathcal{L}_S^t(f) - \mathcal{L}_\mathcal{D}^t(f)| > \tfrac{1}{1200}\right] \leq 2 \cdot \Pr_{S,S'}\left[\sup_{f \in \Delta(\mathcal{H})} |\mathcal{L}_S^t(f) - \mathcal{L}_{S'}^t(f)| > \tfrac{1}{2400}\right].$$

As the proof is standard, it can be found in the supplementary material.

We thus only need to bound $\Pr_{S,S'}[\sup_{f \in \Delta(\mathcal{H})} |\mathcal{L}_S^t(f) - \mathcal{L}_{S'}^t(f)| > 1/2400]$. To do this, consider drawing a data set P of $2m$ i.i.d. samples from $\mathcal{D}$ and then drawing S as a set of m uniform samples from P without replacement and letting S' be the remaining samples. Then S and S' have the same distribution as if they were drawn as two independent sets of m i.i.d. samples each. From here on, we thus think of S and S' as being sampled via P.

Now consider a fixed set P in the support of $\mathcal{D}^{2m}$ and define $\Delta_\delta^\mu(\mathcal{H}, P)$ as the set of voting classifiers $f \in \Delta(\mathcal{H})$ for which $\Pr_{(x,y) \sim P}[|f(x)| \geq \mu] \geq 1 - \delta$. These are the voting classifiers that make predictions of large absolute value on most of *both* S and S' (if $\delta \ll 1/2$). The crucial point, and the whole reason for introducing g, is that regardless of what f is, a random $g \sim \mathcal{D}_{f,t}$ often lies in the set $\Delta_\delta^\mu(\mathcal{H}, P)$:

Lemma 13. *For any data set P, parameters $0 < \delta < 1$ and t, and every $\mu \leq \delta/(9600\sqrt{t})$, we have $\Pr_{g \sim \mathcal{D}_{f,t}}[g \notin \Delta_\delta^\mu(\mathcal{H}, P)] \leq 1/4800$.*

Proof. Define an indicator X_i for each $(x_i, y_i) \in P$ taking the value 1 if $|g(x_i)| \leq \mu$. By Lemma 8, we have $\mathbb{E}[\sum_i X_i] \leq |P| 2\mu\sqrt{t} \leq |P| \delta/4800$. By Markov's inequality $\Pr[\sum_i X_i \geq \delta|P|] \leq 1/4800$. $\square$

If we had just considered f, we had no way of arguing that f makes predictions of large absolute value on S', since the only promise we are given is that it does so on S. That g makes predictions of large absolute value even outside of S is crucial for bounding the generalization error in the following.

Let us now define $\hat{\Delta}_\delta^\mu(P) = \text{sign}\left(\Delta_\delta^\mu(\mathcal{H}, P)\right)$ which means that $\hat{\Delta}_\delta^\mu(P)$ contains all the hypotheses that are obtained by voting classifiers in $\Delta_\delta^\mu(\mathcal{H}, P)$ when taking the sign. Since g is in $\Delta_\delta^\mu(\mathcal{H}, P)$ except with probability $1/4800$ by Lemma 13, we can prove:

Lemma 14. *For any $0 < \delta < 1$, every t, and every $\mu \leq \delta/(9600\sqrt{t})$, we have*

$$\Pr_{S,S'}\left[\sup_{f\in\Delta(\mathcal{H})}\left|\mathcal{L}_S^t(f) - \mathcal{L}_{S'}^t(f)\right| > \tfrac{1}{2400}\right] \leq \sup_P 2\left|\hat{\Delta}_\delta^\mu(P)\right|\exp\left(-2m/9600^2\right).$$

Again, the proof of the lemma can be found in the supplementary material. What Lemma 14 gives us, is that it relates the generalization error to the growth function $|\hat{\Delta}_\delta^\mu(P)|$. The key point is that $\hat{\Delta}_\delta^\mu(P)$ was obtained from voting classifiers with predictions of large absolute value on all but a δ fraction of points in P. This implies that we can bound the VC-dimension of $\hat{\Delta}_\delta^\mu(P)$ when restricted to the point set P using Rademacher complexity:

Lemma 15. *Let $\mathcal{H}$ be a hypothesis set of VC-dimension d. For any $\delta, \mu > 0$ and point set P, we have that the largest subset P' of P that $\hat{\Delta}_\delta^\mu(P) = \text{sign}\left(\Delta_\delta^\mu(\mathcal{H}, P)\right)$ can shatter, has size at most $|P'| = d' < \max\{2\delta|P|, 4\alpha^2\mu^{-2}d\}$, where $\alpha > 0$ is a universal constant.*

Proof. Recall that the VC-dimension of $\mathcal{H}$ is d. Thus the Rademacher complexity of $\mathcal{H}$ for any point set P' is:

$$\mathbb{E}_{\sigma\in P'\to\{-1,1\}}\left[\frac{1}{|P'|}\sup_{h\in\mathcal{H}}\left|\sum_{x\in P'}h(x)\sigma(x)\right|\right] < \alpha\sqrt{\frac{d}{|P'|}}$$

for a universal constant $\alpha > 0$ (see e.g. [21]). Assume $P' \subseteq P$ with $|P'| = d'$ can be shattered. Fix any labeling $\sigma \in P' \to \{-1, 1\}$. Let $h_\sigma \in \hat{\Delta}_\delta^\mu(P)$ be the hypothesis generating the dichotomy σ (which exists since P' is shattered). Since $h_\sigma \in \hat{\Delta}_\delta^\mu(P)$, there must be some $g \in \Delta_\delta^\mu(\mathcal{H}, P)$ such that $h_\sigma = \text{sign}(g)$ on the point set P'. If $|P'| \geq 2\delta|P|$, then by definition of $\Delta_\delta^\mu(\mathcal{H}, P)$, there are at least $|P'| - \delta|P| \geq |P'|/2$ points $x \in P'$ for which $|g(x)| \geq \mu$. This means that $(1/|P'|)\sum_{x\in P'}g(x)\sigma(x) \geq (1/2)\mu$. But $g(x)$ is a convex combination of hypotheses from $\mathcal{H}$, hence there is also a hypothesis $h \in \mathcal{H}$ for which $(1/|P'|)\sum_{x\in P'}h(x)\sigma(x) \geq (1/2)\mu$. Since this holds for all σ, by the bound on the Rademacher complexity, we conclude $\alpha\sqrt{d/|P'|} > (1/2)\mu \implies |P'| < 4\alpha^2\mu^{-2}d$. We thus conclude that the largest set that $\hat{\Delta}_\delta^\mu(P)$ can shatter, has size less than $\max\{2\delta|P|, 4\alpha^2\mu^{-2}d\}$. $\square$

We remark that it was crucial to introduce the random hypothesis g, since all we are promised about the original hypothesis f is that it has large margins on S, i.e. on only half the points in P. That case would correspond to $\delta = 1/2$ in Lemma 15 and would mean that we could potentially shatter all of P. In order for the bound to be useful, we thus need $\delta \ll 1/2$ and thus large margins on much more than half of P (which we get by using g).

For a $0 < \delta < 1$ to be determined, let us now fix $\mu = \delta/(9600\sqrt{t})$ and assume that the number of samples m satisfies $m \geq \max\{\alpha^2\mu^{-2}d/\delta, 2400^2\}$ where α is the constant from Lemma 15. By Lemma 14, we have

$$\Pr_{S,S'}\left[\sup_{f\in\Delta(\mathcal{H})}\left|\mathcal{L}_S^t(f) - \mathcal{L}_{S'}^t(f)\right| > \tfrac{1}{2400}\right] \leq \sup_P 2|\hat{\Delta}_\delta^\mu(P)|\exp(-2m/9600^2).$$

Lemma 15 gives us that the largest subset $P' \subseteq P$ that $\hat{\Delta}_\delta^\mu(P)$ shatters has size at most $d' < \max\{2\delta|P|, 4\alpha^2\mu^{-2}d\}$. By our assumption on m, the term $2\delta|P| = 4\delta m$ is at least $4c^2\mu^{-2}d$ and thus $2\delta|P| = 4\delta m$ takes the maximum in the bound on d'. By the Sauer-Shelah lemma, we have that $|\hat{\Delta}_\delta^\mu(P)| \leq \sum_{i=0}^{4\delta m-1}\binom{2m}{i}$. For $\delta \leq 1/4$, this is at most $\binom{2m}{4\delta m} \leq (e\delta^{-1}/2)^{4\delta m} = \exp\left(4\delta m\ln(e\delta^{-1}/2)\right)$.

As conclusion we have:

$$\Pr_{S,S'}\left[\sup_{f\in\Delta(\mathcal{H})}\left|\mathcal{L}_S^t(f) - \mathcal{L}_{S'}^t(f)\right| > \tfrac{1}{2400}\right] \leq 2\exp(4\delta m\ln(e\delta^{-1}/2))\exp(-2m/9600^2).$$

Algorithm 1: *Sub-Sample*(A, B) (Hanneke [12])

Input: Sets A and B
1 **if** $|A| \leq 3$ **then**
2 | **return** $A \cup B$
3 **else**
4 | Let A_0 denote the first $|A| - 3\lfloor |A|/4 \rfloor$ elements of A, A_1 the next $\lfloor |A|/4 \rfloor$ elements, A_2 the next $\lfloor |A|/4 \rfloor$ elements, and A_3 the remaining $\lfloor |A|/4 \rfloor$ elements.
5 | **return** *Sub-Sample*$(A_0, A_2 \cup A_3 \cup B)$ ∪ *Sub-Sample*$(A_0, A_1 \cup A_3 \cup B)$ ∪ *Sub-Sample*$(A_0, A_1 \cup A_2 \cup B)$

Algorithm 2: Optimal weak-to-strong learner

Input: Set S of m samples.
1 $\{C_1, \ldots, C_k\} = $ *Sub-Sample*$(S, \emptyset)$
2 **for** $i = 1, \ldots, k$ **do**
3 | $h_i = \mathcal{A}_\nu^*(C_i)$
4 **return** $h(x) = \mathrm{sign}\left(\sum_{i=1}^k h_i(x) \right)$.
---

304 Let us now fix $\delta = 10^{-10}$. We then have

$$2\exp\left(4\delta m \ln(e\delta^{-1}/2)\right) \exp(-2m/9600^2)$$
$$= 2\exp\left(m(4\delta \ln(e\delta^{-1}/2) - 2/9600^2)\right)$$
$$\leq 2\exp\left(-m/10^8\right)$$

305 where the last step is a numerical calculation. By Lemma 12, this in turn implies:

$$\Pr_S\left[\sup_{f \in \Delta(\mathcal{H})} \left| \mathcal{L}_S^t(f) - \mathcal{L}_{\mathcal{D}}^t(f) \right| > \tfrac{1}{1200} \right] \leq 4\exp(-m/10^8).$$

306 Since we only required $m \geq \max\{\alpha^2 \mu^{-2} d/\delta, 2400^2\}$ and we had $\mu = \delta/(9600\sqrt{t})$, this is satisfied
307 for $m \geq \alpha' t d$ for a large enough constant $\alpha' > 0$. This completes the proof of Lemma 11 and thus
308 also finishes the proof of Theorem 6.

3 Weak to strong learning

310 In this section, we give our algorithm for obtaining a strong learner from a γ-weak learner with
311 optimal sample complexity and sketch the main proof idea.

312 The algorithm obtaining the guarantees of Theorem 3 is as follows: Let $\mathcal{A}_\nu^*$ be an algorithm that on a
313 sample S outputs a classifier $g = \mathrm{sign}(f)$, where f is a voting classifier with margins at least $\gamma/2$ on all
314 samples in S such as AdaBoost$_\nu^*$ [18]. Given a set S of m i.i.d. samples from an unknown distribution
315 $\mathcal{D}$, we run $\mathcal{A}_\nu^*$ on a number of samples $C_1, C_2, \ldots, C_k \subset S$ obtaining hypotheses $h_1, h_2, \ldots, h_k$.
316 We then return the (unweighted) majority vote among $h_1, \ldots, h_k$ as our final hypothesis h^*. The
317 subsets C_i are chosen by the algorithm *Sub-Sample* (shown in Algorithm 1) as in the optimal PAC
318 learning algorithm by Hanneke [12]. The final algorithm (Algorithm 2) calls $\mathcal{A}_\nu^*$ on all subsets
319 returned by Algorithm 1 and returns the majority vote. Note that the final hypothesis returned by
320 Algorithm 2 is a majority of majorities since $\mathcal{A}_\nu^*$ already returns a voting classifier. Let us also
321 remark that in Theorem 6 we have a failure probability $\delta_0 > 0$, while the analysis of AdaBoost$_\nu^*$
322 assumes $\delta_0 = 0$, i.e. that the weak learner always achieves an advantage of at least γ. If one knows γ
323 in advance, this is not an issue as AdaBoost$_\nu^*$ only calls the weak learner on distributions over the
324 training data S and one can thus compute the advantage from the training data. After in expectation
325 $1/(1 - \delta_0)$ invocations of the weak learner, we thus get a hypothesis with advantage γ.

326 In total there are $k = 3^{\lceil \log_4(m) \rceil} \approx m^{0.79}$ calls to the weak learner, each with a sub-sample of linear
327 size. Since AdaBoost$_\nu^*$ runs in polynomial time on its input, given that the weak learner is polynomial,
328 Algorithm 2 is polynomial under the same condition.

329 The formal proof that Algorithm 2 has the guarantees of Theorem 3 is given in the supplementary
330 material due to space constraints. It follows the proof of Hanneke [12] pretty much uneventfully,

although carefully using that a generalization error of $1/200$ suffices for each call of $\mathcal{A}_\gamma^*$. The key observation is that each of the recursively generated sub-samples in Algorithm 1 leaves out a subset A_i of the training data, whereas the two other recursive calls always include all of A_i in their sub-samples. If one considers a hypothesis h trained on the data leaving out A_i, then A_i serves as an independent sample from $\mathcal{D}$. This implies that if h has large error probability over $\mathcal{D}$, then many of the samples in A_i will be classified incorrectly by h. Now, since the two other recursive calls always include A_i, any hypothesis h' trained on a sub-sample from those calls will have margin at least $\gamma/2$ on all points misclassified by h in A_i. But the generalization bound in Theorem 4 then implies that h' makes a mistake only with probability $1/200$ on *the conditional distribution* $\mathcal{D}(\,\cdot\mid h$ errs$)$. Thus, the probability that they both err at the same time is at most the probability that h errs, times $1/200$. Applying this reasoning inductively gives the conclusion that it is very unlikely that the majority of all trained hypotheses err at the same time which then finishes the proof.

4   Lower bound

In this section, we sketch the proof of Theorem 4 which gives a lower bound that matches the sample complexity from Theorem 3. The full proof is given in the supplementary material. Informally, Theorem 4 says that there exists a weakly learnable concept class C such that the hypothesis $\mathcal{A}(S)$ of any $\mathcal{A}$ satisfies $\mathcal{L}_{\mathcal{D}}(\mathcal{A}(S)) \geq \alpha \cdot \frac{d\gamma^{-2}+\ln(1/\delta)}{m}$. Here, the term $\ln(1/\delta)/\varepsilon$ follows from previous work. In particular, we could let $C = \mathcal{H}$ and invoke the tight lower bounds for PAC-learning in the realizable setting [4].

Thus, we let $\delta = 1/3$ and only prove that the loss of $\mathcal{A}(S)$ is at least $\alpha d/(\gamma^2 m)$ with probability $1/3$ over S when $|S| = m$ for some weakly learnable concept class C. This proof uses a construction from Grønlund et al. [8] to obtain a hypothesis set $\mathcal{H}$ over a domain $X = \{x_1, \ldots, x_u\}$ of cardinality $u = \alpha d\gamma^{-2}$ such that a constant fraction of all concepts in $X \to \{-1, 1\}$ can be γ-weakly learned from $\mathcal{H}$. We then create a distribution $\mathcal{D}$ where the first point x_1 is sampled with probability $1 - u/(4m)$ and with the remaining probability, we receive a uniform sample among $x_2, \ldots, x_u$. The key point is that we only expect to see $1 + m \cdot u/(4m) \approx u/4$ distinct points from X in a sample S of cardinality m. Thus, if we consider a random concept that can be γ-weakly learned, the labels it assigns to points not in the sample are almost uniform random and independent. This in turn implies that the best any algorithm $\mathcal{A}$ can do is to guess the labels of points in $X \setminus S$. In that way, $\mathcal{A}$ fails with constant probability if we condition on receiving a sample other than x_1. This happens with probability $u/(4m) = 4\alpha d\gamma^{-2}/m$ and the lower bound follows.

To formally carry out the intuitive argument above, we first argue that for a random concept $c \in C$, the Shannon entropy of c is high, even conditioned on S and the labels $c(S)$. Secondly, we argue that if $\mathcal{A}(S)$ has a small error probability under $\mathcal{D}$, then it must be the case that the hypothesis $\mathcal{A}(S)$ reveals a lot of information about c, i.e. the entropy of c is small conditioned on $\mathcal{A}(S)$. Since $\mathcal{A}(S)$ is a function of S and $c(S)$, the same holds if we condition on S and $c(S)$. This contradicts that c has high entropy and thus we conclude that $\mathcal{A}(S)$ cannot have a small error probability.

5   Conclusion

Overall, we presented a new weak to strong learner with a sample complexity that removes two logarithmic factors from the best-known bound. By accompanying the algorithm with a matching lower bound, we showed that the achieved sample complexity of our algorithm is indeed optimal. Our algorithm uses the same sub-sampling technique as Hanneke [12] and computes a voting classifier with large margins for each sample for example with AdaBoost$_\gamma^*$ [18]. The analysis of our algorithm uses a new generalization bound for voting classifiers with large margins.

Although we determined the exact sample complexity of weak to strong learning (up to multiplicative constants), there are a few connected open problems. Currently, our construction uses $3^{\log_4(m)} \approx m^{0.79}$ many sub-samples of linear size as input to AdaBoost$_\gamma^*$. For very large datasets, it would be great to reduce the number and size of these calls. Next, the output of our algorithm is a majority vote over majority voters. It is unclear whether a simple voter could achieve the same bounds. Last, it would be intriguing to see what can still be proven for voting classifiers that have margins γ on most, but not all, data points.

References

[1] Peter Bartlett, Yoav Freund, Wee Sun Lee, and Robert E Schapire. 1998. Boosting the margin: A new explanation for the effectiveness of voting methods. *The annals of statistics* 26, 5 (1998), 1651–1686.

[2] Kristin P Bennett, Ayhan Demiriz, and John Shawe-Taylor. 2000. A column generation algorithm for boosting. In *Icml*. Citeseer, 65–72.

[3] Leo Breiman. 1999. Prediction games and arcing algorithms. *Neural computation* 11, 7 (1999), 1493–1517.

[4] Andrzej Ehrenfeucht, David Haussler, Michael Kearns, and Leslie Valiant. 1989. A general lower bound on the number of examples needed for learning. *Information and Computation* 82, 3 (1989), 247–261.

[5] P. Erdős. 1945. On a lemma of Littlewood and Offord. *Bull. Amer. Math. Soc.* 51, 12 (1945), 898 – 902.

[6] Yoav Freund and Robert E Schapire. 1997. A decision-theoretic generalization of on-line learning and an application to boosting. *Journal of computer and system sciences* 55, 1 (1997), 119–139.

[7] Wei Gao and Zhi-Hua Zhou. 2013. On the doubt about margin explanation of boosting. *Artificial Intelligence* 203 (2013), 1–18.

[8] Allan Grønlund, Lior Kamma, Kasper Green Larsen, Alexander Mathiasen, and Jelani Nelson. 2019. Margin-based generalization lower bounds for boosted classifiers. *Advances in Neural Information Processing Systems* 32 (2019).

[9] Allan Grønlund, Lior Kamma, and Kasper Green Larsen. 2020. Margins are Insufficient for Explaining Gradient Boosting. In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*.

[10] Allan Grønlund, Lior Kamma, and Kasper Green Larsen. 2020. Near-Tight Margin-Based Generalization Bounds for Support Vector Machines. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event (Proceedings of Machine Learning Research, Vol. 119)*. PMLR, 3779–3788.

[11] Adam J Grove and Dale Schuurmans. 1998. Boosting in the limit: Maximizing the margin of learned ensembles. In *AAAI/IAAI*. 692–699.

[12] Steve Hanneke. 2016. The optimal sample complexity of PAC learning. *The Journal of Machine Learning Research* 17, 1 (2016), 1319–1333.

[13] Steve Hanneke and Aryeh Kontorovich. 2021. Stable Sample Compression Schemes: New Applications and an Optimal SVM Margin Bound. In *Proceedings of the 32nd International Conference on Algorithmic Learning Theory (Proceedings of Machine Learning Research, Vol. 132)*. PMLR, 697–721.

[14] Michael Kearns. 1988. Learning Boolean formulae or finite automata is as hard as factoring. *Technical Report TR-14-88 Harvard University Aikem Computation Laboratory* (1988).

[15] Michael Kearns and Leslie Valiant. 1994. Cryptographic limitations on learning boolean formulae and finite automata. *Journal of the ACM (JACM)* 41, 1 (1994), 67–95.

[16] Alexander Mathiasen, Kasper Green Larsen, and Allan Grønlund. 2019. Optimal minimal margin maximization with boosting. In *International Conference on Machine Learning*. PMLR, 4392–4401.

[17] Gunnar Rätsch and Manfred K Warmuth. 2002. Maximizing the margin with boosting. In *International Conference on Computational Learning Theory*. Springer, 334–350.

[18] Gunnar Rätsch, Manfred K Warmuth, and John Shawe-Taylor. 2005. Efficient Margin Maximizing with Boosting. *Journal of Machine Learning Research* 6, 12 (2005).

[19] Robert E Schapire. 1990. The strength of weak learnability. *Machine learning* 5, 2 (1990), 197–227.

[20] Hans U. Simon. 2015. An Almost Optimal PAC Algorithm. In *Proceedings of The 28th Conference on Learning Theory (Proceedings of Machine Learning Research, Vol. 40)*. PMLR, Paris, France, 1552–1563.

[21] Jon Wellner et al. 2013. *Weak convergence and empirical processes: with applications to statistics*. Springer Science & Business Media.