Differentially Private Sampling from Distributions

Abstract

We initiate an investigation of private sampling from distributions. Given a dataset with n independent observations from an unknown distribution P, a sampling algorithm must output a single observation from a distribution that is close in total variation distance to P while satisfying differential privacy. Sampling abstracts the goal of generating small amounts of realistic-looking data. We provide upper and lower bounds for the dataset size needed for this task for two natural families of distributions: arbitrary distributions on $\{1, \ldots, k\}$ and product distributions on $\{0,1\}^d$. We demonstrate that, in some parameter regimes, private sampling requires asymptotically fewer observations than learning a description of P nonprivately; in other regimes, however, sampling proves to be as difficult as private learning.

1 Introduction

Statistical machine learning models trained on sensitive data are now widely deployed in domains such as education, finance, criminal justice, medicine, and public health. The personal data used to train such models are more detailed than ever, and there is a growing awareness of the privacy risks that come with their use. Differential privacy is a standard for confidentiality that is now well studied and increasingly deployed.

Differentially private algorithms ensure, roughly, that whatever is learned about an individual from the algorithm's output would be roughly the same whether or not that individual's record was actually part of the input dataset. This requirement entails a strong guarantee, but limits the design of algorithms significantly. As a result, there is a substantial line of work on developing good differentially private methodology for learning and statistical estimation tasks, and on understanding how the sample size required for specific tasks increases relative to unconstrained algorithms. A typical task investigated in this area is *distribution learning*: informally, given records drawn i.i.d. from an unknown distribution P, the algorithm aims to produce a description of a distribution Q that is close to P.

However, often the task at hand requires much less than full-fledged learning. We may simply need to generate a small amount of data that has the same distributional properties as the population, or perhaps simply "looks plausible" for the population. For example, one might need realistic data for debugging a software program or for getting a quick idea of the range of values in a dataset.

In this work, we study a basic problem that captures these seemingly less stringent aims. Informally, the goal is to design a sampling algorithm that, given a dataset with n observations drawn i.i.d. from a distribution P, generates a single observation from a distribution Q that is close to P.

To formulate the problem precisely, consider a randomized algorithm $\mathcal{A} : \mathcal{U}^n \to \mathcal{U}$ that takes as input a dataset of n records in some universe $\mathcal{U}$ and outputs a single element of $\mathcal{U}$. Given a distribution P on $\mathcal{U}$, let $\mathbf{X} = (X_1, \ldots X_n)$ be a random dataset with entries drawn i.i.d. from P. Let $\mathcal{A}(\mathbf{X})$ denote the random variable corresponding to the output of the algorithm $\mathcal{A}$ on input $\mathbf{X}$. This random variable depends on both the selection of entries of $\mathbf{X}$ from P and the coins of $\mathcal{A}$. Let $Q_{\mathcal{A},P}$ denote the

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

distribution of $\mathcal{A}(\mathbf{X})$, so that

$$Q_{\mathcal{A},P}(z) = \Pr_{\substack{\mathbf{X} \sim_{i.i.d.} P \\ \text{coins of } \mathcal{A}}} (\mathcal{A}(\mathbf{X}) = z) = \sum_{\mathbf{x} \in \mathcal{U}^n} \left(\Pr(\mathbf{X} = \mathbf{x}) \cdot \Pr_{\text{coins of } \mathcal{A}} (\mathcal{A}(\mathbf{x}) = z) \right).$$

32 The dataset size n is a parameter of $\mathcal{A}$ and thus defined implicitly. We measure the closeness between
33 the input and output distributions in total variation distance.

34 **Definition 1.1** (Accuracy of sampling [2]). *A sampler $\mathcal{A}$ is α-accurate on a distribution P on $\mathcal{U}$ if*

$$d_{TV}(Q_{\mathcal{A},P}, P) \leq \alpha.$$

35 *We say the sampler is accurate on a class $\mathcal{C}$ of distributions on $\mathcal{U}$ if it is accurate for every P in $\mathcal{C}$.*

36 The class $\mathcal{C}$ in the accuracy definition above effectively encodes what the sampler is allowed to assume
37 about P. For example, $\mathcal{C}$ might include all distributions on k elements or product distributions on
38 $\{0,1\}^d$ (that is, distributions on d-bit strings for which the individual binary entries are independent).

39 Our goal in formulating Definition 1.1 was to capture the weakest reasonable task that abstracts
40 the goal of generating data with the same distributional properties as the input data. Without any
41 privacy constraints, this task is trivial to achieve: an algorithm that simply outputs its first input
42 record will sample from exactly the distribution P, so the interesting problem is to generate $m > n$
43 observations when given a sample of size only n (as in the work of Axelrod et al. [2], which inspired
44 our investigation). However, a differentially private algorithm cannot, in general, simply output one
45 of its records in the clear. Even producing a single correctly distributed sample is a non-trivial task.

46 To understand the task and compare our results to existing work, it is helpful to contrast our definition
47 of sampling with the more stringent goal of learning the distribution. We state a formulation with a
48 single parameter α that captures both the distance between distributions and the failure probability.

49 **Definition 1.2** (Distribution learning). *An algorithm $\mathcal{B}$ learns its input distribution to within error α*
50 *on a distribution class $\mathcal{C}$ if (a) for all inputs, $\mathcal{B}$'s output is a description of a distribution over $\mathcal{U}$ and*
51 *(b) for all distributions $P \in \mathcal{C}$,*

$$\Pr_{\substack{\mathbf{X} \sim_{i.i.d.} P \\ \text{coins of } \mathcal{B}}} \left(d_{TV}(\mathcal{B}(\mathbf{X}), P) \leq \alpha \right) \geq 1 - \alpha.$$

52 An algorithm $\mathcal{B}$ that learns to within error α immediately yields a 2α-accurate sampler: the sampler
53 first runs $\mathcal{B}$ to get a distribution $\hat{P}$ and then generates a single value from $\hat{P}$. Thus, it is instructive to
54 compare bounds on the dataset size required for sampling to known results on the sample complexity
55 of distribution learning.

56 **Differential privacy**   Differential privacy is a constraint on the algorithm $\mathcal{A}$ that processes a dataset.
57 It does not rely on any distributional property of the data. We generally use uppercase letters (e.g.,
58 $\mathbf{X} = (X_1, ..., X_n))$ when viewing the data as a random variable, and lowercase symbols (e.g.,
59 $\mathbf{x} = (x_1, ..., x_n))$ when treating the data as fixed. Two datasets $\mathbf{x}, \mathbf{x}' \in \mathcal{U}^n$ are *neighbors* if they
60 differ in at most one entry. If each entry corresponds to the data of one person, then neighboring
61 datasets differ by replacing one person's data with an alternate record. Informally, differential privacy
62 requires that an algorithm's output distributions are similar on all pairs of neighboring datasets.

63 **Definition 1.3** (Differential Privacy [14, 13]). *A randomized algorithm $\mathcal{A} : \mathcal{U}^n \to \mathcal{Y}$ is (ε, δ)-*
64 *differentially private if for every pair of neighboring datasets $\mathbf{x}, \mathbf{x}' \in \mathcal{U}^n$ and for all subsets $Y \subseteq \mathcal{Y}$,*

$$\Pr[\mathcal{A}(\mathbf{x}) \in Y] \leq e^\varepsilon \cdot \Pr[\mathcal{A}(\mathbf{x}') \in Y] + \delta.$$

65 For $\varepsilon \leq 1$ and $\delta < 1/n$, this guarantee implies, roughly, that one can learn the same things about
66 any given individual from the output of the algorithm as one could had their data not been used in
67 the computation [19]. When $\delta = 0$, the guarantee is referred to as pure differential privacy. In the
68 analysis of some of the algorithms, we also use a variant of the definition, *zCDP* [7].

1.1 Our results

70 We initiate a systematic investigation of the sample complexity of differentially private sampling. We
71 provide upper and lower bounds for the sample size needed for this task for two natural families of

Table 1: Sample complexities of sampling and estimation tasks. Our negative results hold for (ε, δ)-differential privacy when $\delta < 1/n$. In this table, $\varepsilon \leq 1$ and $\delta = 1/n^c$ for constant $c > 1$.

	Distributions on $[k]$	Product distributions on $\{0,1\}^d$	Product distributions with $p_j \in [\frac{1}{3}, \frac{2}{3}]$
Nonprivate learning	$\Theta\left(\dfrac{k}{\alpha^2}\right)$	$\Theta\left(\dfrac{d}{\alpha^2}\right)$	
(ε, δ)-DP sampling (this work)	$\Theta\left(\dfrac{k}{\alpha\varepsilon}\right)$
Theorems 1.4, 1.5	$\tilde{O}\left(\dfrac{d}{\alpha\varepsilon}\right), \tilde{\Omega}\left(\sqrt{d}\right)$
Theorems 1.6, 1.7	$\tilde{O}\left(\dfrac{\sqrt{d}}{\varepsilon} + \log\dfrac{1}{\alpha}\right)$
Theorem 1.8
(ε, δ)-DP learning	$\Theta\left(\dfrac{k}{\alpha^2} + \dfrac{k}{\alpha\varepsilon}\right)$ [10]	$\tilde{\Theta}\left(\dfrac{d}{\alpha\varepsilon} + \dfrac{d}{\alpha^2}\right)$ [17, 6]	

distributions: arbitrary distributions on $[k] = \{1, \ldots, k\}$ and product distributions on $\{0,1\}^d$. We demonstrate that, in some parameter regimes, private sampling requires asymptotically fewer samples than learning a description of P nonprivately; in other regimes, however, sampling proves to be as difficult as private learning.

Our results are summarized in Table 1. For simplicity, the table and our informal discussions focus on (ε, δ)-differential privacy (Definition 1.3) in the setting where $\delta = 1/n^c$ for some constant $c > 1$.[1]

Let $\mathcal{C}_k$ be the class of k-ary distributions (that is, distributions on $[k]$). We show that $n = \Theta\left(\frac{k}{\alpha\varepsilon}\right)$ observations are necessary and sufficient for differentially private sampling from $\mathcal{C}_k$ in the worst case.

Theorem 1.4. *For all $k \geq 2, \varepsilon > 0$, and $\alpha \in (0,1)$, there exists an $(\varepsilon, 0)$-differentially private sampler for the distribution class $\mathcal{C}_k$ that is α-accurate for datasets of size $n = O(\frac{k}{\alpha\varepsilon})$.*

Theorem 1.5. *For all $k \geq 2$, $\varepsilon \in (0,1]$, sufficiently small $\alpha > 0$, and $\delta \in \left[0, \frac{1}{1000n}\right]$, every (ε, δ)-differentially private sampler that is α-accurate on the class $\mathcal{C}_k$ needs datasets of size $\Omega(\frac{k}{\alpha\varepsilon})$.*

The second major class we consider consists of product distributions on $\{0,1\}^d$. Each such distribution is described by a vector of d probabilities, called *biases*, $(p_1, ..., p_d) \in [0,1]^d$; a single observation in $\{0,1\}^d$ is generated by flipping d independent coins with respective probabilities $p_1, ..., p_d$ of heads.

Theorem 1.6. *For all $\epsilon \in (0,1]$ and $\alpha, \delta \in (0,1)$, there exists an (ϵ, δ)-differentially private sampler for the class of products of d Bernoulli distributions that is α-accurate for datasets of size $n = \tilde{O}\left(\frac{d}{\alpha\epsilon}\right)$, assuming $\log(1/\delta) = poly(\log n)$.*

Theorem 1.7. *For all $\varepsilon \in [0,1]$, $\delta \in \left[0, \frac{1}{1000n}\right]$, $\alpha \in [0, 0.2]$, and sufficiently large $d \in \mathbb{N}$, every (ε, δ)-differentially private sampler that is α-accurate on the class of products of d Bernoulli distributions requires datasets of size $n = \tilde{\Omega}\left(\sqrt{d}\right)$.*

Finally, we give tighter upper bounds for Bernoulli distributions and, more generally, products of Bernoulli distributions, with bias bounded away from 0 and 1. For simplicity, we consider distributions with bias $p_j \in [\frac{1}{3}, \frac{2}{3}]$ in each coordinate $j \in [d]$. For these distributions, we show that differentially private sampling can be performed with datasets of significantly smaller size than in the general case. For Bernoulli distributions with bounded bias, we achieve this with pure differential privacy, that is, with $\delta = 0$. For products of Bernoulli distributions, we need $\delta > 0$.

Theorem 1.8. *For all $\varepsilon > 0$ and $\alpha, \delta \in (0,1)$, there exists an (ε, δ)-differentially private sampler for the class of products of d Bernoulli distributions with bias in $\left[\frac{1}{3}, \frac{2}{3}\right]$ that is α-accurate for datasets of size $n = O\left(\frac{\sqrt{d\log(1/\delta)}}{\varepsilon} + \log\frac{d}{\alpha}\right)$. When $d = 1$, the sampler has $\delta = 0$ and $n = O(\frac{1}{\varepsilon} + \log\frac{1}{\alpha})$.*

Implications The first observation about our results is that the sample complexity of private sampling can differ substantially from that of private learning (for which known bounds are stated in Table 1). In some settings, sampling is much easier than learning: for example, for product

---

[1]This setting precludes trivial solutions (which are possible when $\delta = \Omega(1/n)$), but allows us to treat factors of $\log(1/\delta)$ as logarithmic in n and absorb them in $\tilde{O}$ expressions.

distributions with bounded biases, private sampling has a lower dependence on the dimension $\sqrt{d}$ and essentially no dependence on α. Even for arbitrary biases or arbitrary k-ary distributions, private sampling is easier when $\alpha \ll \varepsilon$. In other settings, however, private sampling can be as hard as private learning: for $\epsilon \leq \alpha$, the worst-case complexity of sampling and learning k-ary distributions and product distributions is the same.

A more subtle point is that in those settings, sampling accounts for the entire cost of privacy in learning. Specifically, the optimal sample complexity of differentially private learning for arbitrary k-ary distributions is $n = \Theta\left(\frac{k}{\alpha^2} + \frac{k}{\alpha \varepsilon}\right)$ (e.g., see [1, Theorem 13]). We can view this bound as the sum of two terms: the sample complexity of nonprivate learning ($n = \Theta\left(\frac{k}{\alpha^2}\right)$) plus a term to account for the privacy constraint ($\Theta\left(\frac{k}{\alpha \varepsilon}\right)$). One interpretation of our lower bound, which shows that sampling requires $n = \Theta\left(\frac{k}{\alpha \varepsilon}\right)$, is that *the extra privacy term in the complexity of learning can be explained by the complexity of generating a single observation with roughly the correct distribution.* Such a phenomenon may also occur for product distributions with arbitrary biases, though our lower bounds are not currently strong enough to prove that (to establish that, they would have to match the $n = \tilde{O}\left(\frac{d}{\alpha \varepsilon}\right)$ upper bound).

Our results also show that, *in some settings, the distributions that are hardest for learning—nonprivate or private—are the easiest for sampling, and vice versa.* Consider the simple case of Bernoulli distributions (i.e. products with $d = 1$). The "hard" instances for nonprivate learning are distributions with bias $p = \frac{1 \pm \alpha}{2}$, but private sampling is easiest in that range. In contrast, our lower bound for Bernoulli distributions shows that sampling requires $n = \Omega(\frac{1}{\alpha \varepsilon})$ for distributions with bias $O(\alpha)$—very close to 0. A simple variance argument shows that nonprivate learning is easy in that range, requiring only $\frac{1}{\alpha}$ observations. Similarly, our lower bound for product distributions relies on distributions for which there are many coordinates with biases near 0 or 1.

Finally, it is interesting to observe that several of our lower bounds only require that the sampler generate a value in the support of the distribution with high probability.

Taken together, our results show that studying the complexity of generating a single sample helps us understand the true source of difficulty for certain tasks and sheds light on when we might be able to engage in nontrivial statistical tasks with very little data.

Limitations of our results and open questions   Our results leave many questions about the complexity of sampling. First, our upper bounds achieve only the minimal goal of generating a single observation. In most settings, one would presumably want to generate several such samples. One can do so by repeating our algorithms several times on disjoint subsamples, but this is not optimal in some regimes.

Second, we study only two classes of distributions. It is likely that the picture of what is possible for many classes is more complex and nuanced. In the nonprivate setting, Gaussian distributions demonstrate interesting data/accuracy tradeoffs for sampling [2].

Third, even for the settings we study, there remain gaps between our upper and lower bounds. Notably, for product distributions with biases bounded away from 0 and 1, it is not clear if the $\sqrt{d}$ dependence is necessary. For general product distributions, our upper bound requires $\delta > 0$; the private learning upper bound, in contrast, can be realized with $\varepsilon = 0$ [6].

Societal impact   We study the feasibility of basic inference under privacy constraints. Our work is motivated by societal concerns, but focused on fundamental theoretical limits. We do not anticipate direct practical impact.

1.2   An overview of our proofs and techniques

Distributions on $[k]$ For the class of distributions on $[k]$, Theorem 1.4 shows that α-accurate $(\varepsilon, 0)$-differentially private sampling can be performed with a dataset of size $= O(\frac{k}{\alpha \varepsilon})$. Our private sampler computes, for each $j \in [k]$, the proportion $\hat{P}_j$ of its dataset that is equal to j, adds Laplace noise to each count, uses L_1 projection to obtain a valid vector of probabilities $\tilde{P} = (\tilde{P}_1, \ldots, \tilde{P}_k)$, and finally outputs an element of $[k]$ sampled according to $\tilde{P}$.

Theorem 1.5 provides a matching lower bound on n that holds for all (ε, δ)-differentially private algorithms with $\delta = o(1/n)$. We prove our lower bound separately for Bernoulli distributions and for discrete distributions with support size $k \geq 3$, using different analyses. For Bernoulli distributions, we first exploit the group privacy for differentially private algorithms and the fact that the sampler must be accurate for the Bernoulli distribution $\mathsf{Ber}(0)$ to show that, on input with t ones, a differentially private sampler outputs 1 with probability at most $2\alpha e^{\varepsilon t}$. Then we consider $P = \mathsf{Ber}(10\alpha)$. We use α-accuracy in conjunction with the group-privacy-based bound to give a lower and an upper bound on the probability of the output being 1 when the input is drawn i.i.d. from P. This allows us to relate the parameters involved in order to obtain the desired lower bound on n.

The lower bound for distributions on $[k]$ with $k \geq 3$ is more involved. We start by proving general properties of samplers that allow us to restrict our attention to relatively simple algorithms. First, we observe that every sampler can be converted to a *Poisson algorithm*, that is, an algorithm that, instead of receiving an input of a fixed size, gets an input with the number of records that follows a Poisson distribution. This observation uses a standard technique called *Poissonization* that helps break up dependencies between random variables used in the analysis by modifying a probability experiment to replace a fixed quantity with a variable quantity that follows a Poisson distribution. Next, we observe that privacy for samplers can be easily amplified, so that we can assume w.l.o.g. that ε is small. Finally, we observe that every sampler for the class of k-ary distributions can be converted to a *frequency-count-based algorithm*. A sampler is *frequency-count-based* if the probability it outputs a specific element depends only on the number of occurrences of this element in its input and the frequency counts[2] of the input (that is, the number of elements that occur zero times, once, twice, thrice, and so on). Frequency-count-based samplers have been studied for a long time in the context of understanding properties of distributions (see, e.g., [3, 4, 20]).

Equipped with the three observations, we restrict our attention to Poisson, frequency-count-based algorithms, with small ε in the privacy guarantee. In contrast to our lower bound for Bernoulli samplers, we show that when the support size is at least 3 and the dataset size, n, is too small, the sampler is likely to output an element outside of the support of the input distribution P. Here, we exploit group privacy to show that the probability that a sampler outputs a specific element that appears j times in its input differs by at most a factor of $e^{\varepsilon j}$ from the probability that it outputs a specific element that does not appear in the input. Then we consider a distribution P that has most of its mass (specifically, $1 - 60\alpha$) on a special element. Out of the remaining elements in the domain, half are not in the support of P, and the other half appear with the same probability under P. That is, P is a mixture of a unit distribution on the special element and a uniform distribution on half of the remaining elements. We show that, when the dataset size is too small, the sampler is nearly equally likely to output any non-special element. But it has to output non-special elements with probability at least 59α to be α-accurate. The details of the proof are quite technical and appear in Section 2.

Product distributions   Our private sampler for product distributions over $\{0,1\}^d$, used to prove Theorem 1.6, builds on the recursive private preconditioning procedure designed by Kamath et al. [17] for learning this distribution class. In our case, the sampler gets a dataset of size which is asymptotically smaller than necessary for learning this distribution class in some important parameter regimes. Let $(p_1, \cdots, p_d)$ be the attribute biases for the product distribution P from which the data is drawn. For simplicity, we assume w.l.o.g. that all the marginal biases p_j are less than 1/2. The main idea in [17] is that smaller biases have lower sensitivity in the following sense: if we know that a set of attributes has biases p_j that are all at most some bound u then, because we assume a product distribution, the number of ones in those attributes should at most $2ud$ with high probability. We can enforce this bound on the number of ones in those coordinates by truncating each row appropriately, and thus learn the biases of those coordinates to higher accuracy than we knew before. Building on that idea, we partition the input into smaller datatsets and run our algorithm in rounds, each using fresh data, a different truncation threshold, and noise of different magnitude.

Our algorithm consists of two phases. In Phase 1, we use half of the dataset and the technique of [17] to get rough *multiplicative* estimates of all biases p_j except the very small ones (where $p_j < 1/d$). This allows us to partition the coordinates into $\log(d)$ buckets, where biases within each bucket are similar. We show this crude estimation only requires $n = \tilde{O}(d/\alpha\varepsilon)$.

---

[2]The vector of frequency counts is called a *fingerprint* or a *histogram* in previous work.

In Phase 2, we use the buckets to generate our output sample. For each bucket, we can get a fresh estimate of the biases using the other half of the data set and, again, the [17] technique to scale the noise proportionally to the upper bound on the biases that bucket. These estimates are essentially unbiased. Flipping d coins independently according to the estimated biases produces an observation with essentially the correct distribution.

To prove our lower bound for product distributions in Theorem 1.7, we use fingerprinting codes, following a long line of work [8, 21, 16, 17] that have used fingerprinting codes or related techniques to establish lower bounds in differential privacy. Bun et al. [8] prove that high accuracy on the task of producing a *valid codeword* (described below) for a specific family of fingerprinting codes violates differential privacy unless the size n of the dataset is at least, roughly, the square root of the the number of attributes d for each user. We use this lower bound on n by reducing the problem of sampling from products of Bernoulli distributions to the problem of generating valid codewords for the family of codes in [8].

A fingerprinting code is defined by a pair of randomized algorithms $(Gen, Trace)$. First, $Gen(N, d)$ outputs a codebook C containing a d-bit codeword for each user $i \in [N]$. A *coalition* $S \subseteq [N]$ of users run a randomized adversary $\mathcal{A}_{pirate}$ on their set of codewords $C|_S$ to produce a combined codeword $\mathbf{c}^*$ for S. Codeword $\mathbf{c}^*$ is *valid for coalition S* if the j-th bit of $\mathbf{c}^*$ is set to 0 for every column j of all zeros in $C|_S$, and to 1 for every column of all ones in $C|_S$. Roughly, a complete and sound fingerprinting code allows $Trace$ to identify some member of S when the codeword is valid.

Steinke et al. [21] define an algorithm $Gen_{\mathcal{D}}(N, d)$ that creates a codebook by independently drawing N codewords from a product P_{code} of d Bernoulli distributions, where the biases are kept secret. We use the property of distribution P_{code} that, conditioned on a column j in $C \sim P_{code}^{\otimes N}$ containing all zeros, the bias p_j is 0 with probability at least $3/5$; the analogous bound holds for columns of all ones. If a sampler, on input the code, generates an invalid output word, then it has a high chance of producing a string outside the support of the distribution P_{code}. Thus, an α-accurate sampler must produce a valid codeword with probability at least $1 - 3\alpha$. We can leverage the argument of [8] to show that such a sampler cannot be differentially private.

Distributions with bounded bias Interestingly, our sampler for product distributions with bounded bias does not directly add noise to data. It performs the following step independently for each attribute: compute the empirical mean of the sample in that coordinate, obtain the clipped mean by rounding the empirical mean to the interval $[1/4, 3/4]$, and sample a bit according to the clipped mean. The key idea in the analysis of accuracy is that, conditioned no rounding (that is, the empirical mean already being in the required interval), the new bit is sampled from the correct distribution, and rounding occurs with small probability. We argue that this sampler is $(4/n, 0)$-differentially private for the case when $d = 1$. For larger d, the sampler is a composition of d differentially private algorithms, and the main bound follows from compositions theorems (and conversions between different variants of differential privacy).

1.3 Related work

To the best of our knowledge, the private sampling problem we formulate has not been studied previously. There is work on nonprivate sample-size amplification, in which an initial dataset of n records is used to generate an output sample of size $n' > n$ from a nearby distribution [2]. Our formulation corresponds to the case where $n' = 1 \ll n$.

In the literature on differential privacy, there is work on private algorithms for sampling from Bayesian posterior distributions [11, 12, 25, 23], often driven by the intuition that the randomness inherent in sampling provides some level of privacy "for free". Our algorithms for product distributions with bounded bias leverage a similar idea. We are not aware of any analysis of the Bayesian approach which provides guarantees along the lines of our formulation (Def. 1.1).

To our knowledge, the most substantially related work in the privacy literature is on upper and lower bounds for learning and estimation tasks, dating back to Warner [24] (see [15, 18] for partial surveys). For learning k-ary distributions, the directly most relevant works are those of [10, 1], though lower bounds for estimating histograms were known as folklore since the mid-2000s. For product distributions, tight upper and lower bounds for (ε, δ)-differentially private estimation in TV distance appear in [17]; the upper bound was later shown to be achievable by an $(\varepsilon, 0)$-differentially private

algorithm [6]. Our upper bound for general product distributions adapts the technique of [17]; it remains open whether our bound is achievable with $\delta = 0$. Our lower bound uses the fingerprinting codes approach pioneered by [8] (which, in particular, was applied to the problem of estimating the parameters of a product distribution in ℓ_∞ distance) and a specific code distribution of [21].

Less directly related is the line of work on the generation of synthetic data sets that match the data distribution in a set of specified characteristics, such as linear queries (e.g., [5]; see [22] for a tutorial). The goal in those works is to generate enough synthetic data to allow an analyst given only the output to estimate the specified characteristics—a much more difficult task than sampling, and one for which a different set of lower bound techniques apply [22].

2 The lower bound for k-ary distributions

In this section, we prove the lower bound for sampling from discrete distributions with the universe of size at least 3. As discussed in Section 1.2, we prove an $n = \Omega(k/\alpha\varepsilon)$ lower bound. The crux of the proof is the case where the sampler is frequency-count-based, Poisson, and is (ε, δ)-differentially private for small ε. The transformation from general samplers to this restricted type of sampler is presented in the supplementary materials. This transformation together with the following Lemma 2.1 completes the proof of Theorem 1.5 for discrete distributions with the universe of size at least 3.

Lemma 2.1. *Fix $k \geq 1, n \in \mathbb{N}, \alpha \in (0, 0.02], \varepsilon \in (0, 1/\ln(1/\alpha)],$ and $\delta \in [0, 0.1\alpha\varepsilon/k]$. Let $\mathcal{C}_{2k+1}$ denote the class of discrete distributions over the universe $[2k+1]$. If sampler $\mathcal{A}$ is (ε, δ)-differentially private, frequency-count-based, and α-accurate on class $\mathcal{C}_{2k+1}$ with dataset size distributed as $\mathsf{Po}(n)$, then $n > \frac{1}{60} \cdot \frac{k}{\alpha\varepsilon}$.*

Proof. We consider the following distribution P over the universe $\mathcal{U} = [2k + 1]$. Fix $\alpha^* = 60\alpha$ and a set $S^* \subset [2k]$ of size k. Distribution P has mass α^*/k on each element in S^* and mass $1 - \alpha^*$ on the *special* element $2k + 1$.

Consider a sampler $\mathcal{A}$ satisfying the conditions of Lemma 2.1. Let $Q_{\mathcal{A},P}$ denote the output distribution of $\mathcal{A}$ when the dataset size $N \sim \mathsf{Po}(n)$ and the dataset $\mathbf{X} \sim P^{\otimes N}$. Observe that

$$d_{TV}(Q_{\mathcal{A},P}, P) \geq \Pr_{\substack{N \sim \mathsf{Po}(n) \\ \mathbf{X} \sim P^{\otimes N}}}[\mathcal{A}(\mathbf{X}) \notin Supp(P)]. \tag{1}$$

We show that if $n \leq \frac{k}{60\alpha\varepsilon}$ and ε and δ are in the specified range, the right-hand side of (1) is large. We start by deriving a lower bound on $\Pr[\mathcal{A}(\mathbf{x}) \notin Supp(P)]$ for a fixed dataset $\mathbf{x}$ of a fixed size N. Let $p_{j,F(\mathbf{x})}$ be the probability that $\mathcal{A}$ outputs a specific element in $[2k]$ that occurs j times in $\mathbf{x}$, where $F(\mathbf{x})$ is the frequency-count of $\mathbf{x}$; these probabilities are well-defined because $\mathcal{A}$ is frequency-count-based. Let $F_0^*(\mathbf{x})$ denote the number of elements in $[2k]$ that occur 0 times in $\mathbf{x}$ (excluding the special element $2k + 1$ from this count). By definition, $F_0^*(\mathbf{x}) \leq 2k$. Consequently,

$$\Pr[\mathcal{A}(\mathbf{x}) \notin Supp(P)] = k \cdot p_{0,F(\mathbf{x})} \geq \frac{1}{2} \cdot F_0^*(\mathbf{x}) \cdot p_{0,F(\mathbf{x})}. \tag{2}$$

The next claim uses the fact that $\mathcal{A}$ is (ε, δ)-differentially private to show that the probability $p_{j,F(\mathbf{x})}$ cannot be much larger than the probability that $\mathcal{A}$ outputs a specific element in $\mathcal{U}$ that does not appear in $\mathbf{x}$.

Claim 2.2. *For all (ε, δ)-differentially private samplers, frequency counts $f \in \mathbb{Z}^*$, and elements $j \in \mathcal{U}$,*

$$p_{j,f} \leq e^{\varepsilon j}\left(p_{0,f} + \frac{\delta}{\varepsilon}\right). \tag{3}$$

Proof. Consider a frequency count f and a dataset $\mathbf{x}$ with $F(\mathbf{x}) = f$. Note that (3) is true trivially for all j such that $F_j(\mathbf{x}) = 0$ because, in that case, $p_{j,F(\mathbf{x})}$ is set to 0.

Fix any $j \in \mathcal{U}$ with $F_j(\mathbf{x}) > 0$. Let a be any element in $\mathcal{U}$ that occurs j times in the dataset $\mathbf{x}$. Let b be any element in $\mathcal{U}$ that is not in the support of the distribution P. Let $\mathbf{x}|_{a \to b}$ denote the dataset obtained by replacing every instance of a in the dataset $\mathbf{x}$ with element b. By group privacy [14],

$$\Pr[\mathcal{A}(\mathbf{x}) = a] \leq e^{j\varepsilon} \Pr[\mathcal{A}(\mathbf{x}|_{a \to b}) = a] + \delta \cdot \frac{e^{\varepsilon j} - 1}{e^\varepsilon - 1}. \tag{4}$$

Note that the dataset $\mathbf{x}|_{a \to b}$ does not contain element a, since we've replaced every instance of it with b. Importantly, $F(\mathbf{x}|_{a \to b}) = F(\mathbf{x})$ because b is outside of the support of the distribution P and hence does not occur in $\mathbf{x}$. Since $\mathcal{A}$ is frequency-count-based and $F(\mathbf{x}) = F(\mathbf{x}|_{a \to b})$, we get that $p_{0,F(\mathbf{x})} = p_{0,F(\mathbf{x}|_{a \to b})}$. Substituting this into (4) and using the fact that $e^\varepsilon - 1 \geq \varepsilon$ for all ε, we get

$$p_{j,F(\mathbf{x})} \leq e^{j\varepsilon} \cdot p_{0,F(\mathbf{x})} + \delta \cdot \frac{e^{\varepsilon j} - 1}{e^\varepsilon - 1} \leq e^{\varepsilon j}\left(p_{0,f} + \frac{\delta}{\varepsilon}\right).$$

This completes the proof of Claim 2.2. $\qquad\square$

For a dataset $\mathbf{x}$ and $i \in [2k+1]$, let $N_i(\mathbf{x})$ denote the number of occurrences of element i in $\mathbf{x}$. Next, we give a lower bound on $\Pr[\mathcal{A}(\mathbf{x}) \notin Supp(P)]$ in terms of the counts $N_i(\mathbf{x})$.

Claim 2.3. *Let $N \in \mathbb{N}$ and $\mathbf{x} \in [2k+1]^N$ be a fixed dataset. Set $Y = \sum_{i \in S^*}\left[e^{N_i(\mathbf{x})\varepsilon}\right]$. Then*

$$\Pr[\mathcal{A}(\mathbf{x}) \notin Supp(P)] \geq \frac{1}{2} \cdot \frac{\Pr[\mathcal{A}(\mathbf{x}) \in [2k]]}{1 + Y/k} - \frac{k\delta}{\varepsilon}.$$

Proof. In the following derivation, we use the fact that that an element $j \in [2k]$ that appears j times in $\mathbf{x}$ is returned by $\mathcal{A}$ with probability $p_{j,F(\mathbf{x})}$, then split the elements into those that do not appear in $\mathbf{x}$ and those that do, next use the fact that all elements from $[2k]$ that appear in $\mathbf{x}$ must be in S^*, then apply Claim 2.2, and finally substitute Y for $\sum_{i \in S^*}\left[e^{N_i(\mathbf{x})\varepsilon}\right]$:

$$\begin{aligned}
\Pr[\mathcal{A}(\mathbf{x}) \in [2k]] = \sum_{i \in [2k]} p_{N_i(\mathbf{x}),F(\mathbf{x})} &= F_0^*(\mathbf{x}) \cdot p_{0,F(\mathbf{x})} + \sum_{i \in [2k] \cap \mathbf{x}} p_{N_i(\mathbf{x}),F(\mathbf{x})} \\
&\leq F_0^*(\mathbf{x}) \cdot p_{0,F(\mathbf{x})} + \sum_{i \in S^*} p_{N_i(\mathbf{x}),F(\mathbf{x})} \\
&\leq F_0^*(\mathbf{x}) \cdot p_{0,F(\mathbf{x})} + \sum_{i \in S^*} p_{0,F(\mathbf{x})} \cdot \left(e^{\varepsilon N_i(\mathbf{x})} + \frac{\delta}{\varepsilon}\right) \leq \left(F_0^*(\mathbf{x}) + Y\right)\left(p_{0,F(\mathbf{x})} + \frac{\delta}{\varepsilon}\right).
\end{aligned}$$

We rearrange the terms to get $p_{0,F(\mathbf{x})} \geq \dfrac{\Pr[\mathcal{A}(\mathbf{x}) \in [2k]]}{F_0^*(\mathbf{x}) + Y} - \dfrac{\delta}{\varepsilon}$.

Substituting this bound on $p_{0,F(\mathbf{x})}$ into (2), we obtain that $\Pr[\mathcal{A}(\mathbf{x}) \notin Support(P)]$ is at least

$$\frac{1}{2} \cdot \frac{F_0^*(\mathbf{x})\Pr[\mathcal{A}(\mathbf{x}) \in [2k]]}{F_0^*(\mathbf{x}) + Y} - \frac{1}{2} \cdot \frac{F_0^*(\mathbf{x}) \cdot \delta}{\varepsilon} \geq \frac{1}{2} \cdot \frac{\Pr[\mathcal{A}(\mathbf{x}) \in [2k]]}{1 + Y/k} - \frac{k\delta}{\varepsilon},$$

where in the inequality, we used that $k \leq F_0^*(\mathbf{x}) \leq 2k$. This holds since the support of P excludes k elements from $[2k]$ and since $F_0^*(\mathbf{x})$ counts only elements from $[2k]$ that do not appear in $\mathbf{x}$. $\qquad\square$

Finally, we give a lower bound on the right-hand side of (1). Assume for the sake of contradiction that $n \leq \frac{k}{\alpha^* \varepsilon}$. By Claim 2.3,

$$\begin{aligned}
\Pr_{N,\mathbf{X}}[\mathcal{A}(\mathbf{X}) \notin Supp(P)] &\geq \mathop{\mathbb{E}}_{N,\mathbf{X}}\left[\frac{1}{2} \cdot \frac{\Pr[\mathcal{A}(\mathbf{X}) \in [2k]]}{1 + Y/k} - \frac{k\delta}{\varepsilon}\right] \\
&= \frac{1}{2} \cdot \mathop{\mathbb{E}}_{N,\mathbf{X}}\left[\frac{\Pr[\mathcal{A}(\mathbf{X}) \in [2k]]}{1 + Y/k}\right] - \frac{k\delta}{\varepsilon}.
\end{aligned} \tag{5}$$

Next, we analyze the expectation in (5). Let E be the event that $\frac{Y}{k} \leq e^3$. By the law of total expectation,

$$\mathop{\mathbb{E}}_{N,\mathbf{X}}\left[\frac{\Pr[\mathcal{A}(\mathbf{X}) \in [2k]]}{1 + Y/k}\right] \geq \mathop{\mathbb{E}}_{N,\mathbf{X}}\left[\frac{\Pr[\mathcal{A}(\mathbf{X}) \in [2k]]}{1 + Y/k}\Big| E\right] \Pr(E). \tag{6}$$

In Claims 2.4 and 2.5, we argue that both $\Pr(E)$ and $\mathbb{E}_{N,\mathbf{X}}\left[\frac{\Pr[\mathcal{A}(\mathbf{X}) \in [2k]]}{1 + Y/k}\Big| E\right]$ are large.

Claim 2.4. *Suppose $n \leq \frac{k}{60\alpha\varepsilon}$. Let E be the event that $\frac{Y}{k} \leq e^3$. Then $\Pr(E) \geq 1 - \alpha$.*

Proof. Recall that Y was defined as $\sum_{i\in S^*}\left[e^{N_i(\mathbf{x})\varepsilon}\right]$ for a fixed dataset $\mathbf{x}$. Now we consider the case when dataset $\mathbf{X}$ is a random variable. If $N\sim\mathsf{Po}(n)$ and $\mathbf{X}\sim P^{\otimes N}$ then $N_i(\mathbf{X})\sim\mathsf{Po}(\frac{\alpha^*n}{k})$ for all $i\in S^*$ and, additionally, the random variables $N_i(\mathbf{X})$ are mutually independent. When $\mathbf{X}$ is clear from the context, we write N_i instead of $N_i(\mathbf{X})$. Now we calculate the moments of $\frac{Y}{k}$. For all $\lambda>0$,

$$\mathop{\mathbb{E}}_{\substack{N\sim\mathsf{Po}(n)\\\mathbf{X}\sim P^{\otimes N}}}\left[\left(\frac{Y}{k}\right)^\lambda\right]=\mathop{\mathbb{E}}_{\substack{N\sim\mathsf{Po}(n)\\\mathbf{X}\sim P^{\otimes N}}}\left[\left(\frac{1}{k}\sum_{i\in S^*}e^{N_i(\mathbf{X})\varepsilon}\right)^\lambda\right]=\mathop{\mathbb{E}}_{N_1,\cdots,N_k\sim\mathsf{Po}(\frac{\alpha^*n}{k})}\left[\left(\frac{1}{k}\sum_{i\in S^*}e^{N_i\varepsilon}\right)^\lambda\right].\quad(7)$$

Finally, we bound the probability of event E. Set $c=e^3$ and $\lambda=\ln\frac{1}{\alpha}$. By definition of E,

$$\Pr(\overline{E})=\Pr\left(\frac{Y}{k}\geq c\right)=\Pr\left(\left(\frac{Y}{k}\right)^\lambda\geq c^\lambda\right)\leq\frac{1}{c^\lambda}\cdot\mathop{\mathbb{E}}_{\substack{N\sim\mathsf{Po}(n)\\\mathbf{X}\sim P^{\otimes N}}}\left[\left(\frac{Y}{k}\right)^\lambda\right]$$

$$\leq\frac{1}{c^\lambda}\cdot\mathop{\mathbb{E}}_{N_1,\cdots,N_k\sim\mathsf{Po}(\frac{\alpha^*n}{k})}\left[\left(\frac{1}{k}\sum_{i\in S^*}e^{N_i\varepsilon}\right)^\lambda\right]\leq\frac{1}{c^\lambda}\cdot\mathop{\mathbb{E}}_{N_1\sim\mathsf{Po}(\frac{\alpha^*n}{k})}\left[\left(e^{N_1\varepsilon}\right)^\lambda\right]\qquad(8)$$

$$=c^{-\lambda}\cdot e^{\frac{\alpha^*n}{k}(e^{\lambda\varepsilon}-1)}\leq e^{-3\lambda}\cdot e^{\frac{(e^{\lambda\varepsilon}-1)}{\varepsilon}}\leq e^{-3\lambda}\cdot e^{2\lambda}=e^{-\lambda}=e^{-\ln(1/\alpha)}=\alpha,\quad(9)$$

where we use $\lambda>0$ in the second equality, then apply Markov's inequality. To get the inequalities in (8), we apply (7) and then use the fact that the moments of the average of random variables is less than the moment of a single random variable (the proof of this fact is in the supplementary material). To get (9), we use the moment generating function of a Poisson random variable, and then we substitute $c=e^3$ and use the assumption that $n\leq\frac{k}{60\alpha\varepsilon}=\frac{k}{\alpha^*\varepsilon}$. The second inequality in (9) holds because $\lambda=\ln\frac{1}{\alpha}$ and $\varepsilon\in(0,1/\ln\frac{1}{\alpha}]$, so $\lambda\varepsilon\leq1$ and hence $e^{\lambda\varepsilon}\leq1+2\lambda\varepsilon$. The final expression is obtained by substituting the value of λ. We get that $\Pr(E)\geq1-\alpha$, completing the proof of Claim 2.4. $\square$

Claim 2.5. $\mathop{\mathbb{E}}_{\substack{N\sim\mathsf{Po}(n)\\\mathbf{X}\sim P^{\otimes N}}}\left[\frac{\Pr[\mathcal{A}(\mathbf{X})\in[2k]]}{1+Y/k}\Big|E\right]\geq2.3\alpha.$

Proof. When event E occurs, $1+\frac{Y}{k}\leq1+e^3<22$. Then

$$\mathop{\mathbb{E}}_{N,\mathbf{X}}\left[\frac{\Pr[\mathcal{A}(\mathbf{X})\in[2k]]}{1+Y/k}\Big|E\right]>\mathop{\mathbb{E}}_{N,\mathbf{X}}\left[\frac{\Pr[\mathcal{A}(\mathbf{X})\in[2k]]}{22}\Big|E\right]=\frac{1}{22}\cdot\mathop{\mathbb{E}}_{N,\mathbf{X}}\left[\Pr[\mathcal{A}(\mathbf{X})\in[2k]]\mid E\right].$$
$$(10)$$

By the product rule,

$$\Pr[\mathcal{A}(\mathbf{X})\in[2k]]\mid E]=\frac{\Pr[\mathcal{A}(\mathbf{X})\in[2k]]\wedge E]}{\Pr[E]}\geq\Pr[\mathcal{A}(\mathbf{X})\in[2k]]\wedge E]\geq\Pr[\mathcal{A}(\mathbf{X})\in[2k]]-\Pr[\overline{E}].$$

Substituting this into (10) and recalling that $\alpha^*=60\alpha$, we get

$$\mathop{\mathbb{E}}_{N,\mathbf{X}}\left[\frac{\Pr[\mathcal{A}(\mathbf{X})\in[2k]]}{1+Y/k}\Big|E\right]\geq\frac{1}{22}\cdot\mathop{\mathbb{E}}_{N,\mathbf{X}}\left[\Pr[\mathcal{A}(\mathbf{X})\in[2k]]-\Pr[\overline{E}]\right]\geq\frac{1}{22}\cdot\left(\alpha^*-\alpha-\alpha\right)\geq2.3\alpha,$$

since sampler $\mathcal{A}$ is α-accurate on P, and P has mass α^* on $[2k]$, and by Claim 2.4. $\square$

Combining (1), (5), and (6), applying Claims 2.4 and 2.5, and recalling that $\delta\leq0.1\cdot\alpha\varepsilon/k$, we get

$$d_{TV}(P,Q_{\mathcal{A},P})\geq\Pr_{N,\mathbf{X}}[\mathcal{A}(\mathbf{X})\notin Supp(P)]\geq\frac{1}{2}\cdot\mathop{\mathbb{E}}_{N,\mathbf{X}}\left[\frac{\Pr[\mathcal{A}(\mathbf{X})\in[2k]]}{1+Y/k}\right]-\frac{k\delta}{\varepsilon}$$

$$\geq\frac{1}{2}\cdot\mathop{\mathbb{E}}_{N,\mathbf{X}}\left[\frac{\Pr[\mathcal{A}(\mathbf{X})\in[2k]]}{1+Y/k}\Big|E\right]\Pr(E)-0.1\alpha\geq\frac{1}{2}\cdot2.3\alpha\cdot\left(1-\alpha\right)-0.1\alpha>\alpha,$$

where the last inequality holds since $\alpha\leq0.02$. This contradicts α-accuracy of $\mathcal{A}$ on datasets of size $\mathsf{Po}(n)$, where $n\leq\frac{k}{\alpha^*\varepsilon}$, and completes the proof of Lemma 2.1. $\square$

References

[1] Jayadev Acharya, Ziteng Sun, and Huanyu Zhang. Differentially private Assouad, Fano, and Le Cam. In Vitaly Feldman, Katrina Ligett, and Sivan Sabato, editors, *Algorithmic Learning Theory, 16-19 March 2021, Virtual Conference, Worldwide*, volume 132 of *Proceedings of Machine Learning Research*, pages 48–78. PMLR, 2021.

[2] Brian Axelrod, Shivam Garg, Vatsal Sharan, and Gregory Valiant. Sample amplification: Increasing dataset size even when learning is impossible. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pages 442–451. PMLR, 2020.

[3] Tugkan Batu, Eldar Fischer, Lance Fortnow, Ravi Kumar, Ronitt Rubinfeld, and Patrick White. Testing random variables for independence and identity. In *Proceedings 42nd IEEE Symposium on Foundations of Computer Science*, pages 442–451. IEEE, 2001.

[4] Tugkan Batu, Lance Fortnow, Ronitt Rubinfeld, Warren D Smith, and Patrick White. Testing that distributions are close. In *Proceedings 41st Annual Symposium on Foundations of Computer Science*, pages 259–269. IEEE, 2000.

[5] Avrim Blum, Katrina Ligett, and Aaron Roth. A learning theory approach to noninteractive database privacy. *Journal of the ACM (JACM)*, 60(2):1–25, 2013.

[6] Mark Bun, Gautam Kamath, Thomas Steinke, and Zhiwei Steven Wu. Private hypothesis selection. In *Advances in Neural Information Processing Systems*, NeurIPS '19, pages 156–167, Vancouver, Canada, 2019. https://arxiv.org/abs/1905.13229.

[7] Mark Bun and Thomas Steinke. Concentrated differential privacy: Simplifications, extensions, and lower bounds. In *Theory of Cryptography Conference*, pages 635–658. Springer, 2016.

[8] Mark Bun, Jonathan Ullman, and Salil Vadhan. Fingerprinting codes and the price of approximate differential privacy. In *ACM Symposium on the Theory of Computing*, STOC '14, pages 1–10, New York, NY, USA, 2014. Preliminary version of [9].

[9] Mark Bun, Jonathan Ullman, and Salil Vadhan. Fingerprinting codes and the price of approximate differential privacy. *SIAM Journal on Computing*, 47(5):1888–1938, 2018.

[10] Ilias Diakonikolas, Moritz Hardt, and Ludwig Schmidt. Differentially private learning of structured discrete distributions. In *Advances in Neural Information Processing Systems*, pages 2566–2574, 2015.

[11] Christos Dimitrakakis, Blaine Nelson, Aikaterini Mitrokotsa, and Benjamin I. P. Rubinstein. Robust and private bayesian inference. In Peter Auer, Alexander Clark, Thomas Zeugmann, and Sandra Zilles, editors, *Algorithmic Learning Theory - 25th International Conference, ALT 2014, Bled, Slovenia, October 8-10, 2014. Proceedings*, volume 8776 of *Lecture Notes in Computer Science*, pages 291–305. Springer, 2014.

[12] Christos Dimitrakakis, Blaine Nelson, Zuhe Zhang, Aikaterini Mitrokotsa, and Benjamin I. P. Rubinstein. Differential privacy for bayesian inference through posterior sampling. *J. Mach. Learn. Res.*, 18:11:1–11:39, 2017.

[13] Cynthia Dwork, Krishnaram Kenthapadi, Frank McSherry, Ilya Mironov, and Moni Naor. Our data, ourselves: Privacy via distributed noise generation. In *International Conference on the Theory and Applications of Cryptographic Techniques*, EUROCRYPT '06, pages 486–503, St. Petersburg, Russia, 2006.

[14] Cynthia Dwork, Frank McSherry, Kobbi Nissim, and Adam Smith. Calibrating noise to sensitivity in private data analysis. In *Theory of cryptography conference*, pages 265–284. Springer, 2006.

[15] Cynthia Dwork and Adam Smith. Differential privacy for statistics: What we know and what we want to learn. *Journal of Privacy and Confidentiality*, 1(2):135–154, 2009.

[16] Cynthia Dwork, Adam D. Smith, Thomas Steinke, Jonathan R. Ullman, and Salil P. Vadhan. Robust traceability from trace amounts. In Venkatesan Guruswami, editor, *IEEE 56th Annual Symposium on Foundations of Computer Science, FOCS 2015, Berkeley, CA, USA, 17-20 October, 2015*, pages 650–669. IEEE Computer Society, 2015.

[17] Gautam Kamath, Jerry Li, Vikrant Singhal, and Jonathan R. Ullman. Privately learning high-dimensional distributions. In Alina Beygelzimer and Daniel Hsu, editors, *Conference on Learning Theory, COLT 2019, 25-28 June 2019, Phoenix, AZ, USA*, volume 99 of *Proceedings of Machine Learning Research*, pages 1853–1902. PMLR, 2019.

[18] Gautam Kamath and Jonathan Ullman. A primer on private statistics (parts i & ii). https://kamathematics.wordpress.com/2020/04/21/a-primer-on-private-statistics-part-ii/, April 2020.

[19] Shiva Prasad Kasiviswanathan and Adam D. Smith. On the 'semantics' of differential privacy: A bayesian formulation. *Journal of Privacy and Confidentiality*, 2014.

[20] Sofya Raskhodnikova, Dana Ron, Amir Shpilka, and Adam Smith. Strong lower bounds for approximating distribution support size and the distinct elements problem. *SIAM Journal on Computing*, 39(3):813–842, 2009.

[21] Thomas Steinke and Jonathan Ullman. Interactive fingerprinting codes and the hardness of preventing false discovery. In *Conference on learning theory*, pages 1588–1628. PMLR, 2015.

[22] Salil Vadhan. *The Complexity of Differential Privacy*, pages 347–450. Springer, 2017.

[23] Yu-Xiang Wang, Stephen E. Fienberg, and Alexander J. Smola. Privacy for free: Posterior sampling and stochastic gradient monte carlo. In Francis R. Bach and David M. Blei, editors, *Proceedings of the 32nd International Conference on Machine Learning, ICML 2015, Lille, France, 6-11 July 2015*, volume 37 of *JMLR Workshop and Conference Proceedings*, pages 2493–2502. JMLR.org, 2015.

[24] Stanley L. Warner. Randomized response: A survey technique for eliminating evasive answer bias. *Journal of the American Statistical Association*, 60(309):63–69, 1965.

[25] Zuhe Zhang, Benjamin I. P. Rubinstein, and Christos Dimitrakakis. On the differential privacy of bayesian inference. In Dale Schuurmans and Michael P. Wellman, editors, *Proceedings of the Thirtieth AAAI Conference on Artificial Intelligence, February 12-17, 2016, Phoenix, Arizona, USA*, pages 2365–2371. AAAI Press, 2016.