MissDAG: Causal Discovery in the Presence of Missing Data with Continuous Additive Noise Models

Abstract

State-of-the-art causal discovery methods usually assume that the observational data is complete. However, the missing data problem is pervasive in many practical scenarios such as clinical trials, economics, and biology. One straightforward way to address the missing data problem is first to impute the data using off-the-shelf imputation methods and then apply existing causal discovery methods. However, such a two-step method may suffer from suboptimality, as the imputation algorithm may introduce bias for modeling the underlying data distribution. In this paper, we develop a general method, which we call MissDAG, to perform causal discovery from data with incomplete observations. Focusing mainly on the assumptions of ignorable missingness and the identifiable additive noise models (ANMs), MissDAG maximizes the expected likelihood of the visible part of observations under the expectation-maximization (EM) framework. In the E-step, in cases where computing the posterior distributions of parameters in closed-form is not feasible, Monte Carlo EM is leveraged to approximate the likelihood. In the M-step, MissDAG leverages the density transformation to model the noise distributions with simpler and specific formulations by virtue of the ANMs and uses a likelihood-based causal discovery algorithm with directed acyclic graph constraint. We demonstrate the flexibility of MissDAG for incorporating various causal discovery algorithms and its efficacy through extensive simulations and real data experiments.

1 Introduction

Discovering the underlying causal relations among variables of interest often occupies a prominent position for supporting stable inference and rational decisions [42] in many applications such as medical diagnostics [49], recommendation systems [66] and economics [27]. To achieve this goal, conducting randomized controlled trials or using interventions is often acknowledged as the golden rule, which is effective but challenging in practice owing to high costs, ethical issues, or difficulties in obtaining compliance [48]. To address this issue, causal discovery from purely observational data, which may be more realistic in specific settings, has drawn considerable attention in both academic and industrial fields [60, 24, 23, 21].

Existing causal discovery methods, such as constraint-based methods [59, 13], score-based methods [12, 46], and methods based on functional causal models [54, 25, 73, 44], typically focus on the settings in which complete observations are available. However, in practice, datasets often suffer from missing values caused by various factors such as entry errors, deliberate non-responses, and sampling drops [31]. Following the definitions by Little and Rubin [31], the missing types can be categorized into three classes, namely missing completely at random (MCAR), missing at random (MAR), and missing not at random (MNAR), according to different missing mechanisms. Many previous efforts have focused specifically on figuring out more identifiable MNAR cases [6, 34, 37] and estimating the causal graphs from some specific MNAR cases [17, 64], while less attention has

Figure 1: Example of linear Gaussian model with equal noise variance. With zero-mean noises, the recovered covariance matrix $\hat{\Sigma}$ (sufficient statistic) can be a criterion for distribution recovery.

been paid to the M(C)AR cases as no extra assumption is required to recover the ground-truth data distribution from incomplete observations [52, 34].

To perform causal discovery in the M(C)AR case, a naive approach to handle the missing values is the listwise deletion method that simply drops the samples with missing value(s) in at least one of the variables. However, this may lead to unsatisfactory performance if the sample size is limited or the missing rate is high [61, 64] because of the decreased statistical power. Another straightforward approach is to impute those missing values instead of listwise deleting them. However, these imputation methods may introduce bias for modeling the underlying data distribution [29]. Moreover, as shown in Fig. (1), even though Gaussian-EM imputation method can consistently recover the data distribution as there is no model misspecification, it may lead to sub-optimal directed acyclic graph (DAG) estimation because it focuses solely on distribution recovery instead of structure learning. Therefore, a principled causal discovery approach that can handle the M(C)AR case is needed.

Contributions. In this work, we develop *a practical and general EM-based framework*, called MissDAG, to perform causal discovery in the presence of missing data, in which the underlying missing mechanism is independent from the observed information, which includes the M(C)AR case. Considering the data generating model, we focus on the identifiable additive noise models (ANMs) [44], including the linear non-Gaussian model [54], linear Gaussian model with equal noise variances [45], and nonlinear ANM [25, 44]; as a byproduct, our framework also accommodates the typical non-identifiable case, namely the linear Gaussian model with non-equal noise variances that can only be identified to Markov equivalence classes [59]. The resulting MissDAG framework flexibly accommodates different score based causal discovery algorithms [12, 75, 38, 72] developed for complete data and can be potentially extended to deal with more general cases (e.g., the log-determinant term is incorporated in the likelihood function). Moreover, we conduct extensive experiments on a variety of settings, including synthetic and real data, against many baselines to verify the effectiveness of MissDAG.

Related works. Previous BN learing with incomplete data [23, 58, 15, 16, 50] mainly inherit the Expectation-Maximization (EM) method framework [52], which conducts likelihood inference in an iterative optimization way. Friedman [15], Singh [58] iteratively refine the conditional distributions and sampling the missing values from these distributions. [63] proposed a data augmentation method by a stochastic simulation-based method that draws the filled-in value from a predictive distribution. The augmentation method was accelerated by recasting the problem into two phases, parent set identification by an exact search and structure optimization by an approximate algorithm [1]. However, existing BN learning methods from incomplete data focus on identifying the Markov equivalence classes (i.e., discrete cases) under suitable assumptions and usually formulate the structure learning problem as a discrete optimization program, while our work focuses on continuous identifiable ANMs of which the structure is fully identifiable and includes recent structure learning approaches based on continuous optimization. More related works and detailed comparison can be found in Appendix A.

2 Preliminaries

Additive noise models. We adopt the notion of structural causal model (SCM) [42, 43] to characterize the causal relations among variables. Each SCM $\mathcal{M} = \langle \mathcal{Z}, \mathcal{X}, \mathcal{F} \rangle$ consists of the exogenous variable set $\mathcal{Z} = \{Z_1, Z_2, \ldots, Z_d\}$, the endogenous variable set $\mathcal{X} = \{X_1, X_2, \ldots, X_d\}$, and the function set $\mathcal{F} = \{f_1, f_2, \ldots, f_d\}$. Here, each function f_i computes the variable X_i from its parents (or causes) $\mathbf{Pa}_{X_i}$ and an exogenous variable Z_i, i.e., $X_i = f_i(\mathbf{Pa}_{X_i}, Z_i)$. In this work, we focus on a

specific class of SCMs, called the ANMs [25, 44], given by

$$X_i = f_i(\mathbf{Pa}_{X_i}) + Z_i, \quad i = 1, 2, \ldots, d, \tag{1}$$

where Z_i, interpreted as the additive noise variable, is assumed to be independent with variables in $\mathbf{Pa}_{X_i}$ and mutually independent with variables in $\mathcal{Z} \backslash Z_i$.

Causal graph. Each SCM $\mathcal{M}$ induces a causal graph, which we assume in this work to be a DAG[1]. The DAG $\mathcal{G}_{\mathcal{M}} = (\mathbb{V}, \mathbb{E})$ consists of a vertex set $\mathbb{V} := \{1, 2, \ldots, d\}$, in which each node i corresponds to the variable X_i, and an edge set $\mathbb{E} \subseteq \mathbb{V}^2$ where $(i, j) \in \mathbb{E}$ if and only if $X_i \in \mathbf{Pa}_{X_j}$. Let $X = (X_1, X_2, \ldots, X_d)$ be a random vector that includes the variables in $\mathcal{X}$, and $P(X)$ (with density $p(x)$) be the joint distribution of random vector X. We assume that there are no latent common causes of the observed variables (i.e., *causal sufficiency*), which, together with the *acyclicity* assumption, indicates that $P(X)$ and induced DAG $\mathcal{G}_{\mathcal{M}}$ satisfy the causal Markov condition [42].

3 Problem definition

Notations. In this paper, we focus on the finite-sample setting with missing data. Consider a dataset $\mathcal{D} = (\mathbf{X}, \mathbf{Y})$ that consists of N samples, where $\mathbf{X} \in \mathbb{R}^{N \times d}$ and $\mathbf{Y} \in \mathbb{R}^{N \times d}$. Each row $(\mathbf{X}_i, \mathbf{Y}_i)$ is independently sampled from $P(X, Y)$ and represents the i-th sample. $\mathbf{Y}$ is the indicator matrix that records the missing position in $\mathbf{X}$, i.e., $\mathbf{Y}_{ij} = 0$ if $\mathbf{X}_{ij}$ is missing and $\mathbf{Y}_{ij} = 1$ otherwise. In the presence of missing data, the fully observed data $\mathbf{X}$ is unavailable. For simplicity, let $\mathbf{O}$ group all observed positions in $\mathbf{X}$ and $\mathbf{M}$ group all the missing positions. For each observation $\mathbf{X}_i$, let $\mathbf{o}$ group the indexes of the observed part and $\mathbf{m}$ group the indexes of the missing part of $\mathbf{X}_i$. Notice that $\mathbf{o}$ and $\mathbf{m}$ are different for different observations. Then, $\mathbf{X}_{\mathbf{O}} = [\mathbf{X}_{ij} : \mathbf{Y}_{ij} = 1, i \in [N], j \in [d]]$ includes all observed positions and $\mathbf{X}_{\mathbf{M}} = [\mathbf{X}_{ij} : \mathbf{Y}_{ij} = 0, i \in [N], j \in [d]]$[2] includes all missing positions in $\mathbf{X}$. Similarly, we have $\mathbf{X}_{i\mathbf{o}} = [\mathbf{X}_{ij} : \mathbf{Y}_{ij} = 1, j \in [d]]$ and $\mathbf{X}_{i\mathbf{m}} = [\mathbf{X}_{ij} : \mathbf{Y}_{ij} = 0, j \in [d]]$.

Following [31], we define the full likelihood of the i-th sample $(\mathbf{X}_{i\mathbf{o}}, \mathbf{Y}_i)$ as

$$\mathcal{L}_{\text{full}}(\mathbf{X}_{i\mathbf{o}}, \mathbf{Y}_i | \theta, \psi) = \int p(\mathbf{X}_{i\mathbf{o}}, \mathbf{X}_{i\mathbf{m}} | \theta) \, p(\mathbf{Y}_i | \mathbf{X}_{i\mathbf{o}}, \mathbf{X}_{i\mathbf{m}}, \psi) \, d\mathbf{X}_{i\mathbf{m}}, \tag{2}$$

where the parameters ψ govern the missing mechanisms and θ include all the model parameters. The ignorable likelihood of $\mathbf{X}_{i\mathbf{o}}$ is defined as

$$\mathcal{L}_{\text{ignorable}}(\mathbf{X}_{i\mathbf{o}} | \theta) = \int p(\mathbf{X}_{i\mathbf{o}}, \mathbf{X}_{i\mathbf{m}} | \theta) \, d\mathbf{X}_{i\mathbf{m}}. \tag{3}$$

Assumption 1 (Ignorable missingness [31]). *The inference about parameters θ based on the ignorable likelihood evaluated only by $\mathbf{X}_{i\mathbf{o}}$ is the same as inference for θ based on the full likelihood.*

Ignorable missingness [31] is important as it a common assumption that is required by EM-style algorithms and also our method. It can be interpreted as a belief that the available data is sufficient to "correct" the missing data, by assuming that the missingness and model parameters are distinct.

Task definition. Consider a distribution $P(X, Y)$, where the marginal distribution $P(X)$ is induced from a SCM $\mathcal{M}$ satisfying the assumption of ANM as defined in Eq. (1), and a dataset $\mathcal{D} = (\mathbf{X}, \mathbf{Y})$. In practice, the observed distribution is only $P(X_o, Y)$ satisfying Assumption 1 and the observational part of the dataset is $\widetilde{\mathcal{D}} = (\mathbf{X}_{\mathbf{O}}, \mathbf{Y})$. Our task is learn the DAG $\mathcal{G}_{\mathcal{M}}$ from the dataset $\widetilde{\mathcal{D}}$.

4 MissDAG

In this section, we introduce our proposed method, MissDAG, which leverages the penalized EM framework to iteratively identify the causal graph $\mathcal{G}_{\mathcal{M}}$ and model parameters from the incomplete data $\widetilde{\mathcal{D}}$. In the M-step, MissDAG takes the log-likelihood of the observational part of the sample and applies a penalty function as the score function to search for the model parameters. Instead of

---

[1]Indeed, there may be difference between a DAG and a causal graph–the directed edges of the latter is given a causal meaning that allows it to answer interventional queries [28].

[2]We use $[N] = \{1, 2, \ldots, N\}$ to represent the set of all integers from 1 to N.

directly modelling the complex likelihood of the sample, MissDAG equivalently models the simpler noise distributions by the density transformation [35] since ANMs always limit the noise distributions to some specific distribution families. Moreover, the prior information of causal structure is also considered as an inductive bias to reduce the variance of parameter estimation. In the E-step, the log-likelihood function is integrated over the posterior of missing entries to obtain the expectation if the closed-form of the posterior is available. Otherwise, Monte Carlo (MC) simulations [67] are adopted to numerically compute the expectation. The details are shown in the following subsections.

4.1 The overall framework of MissDAG

Leveraging the development of score based causal discovery methods, we follow the style that taking the log-likelihood of observations (only the observational part) and a penalty function as the score function. Then, the general form of the optimization problem can be written as

$$\arg\max_{\theta} \ \mathcal{S}(\theta) = \log p(\mathbf{X_O}|\theta) - \lambda \, \mathbf{PEN}(\theta),$$
$$\text{subject to} \ \ \theta_{\mathcal{G}} \in \mathbf{DAGs}, \tag{4}$$

where $\theta = (\theta_{\mathcal{G}}, \theta_{\mathcal{F}})$, including a graph learning part $\theta_{\mathcal{G}}$ and a causal mechanisms learning part $\theta_{\mathcal{F}}$, denotes the parameters of an SCM $\mathcal{M}$. However, in some methods [75, 76, 38], $\theta_{\mathcal{G}}$ can be absorbed into and induced from $\theta_{\mathcal{F}}$. $\mathbf{PEN}(\cdot)$ is the penalty function and λ is the penalty coefficient. With the i.i.d. assumption of each sample $(\mathbf{X}_i, \mathbf{Y}_i)$, the score function $\mathcal{S}(\theta)$ can be written as

$$\mathcal{S}(\theta) = \sum_{i=1}^{N} \log \int p(\mathbf{X}_{i\mathbf{o}}, \mathbf{X}_{i\mathbf{m}}|\theta) \, \mathrm{d}\mathbf{X}_{i\mathbf{m}} - \lambda \, \mathbf{PEN}(\theta). \tag{5}$$

Unfortunately, the closed-form solution of $\mathcal{S}(\theta)$ cannot be obtained. Since the score function in Eq. (4) gives rise to a penalized maximum likelihood estimation problem, we can take the iterative penalized EM method [11], which relates the parameters estimation of the SCM from $\log p(\mathbf{X_O}|\theta)$ to the same parameters estimation from the complete-data log-likelihood $\log p(\mathbf{X}|\theta)$.

Different from the imputation methods that replace the missing entries $\mathbf{X_M}$ by some specific values, EM based methods formulate a two-step iterative operation: (1) the E-step takes the estimated model parameters of the previous step and the observational part $\mathbf{X_O}$ to impute the missing entries by the distribution of $\mathbf{X_M}$, which, in other words, gets the expected log-likelihood of the complete-data. (2) the M-step maximizes the complete-data log-likelihood $\log p(\mathbf{X}|\theta)$. Here, let θ^t denote the estimated parameters in the t-th iteration. Then, we define the $\mathcal{Q}$ function as

$$\mathcal{Q}(\theta|\theta^t) = \int p(\mathbf{X_M}|\mathbf{X_O}, \theta^t) \log p(\mathbf{X_O}, \mathbf{X_M}|\theta) \, \mathrm{d}\mathbf{X_M} - \lambda \, \mathbf{PEN}(\theta)$$
$$= \mathbb{E}_{X_m|X_o, \theta^t} \left\{ \log p(\mathbf{X_O}, \mathbf{X_M}|\theta) \right\} - \lambda \, \mathbf{PEN}(\theta). \tag{6}$$

The E-step calculates the expected data log-likelihood $\mathcal{Q}(\theta|\theta^t)$. The following M-step, then, maximizes $\mathcal{Q}(\theta|\theta^t)$ in θ for the fixed θ^t, i.e., gets $\theta^{(t+1)} = \arg\max_{\theta} \mathcal{Q}(\theta|\theta^t)$ with DAG constraint. The convergence analysis of MissDAG is provided in Appendix E.

4.1.1 Log-likelihood term of $\mathcal{S}(\theta)$

The final problem comes to the exact formulation of $p(\mathbf{X}|\theta)$, which is not straightforward to obtain in our problem since ANMs typically impose assumptions on the noise distribution instead of the joint distribution $P(X)$. Benefiting from the well-researched results of the change of variables rule of density transformation [35], we can equivalently formulate $p(\mathbf{X}|\theta)$ by transforming it to $p(\mathbf{Z}|\theta)$. Here, for simplicity, we take $Z = (Z_1, Z_2, \ldots, Z_d)$ and $f = (f_1, f_2, \ldots, f_d)$. Then, we have

$$p_X(X) = p_Z(X - f(X))|\det(\mathbf{I} - \mathbf{J}_f)|, \tag{7}$$

where $\mathbf{I}$ is the identity matrix and $\mathbf{J}_f$ represents the Jacobian of f evaluated on X.

Proposition 1. *If $\theta_{\mathcal{G}}$ represents a DAG, then $|\det(\mathbf{I} - \mathbf{J}_f)| = 1$.*

The proof is included in Appendix B.1. With Proposition 1, the log-determinant term becomes zero if the candidate solution is acyclic and can be dropped to simplify Eq. (8). However, we would also like to point out that some recent score-based structure learning methods based on continuous optimization,

158 e.g., GOLEM [38] and NOTEARS-ICA [74], have shown that including the log-determinant term
159 (which corresponds to likelihood based on directed cyclic graphs) in its objective function may be
160 desirable and lead to better performance. In this work, this term is ignored since only acyclic models
161 are considered. Then, with Eq. (7) and Proposition 1, we can model the log-likelihood of the simpler
162 mutually independent noises distributions. Then, we have

$$\mathcal{L}(\mathbf{X}_i|\theta) = \sum_{j=1}^{d} \log p_{Z_i}(\mathbf{X}_{ij} - f_j(\mathbf{X}_i)) + \log|\det(\mathbf{I} - \mathbf{J}_f)| = \sum_{j=1}^{d} \log p_{Z_i}(\mathbf{X}_{ij} - f_j(\mathbf{X}_i)). \quad (8)$$

164 In the E-step, with different data generation models, the exact formulation of the posterior may be
165 unavailable. Therefore, we split up these two cases for presentations.

4.2 Exact posterior

167 Firstly, we deal with the linear Gaussian models including linear Gaussian model with equal variance
168 (LGM-EV) and linear Gaussian model with non-equal variance (LGM-NV). That is to say, in Eq. (1),
169 each $f_i \in \mathcal{F}$ is a linear function and $Z_i \sim \mathcal{N}(0, \sigma_i^2)$ with $\Sigma_Z = \text{diag}(\sigma_1^2, \sigma_2^2, \ldots, \sigma_d^2)$. Then, the
170 model can be rewritten as

$$X = W^T X + Z, \quad (9)$$

171 where $W \in \mathbb{R}^{d \times d}$ is the weight matrix and $W_{ij} \neq 0$ means that X_i is one of the causes of X_j.
172 Based on the density of a linear transformation, we know $P(X)$ belongs to a multivariate Gaussian
173 distribution. For multivariate Gaussian, sufficient statistics consist of the mean vector $\mu(X)$ (the
174 first-order moment) and the covariance matrix $\text{cov}(X)$ (the second-order moment). With zero-mean
175 assumption of Z, we have $\mu(X) = \mathbf{0}$ and estimate $\text{cov}(X)$ by $\mathbf{T}$. In other words, we can equivalently
176 replace $p(\mathbf{X}|\theta)$ by $p(\mathbf{T}|\theta)$. Specifically, with full data, $\mathbf{T}$ can be directly calculated by $\mathbf{T} = \frac{1}{N}\mathbf{X}^T\mathbf{X}$.

177 In this case, we specify $\theta = (W, \Sigma_Z)$ since the two parameters can govern the distribution $P(X)$.
178 According to Eq. (8), the complete log-likelihood $\mathcal{L}(\mathbf{X}|W, \Sigma_Z)$ can be sufficiently formulated by

$$\mathcal{L}(\mathbf{X}|W, \Sigma_Z) = \log p(\mathbf{T}|W, \Sigma_Z)$$
$$= -\frac{1}{2}\text{Tr}(\log \Sigma_Z) - \frac{1}{2N}\text{Tr}((\mathbf{I} - W)^T \mathbf{T}(\mathbf{I} - W)\Sigma_Z) - \frac{d}{2}\log 2\pi. \quad (10)$$

180 Since (10) is linear in $\mathbf{T}$, the $\mathcal{Q}$ function can be formulated in a closed-form.

4.2.1 E-step: compute $\mathcal{Q}(W, \Sigma_Z \mid W^t, \Sigma_Z^t)$

182 As discussed before, the E-step calculates the expected log-likelihood $\log p(\mathbf{T}|W, \Sigma_Z)$ with $\mathbf{X_O}$ and
183 (W^t, Σ_Z^t). From Eq. (9), we have $X = (\mathbf{I} - W^T)^{-1}Z$. Then, the implicit parameter Σ_X^t can be
184 estimated by $\Sigma_X^t = (\mathbf{I} - W)^{-T}\Sigma_Z^t(\mathbf{I} - W)^{-1}$. Then, $\mathbf{T}^t = \mathbb{E}[\mathbf{T} \mid \mathbf{X_O}, \Sigma_X^t]$ can be straightforwardly
185 calculated by the well-known results on the conditional distributions of the multivariate Gaussian.
186 Each entry of $\mathbf{T}^t$ is obtained by $\mathbf{T}_{ij}^t = [\frac{1}{N}\sum_{k=1}^{N} \xi_k \mid \mathbf{X_O}, \Sigma_X^t]$, where

$$\xi_k = \begin{cases} \Sigma_{Xij}^t + \hat{\mathbf{X}}_{ki}\hat{\mathbf{X}}_{kj} & \text{if } \mathbf{X}_{ki} \& \mathbf{X}_{kj} \text{ are missing.} \\ \hat{\mathbf{X}}_{ki}\hat{\mathbf{X}}_{kj} & \text{Otherwise.} \end{cases} \quad (11)$$

187 $\hat{\mathbf{X}}_k$ records the expectation of missing part of the k-th instance $\mathbf{X}_k$ and also shares the same indexes
188 with $\mathbf{X}_k$. $\hat{\mathbf{X}}_k$ is initialized as $\mathbf{X}_k$. Then, $\hat{\mathbf{X}}_{k\mathbf{m}} = \Sigma_{X\mathbf{mo}}^t \Sigma_{X\mathbf{o}^{-1}\mathbf{o}}^t \mathbf{X}_{k\mathbf{o}}$.

4.2.2 M-step: maximize $\mathcal{Q}(W, \Sigma_Z \mid W^t, \Sigma_Z^t)$

190 With $\mathbf{T}^t$, the M-step maximizes the score $\mathcal{S}(\theta)$ with $\mathcal{L}(\mathbf{T}^t|W, \Sigma_Z) = \log p(\mathbf{T}^t|W, \Sigma_Z)$. Here, we
191 also plug in the DAG constraint for optimization to ensure that the estimated graph is acyclic. Then,
192 the overall optimization problem can be formulated as

$$W^{t+1}, \Sigma_Z^{t+1} = \arg\max_{W, \Sigma_Z} \mathcal{L}(\mathbf{T}^t|W, \Sigma_Z) + \lambda \mathbf{PEN}(W), \quad (12)$$
$$\text{subject to } \mathcal{G}_W \in \mathbf{DAGs},$$

where $\mathcal{G}_W$ means the graph induced from W. Here, we do not restrict the use of any specific algorithm for solving this problem. For the LGM-EV, one can adopt the greedy search method by Peters and Bühlmann [45], GOLEM [38], or NOTEARS [75] to estimate the DAG $\mathcal{G}$, while for the LGM-NV, one can apply different search methods like GES [12], A* [72], and GOLEM [38]. Notice that, score based methods based on continuous optimization (e.g., NOTEARS, GOLEM) may suffer from the preprocessed or scaled observations [47]; see Appendix G for a detailed discussion.

4.3 Approximate posterior

Unfortunately, for Non-Linear (NL)-ANMs and Linear Non-GAussian Model (LiNGAM) cases, the E-step is not available in a closed-form, which would make the likelihood inference for missing data more difficult. There are mainly two problems to compute the expectation: (1) computing the posterior distribution $p(\mathbf{X}_{im}|\mathbf{X}_{io}, \theta^t)$; (2) computing the integral. Since the problem mainly comes from the noise modeling as we later show, we prefer to first introduce the M-step of our method.

4.3.1 M-step: maximize $\mathcal{Q}(\theta \mid \theta^t)$

From Eq. (8), we know that two reasons lead to the non-closed-form for integral. The first one is that f includes some complex non-linear functions. However, considering the likelihood issue, the non-linearity problem can be well handled by taking neural networks to model f [76, 40, 30]. Therefore we leave f for both linear and non-linear models for brevity. The second problem is non-Gaussian noise, which needs to be clarified before the M-step.

The problem of $p_Z(Z)$. If noises are non-Gaussian, the exact formulation of each noise distribution is unknown. To make the likelihood-based methods work, a fixed Super (Sub)-Gaussian prior distribution can be set to model the noise distributions [26, 76]. The theoretical result that the maximum likelihood estimate is locally consistent even in the presence of small misspecification error is well-established [2]. Here, we take the Super-Gaussian distribution as an example:

$$p_i(Z_i) = c_Z \exp\left(-2\log\cosh\left(Z_i\right)\right), \tag{13}$$

where c_Z is a constant. Notice that using (13) needs to assume the unit scale of noise, which may not hold for the real scenarios. Therefore, we prefer to take a normalized likelihood for standardized noise variable Z_i/σ_i. Then, the standardized log-likelihood[3] of the observation $\mathbf{X}_i$ will be

$$\mathcal{L}_{\text{standardized}}(\mathbf{X}_i|\theta) = \sum_{j=1}^{d} \log p_{Z_j}\left(\frac{\mathbf{X}_{ij} - f_j(\mathbf{X}_i)}{\hat{\sigma}_j}\right) - \log\hat{\sigma}_j, \tag{14}$$

where $\sigma_j^2 = \text{Var}(Z_j)$ is the variance of noise Z_j with empirical version of $\hat{\sigma}_j^2 = \frac{1}{N}\sum_{j=1}^{N}(\mathbf{X}_{:,j} - f_j(\mathbf{X}))^2$. Then, Eq. (14) can serve as the log-likelihood term and the overall optimization problem in the M-step can be written as

$$\theta^{t+1} = \arg\max_\theta \ \mathcal{L}_{std}(\mathbf{X}^t|\theta) - \lambda \, \mathbf{PEN}(\theta), \tag{15}$$

$$\text{subject to } \theta_\mathcal{G} \in \mathbf{DAGs},$$

where $\mathcal{L}_{\text{standardized}}(\mathbf{X}^t|\theta)$ represents the expected log-likelihood function in the t-th iteration.

4.3.2 E-step: compute $\mathcal{Q}(\theta \mid \theta^t)$

The problem of the integral. For LiNGAM and NL-ANM, there is no closed-form for the integral to get the expectation of log-likelihood in the E-step. Naturally, we take the Monte Carlo Sampling method [51] to approximate the expectation. Then, Eq. (6) can be reformulated as

$$\mathcal{Q}(\theta|\theta^t) = \mathbb{E}_{X_m|X_o,\theta^t}\left\{\log p(\mathbf{X_O}, \mathbf{X_M} \mid \theta)\right\} = \sum_{i=1}^{N}\sum_{j=1}^{N_s} \log p(\mathbf{X}_{io}, x_{im}^{(j)} \mid \theta), \tag{16}$$

where $x_{im}^{(j)}$, sampled from the posterior, represents the j-th value of the total N_s sampling results for the missing part $\mathbf{X}_{im}$ of the observation $\mathbf{X}_i$.

---

[3]The term "standardized log-likelihood" is taken to follow the literature of independent component analysis.

(a) LGM-EV.   (b) LGM-NV.

Figure 2: Recovery of the true structure measured by SHD or SHD-CPDAG ($\downarrow$). (a) LGM-EV with $d = 20$. (b) LGM-NV with $d = 15$ since the searching time of A* is too long. Rows: ER1, ER2, and SF2 graphs. Columns: different methods. Some results for Gaussian-EM imputation are truncated because its SHDs are too large in those cases.

The problem of sampling from the posterior. Instead of directly sampling from $p(\mathbf{X}_{i\mathbf{m}}|\mathbf{X}_{i\mathbf{o}}, \theta^t)$ to fill the missing part $\mathbf{X}_{i\mathbf{m}}$, we use rejection sampling [8] to sample from a proposal distribution $Q(X_{\mathbf{m}})$ with the probability density function $q(X_{\mathbf{m}})$, from which we can readily draw samples. Then, a constant c_k is set to guarantee that $c_k q(X_{\mathbf{m}}) \geq p(\mathbf{X}_{i\mathbf{m}}|\mathbf{X}_{i\mathbf{o}}, \theta^t)$ for $\forall X_{\mathbf{m}}$. For each sample $x_{\mathbf{m}}^j$ from $q(X_{\mathbf{m}})$, the accept rate would be $p_{\text{accept}} = \frac{p(x_{\mathbf{m}}^j|\mathbf{X}_{i\mathbf{o}}, \theta^t)}{c_k q(x_{\mathbf{m}}^j)}$. However, $p(\mathbf{X}_{i\mathbf{m}}|\mathbf{X}_{i\mathbf{o}}, \theta^t)$ can not be directly obtained. With Bayes Rule, we have

$$p(\mathbf{X}_{i\mathbf{m}}|\mathbf{X}_{i\mathbf{o}}, \theta^t) = \frac{p(\mathbf{X}_i, \theta^t)}{p(\mathbf{X}_{i\mathbf{o}}, \theta^t)}, \tag{17}$$

while for each instance $\mathbf{X}_i$, $p(\mathbf{X}_{i\mathbf{o}}, \theta^t)$ is a constant marked as c_o. However, the posterior of joint distribution $p(\mathbf{X}_i, \theta^t)$ is still not directly available. With Eq. (7) and Proposition 1, we find that we may skip for obtaining the closed-form of $p(\mathbf{X}_i, \theta^t)$ but equivalently provide the value of $p_Z(\mathbf{Z}_i, \theta^t)$:

$$p(\mathbf{X}_i, \theta^t) = |\det(\mathbf{I} - \mathbf{J}_{\theta_f^t})| p_Z(\mathbf{Z}_i, \theta^t) = \prod_{j=1}^{d} p_Z(\mathbf{X}_{ij} - \theta_{f_j}^t(\mathbf{X}_i)). \tag{18}$$

Then, just like in the M-step, we take a normalized distribution to model the noise distributions. Then, the probability that a sample can be accepted is given by

$$p_{\text{accept}} = \frac{\prod_{j=1}^{d} p_Z(\mathbf{X}_{ij} - \theta_{f_j}^t(\mathbf{X}_i))}{c_o c_k q(x_{\mathbf{m}}^j)}. \tag{19}$$

Here, we take $c_r = c_o c_k$ as a re-normalized constant to activate the rejection sampling methods.

5   Experiments

We report the empirical results to verify the effectiveness of MissDAG on both synthetic and a biological dataset.

Baselines. We mainly take imputation methods as baselines including Mean Imputation, MissForest Imputation [62], and Optimal Transport (OT)-imputation [36] to impute the incomplete data at first,[4] and then apply the causal discovery methods including GOLEM [38], NOTEARS [75], the algorithm ('Ghoshal') by Ghoshal and Honorio [20], NOTEARS-MLP [76], and NOTEARS-ICA [74] to estimate the causal graph for different assumed models (see Appendix D for details.). For LGM, we also include the structural EM method for multivariate Gaussian distribution, which we called Gaussian-EM imputation, to recover the complete data. For LGM-NV that aims to identify the

---

[4]Results on more imputation methods including GAIN [69], KNNImputer [3], MICE [68] are shown in Appendix F.1.

Figure 3: Results of LiNGAM.   Figure 4: Results of NL-ANMs.   Figure 5: Dream4 results.

Complete Partial DAG (CPDAG), we also include different searching methods such as A* [72, 39] and
GES [12] to solve the optimization problem of the M-step. Also, we include the Test-wise Deletion
PC (TD-PC) as a baseline for LGM-NV. For LiNGAM, we also use ICA-LiNGAM and Direct-
LiNGAM as baseline methods and put the results in Appendix F.7.2. The detailed implementations
of the imputation and structure learning methods, as well as the hyperparameters of the proposed
method, are presented in Appendix C.[5]

Metrics. We report the widely used criterion named Structural Hamming Distance (SHD), which
refers to the smallest number of edge additions, deletions, and reversals required to transform the
recovered DAG into the true one, averaged over 10 random repetitions to assess how the edges differ
between the estimated and ground-truth DAG in the identifiable cases. For the non-identifiable case
such as LGM-NV, we report the SHD-CPDAG to measure the distances between different CPDAGs.
Other criteria such as F1 and recall are included for the supplementary experiments in Appendix F.

5.1 Synthetic data

Simulations. The synthetic data we consider here is generated according to the ANM in Eq. (1).
As illustrated above, we consider four cases, including LGM-EV, LGM-NV, LiNGAM, and NL-
ANM. In each experiment, a ground-truth DAG $\mathcal{G}$ with d nodes and kd directed edges was first
generated from one of the two graph models, Erdős-Rényi (ER) or Scale-Free (SF). According to
different edges, kd edges ($k = 1, 2$), the graph model is named ERk or SFk. We also simulate
denser graphs in Appendix F.6. Then, for linear models, a weighted matrix $W \in \mathbb{R}^{d \times d}$ with
coefficients sampled from $\mathrm{Uniform}([-2.0, -0.5] \cup [0.5, 2.0])$ with equal probability is generated
to assign values to each edge in $\mathcal{G}$. For the non-linear model, corresponding to each edge in $\mathcal{G}$,
a f_i is constructed from a fixed MLP with random coefficients. The non-Gaussian noise we take
here follows a Gumbel distribution. Experimental results on more different non-linear functions
and different noise distributions are included in Appendix F.8 and Appendix F.7.1, respectively. In
equal variance/scale sets, all independent noises belongs to their distributions with variance/scale as
1 while non-equal variance/scale settings get the scale of each noise independently sampled from
$\mathrm{Uniform}[1.0, 2.0]$. For each experiment, we sample 100 observations for linear models and 200
observations for non-linear models. More results on different numbers of samples with fixed number
of nodes and different numbers of nodes with the fixed number of samples are shown in Appendix F.3
and Appendix F.4, respectively. We also add the experiment with d nodes and $2d$ observations with
run-time comparisons in Appendix F.5. The missing type in our experiments is MCAR while the
results on MAR and MNAR are also implemented in Appendix F.2.

Linear Gaussian case. In Fig. (2a), across all settings for LGM-EV, including different graphs
and missing rates, MissDAG with GOLEM, NOTEARS and Ghoshal as baseline methods can show
consistently the best performance or performance comparable to the best performances. While all
imputation methods are sensitive to different baseline methods, all NOTEARS-based methods show
improvements compared to GOLEM-based methods although GOLEM is the real full likelihood
method for LGM. However, GOLEM solves the problem by soft-constraint, which may suffer from the

---

[5]Our code is available at `https://github.com/s9aida3nw1sjq/anonymous-submission`.

(a) Ground truth. (b) Optimization process; $W^{(n)}$ refers to estimated graph in n-th EM iteration.

(c) LGM-EV.

Figure 6: Visualizations of the optimization process.

finite sample. For imputation methods, we can see that MissForest usually acquires the second-best place. Gaussian-EM imputation can consistently recover the real multivariate Gaussian distribution, but its performance varies a lot with different causal discovery methods. With NOTEARS, Gaussian-EM imputation can gain better, even the best results comparing to others. The results of LGM-NV are shown in Fig. (2b). Three different searching strategies are considered. We can see that MissDAG can still achieve the best performances across all settings. The capacities of A* and GES are limited by the finite observations while GES gets the worst results. Moreover, A*, an exact search method, suffers from high computing complexity.

Visualization of the learned DAG of MissDAG. We take an example of the MissDAG optimization process on LGM-EV and plot the change in estimated parameters in Fig. (6), which shows that the learned causal graph asymptotically approximates the ground-truth DAG $\mathcal{G}$, including the existence of edges and their weights. The data distribution can also be well recovered.

LiNGAM and NL-ANM. Fig. (3) shows the performances of MissDAG and different baseline methods with NOTEARS-ICA as the causal discovery algorithm on LiNGAM while Fig. (4) provides the results on NL-ANM of 20 variables. One can see that MissDAG still shows a consistent advantage over other methods across all settings. MissForest [62] always shows the second-best performance. Especially for NL-ANMs, MissForest can get comparable results to MissDAG.

5.2 Biological dataset

We take a biological dataset named Dream4 and provided in [22], which simulates gene expression measurements from five sub-networks of transcriptional regulatory networks of E. coli and S. cerevisiae. Here we consider the 10-node networks, which however include feedback loops. We can see that MissDAG occupies the first place for most of the settings and LGM is more suitable to learn from this dataset. The results in Fig. (5) show that there are mis-specifications between our models and real data, probably due to the cycles in the real data.

6 Conclusion

In this paper, we propose a new approach named MissDAG to learn the underlying causal relations from incomplete data. MissDAG, leveraging the EM-based paradigm, iteratively maximizes the likelihood of the observational part of data with the inductive bias of DAG structure. Existing score-based causal discovery methods can be directly integrated into our framework for graph and model parameter learning. Moreover, MCEM is introduced to address the challenge that the closed-form posterior of missing entries is unavailable. The experiments show that our method works well across various of settings. However, our method inherits the time inefficiency issue of EM algorithm. Future works include (1) improving the sampling efficiency with more efficient sampling or variational inference techniques to approximate the posterior to scale up to larger problems, (2) incorporating other advanced causal discovery methods into the MissDAG framework, and (3) allowing unobserved confounders and cycles, e.g., using the methods by Bhattacharya et al. [7], Ghassami et al. [19].

References

[1] Tameem Adel and Cassio P De Campos. Learning bayesian networks with incomplete data by augmentation. In *Association for the Advancement of Artificial Intelligence*, 2017.

[2] Shun-ichi Amari, Tian-Ping Chen, and Andrzej Cichocki. Stability analysis of learning algorithms for blind source separation. *Neural Networks*, 10(8):1345–1351, 1997.

[3] Rebecca R Andridge and Roderick JA Little. A review of hot deck imputation for survey non-response. *International Statistical Review*, 78(1):40–64, 2010.

[4] Dimitri P Bertsekas. *Constrained Optimization and Lagrange Multiplier Methods*. Academic Press, 1982.

[5] Dimitri P Bertsekas. *Nonlinear Programming*. Athena Scientific, 2nd edition, 1999.

[6] Rohit Bhattacharya, Razieh Nabi, Ilya Shpitser, and James M Robins. Identification in missing data models represented by directed acyclic graphs. In *Uncertainty in Artificial Intelligence*, pages 1149–1158. PMLR, 2020.

[7] Rohit Bhattacharya, Tushar Nagarajan, Daniel Malinsky, and Ilya Shpitser. Differentiable causal discovery under unmeasured confounding. In *International Conference on Artificial Intelligence and Statistics*, 2021.

[8] Christopher M. Bishop. *Pattern Recognition and Machine Learning*. Springer, 2006.

[9] Philippe Brouillard, Sébastien Lachapelle, Alexandre Lacoste, Simon Lacoste-Julien, and Alexandre Drouin. Differentiable causal discovery from interventional data. In *Advances in Neural Information Processing Systems*, 2020.

[10] Tony Cai, Weidong Liu, and Xi Luo. A constrained l1 minimization approach to sparse precision matrix estimation. *Journal of the American Statistical Association*, 106(494):594–607, 2011.

[11] Lin S Chen, Ross L Prentice, and Pei Wang. A penalized em algorithm incorporating missing data mechanism for gaussian parameter estimation. *Biometrics*, 70(2):312–322, 2014.

[12] David Maxwell Chickering. Optimal structure identification with greedy search. *Journal of Machine Learning Research*, 3(Nov):507–554, 2002.

[13] Diego Colombo, Marloes Maathuis, Markus Kalisch, and Thomas Richardson. Learning high-dimensional directed acyclic graphs with latent and selection variables. *The Annals of Statistics*, 40:294–321, 2011.

[14] Jerome Friedman, Trevor Hastie, and Robert Tibshirani. Sparse inverse covariance estimation with the graphical Lasso. *Biostatistics*, 9:432–41, 2008.

[15] Nir Friedman. Learning belief networks in the presence of missing values and hidden variables. In *International Conference on Machine Learning*, 1997.

[16] Nir Friedman. The bayesian structural em algorithm. In *Conference on Uncertainty in Artificial Intelligence*, pages 129–138, 1998.

[17] Alexander Gain and Ilya Shpitser. Structure learning under missing data. In *International Conference on Probabilistic Graphical Models*, pages 121–132. PMLR, 2018.

[18] Tomas Geffner, Javier Antoran, Adam Foster, Wenbo Gong, Chao Ma, Emre Kiciman, Amit Sharma, Angus Lamb, Martin Kukla, Nick Pawlowski, et al. Deep end-to-end causal inference. *arXiv preprint arXiv:2202.02195*, 2022.

[19] AmirEmad Ghassami, Alan Yang, Negar Kiyavash, and Kun Zhang. Characterizing distribution equivalence and structure learning for cyclic and acyclic directed graphs. In *International Conference on Machine Learning*, 2020.

[20] Asish Ghoshal and Jean Honorio. Learning linear structural equation models in polynomial time and sample complexity. In *International Conference on Artificial Intelligence and Statistics*, pages 1466–1475. PMLR, 2018.

[21] Clark Glymour, Kun Zhang, and Peter Spirtes. Review of causal discovery methods based on graphical models. *Frontiers in Genetics*, 10:524, 2019.

[22] Alex Greenfield, Aviv Madar, Harry Ostrer, and Richard Bonneau. Dream4: Combining genetic and dynamic information to identify biological networks and dynamical models. *PloS one*, 5 (10):e13397, 2010.

[23] David Heckerman. A tutorial on learning with bayesian networks. *Innovations in Bayesian networks*, pages 33–82, 2008.

[24] David Heckerman, Christopher Meek, and Gregory Cooper. A bayesian approach to causal discovery. In *Innovations in Machine Learning*, pages 1–28. Springer, 2006.

[25] Patrik Hoyer, Dominik Janzing, Joris M Mooij, Jonas Peters, and Bernhard Schölkopf. Nonlinear causal discovery with additive noise models. In *Advances in Neural Information Processing Systems*, 2008.

[26] Aapo Hyvärinen, Kun Zhang, Shohei Shimizu, and Patrik O Hoyer. Estimation of a structural vector autoregression model using non-gaussianity. *Journal of Machine Learning Research*, 11 (5), 2010.

[27] Guido W Imbens and Donald B Rubin. *Causal inference in statistics, social, and biomedical sciences*. Cambridge University Press, 2015.

[28] Daphne Koller and Nir Friedman. *Probabilistic graphical models: principles and techniques*. MIT press, 2009.

[29] Trent Kyono, Yao Zhang, Alexis Bellot, and Mihaela van der Schaar. Miracle: Causally-aware imputation via learning missing data mechanisms. In *Advances in Neural Information Processing Systems*, volume 34, 2021.

[30] Sébastien Lachapelle, Philippe Brouillard, Tristan Deleu, and Simon Lacoste-Julien. Gradient-based neural dag learning. In *International Conference on Learning Representations*, 2020.

[31] Roderick JA Little and Donald B Rubin. *Statistical analysis with missing data*, volume 793. John Wiley & Sons, 2019.

[32] Chao Ma and Cheng Zhang. Identifiable generative models for missing not at random data imputation. *Advances in Neural Information Processing Systems*, 34:27645–27658, 2021.

[33] Imke Mayer, Julie Josse, Félix Raimundo, and Jean-Philippe Vert. Missdeepcausal: Causal inference from incomplete data using deep latent variable models. *arXiv preprint arXiv:2002.10837*, 2020.

[34] Karthika Mohan and Judea Pearl. Graphical models for processing missing data. *Journal of the American Statistical Association*, pages 1–16, 2021.

[35] Joris M Mooij, Dominik Janzing, Tom Heskes, and Bernhard Schölkopf. On causal discovery with cyclic additive noise model. In *Advances in Neural Information Processing Systems*, 2011.

[36] Boris Muzellec, Julie Josse, Claire Boyer, and Marco Cuturi. Missing data imputation using optimal transport. In *International Conference on Machine Learning*, pages 7130–7140. PMLR, 2020.

[37] Razieh Nabi, Rohit Bhattacharya, and Ilya Shpitser. Full law identification in graphical models of missing data: Completeness results. In *International Conference on Machine Learning*, pages 7153–7163. PMLR, 2020.

[38] Ignavier Ng, AmirEmad Ghassami, and Kun Zhang. On the role of sparsity and dag constraints for learning linear dags. In *Advances in Neural Information Processing Systems*, volume 33, 2020.

[39] Ignavier Ng, Yujia Zheng, Jiji Zhang, and Kun Zhang. Reliable causal discovery with improved exact search and weaker assumptions. In *Advances in Neural Information Processing Systems*, volume 34, 2021.

[40] Ignavier Ng, Shengyu Zhu, Zhuangyan Fang, Haoyang Li, Zhitang Chen, and Jun Wang. Masked gradient-based causal structure learning. In *SIAM International Conference on Data Mining*, pages 424–432, 2022.

[41] Roxana Pamfil, Nisara Sriwattanaworachai, Shaan Desai, Philip Pilgerstorfer, Konstantinos Georgatzis, Paul Beaumont, and Bryon Aragam. Dynotears: Structure learning from time-series data. In *International Conference on Artificial Intelligence and Statistics*, 2020.

[42] Judea Pearl. *Causality: Models, reasoning, and inference*. Cambridge University Press, 2009.

[43] Judea Pearl, Madelyn Glymour, and Nicholas P Jewell. *Causal inference in statistics: A primer*. John Wiley & Sons, 2016.

[44] J Peters, JM Mooij, D Janzing, and B Schölkopf. Causal discovery with continuous additive noise models. *Journal of Machine Learning Research*, 15(1):2009–2053, 2014.

[45] Jonas Peters and Peter Bühlmann. Identifiability of gaussian structural equation models with equal error variances. *Biometrika*, 101(1):219–228, 2014.

[46] Garvesh Raskutti and Caroline Uhler. Learning directed acyclic graph models based on sparsest permutations. *Stat*, 7(1):e183, 2018.

[47] Alexander Reisach, Christof Seiler, and Sebastian Weichwald. Beware of the simulated dag! causal discovery benchmarks may be easy to game. In *Advances in Neural Information Processing Systems*, volume 34, pages 27772–27784, 2021.

[48] David B Resnik. Randomized controlled trials in environmental health research: ethical issues. *Journal of Environmental Health*, 70(6):28, 2008.

[49] Jonathan G Richens, Ciarán M Lee, and Saurabh Johri. Improving the accuracy of medical diagnosis with causal machine learning. *Nature communications*, 11(1):1–9, 2020.

[50] Carsten Riggelsen. Learning bayesian networks from incomplete data: An efficient method for generating approximate predictive distributions. In *SIAM International Conference on Data Mining*, pages 130–140. SIAM, 2006.

[51] Christian P Robert, George Casella, and George Casella. *Monte Carlo statistical methods*, volume 2. Springer, 2004.

[52] Donald B Rubin. Inference and missing data. *Biometrika*, 63(3):581–592, 1976.

[53] Gideon Schwarz. Estimating the dimension of a model. *The Annals of Statistics*, pages 461–464, 1978.

[54] Shohei Shimizu, Patrik O Hoyer, Aapo Hyvärinen, Antti Kerminen, and Michael Jordan. A linear non-gaussian acyclic model for causal discovery. *Journal of Machine Learning Research*, 7(10), 2006.

[55] Shohei Shimizu, Takanori Inazumi, Yasuhiro Sogawa, Aapo Hyvärinen, Yoshinobu Kawahara, Takashi Washio, Patrik O Hoyer, and Kenneth Bollen. DirectLiNGAM: A direct method for learning a linear non-Gaussian structural equation model. *Journal of Machine Learning Research*, 12(Apr):1225–1248, 2011.

[56] Ilya Shpitser, Robin J Evans, Thomas S Richardson, and James M Robins. Introduction to nested markov models. *Behaviormetrika*, 41(1):3–39, 2014.

[57] Ajit P. Singh and Andrew W. Moore. Finding optimal Bayesian networks by dynamic programming. Technical report, Carnegie Mellon University, 2005.

[58] Moninder Singh. Learning bayesian networks from incomplete data. In *Association for the Advancement of Artificial Intelligence*, pages 534–539, 1997.

[59] Peter Spirtes and Clark Glymour. An algorithm for fast recovery of sparse causal graphs. *Social Science Computer Review*, 9:62–72, 1991.

[60] Peter Spirtes, Clark Glymour, Richard Scheines, et al. *Causation, Prediction, and Search*, volume 1. The MIT Press, 2001.

[61] Nicolas Städler and Peter Bühlmann. Missing values: sparse inverse covariance estimation and an extension to sparse regression. *Statistics and Computing*, 22(1):219–235, 2012.

[62] Daniel J Stekhoven and Peter Bühlmann. Missforest—non-parametric missing value imputation for mixed-type data. *Bioinformatics*, 28(1):112–118, 2012.

[63] Martin A Tanner and Wing Hung Wong. The calculation of posterior distributions by data augmentation. *Journal of the American statistical Association*, 82(398):528–540, 1987.

[64] Ruibo Tu, Cheng Zhang, Paul Ackermann, Karthika Mohan, Hedvig Kjellström, and Kun Zhang. Causal discovery in the presence of missing data. In *International Conference on Artificial Intelligence and Statistics*, pages 1762–1770. PMLR, 2019.

[65] Xiaoqiang Wang, Yali Du, Shengyu Zhu, Liangjun Ke, Zhitang Chen, Jianye Hao, and Jun Wang. Ordering-based causal discovery with reinforcement learning. In *International Joint Conference on Artificial Intelligence*, 2021.

[66] Yixin Wang, Dawen Liang, Laurent Charlin, and David M Blei. Causal inference for recommender systems. In *ACM Conference on Recommender Systems*, pages 426–431, 2020.

[67] Greg CG Wei and Martin A Tanner. A monte carlo implementation of the em algorithm and the poor man's data augmentation algorithms. *Journal of the American statistical Association*, 85 (411):699–704, 1990.

[68] Ian R White, Patrick Royston, and Angela M Wood. Multiple imputation using chained equations: issues and guidance for practice. *Statistics in medicine*, 30(4):377–399, 2011.

[69] Jinsung Yoon, James Jordon, and Mihaela Schaar. Gain: Missing data imputation using generative adversarial nets. In *International Conference on Machine Learning*, pages 5689–5698. PMLR, 2018.

[70] Yue Yu, Jie Chen, Tian Gao, and Mo Yu. DAG-GNN: DAG structure learning with graph neural networks. In *International Conference on Machine Learning*, 2019.

[71] Changhe Yuan and Brandon Malone. Learning optimal Bayesian networks: A shortest path perspective. *Journal of Artificial Intelligence Research*, 48(1):23–65, 2013.

[72] Changhe Yuan, Brandon Malone, and Xiaojian Wu. Learning optimal bayesian networks using a* search. In *International Joint Conference on Artificial Intelligence*, 2011.

[73] Kun Zhang and Aapo Hyvarinen. On the identifiability of the post-nonlinear causal model. In *Conference on Uncertainty in Artificial Intelligence*, 2009.

[74] Xun Zheng. *Learning DAGs with Continuous Optimization*. PhD thesis, Carnegie Mellon University, 2020.

[75] Xun Zheng, Bryon Aragam, Pradeep K Ravikumar, and Eric P Xing. DAGs with NO TEARS: Continuous Optimization for Structure Learning. In *Advances in Neural Information Processing Systems*, volume 31, 2018.

[76] Xun Zheng, Chen Dan, Bryon Aragam, Pradeep Ravikumar, and Eric P. Xing. Learning sparse nonparametric DAGs. In *International Conference on Artificial Intelligence and Statistics*, 2020.

[77] Shengyu Zhu, Ignavier Ng, and Zhitang Chen. Causal discovery with reinforcement learning. In *International Conference on Learning Representations*, 2020.