MOTO: Offline Pre-training to Online Fine-tuning for Model-based Robot Learning

Abstract: We study the problem of offline pre-training and online fine-tuning for reinforcement learning from high-dimensional observations in the context of realistic robot tasks. Recent offline model-free approaches successfully use online fine-tuning to either improve the performance of the agent over the data collection policy or adapt to novel tasks. At the same time, model-based RL algorithms have achieved significant progress in sample efficiency and the complexity of the tasks they can solve, yet remain under-utilized in the fine-tuning setting. In this work, we argue that existing methods for high-dimensional model-based offline RL are not suitable for offline-to-online fine-tuning due to issues with distribution shifts, off-dynamics data, and non-stationary rewards. We propose an on-policy model-based method that can efficiently reuse prior data through model-based value expansion and policy regularization, while preventing model exploitation by controlling epistemic uncertainty. We find that our approach successfully solves tasks from the MetaWorld benchmark, as well as the Franka Kitchen robot manipulation environment completely from images. To our knowledge, MOTO is the first and only method to solve this environment from pixels.[1]

Keywords: Model-based reinforcement learning, offline-to-online fine-tuning, high-dimensional observations

1 Introduction

Pre-training and fine-tuning as a paradigm has been instrumental to recent advances in machine learning. In the context of reinforcement learning, this takes the form of pre-training a policy with offline learning [1, 2], i.e. when only a static dataset of environment interactions is available; subsequently fine-tuning that policy with a limited amount of online fine-tuning. We study the offline-to-online fine-tuning problem with a focus on high-dimensional pixel observations, as found in real-world applications, such as robotics.

Prior works for offline-to-online fine-tuning often train a policy with model-free offline RL objectives throughout both the offline and online phases [3, 4, 5, 6, 7, 8]. While this approach addresses the challenge of distribution shift in the offline phase, it leads to excessive conservatism in the online phase, since the policy cannot balance offline conservatism with online exploration. Moreover, model-free works are lacking in generalization abilities, and can even under-perform when trained on non task-specific data [9, 10].

Model-based methods, in which the agent learns a representation and dynamics model, present an interesting alternative, as they have shown generalization ability to new within-distribution tasks [11, 12, 13, 14]; they are sample-efficient and can enable online exploration via model-generated rollouts [15]. Lastly, predictive models can also naturally learn stable representations, which makes

---

[1] Additional details, data, environments and trained agents are available online: `https://sites.google.com/view/mo2o/`

Submitted to the 7th Conference on Robot Learning (CoRL 2023). Do not distribute.

Figure 1: Model-based offline to online fine-tuning. A static dataset of experience is used to train a world model, with which the offline actor-critic agent interacts. The actor-critic agent is trained via both data from the environment and data from the model via model-based value expansion. Model data is penalized via an uncertainty penalty which inhibits model exploitation. Finally, during fine-tuning, the agent interacts with the environment, and collects new trajectories, which are used to jointly fine-tune the world model and actor-critic.

them suitable for realistic high-dimensional domains [16, 17, 18, 19]. Despite the good case for model-based learning in the offline-to-online fine-tuning problem, this has been under-explored, with the literature focused mostly on model-free methods.

In this work, we argue that existing algorithms for offline model-based RL are not suitable to the pre-training and fine-tuning or continual learning regimes. In particular, algorithms that use replay buffers of model-generated data, such as [11, 12, 13, 19], create significant distributional shift issues, as the learned model dynamics and reward functions change with additional online interactions. Moreover, models with high-dimensional observations, such as [19, 12], deal with the additional complexity of representation shift of the latent data. These algorithms are also not feasible in large models with high-dimensional representation spaces, which are common in real-world applications [16, 17, 18]. On the other hand, on-policy model-based RL methods such as [20, 21] are amenable to fine-tuning but do not make efficient use of high-quality data in the policy training objective or are not scalable to models with changing representation spaces.

To alleviate these issues, we propose the MOTO (**M**odel-based **O**ffline-**T**o-**O**nline) algorithm. MOTO is a model-based actor-critic algorithm which operates in high-dimensional observation spaces. Crucially, MOTO uses model-based value expansion, which removes the need for large replay buffers, alleviates the distributional shift issue, and allows for the use of large-scale predictive models while still allowing us to use high-quality offline data in the critic learning. To prevent model exploitation, we additionally implement ensemble model-based uncertainty estimation and policy regularization. We evaluate MOTO on 10 tasks from the MetaWorld benchmark [22] and two tasks in the Franka Kitchen domain [23, 24], completely from vision. Our approach outperforms baselines on 9/10 environments in the MetaWorld benchmark and solves both settings in the Franka kicthen domain. As far as we are aware, is the first method to solve this environment completely from vision. Moreover, by studying the fine-tuning regime, we empirically validate theoretical performance bounds from prior model-based offline RL.

We summarize our contributions as follows: (1) we propose a new model-based actor-critic algorithm for offline pre-training and online fine-tuning; (2) we show the first successful solution to the Franka Kitchen task from images; (3) we empirically verify a proposed theoretical performance gap; (4) to facilitate further research in this area, we will publicly release our environments and datasets.

2   Related Work

Our work is at the intersection of offline RL, model-based RL and control from high-dimensional observations (i.e. images). We review related work from these fields below.

Model-Based Offline RL   Model-based offline RL algorithms [20, 11, 25, 21, 26, 19, 12] learn a predictive model from the offline dataset and use it for policy training. We would like to design a model-based reinforcement learning algorithm that can efficiently utilize offline datasets, while being easily amenable to continual learning and online fine-tuning. A line of prior works [11, 12, 13] uses MBPO-style optimization [27], which mixes real and model-generated data in a replay buffer used for policy training. [19] generalizes this approach to more realistic domains using variational models and latent ensembles and manages to solve a real robot task involving desk manipulation. However, these methods are not well-suited to the fine-tuning tasks, since the data in the replay buffer is sampled form the model's internal representation space, which suffers from significant distribution shift as the model is fine-tuned. Moreover, the need for replay buffers limits the scalability of these algorithms, as state-of-the-art predictive models in many realistic applications (such as autonomous driving [16, 17, 18]) require very large model and representation sizes. Several algorithms such as MOREL [20] and BREMEN [21] use on-policy training within the learned model without the need for large replay buffers, making them well-suited to continual learning settings, but cannot use potentially high-quality data from the offline dataset to supervise the actor-critic training.

Variational Dynamics Models   Variational predictive models have demonstrated success in a variety of challenging applications. One line of research [16, 17, 28, 29, 30] utilizes the model for representation purposes only and uses standard RL, control, or imitation on top of it. Others such as [31, 32, 15, 33] use the latent dynamics model either to learn a policy within the model or deploy shooting-based planning methods. However, most of those prior works focus on the online setting and do not make good use of highly-structured prior data or account for distribution shift. Our method utilizes model-based value expansion, which allows us to take advantage of the efficiency of model-based training, while also using high-quality offline data for critic supervision.

3   Preliminaries

In this section we review the modeling framework for our world model and epistemic uncertainty estimates.

World Model   To model the high-dimensional observations of the environment, we use a recurrent VAE based on the RSSM model [31, 32]. The model consists of the following components:

$$
\begin{aligned}
\boldsymbol{z}_t &\sim q_\theta(\boldsymbol{z}_t \mid \boldsymbol{h}_t, \boldsymbol{x}_t) && \text{latent representation encoder} \\
\boldsymbol{h}_t &= f_\theta(\boldsymbol{z}_{t-1}, \boldsymbol{h}_{t-1}, \boldsymbol{a}_{t-1}) && \text{deterministic latent state} \\
\hat{\boldsymbol{z}}_t &\sim p_\theta^i(\boldsymbol{z}_t \mid \boldsymbol{h}_t) && \text{stochastic latent state} \\
\hat{\boldsymbol{x}}_t &\sim p_\theta(\boldsymbol{x}_t \mid \boldsymbol{z}_t, \boldsymbol{h}_t) && \text{observation decoder} \\
\hat{\boldsymbol{r}}_t &\sim p_\theta(\boldsymbol{r}_t \mid \boldsymbol{z}_t, \boldsymbol{h}_t) && \text{reward decoder}
\end{aligned}
$$

where $\boldsymbol{x}_t$ are the high-dimensional environment observations, $\boldsymbol{a}_t$ are the actions, $\boldsymbol{r}_t$ are the rewards, $\boldsymbol{h}_t$ are deterministic latent states, and $\boldsymbol{z}_t$ are stochastic latent states. We denote the latent state $\boldsymbol{s}_t = [\boldsymbol{h}_t, \boldsymbol{z}_t]$ as the concatenation of both. All components of the model are trained jointy via the ELBO loss as:

$$
\begin{aligned}
\mathcal{L}_{p_\theta, q_\theta}^{\text{model}} = \mathop{\mathbb{E}}_{\tau \sim \mathcal{D}} \Big[\sum_t & -\ln p_\theta(\boldsymbol{x}_t \mid \boldsymbol{s}_t) - \ln p_\theta(\boldsymbol{r}_t \mid \boldsymbol{s}_t) + \\
& \mathbb{D}_{KL}\big[q_\theta(\boldsymbol{s}_t | \boldsymbol{x}_t, \boldsymbol{s}_{t-1}, \boldsymbol{a}_{t-1}) || p_\theta^{i_t}(\boldsymbol{s}_t | \boldsymbol{s}_{t-1}, \boldsymbol{a}_{t-1})\big] \Big].
\end{aligned} \tag{1}
$$

In our experiments we use discrete latent state models, following the DreamerV2 architecture [15]. Notice that we train an ensemble of stochastic latent dynamics models $\{p_\theta^i(\boldsymbol{s}_{t+1} | \boldsymbol{z}_t)\}_{i=1}^M$ following [19] by randomly selecting one model $p_\theta^{i_t}$ to optimize at each time step of the trajectory in the model in Eq. 1. This makes the ensemble training no more computationally expensive than single model optimization.

Algorithm 1 MOTO: Model-based Offline to Online Fine-tuning

Require: Offline dataset D, initialized policy π_ψ and critics Q_ψ, initialized prediction and reward model M_θ, policy rollout length H, number of offline training steps N_{offline}, number of online episodes to collect $N_{\text{online episodes}}$, number of online gradient updates per episode G.

1: // *offline pre-training*
2: **for** $i = 1, 2, 3, \cdots, N_{\text{offline}}$ **do**
3:     Sample a batch of trajectories $B \sim \mathcal{D}$.
4:     Update M_θ on B according to Eq. 1.
5:     Generate H-step latent policy rollouts with penalized rewards (Eq. 3).
6:     Update π_ψ according to Eq. 10
7:     update Q_ψ according to Eq. 9 on the real and model data.
8: **end for**
9: // *online fine-tuning*
10: **for** $i = 1, 2, 3, \cdots, N_{\text{online episodes}}$ **do**
11:     Rollout the policy π_θ in the environment for an episode to collect a new trajectory τ
12:     $\mathcal{D} = \mathcal{D} \cup \tau$
13:     **for** step $= 1, 2, 3, \cdots, G$ **do**
14:         Sample a batch of trajectories $B \sim \mathcal{D}$.
15:         Update M_θ on B according to Eq. 1.
16:         Generate H-step latent policy rollouts with penalized rewards (Eq. 3).
17:         Update π_ψ according to Eq. 10
18:         update Q_ψ according to Eq. 9 on the real and model data.
19:     **end for**
20: **end for**

Offline Model-Based RL From High-Dimensional Observations   To mitigate issues with model exploitation, similar to [19, 11], we train a latent dynamics model ensemble $\{p_\theta^i(\boldsymbol{s}_{t+1}|\boldsymbol{z}_t)\}_{i=1}^M$, and implement model conservatism by penalizing rewards via dynamics model disagreement, which acts as a proxy for epistemic uncertainty. We use the penalty:

$$u_\theta(\boldsymbol{s}_t, \boldsymbol{a}_t) = \text{std}(\{l_{\theta^i}(\boldsymbol{z}_{t+1})\}_{i=1}^M), \tag{2}$$

where $l_\theta^i(\boldsymbol{z}_{t+1})$ is the logit outputs of the discrete distribution $p_\theta^i(\cdot|\boldsymbol{z}_{t+1})$. Hence, the final reward function is

$$\hat{r}_\theta(\boldsymbol{s}_t, \boldsymbol{a}_t, \boldsymbol{s}_{t+1}) = r_\theta(\boldsymbol{s}_{t+1}) - \alpha u_\theta(\boldsymbol{s}_t, \boldsymbol{a}_t) \tag{3}$$

where α is a tarde-off parameter between reward maximization and conservatism.

4   Model-based Offline to Online Fine-tuning (MOTO)

Our model training architecture and objective follow prior works [19 **?**], but we significantly change the actor-critic algorithm optimization towards the goal of efficient online fine-tuning from offline data. We build the MOTO policy optimization procedure on three main design choices: 1) model-based value expansion, 2) uncertainty-aware predictive modelling, and 3) behaviour-regularized policy optimization. The full algorithm training outline is presented in Algorithm 1.

Variational Model-Based Value Expansion   We would like to train a policy using model-based training that can still utilize previously collected high-quality data without the use of latent replay buffers, as to alleviate the issues described in Section 2. To this end, we adapt ideas from the model-based value expansion literature [34, 35, 36, 37]. We consider sequences of data of the form $\tau = (\boldsymbol{x}_{1:T}, \boldsymbol{a}_{1:T}, \boldsymbol{r}_{1:T})$. At each agent training step, we infer latent states $\boldsymbol{s}_{1:T}^0 \sim q_\theta(\boldsymbol{s}_{1:T}|\boldsymbol{x}_{1:T}, \boldsymbol{a}_{1:T})$. We then use the true data as starting points for model-generated rollouts, as:

$$\hat{\boldsymbol{a}}_j^t \sim \pi_\psi(\boldsymbol{a}|\hat{\boldsymbol{s}}_j^{t-1}), \quad \hat{\boldsymbol{s}}_j^{t+1} \sim p_\theta(\boldsymbol{s}|\hat{\boldsymbol{a}}_j^t, \hat{\boldsymbol{s}}_j^t), \quad \hat{r}_j^t \sim p_\theta(\boldsymbol{r}|\hat{\boldsymbol{s}}_j^t), \tag{4}$$

where the rewards are computed according to Eq. 3. Following standard off-policy learning algorithms, we use critics $\{Q_{\psi^1}, Q_{\psi^2}\}$ and and target networks $\{\bar{Q}_{\psi^1}, \bar{Q}_{\psi^2}\}$. We can then use our model to estimate Monte-Carlo based policy returns:

$$V_0^{\pi_\psi}(\hat{\boldsymbol{s}}_j^t) = \min\{Q_{\psi^1}(\hat{\boldsymbol{s}}_j^t, \hat{\boldsymbol{a}}_j^t), Q_{\psi^2}(\hat{\boldsymbol{s}}_j^t, \hat{\boldsymbol{a}}_j^t)\}, \quad V_K^{\pi_\psi}(\hat{\boldsymbol{s}}_j^t) = \sum_{k=1}^K \gamma^{k-1}\hat{r}_j^{k+t} + \gamma^K V_0^{\pi_\psi}(\hat{\boldsymbol{s}}_j^{t+K})$$

And compute the GAE(γ, λ) estimate:

$$V^{\pi_\psi}(\hat{\boldsymbol{s}}_j^t) = (1 - \lambda) \sum_{k=1}^{H-t-1} \lambda^{k-1} V_k^{\pi_\psi}(\hat{\boldsymbol{s}}_j^t) + \lambda^{H-t-1} V_{H-t}^{\pi_\psi}(\hat{\boldsymbol{s}}_j^t) \tag{5}$$

We denote $\widehat{V}^{\pi_\psi}(\boldsymbol{s}) := \lambda V^{\pi_\psi}(\boldsymbol{s}) + (1 - \lambda) V_0^{\pi_\psi}$, and optimize the actor objective as:

$$\mathcal{L}_{\pi_\psi}^{\text{model}} = -\frac{1}{HT} \mathop{\mathbb{E}}_{\tau \sim \mathcal{D}} \mathop{\mathbb{E}}_{\pi_\psi, p_\theta} \left[\sum_{t=0, j=1}^{H-1, T} \widehat{V}^{\pi_\psi}(\hat{\boldsymbol{s}}_j^t) \right] \tag{6}$$

This objective essentially estimates the actor return by mixing Monte-Carlo based estimates at various horizons. Notice that is a fully differentiable function of the policy parameters, by back-propagating through the Q-functions and dynamics model. Also notice that for $H = 0$ this is just the standard actor-critic policy update.

We can similarly use MC return estimates to train the critics. We recompute the critic target values $\bar{V}^k(\hat{\boldsymbol{s}}_j^t)$ for all states similarly to Eq. 5 using the target networks $\{\bar{Q}_{\psi^1}, \bar{Q}_{\psi^2}\}$. The critics are trained on both the model-generated and real data with the sum of two losses:

$$\mathcal{L}_{Q_{\psi^i}}^{\text{model}} = \frac{1}{HT} \sum_{t=0, j=1}^{H-1, T} (\bar{V}^{\pi_\psi}(\hat{\boldsymbol{s}}_j^t) - Q_{\psi^i}(\hat{\boldsymbol{s}}_j^t, \hat{\boldsymbol{a}}_j^t))^2 \tag{7}$$

$$\mathcal{L}_{Q_{\psi^i}}^{\text{data}} = \frac{1}{T-1} \left[\sum_{j=1}^{T-1} \left(\boldsymbol{r}_{j+1}^0 + \gamma \widehat{V}^{\pi_\psi}(\boldsymbol{s}_{j+1}^0) - Q_{\psi^i}(\boldsymbol{s}_j^0, \boldsymbol{a}_j^0) \right)^2 \right] \tag{8}$$

and the final critic loss is the sum of the two:

$$\mathcal{L}_{Q_{\psi^i}}^{\text{final}} = \mathcal{L}_{Q_{\psi^i}}^{\text{model}} + \mathcal{L}_{Q_{\psi^i}}^{\text{data}} \tag{9}$$

Training the critic networks on the available offline data serves as a strong supervision when the dataset already contains rollouts with high returns.

Uncertainty-aware Predictive Modelling In order to prevent model exploitation in the offline training, we use model-based uncertainty estimates via ensemble statistics, similar to [38, 39, 40, 41, 42, 43, 44, 45]. Note that the loss $\mathcal{L}_{Q_{\psi^i}}^{\text{data}}$ is computed on transitions sampled from the dataset trajectories through the inference model q_θ and have ground-truth environment rewards. In contrast, the critic loss $\mathcal{L}_{Q_{\psi^i}}^{\text{model}}$ is computed on synthetic states sampled from the model using only uncertainty-penalized rewards. This explicitly builds conservatism into the critic values by biasing them towards dataset states and actions. We also considered alternative conservative critic optimization [4, 12]. However, these approaches are incompatible with multi-step returns and require the use of a latent replay buffer which is undesirable. Following prior works [11, 20, 19] we provide theoretical verification for our modelling choices. In addition, by studying the online fine-tuning regime, for the first time, we are able to provide empirical verification for prior offline MBRL performance bounds. Since the current work does not focus on theoretical contributions, we defer these results to Appendix B.

Behaviour Prior Policy Regularization Realistic robot learning datasets often consist of narrow data like planner based rollouts or human demonstrations. As such, at the initial stages of training dynamics models can be quite inaccurate and the agent can benefit from stronger data regularization for the policy [26, 13, 25, 21]. To avoid additional complexity of modelling the behaviour distribution we follow an approach similar to [46] which deploy a regularization term of the form

$$\mathcal{L}_{\pi_\psi}^{\text{reg}} = -\mathop{\mathbb{E}}_{\tau \sim \mathcal{D}} \left[\sum_{t=1}^{T} \log \pi_\psi(\boldsymbol{a}_t \mid \boldsymbol{s}_t) f\left(\underbrace{\gamma^H V^{\pi_\psi}(\boldsymbol{s}_{t+H}) + \sum_{j=1}^{H} \gamma^j \boldsymbol{r}_{t+j} - V^{\pi_\psi}(\boldsymbol{s}_t)}_{\text{Advantage over trajectory snippet } \boldsymbol{s}_t \, : \, \boldsymbol{s}_{t+H}} \right) \right]$$

Figure 2: The success rates across the 10 MetaWorld tasks. MOTO matches or outperforms other methods on 9 out of the 10 tasks, demonstrating MOTO's ability to successfully pre-train offline and fine-tuning online on a variety of manipulation tasks using limited offline data. DreamerV2 is the only other method to achieve competitive results on the MetaWorld tasks. The model free baselines achieve low to moderate performance across all tasks.

for some function f. The authors suggest a simple threshold function works well (i.e adding a behaviour cloning term to snippets with positive advantage), [13] can also be viewed as an instance of this approach using exponential weighting. In this work we focus on realistic robot manipulation tasks with sparse rewards, and just threshold trajectories based on whether they achieve the goals in the environment. We then optimize the joint actor loss:

$$\mathcal{L}_{\pi_\psi} = \mathcal{L}_{\pi_\psi}^{\text{model}} + \beta \mathcal{L}_{\pi_\psi}^{\text{reg}} \tag{10}$$

where β is a hyper-parameter that trades-off between model-based optimization and data regularization.

5 Experiments and Results

We aim to answer the following questions: (1) Can MOTO pre-train offline and successfully fine-tune online? (2) What is the impact of different model components? (3) Does MOTO exhibit good generalization and sample efficiency?

Experiment Setup   We evaluate our method on two challenging dexterous manipulation domains, MetaWorld [22] and the Franka Kitchen RPL environment [23].

MetaWorld contains a variety of simulated manipulation tasks in a shared, table-top environment to be solved with a Sawyer robotic arm. We use ten of these tasks for our experiments (see Figure 7). We modify these environments to use 64x64 RGB image observations, without any robot proprioception and use sparse rewards based on task completion. For each environment we collected a small dataset of 9-10 episodes using a scripted policy. More details can be found in Appendix C.

Figure 3: Visualizations of the MetaWorld `hammer-v2` and the Franka Kitchen RPL environments.

The Franka Kitchen RPL environment is a challenging long-range control problem that requires using a simulated 9-DOF Franka Emika Robot to manipulate multiple different objects in a simulated kitchen area. The goal of the agent is to manipulate a set of 4 pre-defined objects into their desired configurations, receiving a reward of 1.0 for each object in right configuration at each time step. The observations are 64x64 RGB image; we do not assume access to object states or robot proprioception. For our experiments, we render the original RPL datasets and consider two tasks from the D4RL benchmark [24]. The "mixed" task requires operating the microwave, kettle, light

Figure 4: (**Left**) Success rate of completing the "mixed" and "partial" tasks in Franka Kitchen. MOTO outperforms all methods on both tasks, and is the only method to achieve meaningful progress on the "partial" task, indicating MOTO's capacity for combinatorial generalization. (**Right**) We carry out a number of ablations on the MOTO design, such as not uncertainty penalties "No Unc.", not using policy regularization "No. Reg", and removing both "No Reg., No Unc.". The top graph presents the learning curves over the online fine-tuning phase, while the bottom bar chart shows successful completions in the last 200 evaluation episodes. We see that all model components contribute to learning and final performance.

switch and slide cabinet. It contains a small set of successful demos in the offline dataset. The "partial" task, which requires manipulating the microwave, kettle, bottom burner and light switch does not have any trajectories that successfully complete all four objects, but has demonstrations for several configurations which complete up to three objects. Since the "partial" task does not contain successful trajectories for all four objects, we only regularize policy training with respect to the first three objects. We will release this dataset with our project to facilitate the development and testing of vision-based offline RL algorithms. Details of the Franka Kitchen environments and datasets can be found in Appendix C.

Baselines We compare our method to prior vision-based offline model-based RL algorithms LOMPO [19] and COMBO [12] as well as DreamerV2 [15], a state-of-the art online model-based learning algorithm. We also compare our approach against CQL, [4] a successful model-free offline RL algorithm, IQL, [3] a state-of-the art model-free regression-based fine-tuning algorithm, SAC [47], and behaviour cloning. All methods are pre-trained offline for 10 thousand gradient steps and fine-tuned with online interactions for a total of 500 thousand environment steps.

MetaWorld Results Results for the MetaWorld tasks are in Fig. 2. MOTO outperforms other methods on 9 out of 10 tasks in that domain. This shows MOTO's ability to successfully pre-train offline and fine-tune online on a variety of manipulation tasks using limited offline data. DreamerV2 is the only other method to achieve competitive results on the MetaWorld tasks. The model free baselines achieve low to moderate performance across all tasks. Perhaps somewhat surprisingly, COMBO and LOMPO achieve very low success rates on most of the tasks. A speculative explanation for this is that the MetaWorld environments have a significant degree of randomization between them at each new episode, causing the learned image representations to change frequently. Since COMBO and LOMPO are off-policy methods that maintain replay buffers of the latent state representations, if these representations change frequently this would lead to poor performance.

Franka Kitchen Results As seen in Fig. 4, our method successfully solves both the "mixed" and "partial" tasks of Franka Kitchen with 100% and 90.5% final success rates respectively. DreamerV2 is the only other method to obtain non-trivial success rates. Noteworthy is MOTO's success on the "partial" task, which demonstrates that the world model is capable of combinatoric generalization.

While model-free methods make some progress, ultimately they stagnate and cannot successfully complete all four objects on either task. This is likely due to the partial observability of the environment, since the robot can occlude manipulated objects and also requires joint state estimation directly from images. In contrast, variational models serve as Bayesian filters and naturally build state estimations of the environment in the latent space. Model-based methods LOMPO and COMBO achieve very limited progress, due to the non-stationarity issues described in the beginning of Section 4. The DreamerV2 algorithm learns more slowly and only reaches final success rates of 77.5%

and 13.5% versus 100% and 90.5% for our method on the "mixed" and "partial" task. As far as we know, our model is the first method to solve the Franka Kitchen environment from images.

Ablation Studies   In this section we evaluate the contribution of each model component to final performance. Results are presented in Fig. 5 (right). We also include the standard DreamerV2 algorithm for direct model-based comparison. While all ablations make significant progress on the "mixed" task, only the full model manages to solve it entirely. The full model outperforms the others on the "partial" task by a very significant margin. We also note that without any data regularization, both the "No Reg., No Unc." and DreamerV2 methods learn unsafe behaviours, such as hitting the kettle into the goal position, or smashing the light switch with the robot head, instead of using its gripper to grasp and place the objects. These policies would be unsafe for both the hardware and environment in a real setting. Such behaviours are not present in any of the regularized methods (videos are available on the project website).

6   Discussion

Future Work   The MOTO algorithm design does not require large replay buffers of intermediate representations, while still allowing the use of high-quality data to supervise the critic learning and bootstrap the policy optimization. We believe that these qualities make MOTO very suitable for realistic applications, which require large scale models [16, 17, 18]. We plan to evaluate MOTO on large-scale realistic domains, such as CARLA [48] in future work.

MOTO is also well-suited to the model-based imitation learning setting [49, 14, 50, 51], which has recently been successfully applied to real world scenarios as well [52, 53]. By using on-policy rollouts, MOTO can maintain the stability and theoretical guarantees of adversarial imitation learning [54, 55, 19], while still using the high-quality expert data to both provide supervision to the critic, as well as to regularize the policy.

Limitations   MOTO builds a level of pessimism through penalizing state-action epistemic model uncertainty. Excessive pessimism can prevent the model from exploring or generalizing outside of the available data distribution. This can hurt performance if the offline dataset consists of lower-quality or incomplete data. MOTO also uses policy regularization, which is based on task success. It may be difficult to adapt this approach to tasks that involve more complex or non-sparse rewards. Finally, a key component of MOTO is controlling model-based epistemic uncertainty. We train an ensemble of latent transition models and use their disagreement as a reward penalty. The models we consider use MLPs for the latent dynamics, however it is not clear if this scheme can transfer to more complex architectures, such as Transformers, which are now more widely used within the predictive modeling context.

7   Conclusion

We present MOTO, a model-based reinforcement learning algorithm specifically designed for the offline pre-training and down-stream fine-tuning regime. MOTO learns a variational model directly from pixels, and trains an actor-critic agent within the learned latent dynamics model using model-based value expansion, epistemic uncertainty corrections, and policy regularization, all of which we show have an impact in improving performance, and deriving safe and robust policies. MOTO outperforms baselines in terms of sample efficiency and final performance on 9/10 MetaWorld tasks and far as we are aware is the first and only method to solve the Franka Kitchen benchmark from images. Furthermore, by studying the offline pre-training and fine-tuning regime, we empirically verify long-standing theoretical results on the offline model-based RL problem. Finally, the structure of the algorithm makes it suitable for use in very large scale dynamics models, such as the ones used in autonomous driving, which prior work was not able to utilize, as well as a backbone for model-based imitation, multi-task and transfer learning. We plan to explore these directions in follow-up works.

References

[1] S. Lange, T. Gabel, and M. A. Riedmiller. Batch reinforcement learning. In *Reinforcement Learning*, volume 12. Springer, 2012.

[2] S. Levine, A. Kumar, G. Tucker, and J. Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *arXiv preprint arXiv:2005.01643*, 2020.

[3] I. Kostrikov, A. Nair, and S. Levine. Offline reinforcement learning with implicit q-learning. *arXiv preprint arXiv:2110.06169*, 2021.

[4] A. Kumar, A. Zhou, G. Tucker, and S. Levine. Conservative q-learning for offline reinforcement learning. *arXiv preprint arXiv:2006.04779*, 2020.

[5] A. Nair, M. Dalal, A. Gupta, and S. Levine. Accelerating online reinforcement learning with offline datasets. *arXiv preprint arXiv:2006.09359*, 2020.

[6] M. Yang and O. Nachum. Representation matters: offline pretraining for sequential decision making. In *International Conference on Machine Learning*, pages 11784–11794. PMLR, 2021.

[7] L. Chen, K. Lu, A. Rajeswaran, K. Lee, A. Grover, M. Laskin, P. Abbeel, A. Srinivas, and I. Mordatch. Decision transformer: Reinforcement learning via sequence modeling. *Advances in neural information processing systems*, 34:15084–15097, 2021.

[8] S. Reed, K. Zolna, E. Parisotto, S. G. Colmenarejo, A. Novikov, G. Barth-Maron, M. Gimenez, Y. Sulsky, J. Kay, J. T. Springenberg, et al. A generalist agent. *arXiv preprint arXiv:2205.06175*, 2022.

[9] T. Yu, A. Kumar, Y. Chebotar, K. Hausman, S. Levine, and C. Finn. Conservative data sharing for multi-task offline reinforcement learning. *Advances in Neural Information Processing Systems*, 34:11501–11516, 2021.

[10] T. Yu, A. Kumar, Y. Chebotar, C. Finn, S. Levine, and K. Hausman. Data sharing without rewards in multi-task offline reinforcement learning. 2021.

[11] T. Yu, G. Thomas, L. Yu, S. Ermon, J. Zou, S. Levine, C. Finn, and T. Ma. Mopo: Model-based offline policy optimization. *arXiv preprint arXiv:2005.13239*, 2020.

[12] T. Yu, A. Kumar, R. Rafailov, A. Rajeswaran, S. Levine, and C. Finn. Combo: Conservative offline model-based policy optimization. *Advances in neural information processing systems*, 34:28954–28967, 2021.

[13] C. Cang, A. Rajeswaran, P. Abbeel, and M. Laskin. Behavioral priors and dynamics models: Improving performance and domain transfer in offline rl. *arXiv preprint arXiv:2106.09119*, 2021.

[14] R. Rafailov, T. Yu, A. Rajeswaran, and C. Finn. Visual adversarial imitation learning using variational models. *Advances in Neural Information Processing Systems*, 34:3016–3028, 2021.

[15] D. Hafner, T. Lillicrap, M. Norouzi, and J. Ba. Mastering atari with discrete world models. *arXiv preprint arXiv:2010.02193*, 2020.

[16] A. Hu, G. Corrado, N. Griffiths, Z. Murez, C. Gurau, H. Yeo, A. Kendall, R. Cipolla, and J. Shotton. Model-based imitation learning for urban driving. *arXiv preprint arXiv:2210.07729*, 2022.

[17] A. Hu, Z. Murez, N. Mohan, S. Dudas, J. Hawke, V. Badrinarayanan, R. Cipolla, and A. Kendall. Fiery: Future instance prediction in bird's-eye view from surround monocular cameras. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 15273–15282, 2021.

[18] A. K. Akan and F. Güney. Stretchbev: Stretching future instance prediction spatially and temporally. *arXiv preprint arXiv:2203.13641*, 2022.

[19] R. Rafailov, T. Yu, A. Rajeswaran, and C. Finn. Offline reinforcement learning from images with latent space models. *ArXiv*, abs/2012.11547, 2020.

[20] R. Kidambi, A. Rajeswaran, P. Netrapalli, and T. Joachims. Morel: Model-based offline reinforcement learning. *arXiv preprint arXiv:2005.05951*, 2020.

[21] T. Matsushima, H. Furuta, Y. Matsuo, O. Nachum, and S. Gu. Deployment-efficient reinforcement learning via model-based offline optimization. *arXiv preprint arXiv:2006.03647*, 2020.

[22] T. Yu, D. Quillen, Z. He, R. Julian, K. Hausman, C. Finn, and S. Levine. Meta-world: A benchmark and evaluation for multi-task and meta reinforcement learning. In *Conference on Robot Learning*, pages 1094–1100. PMLR, 2020.

[23] A. Gupta, V. Kumar, C. Lynch, S. Levine, and K. Hausman. Relay policy learning: Solving long-horizon tasks via imitation and reinforcement learning. *arXiv preprint arXiv:1910.11956*, 2019.

[24] J. Fu, A. Kumar, O. Nachum, G. Tucker, and S. Levine. D4rl: Datasets for deep data-driven reinforcement learning. *arXiv preprint arXiv:2004.07219*, 2020.

[25] A. Argenson and G. Dulac-Arnold. Model-based offline planning. *arXiv preprint arXiv:2008.05556*, 2020.

[26] P. Swazinna, S. Udluft, and T. Runkler. Overcoming model bias for robust offline deep reinforcement learning. *arXiv preprint arXiv:2008.05533*, 2020.

[27] M. Janner, J. Fu, M. Zhang, and S. Levine. When to trust your model: Model-based policy optimization. In *Advances in Neural Information Processing Systems*, pages 12498–12509, 2019.

[28] M. Watter, J. Springenberg, J. Boedecker, and M. Riedmiller. Embed to control: A locally linear latent dynamics model for control from raw images. In *Advances in neural information processing systems*, pages 2746–2754, 2015.

[29] M. Zhang, S. Vikram, L. Smith, P. Abbeel, M. Johnson, and S. Levine. Solar: Deep structured representations for model-based reinforcement learning. In *International Conference on Machine Learning*, pages 7444–7453. PMLR, 2019.

[30] A. X. Lee, A. Nagabandi, P. Abbeel, and S. Levine. Stochastic latent actor-critic: Deep reinforcement learning with a latent variable model. *arXiv preprint arxiv:1907.00953.pdf*, 2020.

[31] D. Hafner, T. Lillicrap, I. Fischer, R. Villegas, D. Ha, H. Lee, and J. Davidson. Learning latent dynamics for planning from pixels. *International Conference on Learning Representations*, 2019.

[32] D. Hafner, T. Lillicrap, J. Ba, and M. Norouzi. Dream to control: Learning behaviors by latent imagination. *International Conference on Learning Representations*, 2020.

[33] D. Ha and J. Schmidhuber. World models. *arXiv preprint arXiv:1803.10122*, 2018.

[34] V. Feinberg, A. Wan, I. Stoica, M. I. Jordan, J. E. Gonzalez, and S. Levine. Model-based value estimation for efficient model-free reinforcement learning. *arXiv preprint arXiv:1803.00101*, 2018.

[35] J. Buckman, D. Hafner, G. Tucker, E. Brevdo, and H. Lee. Sample-efficient reinforcement learning with stochastic ensemble value expansion. *Advances in neural information processing systems*, 31, 2018.

[36] B. Amos, S. Stanton, D. Yarats, and A. G. Wilson. On the model-based stochastic value gradient for continuous reinforcement learning. In *Learning for Dynamics and Control*, pages 6–20. PMLR, 2021.

[37] I. Clavera, V. Fu, and P. Abbeel. Model-augmented actor-critic: Backpropagating through paths. *arXiv preprint arXiv:2005.08068*, 2020.

[38] K. Chua, R. Calandra, R. McAllister, and S. Levine. Deep reinforcement learning in a handful of trials using probabilistic dynamics models. *Advances in neural information processing systems*, 31, 2018.

[39] I. Clavera, J. Rothfuss, J. Schulman, Y. Fujita, T. Asfour, and P. Abbeel. Model-based reinforcement learning via meta-policy optimization. In *Conference on Robot Learning*, pages 617–629. PMLR, 2018.

[40] M. Deisenroth and C. E. Rasmussen. Pilco: A model-based and data-efficient approach to policy search. In *Proceedings of the 28th International Conference on machine learning (ICML-11)*, pages 465–472, 2011.

[41] T. Kurutach, I. Clavera, Y. Duan, A. Tamar, and P. Abbeel. Model-ensemble trust-region policy optimization. *arXiv preprint arXiv:1802.10592*, 2018.

[42] A. Nagabandi, K. Konolige, S. Levine, and V. Kumar. Deep dynamics models for learning dexterous manipulation. In *Conference on Robot Learning*, pages 1101–1112. PMLR, 2020.

[43] Y. Luo, H. Xu, Y. Li, Y. Tian, T. Darrell, and T. Ma. Algorithmic framework for model-based deep reinforcement learning with theoretical guarantees. *arXiv preprint arXiv:1807.03858*, 2018.

[44] A. L. Strehl and M. L. Littman. An analysis of model-based interval estimation for markov decision processes. *Journal of Computer and System Sciences*, 74(8):1309–1331, 2008.

[45] A. Zanette and E. Brunskill. Tighter problem-dependent regret bounds in reinforcement learning without domain knowledge using value function bounds. In *International Conference on Machine Learning*, pages 7304–7312. PMLR, 2019.

[46] N. Y. Siegel, J. T. Springenberg, F. Berkenkamp, A. Abdolmaleki, M. Neunert, T. Lampe, R. Hafner, N. Heess, and M. Riedmiller. Keep doing what worked: Behavioral modelling priors for offline reinforcement learning, 2020.

[47] T. Haarnoja, A. Zhou, P. Abbeel, and S. Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. *arXiv preprint arXiv:1801.01290*, 2018.

[48] A. Dosovitskiy, G. Ros, F. Codevilla, A. Lopez, and V. Koltun. CARLA: An open urban driving simulator. In *Proceedings of the 1st Annual Conference on Robot Learning*, pages 1–16, 2017.

[49] N. Baram, O. Anschel, I. Caspi, and S. Mannor. End-to-end differentiable adversarial imitation learning. In *International Conference on Machine Learning*, pages 390–399. PMLR, 2017.

[50] J. D. Chang, M. Uehara, D. Sreenivas, R. Kidambi, and W. Sun. Mitigating covariate shift in imitation learning via offline data without great coverage. *arXiv preprint arXiv:2106.03207*, 2021.

[51] W. Zhang, H. Xu, H. Niu, P. Cheng, M. Li, H. Zhang, G. Zhou, and X. Zhan. Discriminator-guided model-based offline imitation learning. *arXiv preprint arXiv:2207.00244*, 2022.

[52] Y. Lu, J. Fu, G. Tucker, X. Pan, E. Bronstein, B. Roelofs, B. Sapp, B. White, A. Faust, S. Whiteson, et al. Imitation is not enough: Robustifying imitation with reinforcement learning for challenging driving scenarios. *arXiv preprint arXiv:2212.11419*, 2022.

[53] E. Bronstein, M. Palatucci, D. Notz, B. White, A. Kuefler, Y. Lu, S. Paul, P. Nikdel, P. Mougin, H. Chen, et al. Hierarchical model-based imitation learning for planning in autonomous driving. In *2022 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 8652–8659. IEEE, 2022.

[54] J. Ho and S. Ermon. Generative adversarial imitation learning. *Advances in neural information processing systems*, 29, 2016.

[55] C. Finn, X. Y. Tan, Y. Duan, T. Darrell, S. Levine, and P. Abbeel. Deep spatial autoencoders for visuomotor learning. In *2016 IEEE International Conference on Robotics and Automation (ICRA)*, pages 512–519. IEEE, 2016.

[56] D. Hafner, T. Lillicrap, I. Fischer, R. Villegas, D. Ha, H. Lee, and J. Davidson. Learning latent dynamics for planning from pixels. In *International conference on machine learning*, pages 2555–2565. PMLR, 2019.

[57] I. Kostrikov. JAXRL: Implementations of Reinforcement Learning algorithms in JAX, 10 2022. URL https://github.com/ikostrikov/jaxrl2. v2.

[58] G. Barth-Maron, M. W. Hoffman, D. Budden, W. Dabney, D. Horgan, D. Tb, A. Muldal, N. Heess, and T. Lillicrap. Distributed distributional deterministic policy gradients. *arXiv preprint arXiv:1804.08617*, 2018.