Efficient Automatic Machine Learning via Design Graphs

Abstract

Despite the success of automated machine learning (AutoML), which aims to find the best design, including the architecture of deep networks and hyper-parameters, conventional AutoML methods are computationally expensive and hardly provide insights into the effect of various model design choices. To tackle the challenges, we propose FALCON, an efficient sample-based method to predict the performance of a model and search for the optimal model design. Our key insight is to model the design space of possible model designs as a *design graph*, where the nodes represent design choices, and the edges denote design similarities. FALCON features 1) a task-agnostic module, which performs message passing on the design graph via a Graph Neural Network (GNN), and 2) a task-specific module, which conducts label propagation of the known model performance information on the design graph. Both modules are combined to predict the performances of each design in the design space. We conduct extensive experiments on 27 tasks on graphs including node and graph classifications in various application domains, and an image classification task on the CIFAR-10 dataset. We empirically show that FALCON can efficiently obtain the well-performing designs for each task using only 30 explored nodes. Specifically, FALCON has a comparable time cost with the one-shot approaches while achieving an average improvement of 3.3% compared with the best baselines.

1 Introduction

Automated machine learning (AutoML) [1, 2, 3, 4, 5, 6, 7, 8, 9, 10] has demonstrated great success in various domains including computer vision [11, 12, 13], language modeling [5, 14], and recommender systems [15]. It is an essential component for the state-of-the-art deep learning models [16, 17, 18, 19].

Given a machine learning task, *e.g.,* a node/graph classification task on graphs or an image classification task, our goal of AutoML is to search for a model architecture and hyper-parameter setting from a design space that results in the best test performance on the task. Following previous works [9], we define *design* as a set of architecture and hyper-parameter choices (*e.g.,* 3 layer, 64 embedding dimensions, batch normalization, skip connection between consecutive layers), and define *design space* as the space of all possible designs for a given task.

However, AutoML is very computationally intensive. The design space of interest often involves millions of possible designs [20, 21]. Sample-based AutoML [5, 8, 22, 23, 24] has been used to perform search via sampling candidate designs from the design space to explore and training a small portion of them with potentially good performance. One central challenge of existing sample-based AutoML solutions is its sample efficiency: it needs to train as few models as possible to identify the best-performing model in the vast design space. To improve the efficiency, existing research focuses on developing good search algorithms to navigate in the design space [25, 26, 27].

#pre	#mp	#post	stage	agg
[1, 2]	[2, 4, 6, 8]	[2, 3]	skipconcat skipsum	min, max, add

(a) Design graph example   (b) Search strategy of our method

Figure 1: **Overview of FALCON**. (a) **Design graph example**. We present a small design graph on TU-COX2 graph classification dataset. The design choices are shown in the table, #pre, #mp, #post denotes the numbers of pre-processing, message passing, and post-processing layers, respectively. The better design performance, the darker node colors. (b) **FALCON search strategy.** Red: Explored nodes. Green: Candidate nodes to be sampled from. Blue: The best node. Gray: Other nodes. Locally, FALCON extends the design subgraph via a search strategy detailed in Section 3.3. Globally, FALCON approaches the optimal design navigated by the inductive bias of the design relations.

However, these methods do not consider modeling the effect of model design choices, which provides strong inductive biases in searching for the best-performing model. For example, human often relies on two types of intuitions when designing architectures and hyper-parameters: (1) boundedness: "higher embedding dimensions result in higher performance until reaching a threshold" and (2) dependency: "using a large number of layers without batch normalization degrades the performance" to find the best design. Moreover, some variables may "dominate" the design performance, *e.g.,* in Figure 1 (a), the design performance is highly correlated with the number of message passing layers. Thus, an efficient sample strategy should rapidly rule out a large subset of the design space with possibly bad performance, leveraging such inductive bias learned during a search process.

Proposed approach. To overcome the limitations, we propose FALCON, an AutoML framework that achieves state-of-the-art sample efficiency and performance by leveraging model design insights. Our key insight is to build a *design graph* over the design space of architecture and hyper-parameter choices. FALCON extracts model design insights by learning a *meta-model* that captures the relation between the design graph and model performance and uses it to inform a sample-efficient search strategy. FALCON consists of the following two novel components.

Design space as a graph. Previous works view the model design space as a high-dimensional space with isolated design choices [9]. However, such a representation offers few insights regarding the *relations* between different design choices and the inductive biases of design choices. For example, through trial runs if we find the models with more than 3 layers do not work well without batch normalization, this insight could help us reduce the search space by excluding all model designs of more than 3 layers with batch normalization set to false. While such insights are hardly obtained with existing AutoML algorithms [1, 2, 8, 5, 6], FALCON achieves it via constructing a graph representation among all the design choices, which we call the design graph. Figure 1(a) shows a visualization of a design graph. Each node represents a candidate design, and edges denote the similarity between the designs. See Section 3.1 for details on the similarity and graph construction.

Search by navigating on the design graph. Given the design graph, FALCON deploys a Graph Neural Network predictor, short for *meta-GNN*, which is supervised by the explored nodes' performances and learns to predict the performance of a specific design given the corresponding node in the design graph. The meta-GNN is designed with 1) a task-agnostic module, which performs message passing on the design graph, and 2) a task-specific module, which conducts label propagation of the known model performance information on the design graph. Furthermore, we propose a search strategy that uses meta-GNN predictions to navigate the search in the design graph efficiently.

Experiments. Without loss of generality, we mainly focus on AutoML for graph representation learning in this paper. We conduct extensive experiments on 27 graph datasets, covering node- and graph-level tasks with distinct distributions. Moreover, we show that FALCON can work well on other machine learning domains with the experiments on the CIFAR-10 image dataset. We provide implementations of FALCON on two popular platforms: GraphGym [9] and NNI[1]. Our code is available at https://anonymous.4open.science/r/Falcon.

2 Related Work

Automatic Machine Learning (AutoML) is the cornerstone of discovering state-of-the-art model designs without costing massive human efforts. We introduce four types of related works below.

Sample-based AutoML methods. Existing sample-based approaches explore the search space via sampling candidate designs, which includes heuristic search algorithms, *e.g.,* Simulated Annealing, Bayesian Optimization approaches [22, 25, 27], evolutionary- [28, 29] and reinforcement-based methods [5, 30, 8]. However, they tend to train thousands of models from scratch, which results in the low sample efficiency. For example, [5, 8] usually involve training hundreds of GPUs for several days, hindering the development of AutoML in real-world applications [3].

One-shot AutoML methods. The one-shot approaches [1, 2, 31, 3, 32] have been popular for the high search efficiency. Specifically, they involve training a super-net representing the design space, *i.e.,* containing every candidate design, and shares the weights for the same computational cell. Nevertheless, weight sharing degrades the reliability of design ranking, as it fails to reflect the true performance of the candidate designs [33].

Graph-based AutoML methods. The key insight of our work is to construct the design space as a design graph, where nodes are candidate designs and edges denote design similarities, and deploy a Graph Neural Network, *i.e.,* meta-GNN, to predict the design performance. Graph HyperNetwork [34] directly generates weights for each node in a computation graph representation. You et al. study network generators that output relational graphs and analyze the link between their predictive performance and the graph structure. Recently, PDNAS [35] considers both the micro- (*i.e.,* a single block) and macro-architecture (*i.e.,* block connections) of each design in graph domain. Notably, none of these works model the search space as a design graph.

Design Performance Predictor. Previous works predict the performance of a design using the learning curves [36], layer-wise features [37], computational graph structure [34, 25, 38, 27, 39, 40], or combining dataset information [40] via a dataset encoder. To highlight, FALCON explicitly models the relations among model designs. Moreover, it leverages the performance information on training instances to provide task-specific information besides the design features, which is differently motivated compared with HELP [41] that employs meta-learning techniques and incorporate hardware features to rapidly adapt to unseen devices. Besides, meta-GNN is applicable for a wider range of data types, *e.g.,* images and graphs, than MetaD2A [40].

3 Proposed Method

This section introduces our proposed approach FALCON for sample-based AutoML. In Section 3.1, we introduce the construction of design graph, and formulate the AutoML goal as a search on the design graph for the node with the best task performance. In Section 3.2, we introduce our novel neural predictor consisting of a task-agnostic module and a task-specific module, which predicts the performances of unknown designs. Finally, we detail our search strategy in Section 3.3. We refer the reader to Figure 1 (b) for a high-level overview of FALCON.

3.1 Design Space as a Graph

Motivation. Previous works generally consider each design choice as isolated from other designs. However, it is often observed that some designs that share the same design features, *e.g.,* graph neural networks (GNNs) that are more than 3 layers and have batch normalization layers, may have similar performances. Moreover, the inductive bias of the relations between design choices can provide

---

[1]https://github.com/microsoft/nni

valuable information for navigating the design space for the best design. For example, suppose we find that setting batch normalization of a 3-layer GCN [42] and a 4-layer GIN [43] to false both degrade the performance. Then we can reasonably infer that a 3-layer GraphSAGE [44] with batch normalization outperforms the one without. We could leverage such knowledge and only search for the designs that are more likely to improve the task performance. To the best of our knowledge, FALCON is the first method to explicitly consider such relational information among model designs.

Design graph. We denote the design graph as $\mathcal{G}(\mathcal{N}, \mathcal{E})$, where the nodes $\mathcal{N}$ include the candidate designs, and edges $\mathcal{E}$ denote the similarities between the candidate designs. Specifically, we use the notion of design distance to decide the graph connectivity, and we elaborate on them below.

Design distance. For each numerical design dimension, two design choices have a distance 1 if they are adjacent in the ordered list of design choices. For example, if the hidden dimension size can take values $[16, 32, 64, 128]$, then the distance between 16 and 32 is 1, and the distance between 32 and 128 is 2. For each categorical design dimension, any two distinct design choices have a distance 1. We then define the connectivity of the design graph in terms of the design distance:

Definition 1 (Design Graph Connectivity). *The design graph can be expressed as $\mathcal{G}(\mathcal{N}, \mathcal{E})$, where the nodes $\mathcal{N} = \{d_1, \ldots, d_n\}$ are model designs, and $(d_i, d_j) \in \mathcal{E}$ iff the design distance between d_i and d_j is 1.*

Structure of the design graph. The definition of edges implies that the design graph is highly structured, with the following properties: (1) All designs that are the same except for one categorical design dimension form a clique subgraph. (2) All designs that are the same except k numerical design dimensions form a grid graph structure. Moreover, we use a special calculation for the design distance with a combination of design dimensions that have dependencies. For example, the design dimensions of pooling operations, pooling layers, and the number of layers can depend on each other, thus the design graph structure becomes more complex. See the details in Appendix A.2.

Design subgraph. The design graph may contain millions of nodes. Therefore, directly applying the meta-model to the design graph is computationally intensive. Moreover, a reliable performance estimation for an unknown node depends on its similarity between the nodes already explored by the search algorithm. Therefore, we focus on using a meta-model to predict performance for a dynamic subgraph, *i.e.,* design subgraph, containing the explored nodes in the current search stage and the candidate nodes to be sampled in the next step. The candidate set can be constructed by selecting the multi-hop neighbors of explored nodes or performing random walks on the design graph. The design subgraph is defined as:

Definition 2 (Design Subgraph). *During a search, suppose the explored node set is $\mathcal{N}_e$ and the candidate set is $\mathcal{N}_c$. The design subgraph is formulated as $\mathcal{G}_s(\mathcal{N}_s, \mathcal{E}_s)$, where $\mathcal{N}_s = \mathcal{N}_e \cup \mathcal{N}_c$ are the nodes and $\mathcal{E}_s = \{(u, v) | u \in \mathcal{N}_s, v \in \mathcal{N}_s, (u, v) \in \mathcal{N}\}$ are the edges.*

Given the design subgraph, we formulate the AutoML problem as searching for the node, *i.e.,* design choice, with the best task performance.

3.2 Meta-GNN for Performance Prediction

Here we introduce a meta-model, called meta-GNN, to predict the performance of model designs, corresponding to nodes in the design subgraph. As is illustrated in Figure 2, the meta-GNN comprises a task-agnostic module and a task-specific module, used to capture the knowledge of model design and task performance, respectively.

Task-agnostic module. The task-agnostic module uses a design encoder to encode the design features on nodes of the design subgraph, and a relation encoder to capture the design similarities and differences on edges of the design subgraph. After that, it performs message passing on the design subgraph. We introduce each component below:

- *Design encoder*: it computes the node features of design subgraph by the concatenation of the feature encoding of each design dimension of the architecture design. For numerical design dimensions such as hidden dimension size, we conduct min-max normalization for the numerical value as the feature. For categorical design dimensions such as aggregation operator which takes one of (SUM, MAX, MEAN), we encode it as a one-hot feature.

Figure 2: **Meta-GNN Framework**: Task-agnostic module generates the embedding given the design variables and their graphical structures. Task-specific module leverages performance information and conducts label propagation to generate the task-specific embeddings. The two embeddings are concatenated and input into an MLP for predicting the design performance.

- *Relation encoder*: it captures the similarity relationships between the connecting designs. For each $(d_i, d_j) \in \mathcal{E}$, we encode the design dimension where d_i and d_j differ by a one-hot encoding.

- *Message passing module*: a GNN model is used to take the design subgraph and the processed features to perform message passing and output a representation of each design node. This information will be combined with the task-specific module to predict the design's performance. In practice, we use a graph attention network (GAT) [45] as the GNN architecture, which has the benefit of learning to attend to the most relevant architecture design in each neighborhood of the design subgraph.

Task-specific module. The task-specific module takes into account the information of design performance on selected training instances and thus is specific for one dataset.

The challenge of including such performance information is that it is only available on a very limited set of explored nodes. To overcome the challenge, we use label propagation to propagate the performance information of explored nodes to the unexplored candidate nodes. This is based on our observation that models trained with similar designs typically make similar predictions on instances. Without loss of generality, we follow an example on a binary node classification task (*cf.* Figure 2) to illustrate the task-specific module.

- *Identifying critical instances*: The first step is to identify critical training instances that result in different performances across different designs. Thus, we compute the entropy of each instance in the training set for a set of sampled explored designs. After that, we obtain the instance-wise probability via Softmax on the instance-wise entropy vector and use a probability sampler to sample instances that result in high variation across designs. The high variation in the downstream model predictions implies that these instances can distinguish good design nodes from bad ones in the design subgraph, which is informative.

- *Label propagation and linear projection*: Based on the inductive bias of smoothness, we perform label propagation to make the task-specific information available to all candidate designs. Concretely, label propagation can be written as

$$\mathbf{Y}^{(k+1)} = \alpha \cdot D^{-1/2} A D^{-1/2} \mathbf{Y}^{(k)} + (1 - \alpha) \mathbf{Y}^{(k)} \tag{1}$$

where each row of $\mathbf{Y}$ is the performance vector of design i (if explored) or a zero vector (for the unexplored designs). $D \in \mathbb{R}^{|N_s| \times |N_s|}$ is the diagonal matrix of node degree, $A \in \mathbb{R}^{|N_s| \times |N_s|}$ is the adjacent matrix of the design subgraph, and α is a hyper-parameter. After label propagation, we use a linear layer to project the performance information to another high-dimensional space.

Finally, as shown in Figure 2, we concatenate the output embeddings of the task-specific and task-agnostic modules and use an MLP to produce the performance predictions.

Algorithm 1: Pseudocode of FALCON

Require: S: Design space. K: Exploration size. h_θ: Meta-GNN. V/V': Warm-up / Full epoch. η: Learning rate. C: Number of start nodes.

1: $\Omega \leftarrow$ Sample-Nodes(S, C) // Initialize the exploration set
2: $\Gamma \leftarrow$ Multi-hop-Neighbors(Ω) // Multi-hop neighbors as the candidate set
3: $Y_\Omega =$ Get-Validation-Performance(Ω, V)
4: **while** $t = |\Omega| < K$ **do**
5:     $\mathcal{G}_s^{(t)} \leftarrow (\mathcal{N}_v = \Omega \cup \Gamma, \mathcal{E} =$ Similarity$(\mathcal{N}_v))$ // (1) Design subgraph update
6:     **while** not converge **do**
7:        $\theta \leftarrow \theta - \eta \cdot \partial \mathcal{L}(\hat{Y}_\Omega, h_\theta(\mathcal{G}_s^{(t)})_\Omega)/\partial\theta$ // (2) Meta-GNN optimization
8:     **end while**
9:     $d^{(t)} =$ Sample-with-Logits$(\Gamma, h_\theta(\mathcal{G}_s^{(t)})_\Gamma)$ // (3) Node exploration
10:    $Y_t =$ Get-Validation-Performance$(d^{(t)}, V)$
11:    $\Omega \leftarrow \Omega \cup \{d^{(t)}\}, \Gamma \leftarrow \Gamma \cup$ Multi-hop-Neighbors$(\{d^{(t)}\})$
12: **end while**
13: $D =$ Select-TopK$(\{\Omega_i : Y_i\}_{i=1}^K,$ size $=$ Min$(\lceil 10\% \cdot K \rceil, 5))$ // Models to be fully trained
14: $Y' =$ Get-Validation-Performance(D, V')
15: $I =$ Argmax(Y')
16: **return** D_I, Y'_I

Objective for Meta-GNN. The training of neural performance predictor is commonly formulated as a regression using mean square error (MSE), in order to predict how good the candidate designs are for the current task. However, the number of explored designs is usually small for sample-efficient AutoML, especially during the early stage of the search process. Thus, the deep predictor tends to overfit, degrading the reliability of performance prediction. To solve this problem, we incorporate a pair-wise rank loss [46, 47] with the MSE objective, resulting in a quadratic number of training pairs, thus reducing overfitting. Furthermore, predicting relative performance is more robust across datasets than predicting absolute performance. Overall, the objective is formulated as follows:

$$\mathcal{L}(\hat{Y}, Y) = \sum_{i=1}^{N}(\hat{Y}_i - Y_i)^2 + \lambda\mathcal{L}_{rank}(\hat{Y}, Y), \text{ where}$$

$$\mathcal{L}_{rank}(\hat{Y}, Y) = \sum_{i=1}^{N}\sum_{j=i}^{N}(-1)^{\mathbb{I}(Y_i > Y_j)} \cdot \sigma\left(\frac{\hat{Y}_i - \hat{Y}_j}{\tau}\right) \tag{2}$$

where λ is the trade-off hyper-parameter. $\mathcal{L}_{rank}$ is the pair-wise rank. τ is the temperature controlling the minimal performance difference that will be highly penalized, and σ denotes the Sigmoid function. Thus, the meta-GNN is trained to predict the node performance on the design subgraphsupervised by the explored node performance.

3.3 Search Strategy

Equipped with the meta-GNN, we propose a sequential search strategy to search for the best design in the design graph. The core idea is to leverage meta-GNN to perform fast inference on the dynamic design subgraph, and decide what would be the next node to explore, thus navigating the search. Concretely, our search strategy is consist of the following three steps:

- *Initialization*: Firstly, FALCON randomly samples multiple nodes (*cf.* Figure 1 (b)) on the design graph. The motivation of sampling multiple nodes in the initial step is to enlarge the receptive field on the design graph to avoid the local optima and bad performance due to bad initialization. This benefit is empirically verified in Appendix D. After that, we explore the initialized nodes by training designs on the tasks and construct the instance mask for task-specific module.

- *Meta-GNN training*: Following Figure 2, meta-GNN predicts the performance of the explored nodes. The loss is computed via Equation 2 and back-propagated to optimize the meta-GNN.

- *Exploration via inference*: Meta-GNN is then used to make predictions of the performances for all candidate nodes. FALCON samples the best candidate node based on the predicted performance and updates the design subgraph in the next step.

227 At every iteration, we extend the design subgraph through the last two steps. After a fixed number of
228 iterations, we select and retrain a few designs in the search trajectory with top validation performances.
229 We summarize our search strategy in Algorithm 1. Overall, FALCON approaches the optimal design
230 navigated by the inductive bias learned by meta-GNN (*cf.* Figure 1 (b)).

4 Experiments

232 We conduct extensive experiments on 28 graph datasets and an image dataset. The goal is twofold:
233 (1) to show FALCON's sample efficiency over the existing AutoML methods (*cf.* Section 4.2) and
234 (2) to provide insights into how the inductive bias learned from the relational information of designs
235 navigate the search on the design graph (*cf.* Section 4.3).

4.1 Experimental Settings

237 We consider the following tasks in our evaluation and we leave the details including dataset split,
238 evaluation metrics, and hyper-parameters in Appendix A.

239 **Node classification tasks**. We use 6 benchmarks ranging from citation networks to product or social
240 networks: Cora, CiteSeer, PubMed [48], ogbn-arxiv [49], AmazonComputers [50], and Reddit [51].

241 **Graph classification tasks**. We use 21 benchmark binary classification tasks in TUDataset [52],
242 which are to predict certain properties for molecule datasets with various distribution.

243 **Image classification tasks**. We use CIFAR-10 [53]. Pre-processing details are in Appendix C.

244 **Baselines**. We compare FALCON with three types of baselines:

245 • Simple search strategies: Random, Simulated Annealing (SA), Bayesian Optimization (BO) [22].
246 • AutoML approaches: DARTS [1], ENAS [2], GraphNAS [8], AutoAttend [54], GASSO [32]. The
247   last three methods are only used for the graph tasks.
248 • Ablation models: FALCON-G and FALCON-LP, where FALCON-G discards the design graph and
249   predicts the design performance using an MLP, and FALCON-LP removes the task-specific module
250   and predicts design performance using only the task-agnostic module.

251 We also include a naive method, BRUTEFORCE, which obtains the best design by randomly training
252 5% designs in the design space from scratch, which is regarded as the approximated ground truth
253 of the best designs' performance. We compare all the FALCON and simple search baselines under
254 *sample size controlled search*, where we limit the number of explored designs during each search
255 trial. And we set the exploration size as 30 by default.

256 **Design Space**. We use different design spaces on node- and graph-level tasks. Specifically, The
257 design variables include common hyper-parameters, *e.g.,* learning rate decay and dropout ratio,
258 and architecture choices, *e.g.,* layer connectivity and batch normalization. Moreover, we consider
259 node pooling choices for the graph classification datasets, which is less studied in the previous
260 works [7, 8, 30]. Besides, we follow [9] and control the number of parameters for all the candidate
261 designs to ensure a fair comparison. For one-shot baselines, we construct macro design spaces which
262 have similar structure variables as FALCON. See Appendix A.2 for the details.

4.2 Main Results

264 **Node classification tasks**. Table 1 summarizes the performance of FALCON and the baselines.

Figure 3: Accuracy *v.s.* the number of explored nodes on ogbn-arxiv.

Notably, FALCON takes comparable search cost as the one-shot methods and is 15x less expensive than GraphNAS. Moreover, FALCON achieves the best performances over the baselines with sufficient margins in the most datasets, using only 30 explored designs. For example, FALCON outperforms ENAS by 1.8% in CiteSeer and GASSO by 1.6% in AmazonComputers. Also, the removal of the design graph and task-specific module decreases the performance constantly, which validates their effectiveness. It is worth mentioning that FALCON is competitive with BRUTEFORCE, demonstrating the excellence of FALCON in searching for globally best-performing designs.

Table 1: Search results on five node classification tasks, where Time stands for the search cost (GPU·hours). We compute p-value on our method with the best AutoML baselines.

	Cora		CiteSeer		Pubmed		AmazonComputers		Reddit	
	ACC	Time	ACC	Time	ACC	Time	ACC	Time	F1	Time
Random	$80.8_{\pm1.7}$	0.20	$71.2_{\pm0.8}$	0.22	$86.0_{\pm3.5}$	0.24	$81.6_{\pm3.0}$	0.16	$94.3_{\pm0.1}$	0.97
BO	$85.1_{\pm0.3}$	0.28	$72.6_{\pm0.9}$	0.30	$88.5_{\pm0.3}$	0.31	$82.3_{\pm6.3}$	0.16	$94.2_{\pm0.2}$	0.94
SA	$81.1_{\pm0.8}$	0.24	$74.7_{\pm0.2}$	0.25	$88.9_{\pm0.1}$	0.29	$81.2_{\pm6.9}$	0.23	$94.3_{\pm0.5}$	0.97
ENAS	$85.8_{\pm0.4}$	0.27	$74.9_{\pm0.2}$	0.39	$88.6_{\pm0.8}$	2.06	$74.5_{\pm1.2}$	0.83	$92.3_{\pm1.0}$	1.98
DARTS	$85.8_{\pm0.2}$	0.25	$75.2_{\pm0.3}$	0.25	$89.1_{\pm0.1}$	0.35	$84.1_{\pm1.9}$	0.35	[OoM]	-
GraphNAS	$82.2_{\pm3.6}$	3.12	$74.9_{\pm0.6}$	3.99	$89.2_{\pm0.3}$	5.37	$88.5_{\pm2.4}$	2.53	$89.1_{\pm2.9}$	3.03
AutoAttend	$84.6_{\pm0.2}$	1.23	$73.9_{\pm0.2}$	1.25	$84.4_{\pm0.7}$	1.55	$87.3_{\pm1.1}$	2.62	[OoM]	-
GASSO	$\mathbf{86.8_{\pm1.1}}$	0.38	$75.3_{\pm0.7}$	0.33	$86.3_{\pm0.4}$	0.41	$89.8_{\pm0.1}$	0.73	[OoM]	-
FALCON-G	$84.5_{\pm0.8}$	0.23	$74.3_{\pm1.7}$	0.24	$89.2_{\pm0.1}$	0.26	$87.6_{\pm0.9}$	0.27	$93.7_{\pm0.4}$	1.11
FALCON-LP	$85.5_{\pm1.0}$	0.26	$74.6_{\pm0.1}$	0.26	$89.0_{\pm0.2}$	0.29	$90.7_{\pm0.6}$	0.30	$94.9_{\pm0.2}$	1.00
FALCON	$\mathbf{86.4_{\pm0.5}}$	0.26	$\mathbf{76.2_{\pm0.4}}$	0.28	$\mathbf{89.3_{\pm0.5}}$	0.32	$\mathbf{91.2_{\pm0.5}}$	0.30	$\mathbf{95.2_{\pm0.2}}$	1.15
BRUTEFORCE	87.0	52.5	76.0	59.7	90.0	63.0	91.4	81.5	95.5	>200
p-value	-	-	0.051	-	0.145	-	0.017	-	0002	-

We further investigate the speed-performance trade-off of FALCON and other sample-based approaches in ogbn-arxiv dataset. Specifically, we run several search trials under different sample sizes. As shown in Figure 3, FALCON can reach the approximated ground truth result with very few explored nodes. In contrast, SA and Random require more samples to converge, while BO performs bad even with a large number of explored nodes, potentially due to its inability in dealing with high-dimensional design features.

Graph classification tasks. The graph classification datasets cover a wide range of graph distributions. For example, ER-MD contains only 446 graphs with an average node degree 11.2, compared to MCF-7, which has 27,770 graphs with an average node degree 1.1. Thus, the search algorithm is required to customize a well-performing model structure and optimization hyper-parameters for every dataset, according to the task-specific graph properties and dataset sizes *etc*. In Table 2, we report the selected performance results for graph classification tasks and leave other results including the search costs in Appendix B. We highlight three observations:

• On average, the state-of-the-art AutoML baselines algorithms perform similarly to the simple search methods, indicating the potentially unreliable search which is similarly concluded in [33].

• FALCON surpasses the best AutoML baselines with an average improvement of 3.3%. The sufficient and consistent improvement greatly validates our sample efficiency under a controlled sample size.

• In the second block, we attribute the high sample efficiency of FALCON to the exhibition of design relations and the performance information from the training instances. Specifically, FALCON outperforms FALCON-LP by 4.87% on average, indicating that the task-specific module provides more task information that aids the representation learning of model designs, enabling a fast adaption on a certain task. Moreover, FALCON gains an average improvement of 6.43% compared to FALCON-G, which justifies our motivation in Section 3.1 that the design relations promote the learning of relational inductive bias, which guides the search on the design graph.

We have also observed the performance gap between FALCON and BRUTEFORCE in some datasets. And we argue such decline is acceptable as FALCON only samples 30 designs (0.2% of all designs) and trains them for only a few epochs, comparing to BRUTEFORCE which fully trains 5% designs. We also conduct experiments similar with Figure 3 to investigate how FALCON converges with the increasing sample size (*cf.* Appendix B.1) and report the best designs found by FALCON for each dataset (*cf.* Appendix B.2). Besides, we provide sensitivity analysis on FALCON's hyper-parameters, *e.g.,* number of random start nodes C, in Appendix D.

Image classification task. Due to space limitation, we leave the results of CIFAR-10 to Appendix C and discuss the conclusion here. We found that the search cost of FALCON is comparable to the one-shot based baselines. Specifically, FALCON conducts the search process using approximately 0.8 GPU·days. And it further gains average improvements of 1.4% over the simple search baselines and 0.3% over the one-shot baselines averagely.

Table 2: Selected results for the graph classification tasks. The average task performance (ROC-AUC) of the architectures searched by FALCON is 3.3% over the best AutoML baselines.

	ER-MD	AIDS	OVCAR-8	MCF-7	SN12C	NCI109	Tox21-AhR	Avg.
Random	$77.5_{\pm1.6}$	$97.0_{\pm1.4}$	$56.2_{\pm0.0}$	$58.2_{\pm0.3}$	$57.4_{\pm1.0}$	$73.4_{\pm0.9}$	$75.7_{\pm2.0}$	70.8
BO	$77.6_{\pm3.5}$	$96.1_{\pm1.0}$	$63.6_{\pm0.7}$	$60.7_{\pm0.0}$	$54.8_{\pm1.1}$	$73.6_{\pm1.2}$	$75.5_{\pm1.1}$	71.7
SA	$75.9_{\pm4.2}$	$95.4_{\pm0.9}$	$59.5_{\pm3.2}$	$56.7_{\pm0.8}$	$60.4_{\pm1.7}$	$76.6_{\pm5.6}$	$76.5_{\pm3.0}$	71.6
ENAS	$76.0_{\pm2.2}$	$97.1_{\pm0.4}$	$56.0_{\pm1.3}$	$59.7_{\pm0.8}$	$66.4_{\pm0.6}$	$71.2_{\pm1.0}$	$73.6_{\pm0.9}$	71.4
DARTS	$75.0_{\pm0.7}$	$\mathbf{98.0_{\pm0.0}}$	$56.8_{\pm0.3}$	$60.2_{\pm0.7}$	$66.0_{\pm0.4}$	$73.5_{\pm0.2}$	$76.0_{\pm1.1}$	72.2
GraphNAS	$76.9_{\pm3.6}$	$95.9_{\pm0.8}$	$58.7_{\pm0.8}$	$61.3_{\pm5.2}$	$60.7_{\pm1.5}$	$73.6_{\pm2.9}$	$70.6_{\pm4.3}$	71.1
AutoAttend	$73.1_{\pm0.8}$	$97.4_{\pm0.3}$	$59.8_{\pm0.8}$	$64.4_{\pm0.2}$	$71.8_{\pm0.3}$	$75.9_{\pm1.8}$	$74.1_{\pm0.9}$	73.8
GASSO	$73.2_{\pm0.4}$	$95.2_{\pm0.7}$	$62.3_{\pm0.3}$	$62.5_{\pm0.4}$	$70.9_{\pm2.3}$	$73.9_{\pm0.4}$	$70.2_{\pm3.5}$	72.6
FALCON-G	$78.3_{\pm3.0}$	$96.3_{\pm1.4}$	$56.4_{\pm1.1}$	$62.3_{\pm4.5}$	$69.8_{\pm2.2}$	$70.3_{\pm6.4}$	$72.5_{\pm2.8}$	72.3
FALCON-LP	$76.7_{\pm2.4}$	$96.0_{\pm0.2}$	$61.5_{\pm4.9}$	$59.5_{\pm5.7}$	$70.3_{\pm3.8}$	$73.1_{\pm0.3}$	$76.5_{\pm2.5}$	73.3
FALCON	$\mathbf{78.4_{\pm0.2}}$	$97.5_{\pm1.1}$	$\mathbf{66.7_{\pm3.4}}$	$\mathbf{65.5_{\pm2.5}}$	$\mathbf{73.3_{\pm0.0}}$	$\mathbf{78.4_{\pm2.3}}$	$\mathbf{78.5_{\pm1.1}}$	**76.9**
BRUTEFORCE	83.3	96.0	67.4	70.6	73.7	81.8	82.0	79.3
p-value	0.155	-	0.008	0.035	<0.001	0.096	0.018	-

4.3 Case Study of FALCON

Here we provide insights of FALCON via observing the alignment between the learned design embeddings with the design performance. As shown in Figure 4, we visualize the high-dimensional design embeddings obtained by FALCON via T-SNE [55] after searching on the Cora dataset.

Figure 4: T-SNE visualization for the design embeddings of Cora dataset.

Specifically, the colors in the left figure are associated with the design performance, while the colors in the right figure vary with the dropout ratio. Firstly, the left figure shows that meta-GNN can generally distinguish and separate "good" nodes from "bad" nodes. Secondly, the high discrimination potentially indicates that the over-smoothing effect on the design graph is mild. To mitigate the over-smoothing problem for more dense design graphs, we provide discussion in Section 5 and will explore it in future work. Moreover, by aligning the two figures, we can conclude that the dropout ratio is an influential variable that affects design performance, which also validates the meta-GNN's expressiveness and capacity to learn the relational inductive bias between the design choices.

5 Conclusion, Limitation, and Future Work

This work introduces FALCON , an efficient sample-based AutoML framework. We propose the concept of design graph that explicitly models and encodes relational information among model designs. The design graph is a basis for incorporating inductive biases of designs, which are essential for design space pruning and search navigation. On top of the design graph, we formulate the goal as searching for the node (design) with the best task performance. Further, we develop a sample-efficient strategy to navigate the search on the design graph with a novel meta-model. Through extensive experiments, our algorithm has shown great success in efficiently searching best-performing designs compared to the state-of-the-art AutoML methods.

One future direction is to better tackle the high average node degree on the design graph, especially when the design variables include many categorical variables. Since conducting message passing or label propagation on a dense graph structure could result in over-smoothing of the meta-GNN. A simple solution is to use edge dropout to randomly removes a portion of edges at each training epoch. Moreover, we can develop a local filtering mechanism by edge attention and filters edges with weak relational inductive bias. Another future direction is to develop more powerful relational learning models for AutoML in image datasets. As it usually involves a more complex design space, typically computational graphs, which poses difficulty in measuring the design distance and constructing the design graphs.

References

[1] Hanxiao Liu, Karen Simonyan, and Yiming Yang. DARTS: differentiable architecture search. In *ICLR*, 2019.

[2] Hieu Pham, Melody Y. Guan, Barret Zoph, Quoc V. Le, and Jeff Dean. Efficient neural architecture search via parameter sharing. In Jennifer G. Dy and Andreas Krause, editors, *ICML*, 2018.

[3] Gabriel Bender, Pieter-Jan Kindermans, Barret Zoph, Vijay Vasudevan, and Quoc V. Le. Understanding and simplifying one-shot architecture search. In Jennifer G. Dy and Andreas Krause, editors, *ICML*, 2018.

[4] Esteban Real, Alok Aggarwal, Yanping Huang, and Quoc V. Le. Regularized evolution for image classifier architecture search. AAAI Press, 2019.

[5] Barret Zoph and Quoc V. Le. Neural architecture search with reinforcement learning. In *ICLR*, 2017.

[6] Han Cai, Ligeng Zhu, and Song Han. Proxylessnas: Direct neural architecture search on target task and hardware. In *ICLR*, 2019.

[7] Shaofei Cai, Liang Li, Jincan Deng, Beichen Zhang, Zheng-Jun Zha, Li Su, and Qingming Huang. Rethinking graph neural architecture search from message-passing. In *CVPR*, 2021.

[8] Yang Gao, Hong Yang, Peng Zhang, Chuan Zhou, and Yue Hu. Graphnas: Graph neural architecture search with reinforcement learning. *arXiv*, 1904.09981, 2019.

[9] Jiaxuan You, Zhitao Ying, and Jure Leskovec. Design space for graph neural networks. In *NeurIPS*, 2020.

[10] Ziwei Zhang, Xin Wang, and Wenwu Zhu. Automated machine learning on graphs: A survey. In Zhi-Hua Zhou, editor, *IJCAI*, 2021.

[11] Xiangxiang Chu, Bo Zhang, Hailong Ma, Ruijun Xu, and Qingyuan Li. Fast, accurate and lightweight super-resolution with neural architecture search. In *ICPR*. IEEE, 2020.

[12] Golnaz Ghiasi, Tsung-Yi Lin, and Quoc V. Le. NAS-FPN: learning scalable feature pyramid architecture for object detection. In *CVPR*, 2019.

[13] Yukang Chen, Tong Yang, Xiangyu Zhang, Gaofeng Meng, Chunhong Pan, and Jian Sun. Detnas: Neural architecture search on object detection. 2019.

[14] David R. So, Quoc V. Le, and Chen Liang. The evolved transformer. In Kamalika Chaudhuri and Ruslan Salakhutdinov, editors, *ICML*, 2019.

[15] Bo Chen, Xiangyu Zhao, Yejing Wang, Wenqi Fan, Huifeng Guo, and Ruiming Tang. Automated machine learning for deep recommender systems: A survey. 2022.

[16] Hanxiao Liu, Karen Simonyan, Oriol Vinyals, Chrisantha Fernando, and Koray Kavukcuoglu. Hierarchical representations for efficient architecture search. In *ICLR*, 2018.

[17] Bowen Baker, Otkrist Gupta, Nikhil Naik, and Ramesh Raskar. Designing neural network architectures using reinforcement learning. In *ICLR*, 2017.

[18] Yuhui Xu, Lingxi Xie, Xiaopeng Zhang, Xin Chen, Guo-Jun Qi, Qi Tian, and Hongkai Xiong. PC-DARTS: partial channel connections for memory-efficient architecture search. In *ICLR*, 2020.

[19] Xiangning Chen, Ruochen Wang, Minhao Cheng, Xiaocheng Tang, and Cho-Jui Hsieh. Drnas: Dirichlet neural architecture search. In *ICLR*.

[20] Thomas Elsken, Jan Hendrik Metzen, and Frank Hutter. Neural architecture search: A survey. *J. Mach. Learn. Res.*

[21] Jiaxuan You, Jure Leskovec, Kaiming He, and Saining Xie. Graph structure of neural networks. In *ICML*, 2020.

[22] James Bergstra, Rémi Bardenet, Yoshua Bengio, and Balázs Kégl. Algorithms for hyper-parameter optimization. In *NeurIPS*, 2011.

[23] Chenxi Liu, Barret Zoph, Jonathon Shlens, Wei Hua, Li-Jia Li, Li Fei-Fei, Alan L. Yuille, Jonathan Huang, and Kevin Murphy. Progressive neural architecture search. 1712.00559, 2017.

[24] Renqian Luo, Fei Tian, Tao Qin, Enhong Chen, and Tie-Yan Liu. Neural architecture optimization. In *NeurIPS*, 2018.

[25] Colin White, Willie Neiswanger, and Yash Savani. BANANAS: bayesian optimization with neural architectures for neural architecture search. In *AAAI*, 2021.

[26] Han Shi, Renjie Pi, Hang Xu, Zhenguo Li, James T. Kwok, and Tong Zhang. Bridging the gap between sample-based and one-shot neural architecture search with BONAS. In *NeurIPS*, 2020.

[27] Lizheng Ma, Jiaxu Cui, and Bo Yang. Deep neural architecture search with deep graph bayesian optimization. In Payam M. Barnaghi, Georg Gottlob, Yannis Manolopoulos, Theodoros Tzouramanis, and Athena Vakali, editors, *WI*. ACM, 2019.

[28] Lingxi Xie and Alan L. Yuille. Genetic CNN. In *IEEE*, 2017.

[29] Esteban Real, Sherry Moore, Andrew Selle, Saurabh Saxena, Yutaka Leon Suematsu, Jie Tan, Quoc V. Le, and Alexey Kurakin. Large-scale evolution of image classifiers. In Doina Precup and Yee Whye Teh, editors, *ICML*, 2017.

[30] Kaixiong Zhou, Qingquan Song, Xiao Huang, and Xia Hu. Auto-gnn: Neural architecture search of graph neural networks. 2019.

[31] Sirui Xie, Hehui Zheng, Chunxiao Liu, and Liang Lin. SNAS: stochastic neural architecture search. In *ICLR*, 2019.

[32] Yijian Qin, Xin Wang, Zeyang Zhang, and Wenwu Zhu. Graph differentiable architecture search with structure learning. In *NeurIPS*, 2021.

[33] Kaicheng Yu, Christian Sciuto, Martin Jaggi, Claudiu Musat, and Mathieu Salzmann. Evaluating the search phase of neural architecture search. In *ICLR*, 2020.

[34] Chris Zhang, Mengye Ren, and Raquel Urtasun. Graph hypernetworks for neural architecture search. In *ICLR*, 2019.

[35] Yiren Zhao, Duo Wang, Xitong Gao, Robert D. Mullins, Pietro Liò, and Mateja Jamnik. Probabilistic dual network architecture search on graphs. 2020.

[36] Bowen Baker, Otkrist Gupta, Ramesh Raskar, and Nikhil Naik. Accelerating neural architecture search using performance prediction. In *ICLR*, 2018.

[37] Boyang Deng, Junjie Yan, and Dahua Lin. Peephole: Predicting network performance before training. *Arxiv*, 2017.

[38] Han Shi, Renjie Pi, Hang Xu, Zhenguo Li, James T. Kwok, and Tong Zhang. Multi-objective neural architecture search via predictive network performance optimization. 1911.09336, 2019.

[39] Muhan Zhang, Shali Jiang, Zhicheng Cui, Roman Garnett, and Yixin Chen. D-VAE: A variational autoencoder for directed acyclic graphs. In *NeurIPS*, 2019.

[40] Hayeon Lee, Eunyoung Hyung, and Sung Ju Hwang. Rapid neural architecture search by learning to generate graphs from datasets. In *ICLR*, 2021.

[41] Hayeon Lee, Sewoong Lee, Song Chong, and Sung Ju Hwang. Hardware-adaptive efficient latency prediction for NAS via meta-learning. In Marc'Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan, editors, *NeurIPS*, 2021.

[42] Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *ICLR*, 2017.

[43] Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? In *ICLR*, 2019.

[44] William L. Hamilton, Zhitao Ying, and Jure Leskovec. Inductive representation learning on large graphs. In *NeurIPS*, pages 1024–1034, 2017.

[45] Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. Graph attention networks. *ICLR*, 2018.

[46] Christopher J. C. Burges, Tal Shaked, Erin Renshaw, Ari Lazier, Matt Deeds, Nicole Hamilton, and Gregory N. Hullender. Learning to rank using gradient descent. In *ICML*, 2005.

[47] Chi Hu, Chenglong Wang, Xiangnan Ma, Xia Meng, Yinqiao Li, Tong Xiao, Jingbo Zhu, and Changliang Li. Ranknas: Efficient neural architecture search by pairwise ranking. In *EMNLP*, 2021.

[48] Prithviraj Sen, Galileo Namata, Mustafa Bilgic, Lise Getoor, Brian Gallagher, and Tina Eliassi-Rad. Collective classification in network data. *AI Mag.*, 2008.

[49] Weihua Hu, Matthias Fey, Marinka Zitnik, Yuxiao Dong, Hongyu Ren, Bowen Liu, Michele Catasta, and Jure Leskovec. Open graph benchmark: Datasets for machine learning on graphs. *arXiv preprint arXiv:2005.00687*, 2020.

[50] Oleksandr Shchur, Maximilian Mumme, Aleksandar Bojchevski, and Stephan Günnemann. Pitfalls of graph neural network evaluation. 2018.

[51] Hanqing Zeng, Hongkuan Zhou, Ajitesh Srivastava, Rajgopal Kannan, and Viktor K. Prasanna. Graphsaint: Graph sampling based inductive learning method. In *ICLR*, 2020.

[52] Christopher Morris, Nils M. Kriege, Franka Bause, Kristian Kersting, Petra Mutzel, and Marion Neumann. Tudataset: A collection of benchmark datasets for learning with graphs. 2020.

[53] Alex Krizhevsky. Learning multiple layers of features from tiny images. In *Technical report*, 2009.

[54] Chaoyu Guan, Xin Wang, and Wenwu Zhu. Autoattend: Automated attention representation search. In *ICML*, 2021.

[55] Laurens van der Maaten and Geoffrey Hinton. Visualizing high-dimensional data using t-sne. *Journal of Machine Learning Research*, 2008.

[56] Christopher Morris, Martin Ritzert, Matthias Fey, William L. Hamilton, Jan Eric Lenssen, Gaurav Rattan, and Martin Grohe. Weisfeiler and leman go neural: Higher-order graph neural networks. In *AAAI*, pages 4602–4609, 2019.

[57] Filippo Maria Bianchi, Daniele Grattarola, Lorenzo Livi, and Cesare Alippi. Graph neural networks with convolutional ARMA filters. *arXiv*, 2019.

[58] Jian Du, Shanghang Zhang, Guanhang Wu, José M. F. Moura, and Soummya Kar. Topology adaptive graph convolutional networks.

[59] Hongyang Gao and Shuiwang Ji. Graph u-nets. In *ICML*, volume 97, pages 2083–2092, 2019.

[60] Junhyun Lee, Inyeop Lee, and Jaewoo Kang. Self-attention graph pooling. In *ICML*, 2019.

[61] Zheng Ma, Junyu Xuan, Yu Guang Wang, Ming Li, and Pietro Liò. Path integral based convolution and pooling for graph neural networks. 2020.

[62] Frederik Diehl. Edge contraction pooling for graph neural networks. *CoRR*, abs/1905.10990, 2019.

A Experiment Details

A.1 Settings

Graph classification datasets. The graph classification datasets used in this work are summarized in Table 3. And the detailed dataset statics can be referred from https://chrsmrrs.github.io/datasets/docs/datasets/.

Table 3: List of the graph classification datasets used in this work.

Small Scale	AIDS, BZR-MD, COX2-MD, DHFR-MD, Mutagenicity, NCI1, NCI109, PTC-MM, PTC-MR
Medium/Large Scale	Tox21-AhR, MCF-7, MOLT-4, UACC257, Yeast, NCI-H23, OVCAR-8, P388, PC-3, SF-295, SN12C, SW-620

Specifically, all datasets are binary classification tasks that predict certain properties for small molecules. For example, the labels in Tox21-AhR represent toxicity/non-toxicity, while the graphs in Mutagenicity are classified into two classes based on their mutagenic effect on a bacterium [52]. Consequently, we use atom types as the node features and bond types as edge features.

Evaluation metrics. For Reddit, we use F1 score (micro) as the evaluation metric following the previous work [51]. For other node classification tasks and image dataset, we use classification accuracy as the evaluation metric. For the graph classification tasks, we use ROC-AUC as the evaluation metric.

Dataset splits. For ogbn-arxiv and Reddit, we use the standardized dataset split. For other node classification datasets, we split the nodes in each graph into 70%, 10%, 20% in training, validation, and test sets, respectively. For graph classification tasks, we split the graphs into 80%, 10%, 10% for training, validation, and test sets, respectively.

Hyper-Parameters. We tuned the hyper-parameters of the baselines based on the default setting in their public codes. For FALCON, we construct the candidate set as the 3-hop neighbors of the explored nodes and set the number of start nodes as $\min(\lceil 10\% \cdot K \rceil, 10)$, where K denotes the exploration size. The meta-GNN is constitute of 3 message-passing layers and 3 label propagation layers. All the experiments are repeated at least 3 times.

A.2 Design Spaces

A.2.1 Design Spaces for the Sample-based Methods

In this work, we use different design spaces for the datasets depending on the task types, *i.e.,* node or graph level. We summarize the design variables and choices in Table 4 and Table 5. For the design space of Reddit, we replace "Aggregation" in Table 4 with "Convolutional layer type", which takes values from {GCNConv [42], SAGEConv [44], GraphConv [56], GINConv [43], ARMAConv [57], TAGConv [58]}.

Table 4: Design Space for the node-level tasks (except for Reddit). 11,664 candidates in total.

Type	Variable	Candidate Values
Hyper-parameters	Learning rate decay
Dropout ratio	[0.1, 0.2]
[0.0, 0.3, 0.6]
Architecture	# Pre-process layers
Message passing layers
Post-precess layers
Layer connectivity
Activation
Batch norm
Aggregation	[1, 2, 3]
[2, 4, 6, 8]
[1, 2, 3]
STACK, SUM, CAT
ReLU, Swish, Prelu
True, False
Mean, Max, SUM

Table 5: Design Space for the graph-level tasks. 116,640 candidates in total.

Type	Variable	Candidate Values
Hyper-parameters	Learning rate decay	[0.1, 0.2]
	Dropout ratio	[0.0, 0.3, 0.6]
Architecture	# Pre-process layers	[1, 2, 3]
	# Message passing layers	[2, 4, 6, 8]
	# Post-precess layers	[1, 2, 3]
	Layer connectivity	STACK, SUM, CAT
	Activation	ReLU, Swish, Prelu
	Batch norm	True, False
	Aggregation	Mean, Max, SUM
	Node pooling flag (Use node pooling)	True, False
	Node pooling type (if applicable)	TopkPool [59], SAGPool [60], PANPool [61], EdgePool [62]
	Node pooling loop	[2, 4, 6]

Specifically, The STACK design choice means directly stacking multiple GNN layers, *i.e.,* without skip-connections. We also support node pooling operations for graph classification tasks, where the pooling loop stands for the number of message passing layers between each pooling operation. If the number of message passing layers is m and the node pooling loop is l, there will be a node pooling layer after the ith message passing layer in the design model (hierarchical pooling), where $i \in \{1 + k \cdot l \mid k = 0, \ldots, \lceil (m-1)/l \rceil - 1\}$. Moreover, to avoid duplicated and invalid designs, some design variables are required to satisfy specific dependency rules, and we take two examples to elaborate on this point.

- *If the node pooling flag of a design is False, then the design does not have any value on node pooling type and node pooling loop, and vice versa.*
  For example, we denote node pooling flag as f, node pooling type as t, and $*$ as any design choice, then(f=False, $t=*$) or (f=False, l=*) will both be invalid.

- *The node pooling loop should not exceed the number of message passing layers.*
  For example, design A (m=4, l=4) and design B (m=4, l=6) that take the same values on other design variables are duplicated.

Thus, the design graph constructed under dependency rules is more complex. Without loss of generality, we define that the distance of (f=False) and (f=True, l=MIN($\{i \in \mathbb{L}\}$)) as 1, where $\mathbb{L}$ represents the design choice of node pooling loop. Thus, the design graph is a connected graph that enables the exploration of any node with random initialization. It is also worth mentioning that the search strategy of FALCON is modularized given the design graph. In contrast, the dependency rules constrain the action space of reinforcement learning methods, *e.g.,* (f=Ture $\to$ False) is inapplicable, which requires special operation inside the controller.

Table 6: Statistics and the construction time of the design graphs.

	#Nodes	#Edges (Undirected)	Ave. Degree	Diameter	construction time (s)
DG-1	11,664	84,564	14.5	14	26
DG-2	116,640	1,084,752	18.6	18	295

We further summarize the statistics and construction time of the design graphs in Table 6, where DG-1 and DG-2 denote the design graphs for node-level and graph-level tasks, respectively. We use multi-processing programing on 50 CPUs (Intel Xeon Gold 5118 CPU @ 2.30GHz) to conduct the graph construction. Note that we don't have to construct the entire design graph in the pre-processing step, since we only extend the small portion of the design graph, *i.e.,* , the design subgraph, during the search process. Thus, the total time cost of constructing the design subgraph will be $O(E')$ where E' is the number of edges in the design subgraph, which largely lowers the time costs.

Table 7: Design space for the one-shot baselines on node and graph classification tasks.

Variable	Candidate Values
Dropout ratio	[0.0, 0.3, 0.6]
Layer connectivity	STACK, SUM
# Pre-process layers	[1, 2, 3]
# Message passing layers	[2, 4, 6, 8]
# Post-precess layers	[1, 2, 3]
Activation	ReLU, Swish, Prelu
Batch norm	True, False
Aggregation	Mean, Max, SUM

Figure 5: Search cost on the selected datasets.

A.2.2 Design Spaces for the One-shot Baselines

The one-shot models [1, 2] is built upon a super-model that is required to contain all of the architecture choices. We build the macro search space over entire models for both node classification and graph classification datasets with constraints. Firstly, we do not consider CAT (skip-concatenate) a layer connectivity choice, and we also remove design variables for node pooling. The reason is that CAT and node pooling operations change the input shape and make the output embeddings inapplicable for the subsequent weight-sharing modules in our settings. Secondly, the layer connectivity is customized for each layer following the previous works [1, 2], instead of setting as a global value for every layer. Overall, we summarize the design space in Table 7.

To enable a fair comparison, we fine-tune the hyper-parameters and report the best results of the architectures found by the one-shot methods according to their performance in the validation sets.

B More Experimental Results on Graph Tasks

B.1 Graph Classification Tasks

Task performance. Here we provide more results of task performance on the graph classification dataset. We repeat each experiment at least 3 times and report the average performances and the standard errors. The results are summarized in Table 8. The results well demonstrate the preeminence of FALCON in searching for good designs under different data distributions.

Search cost. As shown in Figure 5, we report the search cost of Random, DARTS, ENAS, GraphNAS, and FALCON on the selected datasets. The time measurements are conducted on a single NVIDIA GeForce 3070 GPU (24G). We see FALCON has a comparable time cost with Random and DARTS, which empirically proves the efficiency of FALCON.

However, as FALCON still needs to sample designs and train them from scratch (*i.e.,* the search cost of FALCON is bounded by the search cost of Random), the computational cost is relatively high in large datasets, *e.g.,* OVCAR-8 and MCF-7. We can potentially alleviate this limitation via integrating dataset sampling to reduce time costs.

Table 8: Test performance (ROC-AUC) on the graph classification datasets.

	DHFR-MD	COX2-MD	Mutagenicity	MOLT-4	NCI-H23	PTC-MR	P388
Random	$59.0_{\pm5.2}$	$63.2_{\pm1.9}$	$77.1_{\pm1.9}$	$58.6_{\pm0.7}$	$58.4_{\pm2.1}$	$59.9_{\pm5.7}$	$63.9_{\pm0.7}$
BO [22]	$55.1_{\pm0.0}$	$\mathbf{71.6_{\pm5.5}}$	$78.3_{\pm0.7}$	$58.1_{\pm2.0}$	$63.6_{\pm0.0}$	$58.8_{\pm7.7}$	$68.9_{\pm0.0}$
SA	$56.0_{\pm7.1}$	$67.4_{\pm3.1}$	$81.1_{\pm0.3}$	$54.8_{\pm1.1}$	$56.7_{\pm3.2}$	$59.4_{\pm6.2}$	$74.4_{\pm1.0}$
ENAS [2]	$53.5_{\pm3.7}$	$57.9_{\pm1.7}$	$75.0_{\pm1.6}$	$61.5_{\pm0.1}$	$61.2_{\pm1.1}$	$59.8_{\pm1.6}$	$68.3_{\pm1.2}$
DARTS [1]	$55.8_{\pm6.3}$	$70.4_{\pm3.2}$	$74.4_{\pm0.7}$	$61.4_{\pm0.7}$	$63.5_{\pm1.9}$	$59.3_{\pm0.5}$	$70.8_{\pm0.7}$
GraphNAS [8]	$61.6_{\pm4.3}$	$63.9_{\pm2.5}$	$80.2_{\pm1.5}$	$62.1_{\pm1.0}$	$62.4_{\pm3.9}$	$58.6_{\pm6.7}$	$68.2_{\pm2.5}$
AutoAttend [54]	$63.3_{\pm0.9}$	$68.8_{\pm0.7}$	$79.6_{\pm0.1}$	$59.5_{\pm0.2}$	$61.8_{\pm0.2}$	$57.8_{\pm0.6}$	$74.9_{\pm0.5}$
GASSO [32]	$60.9_{\pm2.3}$	$68.5_{\pm2.0}$	$75.1_{\pm0.5}$	$57.4_{\pm0.9}$	$64.7_{\pm1.5}$	$51.9_{\pm5.2}$	$71.3_{\pm1.4}$
FALCON-G	$58.5_{\pm8.8}$	$67.3_{\pm3.6}$	$79.8_{\pm1.7}$	$62.8_{\pm3.3}$	$62.2_{\pm1.2}$	$55.6_{\pm6.9}$	$74.2_{\pm3.7}$
FALCON-LP	$61.4_{\pm1.5}$	$66.8_{\pm3.6}$	$80.2_{\pm0.8}$	$58.5_{\pm8.8}$	$63.7_{\pm4.1}$	$55.6_{\pm2.0}$	$75.1_{\pm1.1}$
FALCON	$\mathbf{63.6_{\pm7.9}}$	$67.3_{\pm3.2}$	$\mathbf{81.1_{\pm0.5}}$	$\mathbf{64.4_{\pm4.0}}$	$\mathbf{66.6_{\pm3.3}}$	$\mathbf{60.0_{\pm1.4}}$	$\mathbf{77.0_{\pm1.4}}$

(cont.) PTC-MM	PC-3	SF-295	NCI1	SW-620	UACC257	Yeast	Avg.
$52.5_{\pm5.6}$	$60.4_{\pm0.0}$	$55.3_{\pm0.5}$	$77.5_{\pm0.3}$	$57.5_{\pm2.7}$	$61.1_{\pm0.5}$	$53.3_{\pm0.0}$	61.3
$60.1_{\pm1.5}$	$59.7_{\pm0.1}$	$60.6_{\pm0.3}$	$77.3_{\pm0.0}$	$63.8_{\pm0.9}$	$60.8_{\pm0.0}$	$55.0_{\pm0.0}$	63.7
$58.1_{\pm4.6}$	$69.0_{\pm2.0}$	$55.3_{\pm0.6}$	$79.6_{\pm5.3}$	$58.2_{\pm2.1}$	$64.2_{\pm0.1}$	$53.8_{\pm1.2}$	63.4
$52.4_{\pm2.9}$	$62.2_{\pm1.1}$	$60.9_{\pm2.2}$	$77.2_{\pm1.2}$	$64.8_{\pm2.2}$	$64.7_{\pm0.5}$	$\mathbf{63.0_{\pm1.1}}$	63.0
$52.6_{\pm4.1}$	$61.6_{\pm0.5}$	$62.2_{\pm1.1}$	$66.3_{\pm3.0}$	$66.0_{\pm0.3}$	$65.7_{\pm0.2}$	$61.4_{\pm1.4}$	63.7
$54.8_{\pm3.9}$	$68.6_{\pm2.6}$	$65.0_{\pm3.1}$	$78.1_{\pm3.6}$	$61.8_{\pm4.4}$	$61.5_{\pm5.1}$	$57.2_{\pm1.1}$	64.6
$\mathbf{64.7_{\pm1.2}}$	$66.2_{\pm0.3}$	$64.2_{\pm0.9}$	$79.3_{\pm1.6}$	$65.5_{\pm0.4}$	$57.1_{\pm0.5}$	$59.6_{\pm0.8}$	65.9
$63.2_{\pm0.7}$	$66.0_{\pm1.8}$	$\mathbf{65.8_{\pm0.4}}$	$76.6_{\pm0.6}$	$64.7_{\pm1.1}$	$62.7_{\pm0.2}$	$60.1_{\pm0.4}$	64.9
$55.2_{\pm2.4}$	$65.1_{\pm2.8}$	$64.3_{\pm2.1}$	$80.6_{\pm0.8}$	$62.0_{\pm3.0}$	$61.0_{\pm3.8}$	$57.5_{\pm1.5}$	64.7
$56.8_{\pm6.1}$	$68.1_{\pm0.3}$	$63.5_{\pm3.4}$	$80.4_{\pm0.5}$	$65.2_{\pm1.7}$	$54.5_{\pm1.1}$	$56.6_{\pm1.7}$	64.7
$57.1_{\pm0.1}$	$\mathbf{71.0_{\pm1.7}}$	$64.4_{\pm0.4}$	$\mathbf{80.9_{\pm0.8}}$	$\mathbf{66.6_{\pm2.1}}$	$\mathbf{66.7_{\pm2.1}}$	$58.1_{\pm1.7}$	$\mathbf{67.5^{*}}$

Figure 6: Accuracy *v.s.* the number of explored nodes on two graph classification datasets.

ROC-AUC *v.s.* exploration size. Here we report the change in task performance on graph classification datasets with the number of explored nodes. In Figure 6, we visualize the results on two graph classification datasets. We see that FALCON can approach the best-performing designs quickly as the explored size grows.

B.2 Best Designs

In Table 9 and Table 10, we summarize the best designs found by FALCON and BRUTEFORCE in each dataset, where the average number of parameters is 137.5k for all the graph classification datasets. Note that we select the best designs according to their performance on validation sets; thus, there are cases where FALCON surpasses BRUTEFORCE. We highlight the design variables that are different between FALCON and BRUTEFORCE for comparison.

Table 9: Average parameters & Best designs in the node classification datasets.

Dataset	Average Param (k)	Best design		Test performance (%)
ogbn-arxiv	44.5	FALCON	*(0.1, 0.0, 1, 4, 2, STACK, Swish, True, Mean)*	70.36
		BRUTEFORCE	*(0.1, 0.3, 1, 4, 2, SUM, Relu, True, Mean)*	70.51
Cora	77.8	FALCON	*(0.1, 0.0, 1, 6, 1, SUM, Swish, False, Mean)*	87.18
		BRUTEFORCE	*(0.1, 0.0, 1, 4, 1, STACK, Swish, False, Mean)*	86.99
Citeseer	289.0	FALCON	*(0.1, 0.3, 1, 2, 1, SUM, Prelu, True, Mean)*	76.19
		BRUTEFORCE	*(0.2, 0.3, 1, 2, 2, SUM, Prelu, False, Mean)*	75.99
Pubmed	57.8	FALCON	*(0.2, 0.3, 1, 8, 1, SUM, Relu, True, Add)*	90.04
		BRUTEFORCE	*(0.2, 0.3, 1, 8, 1, SUM, Relu, True, Add)*	90.04
AmazonComputers	46.2	FALCON	*(0.1, 0.0, 1, 4, 1, STACK, Swish, True, Mean)*	91.64
		BRUTEFORCE	*(0.1, 0.0, 3, 4, 2, STACK, Prelu, True, Mean)*	91.35
Reddit	47.2	FALCON	*(0.1, 0.0, 3, 4, 2, STACK, Prelu, True, ARMAConv)*	95.46
		BRUTEFORCE	*(0.1, 0.0, 3, 4, 2, STACK, Prelu, True, ARMAConv)*	95.46

B.3 Bruteforce's confidence interval and variant

To estimate the uncertainty of Bruteforce, we compute the 95% confidence interval of Bruteforce using bootstrapping. Moreover, we consider a variant of Bruteforce baseline to compare with Bruteforce. Specifically, we train all the designs in the design space for 30 epochs, select the top 10% design, and resume the training until 50 epochs. After that, we choose the top 50% designs to be fully trained and return the best fully trained design based on the validation performance. We run Bruteforce-bootstrap on four datasets as demonstrations. We summarize the results in Table 11.

Table 11: Test performances of Bruteforce and its variant.

	Cora	CiteSeer	ER-MD	AIDS
Bruteforce (max)	87.0	76.0	83.3	96.0
Confidence interval length	0.2	0.1	0.6	0.0
Bruteforce-bootstrap	87.0	76.4	83.8	95.7

Surprisingly, we found that the performance of Bruteforce and Bruteforce-bootstrap are very close. This indicates that Bruteforce (fully trained 5% design) is a good surrogate of Bruteforce-bootstrapping (fully trained 5% design, but using bootstrapping selection), and could also well approximate the ground truth performance of the best design.

C   Experimental Results on the Image Task

C.1   Dataset pre-processing

We use the CIFAR-10 [53] image dataset to show FALCON can work well on other machine learning domains. This dataset consists of 50,000 training images and 10,000 test images. And we randomly crop them to size 32×32, and conduct random flipping and normalization.

C.2   Design Space

We construct micro design space for the computational cells. Each cell constitutes of two branches, where we enable five selections: separable convolution with kernel size 3×3 and 5×5, average pooling and max pooling with kernel size 3×3, and identity. In each branch, we have one dropout layer, where the dropout ratio is one of $\{0.0, 0.3, 0.6\}$, and one batch normalization layer. We also use one of identity and skip-sum as skip-connection within each branch. After the input data is separately computed in each branch, the outputs are added as the final cell output, which is different with the original ENAS paper that searches the computational DAG on the defined nodes. For

Table 10: Best designs in the graph classification datasets.

Dataset		Best design	Test performance (%)
AIDS	FALCON	(0.2, 0.3, 1, 4, 2, SUM, Prelu, True, Add, NoPool)	99.02
	BRUTEFORCE	(0.2, 0.0, 3, 8, 2, STACK, Relu, True, Add, SAGPool, 2)	95.97
COX2-MD	FALCON	(0.2, 0.0, 2, 6, 1, SUM, Swish, True, Add, EdgePool, 2)	69.87
	BRUTEFORCE	(0.2, 0.0, 1, 4, 3, STACK, Prelu, True, Max, TopkPool, 2)	65.39
DHFR-MD	FALCON	(0.1, 0.3, 2, 4, 2, SUM, Swish, True, Mean, PANPool, 2)	71.33
	BRUTEFORCE	(0.1, 0.0, 1, 4, 3, CAT, Prelu, True, Mean, SAGPool, 4)	56.22
ER-MD	FALCON	(0.2, 0.3, 3, 4, 2, CAT, Relu, True, Add, PANPool, 2)	81.67
	BRUTEFORCE	(0.2, 0.0, 3, 5, 3, CAT, Prelu, True, Max, PANPool, 6)	83.33
MCF-7	FALCON	(0.2, 0.6, 1, 8, 2, CAT, Swish, True, Add, NoPool)	67.85
	BRUTEFORCE	(0.1, 0.0, 1, 2, 6, SUM, Prelu, True, Add, NoPool)	70.61
MOLT-4	FALCON	(0.1, 0.0, 3, 6, 2, SUM, Prelu, True, Max, NoPool)	69.03
	BRUTEFORCE	(0.1, 0.0, 1, 6, 1, SUM, Prelu, True, Add, NoPool)	70.30
Mutagenicity	FALCON	(0.1, 0.0, 2, 6, 1, CAT, Relu, True, Add, NoPool)	81.73
	BRUTEFORCE	(0.1, 0.0, 2, 4, 2, CAT, Relu, True, Add, PANPool, 2)	81.17
NCI1	FALCON	(0.1, 0.0, 2, 4, 2, SUM, Swish, True, Max, EdgePool, 2)	80.13
	BRUTEFORCE	(0.1, 0.0, 1, 4, 2, STACK, Prelu, True, Add, EdgePool, 4)	82.81
NCI109	FALCON	(0.1, 0.0, 2, 8, 2, STACK, Prelu, True, Max, NoPool)	79.98
	BRUTEFORCE	(0.2, 0.0, 3, 6, 2, STACK, Prelu, True, Add, EdgePool, 6)	81.77
NCI-H23	FALCON	(0.1, 0.0, 2, 6, 1, CAT, Swish, True, Add, NoPool)	71.14
	BRUTEFORCE	(0.1, 0.0, 2, 6, 1, CAT, Swish, True, Add, NoPool)	71.14
OVCAR-8	FALCON	(0.1, 0.6, 2, 6, 2, CAT, Swish, True, Add, NoPool)	68.21
	BRUTEFORCE	(0.1, 0.6, 1, 2, 3, CAT, Swish, True, Add, NoPool)	67.40
P388	FALCON	(0.1, 0.0, 2, 6, 2, CAT, Prelu, True, Add, NoPool)	78.75
	BRUTEFORCE	(0.1, 0.0, 2, 6, 2, CAT, Prelu, True, Add, NoPool)	78.75
PC-3	FALCON	(0.2, 0.0, 2, 6, 1, SUM, Relu, True, Max, NoPool)	73.28
	BRUTEFORCE	(0.2, 0.0, 2, 6, 1, SUM, Relu, True, Max, NoPool)	73.28
PTC-MM	FALCON	(0.2, 0.0, 2, 4, 2, STACK, Swish, True, Max, EdgePool, 2)	56.96
	BRUTEFORCE	(0.2, 0.0, 3, 6, 1, SUM, Swish, True, Mean, EdgePool, 2)	52.93
PTC-MR	FALCON	(0.2, 0.0, 2, 4, 2, SUM, Swish, True, Mean, TopkPool, 2)	60.56
	BRUTEFORCE	(0.1, 0.3, 1, 6, 2, SUM, Relu, True, Add, NoPool)	63.06
SF-295	FALCON	(0.1, 0.6, 2, 6, 2, CAT, Swish, True, Add, NoPool)	64.75
	BRUTEFORCE	(0.1, 0.0, 3, 8, 3, SUM, Prelu, True, Max, PANPool, 4)	66.47
SN12C	FALCON	(0.1, 0.0, 1, 8, 1, CAT, Swish, True, Add, NoPool)	73.34
	BRUTEFORCE	(0.1, 0.0, 1, 8, 3, CAT, Prelu, True, Add, EdgePool, 6)	73.73
SW-620	FALCON	(0.1, 0.0, 2, 4, 2, STACK, Prelu, True, Max, NoPool)	69.26
	BRUTEFORCE	(0.1, 0.0, 2, 4, 2, STACK, Prelu, True, Max, NoPool)	69.26
Tox21-AhR	FALCON	(0.1, 0.0, 2, 4, 2, SUM, Prelu, True, Add, EdgePool, 2)	79.10
	BRUTEFORCE	(0.2, 0.0, 3, 6, 2, SUM, Prelu, True, Add, NoPool)	82.02
UACC257	FALCON	(0.2, 0.3, 2, 6, 2, CAT, Swish, True, Max, NoPool)	67.94
	BRUTEFORCE	(0.2, 0.0, 3, 6, 1, SUM, Prelu, True, Max, NoPool)	70.24
Yeast	FALCON	(0.1, 0.6, 1, 8, 1, CAT, Prelu, True, Add, NoPool)	59.60
	BRUTEFORCE	(0.1, 0.0, 1, 2, 3, SUM, Swish, True, Add, EdgePool, 2)	60.41

FALCON, we also include other hyper-parameters, including learning rate decay with design choice set $\{0.1, 0.2, 0.5\}$, and batch size, which is one of $\{64, 128, 256\}$.

C.3 Experiment Results

We set the exploration size as 25 for all the sample-based methods. For ENAS and DARTS, the learning rate is 0.01, and the maximum training epoch is 300. We repeat each experiment three times and summarize the results in Table 12.

Figure 7: Sensitivity of FALCON's hyper-parameters.

Table 12: Search results on CIFAR-10.

	Average Error (%)	Search Cost (GPU days)
Random	10.43	0.64
BO	9.83	0.67
SA	10.16	0.62
ENAS-micro	9.20	0.77
DARTS-micro	8.97	0.89
FALCON	8.79	0.81

D Sensitivity Analysis

We analyze the sensitivity of the hyper-parameters in the search strategy of FALCON, using a node classification task, CiteSeer, and a graph classification task, Tox21-AhR. Specifically, we study the influence of the number of random starting nodes and the candidate scale resulting from an explored node (*i.e.,* how many hop neighbors of an explored node are to be included in the candidate set).

As shown in Figure 7, we find that FALCON outperforms the best AutoML baselines with a large range of hyper-parameters. Specifically, 73% and 97% hyper-parameter combinations of FALCON rank best among the baselines in CiteSeer and Tox21-AhR, respectively.

Moreover, we discover an interesting insight about the size of *receptive field*, *i.e.,* the number of design candidates, during the search process of FALCON. According to the construction of design subgraph, the receptive field size is $O(rh^d)$, where r is the number of random start nodes, h is the number of neighbor hops, and d is the average node degree. We find that the performance of design searched by FALCON increases with the receptive field's size until it reaches a certain scale.

Such patterns have been widely observed in multiple datasets. While the receptive field on the design subgraph should contain sufficient candidates for sampling good ones, it should also prune inferior design space, which doesn't provide insights on navigating the best-performing designs. Thus, the size of the receptive field may be a crucial factor influencing the search quality of FALCON.