What Makes a "Good" Data Augmentation in Knowledge Distillation – A Statistical Perspective

Huan Wang[1,2,†]   **Suhas Lohit**[2,*]   **Mike Jones**[2]   **Yun Fu**[1]
[1]Northeastern University, Boston, MA   [2]MERL, Cambridge, MA
Project: https://huanwang.tech/Good-DA-in-KD

(a) Apply additional stronger DA in KD   (b) S. test loss *vs.* T. stddev with different DA schemes

Figure 1: **(a)** Illustration of applying a stronger data augmentation (DA) in addition to the standard DA (random crop+flip) in knowledge distillation (KD). We ask: *What characterizes a "good" DA when it is utilized in KD?* **(b)** Our major contributions are a proposition (Proposition 1) to answer the question rigorously, along with a practical metric to evaluate the "goodness" of a DA. The proposed metric is called *stddev of teacher's mean probability* (shorted as T. stddev). As seen in (b), there is a *strong* positive correlation between the student's test loss (S. test loss) and T. stddev, justifying the efficacy of the metric and the proposition (see more similar plots in our experiments).

Abstract

Knowledge distillation (KD) is a general neural network training approach that uses a teacher to guide a student. Existing works mainly study KD from the network output side (*e.g.*, how to design a better KD loss function), while few have attempted to understand it from the input side. Especially, its interplay with data augmentation (DA) has not been well understood. In this paper, we ask: Why do some DA schemes (*e.g.*, CutMix) inherently perform much better than others in KD? What characterizes a "good" DA in KD? Our investigation from a statistical perspective suggests that a good DA scheme should reduce the variance of the teacher's mean probability, which will eventually lead to a lower generalization error gap for the student. Besides the theoretical understanding, we also propose a new entropy-based data-mixing DA scheme to enhance CutMix. Extensive empirical studies support our claims and demonstrate how we can harvest considerable performance gains simply by using a better DA scheme in distillation.

[†]Work done when Huan was an intern at MERL
[*]Corresponding author: `slohit@merl.com`

1 Introduction

Deep neural networks (DNNs) are the top performing method in many artificial intelligence areas [24, 36]. How to effectively train a deep network for classification has been a central topic for decades. In the past several years, efforts have mainly focused on better architecture design (*e.g.*, batch normalization [19], residual blocks [13], dense connections [18]) and better loss functions (*e.g.*, label smoothing [41, 29], contrastive loss [17], large-margin softmax [25]) than the standard cross-entropy (CE) loss. Knowledge distillation (KD) [16] is a training method that falls into the second group. In KD, a stronger network – called teacher – is introduced to guide the learning of the original network – called student – by minimizing the discrepancy between the representations of the two networks,

$$\mathcal{L}_{KD} = (1 - \alpha)\mathcal{L}_{CE}(y, \mathbf{p}^{(s)}) + \alpha\tau^2 \mathcal{D}_{KL}(\mathbf{p}^{(t)}/\tau, \mathbf{p}^{(s)}/\tau), \tag{1}$$

where $\mathcal{D}_{KL}$ represents KL divergence [23]; $\alpha \in (0, 1)$ is a factor to balance the two loss terms; $\mathcal{L}_{CE}$ denotes the cross-entropy loss; y is the one-hot label and $\mathbf{p}^{(t)}, \mathbf{p}^{(s)}$ stand for the teacher's and student's output probabilities over the classes; τ is a temperature constant [16] to smooth predicted probabilities. KD allows us to train smaller, more efficient neural networks without compromising on accuracy, which facilitates deploying deep learning in resource constrained environments (*e.g.*, on mobile devices). KD has found plenty of applications in many tasks [6, 47, 12, 20, 48].

Most existing KD methods have attempted to improve it by proposing better KD loss functions applied at the network outputs [33, 30, 43]. Few works have considered KD from *the input side*. Especially, the interplay between KD and data augmentation (DA) [39] has not been well understood so far (note, by DA here, we mean the conventional DA concept: generating a new input by *transforming one or multiple inputs*. A broader scope of DA may involve the *neural network*, *e.g.*, dropout can be seen as a kind of data augmentation [3]. We do not consider this type of DA in this paper due to the limited length). In this work, we ask: *What defines a "better" data augmentation in knowledge distillation*? A clear answer to this question has many benefits. First, theoretically, it can help us towards a better understanding about how data augmentation plays a role in KD. Second, practically, it can bring us considerable performance gain – in Fig. 2, we empirically show that a stronger DA can lower the test error rate and admit more training iterations without overfitting. The figure shows test error rates using standard cross entropy loss (no teacher) as well as using knowledge distillation loss (with a teacher). It is pretty obvious to see that "Flip+Crop" is stronger than "Flip" alone in Fig. 2. However, for other DA schemes, such as Mixup [52] *vs.* AutoAugment [7], which one is stronger? We desire a principled way (for example, a concrete metric) to make the vague concept "stronger" exact. Presenting such a theoretically sound metric and empirically validating its effectiveness is the goal of this paper.

Intuitively, a better DA should enrich the input data and expose more knowledge of the teacher so that the student can generalize better. We formalize this idea from a statistical learning perspective. Specifically, we will show a good DA scheme is defined by a lower variance (or covariance) of the teacher's mean output probability over different input samples, which ultimately leads to a lower generalization gap for the student. The proposed theory is well justified by our extensive empirical studies on CIFAR100 and Tiny ImageNet datasets with various pairs. The proposed theory well explains why Cut-Mix is better than other alternatives (such as Mixup [52], AutoAugment [7]) in KD.

Besides the new theoretical results, we also propose an entropy-based data picking scheme to select more informative samples for KD, which can deliver even lower variance of the teacher's mean probability as well as lower generalization error of the student. We make the following contributions in this paper:

Figure 2: Test error rate of resnet20 on CIFAR100 when trained for different numbers of epochs with (KD) and without (CE) knowledge distillation (the teacher is resnet56 for KD). Each result is obtained by averaging 3 random runs (shaded area indicates the std). "Flip": random horizontal flip; "Crop": random crop. The optimal number of training epochs and its test loss are highlighted in red.

- We present a proven proposition that precisely answers what defines a better DA in KD: Given a fixed teacher, a better DA is the one that gives a lower variance of the teacher's mean output probability.

- The proposition is well justified empirically on standard image classification datasets with many teacher-student pairs.

- An entropy-based data picking scheme is introduced to further reduce the variance of the teacher's mean probability, which can further advance CutMix, the prior state-of-the-art DA approach among those evaluated in this paper.

- Empirically, we show how the presented theory can benefit in practice – we can simply enhance the existing KD methods by using a stronger DA and prolonged training iterations.

2 Related Work

Knowledge Distillation. The general idea of knowledge distillation is to guide the training of a student model through a stronger pretrained teacher model (or an ensemble of models). It was pioneered by Buciluǎ *et al.* [4] and later refined by Hinton *et al.* [16], who coined the term. Since its debut, knowledge distillation has seen extensive application in vision and language tasks [6, 14, 47, 20, 48]. Many variants have been proposed regarding the central question in knowledge distillation, that is, how to define the *knowledge* that is supposed to be transferred from the teacher to the student. Examples of such knowledge definitions include feature distance [34], feature map attention [51], feature distribution [31], activation boundary [15], inter-sample distance relationship [30, 33, 26, 44], and mutual information [43]. Several works [29, 38, 5] investigate the connection between label smoothing and knowledge distillation. Another line of work [42] attempts to understand KD more theoretically. Over the past several years, the progress has been made primarily for intermediate feature maps and network outputs (*i.e.*, through a better loss function). In contrast, our goal in this paper is to improve the KD performance at the *input end* with the help of data augmentation. We will show this path is as effective and also has much potential for future research.

Data Augmentation. Deep neural networks are prone to overfitting, *i.e.*, building input-target mappings using undesirable or irrelevant features (like noise) in the data. Data augmentation is a prevailing technique to curb overfitting [39]. In classification tasks, data augmentation aims to explicitly provide data with label-invariant transformations (such as random crop, horizontal flip, color jittering, Cutout [11]) during training so that the model can learn representations robust to those nuisance factors. Recently, more advanced data augmentation methods were proposed, which not only transform the input, but also transform the target. For example, Mixup [52] linearly mixes two images with the labels mixed by the same linear interpolation. Manifold Mixup [46] is similar to Mixup but conducts the mix operation in the feature level instead of pixel level; CutMix [49] pastes a patch cut from an image onto another image with the label decided by the area ratio of the two parts. AutoAugment [7] is a strong DA method that finds an optimal augmentation policy from a large search space that minimizes a task loss. When both the input and target are transformed simultaneously, the key is to maintain a *semantic correspondence* between the new input and new target. Although these methods have been proven effective, one lingering concern is the reasoning behind them. Specifically, it is easy to come up with examples where the semantic correspondence is poorly kept (see our Appendix for examples of CutMix on ImageNet). Unlike these methods, which focus on general classification using the cross-entropy loss, our work investigates the interplay between data augmentation and knowledge distillation loss and proposes new data augmentation specifically for knowledge distillation.

Some recent KD works also involve the utilization of DA in KD, such as [2, 8]. Especially, [2] also employs mixup and prolonged training to enhance the student performance in KD, akin to ours. Yet it is worthwhile to note that our paper is *substantially different* from them, in that we are seeking the *fundamental* reason explaining how to define a "better" DA in KD to deliver better performance; these works mainly investigate in an empirical fashion, with no rigorous results presented. Our work is not limited to one specific DA (see Sec. 5). We target a *general theoretical* understanding which can apply to a broad scope of DA schemes (fortunately, as our experiments show, the proposed theory and the derived DA "goodness" measure *indeed* capture it). The fact that [2] utilizes mixup [52] and prolonged training to deliver 82.8% top-1 accuracy with resnet-50 [13] on ImageNet [10] can be a direct proof that the principle proposed in this work can bring us very promising practical benefits.

One recent work [9] also conducts an empirical study on the impact of data augmentation on knowledge distillation. They first apply data augmentation (*e.g.*, mixup/CutMix) to the teacher then conduct the distillation step as usual (no extra data augmentation in this step); our investigation is the *exact opposite* to their setup: we train the teacher as usual (not applying mixup/CutMix), then in the distillation step we employ a more advanced data augmentation (*e.g.*, mixup/CutMix). Interestingly, they conclude that the teacher trained with mixup/CutMix *hurts* the student's generalization ability, while we consistently see a student performance boost via a stronger DA in the KD step.

The work of [28] presents a statistical perspective to understand how the softened probabilities in KD are better than the one-hot hard labels. Our work is inspired by their *Bayes teacher* notion. This said, our work is different from theirs in that we focus on explaining how data augmentation plays a role in KD and answer what characterizes a good DA, while they attempt to answer why the KD loss is better than the standard cross-entropy loss.

3 Theoretical Investigation

3.1 Prerequisites: Multi-Class Classification with KD

Given a training set $S = \{(x_n, y_n)\}_{n=1}^N \sim \mathcal{D}^N$, where $\mathcal{D}$ is the joint distribution for input-output random variable pair (x, y), the goal in multi-class classification is to pin down a predictor $\mathbf{f} : \mathcal{X} \to \mathbb{R}^C$ from hypothesis class $\mathcal{H}$ (C: the number of classes), which is supposed to minimize the *true risk*

$$R_{\mathcal{D}}(\mathbf{f}) \stackrel{\text{def}}{=} \mathop{\mathrm{E}}_{(x,y)\sim\mathcal{D}} \left[L(y, \mathbf{f}(x)) \right], \tag{2}$$

where L stands for the loss objective function (*e.g.*, cross-entropy); the subscript $\mathcal{D}$ of $R_{\mathcal{D}}$ is to emphasize that the true risk is defined on the data distribution. The true risk is approximated in practice on a separate test set.

For training, the predictor aims to minimize the *empirical risk* defined on the training sequence S,

$$R_S(\mathbf{f}) \stackrel{\text{def}}{=} -\frac{1}{N} \sum_{n=1}^N \mathbf{e}_{y_n}^\top \log(\mathbf{f}(x_n)), \tag{3}$$

where $\mathbf{e}_y \in \{0, 1\}^C$ is a one-hot vector indicating the label $y \in [C] = \{1, 2, \cdots, C\}$. The subscript S of R_S is to emphasize the empirical risk is defined on the finite sampled data points.

In the context of KD, the one-hot hard target vector $\mathbf{e}_y$ is replaced with a probability vector $\mathbf{p}^{(t)}(x) \in \mathbb{R}_+^C$, giving us the *empirical distilled risk* of $\mathbf{f}$

$$\hat{R}_S(\mathbf{f}) \stackrel{\text{def}}{=} -\frac{1}{N} \sum_{n=1}^N \mathbf{p}^{(t)}(x_n)^\top \log(\mathbf{f}(x_n)), \tag{4}$$

where the super-script t indicates the *fixed* teacher model. The theory concerning why Eq. (4) is better than Eq. (3) has been established in [28]. Interested readers may refer to their paper for more details. Next, we look into how the data augmentation plays a role in KD.

3.2 What Makes a "Good" DA in Distillation?

Intuitively, a better DA should provide more information, *i.e.*, expose more knowledge of the teacher so that the student can absorb more and thus generalize better. We make this idea rigorous as follows.

Proposition 1. *Given a bounded loss function and a fixed teacher model with the empirical distilled risk defined in Eq. (4), for any predictor* $\mathbf{f}$*, consider two sampled sequences* $S_1 \in \mathcal{D}^N$ *and* $S_2 \in \mathcal{D}^N$*, they are made up of elements sampled from the same distribution* $\mathcal{D}$*, **while not i.i.d.** (especially when we use data augmentation). If the elements in* S_1 *present a larger correlation than those in* S_2*, then the student's generalization gap trained on* S_1 *will be greater than that trained on* S_2*:*

$$\mathop{\mathrm{E}}_{S_1 \sim \mathcal{D}^N} \left[(\hat{R}_{S_1}(\mathbf{f}) - R_{\mathcal{D}}(\mathbf{f}))^2 \right] > \mathop{\mathrm{E}}_{S_2 \sim \mathcal{D}^N} \left[(\hat{R}_{S_2}(\mathbf{f}) - R_{\mathcal{D}}(\mathbf{f}))^2 \right]. \tag{5}$$

Proof. Let $\Delta = \hat{R}_S(\mathbf{f}) - R_{\mathcal{D}}(\mathbf{f})$. By the definition of variance, $\mathrm{E}_S[\Delta^2] = \mathrm{Var}_S[\Delta] + (\mathrm{E}_S[\Delta])^2$. To make the notation clearer, we define $q(x_i) = -\mathbf{p}^{(t)}(x_i)^\top \log(\mathbf{f}(x_i))$.

(1) Since $R_\mathcal{D}(\mathbf{f})$ is a constant (albeit unknown),

$$\mathrm{E}_{S \sim \mathcal{D}^N}[\Delta] = \mathrm{E}_S[\hat{R}_S(\mathbf{f})] + \text{Const} = \mathrm{E}_S[\frac{1}{N}\sum_{i=1}^N q(x_i)] + \text{Const}$$

$$= \frac{1}{N}\sum_{i=1}^N \mathrm{E}_S[q(x_i)] + \text{Const} = \frac{1}{N}\sum_{i=1}^N \mathrm{E}_{x_i}[q(x_i)] + \text{Const} \tag{6}$$

$$= \frac{1}{N} \cdot N \cdot \mathrm{E}_x[q(x)] + \text{Const} = \mathrm{E}_x[q(x)] + \text{Const},$$

where the second last equation is due to the fact that each element x_i in S is drawn from the same distribution $\mathcal{D}$. We can clearly see that for S_1, S_2, $\mathrm{E}_S[\Delta]$ is the same.

(2) Then we consider $\mathrm{Var}_S[\Delta]$. Again, since $R_\mathcal{D}(\mathbf{f})$ is a constant,

$$\mathrm{Var}_S[\hat{R}_S(\mathbf{f})] = \mathrm{Var}_S[\frac{1}{N}\sum_{i=1}^N q(x_i)] = \frac{1}{N^2}\mathrm{Cov}_S[\sum_{j=1}^N q(x_j), \sum_{k=1}^N q(x_k)]$$

$$= \frac{1}{N^2}\Big(\sum_{i=1}^N \mathrm{Var}_{x_i}[q(x_i)] + 2\sum_{1 \le j < k \le N} \mathrm{Cov}_S[q(x_j), q(x_k)]\Big) \tag{7}$$

$$= \frac{1}{N^2}\Big(N \cdot \mathrm{Var}_x[q(x)] + 2\sum_{1 \le j < k \le N} \mathrm{Cov}_S[q(x_j), q(x_k)]\Big)$$

$$= \frac{1}{N}\mathrm{Var}_x[q(x)] + \frac{2}{N^2}\sum_{1 \le j < k \le N} \mathrm{Cov}_S[q(x_j), q(x_k)],$$

where $\mathrm{Cov}[\cdot, \cdot]$ stands for covariance. From the last item in Eq. (7), we can see that the covariance part is different for different sampled S. If the samples in S_1 present a larger correlation than those in S_2, we will have $\mathrm{Var}_{S_1}[\Delta] > \mathrm{Var}_{S_2}[\Delta]$, which further leads to increased generalization gap for the student, $\mathrm{E}_{S_1}[(R_{S_1}(\mathbf{f}) - R_\mathcal{D}(\mathbf{f}))^2] > \mathrm{E}_{S_2}[(R_{S_2}(\mathbf{f}) - R_\mathcal{D}(\mathbf{f}))^2]$. $\qquad\square$

Practical use: Stddev of teacher's mean probability (T. stddev). Note in Proposition 1, the predictor $\mathbf{f}$ (*i.e.*, the student model) can be any one (not necessarily a converged model). Each student would have an order of different DA schemes regarding which is better in its opinion. Presumably, different students will lead to different such orders. For practical use, we must pick a certain student as "oracle" to do the evaluation. Here, we can play a trick that can make it rather simple to use our theory – *assume* there is a student that performs exactly the same with the teacher (this assumption is not unpractical, since one straightforward example is to use the teacher as student). Then we have

$$\mathrm{Cov}[q(x_j), q(x_k)] = \mathrm{Cov}[\mathbf{p}^{(t)}(x_j)^\top \log(\mathbf{f}(x_j)), \mathbf{p}^{(t)}(x_k)^\top \log(\mathbf{f}(x_k))]$$
$$= \mathrm{Cov}[\mathbf{p}^{(t)}(x_j)^\top \log(\mathbf{p}^{(t)}(x_j)), \mathbf{p}^{(t)}(x_k)^\top \log(\mathbf{p}^{(t)}(x_k))]. \tag{8}$$

That is, we only need the covariance of the *teacher's* probability to measure the "goodness" of a certain DA technique, no need for the student. Despite not using any information of the student, the proposed metric turns out to correlate surprisingly well with the student's performance (see Fig. 4 and Sec. A.1).

Based on Eq. (8), when using S_1 *vs.* S_2 as training sequence, the fundamental factor answering for the variance gap of $\mathrm{Var}_S[\Delta]$ boils down to the covariance in $\{\mathbf{p}^{(t)}(x_i)\}_{i=1}^N$. That is, a larger covariance in $\{\mathbf{p}^{(t)}(x_i)\}_{i=1}^N$ leads to a larger covariance in $\{\mathbf{p}^{(t)}(x_i)^\top \log(\mathbf{p}^{(t)}(x_i))\}_{i=1}^N$ in Eq. (8), which ultimately leads to a higher $\mathrm{Var}_S[\Delta]$ in Eq. (7).

The next step is to find a feasible way to estimate the covariance in $\{\mathbf{p}^{(t)}(x_i)\}_{i=1}^N$. Consider the average variable (denoted as $\mathbf{u}$ here) of several random variables $\{\mathbf{p}^{(t)}(x_k)\}_{k=1}^K$,

$$\mathbf{u} = \frac{1}{K}\sum_{x_k \in S^*} \mathbf{p}^{(t)}(x_k), \mathbf{u} \in \mathbb{R}_+^C. \tag{9}$$

Its variance (or equivalently, stddev) inherently takes into account the covariance among its addends. Therefore, we can use the variance of $\mathbf{u}$ as a proxy for the covariance in $\{\mathbf{p}^{(t)}(x_k)\}_{k=1}^K$:

$$\mathbf{m} = \mathrm{Var}_{S^*}(\mathbf{u}), \mathbf{m} \in \mathbb{R}_+^C, \quad \bar{m} = \frac{1}{C}\sum_{i \in [C]} (\mathbf{m}_i)^{\frac{1}{2}}, \bar{m} \in \mathbb{R}_+, \tag{10}$$

Figure 3: **(a)** Illustration of the difference of supervised target between the KD loss and cross-entropy (CE) loss. An input is transformed to different versions owing to data augmentation. KD loss can provide extra information to the student by mapping these views to different targets, while the CE loss cannot. This work attempts to answer what characterizes a "good" data augmentation scheme in distillation. **(b)** Illustration of adapting an existing DA approach to KD. The standard DA consists of random crop and horizontal flip. This training framework is employed to empirically verify our proposed metric to define a "stronger" data augmentation.

where K is a pre-defined number of samples of set S^* to realize the averaging effect (*e.g.*, $K = 640$ in our experiments for CIFAR100 and Tiny ImageNet – see Appendix Sec. A.3 for a concrete calculation example). Note, $\mathbf{u}$ can be interpreted as the *teacher's mean probability* over K input samples.

If there is a large covariance among $\{\mathbf{p}^{(t)}(x_k)\}_{k=1}^{K}$, $\mathbf{m}$ will be large (in an element-wise sense). Then the average of $\mathbf{m}$ over classes (we do this averaging simply because we desire a *scalar* metric) is a good indicator to capture such covariance. *We thus formally introduce $\bar{m}$, the (averaged) T. stddev, as the proposed metric to measure the quality of a data augmentation scheme.* A *lower* $\bar{m}$ implies a *better* DA by our definition. In the experiments, we will show this metric defined merely using the *teacher* can accurately characterize the generalization error of the *students* after distillation.

4 Evaluated Algorithms

4.1 Extend Existing DA Approaches for KD

Given an existing DA approach, this section explains how we adapt it properly to the case of KD.

Specifically, let x_0 denote the raw data, x denote the transformed data by the standard augmentation (random crop and flip). Illustrated in Fig. 3(b), we will add the DA following x to obtain x'. Unlike the common data augmentation where *only* the transformed input is fed into the network, we keep *both the input x and x'* for the training (as such, the number of input examples is increased, typically doubled). The consideration of keeping both inputs is to maintain the information path for the original input x so that we can easily see how the added information path of x' leads to a difference.

For x, its loss is still the original KD loss, consisting of the cross-entropy loss and the KL divergence (Eq. (1)). Of special note is that, for x', its loss is *only* the KL divergence, *i.e.*, *we do not use the labels assigned by the DA algorithm* (for example, in the original Mixup and CutMix, they assign a linearly interpolated label to the augmented sample) because these labels can actually be *wrong* (see Appendix Sec. A.4 for concrete examples on ImageNet). In fact, not using the hard label has another bonus. A dataset augmentation scheme which employs CE loss has to provide corresponding labels as supervisory information. In order to maintain the semantic correspondence, it cannot admit very extreme transformations for data augmentation. In contrast, in the mixup/CutMix+KD setting described above, the data augmentation scheme need not worry about the labels as they are assigned by the teacher. Therefore, it admits a *broader* set of transformations to expose the teacher's knowledge more completely. This reflects that data augmentation in KD has more freedom than in CE.

Among all the data augmentation techniques evaluated in this paper, we will show *CutMix works best*. The fundamental reason for its success, as we will show, is that it achieves a much lower variance of the teacher's mean probability, implying it produces more diverse data than its counterparts.

4.2 CutMixPick: Enhance CutMix with Entropy-based Data Picking

In this section, we propose a data picking scheme to further reduce the variance of the teacher's mean probability. The idea is partly inspired by *active learning* [37]. In active learning, the learner enjoys the freedom to query the data instances to be labeled for training by an oracle (*i.e.*, the teacher in our case) [37]. Since the augmented data can vary in their quality, we can introduce certain criterion to pick the more valuable data for the student.

Intuitively, we regard a sample with more *information* is of higher quality. Therefore, we take *Shannon's entropy* of the teacher's output probability as a natural measure to select samples,

$$H(\mathbf{p}^{(t)}(x)) = -\mathbf{p}^{(t)}(x)^\top \log(\mathbf{p}^{(t)}(x)). \tag{11}$$

Note this formula is exactly in the same form of Eq. (8) where a converged student is considered. Empirically, we will also show the data selected by this formula indeed results in lower $\bar{m}$ and better test loss of the student.

Concretely, given a batch of data, we first apply CutMix to obtain a bunch of augmented samples. Then sort all the augmented samples by Eq. (11) in ascending order and keep the top r (a pre-defined percentage constant, $r = 0.5$ in our experiments) samples.

This simple technique can be rather effective according to our empirical study. Another seemingly potential alternative is to use the *student's* entropy as the picking metric. The intuition behind this is that a high-entropy sample in the view of the student can be regarded as a hard example. Learning on these hard examples may expand the student's knowledge by reducing its blind spots. Despite this intuitively plausible explanation, in practice, we will show this scheme actually under-performs the former student-agnostic one in Eq. (11).

5 Experimental Results

Datasets and Networks. We evaluate our method on the CIFAR100 [22] and Tiny ImageNet* datasets. CIFAR100 has 100 object classes (32×32 RGB images). Each class has 500 images for training and 100 images for testing. Tiny ImageNet is a small version of ImageNet with 200 classes (64×64 RGB images). Each class has 500 images for training, 50 for validation and 50 for testing. To thoroughly evaluate our methods, we benchmark them on various standard network architectures: vgg [40], resnet [13], wrn (wide resnet) [50], MobileNetV2 [35], ShuffleV2 [27].

Benchmark Methods. In addition to the standard cross-entropy training and the original KD method [16], we also compare with the state-of-the-art distillation approach Contrastive Representation Distillation (CRD) [43]. It is important to note that our method focuses on improving KD by using better *inputs*, while CRD improves KD at the *output* end (*i.e.*, a better loss function). Therefore, they are orthogonal and we will show they can be combined together to deliver even better results.

Hyper-parameter Settings. The temperature τ of knowledge distillation is set to 4. Loss weight $\alpha = 0.9$ (Eq. (1)). For CIFAR100 and Tiny ImageNet, training batch size is 64; the original number of total training epochs is 240, with learning rate (LR) decayed at epoch 150, 180, and 210 by multiplier 0.1. The initial LR is 0.05. All these settings are *the same* as CRD [43] for fair comparison. Note, in our experiments we will show the results of more training iterations. If the number of total epochs is scaled by a factor k, the epochs after which learning rate is decayed is also be scaled by k. For example, if we train a network for CIFAR100 for 480 epochs ($k = 2$) in total, the epochs after which the learning rate is decayed will be 300, 360, and 420.

We use PyTorch [32] to conduct all our experiments. For CIFAR100, we adopt the pretrained teacher models from CRD† for fair comparison with it. For Tiny ImageNet, we train our own teacher models.

Data Augmentation Schemes. We investigate the following popular DA schemes:

- **Identity**: This augmentation scheme simply makes a copy of each batch data during training, which should be the *lower bound* of all DA schemes discussed here since it adds no new information.
- **Flip**: Horizontal flip.
- **Flip+Crop**: Horizontal flip and random crop. This is the standard DA extensively used in 2D image recognition task (such as on CIFAR and ImageNet datasets).

---

*https://tiny-imagenet.herokuapp.com/

†https://github.com/HobbitLong/RepDistiller

- **Cutout** [11]: Cutout occludes a small random patch of an image.
- **AutoAugment** [7]: AutoAugment is an ensemble of a collected DA schemes. The DA policy is automatically selected by reinforcement learning instead of manually.
- **Mixup** [52]: Mixup applies linear interpolation between two inputs and applies the same linear interpolation to their labels to make the new label for the augmented sample.
- **CutMix** [49]: CutMix cuts a small patch from one source image and pastes it to another source image, the resulted image considered as a new input. The target for the new input is a linear interpolation from the two source labels.

5.1 Empirical Verification of Our Proposition

Before presenting results, one point worth mentioning is that, in this section we use test loss instead of accuracy as the measure of student's performance in KD, because (1) all the formulas in Sec. 3 are derived using numerical loss instead of accuracy; (2) more importantly, it is observed that accuracy can mismatch with loss – a model may achieve a better accuracy, meanwhile higher loss too [28], which we also observe many times in our experiments (see Appendix). Using accuracy as measure would prevent us from seeing the correlation between T. stddev and student's performance. Potential extension of our theory from loss to accuracy is reserved for future work.

In Fig. 4, we plot the scatters of S. test loss and T. stddev. The x/y-axis value of each data point is averaged by three random runs (see Tables. 3/4 and Tables 5/6 for detailed numbers). We have the following observations.

(1) Foremost, we see in terms of T. stddev, there is a rough trend (*e.g.*, on the vgg13vgg8 pair on CIFAR100): Identity < Flip < Flip+Crop < Cutout < AutoAugment < Mixup < CutMix. These inequalities are well-aligned with our intuition. For example, AutoAugment [7] includes Cutout [11] in its transformation pool, thus should be stronger than Cutout, which is consistently reflected by the T. stddev on different pairs.

(2) It is easy to see these plots pose an *obvious positive correlation* between the S. test loss and T. stddev. Per our theory, lower T. stddev should lead to better generalization risk for the student. This is generally well verified in these plots. We do see some minor counterexamples. Possible reasons are: 1) The test loss is obtained on the test set with finite samples, which is only an approximation of the true error defined on distribution; 2) The teacher's mean probability is also evaluated on finite data. Despite them, the general picture from Fig. 4 still confirms the positive correlation between the stddev of teacher's mean probability and student's test loss. The correlation is actually *very significant* as the p-values indicate (see Tab. 7).

(3) Importantly, note we only need the teacher to define the quality of a certain DA in KD, *no need for the student*. This is verified in Tabs. 3/4 and Tabs. 5/6, as when different students are used, the coherence between stddev of the teacher's mean probability and student's test loss is steadily maintained. Notably, this is a great advantage in practice since we can decide which DA should be used for the best performance simply using formulas (Eq. (10)) with a few network forwards, without having to fully train the students.

5.2 Boosting KD with Stronger DA

In this section, we present more results to show how the proposed theory can benefit in practice – we can harvest considerable performance gain simply by using a stronger DA in KD.

Prolonged Training. Notably, a stronger DA produces more diverse data, implying more information. Intuitively, it should take a student model *more training iterations* (if the batch size does not change) to fully absorb the excessive information. That is, a stronger DA may take *more* training iterations to fully exhibit its potential. This intuition is confirmed in Fig. 2 (and also two more pairs wrn_40_2/wrn_16_2 and vgg13/vgg8 in the Appendix). Thus, in our experiments, we will also report results with prolonged training iterations for maximized performance.

Results on CIFAR100. The results on CIFAR100 dataset are shown in Table 1.

(1) Comparing the row "KD+CutMix" to "KD", we see the proposed CutMix scheme improves the accuracies of 6/7 teacher-student pairs. On the pair resnet32x4/ShuffleV2, the improvement is very significant (more than 1 percentage point). **(2)** Comparing the row "KD+CutMixPick" to

Figure 4: Scatter plots of T. stddev *vs.* S. test loss of different pairs on CIFAR100 and Tiny ImageNet. The detailed numbers are deferred to Appendix (Tab. 3, Tab. 4, Tab. 5, Tab. 6).

"KD+CutMix", we see 6/7 pairs are improved further, showing the proposed data picking scheme works in most cases. **(3)** Finally, "KD+CutMixPick" scheme can be combined with more training iterations, which delivers even higher accuracies. **(4)** If comparing our best results (KD+CutMixPick$_{960}$) with those of CRD (though this is not an apples-to-apples comparison since the two methods focus on different aspects to improve KD), we can see our approach outperforms CRD on 6/7 pairs.

In the last two rows of Tab. 1, when CRD [43], one of the SOTA KD algorithms, is armed with our proposed "CutMixPick" and more training iterations, its results can be further advanced *consistently*. This demonstrates that the proposed schemes are general and can readily work with those methods focusing on better KD loss functions.

Results on Tiny ImageNet. We also evaluate CutMix and CutMixPick on a more challenging dataset, Tiny ImageNet. Similar to the case on CIFAR100, we have results on different teacher-student pairs, shown in Tab. 2. For prolonged training, we train for 480 epochs instead of 960 to save time. Most claims on the CIFAR100 dataset are also validated here: **(1)** "KD+CutMix" is better than KD, which is verified on *all* pairs. **(2)** "KD+CutMixPick" is better than "KD+CutMix", verified on 6 pairs. The exception pair is resnet56/resnet20, where adding data picking decreases the accuracy slightly by 0.11%. **(3)** When "KD+CutMixPick" is trained for prolonged iterations, the students perform best.

Table 1: Student test accuracy on **CIFAR100**. Each result is obtained by 3 random runs, mean (std) accuracy reported. The best results are in **bold** and second best underlined. The subscript 960 means the total number of training epochs (default: 240).

| Teacher
Student | wrn_40_2
wrn_16_2 | resnet56
resnet20 | resnet32x4
resnet8x4 | vgg13
vgg8 | vgg13
MobileNetV2 | ResNet50
vgg8 | resnet32x4
ShuffleV2 |
|---|---|---|---|---|---|---|---|
| Teacher Acc.
Student Acc. | 75.61
73.26 | 72.34
69.06 | 79.42
72.50 | 74.64
70.36 | 74.64
64.60 | 79.34
70.36 | 79.42
71.82 |
| KD [16] | 74.92 (0.28) | 70.66 (0.24) | 73.33 (0.25) | 72.98 (0.19) | 67.37 (0.32) | 73.81 (0.13) | 74.45 (0.27) |
| KD+CutMix | 75.34 (0.19) | 70.77 (0.17) | 74.91 (0.20) | 74.16 (0.18) | 68.79 (0.35) | 74.85 (0.23) | 76.61 (0.18) |
| **KD+CutMixPick** | 75.59 (0.22) | 70.99 (0.20) | 74.78 (0.35) | 74.43 (0.20) | 69.49 (0.32) | 74.95 (0.18) | 76.90 (0.25) |
| KD$_{960}$ [16] | 75.68 (0.12) | **71.79** (0.29) | 73.14 (0.06) | 74.00 (0.34) | 68.77 (0.05) | 74.04 (0.25) | 74.64 (0.30) |
| **KD+CutMixPick$_{960}$** | **76.41** (0.10) | 71.66 (0.15) | 75.12 (0.18) | 75.00 (0.17) | 70.47 (0.12) | 76.13 (0.16) | 77.90 (0.30) |
| CRD [43] | 75.64 (0.21) | 71.63 (0.15) | 75.46 (0.25) | 74.29 (0.12) | 69.94 (0.05) | 74.58 (0.27) | 76.05 (0.09) |
| CRD+**CutMixPick** | 75.96 (0.27) | 71.41 (0.26) | **76.11** (0.53) | 74.65 (0.12) | 69.95 (0.22) | 75.35 (0.22) | 76.93 (0.11) |
| CRD+**CutMixPick$_{960}$** | **76.61** (0.01) | **72.40** (0.20) | 75.96 (0.29) | **75.41** (0.10) | **70.84** (0.05) | **76.20** (0.22) | **78.51** (0.27) |

Table 2: Student test accuracy on **Tiny ImageNet**. The subscript 480 means the total number of training epochs (default: 240).

| Teacher
Student | wrn_40_2
wrn_16_2 | resnet56
resnet20 | resnet32x4
resnet8x4 | vgg13
vgg8 | vgg13
MobileNetV2 | ResNet50
vgg8 | resnet32x4
ShuffleV2 |
|---|---|---|---|---|---|---|---|
| Teacher Acc.
Student Acc. | 61.28
58.23 | 58.37
52.53 | 64.41
55.41 | 62.59
56.67 | 62.59
58.20 | 68.20
56.67 | 64.41
62.07 |
| KD [16] | 58.65 (0.09) | 53.58 (0.18) | 55.67 (0.09) | 61.48 (0.36) | 59.28 (0.13) | 60.39 (0.16) | 66.34 (0.11) |
| KD+CutMix | 59.06 (0.18) | 53.77 (0.33) | 56.41 (0.04) | 62.17 (0.11) | 60.48 (0.30) | 61.12 (0.18) | 67.01 (0.30) |
| **KD+CutMixPick** | 59.22 (0.05) | 53.66 (0.05) | 56.82 (0.23) | 62.32 (0.18) | 60.53 (0.18) | 61.40 (0.26) | 67.08 (0.13) |
| KD$_{480}$ [16] | 59.20 (0.30) | 54.23 (0.24) | 55.49 (0.11) | 61.72 (0.10) | 59.27 (0.08) | 60.10 (0.30) | 65.81 (0.11) |
| **KD+CutMixPick$_{480}$** | **60.07** (0.04) | **54.25** (0.07) | **57.54** (0.23) | **62.60** (0.25) | **60.66** (0.15) | **61.95** (0.14) | **67.35** (0.21) |
| CRD [43] | 60.79 (0.24) | 55.34 (0.02) | 59.28 (0.13) | 62.92 (0.31) | 62.38 (0.19) | 62.03 (0.16) | 67.33 (0.13) |
| CRD+**CutMixPick** | 60.72 (0.09) | 54.99 (0.16) | 59.65 (0.24) | 63.39 (0.10) | 62.54 (0.22) | **62.85** (0.18) | 67.64 (0.18) |
| CRD+**CutMixPick$_{480}$** | **60.99** (0.33) | **55.68** (0.22) | **60.13** (0.13) | **63.60** (0.20) | **62.79** (0.03) | 62.60 (0.17) | **67.70** (0.35) |

We further evaluate our DA methods equipped with CRD [43], shown in the last two rows of Tab. 2. Our "CutMixPick" method further advances the prior SOTA on 5 pairs. When CRD+CutMixPick is trained for 480 epochs (instead of 240), further improvement can be observed on 6 of 7 pairs.

Apply DA to More KD Methods. Notably, we achieve the above performance boosting simply using the original KD loss [16], *with no bells and whistles*. This justifies one of our motivations in this paper, *i.e.*, existing KD methods [33, 30, 43] mainly improve KD at the network *output* side via better loss functions, while we propose to improve KD at the *input* end and show this path is *just as promising*. Actually, this performance boosting effect is *generic*, not limited to CRD. In the Appendix, we present more results of applying CutMix to another 5 KD methods. *All* of the evaluated pairs see accuracy gains; half of them are even improved by more than 1% point.

Results on ImageNet100. ImageNet100 is a randomly drawn 100-class subset of ImageNet [10]. We defer these results to Appendix A.1. In general, we observe that the correlation between T. stddev and S. test loss become weaker on the more challenging ImageNet100 dataset. This is because the ImageNet100 is inherently harder than CIFAR100 and Tiny ImageNet. Nevertheless, the p-value of the correlation is still below 5%, *i.e.*, still statistically significant.

6 Conclusion

In this paper, we attempt to precisely answer what makes a good data augmentation in knowledge distillation. By analyzing the generalization gap of the student under different sampling schemes, we reach the conclusion that a good data augmentation scheme should reduce the variance of the empirical distilled risk between the teacher and student. Based on this, we propose a new metric, the stddev of the teacher's mean probability (T. stddev), as a feasible measure of the quality of data augmentation techniques. Empirical studies with various teacher-student pairs confirm the efficacy of the proposed metric for data augmentation quality in KD. Besides the theoretical understanding, we also develop an entropy-based data picking scheme to further enhance the prior best augmentation scheme (CutMix) in KD. Finally, we show how we can obtain considerable KD performance gains simply by using a stronger DA guided by the proposed theory.

References

[1] Sungsoo Ahn, Shell Xu Hu, Andreas Damianou, Neil D Lawrence, and Zhenwen Dai. Variational information distillation for knowledge transfer. In *CVPR*, 2019. 16, 17

[2] Lucas Beyer, Xiaohua Zhai, Amélie Royer, Larisa Markeeva, Rohan Anil, and Alexander Kolesnikov. Knowledge distillation: A good teacher is patient and consistent. In *CVPR*, 2022. 3

[3] Xavier Bouthillier, Kishore Konda, Pascal Vincent, and Roland Memisevic. Dropout as data augmentation. *arXiv preprint arXiv:1506.08700*, 2015. 2

[4] Cristian Buciluǎ, Rich Caruana, and Alexandru Niculescu-Mizil. Model compression. In *SIGKDD*, 2006. 3

[5] Keshigeyan Chandrasegaran, Ngoc-Trung Tran, Yunqing Zhao, and Ngai-Man Cheung. Revisiting label smoothing and knowledge distillation compatibility: What was missing? In *ICML*, 2022. 3

[6] Guobin Chen, Wongun Choi, Xiang Yu, Tony Han, and Manmohan Chandraker. Learning efficient object detection models with knowledge distillation. In *NeurIPS*, 2017. 2, 3

[7] Ekin D Cubuk, Barret Zoph, Dandelion Mane, Vijay Vasudevan, and Quoc V Le. Autoaugment: Learning augmentation policies from data. In *CVPR*, 2019. 2, 3, 8

[8] Wanyun Cui and Sen Yan. Isotonic data augmentation for knowledge distillation. *arXiv preprint arXiv:2107.01412*, 2021. 3

[9] Deepan Das, Haley Massa, Abhimanyu Kulkarni, and Theodoros Rekatsinas. An empirical analysis of the impact of data augmentation on knowledge distillation. *arXiv preprint arXiv:2006.03810*, 2020. 4

[10] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *CVPR*, 2009. 3, 10

[11] Terrance DeVries and Graham W Taylor. Improved regularization of convolutional neural networks with cutout. *arXiv preprint arXiv:1708.04552*, 2017. 3, 8

[12] Yushu Feng, Huan Wang, Haoji Hu, and Daniel Yi. Triplet distillation for deep face recognition. In *ICML Workshop*, 2019. 2

[13] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *CVPR*, 2016. 2, 3, 7

[14] Byeongho Heo, Jeesoo Kim, Sangdoo Yun, Hyojin Park, Nojun Kwak, and Jin Young Choi. A comprehensive overhaul of feature distillation. In *ICCV*, 2019. 3

[15] Byeongho Heo, Minsik Lee, Sangdoo Yun, and Jin Young Choi. Knowledge transfer via distillation of activation boundaries formed by hidden neurons. In *AAAI*, 2019. 3

[16] Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. In *NeurIPS Workshop*, 2014. 2, 3, 7, 10, 17

[17] Geoffrey E Hinton. Training products of experts by minimizing contrastive divergence. *Neural Computation*, 14(8):1771–1800, 2002. 2

[18] Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *CVPR*, 2017. 2

[19] Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *ICML*, 2015. 2

[20] Xiaoqi Jiao, Yichun Yin, Lifeng Shang, Xin Jiang, Xiao Chen, Linlin Li, Fang Wang, and Qun Liu. Tinybert: Distilling bert for natural language understanding. *arXiv preprint arXiv:1909.10351*, 2019. 2, 3

[21] Michael J Kearns, Umesh Virkumar Vazirani, and Umesh Vazirani. *An introduction to computational learning theory*. MIT Press, 1994. 15

[22] Alex Krizhevsky. Learning multiple layers of features from tiny images. Technical report, Citeseer, 2009. 7

[23] Solomon Kullback. *Information theory and statistics*. Courier Corporation, 1997. 2

[24] Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *Nature*, 521(7553):436, 2015. 2

[25] Weiyang Liu, Yandong Wen, Zhiding Yu, and Meng Yang. Large-margin softmax loss for convolutional neural networks. In *ICML*, 2016. 2

[26] Yufan Liu, Jiajiong Cao, Bing Li, Chunfeng Yuan, Weiming Hu, Yangxi Li, and Yunqiang Duan. Knowledge distillation via instance relationship graph. In *CVPR*, 2019. 3

[27] Ningning Ma, Xiangyu Zhang, Hai-Tao Zheng, and Jian Sun. Shufflenet v2: Practical guidelines for efficient cnn architecture design. In *ECCV*, 2018. 7

[28] Aditya K Menon, Ankit Singh Rawat, Sashank Reddi, Seungyeon Kim, and Sanjiv Kumar. A statistical perspective on distillation. In *ICML*, 2021. 4, 8

[29] Rafael Müller, Simon Kornblith, and Geoffrey E Hinton. When does label smoothing help? In *NeurIPS*, 2019. 2, 3

[30] Wonpyo Park, Dongju Kim, Yan Lu, and Minsu Cho. Relational knowledge distillation. In *CVPR*, 2019. 2, 3, 10

[31] Nikolaos Passalis and Anastasios Tefas. Learning deep representations with probabilistic knowledge transfer. In *ECCV*, 2018. 3, 16, 17

[32] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. In *NeurIPS*, 2019. 7

[33] Baoyun Peng, Xiao Jin, Jiaheng Liu, Dongsheng Li, Yichao Wu, Yu Liu, Shunfeng Zhou, and Zhaoning Zhang. Correlation congruence for knowledge distillation. In *ICCV*, 2019. 2, 3, 10, 16, 17

[34] Adriana Romero, Nicolas Ballas, Samira Ebrahimi Kahou, Antoine Chassang, Carlo Gatta, and Yoshua Bengio. Fitnets: Hints for thin deep nets. In *ICLR*, 2015. 3

[35] Mark Sandler, Andrew Howard, Menglong Zhu, Andrey Zhmoginov, and Liang-Chieh Chen. Mobilenetv2: Inverted residuals and linear bottlenecks. In *CVPR*, 2018. 7

[36] Jürgen Schmidhuber. Deep learning in neural networks: An overview. *Neural networks*, 61:85–117, 2015. 2

[37] Burr Settles. From theories to queries: Active learning in practice. In *AISTATS Workshop on Active Learning and Experimental Design*, 2011. 7

[38] Zhiqiang Shen, Zechun Liu, Dejia Xu, Zitian Chen, Kwang-Ting Cheng, and Marios Savvides. Is label smoothing truly incompatible with knowledge distillation: An empirical study. In *ICLR*, 2021. 3

[39] Connor Shorten and Taghi M Khoshgoftaar. A survey on image data augmentation for deep learning. *Journal of Big Data*, 6(1):60, 2019. 2, 3

[40] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. In *ICLR*, 2015. 7

[41] Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *CVPR*, 2016. 2

[42] Jiaxi Tang, Rakesh Shivanna, Zhe Zhao, Dong Lin, Anima Singh, Ed H Chi, and Sagar Jain. Understanding and improving knowledge distillation. *arXiv preprint arXiv:2002.03532*, 2020. 3

[43] Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive representation distillation. In *ICLR*, 2020. 2, 3, 7, 9, 10, 16, 17

[44] Frederick Tung and Greg Mori. Similarity-preserving knowledge distillation. In *CVPR*, 2019. 3, 16, 17

[45] Vladimir Vapnik. *The nature of statistical learning theory*. Springer Science & Business Media, 2013. 15

[46] Vikas Verma, Alex Lamb, Christopher Beckham, Amir Najafi, Ioannis Mitliagkas, David Lopez-Paz, and Yoshua Bengio. Manifold mixup: Better representations by interpolating hidden states. In *ICML*, 2019. 3

[47] Huan Wang, Yijun Li, Yuehai Wang, Haoji Hu, and Ming-Hsuan Yang. Collaborative distillation for ultra-resolution universal style transfer. In *CVPR*, 2020. 2, 3

[48] Lin Wang and Kuk-Jin Yoon. Knowledge distillation and student-teacher learning for visual intelligence: A review and new outlooks. *TPAMI*, 2021. 2, 3

[49] Sangdoo Yun, Dongyoon Han, Seong Joon Oh, Sanghyuk Chun, Junsuk Choe, and Youngjoon Yoo. Cutmix: Regularization strategy to train strong classifiers with localizable features. In *ICCV*, 2019. 3, 8

[50] Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. In *BMVC*, 2016. 7

[51] Sergey Zagoruyko and Nikos Komodakis. Paying more attention to attention: Improving the performance of convolutional neural networks via attention transfer. In *ICLR*, 2017. 3, 16, 17

[52] Hongyi Zhang, Moustapha Cisse, Yann N Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. In *ICLR*, 2018. 2, 3, 8

Table 3: Student test loss (S. test loss) and the stddev of teacher's mean probability (T. stddev, $\times 10^{-3}$) comparison on **CIFAR100** when using different DA schemes.

Teacher	wrn_40_2	wrn_40_2	wrn_40_2	resnet56	resnet56	resnet56
Student	/	wrn_16_2	vgg8	/	resnet20	ShuffleV2
Metric	T. stddev	S. test loss	S. test loss	T. stddev	S. test loss	S. test loss
KD+Identity	$5.473_{\pm 0.002}$	$1.0976_{\pm 0.0136}$	$1.1830_{\pm 0.0065}$	$5.248_{\pm 0.004}$	$1.1783_{\pm 0.0081}$	$0.9785_{\pm 0.0137}$
KD+Flip	$5.471_{\pm 0.004}$	$1.0774_{\pm 0.0101}$	$1.1673_{\pm 0.0060}$	$5.232_{\pm 0.003}$	$1.1668_{\pm 0.0060}$	$0.9961_{\pm 0.0072}$
KD+Crop+Flip	$5.410_{\pm 0.009}$	$1.0837_{\pm 0.0097}$	$1.1446_{\pm 0.0182}$	$5.121_{\pm 0.006}$	$1.1763_{\pm 0.0092}$	$0.9736_{\pm 0.0062}$
KD+Cutout	$5.255_{\pm 0.009}$	$1.0564_{\pm 0.0090}$	$1.1306_{\pm 0.0156}$	$4.983_{\pm 0.012}$	$1.1687_{\pm 0.0115}$	$0.9541_{\pm 0.0088}$
KD+AutoAugment	$5.110_{\pm 0.004}$	$1.0305_{\pm 0.0290}$	$1.1102_{\pm 0.0016}$	$4.904_{\pm 0.007}$	$1.1478_{\pm 0.0041}$	$0.9355_{\pm 0.0099}$
KD+Mixup	$4.988_{\pm 0.012}$	$1.0486_{\pm 0.0225}$	$1.0917_{\pm 0.0044}$	$4.719_{\pm 0.002}$	$1.1621_{\pm 0.0121}$	$0.9703_{\pm 0.0060}$
KD+CutMix	$4.719_{\pm 0.005}$	$1.0275_{\pm 0.0112}$	$1.0657_{\pm 0.0145}$	$4.443_{\pm 0.002}$	$1.1440_{\pm 0.0040}$	$0.9348_{\pm 0.0107}$
KD+CutMixPick (S. ent.)	$4.400_{\pm 0.007}$	$1.0054_{\pm 0.0118}$	$1.0471_{\pm 0.0111}$	$4.039_{\pm 0.004}$	$1.1269_{\pm 0.0095}$	$0.9339_{\pm 0.0070}$
KD+CutMixPick (T. ent.)	$4.154_{\pm 0.005}$	$0.9746_{\pm 0.0073}$	$0.9928_{\pm 0.0061}$	$3.788_{\pm 0.004}$	$1.0924_{\pm 0.0085}$	$0.9038_{\pm 0.0148}$

Table 4: Continued: Student test loss (S. test loss) and the stddev of teacher's mean probability (T. stddev, $\times 10^{-3}$) comparison on **CIFAR100** when using different DA schemes.

Teacher	vgg13	vgg13	vgg13	resnet32x4	resnet32x4	resnet32x4	ResNet50	ResNet50
Student	/	vgg8	MobileNetV2	/	resnet8x4	ShuffleV2	/	vgg8
Metric	T. stddev	S. test loss	S. test loss	T. stddev	S. test loss	S. test loss	T. stddev	S. test loss
KD+Identity	$5.519_{\pm 0.006}$	$1.1856_{\pm 0.0196}$	$1.6021_{\pm 0.0366}$	$5.524_{\pm 0.015}$	$1.0973_{\pm 0.0134}$	$1.3381_{\pm 0.0072}$	$5.530_{\pm 0.005}$	$1.2418_{\pm 0.0067}$
KD+Flip	$5.516_{\pm 0.002}$	$1.1754_{\pm 0.0105}$	$1.5779_{\pm 0.0076}$	$5.530_{\pm 0.009}$	$1.0967_{\pm 0.0038}$	$1.3208_{\pm 0.0172}$	$5.532_{\pm 0.002}$	$1.2110_{\pm 0.0024}$
KD+Crop+Flip	$5.457_{\pm 0.010}$	$1.1537_{\pm 0.0059}$	$1.5244_{\pm 0.0149}$	$5.498_{\pm 0.004}$	$1.0685_{\pm 0.0031}$	$1.3091_{\pm 0.0283}$	$5.494_{\pm 0.013}$	$1.1976_{\pm 0.0160}$
KD+Cutout	$5.295_{\pm 0.012}$	$1.1279_{\pm 0.0055}$	$1.4963_{\pm 0.0104}$	$5.356_{\pm 0.014}$	$1.0627_{\pm 0.0063}$	$1.2528_{\pm 0.0127}$	$5.370_{\pm 0.004}$	$1.1925_{\pm 0.0128}$
KD+AutoAugment	$5.176_{\pm 0.012}$	$1.1273_{\pm 0.0213}$	$1.4137_{\pm 0.0440}$	$5.198_{\pm 0.015}$	$1.0289_{\pm 0.0078}$	$1.1353_{\pm 0.0164}$	$5.248_{\pm 0.011}$	$1.1443_{\pm 0.0064}$
KD+Mixup	$5.075_{\pm 0.001}$	$1.1194_{\pm 0.0176}$	$1.4009_{\pm 0.0044}$	$5.082_{\pm 0.004}$	$1.0182_{\pm 0.0128}$	$1.0840_{\pm 0.0229}$	$5.083_{\pm 0.006}$	$1.1188_{\pm 0.0133}$
KD+CutMix	$4.665_{\pm 0.009}$	$1.0862_{\pm 0.0140}$	$1.2846_{\pm 0.0178}$	$4.851_{\pm 0.016}$	$1.0166_{\pm 0.0096}$	$1.0544_{\pm 0.0095}$	$4.870_{\pm 0.002}$	$1.1161_{\pm 0.0026}$
KD+CutMixPick (S. ent.)	$4.300_{\pm 0.016}$	$1.0605_{\pm 0.0249}$	$1.2739_{\pm 0.0064}$	$4.590_{\pm 0.006}$	$0.9888_{\pm 0.0015}$	$1.0288_{\pm 0.0049}$	$4.656_{\pm 0.012}$	$1.0851_{\pm 0.0101}$
KD+CutMixPick (T. ent.)	$4.042_{\pm 0.007}$	$0.9981_{\pm 0.0087}$	$1.1876_{\pm 0.0233}$	$4.323_{\pm 0.007}$	$0.9485_{\pm 0.0116}$	$0.9570_{\pm 0.0122}$	$4.397_{\pm 0.006}$	$1.0069_{\pm 0.0027}$

4. If you are using existing assets (e.g., code, data, models) or curating/releasing new assets...

    (a) If your work uses existing assets, did you cite the creators? [Yes]

    (b) Did you mention the license of the assets? [Yes] See supplementary material.

    (c) Did you include any new assets either in the supplemental material or as a URL? [No]

    (d) Did you discuss whether and how consent was obtained from people whose data you're using/curating? [Yes] The data we use are all publicly available.

    (e) Did you discuss whether the data you are using/curating contains personally identifiable information or offensive content? [Yes] The data we use contains *no* personally identifiable information or offensive content.

5. If you used crowdsourcing or conducted research with human subjects...

    (a) Did you include the full text of instructions given to participants and screenshots, if applicable? [No] No crowdsourcing in this work.

    (b) Did you describe any potential participant risks, with links to Institutional Review Board (IRB) approvals, if applicable? [No] No crowdsourcing in this work.

    (c) Did you include the estimated hourly wage paid to participants and the total amount spent on participant compensation? [No] No crowdsourcing in this work.

A Appendix

A.1 More Results

Detailed numerical results of S. test loss and T. stddev on CIFAR100 and Tiny ImageNet. See Tab. 3, Tab. 4, Tab. 5, Tab. 6. These tables are the numerical results that we use to plot Fig. 4.

Correlation and p-values of S. test loss and T. stddev. Tab. 7 presents the correlation coefficient between S. test loss and T. stddev on some pairs in Tabs. 3/4 and Tabs. 5/6. Three popular correlation (Pearson, Spearman, Kendall) in statistics are considered here.

As seen, the positive correlation between the proposed metric and the student's test loss is **very strong**, indicated by the p-values. It is worth emphasizing that, the metric is calculated solely with

Table 5: Student test loss (S. test loss) and the stddev of teacher's mean probability (T. stddev, $\times 10^{-3}$) comparison on **Tiny ImageNet** when using different DA schemes.

Teacher	wrn_40_2	wrn_40_2	wrn_40_2	resnet56	resnet56	resnet56
Student	/	wrn_16_2	vgg8	/	resnet20	ShuffleV2
Metric	T. stddev	S. test loss	S. test loss	T. stddev	S. test loss	S. test loss
KD+Identity	$3.482_{\pm 0.002}$	$1.7676_{\pm 0.0079}$	$1.7374_{\pm 0.0111}$	$2.994_{\pm 0.001}$	$1.9459_{\pm 0.0065}$	$1.5600_{\pm 0.0077}$
KD+Flip	$3.473_{\pm 0.003}$	$1.7567_{\pm 0.0099}$	$1.7322_{\pm 0.0107}$	$2.978_{\pm 0.001}$	$1.9352_{\pm 0.0127}$	$1.5629_{\pm 0.0034}$
KD+Crop+Flip	$3.385_{\pm 0.004}$	$1.7599_{\pm 0.0083}$	$1.7283_{\pm 0.0083}$	$2.893_{\pm 0.000}$	$1.9343_{\pm 0.0060}$	$1.5593_{\pm 0.0048}$
KD+Cutout	$3.305_{\pm 0.002}$	$1.7610_{\pm 0.0053}$	$1.7104_{\pm 0.0040}$	$2.845_{\pm 0.003}$	$1.9369_{\pm 0.0044}$	$1.5636_{\pm 0.0052}$
KD+AutoAugment	$2.953_{\pm 0.002}$	$1.7274_{\pm 0.0065}$	1.7630	$2.610_{\pm 0.002}$	$1.9569_{\pm 0.0071}$	$1.5782_{\pm 0.0085}$
KD+Mixup	$2.999_{\pm 0.002}$	$1.7294_{\pm 0.0064}$	$1.6980_{\pm 0.0029}$	$2.593_{\pm 0.004}$	$1.9201_{\pm 0.0075}$	$1.5765_{\pm 0.0036}$
KD+CutMix	$2.921_{\pm 0.005}$	$1.7296_{\pm 0.0025}$	$1.6927_{\pm 0.0013}$	$2.494_{\pm 0.005}$	$1.9136_{\pm 0.0020}$	$1.5605_{\pm 0.0024}$
KD+CutMixPick (S. ent.)	$2.609_{\pm 0.003}$	1.7078	$1.6483_{\pm 0.0005}$	$2.148_{\pm 0.001}$	$1.8985_{\pm 0.0059}$	1.5508
KD+CutMixPick (T. ent.)	$2.386_{\pm 0.002}$	$1.6845_{\pm 0.0067}$	1.6278	$1.972_{\pm 0.003}$	$1.8817_{\pm 0.0040}$	$1.5438_{\pm 0.0067}$

Table 6: Continued: Student test loss (S. test loss) and the stddev of teacher's mean probability (T. stddev, $\times 10^{-3}$) comparison on **Tiny ImageNet** when using different DA schemes.

Teacher	vgg13	vgg13	vgg13	resnet32x4	resnet32x4	resnet32x4	ResNet50	ResNet50
Student	/	vgg8	MobileNetV2	/	resnet8x4	ShuffleV2	/	vgg8
Metric	T. stddev	S. test loss	S. test loss	T. stddev	S. test loss	S. test loss	T. stddev	S. test loss
KD+Identity	$3.873_{\pm 0.001}$	$1.8377_{\pm 0.0021}$	$2.0258_{\pm 0.0211}$	$3.847_{\pm 0.004}$	$1.9859_{\pm 0.0108}$	$1.7404_{\pm 0.2064}$	$3.903_{\pm 0.001}$	$1.9767_{\pm 0.0230}$
KD+Flip	$3.873_{\pm 0.002}$	$1.8379_{\pm 0.0207}$	$1.9946_{\pm 0.0180}$	$3.842_{\pm 0.005}$	$1.9531_{\pm 0.0049}$	$1.6092_{\pm 0.0077}$	$3.901_{\pm 0.001}$	$1.9674_{\pm 0.0104}$
KD+Crop+Flip	$3.808_{\pm 0.004}$	$1.8346_{\pm 0.0108}$	$1.9707_{\pm 0.0089}$	$3.784_{\pm 0.002}$	$1.9725_{\pm 0.0092}$	$1.6009_{\pm 0.0111}$	$3.860_{\pm 0.003}$	$1.9249_{\pm 0.0132}$
KD+Cutout	$3.734_{\pm 0.066}$	$1.7932_{\pm 0.0137}$	$1.9544_{\pm 0.0101}$	$3.688_{\pm 0.001}$	$1.9839_{\pm 0.0008}$	$1.5900_{\pm 0.0092}$	$3.773_{\pm 0.003}$	$1.8962_{\pm 0.0159}$
KD+AutoAugment	$3.284_{\pm 0.003}$	$1.7310_{\pm 0.0200}$	$1.7970_{\pm 0.0445}$	$3.269_{\pm 0.003}$	$1.9159_{\pm 0.0218}$	$1.4969_{\pm 0.0159}$	$3.329_{\pm 0.005}$	$1.7600_{\pm 0.0172}$
KD+Mixup	$3.388_{\pm 0.002}$	$1.7757_{\pm 0.0168}$	$1.8587_{\pm 0.0141}$	$3.325_{\pm 0.002}$	$1.9138_{\pm 0.0140}$	$1.5442_{\pm 0.0028}$	$3.412_{\pm 0.000}$	$1.8450_{\pm 0.0241}$
KD+CutMix	$3.173_{\pm 0.001}$	$1.7259_{\pm 0.0189}$	$1.8269_{\pm 0.0423}$	$3.273_{\pm 0.002}$	$1.9420_{\pm 0.0082}$	$1.5350_{\pm 0.0083}$	$3.375_{\pm 0.003}$	$1.8225_{\pm 0.0101}$
KD+CutMixPick (S. ent.)	$2.905_{\pm 0.000}$	$1.6556_{\pm 0.0061}$	$1.7509_{\pm 0.0080}$	$3.086_{\pm 0.001}$	1.8227	1.5156	$3.197_{\pm 0.001}$	$1.7282_{\pm 0.0094}$
KD+CutMixPick (T. ent.)	$2.681_{\pm 0.005}$	$1.6237_{\pm 0.0094}$	$1.6839_{\pm 0.0159}$	$2.812_{\pm 0.002}$	$1.8368_{\pm 0.0060}$	$1.4317_{\pm 0.0096}$	$2.948_{\pm 0.005}$	$1.6724_{\pm 0.0113}$

the *teacher's* output; while it can accurately "predict" the trend of the *student*'s generalization ability *without knowing the student at all*. This surprising fact shows the effectiveness of the proposed metric, meanwhile justifying the validity of the proposed theory (Proposition 1) in turn.

The above fact also differentiates our work from the traditional works studying the connection between data dependency and generalization ability. In statistical learning [21, 45], it is already known that if the data presents *stronger* self-dependency, the model learned with the data will generalize *worse*. We need to re-iterate that our work is *starkly different* from them. (**1**) The existing works [21, 45] study the dependency in the input data, while an important point in our theory is that we consider the *teacher's output* of the input, *not* the input per se. Namely, the proposed theory must be discussed in the context of KD. Existing works [21, 45] clearly are not in this scope.

Table 7: Correlation between "Std of mean prob." and "Test err." in Tabs. 1 and 2 (first 6 pairs for CIFAR100, last 2 for Tiny ImageNet). Below the dashline are the **p-values**. Typically, a result is considered *statistically significant* if p-value $< 5\%$. *P-values below are much lower than 5%, implying a very strong correlation.*

Teacher	wrn_40_2	wrn_40_2	resnet56	resnet56	vgg13	vgg13	vgg13	vgg13
Student	wrn_16_2	vgg8	resnet20	ShuffleV2	vgg8	MobileNetV2	vgg8	MobileNetV2
Pearson	0.9549	0.9817	0.9357	0.8642	0.9755	0.9673	0.9922	0.9869
Spearman	0.9333	1.0000	0.9333	0.9333	1.0000	1.0000	0.9833	0.9833
Kendall	0.8333	1.0000	0.8333	0.8333	1.0000	1.0000	0.9444	0.9444
Pearson	0.01%	0.00%	0.02%	0.27%	0.00%	0.00%	0.00%	0.00%
Spearman	0.02%	0.00%	0.02%	0.02%	0.00%	0.00%	0.00%	0.00%
Kendall	0.09%	0.00%	0.09%	0.09%	0.00%	0.00%	0.01%	0.01%

ImageNet100 Results. See Tab. 8. As seen, there are a few cases that go against the proposed theory. E.g., Flip+Crop has a lower T. stddev than Flip, while the student loss is higher. This means that large-size dataset like ImageNet100 is indeed more challenging and making the validation of the proposed theory harder. This said, the general trend is still aligned with our expectation: The proposed method CutMixPick achieves the lowest T. stddev, also, the lowest S. test loss, implying it can generalize

to the large-size dataset. We report the correlation coefficients and p-values (in the parentheses): Pearson: 0.7331 (0.02463), Spearman: 0.6667 (0.04987) Kendall: 0.5556 (0.04462). Note, all the p-values are still below 5%, meaning the positive correlation between S. test loss *vs.* T. stddev is statistically significant even on this challenging ImageNet100 dataset.

Table 8: Student test loss (S. test loss) and the stddev of teacher's mean probability (T. stddev) comparison on **ImageNet100** (a subset with 100 classes randomly drawn from ImageNet) when using different data augmentation schemes. *The S. test losses are averaged by the last 5 epochs to mitigate the random variation.*

Teacher	resnet34	resnet34
Student	/	resnet18
Metric	T. stddev	S. test loss
KD+Identity	0.002545	0.669444
KD+Flip	0.002543↓	0.659119↓
KD+Flip+Crop	0.002456↓	0.667045↑
KD+Cutout	0.002505↑	0.668883↑
KD+AutoAugment	0.002463↓	0.651285↓
KD+Mixup	0.002365↓	0.667565↑
KD+CutMix	0.002363↓	0.660041↓
KD+CutMixPick (S. ent.)	0.002215↓	0.647726↓
KD+CutMixPick (T. ent.)	0.002166↓	0.634186↓

Combining CutMix with Other KD Methods. In the main paper, we show that CutMix and our proposed method can advance one of the previous state-of-the-art KD methods, CRD [43], on most pairs (see Tabs. 1 and 2). It is interesting to see if this bonus from data augmentation can translate to more KD methods. Therefore, here we combine CutMix with five more KD methods to see how it works. The five methods are AT [51], CC [33], SP [44], PKT [31], and VID [1]. Note, these five methods we select are the *top-performing* KD methods (besides CRD) based on the CIFAR100 results in the CRD paper (it is easy to improve a mediocre KD method).

Results are shown in Tab. 9. When equipped with our proposed CutMix, *all* these methods see accuracy gains, although some teacher-student pairs see more improvement than others. For example, SP+CutMix and VID+CutMix only have marginal gains on the resnet110/resnet20 pair. Except them, *all the other* pairs see a *significant* accuracy improvement. There are 42 results in total in Tab. 9. **Half of them (21 pairs) are improved by more than 1% point**. Several (5 pairs) are even improved by over 2% points.

As explained in the main paper, our method focuses on the *input* end to improve KD, while methods like AT, CC, SP, PKT and VID focus on the *output* end (*i.e.*, a better loss function). Therefore, they are complementary. The results here reiterate one of our contributions in this paper: most existing KD papers seek to improve KD through a better loss function while we discover a new axis – improving KD through a stronger DA, which is just as promising.

KD *vs.* CE loss on wrn_40_2/wrn_16_2 and vgg13/vgg8. See Fig. 5.

A.2 More Explanations from Eq. (7) to Eq. (8)

In Proposition 1, the main idea is to have lower covariance among samples (in terms of the teacher's outputs), as suggested by Eq. (7). Then, it seems that the most straightforward idea is to use the covariance (or possibly the normalized covariance, *i.e.*, correlation) of the teacher's output as metric to capture the dependency among samples. Why does the paper not use this idea?

We first show this idea does not work as well in practice as our proposed metric. Then we explain why.

Given a batch of input images, the teacher's output probability is $P \in \mathbb{R}^{N \times C}$, where N is the batch size, C is the number of classes. Then we consider the covariance and correlation of P and try to construct a new metric from them:

$$Cov(P, P) \in \mathbb{R}^{N \times N} \Rightarrow v = Cov(P, P).mean() \in \mathbb{R},$$
$$Cor(P, P) \in \mathbb{R}^{N \times N} \Rightarrow r = Cor(P, P).mean() \in \mathbb{R}. \tag{12}$$

Table 9: Student test accuracy (standard deviation) of different KD methods on CIFAR100 *when equipped with the proposed CutMix*. The results of the different KD methods are directly cited from the CRD paper Table 7 [43] (where they did not report the standard deviation of the accuracies except for the original KD method [16], so the standard deviation of accuracies of these methods are missing here as well). AT, CC, SP, PKT, and VID methods include the original KD loss as part of their loss functions. Each our result is obtained by 3 random runs, mean (std) accuracy reported. Accuracy gains are colored in red (this table is *best viewed in color*).

| Teacher
Student | wrn_40_2
wrn_16_2 | resnet110
resnet20 | resnet32x4
resnet8x4 | vgg13
vgg8 | vgg13
MobileNetV2 | ResNet50
vgg8 | resnet32x4
ShuffleV2 |
|---|---|---|---|---|---|---|---|
| Teacher Acc.
Student Acc. | 75.61
73.26 | 74.31
69.06 | 79.42
72.50 | 74.64
70.36 | 74.64
64.60 | 79.34
70.36 | 79.42
71.82 |
| KD [16] | 74.92 (0.28) | 70.67 (0.27) | 73.33 (0.25) | 72.98 (0.19) | 67.37 (0.32) | 73.81 (0.13) | 74.45 (0.27) |
| **KD+CutMix** (ours) | 75.34 (0.19) | 71.19 (0.23) | 74.91 (0.20) | 74.16 (0.18) | 68.79 (0.35) | 74.85 (0.23) | 76.61 (0.18) |
| Acc. gain | +0.42 | +0.52 | +1.58 | +1.18 | +1.42 | +1.04 | +2.16 |
| AT [51] | 75.32 | 70.97 | 74.53 | 73.48 | 65.13 | 74.01 | 75.39 |
| **AT+CutMix** (ours) | 75.65 (0.27) | 71.66 (0.07) | 75.68 (0.13) | 74.02 (0.15) | 67.20 (0.24) | 74.67 (0.14) | 76.25 (0.13) |
| Acc. gain | +0.33 | +0.69 | +1.15 | +0.54 | +2.07 | +0.66 | +0.86 |
| CC [33] | 75.09 | 70.88 | 74.21 | 73.04 | 68.02 | 73.48 | 74.71 |
| **CC+CutMix** (ours) | 75.75 (0.27) | 71.41 (0.24) | 75.54 (0.28) | 74.35 (0.27) | 68.44 (0.46) | 74.76 (0.09) | 76.78 (0.18) |
| Acc. gain | +0.66 | +0.53 | +1.33 | +1.31 | +0.42 | +1.28 | +2.07 |
| SP [44] | 74.98 | 71.02 | 74.02 | 73.49 | 68.41 | 73.52 | 74.88 |
| **SP+CutMix** (ours) | 75.29 (0.39) | 71.10 (0.07) | 74.96 (0.13) | 74.10 (0.27) | 68.79 (0.24) | 74.77 (0.33) | 76.24 (0.14) |
| Acc. gain | +0.31 | +0.08 | +0.94 | +0.61 | +0.38 | +1.25 | +1.36 |
| PKT [31] | 75.33 | 70.72 | 74.23 | 73.25 | 68.13 | 73.61 | 74.66 |
| **PKT+CutMix** (ours) | 75.85 (0.42) | 71.33 (0.06) | 75.44 (0.08) | 74.30 (0.18) | 68.98 (0.60) | 74.70 (0.32) | 76.79 (0.10) |
| Acc. gain | +0.52 | +0.61 | +1.21 | +1.05 | +0.85 | +1.09 | +2.13 |
| VID [1] | 75.14 | 71.10 | 74.56 | 73.19 | 68.27 | 73.46 | 74.85 |
| **VID+CutMix** (ours) | 75.66 (0.21) | 71.13 (0.27) | 75.40 (0.17) | 74.24 (0.12) | 69.70 (0.22) | 74.67 (0.17) | 76.90 (0.17) |
| Acc. gain | +0.52 | +0.03 | +0.84 | +1.05 | +1.43 | +1.21 | +2.05 |

(a) wrn_16_2 (teacher: wrn_40_2) (b) vgg8 (teacher: vgg13)

Figure 5: Test error rate of wrn_16_2 and vgg8 on CIFAR100 when trained for different numbers of epochs, using KD or cross-entropy (CE) loss, with or without data augmentation (DA). Every error rate is averaged by 3 random runs (shaded area indicates the stddev). Consistent with Fig. 2 in the main text, when DA is used, the optimal number of epochs is postponed and postponed more for KD than CE. When a stronger DA is used, the optimal number of epochs is postponed even more with smaller optimal test loss.

We collect this (mean) covariance v (a scalar) and correlation r (a scalar) over many batches and then take the average of all the collected v and r,

$$\bar{v} = \frac{1}{K} \sum_{k \in [K]} v_k,$$

$$\bar{r} = \frac{1}{K} \sum_{k \in [K]} r_k.$$
(13)

where K is the total number of batches (10 epochs in our experiments, $K = 7,818$).

Then, we replace the proposed "Std of mean prob." with $\bar{v}$ and $\bar{r}$ in Tab. 1, resulting in two new tables: Tab. 10 and Tab. 11.

As seen, the foremost impression of Tab. 10 and Tab. 11 is that they have more red uparrows, which implies the metric goes *against* the supposed order, undermining its efficacy. *E.g.*, AutoAugment is stronger than Cutout (in that Autoaugment includes Cutout as a part; also AutoAugment performs better than Cutout as the test losses indicate). However, by $\bar{v}$ (see Tab. 10), AutoAugment is ranked "*weaker*" than Cutout with teacher resnet56 and vgg13.

As for Tab. 11, the correlation metric $\bar{r}$ is even worse than $\bar{v}$ in the sense that it incurs even more red uparrows than $\bar{v}$. Especially, CutMixPick (T. ent.) is the best DA (delivering the lowest test loss) while by $\bar{r}$ it "*underperforms*" all the other DA schemes except Identity and Autoaugment, with the teacher resnet56.

Why does the covariance metric $\bar{v}$ not work as well as our proposed metric? The covariance metric arises directly from our proposition, if the proposition is correct, why does it not work well? Fundamentally, the reason is that the covariance among samples is *hard* to estimate accurately. When we calculate the covariance matrix $Cov(P, P)$, P is of shape $N \times C$. Note, each row of P is an *attribute (or random variable, RV)* and each column of P is an *observation*[‡]. The number of observations of P is the number of classes, *which is a constant* for a given dataset (in the current case, it is 100 for the CIFAR100 dataset). Intuitively, given two random variables, in order to estimate the covariance between them, merely 100 observations is not very much. Namely, the limited observations render the direct estimation of the covariance among samples *inaccurate*. This can explain the counterexamples between $\bar{v}$ and test loss in Tab. 10.

(If the covariance metric is accurately estimated, it would not be surprising that the correlation in Tab. 11 is also inaccurate. Especially, the normalization itself may not be desired. We put the results of using correlation as metric simply for a reference.)

Then, how does the proposed metric resolve this "limited observation" problem? The "smart thing" of the proposed metric is that it considers *the sum of RVs* instead of the RV itself. In statistics, it is well-known that, when multiple RVs are added together, the variance (or equivalently, std) of the sum RV will take into account the covariance among its members[§], as shown below:

$$Var(\sum_{i=1}^{N} X_i) = \sum_{i=1}^{N} Var(X_i) + 2 \sum_{1 \le i < j \le N} Cov(X_i, X_j), \tag{14}$$

where X_i (with a little abuse of notation here) is the teacher's output probability of the i-th example. Essentially, we want to estimate the covariance term in RHS (*i.e.*, $\sum_{1 \le i < j \le N} Cov(X_i, X_j)$). Now, what we do in the paper is to use the LHS (*i.e.*, $Var(\sum_{i=1}^{N} X_i)$) as a *proxy* of the covariance term. Clearly, there is a *hidden assumption* here to allow us to use such a proxy: the first term of RHS (*i.e.*, $\sum_{i=1}^{N} Var(X_i)$) stays (nearly) the same for different samples (*i.e.*, different batches) of $\{X_i\}$. In our work, there are two conditions to make this hidden assumption hold in practice. **(1)** The augmented images are based on the original images. We can still consider them in the same domain (in our Proposition 1, X_i is actually assumed to be drawn from the same distribution), so $Var(X_i)$ is close for different X_i. **(2)** We have abundant samples ($N = 640$ in our experiments). The sum effect of so many samples makes $\sum_{i=1}^{N} Var(X_i)$ stabilize to a constant.

These said, we can actually come up with counterexamples that *intentionally* break the hidden assumption. *E.g.*, consider a "bad" DA which turns all input images to a *constant* image. Then the input batch will become a repetition of just one image. When we input such a batch to the teacher, the teacher's output probability will be the same. Then the $Var(\sum_{i=1}^{N} X_i)$ term will become zero. It cannot be a legitimate proxy for the covariance term anymore as the first term of RHS now is zero.

We are aware of the existence of such counterexamples. Notably, they do *not* affect the validity of the proposed metric. Here are the reasons – For one thing, such bad DA rarely appears in practice. The strong correlation per se already demonstrates the efficacy of the proposed metric in practical cases. For another thing, there is an important design in our training setup to avoid such counterexamples – Note we *add* the augmented images to the original images instead of replacing

---

[‡]Interested readers are encouraged to check out this numpy covariance function, which we use to implement $\bar{v}$: https://numpy.org/doc/stable/reference/generated/numpy.cov.html

[§]See https://www.wikiwand.com/en/Variance, "Linear combinations" part.

them (see Fig. 3). Therefore, in a batch, it is *unlikely* that all the images degenerate to one image. Namely, the counterexample we just mentioned never appear in practice.

Then how to understand such counterexample? Why it *appears* to go against our theory? Fundamentally, the counterexample we just mentioned breaks one of the key assumptions of our proposition in the first place – each individual sample (including the original image *and the augmented image*) obeys the same true (unknown) data distribution $\mathcal{D}$. The bad DA transforms all input images to a constant image, which already means the individual sample is not drawn from the true data distribution since randomly drawing from the true data distribution will not give us the same image.

To further confirm this, we implement the "bad" DA and re-check the validity of the proposed metric $\bar{m}$ with wrn_40_2/wrn_16_2 on CIFAR100. When using the "bad" DA, we have the metric value $\bar{m} = 0.022439$. Compare this to Tab. 3, we will notice it is ranked the *highest* (*i.e.*, the *worst*). This agrees with our expectation.

In short, the counterexamples above do not affect the efficacy of our proposed metric in practice.

Table 10: KD test loss ("Test loss") and the **covariance of the teacher's output** ($\bar{v}$) comparison on CIFAR100 when using different data augmentation schemes. This table is a replica of Tab. 1 in the paper just replacing the "Std of mean prob." with $\bar{v}$ here.

| Teacher | wrn_40_2 | | | resnet56 | | | vgg13 | | |
| Student | wrn_16_2/vgg8 | | | resnet20/ShuffleV2 | | | vgg8/MobileNetV2 | | |
	wrn_40_2 $\bar{v}$	wrn_16_2 Test loss	vgg8 Test loss	resnet56 $\bar{v}$	resnet20 Test loss	ShuffleV2 Test loss	vgg13 $\bar{v}$	vgg8 Test loss	MobileNetV2 Test loss
KD+Identity	0.00015322	1.0976	1.1830	0.00014041	1.1783	0.9785	0.00015447	1.1856	1.6021
KD+Flip	0.00015258↓	1.0774↓	1.1673↓	0.00013956↓	1.1668↓	0.9961↑	0.00015522↑	1.1754↓	1.5779↓
KD+Flip+Crop	0.00014922↓	1.0837↑	1.1446↓	0.00013380↓	1.1763↑	0.9736↓	0.00015133↓	1.1537↓	1.5244↓
KD+Cutout	0.00014114↓	1.0564↓	1.1306↓	0.00012680↓	1.1687↓	0.9541↓	0.00014300↓	1.1279↓	1.4963↓
KD+AutoAugment	0.00013504↓	1.0305↓	1.1102↓	0.00012304↑	1.1478↓	0.9355↓	0.00014306↑	1.1273↓	1.4137↓
KD+Mixup	0.00012844↓	1.0507↓	1.0917↓	0.00011760↓	1.1621↓	0.9703↓	0.00013265↓	1.1194↓	1.4009↓
KD+CutMix	0.00011725↓	1.0310↓	1.0657↓	0.00010520↓	1.1424↓	0.9348↓	0.00011377↓	1.0728↓	1.2846↓
KD+CutMixPick (S. ent.)	0.00010184↓	1.0054↓	1.0471↓	0.00008972↓	1.1269↓	0.9339↓	0.00009727↓	1.0605↓	1.2739↓
KD+CutMixPick (T. ent.)	0.00009197↓	0.9753↓	0.9928↓	0.00007949↓	1.0853↓	0.9038↓	0.00008676↓	0.9884↓	1.1876↓

Table 11: KD test loss ("Test loss") and the **correlation coefficient of the teacher's output** ($\bar{r}$) comparison on CIFAR100 when using different data augmentation schemes. This table is a replica of Tab. 1 in the paper just replacing the "Std of mean prob." with $\bar{r}$ here.

| Teacher | wrn_40_2 | | | resnet56 | | | vgg13 | | |
| Student | wrn_16_2/vgg8 | | | resnet20/ShuffleV2 | | | vgg8/MobileNetV2 | | |
	wrn_40_2 $\bar{r}$	wrn_16_2 Test loss	vgg8 Test loss	resnet56 $\bar{r}$	resnet20 Test loss	ShuffleV2 Test loss	vgg13 $\bar{r}$	vgg8 Test loss	MobileNetV2 Test loss
KD+Identity	0.01570871	1.0976	1.1830	0.01570028	1.1783	0.9785	0.01562722	1.1856	1.6021
KD+Flip	0.01564524↓	1.0774↓	1.1673↓	0.01559539↓	1.1668↓	0.9961↑	0.01570224↑	1.1754↓	1.5779↓
KD+Flip+Crop	0.01559558↓	1.0837↑	1.1446↓	0.01537652↓	1.1763↑	0.9736↓	0.01559079↓	1.1537↓	1.5244↓
KD+Cutout	0.01530729↓	1.0564↓	1.1306↓	0.01510221↓	1.1687↓	0.9541↓	0.01531730↓	1.1279↓	1.4963↓
KD+AutoAugment	0.01856617↑	1.0305↓	1.1102↓	0.01971744↑	1.1478↓	0.9355↓	0.01947365↑	1.1273↓	1.4137↓
KD+Mixup	0.01497638↓	1.0507↓	1.0917↓	0.01512188↓	1.1621↓	0.9703↓	0.01507644↓	1.1194↓	1.4009↓
KD+CutMix	0.01498818↑	1.0310↓	1.0657↓	0.01502888↓	1.1424↓	0.9348↓	0.01473911↓	1.0728↓	1.2846↓
KD+CutMixPick (S. ent.)	0.01508117↑	1.0054↓	1.0471↓	0.01536088↓	1.1269↓	0.9339↓	0.01462629↓	1.0605↓	1.2739↓
KD+CutMixPick (T. ent.)	0.01525488↑	0.9753↓	0.9928↓	0.01564995↑	1.0853↓	0.9038↓	0.01487075↑	0.9884↓	1.1876↓

A.3 Example of Calculating T. Stddev

Take CIFAR100 for an example. It has 50,000 training samples. With batch size 64, one epoch amounts to 782 batches. During training, the K in Eq. (9) is set to 10. During the iteration of training data loader, we collect the teacher's outputs. Every $K/2$ training batches (the division of 2 is because we *append* the augmented images to the original images), we obtain a matrix of shape $[K \times \text{batch}_{\text{s}}\text{ize}, \text{num\_classes}]$. Then we average this matrix along the 1st axis to give us a vector, *i.e.*, the $\mathbf{u}$ in Eq. (9). In brief, every $K/2$ batches, we have one sample of $\mathbf{u}$. In total, we run the data loader for *10 epochs* (10 is empirically set; more epochs should give us more accurate estimation but we just find 10 is good enough), which gives us 7820/5=1654 $\mathbf{u}$'s, *i.e.*, a matrix of shape $[1654, \text{num\_classes}]$. Then we calculate the variance along the 1st axis, giving us a vector of shape $[\text{num\_classes}]$, *i.e.*, the $\mathbf{m}$ in Eq. (10). Finally, we average the stddev elements in $\mathbf{m}$ to obtain the proposed *scalar* metric.

A.4 CutMix Sample Analysis on ImageNet

CutMix sample analysis and why KD is naturally suited to exploit CutMix. During the KD training of resnet34/resnet18 on ImageNet, we recorded the CutMix samples on which the teacher *disagrees* with the CutMix scheme on the label. We call this *label disagreement issue*.

As show in Fig. 6. there exist cases where the image cut from one image covers the salient object in the other. For example, the cab in (a) completely covers the ground beetle. In this case, using the label by CutMix does not make sense anymore. A similar problem appears on (b). Note that these misleading labels by CutMix are rectified when the teacher is employed to guide the student. The teacher assigns the correct label "cab" to (a) and "Yorkshire terrier" to (b) (which is still not the true label "Tibetan terrier" but it is clearly more relevant and "Tibetan terrier" is also in the top-5 predictions). For (c) and (d), they pose a problem more than occlusion: the foreground cut in (c) is labeled as "acoustic guitar", however, the cut is too small for us to make it out without knowing the label. Meanwhile, the background object "Arabian camel" is occluded. Then the grids in the picture turn out to be the most salient part. If we look at the predictions of the teacher, "shopping cart" and "shopping basket" clearly make more sense than either of the original two labels. A similar issue happens on (d), where the "Indian elephant" is largely occluded. The foreground cut is labeled "quill" but the bottle in the middle is more salient. Thus the teacher predicted it as "coffeepot", "milk can", etc.

In order to see how severe the label disagreement issue is, we counted the number of these synthetic samples and found that on **more than half of the samples (52.1%)** produced by CutMix, the teacher model and CutMix hold a different view regarding the label. Many of these suffer from the problem shown in Fig. 6. The KD loss can rectify these label mistakes. This further shows the interplay between KD and DA: KD thrives on DA and *in turn, some DA schemes are more reasonable for KD* (than CE) where a teacher can supply more relevant labels.

Figure 6: ImageNet CutMix samples where the main object in one of the images is no longer visible after CutMix augmentation. Below each sample, the first is the target probability assigned by CutMix and the second is the top-5 predicted probabilities by the teacher. These examples can be misleading when cross-entropy loss is used, but not for KD, as explained in the text.

A.5 Limitations and Potential Negative Societal Impacts

Limitations. The proposed metric is calculated with finite training samples. The precision of the metric values will necessarily depend on the number of training samples used. In this regard, we have tried our best to avoid the influence of statistical variations (using abundant samples). The presented results in the paper are shown stable. Especially, the correlation in Tabs. 1 and 2 is strong. This fact itself is a proof that the limitation of our paper in this regard is small.

Potential Negative Societal Impacts. Simply put, this work proposes theories and algorithms that can boost the performance of a network with the aid of a larger network (*i.e.*, the teacher-student distillation), that is, make it smaller, faster, and possibly consume less energy in practical applications. We focus on the classification task, which is generally the foundation of the many up-stream computer vision tasks like detection and segmentation. Therefore, this work potentially has a broad application especially in the computer vision areas.

The algorithm itself has few negative societal issues, but when it makes many AI-driven technologies applicable in practice, the impact really depends on how humans use them. This actually falls into the general ethical discussion on whether AI is good or not. Beyond this scope, this work does not have specific negative societal impacts brought by its potential application, to our best knowledge.