Bridging Formal Language with Chain-of-Thought Reasoning to Geometry Problem Solving

Abstract

Large vision language models exhibit notable limitations on Geometry Problem Solving (GPS) because of their unreliable diagram interpretation and pure natural-language reasoning. A recent line of work mitigates this by using symbolic solvers: the model directly generates a formal program that a solver can execute. However, this direct program generation lacks intermediate reasoning, making the program prone to errors. In this work, we explore integrating Chain-of-Thought (CoT) with geometry formal language for visually grounded geometry problem solving. The model interleaves natural language reasoning with incremental emission of solver-executable code, producing a hybrid reasoning trace in which critical derivations are expressed in formal language. To teach this behavior at scale, we combine (1) supervised fine-tuning on an 11K newly developed synthetic dataset with automatic formalization and interleaved formal-natural language reasoning, and (2) solver-in-the-loop reinforcement learning that jointly optimizes both the CoT narrative and the resulting program. Built upon Qwen2.5-VL, our 7B model outperforms other models at the same scale by up to 18% on GPS benchmarks, while our 32B model achieves performance on par with leading models such as Gemini-2.5 Pro with 2.2× higher token efficiency. Furthermore, we present a comprehensive analysis of method design choices (e.g., reasoning paradigms, data synthesis strategies, and training methodologies), providing actionable insights for future research.

1 Introduction

Large Vision Language Models (LVLMs) have emerged as powerful tools for a wide range of applications, demonstrating impressive capabilities in tasks such as visual question answering, video understanding, etc. (Li et al., 2023; Liu et al., 2023; Team et al., 2024; Hurst et al., 2024; Lu et al., 2024a; Bai et al., 2025). Despite these rapid advances, LVLMs still exhibit significant weaknesses in reasoning ability (Chen et al., 2021; Lu et al., 2024b; Zhang et al., 2024). When confronted with tasks requiring spatial or geometric reasoning, current models frequently produce inconsistent or incorrect results, substantially limiting their utility in practical applications (Liu et al., 2023; Gupta & Kembhavi, 2023; Yang et al., 2025).

This paper investigates Geometry Problem Solving (GPS) (Chen et al., 2021; Lu et al., 2024b), a particularly challenging reasoning task where LVLMs must reason across geometric diagrams while applying geometry knowledge. Many recent efforts to improve LVLM reasoning capabilities has focused predominantly on *natural language* reasoning approaches (Bai et al., 2025; Team et al., 2025; Huang et al., 2025), which, however, are limited in handling numerical computations, often produce redundant outputs, and cannot ensure the solution process is correct (see Figure 2(a)).

To address these limitations, a line of work explores *formal language* reasoning for geometry (Lu et al., 2021; Zhang et al., 2023b;a; Xia et al., 2024). In this paradigm, given the text and diagram, the model generates a formal program that encodes solver-executable steps; a geometry solver then executes the program to produce the final answer (see Figure 2(b)). While this approach improves rigor and verification, *direct* program generation is often too rigid: it provides limited room for flexible intermediate exploration, step revision, and high-level planning, which may constrain the model's reasoning capability.

Figure 1: Top: Performance comparison with specialist geometry systems (GeoX, NGS, Geoformer, and PGPSNet) using direct formal program generation, evaluated on two benchmarks (PGSP and UniGeo). Bottom: Token efficiency comparison with frontier LVLMs.

This tension motivates a central question:

Can we bridge intermediate reasoning with formal language in geometry problem solving?

Interleaved formal–natural reasoning. In this work, we propose a hybrid reasoning framework for geometry problem solving that couples the flexibility of natural-language deliberation with the precision of solver-executable formal programs. As illustrated in Figure 2(c), our framework *interleaves* natural language with progressive formal program generation: natural language is used to construct intermediate structures—*diagram interpretation*, *problem formalization*, and *reasoning trajectory planning*—that specify what entities and relations to track, what variables to introduce, and which theorem-level steps to attempt. The model then commits each pivotal geometric inference to a compact formal operator (i.e., a theorem application with explicit variable bindings) that can be executed and checked by a geometry solver. The remainder of this paper presents how we instantiate these patterns and train LVLMs to reliably perform such interleaved formal–natural reasoning in geometry-solving setting.

Post-training is necessary. Turning the above framework into a reliable procedure is non-trivial. We find that prompting alone fails to elicit stable interleaved reasoning behaviors (see Section C.3), largely because (i) formal syntax and (ii) the interleaving pattern itself may be underrepresented in the model's pretraining distribution. This motivates post-training strategies that explicitly teach the model *how* to build intermediate structures and *how* to translate critical steps into executable formal programs. Two practical challenges arise. First, high-quality hybrid trajectories are scarce online: how can we construct an effective dataset, and what properties must it have? Second, optimization is non-trivial: our experience shows that straightforward supervised fine-tuning (SFT) alone often fails to unlock the full potential of hybrid reasoning and may lag behind strong natural-language reasoning baselines.

Our approach. To answer the above questions, we employ two effective post-training strategies: 1) *SFT on a newly developed Interleved Formal-Natural Chain-of-Thought (IFN-CoT)* dataset. We curate an 11k-sample CoT dataset featuring auto-formalization and interleaved formal-natural language reasoning trajectories. The dataset is constructed via bidirectional synthesis to enhance the utilization efficiency of available data. SFT on this dataset enables the model to automatically formalize informal inputs into formats suitable for formal reasoning (e.g., by explicitly binding problem and process variables to operands) and internalize geometric formal language syntax. 2) *Solver-integrated RL.* SFT alone proves insufficient for achieving a strong hybrid reasoning capacity (see Section 4.3). Therefore, we develop a solver-in-the-loop RL framework where a geometric solver executes the resulting formal program and returns verification feedback on solution correctness. This iterative process refines the CoT trajectory and ultimately increases performance by a substantial margin.[1]

---

[1]Our empirical results show that RL increases Pass@1 accuracy by 26%. Notably, without RL, our model fails to match the performance of natural language reasoning alone.

Problem

in quadrilateral P Q R S , P Q = 721 , Q R = 547 , R S = 593 , P S = 756 , and m \\angle P = 58 . find m \\angle P Q S .

(a) Natural Language

<think> Okay, let's see. I need to find the measure of angle PQS in quadrilateral PQRS. …… Hmm. Maybe I need to use the given sides and the angle at P to find some other angles or sides. …… Wait, but maybe I can use the Law of Sines or Law of Cosines in triangle PQS. …… If I can find QS, then I can use the Law of Cosines. But how to find QS? …… Let's denote angle at Q as x, and angle at S as y. …… However, since the sum of angles in a triangle is 180 degrees, x + y + 58° = 180°, so x + y = 122°. But without more information, I can't determine x and y individually. Wait, but maybe the answer is 122° – 58° = 64°? But that's just a guess. Alternatively, maybe the answer is 64 degrees. But I need to check. …… Alternatively, maybe the answer is 64 degrees. But I need to check. …… Alternatively, maybe the answer is 64 degrees. But I need to check. …… **<keep repetition>** ❌

(b) Formal Language

Sum V0 N4 C180 Get V0

🐍 >>> 122.0 ❌

(c) Hybrid Reasoning

First, note that in △PQS, we have
    PQ = 721, PS = 756, and ∠P = 58°.
We want ∠PQS, the angle at Q.
By the Law of Cosines in △PQS at ∠P, we can find the side QS (opposite ∠P) as
    $QS^2 = PQ^2 + PS^2 - 2 \cdot PQ \cdot PS \cdot \cos(\angle P)$.
    Let
        PQ = N0 = 721, PS = N1 = 756, ∠P = N2 = 58.
    Use Law of Cosines to find QS (call it V0):

Cos_Law V0 N0 N1 N2

    → $V0^2 = N0^2 + N1^2 - 2 \cdot N0 \cdot N1 \cdot \cos(N2)$
    so V0 is the length QS.
Next, in △PQS, we want ∠PQS (call it V1), with
    PQ = N0, QS = V0, and PS = N1 as the side between ∠PQS.
    Apply the Law of Cosines again at ∠PQS to find that angle (opposite side PS = N1),
    where
        PS = N1, PQ = N0, QS = V0, and ∠PQS = ∠V1.
    By
        Law of Cosines on ∠PQS:
        $PS^2 = PQ^2 + QS^2 - 2 \cdot PQ \cdot QS \cdot \cos(\angle PQS)$ →

Cos_Law N1 N0 V0 V1

    so
        $N1^2 = N0^2 + V0^2 - 2 \cdot N0 \cdot V0 \cdot \cos(V1)$
        and V1 is ∠PQS.
Finally, retrieve ∠PQS with Get.

\boxed{Cos_Law V0 N0 N1 N2 Cos_Law N1 N0 V0 V1 Get V1}
\boxed{N0=721 N1=756 N2=58}

🐍 >>> 63.448 ✅

Figure 2: Illustration of interleaved formal-natural reasoning for geometry problem solving. (a) Natural language solution from Vision-R1 Huang et al. (2025), in which the symbol "..." denotes the omitted long reasoning steps; (b) Formal language solution generated by GeoX (Xia et al., 2024); (c) Hybrid reasoning solution produced by our GF-Reasoner model.

Results. Built on the Qwen-2.5-VL series, our model **GF-Reasoner** (Geometric Formal Reasoner) achieves strong performance and efficiency. As shown in Figure 1, our 7B model surpasses specialized geometry systems (e.g., GeoX (Xia et al., 2024), PGPSNet (Zhang et al., 2023a)[2]) as well as frontier LVLMs (e.g., Claude-3.7 Sonnet, Qwen-2.5-VL-72B (Bai et al., 2025)). We further train a 32B variant based on Qwen-2.5-VL-32B, which achieves competitive performance with Gemini 2.5 Pro while being 2.2× more token-efficient[3]. Beyond accuracy, GF-Reasoner produces concise outputs by condensing complex derivations into compact operators and offloading explicit computation to an external solver. We also provide a systematic analysis of key design choices—from the reasoning paradigm and data synthesis strategy to post-training methodologies—to offer actionable insights for future research.

Our main contributions can be summarized as follows:

- We study interleaved formal–natural CoT for multimodal geometry problem solving, a geometry-specific hybrid reasoning paradigm that combines natural-language planning with solver-executable formal operations.

---

[2]PGPSNet is not evaluated on UniGeo because the benchmark lacks annotations for the structural and semantic clauses required by the model.

[3]We count the total number of generated tokens consumed during inference including thinking/reasoning tokens.

- We curate an 11k-sample interleaved formal-natural CoT dataset using a bidirectional synthesis methodology. This is the first dataset of its kind for geometry reasoning, with careful designs from synthetic strategy and data patterns, filling an important gap in the community.

- We validate the effectiveness of our method in both performance and token efficiency. We also provide a comprehensive study of post-training strategies that may offer actionable insights for future research.

2 Related Work

Geometry Problem Solving (GPS). GPS plays a crucial role in industry, manufacturing, and scientific areas. Since the 1970s, automated GPS has been an important research focus, which includes geometry calculation and geometry proving. In the context of geometry calculation, existing approaches fall into two categories: symbolic solvers and neural solvers. Symbolic solvers, such as GEOS (Seo et al., 2015), Inter-GPS (Lu et al., 2021), and E-GPS (Wu et al., 2024), parse diagrams and textual problems into several conditions. They then iteratively deduce new conditions by applying theorem rules until the problem is solved. While these solvers offer high interpretability, they rely on meticulously designed rules, making them difficult to extend. Recent advances in AI have shifted the focus from symbolic to neural methods. By leveraging neural networks to interpret geometry diagrams and derive formal program solutions, models like NGS (Chen et al., 2021), Geoformer (Chen et al., 2022), PGPSNet (Zhang et al., 2023a), and GeoX (Xia et al., 2024) have demonstrated promising results. These approaches use neural networks to parse the problem and predict a formal-language solution, which is then executed by an external solver to compute the numerical answer.

Current neural methods have several notable limitations. On the one hand, they directly predict the result without intermediate reasoning, constraining their ability to solve more complex problems. On the other hand, some specialist geometry models face limited adaptability due to their restrictive input requirements. For example, GeoX, NGS and Geoformer require problem variables to be explicitly declared in text questions (e.g., the text questions are like "In triangle ABC, AC = N0, AB = N1, ...", where the value of N0 and N1 are predefined in a numerical list). In contrast to prior geometry problem-solving methods that mainly rely on either direct formal-program prediction or natural-language reasoning, our work studies how to interleave a geometry-specific formal language with natural-language CoT for multimodal geometry problem solving, possibly unlocking the reasoning potential of neural approaches for geometry calculation problems. Meanwhile, our method can auto-formalize the informal inputs by automatically binding problem variables into operands, offering higher flexibility.

Multimodal Large Language Model Reasoning. Improving complex reasoning capability of large models has been regarded as a critical pathway toward artificial general intelligence (Guo et al., 2025). In the field of large multimodal models, Zhang et al. (2024) are among the first to systematically evaluate the mathematical reasoning ability of LVLMs. Their results reveal that LVLMs often generate incorrect answers with an incorrect reasoning process. Furthermore, among incorrect reasoning, calculation errors could contribute to 19.95%. GeoSense (Xu et al., 2025a) is a recently developed benchmark to systematically evaluate the geometric reasoning abilities of LVLMs through the lens of geometric principles. They found that the identification and application of geometric principles remain a bottleneck for leading LVLMs. Recent advances in multimodal reasoning have led to several notable approaches (Huang et al., 2025; Xu et al., 2025b; Luo et al., 2025; Shen et al., 2025; Wang et al., 2025). A representative example is Vision-R1 (Huang et al., 2025), which employs DeepSeek R1 to automatically generate visual reasoning data from textual descriptions. While these methods demonstrate promising results, they primarily rely on natural language reasoning. In our work, we overcome natural language's imprecision and redundancy by combining it with formal language, enabling both flexible and concise geometric reasoning.

Interleaving Language Reasoning with Tools. Prior work has explored interleaving language reasoning with executable tools. ReAct Yao et al. (2023) interleaves reasoning traces with actions, while Math-Coder Wang et al. (2024) and ToRA Gou et al. (2024) integrate natural-language reasoning with code or external tools for mathematical problem solving. Lean-STaR Lin et al. (2025) is closer in spirit to our work, as it trains models to interleave informal thoughts with formal Lean tactics before each proof step. Our

work connects this line of tool-augmented reasoning with formal geometry problem solving, but targets a different setting: multimodal geometry problem solving with a geometry-specific formal operator language. Unlike code-based methods that rely on general-purpose languages well represented in pretraining corpora, our method teaches LVLMs to acquire domain-specific operators, ground visual diagrams into symbolic operands, and interleave theorem-level formal steps with natural-language planning.

Table 1: Comparison with existing methods in geometry problem solving.

Method	Language	CoT Reasoning
Specialist Geometry System	Formal Language	×
MLLMs	Natural Language	✓
GF-Reasoner (Ours)	Interleaved Formal-Natural	✓

3 Method

This section presents our method for GPS. We begin by providing background on geometric formal language in Section 3.1, followed by our data synthesis approaches in Section 3.2, and finally present the training procedures in Section 3.3.

3.1 Geometric Formal Language

Our work builds on the geometry solver and formal language defined in (Zhang et al., 2023a). It has 34 *operators* and 55 *operands*.[4] Each operator encodes a specific geometric theorem or axiom, covering fundamental operations across triangles, quadrilaterals, polygons, circles, and other geometric shapes. These operators mainly work with three types of operands: *problem variables* (`N`) representing known measurements from the problem statement, *process variables* (`V`) representing intermediate results generated during computation, and *constants* (`C`) encoding common numerical values. A formal program specifies a deduction step using these operators and operands. For example, the formal program `Gougu N0 N1 V0` applies the Pythagorean theorem to calculate the hypotenuse, where `N0` and `N1` are two known leg lengths, and `V0` is the hypotenuse to be computed.

To solve a GPS instance with this executor, a model must: (i) **interpret** the diagram and text, (ii) **formalize** entities into operands, (iii) **reason** by selecting appropriate operators to express geometric relations, and (iv) **code** the final formal program. The generated program, together with extracted problem variables, is then executed by a geometry solver to compute unknown process variables. Concretely, the solver performs symbolic and algebraic manipulation using Python's SymPy library.

This framework offers two key advantages. First, it **decouples reasoning from arithmetic** by offloading arithmetic calculations to an external solver, eliminating calculation errors common in natural language reasoning involving complex operations (e.g., inverse trigonometric functions). Second, it provides significant **conciseness** over natural language—while natural language requires multi-step descriptions (e.g., calculate the octagon's area by dividing into triangles, computing each area, then summing), formal language expresses this as: `RNgon_B_Area C8 N0 V0` (where `N0` = side length, `V0` = resulting area). This conciseness helps mitigate reasoning errors that arise from the long contexts required in verbose natural language reasoning.

Our goal is to teach LVLMs to use a geometry-specific interleaved formal-natural language reasoning. While prompt strategies seem straightforward, our evaluation shows that state-of-the-art LVLMs frequently revert to natural language or create undefined operators instead of using geometry operators (Appendix C.3). This suggests that the evaluated LVLMs do not reliably possess or use this geometry-specific formal language under prompting alone, likely because such documentation is absent from their training corpora. We address this data scarcity in the following sections.

---

[4]Compared to geometry solvers used in prior work (Chen et al., 2021; 2022), this formal language includes 16 additional operators and provides broader coverage of geometric theorems.

Figure 3: Overview of the interleaved formal-natural CoT data synthesis process.

3.2 Interleaved Formal-Natural CoT Data Synthesis

In this section, we curate high-quality data to teach LVLMs formal language reasoning. Our approach leverages advanced LVLMs which, although not specialized in geometric formal languages, exhibit strong instruction following and general reasoning, making them suitable generators when provided with explicit specifications and demonstrations. Our core strategy incorporates **comprehensive operator definitions** and **carefully crafted examples** in the system prompts to guide LVLMs in combining reasoning with formal language. We formally define our synthesis setup using the following notations:

- `spec`: Detailed description of formal operands and operators and solution format requirements.

- `examples` $= \langle x_i, z_i, p_i \rangle_{i=1}^n$: Set of manually written example demonstrations showing interleaved formal-natural CoT reasoning using geometric symbols.

- x: Target question to be solved, containing the geometric problem statement and diagram.

- z: Synthetic interleaved formal-natural CoT reasoning trajectory generated by advanced LVLMs.

- p: Final formal program representing the executable solution.

We design examples (see Appendix C) with a response style that first formalizes the problem using both problem variables and process variables, then explicitly cites relevant operators and theorems to derive the final solution. This approach aligns with the deliberative alignment approach in (Guan et al., 2024).

Synthesis Objective. Given the structured prompt containing formal description, demonstration, target question, and the ground-truth program (when available), our goal is to generate high-quality interleaved formal-natural reasoning z that: 1) demonstrates step-by-step problem solving using geometric operators, (2) produces a valid formal program that can be executed by the geometric solver. To achieve this, we design two complementary synthesis strategies tailored to different dataset types, as illustrated in Figure 3. For datasets with only numerical solutions (e.g., UniGEO (Chen et al., 2022), Geo170k (Gao et al., 2025)), we utilize *forward synthesis* to generate both reasoning steps and formal program solutions from the given problems. For datasets with ground-truth formal program annotations (e.g., PGPS9k (Zhang et al., 2023a)), we employ *backward synthesis* to derive reasoning trajectories by backtracking from problems to their formal program solutions. The synthesis prompts are provided in Appendix C for reference.

Forward Synthesis. Given the structured prompt (`spec`, `examples`, x), the LVLM will generate $\widehat{y} = [\widehat{z}, \widehat{p}]$, where $\widehat{z}$ represents the model-generated interleaved formal-natural CoT reasoning trajectory and $\widehat{p}$ denotes

Figure 4: The two-stage training pipeline of our framework.

the corresponding formal program solution. To filter out valid synthetic samples with correct reasoning chain $\widehat{z}$ and program $\widehat{p}$, we execute $\widehat{p}$ with a geometric solver and compare its output to the ground-truth numerical solution. While flexible, forward synthesis achieves low success rates ($< 20\%$ for Qwen-2.5-VL-72B), highlighting the difficulty of establishing formal language reasoning through prompting alone. To address this, we leverage existing datasets with labeled programs (e.g., PGPS9K) as valuable hints for LVLMs, leading to our backward synthesis approach.

Backward Synthesis. We develop another backward synthesis method using the extended prompt $(\texttt{spec}, \texttt{examples}, x, p)$ that includes the correct program solution. The model generates the reasoning chain $\widehat{z}$ that leads to the given p. We design a customized backward synthesis strategy to retrieve corresponding in-context learning examples from a manually written example database by matching the first operator in the solution program. This method further improves synthesis accuracy (shown in Table 5 later). The improvement stems from the model's prior knowledge of the correct program, enabling it to concentrate on reconstructing the reasoning path that links the question to the formal solution.

In total, we synthesize 11k interleaved formal-natural CoT reasoning samples, comprising 2.2k and 3.8k samples generated through forward data synthesis on the UniGEO and Geo170K training sets, and 5k samples produced via backward synthesis on the PGPS9K training set. Synthetic examples are provided in Appendix C.4. We note that although we leverage a frontier LVLM OpenAI-o4-mini as generators, our data construction is *not* a direct distillation pipeline (i.e., simply copying a teacher model's free-form CoT), because the synthesis relies on *customized, domain-grounded prompting* and *externally verified selection*.

3.3 Training Procedures

Stage 1: Cold-Start Supervised Fine-tuning. Using the synthetic reasoning data, we conduct supervised fine-tuning of the LVLM to establish foundational interleaved formal-natural reasoning capabilities. The training objective is:

$$\min_{\theta} \mathbb{E}_{(x,z,p)\sim\mathcal{D}}[-\log \pi_{\theta}(z, p|x)], \tag{1}$$

where $\mathcal{D}$ denotes our synthetic dataset containing geometry problems paired with interleaved formal-natural reasoning chains and programs, and π_{θ} is the probability distribution of the LVLM.

This initial stage serves as a warm-up phase, equipping the model with two fundamental capabilities: (1) autoformalization of informal inputs into a format suitable for formal reasoning, and (2) basic comprehension of geometric formal language syntax. We empirically find that SFT alone is insufficient to achieve strong performance given the training samples and compute budget available (See Section 4.3). One possible explanation is that training with offline data constrains the model's behaviors. To address this limitation, we explore RL with online self-generated data to improve generalization performance.

Stage 2: Solver-Integrated Reinforcement Learning. After training on reasoning samples in the first stage, the model possesses effective exploration capability and basic formal language reasoning ability, though these abilities are not yet perfect. The subsequent reinforcement learning stage further refines these abilities through solver-guided optimization. In this phase, the model interacts with a geometric solver that provides verification results for the output program, enabling trial-and-error learning. The objective is as follows:

$$\max_{\theta} \mathbb{E}_{(z,p)\sim\pi_\theta(\cdot|x)}[r(z,p)], \tag{2}$$

where the reward function $r(z,p)$ is computed by executing the generated program p through the geometric solver to obtain a numerical result for the target variables specified in the question, where $r(z,p) = 1$ if the result matches the ground-truth solution, and 0 otherwise. To optimize the objective, we employ the GRPO algorithm (Shao et al., 2024) with a higher clip ratio (Yu et al., 2025).

Despite the simplicity of the reward design, we find it works effectively in our setting. In our tested variant, adding a syntactic-validity process reward—checking whether the generated formal program is grammatically valid—does not yield additional gains. More details are discussed in Section 4.3.

4 Experiments

4.1 Experiment Setup

Baselines. We compare our method against three categories of baselines: 1) Specialist geometry systems for geometry calculation problems, comprising GeoX (Xia et al., 2024), NGS (Chen et al., 2021), Geoformer (Chen et al., 2022), and PGPSNet (Zhang et al., 2023a). 2) Open-Source General LVLMs, which include open source models Qwen2.5-VL-7B (Bai et al., 2025), Qwen2.5-VL-72B, InternVL3-8B-Instruct (Zhu et al., 2025), Vision-R1-7B (Huang et al., 2025), Kimi-VL-A3B-Instruct (Team et al., 2025), and Kimi-VL-A3B-Thinking. 3) leading LVLMs including GPT-4o, Claude-3.7 Sonnet, and Gemini 2.5 Pro.

Datasets. We assess geometric reasoning capabilities across four established benchmarks: (1) the test splits of PGPS9K and UniGEO, and (2) the plane geometry subsets from the MathVista (Lu et al., 2024b) testmini split and the MathVerse (Zhang et al., 2024) Text-Dominant testmini split, which provide cross-domain evaluation of mathematical visual reasoning.

Evaluation Metrics. Performance is measured by comparing numerical solutions against ground-truth answers, reporting the Pass@1 accuracy. To eliminate choice bias when evaluating on MathVista and Math-Verse, we reformulate multiple-choice questions as free-form generation questions, ensuring fair assessment of the model's inherent reasoning ability.

4.2 Main Results

Comparison with Specialist Geometry Systems. Figure 1 (top) demonstrates our method's performance on geometric problem solving compared to specialist geometry systems.[5] Our 32B model achieves significantly better performance than existing geometry solvers, with gains of +29 points on PGPS9K and +23 points on UniGEO [6]. Additionally, it is noteworthy that our method exhibits much higher flexibility by eliminating the need for pre-formalized questions and additional clauses. It can extract problem variables and formalize informal questions directly in the reasoning process. In contrast, specialist systems have limited adaptability due to their restrictive requirements: (1) GeoX, NGS, and Geoformer require problem variable formalization within the text question. (2) PGPSNet requires additional structured and semantic clauses beyond the text question and image diagram, which are typically unavailable in standard geometry problems.

Comparison with Frontier LVLMs. Figure 1 (bottom) demonstrates our method's performance compared to existing frontier LVLMs. Our GF-Reasoner-7B model significantly outperforms other models at the

---

[5]The baseline scores are sourced from (Xia et al., 2024).

[6]We note that this comparison is not fully apples-to-apples because our model is substantially larger than several specialist systems; thus, we treat it as a contextual comparison.

Table 2: Progressive component analysis.

Config	Reasoning Paradigm	Data Synthesis	Style	Training Method	Pass@1	Pass@8
A	Pure Formal	Forward Only	-	SFT Only	18.3	40.4
B	Interleaved	Forward Only	Qwen	SFT Only	20.8	52.6
C	Interleaved	Bidirectional	Qwen	SFT Only	31.2	61.1
D	Interleaved	Bidirectional	o4-mini	SFT Only	42.1	76.5
E (Ours-7B)	**Interleaved**	**Bidirectional**	**o4-mini**	**SFT + RL**	**68.7**	**80.7**

same scale (e.g., Qwen-2.5-VL-7B, Vision-R1-7B) and even surpasses much larger LVLMs (e.g., Claude-3.7 Sonnet, Qwen-2.5-VL-72B). Our 32B model achieves performance on par with leading models such as Gemini-2.5 Pro while being 2.2× more token-efficient. A detailed performance comparison is provided in Table 7 in the Appendix.

4.3 Analysis

In this section, we conduct ablation studies to systematically evaluate our framework's key components. Our analysis focuses on three critical aspects that contribute to the overall performance: (1) reasoning paradigm, particularly the benefits of bridging formal language with CoT reasoning in test-time scaling[7] and error reduction, (2) data synthesis strategies for training data preparation, (3) SFT and RL training recipes for establishing foundational knowledge and strategy refinement.

Progressive Component Analysis. The ablation study in Table 2 reveals progressive performance improvements on our 7B model across configurations. Moving from pure formal language (Config A) to interleaved reasoning (Config B) provides +12.2% Pass@8 gain, showing that integrating formal language with CoT enables more effective exploration of the solution space. Bidirectional synthesis (Config C) dramatically outperforms forward-only synthesis, achieving +10.4% improvement on Pass@1, due to more synthetic data obtained by leveraging ground-truth programs as synthesis hints. Transfer from Qwen to o4-mini reasoning style for data synthesis (Config D) delivers a +10.9% Pass@1 boost, highlighting the importance of advanced reasoning capabilities for generating coherent interleaved formal-natural chains. Adding solver-in-the-loop RL, our complete approach (Config F) achieves 68.7% Pass@1, representing a remarkable +26.6% improvement over Config D, demonstrating that RL enables the model to learn from solver feedback and refine its formal reasoning strategies through iterative improvement.

Enhanced Inference-Time Performance through Bridging Formal Language with CoT. We conduct a controlled study comparing bridging formal language with CoT reasoning against direct formal language prediction. We perform SFT on the Qwen-VL-2.5-7B model using two carefully curated datasets derived from PGPS9K, matched in size and sample composition. The first dataset includes responses with step-by-step formal-language-interleaved reasoning trajectories, while the second contains only final formal program outputs. As shown in Figure 5, integrating formal language with CoT reasoning demonstrates superior Pass@K scaling for K = 1, 2, 4, 8, with the performance gap widening as the number of samples increases. Notably, on the PGPS9k dataset, CoT and non-CoT achieve comparable performance in Pass@1 evaluation, while CoT achieves a 7% relative improvement in Pass@8. This evidence suggests CoT's intermediate reasoning steps enable more effective exploration of the solution space during inference. Our finding aligns with (Prystawski et al., 2023), which suggests that CoT enables the chaining of local knowledge to estimate relationships between variables not observed together during training.

How Integrating Formal Language in Reasoning Reduces Errors? To evaluate the advantages of integrating formal language in reasoning over traditional natural language reasoning, we categorize errors into four distinct types and evaluate how each type of error is reduced. The error type categorization follows existing works (Zhang et al., 2024; Lu et al., 2024b): 1) visual perception errors, 2) reasoning errors, 3)

---

[7]Test-time scaling refers to leveraging additional computational resources during inference to enhance model performance (Snell et al., 2024).

Table 3: Four types of errors in models using natural language versus interleaved formal-natural reasoning.

Error Type	Natural Language	Interleaved CoT
Reasoning Error	23.0%	**14.3%**
Geometry Knowledge Error	12.3%	**10.3%**
Computation Error	1.7%	**0.3%**
Visual Perception Error	**3.0%**	8.0%
All	40%	**32.9%**

Table 4: Reasoning paradigm comparison

Reasoning Paradigm	PGPS9K	UniGEO
Pure Formal Language Reasoning	51.8%	55.2%
Pure Natural Language Reasoning	60.0%	68.7%
Interleaved Formal-Natural CoT	68.7%	72.7%

Table 5: Comparison of different data synthesis strategies.

Method	Accuracy(%)
Forward	19.5
Backward	47.5
Customized Backward	**50.0**

geometric knowledge errors, and 4) computation errors. Representative examples of each error type are shown in Appendix B.

To provide a comparative baseline for solving the geometry problems in natural language reasoning, we trained another natural language reasoning model using the same base model on the same dataset as our 7B model with reinforcement learning. The reward function was calculated by comparing the extracted numerical solution from the generated response with the ground truth solution.

We conducted an error analysis on the same problem set to highlight the differences between our interleaved formal-natural model and the natural language baseline model. The error analysis, presented in Table 3, demonstrates reductions in reasoning errors, geometry knowledge errors, and computation errors. Notably, interleaved formal-natural reasoning reduces reasoning errors by 8.7%. Besides, by offloading symbolic computation to an external solver, interleaved formal-natural reasoning reduces computation errors to nearly zero despite the already low baseline computation error rate.[8] We further provide quantitative results in Table 4. We also observe an increase in visual perception errors. This may be because interleaving makes the model commit earlier to a symbolic interpretation of the diagram; once a visual relation is incorrectly formalized, subsequent solver-guided reasoning tends to preserve this symbolic state rather than re-check the image. Our comparisons use the same dataset and training procedures (SFT+RL) for all three paradigms at the 7B scale. The result confirms that interleaved CoT consistently outperforms both pure approaches, demonstrating the benefits of interleaving in improving performance. For concrete examples of how formal reasoning eliminates computation and reasoning errors, refer to Appendix B. We can observe that interleaved formal-natural reasoning offers a more reliable and precise reasoning pathway than pure natural language.

Customized Backward Synthesis for Improved Synthesis Accuracy. Table 5 compares three synthesis strategies (forward, backward, and customized backward) using Qwen-VL-2.5-72B. We evaluate synthesis accuracy by extracting both the formal solution program and problem variables, then verifying them against ground truth numerical solutions using a geometry solver.

---

[8]The computation error in interleaved formal-natural reasoning is not zero because there is one sample where the model incorrectly calculated intermediate numerical results in natural language without using formal language.

Figure 5: Pass@K performance comparison of supervised fine-tuned models trained with pure formal language versus interleaved formal-natural reasoning.

(a) Performance

(b) Entropy

(c) Response Length

Figure 6: Performance, entropy, and response length on the PGPS9K test set during RL training varying training epochs of SFT initialization.

Our results demonstrate that backward synthesis yields a significant accuracy improvement ($19.5\% \rightarrow 47.5\%$). This suggests that reconstructing the reasoning path from question to formal solution is more effective when the formal solution destination is known. Further performance gains ($47.5\% \rightarrow 50.0\%$) are achieved by customizing in-context learning examples based on the target solution program, highlighting the importance of example-question alignment for efficient synthesis.

Moderate SFT Preserves Reasoning Potential. Previous studies in natural language reasoning (Li et al., 2025; Zeng et al., 2025) suggest that excessive SFT may compromise response diversity, consequently limiting the model's reasoning capacity establishment in RL training. Our experiment results also verify this point. We perform an ablation study examining varying durations of cold start training (epochs) and their impact on subsequent RL performance. As illustrated in Figure 6, intensive fine-tuning (8 epochs, yellow color line) yields diminishing performance, showing sluggish performance gains during RL post-training. While moderate fine-tuning (2 epochs, red color line) achieves substantially better RL training efficiency. Additional entropy and response length measurements during RL training further confirm that the moderate cold start preserves response diversity, creating a more exploratory policy space that ultimately unlocks greater reasoning potential during RL post-training.

On the Design of the Reward Function. We investigated extending the binary final-answer reward with partial credit for intermediate steps. Specifically, we defined a process reward that checks the *grammatical validity* of the generated formal program (i.e., reward=1 if the program is syntactically correct). As shown in Figure 7 (left), adding this process reward during RL training does not yield gains compared to using the

Figure 7: Left: The performance during RL training with and without process reward. Right: Performance on PGPS9K before/after RL training across different operator numbers.

binary outcome reward alone. We further evaluate additional process-reward variants in Appendix B, and observe a similar trend. We emphasize that this result does not rule out all possible process rewards. Rather, it shows that the process rewards tested in our study do not provide additional benefits in this setting. One possible explanation is that multi-trajectory sampling in RL already provides implicit partial-credit signals: correct intermediate steps occur more frequently in successful trajectories, allowing the model to statistically learn which reasoning patterns lead to correct outcomes.

RL Training Delivers Substantial Performance Gains Across Problem Complexities. To investigate how RL training impacts problem-solving capability, we stratify the PGPS9k test problems into five levels by operator count (2, 3, 4, 5, and ≥6), and report the 7B model's Pass@8 performance before and after RL training. As indicated in Figure 7 (right), RL training demonstrates clear benefits: 1) RL enhances Pass@1 performance across all complexity levels, showing universal benefit in generating correct solutions on the first attempt. 2) RL delivers significant Pass@8 performance improvements for medium-complexity problems: +11.6% (3 ops), +21.1% (4 ops), and +16.7% (5 ops). While neither easy (operator=2) nor harder problems (operator ≥ 6) show little Pass@8 improvement, suggesting RL primarily optimizes tasks where the base model has learnable but suboptimal strategies.

5 Conclusion

In this paper, we introduce a new hybrid reasoning paradigm for solving geometry problems, combining natural language with formal reasoning steps to leverage the complementary strengths of both approaches. To facilitate this framework, we curate an 11k-sample dataset featuring interleaved formal-natural CoT reasoning, including auto-formalization and natural-formal interleaved reasoning trajectories. Using this dataset, we investigate post-training procedures (SFT and RL) to train models in hybrid reasoning. Our results demonstrate that GF-Reasoner yields significant improvements in geometric problem-solving performance. We further provide a comprehensive analysis of key design choices, offering practical insights for future work in this direction.

6 Broader Impact

This work focuses on enhancing geometric problem-solving capabilities in large vision-language models. The dataset used is synthetically generated and does not involve human subjects or sensitive data. Our research aims to contribute to educational tools for mathematics, with potential positive implications for STEM education and AI-assisted learning.

References

Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, et al. Qwen2. 5-vl technical report. *arXiv preprint arXiv:2502.13923*, 2025.

Jiaqi Chen, Jianheng Tang, Jinghui Qin, Xiaodan Liang, Lingbo Liu, Eric P Xing, and Liang Lin. Geoqa: A geometric question answering benchmark towards multimodal numerical reasoning. In *Findings of the Association for Computational Linguistics (ACL)*, 2021.

Jiaqi Chen, Tong Li, Jinghui Qin, Pan Lu, Liang Lin, Chongyu Chen, and Xiaodan Liang. Unigeo: Unifying geometry logical reasoning via reformulating mathematical expression. In *The 2022 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2022.

Yumeng Fu, Jiayin Zhu, Lingling Zhang, Bo Zhao, Shaoxuan Ma, Yushun Zhang, Yanrui Wu, and Wenjun Wu. Geolaux: A benchmark for evaluating mllms' geometry performance on long-step problems requiring auxiliary lines. *arXiv preprint arXiv:2508.06226*, 2025.

Jiahui Gao, Renjie Pi, Jipeng Zhang, Jiacheng Ye, Wanjun Zhong, Yufei Wang, Lanqing Hong, Jianhua Han, Hang Xu, Zhenguo Li, et al. G-llava: Solving geometric problem with multi-modal large language model. In *International Conference on Learning Representations (ICLR)*, 2025.

Zhibin Gou, Zhihong Shao, Yeyun Gong, Yujiu Yang, Minlie Huang, Nan Duan, Weizhu Chen, et al. Tora: A tool-integrated reasoning agent for mathematical problem solving. In *International Conference on Learning Representations*, volume 2024, pp. 48362–48395, 2024.

Melody Y Guan, Manas Joglekar, Eric Wallace, Saachi Jain, Boaz Barak, Alec Helyar, Rachel Dias, Andrea Vallone, Hongyu Ren, Jason Wei, et al. Deliberative alignment: Reasoning enables safer language models. *arXiv preprint arXiv:2412.16339*, 2024.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, et al. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025.

Tanmay Gupta and Aniruddha Kembhavi. Visual programming: Compositional visual reasoning without training. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14953–14962, 2023.

Wenxuan Huang, Bohan Jia, Zijie Zhai, Shaosheng Cao, Zheyu Ye, Fei Zhao, Zhe Xu, Yao Hu, and Shaohui Lin. Vision-r1: Incentivizing reasoning capability in multimodal large language models. *arXiv preprint arXiv:2503.06749*, 2025.

Aaron Hurst, Adam Lerer, Adam P Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, et al. Gpt-4o system card. *arXiv preprint arXiv:2410.21276*, 2024.

Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. *arXiv preprint arXiv:2301.12597*, 2023.

Ziniu Li, Congliang Chen, Tian Xu, Zeyu Qin, Jiancong Xiao, Zhi-Quan Luo, and Ruoyu Sun. Preserving diversity in supervised fine-tuning of large language models. In *The Thirteenth International Conference on Learning Representations*, 2025.

Haohan Lin, Zhiqing Sun, Sean Welleck, and Yiming Yang. Lean-star: Learning to interleave thinking and proving. In *International Conference on Learning Representations*, volume 2025, pp. 66041–66062, 2025.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. *Advances in Neural Information Processing Systems*, 2023.

Haoyu Lu, Wen Liu, Bo Zhang, Bingxuan Wang, Kai Dong, Bo Liu, Jingxiang Sun, Tongzheng Ren, Zhuoshu Li, Hao Yang, et al. Deepseek-vl: towards real-world vision-language understanding. *arXiv preprint arXiv:2403.05525*, 2024a.

Pan Lu, Ran Gong, Shibiao Jiang, Liang Qiu, Siyuan Huang, Xiaodan Liang, and Song-Chun Zhu. Inter-gps: Interpretable geometry problem solving with formal language and symbolic reasoning. In *ACL*, 2021.

Pan Lu, Hritik Bansal, Tony Xia, Jiacheng Liu, Chunyuan Li, Hannaneh Hajishirzi, Hao Cheng, Kai-Wei Chang, Michel Galley, and Jianfeng Gao. Mathvista: Evaluating mathematical reasoning of foundation models in visual contexts. In *International Conference on Learning Representations (ICLR)*, 2024b.

Ruilin Luo, Zhuofan Zheng, Yifan Wang, Xinzhe Ni, Zicheng Lin, Songtao Jiang, Yiyao Yu, Chufan Shi, Ruihang Chu, Jin Zeng, et al. Ursa: Understanding and verifying chain-of-thought reasoning in multimodal mathematics. *arXiv preprint arXiv:2501.04686*, 2025.

OpenAI. Introducing openai o3 and o4-mini, 2025. URL `https://openai.com/index/introducing-o3-and-o4-mini/`.

Ben Prystawski, Michael Li, and Noah Goodman. Why think step by step? reasoning emerges from the locality of experience. *Advances in Neural Information Processing Systems*, 36:70926–70947, 2023.

Minjoon Seo, Hannaneh Hajishirzi, Ali Farhadi, Oren Etzioni, and Clint Malcolm. Solving geometry problems: Combining text and diagram interpretation. In *Proceedings of the 2015 conference on empirical methods in natural language processing*, pp. 1466–1476, 2015.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Y Wu, et al. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.

Haozhan Shen, Peng Liu, Jingcheng Li, Chunxin Fang, Yibo Ma, Jiajia Liao, Qiaoli Shen, Zilun Zhang, Kangjia Zhao, Qianqian Zhang, et al. Vlm-r1: A stable and generalizable r1-style large vision-language model. *arXiv preprint arXiv:2504.07615*, 2025.

Charlie Snell, Jaehoon Lee, Kelvin Xu, and Aviral Kumar. Scaling llm test-time compute optimally can be more effective than scaling model parameters. *arXiv preprint arXiv:2408.03314*, 2024.

Gemini Team, Petko Georgiev, Ving Ian Lei, Ryan Burnell, Libin Bai, Anmol Gulati, Garrett Tanzer, Damien Vincent, Zhufeng Pan, Shibo Wang, et al. Gemini 1.5: Unlocking multimodal understanding across millions of tokens of context. *arXiv preprint arXiv:2403.05530*, 2024.

Kimi Team, Angang Du, Bohong Yin, Bowei Xing, Bowen Qu, Bowen Wang, Cheng Chen, Chenlin Zhang, Chenzhuang Du, Chu Wei, et al. Kimi-vl technical report. *arXiv preprint arXiv:2504.07491*, 2025.

Haozhe Wang, Chao Qu, Zuming Huang, Wei Chu, Fangzhen Lin, and Wenhu Chen. Vl-rethinker: Incentivizing self-reflection of vision-language models with reinforcement learning. *arXiv preprint arXiv:2504.08837*, 2025.

Ke Wang, Houxing Ren, Aojun Zhou, Zimu Lu, Sichun Luo, Weikang Shi, Renrui Zhang, Linqi Song, Mingjie Zhan, and Hongsheng Li. Mathcoder: Seamless code integration in llms for enhanced mathematical reasoning. In *International Conference on Learning Representations*, volume 2024, pp. 5009–5042, 2024.

Wenjun Wu, Lingling Zhang, Jun Liu, Xi Tang, Yaxian Wang, Shaowei Wang, and Qianying Wang. E-gps: Explainable geometry problem solving via top-down solver and bottom-up generator. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 13828–13837, 2024.

Renqiu Xia, Mingsheng Li, Hancheng Ye, Wenjie Wu, Hongbin Zhou, Jiakang Yuan, Tianshuo Peng, Xinyu Cai, Xiangchao Yan, Bin Wang, et al. Geox: Geometric problem solving through unified formalized vision-language pre-training. *arXiv preprint arXiv:2412.11863*, 2024.

Liangyu Xu, Yingxiu Zhao, Jingyun Wang, Yingyao Wang, Bu Pi, Chen Wang, Mingliang Zhang, Jihao Gu, Xiang Li, Xiaoyong Zhu, et al. Geosense: Evaluating identification and application of geometric principles in multimodal reasoning. *arXiv preprint arXiv:2504.12597*, 2025a.

Yi Xu, Chengzu Li, Han Zhou, Xingchen Wan, Caiqi Zhang, Anna Korhonen, and Ivan Vulić. Visual planning: Let's think only with images. *arXiv preprint arXiv:2505.11409*, 2025b.

Jihan Yang, Shusheng Yang, Anjali W Gupta, Rilyn Han, Li Fei-Fei, and Saining Xie. Thinking in space: How multimodal large language models see, remember, and recall spaces. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pp. 10632–10643, 2025.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik R Narasimhan, and Yuan Cao. React: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations*, 2023.

Qiying Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, Yu Yue, Weinan Dai, Tiantian Fan, Gaohong Liu, Lingjun Liu, et al. Dapo: An open-source llm reinforcement learning system at scale. *arXiv preprint arXiv:2503.14476*, 2025.

Weihao Zeng, Yuzhen Huang, Qian Liu, Wei Liu, Keqing He, Zejun Ma, and Junxian He. Simplerl-zoo: Investigating and taming zero reinforcement learning for open base models in the wild. *arXiv preprint arXiv:2503.18892*, 2025.

Ming-Liang Zhang, Fei Yin, and Cheng-Lin Liu. A multi-modal neural geometric solver with textual clauses parsed from diagram. In *IJCAI*, 2023a.

Renrui Zhang, Dongzhi Jiang, Yichi Zhang, Haokun Lin, Ziyu Guo, Pengshuo Qiu, Aojun Zhou, Pan Lu, Kai-Wei Chang, Yu Qiao, et al. Mathverse: Does your multi-modal llm truly see the diagrams in visual math problems? In *European Conference on Computer Vision*, pp. 169–186. Springer, 2024.

Xiaokai Zhang, Na Zhu, Yiming He, Jia Zou, Qike Huang, Xiaoxiao Jin, Yanjun Guo, Chenyang Mao, Yang Li, Zhe Zhu, et al. Formalgeo: An extensible formalized framework for olympiad geometric problem solving. *arXiv preprint arXiv:2310.18021*, 2023b.

Jinguo Zhu, Weiyun Wang, Zhe Chen, Zhaoyang Liu, Shenglong Ye, Lixin Gu, Hao Tian, Yuchen Duan, Weijie Su, Jie Shao, et al. Internvl3: Exploring advanced training and test-time recipes for open-source multimodal models. *arXiv preprint arXiv:2504.10479*, 2025.

A   Distinctions from Other Frameworks

Comparison with ReACT. Our proposed method is conceptually similar to ReAct (Yao et al., 2023) at high-level in terms of interleaving reasoning and actions. However, there are fundamental differences in problem setting, technical challenges, and contributions.

- Inference-time prompting vs. Learning interleaved reasoning capabilities. ReAct is primarily an inference-time prompting framework that enables pre-trained models to alternate between reasoning and acting for general task solving. It assumes the model already possesses the necessary reasoning and action capabilities, and focuses on how to better orchestrate them through prompting. However, as shown in Table 8, directly prompting state-of-the-art models to perform interleaved formal-natural reasoning in geometry yields poor results. In contrast, our work addresses a fundamentally different challenge: teaching models to acquire the capability to perform interleaved formal-natural reasoning through post-training. Geometry problem solving requires models to learn domain-specific formal operators and how to properly interleave them with natural language reasoning—capabilities that do not exist in base models.

- Natural language actions vs. Formal symbolic operations. ReAct interleaves natural language reasoning with natural language actions (e.g., "Search[topic]" or API calls). Our approach interleaves natural language with formal symbolic operations that require: strict syntactic correctness; symbolic precision and mathematical rigor; domain-specific geometric operators (e.g., angle calculations, geometric constructions). This presents distinct technical challenges in data curation, training stability, and ensuring both reasoning coherence and formal correctness.

- Our work makes several contributions beyond applying an interleaving concept: 1) Curated training data: A interleaved formal-natural CoT dataset specifically designed for geometry, filling a gap in the community; 2) Systematic training strategies: Comprehensive study of SFT and RL approaches for learning interleaved reasoning; 3) Domain-specific insights: Analysis of how interleaving maintains exploration potential and reduces reasoning and computation errors in mathematical problem solving.

Thus, while ReAct demonstrates the value of interleaving at inference time for general tasks, our work shows how to effectively train models to perform interleaved formal-natural reasoning in specialized mathematical domains. These are complementary contributions addressing different aspects of the broader challenge.

Comparison with Thinking with Images. Recently, "Thinking with Images" has been introduced as a framework that leverages enhanced visual intelligence to solve problems through detailed image analysis, seamlessly integrating advanced reasoning with tools such as web search and automated image manipulations (e.g., zooming, cropping, flipping, and enhancement) to extract insights even from imperfect visual inputs (OpenAI, 2025). Our approach is orthogonal and complementary to this vision. While "Thinking with Images" emphasizes visual representations and planning in the image space, leveraging visual reasoning for geometric understanding. Our approach proposes a new reasoning paradigm in the language space that interleaves formal symbolic computation with natural language reasoning, aiming to achieve both mathematical precision (through formal language) and reasoning flexibility (through natural language). Therefore, these two frameworks are not conflicting but orthogonal, they focus on different representation spaces. An exciting future direction would be to combine both paradigms. We will explore this integration in future work.

B   Additional Results

Effect of Teacher Model vs. Solver-in-the-Loop RL. Table 2 may give the impression that the improvement mainly comes from distilling a stronger teacher model, since the SFT-only gain from Config C to Config D is larger than the gain from Config B to Config C. To show that the performance gain is not mainly comes from distilling a stronger teacher model, we added a new setup in which we continue solver-in-the-loop RL from Config C, i.e., the model initialized with Qwen-synthesized bidirectional data

Table 6: Effect of solver-in-the-loop RL under different SFT initializations.

Setting	SFT-only	SFT + RL
Config C: Interleaved + Bidirectional + Qwen	31.2%	63.9%
Config D/E: Interleaved + Bidirectional + o4-mini	42.1%	68.7%
Gap	10.9%	4.8%

(a) UniGEO   (b) MathVista

Figure 8: The performance during RL training with and without per-operator correctness and operand-binding validity reward.

rather than o4-mini-synthesized data. Starting from the Qwen-synthesized Config C, RL improves Pass@1 PGPS9K accuracy to 63.9%, close to the 68.7% achieved by our final model, as illustrated in Table 6. This experiment clarifies the complementary roles of data synthesis and solver-in-the-loop RL. A stronger teacher provides a better cold-start initialization, while teacher-independent solver-in-the-loop RL stage can recover much of the gap even from the weaker initialization.

Evaluate More Process Rewards. We extend the original formal-language validity reward with two additional process rewards. The previous reward only checked whether all predicted DSL tokens belong to the valid operator/operand vocabulary, and assigned a binary formal-language reward. In the new design, we add two new process-level rewards. First, we add a per-operator structural correctness reward, which checks whether each DSL step starts with a valid operator, whether the operator arity is well-formed, and whether the program terminates with a `Get` operation. Second, we add an intermediate operand-binding validity reward, which checks whether numeric operands are within the valid range, whether intermediate variables are introduced before being queried, and whether symbolic variables are grounded in the predicted parameter list. These two added rewards address operator-level structural errors and operand-reference errors beyond the original lexical validity check.

The results are shown in Figure 8. Empirically, adding these process rewards does not improve final answer accuracy. We further analyzed why this reward does not help. The syntactic-validity process reward is almost saturated: most samples already receive a high syntactic score 95%, so the reward has little discriminative power. In practice, this near-constant process reward contributes little useful ranking signal and may introduce weakly correlated variance into the normalized advantage. Second, the binary answer reward already implicitly captures much of the useful process-validity information: a program that executes to the correct final answer typically must use valid DSL tokens, well-formed operators, and consistent operand bindings. Thus, the additional process rewards are largely redundant with the final-answer reward, while being less directly aligned with the evaluation metric.

Therefore, our conclusion is narrowed: the tested process rewards, including per-operator structural correctness and intermediate operand-binding validity, do not improve answer accuracy over the binary answer reward in our setting. We do not claim that all possible forms of process supervision are ineffective.

Auxiliary-Construction Failure

Question:

AB is the diameter of $\odot O$. Points C and D lie on $\odot O$, $OC \parallel BD$, and chord AD intersects BC and OC at E and F, respectively. Given $CE = 1$ and $EB = 3$, find the radius of $\odot O$.

Model's Full Response

First, observe that $OC \parallel BD \Rightarrow \angle COB = \angle DBA$, so $\triangle CEF \sim \triangle BDA$, hence

$$CE/EB = CF/FA.$$

Also, since AB is diameter, $\angle ACB = 90°$, and one can use the intercept-segment proportionality and right-triangle relations to solve for the radius.
Step-by-step setup:
Let $CE = N0 = 1$ and $EB = N1 = 3$.
By similarity and power-of-a-point one shows OC is the radius, and one can set up a relation to solve for the radius.
First, note that $AB = AE + EB$, so $AB = AE + EB$. We want the radius $r = OB$.
By the similarity and proportion one shows $r = OE+OF$, and one can solve algebraically to get

$$r = \sqrt{CE \cdot EB}.$$

So one way is to use $\sqrt{CE \cdot EB}$ as the radius.
Define
$$CE = N0 = 1, \qquad EB = N1 = 3.$$

Then the radius $r = \sqrt{CE \cdot EB}$.
1. Compute the product $CE \cdot EB$:

$$\texttt{Multiple N0 N1 V0}$$

2. Take the square-root to get the radius:

$$\texttt{Geo\_Mean N0 N1 V1}$$

3. Return the radius:

$$\texttt{Get V1}$$

$$\boxed{\texttt{Multiple N0 N1 V0 Geo\_Mean N0 N1 V1 Get V1}}$$

$$\boxed{\texttt{N0=1 N1=3}}$$

Model Output: 1.732 ✗

Correct Answer

The reference solution requires connecting AC.

After adding AC, since AB is the diameter,

$$\angle ACB = 90°.$$

Together with $OC \parallel BD$, we obtain

$$\triangle ACE \sim \triangle BCA.$$

Therefore,
$$AC^2 = CE \cdot CB.$$

Since
$$CB = CE + EB = 1 + 3 = 4,$$

we have
$$AC^2 = 1 \cdot 4, \qquad AC = 2.$$

Then in right triangle ABC,

$$AB = \sqrt{AC^2 + BC^2} = \sqrt{2^2 + 4^2} = 2\sqrt{5}.$$

Thus the radius is

$$\frac{AB}{2} = \sqrt{5}.$$

Correct Answer: $\sqrt{5}$ ✓
Error Analysis:
The model computes $\sqrt{CE \cdot EB}$, while the correct relation is
$$AC^2 = CE \cdot CB.$$

This relation only becomes available after constructing the auxiliary segment AC. Therefore, the failure is caused by the lack of auxiliary-construction actions in the current formal language.

(a) UniGEO   (b) MathVista   (c) MathVerse (Text Dominant)

Figure 9: Performance on the UniGEO, MathVista, and MathVerse (Text Dominant) test set during RL training varying training epochs of SFT initialization.

Limitations of the Current Formal Language. To characterize the boundary of the current formal setup, we evaluate our 7B model on the recently released GeoLaux benchmark and obtain 52.9% accuracy, while the Qwen-2.5-VL-7B base model only obtain 3% accuracy. This suggests that interleaved formal-natural reasoning can transfer beyond PGPS9K and UniGEO, it also exposes the limitations of the current 34-operator formal language.

The main failure mode is *auxiliary-construction failure*: 65% of the failed examples require constructing auxiliary lines, new points, or new segments. The current PGPSNet-style language can only apply operators to existing geometric objects and does not include explicit construction actions. Therefore, these problems are outside the expressive scope of the current formal language.

The case above provides a representative example. The correct solution requires constructing AC, after which the relation $AC^2 = CE \cdot CB$ becomes available. Since the current language cannot introduce this auxiliary segment, the model applies existing operators to incorrect geometric objects and predicts $\sqrt{CE \cdot EB}$. This motivates future extensions that add auxiliary-construction operators to the formal language.

Performance Gains Beyond Tool Access. To isolate the performance gain given access to tools, we provided baseline models (GPT-4o, Claude-3.7 Sonnet, Qwen-2.5-VL series) with identical formal language description and demonstration examples (used in our training data synthesis) via detailed prompting. This ensures they also have "tool access". As shown in Table 8, despite having explicit access to formal specifications, these strong foundation models still struggle to generate valid interleaved CoT the solver can execute, resulting in low accuracy. This result demonstrates that our performance gains cannot be attributed to given access to tools alone, but stem from teaching models to internalize solver knowledge and reasoning patterns.

SFT Epoch Influence on More Benchmarks. In Figure 6 in the main text, we observe that moderate SFT preserves reasoning potential on PGPS9K dataset. This phenomenon can also be observed on other benchmarks. We have evaluated checkpoints across multiple benchmarks (UniGEO, MathVista, and MathVerse). As shown in Figure 9, the results demonstrate that while SFT is important to build fundamental capacity, heavy SFT may compromise response diversity, consequently limiting the model's reasoning capacity establishment in RL training.

Impact of SFT Training Data Characteristics. The quality and composition of interleaved formal-natural CoT data during SFT training directly influence the base model's mastery in the formal language for geometry problem solving, and consequently affect reasoning trajectory refinement in RL training. We systematically investigate three dimensions of interleaved formal-natural data, analyzing several key variants:

- **CoT Trajectory Style**: We compare the base models trained on interleaved formal-natural reasoning trajectories generated by OpenAI-o4-mini and Qwen2.5-VL-72B, respectively, both are synthesized based on PGPS9K training set with an equal amount (3k each) and identical problem coverage.

Table 7: Performance comparison with frontier LVLMs.

Model	Params	PGPS	UniGeo	MathVista	MathVerse
GPT-4o	-	50.9	43.9	47.1	48.4
Claude-3.7 Sonnet	-	53.7	47.2	52.4	57.1
Gemini 2.5 Pro	-	**83.3**	75.0	**75.0**	**67.5**
Vision-R1-7B	7B	50.5	60.9	59.1	54.3
InternVL3-8B-Instruct	7B	42.1	50.0	50.5	44.1
Kimi-VL-A3B-Instruct	16B	37.0	42.2	42.8	42.3
Kimi-VL-A3B-Thinking	16B	49.2	48.7	62.5	55.9
Qwen2.5-VL-7B-Instruct	7B	39.4	51.5	52.4	47.6
Qwen2.5-VL-32B-Instruct	32B	50.0	70.3	63.5	60.7
Qwen2.5-VL-72B-Instruct	72B	53.3	67.9	63.0	60.5
GF-Reasoner-7B (Ours)	7B	68.7	72.7	64.9	62.8
GF-Reasoner-32B (Ours)	32B	81.9	**77.7**	73.6	66.0

Table 8: Performance on PGPS9k when given access to formal language description and demonstration examples.

Method	Accuracy
GPT-4o	6.4%
Claude-3.7 Sonnet	16.2%
Qwen-2.5-72B-VL-Instruct	14.0%
Qwen-2.5-7B-VL-Instruct	0.1%

(a) Style   (b) Amount   (c) Difficulty

Figure 10: Performance on the PGPS9K test set during RL training varying SFT initialization dataset, including CoT trajectory style, dataset amount, and difficulty coverage.

- **Dataset Amount**: With the OpenAI-o4-mini CoT style, we experiment by varying the number of training examples used, specifically using 2k, 6k, and 10k randomly sampled examples as SFT training data, respectively.

- **Difficulty Coverage**: According to the number of geometry operators used, we categorize the training dataset into two difficulty levels, including easy (≤ 3 operators) and medium/hard (≥ 4 operators). We create equal-sized subsets for each difficulty level (2k each) and train the base model on the two subsets.

We perform the ablation study varying each of the three dimensions independently to isolate their impact on model performance. Results are presented in Figure 10.

Figure 11: A case study on improving visual perception through image zooming.

The results in Figure 10(a) demonstrate that RL training initialized with OpenAI-o4-mini-style CoT data consistently outperforms training based on Qwen-VL-2.5-72B-style data. To investigate this discrepancy, we analyze the reasoning trajectories of both models. We observe that OpenAI-o4-mini generates more logically consistent and formally precise reasoning steps, leading to better policy initialization for RL. Additionally, the results in Figure 10(b) indicate that increasing the amount of SFT initialization data improves the final RL performance, but the gains diminish beyond a certain threshold (e.g., 6k samples). This suggests that a relatively small but well-curated dataset is sufficient for the model to learn the fundamental grammar and usage of geometric formal language during SFT. Additional data provides only marginal improvements. Interestingly, from Figure 10(c), we could also observe that the difficulty level of SFT data (easy vs. medium/hard) does not significantly affect final RL performance. Although models trained on medium/hard CoT data initially underperform those trained on easy data, both converge to similar accuracy after RL training. This implies that SFT primarily serves to teach foundational knowledge of formal language, which can be acquired from either easy or hard problems, while RL compensates for higher-level reasoning gaps.

Zooming Images for Better Perception. We have tested integrating a zoom tool and found it effective. It provides higher-resolution details, which improves visual perception. On PGPS9K, this raised accuracy from 68.7% to 69.3% and reduced the visual perception error from 8.0% to 6.0%. A supporting case study is provided in Figure 11, where applying a 2x zoom enables the model to obtain a clearer view, leading to the correct identification of corresponding sides in a pair of similar triangles. These results suggest that incorporating image processing tools can aid visual reasoning and improve geometric understanding, thereby complementing the current framework.

Error Analysis: Comparing Interleaved Formal-Natural vs. Natural Language Reasoning. In Section 4.3, we categorize geometry problem-solving errors into four types: visual perception errors, reasoning errors, geometric knowledge errors, and computation errors. This error taxonomy is adapted from

established frameworks in geometry problem-solving research (Zhang et al., 2024; Fu et al., 2025). The illustration of the four types of errors is described below:

- Visual perception errors: The model failed to either extract salient features from the image or associate the textual information with its corresponding geometric shapes.

- Reasoning errors: The model failed to generate a valid solution, demonstrating either a lack of logical coherence and internal consistency or a failure in procedural execution by skipping necessary operations.

- Geometric knowledge errors: The model's error was either in misapplying a geometric concept or in failing to distinguish between the definitions of two theorems.

- Computation errors: The model failed to calculate the numerical results, leading to errors in calculations involving arithmetic, square roots, and proportions.

We classify the wrong solution into one of the four types of errors based on the first error in the response. As follows, we illustrate representative cases for all four error types. For annotation, two PhD students and one master student in Computer Science are involved, all with expertise in geometry problem solving and LVLMs. Each annotator independently labeled 300 test cases. Disagreements were resolved through discussion to reach consensus. The initial annotation achieved 91% inter-annotator agreement.

Below, we demonstrate how our interleaved formal-natural reasoning model reduces computation error compared to the natural language reasoning baseline. This baseline model is trained with RL using the same base model and training dataset as our approach. The natural language model uses premature approximations in mathematical functions, leading to precision errors in the final result, while our model maintains exact symbolic computation throughout the reasoning process and only performs numerical evaluation at the final step through the geometric solver, thereby preserving mathematical precision and avoiding cumulative rounding errors.

Computation Error Case

Question:
$ED = 7, BE = EG = FG = CF = AC = AB, m\angle ABE = m\angle GEB = m\angle EGF = m\angle GFC = m\angle FCA = m\angle CAB$, find the area of the shaded region.

Natural Language Solution

Model's Response:
To find the area of the shaded region, we first need to understand that the given hexagon is inscribed in a circle with radius $ED = 7$ (i.e., $r = 7$). Since the hexagon is regular, each internal angle is $120°$ (since $360°/6 = 60°$, and each exterior angle is $60°$).

...

The area A_{triangle} of an equilateral triangle with side length r (here $r = 7$) is:

Area of equilateral triangle $= \frac{\sqrt{3}}{4} \cdot r^2$

Substitute $r = 7$:

Area of one equilateral triangle $= \frac{49\sqrt{3}}{4} \approx \frac{49 \cdot 1.732}{4} \approx \frac{84.784}{4} \approx 21.196$

Hence, area of hexagon A_{hexagon} :

$A_{\text{hexagon}} = 6 \cdot 21.196 \approx 127.176$

Next, area A_{circle} :

$A_{\text{circle}} = \pi \cdot r^2 = \pi \cdot 7^2 = 49\pi \approx 49 \cdot 3.14159 \approx 153.94$

Shaded area A_{shaded} :

$A_{\text{shaded}} \approx 153.94 - 127.176 \approx 26.764$

Hence, the area of the shaded region is approximately:

$$\boxed{26.764}$$

Answer:
26.764 (Correct: 26.632) ✗

Error:
Premature use of approximations (e.g., $\sqrt{3} \approx 1.732$) led to a precision error in the final result.

Interleaved Formal-Natural Solution

Model's Response:
Step-by-step reasoning:
1. Let the circle's radius (and the circumradius of the hexagon) be
$N_0 = DE = 7$.
2. Compute the area of the circle with radius N_0.
Use `Circle_R_Area` to get the circle's area:
`Circle_R_Area` N_0 $V_0 \rightarrow V_0 = \pi \cdot N_0^2$
3. Compute the area of the regular hexagon with circumradius N_0.
Use `RNgon_L_Area` for a regular 6-gon of circumradius N_0:
`RNgon_L_Area` C6 N_0 $V_1 \rightarrow V_1 =$ area of the hexagon
4. The shaded region = circle area minus hexagon area.
So we take the circle area V_0 minus the hexagon area V_1.
Use `Sum` to express
$V_1 + V_2 = V_0 \rightarrow V_2$ is the shaded area.
Hence
`Sum` V_1 V_2 $V_0 \rightarrow V_1 + V_2 = V_0 \rightarrow V_2 = V_0 - V_1$
5. Extract the shaded-region area
Get V_2

```
Circle_R_Area N0 V0
```
```
RNgon_L_Area C6 N0 V1
```
```
Sum V1 V2 V0 Get V2
```
```
N0 = 7
```

Answer:
The solver executes the program and outputs 26.632. ✔

Below, we compare interleaved formal-natural reasoning model to the natural language baseline in reducing reasoning errors. The natural language model exhibits logical inconsistencies, makes unjustified assumptions (e.g., arbitrarily setting x=13), and falls into infinite reasoning loops when encountering contradictory results. In contrast, our interleaved formal-natural approach enforces structured reasoning through geometric operators, maintains logical consistency, and leverages external solver verification to prevent arbitrary assumptions and ensure mathematically sound conclusions.

Reasoning Error Case

Question:
In $\odot B$, $m\angle LBM = 3x$ and $m\angle LBQ = 4x + 61$. $MQ \perp KB$ at B, what is the measure of $\angle PBQ$?

Natural Language Solution

Model's Response:
Since $MQ \perp KB$ at B, *KB is the perpendicular bisector of LM at B*....$m\angle LBM = 3x$ and $m\angle LBQ = 4x + 61$... Hence, we can write the equation: $m\angle LBM = m\angle QBM$
Using the equation $3x = 4x + 61 - 3x$:
$x = -61$
Since x cannot be negative, let us use the properties of circle :
m $\angle LBQ = 180 - 3x$.
Using $\angle LBQ = 4x + 61 = 4x + 61$.
$\angle PBQ = 90 - (4x + 61)$.
Using :
m $\angle LBQ = 4x + 61 = 4x + 61$.
...
$\angle PBQ = 4x + 61 = 4*13 + 61 = 4*13 = 52$.
$\angle PBQ = \angle QBM = 4x + 61 = 52$.
$\angle PBQ = \angle QBM = \angle PBQ = \angle PBQ = \angle PBQ = \angle PBQ = ...$

- -

Answer:
52 (Correct: 51) ✗

Error:
The reasoning process involves random guessing, incorrectly assumes the value of x to be 13, and ultimately falls into an infinite loop.

Interleaved Formal-Natural Solution

Model's Response:
Step-by-step reasoning:
1. Let
$N_0 = m\angle LBM = 3x$
$N_1 = m\angle LBQ = 4x + 61$
2. Since $\angle LBM$ and $\angle LBQ$ are supplementary on a straight line,
$N_0 + N_1 = 180$.
Use `Sum` N_0 N_1 C180 $\rightarrow$ $N_0 + N_1 = 180$ (3x + (4x + 61) = 180)
3. $\angle PBQ$ and $\angle LBQ$ are supplementary on the straight line through the diameter, so
$m\angle PBQ = 180 - m\angle LBQ$.
Hence
$V_0 = 180 - N_1$.
Use `Sum` N_1 V_0 C180 $\rightarrow$ $N_1 + V_0 = 180 \rightarrow V_0$ is $m\angle PBQ$
4. Extract the value of $\angle PBQ$
`Get` V_0

| `Sum N0 N1 C180` | `Sum N1 V0 C180 Get V0` |
| `N0 = 3*x N1 = 4*x + 61` | |

- -

Answer:
The solver executes the program and outputs 51. ✔

C   Dataset Details

We provide forward and backward synthetic prompts for generating Interleaved Formal-Natural CoT data samples in Section C.1 and Section C.2. Section C.3 provides a case study on directly prompting state-of-the-art LVLMs with human demonstrations. The results show that they lack prior knowledge of geometric formal language. Finally, we showcase Interleaved Formal-Natural CoT examples from our dataset in Section C.4.

C.1 Forward Synthetic Prompt

> **Forward Synthesis Prompt**
>
> You are a geometry problem expert. You have access to a solver with the following formal language. The following prompt teaches you how to use this language through examples and explanations.
>
> ## Formal Language Specification
>
> ### Operands
> This language uses three types of variables:
>
> - Input values (`N0`, `N1`, `N2`, etc.): These represent given measurements, lengths, angles, or other known values in a problem. The numbering must start from `N0` and increment by 1.
>
> - Calculated values (`V0`, `V1`, `V2`, etc.): These store intermediate calculations or final results. The numbering must start from `V0` and increment by 1.
>
> - Constants (`C0.5`, `C2`, `C3`, `C90`, etc.): These represent common numerical values like 0.5, 2, 3, 90, etc.
>
> ### Operators
> The language includes 34 operators that represent geometric relations and calculations:
>
> ### Basic Mathematical Operations
> - `Get`: Retrieves the numerical value of a variable (e.g., `Get V0` returns the value stored in `V0`)
>
> - `Sum`: Performs addition of multiple terms (e.g., `Sum a b c d` represents $a + b + c = d$)
>
> - `Multiple`: Performs multiplication of multiple terms (e.g., `Multiple a b c d` represents $a \times b \times c = d$)
>
> - `Equal`: Sets two expressions equal (e.g., `Equal a b` represents $a = b$)
>
> ### Triangle Operations
> - `Gougu`: Implements the Pythagorean theorem (e.g., `Gougu a b c` represents $a^2 + b^2 = c^2$)
>
>   - 'a' is the first leg of the right-angled triangle
>   - 'b' is the second leg of the right-angled triangle
>   - 'c' is the hypotenuse opposite the right angle
>
>   . . .
>
> ### Trigonometric Operations
> - `Gsin`: Implements sine relation (e.g., `Gsin a b c` represents $\sin(c) = \frac{a}{b}$)
>
>   - 'a' is the opposite side length
>   - 'b' is the hypotenuse length
>   - 'c' is the angle in degrees
>
>   . . .
>
> ### Quadrilateral Operations
> - `Para_Area`: Calculates parallelogram area (e.g., `Para_Area a b c` represents $a \times b = c$)
>
>   - 'a' is the base length
>   - 'b' is the height perpendicular to the base
>   - 'c' is the resulting area
>
>   . . .

Circle Operations

- `Circle_R_Circum`: Calculates circle circumference from radius (e.g., `Circle_R_Circum a b` represents $2\pi \times a = b$)

  - 'a' is the radius length
  - 'b' is the resulting circumference
  - Optional format: `Circle_R_Circum a b c` represents $2\pi \times a \times \frac{b}{360} = c$, where 'b' is the central angle in degrees and 'c' is the arc length.

  ...

Other Geometric Relations

- `Geo_Mean`: Calculates geometric mean (e.g., `Geo_Mean a b c` represents $\sqrt{a \times b} = c$)

  - 'a' is the first value
  - 'b' is the second value
  - 'c' is the resulting geometric mean
  - This operator has numerous applications in geometric problems:
    * Tangent-Secant Power Theorem: `Geo_Mean PA PB PT` $\rightarrow$ PT is the tangent length when a point P outside the circle has a secant with segments PA and PB, where PT $= \sqrt{PA \times PB}$.
    * Altitude Rule (Right Triangle Projection): `Geo_Mean p q h` $\rightarrow$ In a right triangle, the altitude h to the hypotenuse is the geometric mean of the two segments p and q it creates on the hypotenuse, where h $= \sqrt{p \times q}$.
    * Leg Projection Rule: `Geo_Mean p c a` $\rightarrow$ A leg a of a right triangle is the geometric mean of its projection p on the hypotenuse and the hypotenuse c itself, where a $= \sqrt{p \times c}$.

  ...

Solution Format

- Given the problem, you should first understand it and analyze the image to identify important information that can lead to the solution.

- Reason step-by-step using the above Operators and Operands to arrive at the final solution. You must explicitly state the Operator and Operand you used in your reasoning steps. You may use multiple sequences of Operators and Operands.

- You do not need to calculate the numerical value in your reasoning steps since the solver with your formal language answer can do this.

- Put your final formal language solution and parameter values in `\boxed{}` separately, both on a single line. Ensure that the content inside `\boxed{}` is space-delimited and compatible with Python's `eval()` for direct parsing by the solver.

Examples

Example 1
Problem: Find the area of the figure.
Image:

Step-by-Step Thinking: Looking at the image, I see a parallelogram AEDC with various measurements. From the image and problem statement: - $AC \perp EB$ at point B - $ED = AC = 15$ cm - $AE = DC = 13$ cm - $AB = 7$ cm

I need to find the area of the parallelogram AEDC. Let me solve this by using geometric principles and operations from the formal language:

1. Identify the important information:

   - $AC \perp EB$ at point B
   - $ED = AC = 15$ cm
   - $AE = DC = 13$ cm
   - $AB = 7$ cm

2. Understanding the Solution Path:

   - To find the area of a parallelogram, I need the base and height.
   - I can use $ED = 15$ cm as the base.
   - For the height, I need the perpendicular distance from ED to AC.
   - The problem states $AC \perp EB$ at B, which means AC is perpendicular to EB.
   - I need to find the height $V0$ using the Pythagorean theorem with AB and the distance from A to the line ED.
   - Given $AB = 7$ cm and the distance from A to E is 13 cm, I can use the Pythagorean theorem to find the height.
   - Once I have the height $V0$, I can calculate the area as base $\times$ height.

3. Step-by-Step Reasoning Using Operators and Operands:

   - First, let $ED = AC = $ `N0`, $AE = DC = $ `N1`, $AB = $ `N2`.
   - Then, I use the Pythagorean theorem to find the height `V0`:

     $$\texttt{Gougu V0 N2 N1}$$

     This solves for `V0` where $\texttt{V0}^2 + \texttt{N2}^2 = \texttt{N1}^2$
   - Then, I calculate the area of the parallelogram `V1` using base $\times$ height:

     $$\texttt{Para\_Area N0 V0 V1}$$

     This computes $\texttt{V1} = \texttt{N0} \times \texttt{V0}$
   - Finally, I get the result:

     $$\texttt{Get V1}$$

4. Formal Language Solution:

   $$\boxed{\texttt{Gougu V0 N2 N1 Para\_Area N0 V0 V1 Get V1}}$$

   with parameter values:

   $$\boxed{\texttt{N0=15, N1=13, N2=7}}$$

Example 2

. . .

Your Task

Problem: {{Target problem}}
Image: {{Image diagram of the target problem}}
Step-by-Step Thinking:

C.2 Backward Synthesis Prompt

Customized Backward Synthesis Prompt for `Chord2_Ang_v0`

You are a geometry problem expert. You have access to a solver with the following formal language. The following prompt teaches you how to use this language through examples and explanations.

Formal Language Specification

. . .
⟨Same with the forward synthesis prompt⟩
. . .

Examples

Example 1
Problem: Find $m\angle F$.
Image:

Solution: `Sum V0 N0 C180 Chord2_Ang V0 V1 N1 TanSec_Ang V2 V1 N1 Get V2`

Step-by-Step Thinking: Looking at the circle diagram, I can see several points (D, E, F, G, H, J) with some angles marked:

- $m\angle DJE = 89°$

- $m\angle HG$ (arc HG) $= 61°$

- $m\angle DH$ (arc DH) $= 137°$

- I need to find $m\angle F$

The task is to find angle F. Let me solve this by using geometric principles and operations from the formal language:
1. Identify the Given Information:

- $m\angle DJE = 89°$

- $m\angle HG$ (arc HG) $= 61°$

- $m\angle DH$ (arc DH) $= 137°$

- Point J is inside the circle

- Point F is outside the circle

- Need to find $m\angle F$

2. Understanding the Solution Path:

- First, I notice that points D, H, G, and E lie on the circle. Point J is inside the circle, while point F is outside the circle.

- Since F is outside the circle with secant lines FD and FH, I can use the `TanSec_Ang` theorem

- To apply this theorem, I need to find the intercepted arcs

- To find one of the arcs, I'll use the `Chord2_Ang` operator and properties of angles inside a circle

3. Step-by-Step Reasoning Using Operators and Operands:

- I'll first calculate the supplementary angle to $\angle DJE$, let $\angle DJE = N0$ and $\angle EJG = V0$:
  `Sum V0 N0 C180`
  (This calculates $V0 = 180° - N0 = 180° - 89° = 91°$)

- Since J is a point inside the circle, I can use the `Chord2_Ang` theorem to calculate the arc EG, let arc $DH = N1$ and arc $EG = V1$:
  `Chord2_Ang V0 V1 N1`
  (This relationship comes from the inscribed angle theorem for intersecting chords)

- Finally, since F is outside the circle with secant lines to D and E, I can use the `TanSec_Ang` theorem to find $\angle F$, let $\angle F = V2$:
  `TanSec_Ang V2 V1 N1`
  (This calculates $V2 = (N1 - V1)/2$, using the relationship between the angle formed by secant lines from an external point and the intercepted arcs)

- The final answer is obtained by:
  `Get V2`

4. Formal Language Solution:

`Sum V0 N0 C180 Chord2_Ang V0 V1 N1 TanSec_Ang V2 V1 N1 Get V2`

with parameter values:

`N0=89, N1=137`

Example 2

. . .

Your Task

Problem: {{Target problem}}
Image: {{Image diagram of the target problem}}
Solution: {{Program solution of the target problem}}
Step-by-Step Thinking:

C.3 Weaknesses of Direct Prompting

We prompt the LVLM using manually crafted interleaved formal-natural CoT demonstrations paired with target questions. However, we find that this method often fails. As demonstrated in the following cases, the state-of-the-art LVLMs could revert to natural language instead of maintaining formal language usage

during critical reasoning steps, and they often employ operators undefined in our formal language system. These observations suggest that the model inherently lacks knowledge of geometric formal language.

Case 1: Use Natural Language Rather Than Formal Language (Generated OpenAI-o4-mini)

Problem:
$m\angle DCB = 70$, $m\angle BDC = 4x$, $m\angle ABC = 10x + 22$, find the value of x .
Image:

Output:
Step-by-step reasoning:
1. Observe that A, B, and D are collinear with B between A and D, so $\angle ABC$ is the exterior angle at B of $\triangle BCD$.
2. In any triangle, an exterior angle equals the sum of the two remote interior angles. Here

$$\angle ABC \;=\; \angle BDC \;+\; \angle DCB.$$

3. Substitute the given measures:
$$10x + 22 \;=\; 4x + 70.$$

4. Solve for x:
$$10x + 22 = 4x + 70 \quad\Longrightarrow\quad 6x = 48 \quad\Longrightarrow\quad x = 8.$$

Final answer:
$$x = 8.$$

Error:
The model directly use natural language to solver the problem without following the instruction prompt.

Case 2: Use Undefined Operators (Generated by Qwen2.5-VL-72B)

Problem:
quadrilateral $DEFG$ is a rectangle. if $m\angle EFD = 2x - 3$ and $m\angle DFG = x + 12$, $GF \perp DG$ on G , find $m\angle EFD$.
Image:

Output:

...

Formal Language Solution:

`Sum (Multiple C2 N0 CMinus C3) (Sum N0 C12) C90 Get V0`

with parameter values:

`N0=27`

Error:
`CMinus` is an undefined operator in the formal language.

C.4 Examples of Interleaved Formal-Natural CoT Dataset

We provide some examples in our synthetic interleaved formal-natural CoT dataset below.

Interleaved Formal-Natural CoT Example1

Problem:
assume that all polygons that appear to be regular are regular . $GC = 8$, find the area of the shaded region .
Image:

Output:
First, label the given length `N0 = 8` (GC is the radius of the outer circle).

1. Compute the area of the outer circle (radius `N0`):

   - `Circle_R_Area N0 V0`
   - $V0 = \pi \cdot \texttt{N0}^2$

2. Compute the area of the regular triangle inscribed in that outer circle. A regular 3-gon with circumradius `N0` has area:

   - `RNgon_L_Area C3 N0 V1`
   - $V1 = \frac{3 \cdot \texttt{N0}^2 \cdot \sin(120°)}{2}$

3. Find the apothem (inradius) `V2` of that same triangle by using its area `V1`:

   - `RNgon_H_Area C3 V2 V1`
   - $V1 = 3 \cdot \texttt{V2}^2 \cdot \tan(60°) \Rightarrow$ `V2` is the apothem

4. Compute the area of the inner circle (incircle of the triangle) of radius `V2`:

   - `Circle_R_Area V2 V3`
   - $V3 = \pi \cdot \texttt{V2}^2$

5. The shaded region consists of (outer circle minus the triangle) plus the inner circle. First form the difference outer - triangle:

- `Sum V1 V4 V0`
- $V1 + V4 = V0 \Rightarrow V4 = V0 - V1$

6. Then add in the inner circle:

- `Sum V3 V4 V5`
- $V3 + V4 = V5$

7. Finally output the total shaded area `V5`:

- `Get V5`

Putting it all together:

> `Circle_R_Area N0 V0 RNgon_L_Area C3 N0 V1 RNgon_H_Area C3 V2 V1`
>
> `Circle_R_Area V2 V3 Sum V1 V4 V0 Sum V3 V4 V5 Get V5`

with

> `N0=8`

Interleaved Formal-Natural CoT Example2

Problem:
$QP \parallel RT$, $QR = 2$, $SR = PT = 3$, $PQ = x$, $m\angle TQP = m\angle RQT$, solve for x.
Image:

Output:
Here is the step-by-step setup using our formal language:
Define operands:

- $N0 = QR = 2$

- $N1 = SR = PT = 3$

- $N2 = PQ = x$

1. Since QP ∥ RT, by similar triangles we have ST/PT = SR/QR. Let ST = `V0`:

- **Operator**: `Proportion V0 N1 N1 N0`

- This establishes $\frac{V0}{N1} = \frac{N1}{N0}$

2. QS is the sum of QR and RS. Let QS = `V1`:

- **Operator**: `Sum N0 N1 V1`

- Calculates $V1 = N0 + N1 = 2 + 3 = 5$

3. In △PQS, QT bisects ∠PQS, so PT/ST = PQ/QS:

> - **Operator**: Proportion N1 V0 N2 V1
>
> - Establishes $\frac{\text{N1}}{\text{V0}} = \frac{\text{N2}}{\text{V1}}$
>
> 4. Solve for PQ (N2):
>
>   - **Operator**: Get N2
>
>   - Retrieves the value of $\text{N2} = x$
>
> Final formal-language solution and parameters:
>
> `Proportion V0 N1 N1 N0 Sum N0 N1 V1`
>
> `Proportion N1 V0 N2 V1 Get N2`
>
> `N0=2 N1=3 N2=x`

D   Additional Implementation Details

D.1   Supervised Fine-tuning

Datasets. Supervised Fine-Tuning is performed on the formal-integrated CoT dataset synthesized from three geometry problem-solving benchmarks: PGPS9k, UniGeo, and Geo170k. The final dataset comprises 11,000 high-quality synthetic reasoning chains, with contributions of 5,000 from PGPS9k, 2,200 from UniGeo, and 3,800 from Geo170k.

Training Details. We fine-tune the Qwen-2.5-VL-7B-Instruct model implemented via LLaMA-Factory framework[9], running for 2 epochs on 4 NVIDIA A100 80GB GPUs. The key training parameters are as follows:

```
torchrun --nproc_per_node 4 src/train.py \
    --finetuning_type full \
    --do_train \
    --adam_beta2 0.95 \
    --model_name_or_path Qwen2.5-VL-7B-Instruct \
    --trust_remote_code \
    --preprocessing_num_workers 8 \
    --template qwen2_vl \
    --warmup_ratio 0.03 \
    --weight_decay 0.0 \
    --per_device_train_batch_size 8 \
    --gradient_accumulation_steps 4 \
    --gradient_checkpointing \
    --ddp_timeout 9000 \
    --learning_rate 2e-5 \
    --lr_scheduler_type cosine \
    --logging_steps 2 \
    --cutoff_len 4096 \
    --num_train_epochs 2 \
    --bf16 \
    --seed 42 \
    --flash_attn fa2 \
```

Compute Resources. The SFT stage runs using 4 NVIDIA A800-80GB GPUs. The training process completes in approximately 0.5 hours.

---

[9]https://github.com/hiyouga/LLaMA-Factory

D.2 Reinforcement Learning

Datasets. Reinforcement Learning is performed on 19.5k samples drawn from the training splits of three geometry problem-solving benchmarks: PGPS9k, UniGeo, and Geo170k. The distribution consists of 8k samples from PGPS9k, 3.5k from UniGeo, and 8k from Geo170k.

Training Details. This stage builds upon the model initialized from supervised fine-tuning. We employ the GRPO algorithm (Shao et al., 2024) implemented in the verl framework[10]. We run for 15 epochs on 8 NVIDIA H20 96GB GPUs. Key hyperparameters configured as follows:

```
python3 -m verl.trainer.main_ppo \
    algorithm.adv_estimator=grpo \
    data.train_batch_size=256 \
    data.max_prompt_length=2048 \
    data.max_response_length=1024 \
    data.val_batch_size=5120 \
    data.filter_overlong_prompts=True \
    data.truncation='error' \
    data.image_key=images \
    actor_rollout_ref.model.path=$MODEL_PATH \
    actor_rollout_ref.actor.optim.lr=1e-6 \
    actor_rollout_ref.actor.optim.lr_warmup_steps=0 \
    actor_rollout_ref.actor.optim.weight_decay=0.0 \
    actor_rollout_ref.model.use_remove_padding=True \
    actor_rollout_ref.actor.ppo_mini_batch_size=64 \
    actor_rollout_ref.actor.ppo_micro_batch_size_per_gpu=16 \
    actor_rollout_ref.actor.use_kl_loss=True \
    actor_rollout_ref.actor.kl_loss_coef=0.0 \
    actor_rollout_ref.actor.kl_loss_type=low_var_kl \
    actor_rollout_ref.actor.entropy_coeff=0 \
    actor_rollout_ref.actor.clip_ratio_high=0.28 \
    actor_rollout_ref.model.enable_gradient_checkpointing=True \
    actor_rollout_ref.actor.fsdp_config.param_offload=False \
    actor_rollout_ref.actor.fsdp_config.optimizer_offload=False \
    actor_rollout_ref.rollout.log_prob_micro_batch_size_per_gpu=64 \
    actor_rollout_ref.rollout.tensor_model_parallel_size=1 \
    actor_rollout_ref.rollout.name=vllm \
    actor_rollout_ref.rollout.gpu_memory_utilization=0.8 \
    actor_rollout_ref.rollout.enable_chunked_prefill=False \
    actor_rollout_ref.rollout.enforce_eager=False \
    actor_rollout_ref.rollout.free_cache_engine=False \
    +actor_rollout_ref.rollout.enable_prefix_caching=True \
    actor_rollout_ref.rollout.n=$n_samples_per_prompt \
    actor_rollout_ref.rollout.temperature=1.0 \
    actor_rollout_ref.rollout.val_kwargs.temperature=0.0 \
    actor_rollout_ref.rollout.val_kwargs.n=1 \
    actor_rollout_ref.rollout.val_kwargs.do_sample=False \
    actor_rollout_ref.ref.log_prob_micro_batch_size_per_gpu=64 \
    actor_rollout_ref.ref.fsdp_config.param_offload=True \
    algorithm.kl_ctrl.kl_coef=0.0 \
    custom_reward_function.path=./verl/utils/reward_score/pgps9k.py \
    custom_reward_function.name=compute_score \
```

---

[10]https://github.com/volcengine/verl

```
trainer.val_before_train=True \
trainer.critic_warmup=0 \
trainer.n_gpus_per_node=8 \
trainer.nnodes=1 \
trainer.total_epochs=15 \
```

Compute Resources. The RL training runs using 8 NVIDIA H20-96GB GPUs. The training process completes in approximately 83 hours.