Unlabeled Abdominal Multi-organ Image Segmentation Based on Semi-supervised Adversarial Training Strategy

YuanKe Pan[*1], Jinxin Zhu[*1], Liyilei Su[*1], and Bingding Huang[✉1]

College of Big Data and Internet, Shenzhen Technology University, Shenzhen, 518188, China
[*] These authors contributed equally to this work
[✉]Corresponding author:`huangbingding@sztu.edu.cn`

Abstract. The unlabeled images are helpful to generalize segmentation models. To make full use of the unlabeled images, we develop a generator-discriminator training pipeline based on the EfficientSegNet, which has achieved the best performance and efficiency in previous FLARE 2021 challenge. For the generator, a coarse-to-fine strategy is used to produce segmentations of abdominal organs. Then the labeled image and the ground truth are applied to optimize the generator. The discriminator receives the original unlabeled image or the relevant noised image, together with their generated segmentation results to determine which segmentation is better for the unlabeled image. After the adversarial training, the generator is used to segment the unlabeled images. On the FLARE 2022 validation dataset, our method achieved an average Dice Similarity Coefficient (DSC) of 0.840 and a Normalized Surface Dice (NSD) of 0.872 with an average process time of 11.6 seconds per case in the inference phase. The source code is freely available at https://github.com/Yuanke-Pan/Adversarial-EfficientSegNet.

Keywords: Unlabeled image segmentation · Semi-supervised learning · Adverarial training

1 Introduction

The lack of labeled images is a great burden in medical imaging tasks. In the past five years, there are many researches [1,9,11] show the potential of semi-supervised algorithms in medical applications. In this paper, we focus on building an abdominal multi-organ segmentation model with only 50 labeled and 2000 unlabeled abdominal CT scans. There are two main difficulties in this task: 1) how to use those 2000 unlabeled CT scans to obtain more generalized results. 2) how to keep GPU memory and computation cost at a low level.

The EfficientSegNet [10] has shown excellent performance and efficiency in FLARE 2021 challenge. The basic idea of our method is inheriting the network architecture of EfficientSegNet and applying semi-supervised learning algorithms to improve the generalizability of the inference model. In this work, we propose

a novel adversarial strategy to use the unlabeled CT images which can improve the segmentation results. The main contributions of this work are:

1. We propose an adversarial semi-supervised learning pipeline for segmentation of medical images.
2. We design an image-label fusion discriminator to make full use of unlabeled images.

2   Method

2.1   Preprocessing

We use the same preprocessing strategy in both training and prediction. The details are described as follows:

- Reorienting the images to the left-posterior-inferior (LPI) view by flipping and reordering.
- Resampling the images to the fixed sizes. The sizes of coarse and fine input are [160, 160, 160] and [192, 192, 192], respectively.

  For labeled images, we implement the following preprocessing steps:

- Reorienting the masks to the LPI view by flipping and reordering.
- Cropping the images according to the masks with a margin of [20, 20, 20].

2.2   Proposed Method

In this work, we combined efficient context-aware network as generator and image-label fusion discriminator to make cross learning between labeled CT images and unlabeled images. The whole workflow of our method is illustrated in Fig. 1,

The training phase of our proposed adversarial semi-supervise learning workflow consists of three steps in every iterations:

- In step 1, we use the generator to produce segmentation result of the original image. Then we train the discriminator with the original image, the generated segmentation and the ground truth. Here we assume that the ground truth is always the best segmentation of the original image.
- In step 2, we train the generator with original image and the ground truth as supervised learning.
- In step 3, we first add the Gaussian noise to the unlabeled image to get the relevant noised image. Then we input the unlabeled image and the noised image into the generator to produce segmentation-Unlabeled and segmentation-Noised, respectively. After that, we input the unlabeled image and the noised image separately with the two generated segmentation results (segmentation-Unlabeled and segmentation-Noised) into the discriminator to determine which segmentation is better. The better segmentation will be used as the pseudo label and will be used to train the generator.

Fig. 1. The whole workflow of our proposed method.

It is important to emphasize that for the first 50 and the last 50 training iterations, we only use step 2 to fine-tune the network. After the training process, the final generator is used to segment the unlabeled images.

Generator For the coarse-to-fine training strategy, there are two different networks to extract global and local information. The coarse model is a typical 5-layer U-net structure which is employed to locate target organs. The fine model is the EfficientSegNet shown in Fig. 2, which receives the coarse segmentation results from the coarse model for further refinement.

Discriminator The input of the discriminator includes the original image and two segmentation results. For the labeled images, these two segmentation results are the generated segmentation and the ground truth. For the unlabeled images, these two segmentation results are derived from the unlabeled image and the relevant noised unlabeled image. The discriminator is used to decide which segmentation is better for the original image.

As shown in Fig. 3, the image-label fusion discriminator fuses the original image with the two segmentation labels to output which label is better.

Optional Operation In order to improve the discriminator's performance, we apply an augmentation to the ground truth called mask poisoning. This

Fig. 2. The architecture of the fine network in the generator.

Fig. 3. The architecture of the discriminator network.

augmentation step adds a random noise to the ground truth, which can make the discriminator more concentrate on the data distribution.

Accelerate strategy The same as the EfficientSegNet, the anisotropic convolution, anisotropic pooling and coarse-to-fine strategy are used to reduce inference time and GPU memory usage.

2.3 Post-processing

In the last step of the coarse-to-fine model, we apply a connected components analysis [7] to get the final segmentation results.

3   Experiments

3.1 Dataset and evaluation metrics

The FLARE 2022 dataset is curated from more than 20 medical groups under the license permission, including MSD [8], KiTS [3,4], AbdomenCT-1K [6], and TCIA [2]. The training set includes 50 labeled CT scans with pancreas disease and 2000 unlabeled CT scans with liver, kidney, spleen, or pancreas diseases. The validation dataset includes 50 CT scans with liver, kidney, spleen, or pancreas diseases. The test dataset includes 200 CT scans where 100 cases with liver, kidney, spleen, or pancreas diseases and the other 100 cases with uterine corpus endometrial, urothelial bladder, stomach, sarcomas, or ovarian diseases. All the CT scans only have image information and the center information is not available.

   The evaluation metrics are two accuracy measurements: Dice Similarity Coefficient (DSC) and Normalized Surface Dice (NSD), and three running efficiency measurements: running time, area under GPU memory-time curve, and area under CPU utilization-time curve. All measurements will be used to compute the ranking. Moreover, the GPU memory consumption has a tolerance of 2 GB.

3.2 Implementation details

Environment settings The development environments and requirements are shown in Table 1.

Training protocols During the training process, we apply random shift and brightness to the whole dataset, and Gaussian noise to the unlabeled images. The details of the training protocols are shown in Table 2 and Table 3.

4   Results and discussion

4.1 Performance

We compare our proposed method with the baseline model. The evaluation results are shown in Table 4.

Table 1. Development environments and requirements.

Windows/Ubuntu version	Ubuntu 20.04.1 LTS
CPU	AMD EPYC 7742 64-Core Processor
RAM	16×4GB
GPU	coarse: 2*NVIDIA A100 40G
	refine: 4*NVIDIA A100 40G
CUDA version	11.2
Programming language	Python 3.9
Deep learning framework	Pytorch (Torch 1.11, torchvision 0.12.0)

Table 2. Training protocols for the coarse model.

Network initialization	"he" normal initialization
Batch size	Labelled data: 4
	UnLabelled data: 2
Patch size	160×160×160
Total epochs	300
Optimizer	Adam ($\mu = 0.99$)
Initial learning rate (lr)	0.001
Lr decay schedule	halved by 200 epochs
Training time	6 hours
Loss function	$\mathbf{L} = 1 - \frac{2*\sum p_{\text{true}} * p_{\text{pred}}}{\sum p_{\text{true}}^2 + \sum p_{\text{pred}}^2}$

Table 3. Training protocols for the fine model.

Network initialization	"he" normal initialization
Batch size	Labelled data: 8
	UnLabelled data: 4
Patch size	192×192×192
Total epochs	500
Optimizer	Adam ($\mu = 0.99$)
Initial learning rate (lr)	0.001
lr decay schedule	halved by 200 epochs
Training time	3.4 hours
Loss function	$\mathbf{L} = 1 - \frac{2*\sum p_{\text{true}} * p_{\text{pred}}}{\sum p_{\text{true}}^2 + \sum p_{\text{pred}}^2}$

Table 4. Evaluation Results of baseline and baseline+SS (semi-supervised).

	Baseline		Baseline+SS	
Organ	DSC	NSD	DSC	NSD
Liver	0.936	0.915	0.961	0.955
RK	0.818	0.796	0.838	0.815
Spleen	0.920	0.899	0.941	0.932
Pancreas	0.762	0.848	0.816	0.892
Aorta	0.945	0.977	0.958	0.986
IVC	0.835	0.825	0.891	0.892
RAG	0.709	0.820	0.660	0.745
LAG	0.709	0.798	0.821	0.900
Gallbladder	0.676	0.658	0.753	0.751
Esophagus	0.798	0.884	0.806	0.877
Stomach	0.731	0.752	0.864	0.883
Duodenum	0.675	0.829	0.718	0.811
LK	0.889	0.879	0.893	0.893
Average	0.800	0.837	0.840	0.872

4.2   Qualitative results on the validation dataset

In the case of comparison with the ground truth, Fig. 4 and Fig. 5 show two examples with good segmentation results and two examples with poor segmentation results, respectively. For all 20 cases in the validation dataset, the average of DSC and NSD of our model are 0.840 and 0.872, respectively. The average DSC and NSD of NO.6 and NO.21 are 0.942, 0.942 and 0.949, 0.986, respectively. On the other hand, NO.47 and NO.48 show poor performance with their average DSC and NSD are 0.694, 0.699 and 0.635, 0.656, respectively. At the same time, we observe that the segmentation results of our proposed model on Right Adrenal Gland (RAG) is the worst in all organs, with the average DSC and average NSD of 0.660 and 0.745, respectively. One reason may be that there are too many organs around it.

4.3   Limitation and future work

In our work, we separate the training pipeline into three steps. In each step, the parameters of the discriminator and the generator are not updated at the same time, it might cost additional training time. An end-to-end semi-supervised learning algorithm will be our goal in the future. Due to the time limitations, we do not find a way to perform the proper analysis of the dataset. Considering the success of nn-UNet[5], we believe that a proper analysis might improve our final segmentation results.

Fig. 4. Comparison of 3D segmentation in two good segmentation results (FLARETs_0006 and FLARETs_0021) and two poor segmentation results (FLARETs_0047 and FLARETs_0048).

Fig. 5. Comparison of section segmentation of a layer in two good segmentation results (FLARETs_0006 and FLARETs_0021) and two poor segmentation results (FLARETs_0047 and FLARETs_0048).

Table 5. DSC of each organ in the two good segmentation results (NO.6 and NO.21) and two poor segmentation results (NO.47 and NO.48).

Organ	NO.6	NO.21	NO.47	NO.48
Liver	0.983	0.978	0.917	0.860
RK	0.979	0.978	0.984	0.738
Spleen	0.986	0.989	0.769	0.613
Pancreas	0.894	0.927	0.700	0.800
Aorta	0.976	0.972	0.938	0.828
IVC	0.970	0.951	0.734	0.523
RAG	0.898	0.807	0.000	0.788
LAG	0.926	0.888	0.860	0.921
Gallbladder	1.000	1.000	0.557	0.000
Esophagus	0.907	0.951	0.841	0.260
Stomach	0.938	0.977	0.734	0.297
Duodenum	0.826	0.939	0.000	0.708
LK	0.968	0.986	0.984	0.920
Average	0.942	0.949	0.694	0.635

Table 6. NSD of each organ in the two good segmentation results (NO.6 and NO.21) and two poor segmentation results (NO.47 and NO.48).

Organ	NO.6	NO.21	NO.47	NO.48
Liver	0.982	0.991	0.812	0.781
RK	0.988	0.986	0.998	0.658
Spleen	0.989	1.000	0.638	0.510
Pancreas	0.947	0.991	0.758	0.851
Aorta	0.998	0.999	0.988	0.850
IVC	0.996	0.962	0.688	0.581
RAG	0.968	0.918	0.000	0.888
LAG	0.989	0.972	0.944	0.984
Gallbladder	1.000	1.000	0.610	0.000
Esophagus	0.988	1.000	0.892	0.335
Stomach	0.948	0.999	0.772	0.373
Duodenum	0.871	0.999	0.001	0.836
LK	0.934	0.998	0.985	0.876
Average	0.969	0.986	0.699	0.656

5   Conclusion

In this paper, in order to use the large amount of unlabeled data, we develop an adversarial generator-discriminator training pipeline based on the EfficientSeg-Net. For the generator, we employ the coarse-to-fine strategy to generate segmentation results. The labeled images and their ground truth are used to optimize the generator. For the discriminator, we first add noise to the original unlabeled images, then the discriminator receives the original unlabeled image or the relevant noised image together with their generated segmentation results. The better segmentation is determined by the discriminator as the pseudo label of the unlabeled image. On the FLARE 2022 validation dataset, our method achieved an average DSC of 0.840 and a NSD of 0.872 with an average process time of 11.6 seconds per case in the inference phase.

Acknowledgements The authors of this paper declare that the segmentation method implemented for participation in the FLARE 2022 challenge has not used any pre-trained models nor additional datasets other than those provided by the organizers. The proposed solution is fully automatic without any manual intervention.

References

1. Chen, X., Yuan, Y., Zeng, G., Wang, J.: Semi-supervised semantic segmentation with cross pseudo supervision. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 2613–2622 (2021) 1
2. Clark, K., Vendt, B., Smith, K., Freymann, J., Kirby, J., Koppel, P., Moore, S., Phillips, S., Maffitt, D., Pringle, M., et al.: The cancer imaging archive (tcia): maintaining and operating a public information repository. Journal of Digital Imaging **26**(6), 1045–1057 (2013) 5
3. Heller, N., Isensee, F., Maier-Hein, K.H., Hou, X., Xie, C., Li, F., Nan, Y., Mu, G., Lin, Z., Han, M., et al.: The state of the art in kidney and kidney tumor segmentation in contrast-enhanced ct imaging: Results of the kits19 challenge. Medical Image Analysis **67**, 101821 (2021) 5
4. Heller, N., McSweeney, S., Peterson, M.T., Peterson, S., Rickman, J., Stai, B., Tejpaul, R., Oestreich, M., Blake, P., Rosenberg, J., et al.: An international challenge to use artificial intelligence to define the state-of-the-art in kidney and kidney tumor segmentation in ct imaging. American Society of Clinical Oncology **38**(6), 626–626 (2020) 5
5. Isensee, F., Petersen, J., Klein, A., Zimmerer, D., Jaeger, P.F., Kohl, S., Wasserthal, J., Koehler, G., Norajitra, T., Wirkert, S., et al.: nnu-net: Self-adapting framework for u-net-based medical image segmentation. arXiv preprint arXiv:1809.10486 (2018) 7
6. Ma, J., Zhang, Y., Gu, S., Zhu, C., Ge, C., Zhang, Y., An, X., Wang, C., Wang, Q., Liu, X., Cao, S., Zhang, Q., Liu, S., Wang, Y., Li, Y., He, J., Yang, X.: Abdomenct-1k: Is abdominal organ segmentation a solved problem? IEEE Transactions on Pattern Analysis and Machine Intelligence (2021). https://doi.org/10.1109/TPAMI.2021.3100536 5

7. Silversmith, W.: connected-components-3d 3.10. 0 5

8. Simpson, A.L., Antonelli, M., Bakas, S., Bilello, M., Farahani, K., Van Ginneken, B., Kopp-Schneider, A., Landman, B.A., Litjens, G., Menze, B., et al.: A large annotated medical image dataset for the development and evaluation of segmentation algorithms. arXiv preprint arXiv:1902.09063 (2019) 5

9. Tarvainen, A., Valpola, H.: Mean teachers are better role models: Weight-averaged consistency targets improve semi-supervised deep learning results. Advances in neural information processing systems **30** (2017) 1

10. Zhang, F., Wang, Y.: Efficient context-aware network for abdominal multi-organ segmentation. ArXiv **abs/2109.10601** (2021) 1

11. Zhang, Y., Yang, L., Chen, J., Fredericksen, M., Hughes, D.P., Chen, D.Z.: Deep adversarial networks for biomedical image segmentation utilizing unannotated images. In: Descoteaux, M., Maier-Hein, L., Franz, A., Jannin, P., Collins, D.L., Duchesne, S. (eds.) Medical Image Computing and Computer Assisted Intervention MICCAI 2017. pp. 408–416. Springer International Publishing, Cham (2017) 1