# LEARNING CONTINUOUS NORMALIZING FLOWS FOR FASTER CONVERGENCE TO TARGET DISTRIBUTION VIA ASCENT REGULARIZATIONS

## ABSTRACT

Normalizing flows (NFs) have been shown to be advantageous in modeling complex distributions and improving sampling efficiency for unbiased sampling. In this work, we propose a new class of continuous NFs, ascent continuous normalizing flows (ACNFs), that makes a base distribution converge faster to a target distribution. Although solving such a flow is non-trivial and barely possible, we propose a practical implementation to learn flexibly parametric ACNFs via ascent regularization and apply in two learning cases: maximum likelihood learning for density estimation and minimizing reverse KL divergence for unbiased sampling and variational inference. The learned ACNFs demonstrate faster convergence towards the target distributions, therefore, achieving better density estimations, unbiased sampling and variational approximation at lower computational cost. Furthermore, the flows show to stabilize themselves to mitigate performance deterioration and are less sensitive to the choice of training flow length $T$.

## 1 INTRODUCTION

Normalizing flows (NFs) provide a flexible way to define an expressive but tractable distribution which only requires a base distribution and a chain of bijective transformations (Papamakarios et al., 2021). Neural ODE (Chen et al., 2018) extends discrete normalizing flows (Dinh et al., 2014; 2016; Papamakarios et al., 2017; Ho et al., 2019) to a new continuous-time analogue by defining the transformation via a differential equation, substantially expanding model flexibility in comparison to the discrete alternatives. (Grathwohl et al., 2018; Chen and Duvenaud, 2019) proposes a computationally cheaper way to estimate the trace of Jacobian to accelerate training, while other methods focus on increasing flow expressiveness by e.g. augmenting with additional states (Dupont et al., 2019; Massaroli et al., 2020), or adding stochastic layers between discrete NFs to alleviate the topological constraint (Wu et al., 2020). Recent diffusion models like (Hodgkinson et al., 2020; Ho et al., 2020; Song et al., 2020; Zhang and Chen, 2021) extend the scope of continuous normalizing flows (CNFs) with stochastic differential equations (SDEs). Although these diffusion models significantly improve the quality of the generated samples, introduced diffusion comes with a cost: some models do not allow for tractable density estimation; or the practical implementations of these models rely on a long chain of discretizations, thus needing relatively more computations compared to tractable CNF methods, which can be critical for some use cases such as online inference.

(Finlay et al., 2020; Onken et al., 2021; Kelly et al., 2020; Yang and Karniadakis, 2020) introduce several regularizations to learn simpler dynamics using optimal transport theory, which decrease the number of discretization steps in integration and thus reduce training time. (Kelly et al., 2020) extends the $L_2$ transport cost to regularize any arbitrary order of dynamics. Although these regularizations are beneficial for decreasing computational costs, it does not improve the slow convergence of density to the target distributions like vanilla CNF models shown in Figure 1. To accelerate the flow convergence, STEER (Ghosh et al., 2020) and TO-FLOW (Du et al., 2022) propose to optimize flow length $T$ in two different approaches: STEER randomly samples the length during training while TO-FLOW establishes a subproblem for $T$ to optimize during training. To understand the effectiveness of these methods, we train multiple Neural ODE models with different flow length $T_n$ for a 2-moon distribution. Figure 2 shows the estimated log-likelihoods of all learned flows. Although optimizing $T$ dynamically performs model selection during training and encourages flows to converge

Figure 1: Distribution transformations of two learned flows for 1d Gaussian mixture from a Gaussian distribution at multiple $t \in [0, 4T]$. Although the two flows have similar densities at $T$, the density of ACNF converges faster to the target distribution before $T$ and diverges slower after $T$ than that of CNF. Color indicates the density of true Gaussian mixture.

Figure 2: The log-likelihood estimates of trained vanilla CNF models with various flow length $T_n$ and steepest ACNF with dynamics defined in eq.(6) at different $t$ on 2-moon distribution. All vanilla CNF models reach their maximum around $T_n$ and deteriorate rapidly afterwards while the log-likelihood estimate of ACNF elevates rapidly at initial and increases monotonically.

faster to the target, both methods cannot prevent the divergence of flows after $T_n$. Furthermore, shorter length flows are more limited in expressiveness and sensitive to integration length.

In this work, we present a new family of CNFs, ascent continuous normalizing flows (ACNFs), to address the aforementioned questions. ACNF concerns a flow that makes a base distribution monotonically converge to a target distribution, and the dynamics of the steepest ACNF is derived. Although solving such a steepest flow is non-trivial and barely possible, we propose a practical implementation to learn parametric ACNFs via ascent regularization. The learned ACNFs exhibit three main distinct behaviors: 1) faster convergence to target distribution with less computation; 2) self-stabilization to mitigate flow deterioration; and 3) insensitivity to flow training length $T$. We demonstrate the beneficial behaviors in three use cases: modeling data distributions; learning annealed samplers for unbiased sampling; and learning a tractable but more flexible variational approximation.

## 2 CONTINUOUS NORMALIZING FLOWS

Considering a time-$t$ transformation $\mathbf{z}(t) = \mathbf{\Phi}_t(\mathbf{x})$ on the initial value $\mathbf{x}$, i.e. $\mathbf{z}(0) = \mathbf{x}$, the change of variable theorem reveals the relation between the transformed distribution $p_t(\mathbf{z}(t))$ and $p(\mathbf{x})$:

$$p_t(\mathbf{z}(t)) = \left| \det\left( \mathcal{J}_{\mathbf{\Phi}_t}^{-1}(\mathbf{x}) \right) \right| p(\mathbf{x}), \tag{1}$$

where $\mathcal{J}_{\mathbf{\Phi}}$ is the Jacobian matrix of the transformation $\mathbf{\Phi}$. As transformation $\mathbf{\Phi}_t$ normalizes $\mathbf{x}$ towards some base distribution, $p_t(\mathbf{z}(t))$ is commonly referred as normalized distribution, starting from $p(\mathbf{x})$.

Continuous normalizing flow is the infinitesimal limit of the chain of discrete flows and the infinitesimal transformation is an ordinary differential equation (ODE):

$$\frac{\mathrm{d}\mathbf{z}(t)}{\mathrm{d}t} = \frac{\mathrm{d}\mathbf{\Phi}_t(\mathbf{x})}{\mathrm{d}t} = \mathbf{f}(\mathbf{z}(t), t). \tag{2}$$

The instantaneous change of variable theorem (Chen et al., 2018, theorem 1) gives the total derivative of $\log p_t(\mathbf{z}(t))$:

$$\frac{\mathrm{d}\log p_t(\mathbf{z}(t))}{\mathrm{d}t} = -\boldsymbol{\nabla} \cdot \mathbf{f}(\mathbf{z}(t), t). \tag{3}$$

Commonly, we assume the normalized distribution at $T$ to be the base distribution, i.e. $p_T \approx \mu$. $\log p_t(\mathbf{z}(t))$ at $t$ can be integrated using solution $\mathbf{z}(T)$:

$$\mathbf{z}(t) = \mathbf{x} + \int_0^t \mathbf{f}(\mathbf{z}(\tau), \tau)\mathrm{d}\tau, \quad \log p_t(\mathbf{z}(t)) \approx \log\mu(\mathbf{z}(T)) - \int_t^T \boldsymbol{\nabla} \cdot \mathbf{f}(\mathbf{z}(\tau), \tau)\mathrm{d}\tau.$$

Figure 3: Upper: transformations on variables and densities on normalization and sampling directions. Lower left: data samples (orange) and the grid of states (blue) transformations along normalization direction. Lower right: density estimation $\tilde{p}_t$ along sampling direction.

The accuracy of $\log p_0(\mathbf{z}(0))$, obtained via the integral on the right hand side, depends on the approximation error of $p_T$ to $\mu$ and the error is not explicitly quantified. Besides, when $\log p_t(\mathbf{z}(t))$ at any $t$ other than $0$ is interested, it still requires to solve the whole trajectory $\mathbf{z}(t), t \in [0, T]$. To avoid these problems and enable better discussion on flow length for the modeled distribution, we present time-$t$ estimated likelihood, $\tilde{p}_t(\mathbf{x})$, defined via the change of variable theorem:

$$\tilde{p}_t(\mathbf{x}) = \left| \det \left( \mathcal{J}_{\mathbf{\Phi}_t}(\mathbf{x}) \right) \right| \mu(\mathbf{\Phi}_t(\mathbf{x})), \tag{4}$$

which initiates from the base distribution, i.e. $\tilde{p}_0(\mathbf{x}) = \mu(\mathbf{\Phi}_0(\mathbf{x})) = \mu(\mathbf{x})$. $\tilde{p}_t(\mathbf{x})$ is the estimation of the true data distribution $p(\mathbf{x})$ by a flow $\mathbf{\Phi}_t$ of length $t$. See Figure 3 for the summary of transformations on variables and densities on both normalization and generation directions. Combining eq.(4) and eq.(1), the estimated likelihood of time-$t$ flow is related to the normalized distribution $p_t(\mathbf{z}(t))$:

$$\frac{\tilde{p}_t(\mathbf{x})}{p(\mathbf{x})} = \frac{\mu(\mathbf{\Phi}_t(\mathbf{x}))}{p_t(\mathbf{\Phi}_t(\mathbf{x}))} = \frac{\mu(\mathbf{z}(t))}{p_t(\mathbf{z}(t))}.$$

It shows that as $p_t \to \mu$, $\tilde{p}_t(\mathbf{x}) \to p(\mathbf{x})$. If there exists a flow, of which the normalized density at length of $T$ is equal to the base distribution, i.e. $p_T = \mu$, then the estimated likelihood of time-$T$ flow is exact to the true data distribution $p(\mathbf{x})$. Like the instantaneous change of variable theorem, we can derive the infinitesimal change of time-$t$ estimated log-likelihood:

**Proposition 1** (Instantaneous Change of Log-likelihood Estimate). *Let $\mathbf{z}(t)$ be a finite continuous random variable at time $t$ as the solution of a differential equation $\frac{d\mathbf{z}(t)}{dt} = \mathbf{f}(\mathbf{z}(t), t)$ with initial value $\mathbf{z}(0) = \mathbf{x}$. Assuming that $\tilde{p}_0 = \mu$ at $t = 0$ and $\mathbf{f}$ is uniformly Lipschitz continuous in $\mathbf{z}$ and $t$, then the change in estimated log-likelihood $\log \tilde{p}_t(\mathbf{x})$ at $t$ follows a differential equation:*

$$\frac{d \log \tilde{p}_t(\mathbf{x})}{dt} = \mathbf{\nabla} \cdot \mathbf{f}(\mathbf{z}(t), t) + \nabla \log \mu(\mathbf{z}(t)) \cdot \mathbf{f}(\mathbf{z}(t), t). \tag{5}$$

*Proof.* See Appendix A.1 for derivation and its relation to eq.(3). Therefore, density of $\mathbf{x}$ at any or/and multiple $t$ can be evaluated by one single integral augmented with $\mathbf{z}$:

$$\log \tilde{p}_t(\mathbf{x}) = \log \mu(\mathbf{x}) + \int_0^t \left( \mathbf{\nabla} \cdot \mathbf{f}(\mathbf{z}(\tau), \tau) + \nabla \log \mu(\mathbf{z}(\tau)) \cdot \mathbf{f}(\mathbf{z}(\tau), \tau) \right) d\tau.$$

## 3 ASCENT CONTINUOUS NORMALIZING FLOWS

Using KL divergence as distance measure of distributions, we have the following duality:

$$\mathrm{KL}(p(\mathbf{x})||\tilde{p}_t(\mathbf{x})) = \mathrm{const} - \int p(\mathbf{x}) \log \tilde{p}_t(\mathbf{x}) d\mathbf{x} = \mathrm{KL}(p_t(\mathbf{z}(t))||\mu(\mathbf{z}(t))),$$

so that maximum likelihood learning to fit $\tilde{p}_t(\mathbf{x})$ for data from $p(\mathbf{x})$ is equivalent to minimizing the reverse KL divergence in normalization direction. Besides, we can quantify the convergence rate of estimate to true data distribution or normalized distribution to base distribution by the time derivative of KL divergence. Therefore, we define ascent continuous normalizing flows (ACNF) that decrease $\mathrm{KL}(p_t(\mathbf{z}(t))||\mu(\mathbf{z}(t)))$ or equivalently increase the expectation of $\log \tilde{p}_t(\mathbf{x})$ monotonically:

$$\frac{\partial}{\partial t} \int p(\mathbf{x}) \log \tilde{p}_t(\mathbf{x}) d\mathbf{x} \geq 0; \text{ or } \frac{\partial}{\partial t} \mathrm{KL}(p_t(\mathbf{z}(t))||\mu(\mathbf{z}(t))) \leq 0.$$

Applying total variation, we can find the dynamics for the steepest ascent of the log-likelihood expectation or the descent of reverse KL divergence:

**Theorem 1** (Dynamics for Steepest Ascent Continuous Normalizing Flows). *Let $\mathbf{z}(t)$ be a finite continuous random variable and the solution of a differential equation $\frac{d\mathbf{z}(t)}{dt} = \mathbf{f}(\mathbf{z}(t), t)$ with initial value $\mathbf{z}(0) = \mathbf{x}$. Its probability $p_t(\mathbf{z}(t))$ subjects to the continuity equation $\partial_t p_t + \boldsymbol{\nabla} \cdot (p_t \mathbf{f}) = 0$. The dynamics of the steepest flow for decreasing $KL(p_t(\mathbf{z}(t)) \| \mu(\mathbf{z}(t)))$ is*

$$\mathbf{f}^*(\mathbf{z}(t), t) = \nabla \log \mu(\mathbf{z}(t)) - \frac{\nabla p_t(\mathbf{z}(t))}{p_t(\mathbf{z}(t))} = \nabla \log \mu(\mathbf{z}(t)) - \nabla \log p_t(\mathbf{z}(t)). \tag{6}$$

*Proof.* See Appendix A.2 for detailed derivation. The convergence rate of the steepest flow can also be proved to be negative Fisher divergence, $\partial KL(p_t \| \mu) / \partial t = -\mathbb{F}(p_t \| \mu) = -\mathbb{E}_{p_t} \| \nabla \log \mu(\mathbf{z}) - \log p_t(\mathbf{z}) \|_2^2$, therefore this deterministic CNF is related to (overdamped) Langevin diffusion, see Appendix A.3 for the derivation of convergence rate and detailed discussion of their relation.

The steepest dynamics is defined by the difference between two gradients: $\nabla \log \mu$ and $\nabla \log p_t$ w.r.t. $\mathbf{z}(t)$. There are a few important implications of eq.(6): 1) the dynamics is time-variant as $p_t$ simultaneously evolves with the flow; 2) at time $t$, it only depends on the current state $\mathbf{z}(t)$, thus no history needs to be saved; 3) the flow is initiated by the gradient difference between $\log \mu(\mathbf{x})$ and $\log p(\mathbf{x})$, and it gradually slows down and eventually stops when $p_t(\mathbf{z}(t))$ converges to $\mu(\mathbf{z}(t))$.

This optimal flow can also be considered as a special instance of Wasserstein gradient flow (Ambrosio et al., 2005) with KL divergence as the energy functional. Several previous works (Finlay et al., 2020; Yang and Karniadakis, 2020; Onken et al., 2021) apply the optimal transport theory to regularize flow dynamics from Euclidean space perspective, while Wasserstein gradient flow instead regularizes it in some probability measure space. We refer readers to (Ambrosio et al., 2005) for accessible introduction. In some cases, this Wasserstein gradient flow can be solved indirectly by introducing a variable potential, $V(\mathbf{z}(t), t) = p_t(\mathbf{z}(t)) / \mu(\mathbf{z}(t))$, and it has a partial differential equation (PDE):

$$\frac{\partial V(\mathbf{z}, t)}{\partial t} = \Delta V(\mathbf{z}, t) + 2 \nabla \log \mu(\mathbf{z}) \cdot \nabla V(\mathbf{z}, t) + \nabla \log V(\mathbf{z}, t) \cdot \nabla V(\mathbf{z}, t), \tag{7}$$

with the initial condition $V(\mathbf{z}(0), 0) = \frac{p_0(\mathbf{z}(0))}{\mu(\mathbf{z}(0))} = \frac{p(\mathbf{x})}{\mu(\mathbf{x})}$. See Appendix A.4 for its derivation. However, solving this PDE is non-trivial since the closed form solution is typically unknown and approximation on the dynamics of density $p_t$, e.g. using JKO integration to approximate, is needed (Mokrov et al., 2021; Fan et al., 2021). Furthermore, the initial condition requires to know $p(\mathbf{x})$, which is generally unavailable and needs to be modeled from samples, or approximate it via spatial discretization of samples (Tabak and Vanden-Eijnden, 2010), which can hardly scale up well for high dimensional problems. To tackle these difficulties, we introduce a practical implementation to learn a parametric ACNF via ascent regularization for two important learning cases: maximum likelihood learning for data modeling and density estimation in Section 4; minimizing reverse KL divergence for learning annealed sampler for unbiased sampling in Section 5.

Before we are able to compute the ascent regularization, we need to know score function in eq.(6). We propose the instantaneous change of the score function, $\nabla \log p_t(\mathbf{z}(t))$ as:

**Theorem 2** (Instantaneous Change of Score Function). *Let $\mathbf{z}(t)$ be a finite continuous random variable with probability density $p_t(\mathbf{z}(t))$ at time $t$. Let $\frac{d\mathbf{z}(t)}{dt} = \mathbf{f}(\mathbf{z}(t), t)$ be a differential equation describing a continuous-in-time transformation of $\mathbf{z}(t)$. Assuming that $\mathbf{f}$ is uniformly Lipschitz continuous in $\mathbf{z}$ and $t$, the infinitesimal change in the gradient of log-density at $t$ is*

$$\frac{d\nabla \log p_t(\mathbf{z}(t))}{dt} = -\nabla \log p_t(\mathbf{z}(t)) \frac{\partial \mathbf{f}(\mathbf{z}(t), t)}{\partial \mathbf{z}(t)} - \nabla (\boldsymbol{\nabla} \cdot \mathbf{f}(\mathbf{z}(t), t)). \tag{8}$$

*Proof.* See Appendix A.5 for detailed derivation. $\nabla \log p(\mathbf{z}(t), t)$ follows a linear matrix differential equation, where the linear coefficient matrix is Jacobian and the bias term is the gradient of divergence. To be noted, this derivation is concurrently developed in (Lu et al., 2022, theorem D.1).

## 4 MAXIMUM LIKELIHOOD LEARNING OF ACNF FOR DENSITY ESTIMATION VIA ASCENT REGULARIZATION

Inspired by previous works (Yang and Karniadakis, 2020; Onken et al., 2021; Finlay et al., 2020; Kelly et al., 2020; Ghosh et al., 2020) that encourage certain behaviors of flows via regularization in

**Algorithm 1** Maximum likelihood learning of ACNF with ascent regularization

**Require:** Data samples $\mathbf{X} = \{\mathbf{x}_j\}_{j=1,\ldots,N}$, parameteric dynamics of flow $\mathbf{f}_{\boldsymbol{\theta}}$, length of flow $T$, ascent regularization coefficient $\lambda$, base distribution $\mu$
  **Initialize $\boldsymbol{\theta}$**
  **while** $\boldsymbol{\theta}$ is not converged **do**
      Sample a mini-batch of data $\mathbf{x}^i \sim \mathbf{X}$
      Integrate augmented states
$[\mathbf{z}^i(t), \log \tilde{p}_t(\mathbf{x}^i)]$ forward with initial value $[\mathbf{x}^i, \mathbf{0}]$ from 0 to $T$
      Integrate augmented states
$[\mathbf{z}^i(t), \nabla \log p_t(\mathbf{z}^i(t))]$ backwards with initial value $[\mathbf{z}^i(T), \nabla \log \mu(\mathbf{z}^i(T))]$ from $T$ to 0
      Compute loss function $\mathcal{L}$ in eq.(9) and $\nabla_{\boldsymbol{\theta}}\mathcal{L}$ by adjoint sensitivity method
      Update $\boldsymbol{\theta}$ by gradient descent algorithm
  **end while**

**Algorithm 2** Training ACNF as annealed sampler for unbiased sampling with ascent regularization

**Require:** target distribution $\pi = \gamma/Z$, parameteric dynamics of flow $\mathbf{f}_{\boldsymbol{\theta}}$, length of flow $T$, number of samples $N$, ascent regularization coefficient $\lambda$, base distribution $\mu$
  **Initialize $\boldsymbol{\theta}$**
  **while** $\boldsymbol{\theta}$ is not converged **do**
      Sample $\mathbf{z}_0^i \sim p_0 = \mu$
      Evaluate $\log \mu(\mathbf{z}_0^i)$ and $\nabla \log \mu(\mathbf{z}_0^i)$
      Integrate augmented states
$[\mathbf{z}^i(t), \log p_t(\mathbf{z}^i(t)), \nabla \log p_t(\mathbf{z}^i(t))]$ with initial value $[\mathbf{z}_0^i, \log \mu(\mathbf{z}_0^i), \nabla \log \mu(\mathbf{z}_0^i)]$ from 0 to $T$
      Evaluate
$\log w(\mathbf{z}^i(T)) = \log \gamma(\mathbf{z}^i(T)) - \log p_T(\mathbf{z}^i(T))$
      Compute loss function $\mathcal{L}$ in eq.(10) and $\nabla_{\boldsymbol{\theta}}\mathcal{L}$ by adjoint sensitivity method
      Update $\boldsymbol{\theta}$ by gradient descent algorithm
  **end while**

training, we propose ascent regularization to learn parametric ACNFs which penalizes the difference between the parameteric dynamics $\mathbf{f}_{\boldsymbol{\theta}}$ and the steepest dynamics as derived in eq.(6). Therefore, the total objective for maximum likelihood learning on data becomes:

$$\min_{\mathbf{f}} \mathcal{L} = \frac{1}{N} \sum_{i=1}^{N} \left( -\log \tilde{p}_T(\mathbf{x}^i; \boldsymbol{\theta}) + \lambda \int_0^T \| \left( \nabla \log p_t(\mathbf{z}^i(t); \boldsymbol{\theta}) - \nabla \log \mu(\mathbf{z}^i(t)) \right) + \mathbf{f}(\mathbf{z}^i(t), t; \boldsymbol{\theta}) \|_2^2 \mathrm{d}t \right),$$
(9)

where $\lambda$ is an ascent regularization coefficient to control the trade-off between maximizing likelihood and regularization on the ascent behavior of the learned dynamics. When $\lambda = 0$, ACNF degrades to CNF. The first term in eq.(9) is obtained by integrating eq.(5) over $[0, T]$, simultaneously with $\mathbf{z}(t)$. The ascent regularization can be integrated backwards with augmented initial $[\mathbf{z}(T), \nabla \log \mu(\mathbf{z}(T))]$ as we assume the normalized distribution at $T$ is close to the base distribution, i.e. $\nabla \log p_T(\mathbf{z}(T)) \approx \nabla \log \mu(\mathbf{z}(T))$. We summarize pseudo-code for maximum likelihood learning of ACNFs in Algorithm 1. We also interpret ascent regularization as score matching objective in Section A.6 in Appendix, thus Algorithm 1 can be implemented in more efficient ways (Lu et al., 2022; Song et al., 2021).

## 5 LEARNING ACNF AS ANNEALED SAMPLER FOR UNBIASED SAMPLING

Except modeling data samples and performing density estimation, NF as a sampler has been found advantageous for Annealed Importance Sampling (AIS) (Neal, 2001) in terms of sample efficiency compared to classic MCMC methods. A typical AIS or its extension relies on a sequence of annealed targets $\{\pi_k\}_{k=0:K}$ that bridges an easy-to-sample and tractable distribution $\pi_0 = \mu$ to the target $\pi_K := \pi = \gamma(\cdot)/Z$. SNF (Wu et al., 2020) and AFT (Arbel et al., 2021) propose to fit $K$ discrete NFs that each approximates the transport map between $\pi_{k-1}$ and $\pi_k$. However, the sampling convergence rate largely depends on the pre-defined annealed target. Besides, a larger number of steps $K$ is needed to decrease the variance of the estimator, but it comes at an additional cost (Doucet et al., 2022).

As ACNF can also define a flow from a base distribution to a target distribution, it can learn a continuous annealed target and later easily generate samples. Different to (Grosse et al., 2013), the annealed target by ACNF does not limit in the form of distribution. Since ACNF is enforced to converge faster to the target distribution, it potentially generates better samples than vanilla CNF or commonly used linear annealed scheduling especially at limited computations, thus the estimate on, e.g. logarithm of normalization constant $\log Z$, becomes more accurate.

Different to maximum likelihood learning, training ACNF for annealed sampling is to minimize the reverse KL divergence $\mathrm{KL}(p_T(\mathbf{z}(T)) \| \pi(\mathbf{z}(T)))$ and eq.(6) directly defines the dynamics for the steepest descent of $\mathrm{KL}(p_t(\mathbf{z}(t)) \| \pi(\mathbf{z}(t)))$. The objective can be equivalently estimated up to a

Figure 4: Comparison on log potential field evaluated on trained vanilla CNF and ACNF with $\lambda = 1$ for 2-modal Gaussian mixture along flow and the numerical PDE solutions of eq.(7) at $t \in [0, 2T]$. Color indicates the value of field: turquoise is 0 and the lighter the color is the larger the value is.

Figure 5: Comparison on density evaluation of trained vanilla CNF and ACNF with $\lambda = 0.0001, 0.0005, 0.001, 0.005$ on 2-moon distribution along integral $t \in [0, 2T]$.

constant by the logarithm of importance weights, $\log w(\mathbf{z}^i(T)) = \log \gamma(\mathbf{z}^i(T)) - \log p_T(\mathbf{z}^i(T))$, where $\mathbf{z}^i(T)$ is samples $\mathbf{z}_0^i \sim \mu$ after applying the flow and $\log p_T(\mathbf{z}^i(T)) = \log \mu(\mathbf{z}_0^i) - \int_0^T \boldsymbol{\nabla} \cdot \mathbf{f}(\mathbf{z}(t), t) \mathrm{d}t$. Therefore, with ascent regularization, the total objective becomes:

$$\min_{\mathbf{f}} \mathcal{L} = \frac{1}{N} \sum_{i=1}^{N} \left( -\log w(\mathbf{z}^i(T); \boldsymbol{\theta}) + \lambda \int_0^T \| \left( \nabla \log p_t(\mathbf{z}^i(t); \boldsymbol{\theta}) - \nabla \log \mu(\mathbf{z}^i(t)) \right) + \mathbf{f}(\mathbf{z}^i(t), t; \boldsymbol{\theta}) \|_2^2 \mathrm{d}t \right),$$

(10)

where $\mathbf{f}_{\boldsymbol{\theta}}$ here is the annealed generation dynamics. Different from previous section, $\mathbf{z}^i(t)$, $\log p_t(\mathbf{z}^i(t))$ and $\nabla \log p_t(\mathbf{z}^i(t))$ can be integrated simultaneously. We summarize pseudo-code for learning ACNF annealed sampler in Algorithm 2. Once ACNF is learned, it can generate unbiased samples: generate one-shot samples from ACNF with integration length $t$ according to computation budget; correct samples by resampling via importance weights like (Müller et al., 2019) or Markov Chain Monte Carlo methods like Metropolis-Hastings. It is also possible to extend the one-shot sampler to SNF (Wu et al., 2020) or AFT (Arbel et al., 2021) with the correction in between the discrete steps of flows to alleviate the topological constraint of diffeomorphism.

# 6 EXPERIMENTS

## 6.1 DENSITY ESTIMATION ON TOY 2D DISTRIBUTIONS

Before we deploy ACNF for modeling complex distributions, we first train ACNF to model data from a 2-modal Gaussian mixture with a standard Gaussian as the base distribution in 2D. Figure 4 shows that the potential fields of learned ACNF is very similar to the PDE solutions while CNF potential converges much slower than ACNF and the PDE solution, and then diverges. See Appendix A.7 for experiment details and comparison on different regularization coefficients $\lambda$ and flow lengths $T$.

We train vanilla CNF, RNODE (Finlay et al., 2020) and ACNFs to model data from various 2D toy distributions and visualize the tractable density evaluation of learned flows. Figure 5 shows the densities at $t \in [0, 2T]$ by CNF and ACNFs learned with $T = 10$ and different regularization coefficients for a 2-moon distribution. The densities that are close to the target distribution are highlighted inside the red border. We show that even with slight regularization, the learned flows 1) converge densities much faster towards the target; 2) maintain the best density estimations for longer length after $T$. The quantitative evaluation is shown by the log-likelihood estimates on the left of Figure 6. More analysis on different $T$ and experiment setups are given in Appendix A.8.

One may suspect that ACNF learns complex dynamics that contributes to the faster ascent of log-likelihoods. To examine the actual improvements by ACNF, we plot the number of function evaluations (NFEs) on the integration with and without log-likelihood augmentation for all models

Figure 6: Left: comparison on estimated log-likelihoods of models trained under different regularization factor $\lambda$ as Figure 5. Middle: log-likelihood vs NFE as the left figure. Right: comparison on NFEs evaluated at $t/T = 1$ of trained ACNF, vanilla CNF model and RNODE on 2-moon distribution under various training flow length $T$ and $\lambda$.

Figure 7: Comparison on density estimations of trained ACNF and vanilla CNF models on various two-dimensional toy distributions along flows with increasing $t \in [0, 2T]$

on the left of Figure 6 and log-likelihood estimate versus NFEs in the middle. It is clearly shown that ascent regularization encourages the learning of even less complex dynamics than CNF and RNODE as log-likelihood gain per NFE of ACNFs are much higher than the two baselines. Comparing different ascent regularization, a larger coefficient strengthens more rapid gain on the log-likelihood at the initial stage, however, too large regularization constrains models to have a lower maximum. A moderate regularization benefits on the balance of a good maximum of likelihood estimate and faster convergence of flows. Furthermore, we report NFEs evaluation at $t/T = 1$ for CNF, RNODE and ACNFs trained with various $T = 0.5, 1, 5, 10$ and $\lambda = 0.0001, 0.005, 0.001, 0.005, 0.01, 0.05$ on the right of Figure 6. Generally, learned ACNFs have lower NFEs than that of CNF and RNODE. Most models reports their lowest NFEs at $T = 1$. It indicates that optimizing $T$ as proposed by TO-FLOW (Du et al., 2022) and STEER (Ghosh et al., 2020) can help to decrease the computational cost, however, the gain is not that much as NFEs are not linear to integration length and the strategy is not as effective as ascent regularization. Besides, neither method cannot prevent the deterioration of density estimation of CNF at $t > T$. Figure 7 show more density evaluations on learning multi-modal distributions. Learned ACNFs show faster convergence than CNFs for all distributions and give higher maximum density estimation on the challenging task, e.g. Olympics distribution.

## 6.2 DENSITY ESTIMATION ON REAL DATASETS

We demonstrate density estimations on real-world benchmarks datasets including POWER, GAS, HEPMASS, MINIBOONE from the UCI machine learning data repository and BSDS300 natural image patches. Like FFJORD, all tabular datasets and BSDS300 are pre-processed as in (Papamakar-ios et al., 2017). Table 1 reports the averaged NLLs on test data for FFJORD and ACNF trained with three different ascent regularization coefficients. The detailed description of experiments and models refers to Appendix A.9. Although FFJORD with multi-step flows increases the flexibility of flows, it tends to have a worse performance than the base distribution and ACNFs initially and improves NLL mainly at the late stage of flows. The larger ascent regularization coefficients of ACNF contributes to more rapid initial increases on NLL which shows that these flows transform the base distribution faster towards the data distribution. When training on HEPMASS and BSDS300, a too large regularization coefficient hinders model convergences.

Table 1: Averaged negative log-likelihoods (NLLs) on test data for density estimation.

| Datasets | Model | $0.1T$ | $0.25T$ | $0.5T$ | $0.75T$ | $T$ | $t > T$‡ |
|---|---|---|---|---|---|---|---|
| POWER | FFJORD†§ | 7.47 | 5.97 | 4.63 | 2.55 | −0.42 | 5.02 |
| | RNODE | 7.80 | 6.11 | 4.80 | 2.64 | −0.46 | 4.59 |
| | ACNF, $1e^{-4}$ | 7.03 | 5.02 | 2.63 | 0.81 | −0.40 | 0.12 |
| | ACNF, $1e^{-3}$ | 6.26 | 4.15 | 1.99 | **0.48** | −0.44 | 0.02 |
| | ACNF, $1e^{-2}$ | **5.43** | **3.47** | **1.87** | **0.48** | **−0.37** | **−0.26** |
| GAS | FFJORD†§ | 11.76 | 241.13 | 145.75 | 132.12 | −8.60 | 279.97 |
| | RNODE | 12.03 | 102.77 | 78.20 | 45.38 | **−8.79** | 90.23 |
| | ACNF, $1e^{-4}$ | 7.25 | 3.31 | −1.28 | −5.5 | −8.56 | −6.88 |
| | ACNF, $1e^{-3}$ | 5.58 | 1.65 | −1.73 | −5.61 | −8.45 | −7.63 |
| | ACNF, $1e^{-2}$ | **3.57** | **−0.14** | **−3.73** | **−6.42** | −8.57 | **−8.33** |
| HEPMASS | FFJORD†§ | 35.51 | 40.19 | 82.08 | 106.81 | 14.90 | 42.09 |
| | RNODE | 35.02 | 40.59 | 68.91 | 96.47 | 15.34 | 39.09 |
| | ACNF, $1e^{-4}$ | 27.75 | 24.88 | 20.63 | 17.17 | 14.95 | **15.36** |
| | ACNF, $1e^{-3}$ | **25.24** | **22.78** | **18.81** | **15.94** | **14.88** | 15.52 |
| MINIBOONE | FFJORD§ | 58.54 | 53.98 | 42.12 | 24.55 | 10.50 | 16.25 |
| | RNODE | 57.98 | 53.65 | 41.79 | 24.12 | 10.77 | 15.86 |
| | ACNF, $1e^{-4}$ | 54.15 | 43.76 | 29.29 | 19.00 | 10.63 | 13.95 |
| | ACNF, $1e^{-3}$ | 52.64 | 42.87 | 28.92 | 18.72 | **10.40** | 12.57 |
| | ACNF, $1e^{-2}$ | **51.52** | **40.52** | **26.53** | **17.16** | 10.95 | **12.14** |
| BSDS300 | FFJORD†§ | 41.72 | 30.11 | 0.91 | −85.92 | −156.60 | −77.20 |
| | RNODE | 42.38 | 33.29 | 1.74 | −84.03 | **−156.71** | −89.35 |
| | ACNF, $1e^{-4}$ | **35.24** | 24.10 | −14.75 | −100.35 | −156.0 | **−125.67** |
| | ACNF, $1e^{-3}$ | 37.45 | **21.53** | **−17.84** | **−105.11** | −156.5 | −120.89 |

† FFJORD uses multi-step flow models for some datasets, so the total length of flow is no longer training configuration of $T$ but $T$ times the number of flow steps. $T$ listed here refers the total length of flow. ‡ The flow length $t$ after $T$ is set slightly different among datasets due to the multi-step FFJORD: $1.2T$ for POWER and GAS, $1.1T$ for HEPMASS, and $1.25T$ for MINIBOONE and BSDS300, but it is always the *same* among different models. §FFJORDs are trained to match the performance as originally reported.

Figure 8: Left: comparison on estimated $\log Z$ by different methods along the flow over 5 different runs. Right: estimated $\log Z$ vs NFEs. See Figure 17 for generated sample comparisons.

## 6.3 ACNF AS A FASTER ANNEALING SAMPLING PROPOSAL FOR UNBIASED SAMPLING

Following Algorithm 2, we train CNF and ACNFs with three regularization coefficients $\lambda = 0.0001, 0.01, 0.01$ for learning annealed targets. We evaluate the normalization constants of a Gaussian mixture with 8 components whose means are fixed evenly in space and standard deviation as 0.3 and the base distribution is chosen as a Gaussian $\mathcal{N}(\mathbf{0}, 3^2\mathbf{I})$ to have adequate support for the target distribution. Figure 8 compares the estimates of $\log Z$ on different flow lengths and reports NFEs versus estimates. Except CNF and ACNFs, we also evaluate the linear annealed target $\log \gamma_k(\cdot) = \beta_k \log \gamma(\cdot) + (1 - \beta_k) \log \pi_0$, where scheduling is $\beta_k = k/K = t_k/T$ and $K = 20$, using $\{170, 25, 10\}$ step Metropolis sampler between each intermediate target. As regularized ACNF converges faster towards the target distribution than CNF, the one-shot samples generated from ACNF are less biased than those from CNF especially at early stage of the flows and ACNFs are more computationally efficient in terms of accuracy gain per NFEs as shown. Compared to the best tuned linear annealed target, ACNFs with coefficients $\lambda = 0.01, 0.001$ have more accurate estimates. Besides, due to the slow mixing in Metropolis sampler, the linear annealed target requires at least 1 order more computations than CNF and ACNFs for comparable accuracy, and is sensitive to the number of MC steps. Therefore, ACNF can prevent slow sample convergence from a suboptimal annealed target and make estimates more accurate with less computation. Figure 17 in Appendix

Table 2: Averaged negative ELBO on MNIST datasets under different length of flows $t$.

| Model | $0.1T$ | $0.25T$ | $0.5T$ | $0.75T$ | $T$ | $1.2T$ |
|---|---|---|---|---|---|---|
| VAE-FFJORD | 85.90 | 85.07 | 83.96 | 83.26 | 82.88(82.82†) | 89.74 |
| VAE-ACNF, $1e^{-4}$ | 85.62 | 84.60 | 83.45 | 83.06 | **82.74** | 85.67 |
| VAE-ACNF, $1e^{-3}$ | **84.70** | **83.95** | **83.22** | **82.53** | 82.80 | **84.37** |

† originally reported in FFJORD

A.10 shows the corresponding generated samples by all methods. Adding MC steps in ACNFs flows can further accelerate sample convergence to target and increase the expressiveness of ACNF.

### 6.4 VARIATIONAL INFERENCE WITH ACNFs

In addition to density estimations and unbiased sampling, CNFs provides more flexible variational approximations to improve variational inference (Rezende and Mohamed, 2015). We follow the experiment setup as (Grathwohl et al., 2018), that uses an encoder/decoder with a CNF architecture, of which the encoder gives the base latent posterior approximation for CNF and the decoder transforms latent inference at the end of the flow to the observation dimension. To train VAE-ACNF model, the log weights in eq.(10) is replaced by ELBO estimate as (Kingma and Welling, 2014).

We compare VAE-ACNF to VAE-FFJORD and vanilla VAE without flow on MNIST data. To make a fair comparison, we fix the learned encoder-decoder when training all three models. A detailed description of model architecture and experimental setup can be found in Appendix A.11. The averaged negative ELBO of vanilla VAE is 86.50. Table 2 reports the averaged negative ELBO on test data for VAE-FFJORD and VAE-ACNFs with two regularization $\lambda = 1e^{-4}, 1e^{-3}$ evaluated at various flow lengths. VAE-ACNFs show the rapid gains on ELBO at early stage of the flows, compared to VAE-FFJORD, and a larger coefficient accelerates the convergence of approximation to true posterior. VAE-ACNFs also circumvent the ELBO deterioration of VAE-FFJORD thanks to the self-stabilization behavior of ACNF. We also show some reconstruction examples from VAE-ACNF in Figure 18 in Appendix A.11. These reconstructions tend to correct some defects from original images, add details to avoid confusion on classifications and remain sharp as the original images.

## 7 SCOPES AND LIMITATIONS

While we have demonstrated that ascent regularization is effective to learn a flow that converges faster to a target distribution, our proposed method has a number of limitations, which we would like to address in the future. First, during training, the integration of the score function needs to evaluate Jacobian matrix and the gradient of divergence, which requires more efficient implementations, e.g. estimators or model design, to scale up for high-dimensional problems. Second, Hypernet (Ha et al., 2016) is found effective to illustrate faster convergence behavior of ACNF as time exerts a large impact on the dynamics, however, it is slower to train than other simpler network architecture. A better architecture design for dynamics can improve the training speed while maintaining the faster convergence behavior of flows. Third, even though proposed ACNF limits itself as a diffeomorphism, the concept of ascent regularization can be extended to score-based models and other stochastic flows. Finally, although the experiments demonstrate in learning static distributions, proposed ACNF and ascent regularization can be extended for a sequence of distributions and applied on the inference of sequential data, e.g. computationally efficient ACNF may benefit for online inference problems.

## 8 CONCLUSION

We have proposed ACNFs, a new class of CNFs, that define flows with monotonic convergence toward a target distribution. We derive the dynamics for the steepest ACNF and propose a practical implementation to learn parameteric ACNFs via ascent regularization. We demonstrate ACNF in three use cases: modeling data and performing density estimation, learning an annealed sampler for unbiased sampling, and learning variational approximation for variational inference. The learned ACNFs illustrate three beneficial behaviors: 1) faster convergence to the target distribution with less computation; 2) self-stabilization to mitigate performance deterioration; 3) insensitivity to flow training length $T$. Experiments on both toy distributions and real-world datasets demonstrate the effectiveness of ascent regularization on learning ACNFs for various purposes.

**Ethics Statement**    As this work mainly concerns to propose a flow-based model and practical implementation for learning, it does not involve human subjects, practices to data set releases, or security and privacy issue. At this stage of study, we do not foresee the effects of potential system failures due to weaknesses in the proposed methods.

**Reproducibility Statement**    All proposition (proposition 1) and theorems (theorem 1 and 2) proposed in this paper are proved with details in Appendix A.1, A.2 and A.5 as well as other minor derivations mentioned in main body of the paper. The pseudo-code for both learning cases are provided in Algorithm 1 and Algorithm 2. The datasets, models, experiment setups for each demonstration are described in details in Appendix A.8 ∼ A.11. Furthermore, we attach source codes in supplementary material for further checkup.

## REFERENCES

George Papamakarios, Eric Nalisnick, Danilo Jimenez Rezende, Shakir Mohamed, and Balaji Lakshminarayanan. Normalizing flows for probabilistic modeling and inference. *Journal of Machine Learning Research*, 22(57):1–64, 2021.

Ricky TQ Chen, Yulia Rubanova, Jesse Bettencourt, and David Duvenaud. Neural ordinary differential equations. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, pages 6572–6583, 2018.

Laurent Dinh, David Krueger, and Yoshua Bengio. Nice: Non-linear independent components estimation. *arXiv preprint arXiv:1410.8516*, 2014.

Laurent Dinh, Jascha Sohl-Dickstein, and Samy Bengio. Density estimation using real nvp. *arXiv preprint arXiv:1605.08803*, 2016.

George Papamakarios, Theo Pavlakou, and Iain Murray. Masked autoregressive flow for density estimation. *Advances in neural information processing systems*, 30, 2017.

Jonathan Ho, Xi Chen, Aravind Srinivas, Yan Duan, and Pieter Abbeel. Flow++: Improving flow-based generative models with variational dequantization and architecture design. In *International Conference on Machine Learning*, pages 2722–2730. PMLR, 2019.

Will Grathwohl, Ricky TQ Chen, Jesse Bettencourt, Ilya Sutskever, and David Duvenaud. Ffjord: Free-form continuous dynamics for scalable reversible generative models. In *International Conference on Learning Representations*, 2018.

Ricky TQ Chen and David K Duvenaud. Neural networks with cheap differential operators. *Advances in Neural Information Processing Systems*, 32, 2019.

Emilien Dupont, Arnaud Doucet, and Yee Whye Teh. Augmented neural odes. In *Advances in Neural Information Processing Systems*, pages 3140–3150, 2019.

Stefano Massaroli, Michael Poli, Jinkyoo Park, Atsushi Yamashita, and Hajime Asama. Dissecting neural odes. *Advances in Neural Information Processing Systems*, 33:3952–3963, 2020.

Hao Wu, Jonas Köhler, and Frank Noé. Stochastic normalizing flows. *arXiv preprint arXiv:2002.06707*, 2020.

Liam Hodgkinson, Chris van der Heide, Fred Roosta, and Michael W Mahoney. Stochastic normalizing flows. *arXiv preprint arXiv:2002.09547*, 2020.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *Advances in Neural Information Processing Systems*, 33:6840–6851, 2020.

Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. In *International Conference on Learning Representations*, 2020.

Qinsheng Zhang and Yongxin Chen. Diffusion normalizing flow. *Advances in Neural Information Processing Systems*, 34, 2021.

Chris Finlay, Jörn-Henrik Jacobsen, Levon Nurbekyan, and Adam M Oberman. How to train your neural ode: the world of jacobian and kinetic regularization. In *International Conference on Machine Learning*, 2020.

Derek Onken, S Wu Fung, Xingjian Li, and Lars Ruthotto. Ot-flow: Fast and accurate continuous normalizing flows via optimal transport. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 1–18, 2021.

Jacob Kelly, Jesse Bettencourt, Matthew J Johnson, and David K Duvenaud. Learning differential equations that are easy to solve. *Advances in Neural Information Processing Systems*, 33:4370–4380, 2020.

Liu Yang and George Em Karniadakis. Potential flow generator with l2 optimal transport regularity for generative models. *IEEE Transactions on Neural Networks and Learning Systems*, 2020.

Arnab Ghosh, Harkirat Behl, Emilien Dupont, Philip Torr, and Vinay Namboodiri. Steer: Simple temporal regularization for neural ode. *Advances in Neural Information Processing Systems*, 33: 14831–14843, 2020.

Shian Du, Yihong Luo, Wei Chen, Jian Xu, and Delu Zeng. To-flow: Efficient continuous normalizing flows with temporal optimization adjoint with moving speed. *arXiv preprint arXiv:2203.10335*, 2022.

Luigi Ambrosio, Nicola Gigli, and Giuseppe Savaré. *Gradient flows: in metric spaces and in the space of probability measures*. Springer Science & Business Media, 2005.

Petr Mokrov, Alexander Korotin, Lingxiao Li, Aude Genevay, Justin M Solomon, and Evgeny Burnaev. Large-scale wasserstein gradient flows. *Advances in Neural Information Processing Systems*, 34, 2021.

Jiaojiao Fan, Amirhossein Taghvaei, and Yongxin Chen. Variational wasserstein gradient flow. *arXiv preprint arXiv:2112.02424*, 2021.

Esteban G Tabak and Eric Vanden-Eijnden. Density estimation by dual ascent of the log-likelihood. *Communications in Mathematical Sciences*, 8(1):217–233, 2010.

Cheng Lu, Kaiwen Zheng, Fan Bao, Jianfei Chen, Chongxuan Li, and Jun Zhu. Maximum likelihood training for score-based diffusion odes by high order denoising score matching. In *International Conference on Machine Learning*, pages 14429–14460. PMLR, 2022.

Yang Song, Conor Durkan, Iain Murray, and Stefano Ermon. Maximum likelihood training of score-based diffusion models. *Advances in Neural Information Processing Systems*, 34:1415–1428, 2021.

Radford M Neal. Annealed importance sampling. *Statistics and computing*, 11(2):125–139, 2001.

Michael Arbel, Alex Matthews, and Arnaud Doucet. Annealed flow transport monte carlo. In *International Conference on Machine Learning*, pages 318–330. PMLR, 2021.

Arnaud Doucet, Will Grathwohl, Alexander GDG Matthews, and Heiko Strathmann. Score-based diffusion meets annealed importance sampling. *arXiv preprint arXiv:2208.07698*, 2022.

Roger B Grosse, Chris J Maddison, and Russ R Salakhutdinov. Annealing between distributions by averaging moments. *Advances in Neural Information Processing Systems*, 26, 2013.

Thomas Müller, Brian McWilliams, Fabrice Rousselle, Markus Gross, and Jan Novák. Neural importance sampling. *ACM Transactions on Graphics (TOG)*, 38(5):1–19, 2019.

Danilo Rezende and Shakir Mohamed. Variational inference with normalizing flows. In *International Conference on Machine Learning*, pages 1530–1538, 2015.

Diederik P. Kingma and Max Welling. Auto-encoding variational bayes. In *2nd International Conference on Learning Representations, ICLR 2014*, 2014.

David Ha, Andrew Dai, and Quoc V Le. Hypernetworks. *arXiv preprint arXiv:1609.09106*, 2016.

Qiang Liu. Stein variational gradient descent as gradient flow. *Advances in neural information processing systems*, 30, 2017.