Structured Prompt Optimization Meets Reinforcement Learning for Global and Local Interpretability over Complex Text

Abstract

LLMs have advanced text classification, yet existing paradigms face a trade-off: supervised (label only) fine-tuning is scalable but offers limited reasoning on complex text and lacks broader model transparency, while discrete prompt optimization offers human-readable instructions but struggles with performance and scalability. We introduce EXTC[1] (EXplainable Text Classifier) with three progressive stages: (1) learning a Standard Operating Procedure (SOP, or rulebook) in natural language via a new Structured Prompt Optimization algorithm; (2) SOP-grounded reasoning distillation from a large teacher LLM into a compact LM; and (3) expanding reasoning capabilities beyond the initial SOP via reinforcement learning. This design enables EXTC to provide (i) fast inference via a compact LM, with (ii) inference-time local reasoning traces, alongside a global, modular explanation of its learned domain rules, while (iii) significantly outperforming existing paradigms across diverse benchmarks in both classification performance and explanation quality, with stage-by-stage gains.

1 Introduction

Text classification finds widespread applications in finance (e.g., market sentiment) (Das and Chen, 2007), healthcare (e.g., clinical note triage) (Jagannatha and Yu, 2016), law (e.g., case outcome prediction) (Chalkidis et al., 2020), cybersecurity (e.g., spam/phishing/malware detection) (Salloum et al., 2022). With the rise of LLM-generated text, it has found critical applications in safety and reliability; e.g., detecting LLM-vs-human content (Mitchell et al., 2023), hallucination (Ji et al., 2023), and harmful/unsafe generations (Gehman et al., 2020).

Despite its popularity, text classification remains challenging due to (i) the high dimensionality of textual input, (ii) complex and nuanced semantics that extend beyond surface-level words, and (iii) long-range dependencies across text. Moreover, many applications require (iv) robust high-level discrimination rather than reliance on spurious low-level signals, as well as (v) interpretable explanations for individual decisions and global understanding of what the model has learned.

Traditional solutions that rely on many textual features (Joachims, 1998), even high-level topics, struggle to address these challenges as features provide fragmented representations that fail to capture rich semantics, long-range context, robust high-level reasoning, and coherent explanations. Explanations based on feature importance and saliency often fail to reflect the deeper rationale underlying classification decisions (Lipton, 2018).

Large language models (LLMs) have transformed many areas of natural language processing (NLP), with major implications for text classification. In fact, BERT (Devlin et al., 2019), as one of the first Transformer-based LMs, already significantly improved classification performance across a wide range of NLP benchmarks, with many follow-up models building on this success (Vajjala and Shimangaud, 2025). The attractiveness of LLMs for text classification is evident from the advantages they offer, including ingrained world and domain knowledge, holistic contextual comprehension, natural language interface, high-level reasoning that is less reliant on low-level spurious signals, and reasoning capabilities that support more interpretable predictions.

However, existing solutions for LLM-driven classification remain limited in key aspects. In general, these approaches fall into two main categories: (1) parameter-efficient (supervised) fine-tuning (PEFT/SFT) of pretrained backbones (Wang et al., 2025a), and (2) prompt optimization (PO), which learns human-readable commands in context that guide a frozen backbone (Pryzant et al., 2023; Wang et al., 2024) to generate the correct la-

---

[1] All code and model checkpoints are open-sourced at https://anonymous.4open.science/r/eXTC.

(a) Example rule from the SOP (excerpt):	[Global Explanation]

Trigger Pattern: Apply `readmit` when discharge happens before pending biopsy / pathology comes back AND specialty follow-up is scheduled within days to weeks. ...
Exceptions: Pending pathology without confirmed disease. ...
Examples: ...

(c) Method	mF1	Judge
Zero-shot CoT	0.517	3.58
Stage I (SPO4SOP)	0.597	3.65
Stage I+II (R-SFT)	0.620	4.29
Stage I+II+III (EXTC)	0.652	4.31

(b) MIMIC Readmission Prediction. *Discharge summary:* Patient has liver spots suspicious for cancer. A biopsy was taken; patient was discharged stable *while awaiting results*, with an *outpatient* oncology clinic visit in 10 days.

Zero-shot CoT reasoning:
"Suspicious for metastatic disease with pending biopsy and planned oncology follow-up indicate serious malignancy concern likely needing chemotherapy/radiation soon. High readmission risk."
Predicted: `readmitted` ✗

v.s.

EXTC (RL) reasoning:	[Local Explanation]

"Biopsy done; results pending but no indication of active malignancy; no intensive treatment in progress, patient stable and ambulatory at discharge."
Predicted: `not_readmitted` (✓)

Figure 1: EXTC **at a glance on MIMIC Readmission.** **(a)** a rule excerpt from our *learned* rulebook (or SOP); **(b)** on a test case: Zero-shot CoT over-fires on the surface trigger, whereas EXTC correctly invokes the rule's *exception* (no confirmed disease yet); **(c)** both metrics improve monotonically across our three Stages. See Case Study in §4.4.

bel tokens as outputs. SFT, and in particular PEFT, is scalable, however, it does not readily provide reasoning traces or a global explanation of the underlying model. Chain-of-Thought prompting (Wei et al., 2022) of models fine-tuned only on labels does not readily produce competitive reasoning, especially for complex text. In contrast, hard (discrete) prompt optimization (PO) can yield human-readable prompts that serve as global explanations, which, however, are often unstructured. In addition, hard PO is computationally demanding, making it less scalable for large-corpus tasks. (See Table 6, and Apdx. A for detailed related work.)

This work bridges these gaps by introducing EXTC, an effective and efficient LLM-powered EXplainable Text Classifier with human-readable global and local explanations. In a multi-stage framework (Fig. 2), EXTC bridges structured prompt optimization, reasoning-based SFT, and reinforcement learning; producing a small distilled LM classifier that also offers reasoning (local explanation), and a structured rulebook in the form of a decision set (global explanation). The following summarizes our main contributions.

- **Reasoning-centric Text Classification:** We introduce EXTC, a new LLM-powered approach to *classification and reasoning over complex text* that provides both global and local explanations. (See example in Fig. 1 (a) and (b).)
- **Formulation and Algorithm Innovations:** EXTC has a multi-stage framework: (i) **SOP Learning** learns a rulebook (SOP) via a new structured prompt optimization (SPO) algorithm, (ii) **SOP-Grounded Distillation** transfers SOP-guided reasoning traces from a large LM onto a small LM, which (iii) further improves through reinforcement learning **Beyond SOP**, with a cur-

riculum designed to increase performance on the hard (i.e., teacher-failed) cases. (See Fig. 1 (c).)
- **Desirable Properties:** EXTC is (i) *effective*, capitalizing on SPO, SFT and RL; (ii) *efficient*, with a compact 4B-parameter student model obtained via distillation; and (iii) *doubly-interpretable*; rulebook constitutes the global "SOP", and small LM's reasoning at inference serves as a local explanation per input.
- **Evaluation:** Extensive experiments on three real-world benchmarks with ground-truth evidence for labels show that EXTC outperforms baselines in terms of both classification performance and explanation quality, with results often improving progressively from SPO to SFT to RL across stages, demonstrating the effectiveness of the proposed multi-stage learning paradigm.

2 Problem and Preliminaries

2.1 Problem Statement

Typical Text Classification: Let $\mathcal{X}$ denote the input space with domain Θ_{lang} representing natural language, where $\mathbf{x}_i \in \mathcal{X}$ represents a text document; i.e., a sequence of tokens. Let $\mathcal{Y}, |\mathcal{Y}| = C$, denote the set of possible classes where $y_i \in \mathcal{Y}$ is the ith example's class label.

Typical text classification aims to learn a model $f_{\text{model}}(\cdot; \boldsymbol{\theta})$, given training set $\mathcal{D} = \{(\mathbf{x}_i, y_i)\}_{i=1}^n$, that achieves low classification error.

Decision Sets: A decision set $\mathcal{R}$ consists of an unordered collection of rules $\{R_1, \ldots, R_K\}$ that are *stand-alone*, i.e., not linked via 'else' statements. This makes them easier to interpret as compared to hierarchical decision lists where a rule deep in a decision list is in fact a long rule and applies only when none of the preceding rules apply.

Definition 1 (**Decision Composition**). *Each rule*

Figure 2: EXTC Overview: **Stage I**: SPO learns a rulebook (or SOP) that *grounds* **Stage II**: teacher-reasoning and distillation; **Stage III** employs RL to increase hit-rate on hard (i.e. teacher-failed) cases. SOP serves as the global explanation, while the small (student) LM is the text classifier with local explanations (i.e. instance-level reasoning).

$R_j \in \mathcal{R}$ *has a target label* $l_j \in \mathcal{Y}$ *and either "fires" for an input* $\mathbf{x}$ *(predicting* l_j*) or "abstains". Given a priority order* $p : \mathcal{Y} \to \{1, \ldots, |\mathcal{Y}|\}$ *with default* $y_{def} := \arg\min_l p(l)$*, a decision set's prediction is*

$$f_{model}(\mathbf{x}; \mathcal{R}) := R_{\arg\max_j \ p(R_j(\mathbf{x}))}(\mathbf{x}) \quad (1)$$

where $R_j(\mathbf{x}) := y_{def}$ *when* R_j *abstains, so if no rule fires,* $f_{model}(\mathbf{x}; \mathcal{R}) = y_{def}$*. In the binary case* $(\mathcal{Y} = \{0, 1\})$*, this reduces to the standard max-pool:* $f_{model}(\mathbf{x}; \mathcal{R}) = 1$ *iff at least one rule fires.*

Decision sets have been effectively used for explainable ML for tabular data (Lakkaraju et al., 2016; Macha and Akoglu, 2018), where each rule corresponds to an itemset; i.e., a conjunction of predicates over numerical and/or categorical features (e.g., `age > 65 ∧ location=California`). Different from prior literature, our work introduces decision sets of rules in *natural language*. This allows us to utilize them (1) as a structured prompt of an LLM-powered text classifier, and (2) as human-readable explanations behind decisions.

Problem 1 (**Explainable Text Classification**). *Given a labeled text corpus* $\mathcal{D} = \{(\mathbf{x}_i, y_i)\}_{i=1}^n$*,* $\mathbf{x}_i \in \Theta_{lang}$*, estimate a text classification model* $f_{model}(\cdot; \boldsymbol{\theta}) : \mathbf{x} \mapsto \{\mathbf{r}, y\}$ *that produces (1) **instance-level local explanation** $\mathbf{r} \in \Theta_{lang}$ (in the form of reasoning), and (2) **model-level global explanation** $\mathcal{R} = \{R_k \in \Theta_{lang}\}$ (in the form of a decision set of natural language rules).*

Our problem statement differs from traditional text classification by explicitly requiring both local and global explanations in natural language, motivating a language-model-driven approach. Further, the global explanation is structured and decomposable, enabling readability and modular inspection. Such explanations provide a more coherent and richer reasoning than fragmented feature importance scores or saliency maps, which often only identify portions of the input text most associated with the predicted label, rather than offering a deeper semantic interpretation of the content.

2.2 Verbalized Machine Learning

Traditional neural models for text classification exhibit numerical parameters $\boldsymbol{\theta}$ in continuous space. Motivated by modern LLMs' prowess in many NLP tasks, recent "verbalized" machine learning approaches (Xiao et al., 2024; Yüksekgönül et al., 2025), employ a pretrained (frozen) LLM as a function approximator that is parameterized by its (text) prompt. In essence, both the input data $\mathcal{D} \in \Theta_{lang}$ and the model parameters $\boldsymbol{\theta} \in \Theta_{lang}$ (i.e., the prompt) are represented in natural language. LLMs are further employed for prompt optimization, to derive "textual gradients" that guide learning the prompt through reasoning and reflection on model mispredictions across training epochs.

3 Proposed Framework

3.1 Motivation and Overview

Fig. 2 illustrates the three stages of EXTC: **I. SOP Learning** employs structured prompt optimization (SPO) to learn a rulebook or SOP (Standard Operating Procedure); **II. SOP-Grounded Distillation** collects grounded reasoning traces and performs distillation; and **III. Beyond SOP** further improves reasoning beyond the learned SOP through reinforcement learning. Stages I and II access the large LM only as a black box; the small LM is trained in Stages II and III. We provide an overview motivating each stage's role within the overall pipeline.

Stage I. SOP Learning (§3.2) *Motivation:* Given ⟨text, label⟩ training pairs $\mathcal{D} = \{(\mathbf{x}_i, y_i)\}_{i=1}^n$, a ba-

sic approach would be SFT/PEFT an existing language model (LM) to map input text to its label. However, this model would not readily produce individual explanations/reasoning $\mathbf{r}_i$'s. CoT-prompting (Wei et al., 2022) does not necessarily induce effective reasoning, especially for complex text, as we show in §4.2 where direct CoT yields poor classification and explanation quality.

Overview: As with RAG-based generations for knowledge-intensive tasks (Lewis et al., 2020), having access to additional information in the context, such as a task-specific SOP (Standard Operating Procedure) or a rulebook could help obtain enriched reasoning. To this end, we learn a rulebook comprising a structured prompt in the form of stand-alone rules (i.e., a decision set) in natural language. We propose a new *structured prompt optimization* (**SPO**) algorithm based on verbalized machine learning (VML) (Xiao et al., 2024) to learn such a task-specific rulebook, which we call Standard Operating Procedure (SOP).

Stage II. SOP-Grounded Distillation (§3.3) *Motivation and Overview:* Given the learned SOP, a teacher LLM is prompted with the enriched and grounded context $\langle \text{SOP}, \mathbf{x} \rangle$ to generate reasoning and label pairs $\langle \mathbf{r}, y \rangle$. Retaining only the teacher-generated traces whose predicted labels agree with the ground truth, we distill triplets $(\mathbf{x}_i, \mathbf{r}_i, y_i) \subset \mathcal{D}$ onto a smaller (student) LM via reasoning-supervised fine-tuning (R-SFT), training the model to map input text to both reasoning and label outputs. This distillation serves two purposes: (i) equipping the student model with *SOP-free* reasoning capability, and (ii) producing a smaller and more efficient inference model. The former enables the model to move beyond the SOP through subsequent reinforcement learning (RL), while the latter facilitates efficient RL rollouts.

Stage III. Beyond SOP (§3.4) *Motivation:* SPO requires costly iterative optimization over multiple LLM calls; therefore, SOP is learned from a relatively small subset of training data, limiting the teacher model's reasoning capability and coverage. In turn, using only those teacher-generated reasoning traces with correct predictions limits distillation to a subset of the training set.

Overview: To further improve reasoning capability, we employ reinforcement learning (RL); enabling the student-LM to generate multiple traces per input within each batch. The training set naturally decomposes into easy and hard examples, reflecting the teacher model's varying accuracy, and

our goal is to rapidly improve performance on the harder cases without imposing an explicit manual curriculum. To this end, we over-sample candidate inputs and filter out both overly easy and overly hard examples whose rollouts yield zero GRPO (Group Relative Policy Optimization) advantage (Shao et al., 2024). Constructing batches from examples with non-zero advantage promotes more informative learning signals, thereby improving RL's sample-efficiency and effectiveness.

3.2 I: SOP Learning via SPO

The first goal is to construct a task-specific rulebook to be placed in-context with each test sample to *ground* a language model's reasoning and classification. The problem can be viewed as prompt optimization (PO), specifically as *structured* PO, where the rulebook is to comprise *standalone* decision rules expressed in natural language. Since the rulebook governs the LM output, we also refer to it as a Standard Operating Procedure (SOP).

Algo. 1 presents SPO4SOP, our proposed structured prompt optimization approach to learning a task-specific SOP (See diagram in Apdx. B.1.1 Fig. 6). In essence, it employs verbalized ML and text gradients to update the SOP by orchestrating a Classifier LLM, Gradient LLM, and Update LLM. *Algorithm at a glance.* SPO4SOP starts *cold* with an empty decision set $\mathcal{R}_0 = \emptyset$ and iterates over T batches drawn from $\mathcal{D}_{\text{train}}$. Each iteration handles two disjoint error modes. (i) **False coverage** (a rule fires on $\mathbf{x}_i$ but its label l_j disagrees with ground truth y_i): the Gradient LLM proposes *exceptions* from the "offending" example, and the Update LLM rewrites the rule into a more precise candidate. (Lines 3–11) (ii) **Blind spots** (no rule fires and the default label y_{def} is wrong): the Gradient LLM extracts an *error pattern* per missed sample, and the Update LLM synthesizes new candidate rules grouped by target label $l \in \mathcal{Y}$. Candidates from each iteration accumulate in a *persistent pool* $\mathcal{P}_t$ throughout the iterations, such that a rule generated early but not initially selected remains available for later subset search. (Lines 13–20) *Subset selection.* From $\mathcal{P}_t$ we select a small active set $\mathcal{R}_t \subseteq \mathcal{P}_t$ ($|\mathcal{R}_t| \leq K$) that maximizes macro-F_1 on $\mathcal{D}_{\text{val}}$ with an AIC-style sparsity penalty $\lambda \cdot |\mathcal{R}_t| / |\mathcal{D}_{\text{val}}|$. Because each rule's per-sample prediction is cached (Line 21), evaluating any candidate subset reduces to composing cached predictions, thanks to the composability of decisions across rules (Definition 1). As such, the LLM cost

Algorithm 1 SPO4SOP: **Structured Prompt Optimization for Standard Operating Procedure**

Given: $\mathcal{D}_{\text{train}} = \{(\mathbf{x}_i, y_i)\}_{i=1}^n$, $\mathcal{D}_{\text{val}}$, max iter.s T, max subset size K, sparsity penalty λ, priority $p : \mathcal{Y} \to \{1, \ldots, |\mathcal{Y}|\}$ (default $y_{\text{def}} := \arg\min_l p(l)$)
Output: SOP (i.e. decision set $\mathcal{R}$ in natural language)

1: Init. SOP, pool, candidates $\mathcal{R}_0 = \mathcal{P}_0 = \mathcal{C} := \emptyset$ {cold start}
2: **for** $t = 1, \ldots, T$, batch $\mathcal{D}_{\text{batch}} \subseteq \mathcal{D}_{\text{train}}$ **do** { *(Iterative Optimization) Revise rules & rule set w.r.t. $\mathcal{D}_{\text{val}}$ error* }
3:     **for** $R_j \in \mathcal{R}_{t-1}$ **do**
4:        $\mathcal{F}_j^+ := \{\mathbf{x}_i \in \mathcal{D}_{\text{batch}} \mid f_{\text{model}}(\mathbf{x}_i; R_j) = l_j \neq y_i\}$ {false coverage by Rule R_j}
5:     **end for**
      ▶ *Handling False Coverage — Update mis-"firing" rules with new exceptions*
6:     **for** $R_j \in \mathcal{R}_{t-1}$ **do**
7:        $\mathcal{G}_j := \emptyset$
8:        **for** $\mathbf{x}_i \in \mathcal{F}_j^+$ **do**
9:           $\mathcal{G}_j := \mathcal{G}_j \cup f_{\text{grad}}(\mathbf{x}_i, y_i; l_j, R_j)$ {add Exception by `Gradient_LLM`; Apdx. C.3}
10:        **end for**
11:        $\mathcal{C} := \mathcal{C} \cup f_{\text{update}}(R_j, \mathcal{G}_j)$ {update R_j based on Exceptions via `Update_LLM`; Apdx. C.4}
12:     **end for**
      ▶ *Handling Misclassifications — Add new rules*
13:     $\mathcal{F}^- := \{\mathbf{x}_i \in \mathcal{D}_{\text{batch}} \mid f_{\text{model}}(\mathbf{x}_i; \mathcal{R}_{t-1}) = y_{\text{def}} \neq y_i\}$ {blind spot; uncovered pattern}
14:     **for** $\mathbf{x}_i \in \mathcal{F}^-$ **do**
15:        $g_i := f_{\text{grad}}(\mathbf{x}_i, y_i; \{R \in \mathcal{R}_{t-1} \mid l = y_i\})$ {Error-Pattern by `Gradient_LLM`; Apdx. C.3}
16:     **end for**
17:     **for** $l \in \mathcal{Y}$ s.t. $\mathcal{G}_l := \{g_i : \mathbf{x}_i \in \mathcal{F}^-, y_i = l\} \neq \emptyset$ **do**
18:        $\mathcal{C} := \mathcal{C} \cup f_{\text{update}}(\mathcal{G}_l; l)$ {cand.s for l; Apdx. C.5}
19:     **end for**
20:     Expand persistent pool; $\mathcal{P}_t := \mathcal{P}_{t-1} \cup \mathcal{C}$

      ▶ *(Rule Subset Selection): Select few rules on $\mathcal{D}_{\text{val}}$*
21:     Classify $\mathcal{D}_{\text{val}}$ by `Classifier_LLM`(Apdx. C.2) against new candidate rules; $\widehat{y}_{ij} = f_{\text{model}}(\mathbf{x}_i \in \mathcal{D}_{\text{val}}; R_j \in \mathcal{C})$
22:     $\mathcal{R}_t := \arg\max_{\mathcal{S} \subseteq \mathcal{P}_t, |\mathcal{S}| \leq K} \left[M(\mathcal{S}; \mathcal{D}_{\text{val}}) - \lambda |\mathcal{S}| / |\mathcal{D}_{\text{val}}| \right]$ {beam search; Apdx. B.1.2 ($M(\cdot \; ; \; \cdot)$ is macro-F_1)}
23: **end for**
24: **Return** $\mathcal{R}_T$

is *linear* in the pool size $|\mathcal{P}_t|$ rather than exponential in subset count. We approximate the argmax with beam search (Line 22); with details in Apdx. B.1.2. After T iterations, SPO4SOP returns the final $\mathcal{R}_T$ as the learned SOP. Importantly, it serves as a global explanation of what the model has learned.

Efficiency. SPO4SOP's key compute cost is the number of required LLM API calls, which may directly translate into monetary cost in practical deployments. Therefore, we analyze the time complexity of EXTC in terms of the #LLM-calls.

Lemma 1 (Scalable subset search). *SPO4SOP's rule subset search scales linearly with the number of candidate rules m, rather than with the exponential number of possible rule subsets. This is enabled by decision composition (Definition 1), which requires only a linear number of LLM calls in m to obtain decisions for arbitrary rule subsets.*

Figure 3: t-SNE of PO-classifier reasoning on MIMIC: SPO4SOP's embeddings form distinct clusters per rule, while those of baselines are diffused and unstructured.

Proof. See Apdx. B.1.3. □

As a qualitative study, Fig. 3 shows 2D embedding of PO-classifier reasonings on MIMIC dataset. SPO4SOP's reasonings form well-separated clusters corresponding to individual rules, while those from baseline PO methods are diffused and unstructured, showing that SPO4SOP's modular standalone rules induce distinct reasoning.

3.3 II: SOP-Grounded Distillation

Teacher trace generation and rejection sampling. To absorb SOP's task knowledge into a compact student model, we collect SOP-grounded reasoning traces from a teacher LLM. A natural choice is to use the same LLM as the Stage I Classifier, ensuring consistent SOP interpretation across stages. We ground the context by concatenating the learned SOP with each training example as $\langle \text{SOP}, \mathbf{x}_i \rangle$, and prompt the teacher for a reasoning-label pair. We draw at most $M=4$ candidate traces per example and accept the first whose predicted label matches ground truth as the distillation trace $(\mathbf{r}_i, y_i)$ for $\mathbf{x}_i$. Examples with all M mispredictions are denoted as *hard* and excluded from R-SFT, while the other *easy* ones form the distillation set. This hard/easy partition further seeds the RL curriculum in §3.4.

Reasoning-supervised fine-tuning (R-SFT). Letting $\mathcal{D}_{\text{rsft}} = \{(\mathbf{x}_i, \mathbf{r}_i, y_i)\}$ denote the accepted (easy) triplets, we fine-tune a smaller student LM with LoRA (Hu et al., 2022) via next-token cross-entropy on $[\mathbf{r}_i; y_i]$ conditioned on $\mathbf{x}_i$. To give the subsequent RL stage a stable starting point, we apply class-balanced upsampling on $\mathcal{D}_{\text{rsft}}$: each epoch traverses the majority class once while minority classes are oversampled to match. This prevents the student from initializing as a majority-biased predictor that would destabilize early policy updates. Training details are in Apdx. D.2.

After R-SFT, the student maps input text directly to both reasoning and label outputs without needing the SOP in-context at inference: i.e., SOP's task knowledge has been internalized into the model's parameters. Student's per-example reasoning then serves as a *local explanation* of its prediction, complementing the SOP's *global explanation* (§3.2).

Table 1: Distribution (%) of rollout outcomes within each hard/easy group at the start of RL (G=8), shown for ICLR Review as a representative example; the other two datasets follow the same pattern (see Apdx. B.2.1, Tab. 7). Only the 1–7/G column carries non-zero GRPO advantages and provides gradient signal.

		Rollouts correct (%)			
Dataset	Diff.	0/G	1–7/G	G/G	% of band
ICLR Review	hard	54.0	43.6	2.4	29.5
	easy	0.7	18.1	81.2	70.5
	all	8.6	21.9	69.5	(14.8% nat.)

3.4 III: Beyond SOP via RL

Why standard GRPO underperforms on classification. Stage II equips the student with SOP-grounded reasoning but leaves the *hard* examples (§3.3) unaddressed. We turn to RL to extend coverage by letting the student self-explore. While GRPO-style RL has been most actively studied on verifiable reasoning tasks such as math and code, where rollouts span correct and incorrect outcomes (Shao et al., 2024; Yu et al., 2025), text classification with a small and often imbalanced label space exposes a distinct failure mode: *rollout homogeneity*. Within a group of G rollouts on the same input, all rollouts often share the same predicted label, yielding a zero-advantage group, hence no gradient signal. Concretely, each rollout i receives a binary correctness reward $R_i = 2 \cdot \mathbf{1}[\widehat{y}_i = y] - 1 \in \{-1, +1\}$, from which GRPO computes a within-group normalized advantage

$$\hat{A}_i = \frac{R_i - \text{mean}(\{R_j\}_{j=1}^G)}{\text{std}(\{R_j\}_{j=1}^G) + \varepsilon}, \quad (2)$$

and optimizes the clipped surrogate

$$\mathcal{J}_{\text{GRPO}}(\theta) = \mathbb{E}\Big[\tfrac{1}{G}\sum_i \min(\rho_i \hat{A}_i,$$
$$\text{clip}(\rho_i, 1-\epsilon, 1+\epsilon)\hat{A}_i)\Big] - \beta\, D_{\text{KL}}[\pi_\theta \| \pi_{\text{ref}}] \quad (3)$$

with importance ratio $\rho_i = \pi_\theta(\mathbf{r}_i|\mathbf{x})/\pi_{\theta_{\text{old}}}(\mathbf{r}_i|\mathbf{x})$, and ε a small constant. When all rollouts in a group share the same prediction, $\text{std}(\{R_j\}) = 0$ and every $\hat{A}_i$ vanishes. To quantify this at the start of RL, we run G=8 rollouts per training example with the Stage II R-SFT model and bucket each example by its number of correct rollouts. Taking ICLR Review as a representative example (Table 1; analogous patterns hold on the other two datasets, Apdx. B.2.1), easy examples are mostly already mastered and a majority of hard examples are unsolved, leaving only a thin informative band of 21.9% where rollouts within a group disagree; implying that most of a *random* GRPO batch contributes no gradient.

Balanced Dynamic GRPO (BD-GRPO). We in-troduce BD-GRPO, a classification-aware variant of GRPO that resolves rollout homogeneity through two coupled mechanisms operating in a specific order. First, training pool is partitioned by class; for each class c with per-class quota n_c, we draw a candidate batch $\widetilde{\mathcal{B}}_c$ of size κn_c from $\mathcal{D}_{\text{train}}^{(c)}$ ($\kappa>1$ the oversample factor; value in Apdx. D.2) and run G rollouts per candidate. Second, in the same spirit as DAPO's dynamic sampling (Yu et al., 2025), we discard groups with $\text{std}(\{R_j\}) = 0$ and take the first n_c survivors per class:

$$\mathcal{B} = \bigcup_{c\in\mathcal{Y}} \text{first}_{n_c}\Big\{\mathbf{x} \in \widetilde{\mathcal{B}}_c : \text{std}(\{R_j(\mathbf{x})\}_{j=1}^G) > 0\Big\}, \quad (4)$$

producing a class-balanced batch composed entirely of informative groups, on which the GRPO update (Eq. 3) is then computed. If a class yields fewer than n_c informative survivors, we top up its quota with random draws from the same class. Performing dynamic sampling *after* per-class over-sampling is critical under severe label imbalance: replacing it with class-agnostic oversampling (D-GRPO) causes RL to over-predict the majority class and collapse on MIMIC (Fig. 4).

Figure 4: Bal-acc vs. time, truncated at each run's RL peak. BD-GRPO hits peak 3-5× faster than B-GRPO; D-GRPO collapses on MIMIC w/out class balance.

Figure 5: RL training progression on ContractNLI (other datasets in Apdx. B.2.1). **Take-aways:** Entropy stays bounded (no collapse), KL remains small, *hard hit rate steadily increases*, and easy hit rate remains high.

Self-guided curriculum and wall-clock time. To-gether, the two mechanisms implement an *implicit self-guided curriculum*: at every step, the model trains on examples currently in its informative band rather than on random batches. The infor-

Table 2: Dataset Overview and Summary Statistics

Dataset	Split (Tr/V/Te)	Avg Tok.	Min Class (%)	Class	Domain	Task Description	Evidence Type
ContractNLI	7191/1037/2091	2185	11	3	Legal	Contract NLI	Contract Spans
ICLR Review	8552/1000/655	2242	37	2	Peer Review	Paper Acceptance	Meta-Review
MIMIC Readmit	8000/1000/1000	3209	22	2	Clinical	Patient Readmission	LACE Risk Factors

mative band is itself hard-heavy: as illustrated in Table 1 for ICLR Review, hard examples occupy a far larger share than in the natural training set (similarly for other datasets), so a BD-GRPO over-represents hard examples relative to a random batch without any hand-crafted schedule. Fig. 5 shows that training is healthy throughout RL: entropy stays bounded, KL-to-reference remains small, hard-set accuracy rises substantially while easy-set accuracy is retained.

The upsampling strategy appears to multiply per-step rollout cost, but the wall-clock comparison in Fig. 4 demonstrates the opposite: BD-GRPO reaches its peak performance 3-5× faster than vanilla B-GRPO across all datasets while matching or exceeding its peak. The speedup comes from two sources: (i) every retained group provides a high-quality gradient signal, yielding more stable update directions than B-GRPO's noisy mix of informative and zero-advantage groups; so BD-GRPO needs far fewer total optimizer steps to peak; and (ii) rollouts within a step are independent and dispatched concurrently across GPUs via vLLM's batched inference, whereas optimizer steps must run sequentially. In addition, B-GRPO's class-balanced batches do not translate to a balanced *effective* signal: zero-advantage groups are unevenly distributed across classes and batches, causing the model to oscillate between over-predicting each class, further slowing convergence. Apdx. D.2 gives RL setting details.

RL learnings on hard cases are incorporated back into the SOP, deferred to Apdx. B.2.2 for brevity.

4 Experiments

4.1 Experiment Setup

Datasets: We use publicly available datasets from three domains: legal contracts, academic peer reviews, and hospital readmissions. All datasets exhibit "evidence" for each label which we use for evaluating explanations. Table 2 provides a summary while Apdx. D.1 gives details.

Models and Configurations: We organize the baselines into two: prompt-based and fine-tuned. CoT employs zero-shot Chain-of-Thought prompting (Wei et al., 2022), while MIPROv2 (Opsahl-Ong et al., 2024) and GEPA (Agrawal et al., 2026)

are two hard prompt optimization (PO) alternatives to our SPO4SOP, producing discrete but unstructured PO. SFT uses a classification head to fine-tune on the labels (only). In contrast, our Reasoning Distillation (Stage II) fine-tunes using both SOP-grounded teacher reasoning and the labels.

Student backbone is Qwen3-4B (Team, 2025b), a compact LM used for all SFT and RL methods. gpt-4.1-mini is the classifier for all prompt-based methods (zero-shot CoT, MIPROv2, GEPA, SPO4SOP) and the teacher generating R-SFT reasoning traces. All fine-tuning runs were carried out on 4× NVIDIA H100 80GB GPUs. Prompt-optimization methods are API-only through OpenAI. For Cls-head SFT with no native reasoning, we extract post-hoc gradient-based input saliency via Captum (Kokhlikyan et al., 2020). Setup for PO, SFT, and RL are detailed in Apdx. D.2.

Metrics: We evaluate both classification performance and explanation quality. The former is measured by **macro-F1** and **balanced accuracy**. Explanations are compared against ground-truth evidence using **NLI** and **LLM-judge** scores. NLI scores use MiniCheck-Flan-T5-Large (Tang et al., 2024), a fact-checking model that scores per-sentence entailment of an explanation against the evidence. LLM judge (gemini-2.5-flash-lite) follows G-Eval (Liu et al., 2023): for each (evidence, explanation) pair, it returns a 1–5 Likert score weighted by token-level output probabilities. Further details are given in Apdx. D.3.

4.2 Main Results

Table 3 presents results across datasets and metrics. Basic zero-shot CoT prompting baseline considerably underperforms across tasks, demonstrating the necessity of training the language models for complex text classification. Our SPO4SOP **substantially outperforms CoT** in terms of both classification and explanation performance, despite being trained only on a small *subset* of training data.

SFT improves classification over prompting by using *all* available training data for fine-tuning, but **it deteriorates notably in explanation quality**, even against basic CoT, because saliency-extracted explanations are fragmented and confined to input spans, underscoring the necessity for reasoning-

Table 3: Classification performance (macro-F1, Balanced Accuracy) and Explanation performance (NLI and LLM Judge scores) across datasets. Top: prompt-based; Bottom: fine-tuned methods. The best and runner-up are highlighted in green and blue, resp. **Take-aways:** SPO4SOP substantially outperforms CoT; SFT improves classification, but falls short in explanation; SPO-grounded R-SFT significantly boosts explanation quality over standard SFT, and EXTC achieves the best overall performance across datasets and the majority of metrics.

Method	Family	ContractNLI				ICLR Review				MIMIC Readmission			
		mF1	BAcc	NLI	Judge	mF1	BAcc	NLI	Judge	mF1	BAcc	NLI	Judge
CoT prompt	Zero-shot	0.743	0.757	0.576	4.31	0.789	0.786	0.160	3.18	0.517	0.528	0.045	3.58
SPO4SOP (I)	SPO	0.790	0.789	0.578	4.33	0.795	0.815	0.200	3.32	0.597	0.593	0.178	3.65
SFT	Cls. Head	0.847	0.865	0.243	3.43	0.825	0.832	0.112	2.97	0.609	0.726	0.051	3.36
Reas. Distill. (I+II)	SPO+R-SFT	0.802	0.811	0.576	4.24	0.821	0.821	0.196	3.40	0.620	0.623	0.057	4.29
eXTC (I+II+III)	SPO+R-SFT+RL	0.849	0.882	0.554	4.37	0.825	0.829	0.217	3.44	0.652	0.642	0.057	4.31

Table 4: **PO ablation**. Top: zero-shot CoT baseline; Bottom: hard-PO methods. **Take-aways:** SPO4SOP outperforms zero-shot CoT and matches or exceeds both hard-PO baselines, MIPROv2 and GEPA, producing a structured, decision set of rules.

Method	ContractNLI		ICLR		MIMIC	
	mF1	BAcc	mF1	BAcc	mF1	BAcc
CoT	0.743	0.757	0.789	0.786	0.517	0.528
MIPROv2	0.753	0.767	0.779	0.808	0.541	0.568
GEPA	0.790	0.786	0.790	0.783	0.450	0.499
SPO4SOP	**0.790**	**0.789**	**0.795**	**0.815**	**0.597**	**0.593**

Table 5: **RL ablation**. Top: R-SFT in II (as reference); Bottom: RL variants in III. B/D prefixes denote class-Balanced batching and Dynamic upsampling-and-filter; BD-GRPO (proposed) combines both; +aux adds an LLM-judge auxiliary reasoning reward on top. Column **best** in bold, runner-up underlined. **Take-aways:** RL variants (Stage III) often improve R-SFT (Stage II); class-balancing is beneficial; upsample-then-filter boosts performance; auxiliary reward can be beneficial.

Method	ContractNLI		ICLR		MIMIC	
	mF1	BAcc	mF1	BAcc	mF1	BAcc
R-SFT (**II**)	0.802	0.811	0.821	0.821	0.620	0.623
B-GRPO	0.841	0.877	0.817	0.808	0.645	0.642
D-GRPO	**0.857**	0.871	0.823	0.818	0.586	0.578
BD-GRPO (**III**)	0.849	**0.882**	0.825	0.829	**0.652**	0.642
BD-GRPO+aux	0.829	0.868	**0.827**	**0.834**	0.646	**0.644**

based fine-tuning. In fact, our **SPO-grounded reasoning distillation significantly boosts explanation quality** over end-to-end SFT, by combining Stage I (learned SOP) and Stage II (R-SFT), while maintaining robust classification performance.

EXTC **achieves the best overall performance across datasets and majority of metrics** by further boosting R-SFT model through Stage III (RL with self-guided curriculum). The improvements in classification and explanation performance justify EXTC's modular design, where SPO grounds R-SFT and RL further boosts the result.

4.3 Ablation Analysis

Table 4 compares SPO4SOP, one of our main contributions, with two existing hard PO approaches that do not produce structured SOPs with stand-alone rules. SPO4SOP consistently performs better across datasets, with especially large gains over MIPROv2 on ContractNLI and GEPA on MIMIC.

Table 5 compares Stage III RL variants and Stage II. Combined class (B)alancing and (D)ynamic batch oversampling consistently improve performance. Extending RL's binary label reward with LLM-judge reasoning reward (Apdx. D.4) yields further gains on some, though not all, datasets, suggesting judge quality may vary across domains.

4.4 Case Study

Fig. 1 presents a case from MIMIC, where (a) shows one of the rules in the learned SOP (see full

SOP in Apdx. F) that predicts readmit under the trigger pattern "pending biopsy" *with the exception* of "no confirmed disease". In (b) right, EXTC predicts no_readmit for a test input, based on the reasoning "biopsy with results pending" but with "no indication of malignancy". In contrast, in (b) left, CoT latches on surface information of "pending biopsy" to incorrectly predict readmit. For brevity, Apdx. E.2 gives additional case studies.

Importantly, after teacher distillation, EXTC **no longer** includes the SOP from Stage I in its prompt. Its continued adherence to the learned rules indicates that this knowledge has been internalized through distillation (II), and that RL (III) remains faithful to those rules during exploration.

5 Conclusion

We introduce EXTC, an effective text classifier that provides both local reasoning and a global, modular rulebook. By strategically uniting *structured* prompt optimization, *reasoning-grounded* distillation, and *targeted* reinforcement learning, EXTC captures the best of both worlds: it overall outperforms traditional fine-tuning and prompt-optimization baselines while simultaneously offering high-quality, auditable interpretability.

Limitations

Our work focused on general text corpora, leveraging and further enhancing LLM capabilities for structured prompt optimization, reasoning, and reinforcement learning. However, we recognize that many real-world corpora are inherently multimodal and contain information beyond plain text, such as images, charts, and structured numerical tables, which were not explicitly addressed in this work. Stages I and II rely on proprietary LLMs; reproducing our results requires comparable access. We used temperature 0 where possible to encourage deterministic outputs, but environmental factors may introduce minor variation.

Ethical Considerations

Our approach inherits ethical considerations associated with LLMs, including potential biases in pretrained models, privacy concerns, and risk of misleading or unfaithful generated rationales. Although structured reasoning is designed to facilitate interpretability, in high-stakes applications, outputs should be used with appropriate human oversight and careful evaluation across diverse populations.

AI assistance: We used Claude and ChatGPT for code drafting, debugging, and editorial polishing of this manuscript, with author oversight. All scientific design, experimental protocols, and analyses were performed by the authors.

References

Lakshya A. Agrawal, Shangyin Tan, Dilara Soylu, Noah Ziems, Rishi Khare, Krista Opsahl-Ong, Arnav Singhvi, Herumb Shandilya, Michael J. Ryan, Meng Jiang, Christopher Potts, Koushik Sen, Alex Dimakis, Ion Stoica, Dan Klein, Matei Zaharia, and Omar Khattab. 2026. GEPA: Reflective prompt evolution can outperform reinforcement learning. In *The Fourteenth International Conference on Learning Representations*.

Ilias Chalkidis, Manos Fergadiotis, Prodromos Malakasiotis, Nikolaos Aletras, and Ion Androutsopoulos. 2020. Legal-bert: The muppets straight out of law school. In *Findings of the association for computational linguistics: EMNLP 2020*, pages 2898–2904.

Sanjiv R. Das and Mike Y. Chen. 2007. Yahoo! for amazon: Sentiment extraction from small talk on the web. *Manag. Sci.*, 53(9):1375–1388.

Chenlong Deng, Kelong Mao, Yuyao Zhang, and Zhicheng Dou. 2024. Enabling discriminative reasoning in LLMs for legal judgment prediction. *arXiv preprint arXiv:2407.01964*.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 4171–4186. Association for Computational Linguistics.

Xiang Gao, Yuguang Yao, Qi Zhang, Kaiwen Dong, Avinash Baidya, Ruocheng Guo, Hilaf Hasson, and Kamalika Das. 2026. RIMRULE: Improving tool-using language agents via MDL-guided rule learning. *arXiv preprint arXiv:2601.00086*.

Samuel Gehman, Suchin Gururangan, Maarten Sap, Yejin Choi, and Noah A. Smith. 2020. Realtoxicityprompts: Evaluating neural toxic degeneration in language models. In *EMNLP*.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Peiyi Wang, Qihao Zhu, Runxin Xu, Ruoyu Zhang, Shirong Ma, Xiao Bi, Xiaokang Zhang, Xingkai Yu, Yu Wu, Z. F. Wu, Zhibin Gou, Zhihong Shao, Zhuoshu Li, Ziyi Gao, Aixin Liu, and 175 others. 2025. Deepseek-r1 incentivizes reasoning in llms through reinforcement learning. *Nat.*, 645(8081):633–638.

Mads Henrichsen and Rasmus Krebs. 2025. Two-stage reasoning-infused learning: Improving classification with LLM-generated reasoning. *arXiv preprint arXiv:2507.00214*.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*.

Abhyuday Jagannatha and Hong Yu. 2016. Bidirectional rnn for medical event detection in electronic health records. In *NAACL*.

Ziwei Ji, Nayeon Lee, Rita Frieske, Tiezheng Yu, Dan Su, Yan Xu, Etsuko Ishii, Ye Jin Bang, Andrea Madotto, and Pascale Fung. 2023. Survey of hallucination in natural language generation. *ACM computing surveys*, 55(12):1–38.

Thorsten Joachims. 1998. Text categorization with support vector machines: Learning with many relevant features. In *ECML*.

Alistair E. W. Johnson, Lucas Bulgarelli, Lu Shen, Alvin Gayles, Ayad Shammout, Steven Horng, Tom J. Pollard, Sicheng Hao, Benjamin Moody, Brian Gow, Li-wei H. Lehman, Leo A. Celi, and Roger G. Mark. 2023. Mimic-iv, a freely accessible electronic health record dataset. *Scientific Data*, 10(1).

Omar Khattab, Arnav Singhvi, Paridhi Maheshwari, Zhiyuan Zhang, Keshav Santhanam, Sri Vardhamanan, Saiful Haq, Ashutosh Sharma, Thomas T. Joshi, Hanna Moazam, Heather Miller, Matei Zaharia, and Christopher Potts. 2023. DSPy: Compiling declarative language model calls into self-improving pipelines. *CoRR*, abs/2310.03714.

Hector Kohler, Quentin Delfosse, Waris Radji, Riad Akrour, and Philippe Preux. 2025. Evaluating interpretable reinforcement learning by distilling policies into programs. *arXiv preprint arXiv:2503.08322*.

Narine Kokhlikyan, Vivek Miglani, Miguel Martin, Edward Wang, Bilal Alsallakh, Jonathan Reynolds, Alexander Melnikov, Natalia Kliushkina, Carlos Araya, Siqi Yan, and Orion Reblitz-Richardson. 2020. Captum: A unified and generic model interpretability library for PyTorch. *arXiv preprint arXiv:2009.07896*.

Yuta Koreeda and Christopher D. Manning. 2021. Contractnli: A dataset for document-level natural language inference for contracts. In *Findings of the Association for Computational Linguistics: EMNLP*, Findings of ACL, pages 1907–1919. Association for Computational Linguistics.

Himabindu Lakkaraju, Stephen H. Bach, and Jure Leskovec. 2016. Interpretable decision sets: A joint framework for description and prediction. In *Proceedings of the 22nd ACM SIGKDD international conference on knowledge discovery and data mining*, pages 1675–1684. ACM.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. 2020. Retrieval-augmented generation for knowledge-intensive NLP tasks. In *Advances in Neural Information Processing Systems*.

Zachary C. Lipton. 2018. The mythos of model interpretability. *Communications of the ACM*.

Shih-Yang Liu, Xin Dong, Ximing Lu, Shizhe Diao, Peter Belcak, Mingjie Liu, Min-Hung Chen, Hongxu Yin, Yu-Chiang Frank Wang, Kwang-Ting Cheng, Yejin Choi, Jan Kautz, and Pavlo Molchanov. 2026. GDPO: Group reward-decoupled normalization policy optimization for multi-reward RL optimization. *arXiv preprint arXiv:2601.05242*.

Yang Liu, Dan Iter, Yichong Xu, Shuohang Wang, Ruochen Xu, and Chenguang Zhu. 2023. G-Eval: NLG evaluation using GPT-4 with better human alignment. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics.

Scott M Lundberg and Su-In Lee. 2017. A unified approach to interpreting model predictions. In *Proceedings of the 31st International Conference on Neural Information Processing Systems (NeurIPS)*, pages 4765–4774.

Qing Lyu, Marianna Apidianaki, and Chris Callison-Burch. 2024. Towards faithful model explanation in NLP: A survey. *Computational Linguistics*, 50(2):657–723.

Meghanath Macha and Leman Akoglu. 2018. Explaining anomalies in groups with characterizing subspace rules. *Data Mining and Knowledge Discovery*, 32:1444–1480.

Eric Mitchell, Yoonho Lee, Alexander Khazatsky, Christopher D. Manning, and Chelsea Finn. 2023. Detectgpt: Zero-shot machine-generated text detection using probability curvature. In *International Conference on Machine Learning, ICML 2023, 23-29 July 2023, Honolulu, Hawaii, USA*, Proceedings of Machine Learning Research, pages 24950–24962. PMLR.

OpenAI. 2024. Gpt-4o system card. *CoRR*, abs/2410.21276.

Krista Opsahl-Ong, Michael J Ryan, Josh Purtell, David Broman, Christopher Potts, Matei Zaharia, and Omar Khattab. 2024. Optimizing instructions and demonstrations for multi-stage language model programs. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 9340–9366.

Arjun Panickssery, Samuel R. Bowman, and Shi Feng. 2024. LLM evaluators recognize and favor their own generations. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Reid Pryzant, Dan Iter, Jerry Li, Yin Tat Lee, Chenguang Zhu, and Michael Zeng. 2023. Automatic prompt optimization with "gradient descent" and beam search. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, EMNLP 2023, Singapore, December 6-10, 2023*, pages 7957–7968. Association for Computational Linguistics.

Hude Quan, Vijaya Sundararajan, Patricia Halfon, Andrew Fong, Bernard Burnand, Jean-Christophe Luthi, L. Duncan Saunders, Cynthia A. Beck, Thomas E. Feasby, and William A. Ghali. 2005. Coding algorithms for defining comorbidities in ICD-9-CM and ICD-10 administrative data. *Medical Care*, 43(11):1130–1139.

Marco Túlio Ribeiro, Sameer Singh, and Carlos Guestrin. 2016. "why should I trust you?": Explaining the predictions of any classifier. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, San Francisco, CA, USA, August 13-17, 2016*, pages 1135–1144. ACM.

Cynthia Rudin. 2019. Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead. *Nat. Mach. Intell.*, 1(5):206–215.

Said Salloum, Tarek Gaber, Sunil Vadera, and Khaled Shaalan. 2022. A systematic literature review on phishing email detection using natural language processing techniques. *Ieee Access*, 10:65703–65727.

Konstantinos Sechidis, Grigorios Tsoumakas, and Ioannis P. Vlahavas. 2011. On the stratification of multi-label data. In *Machine Learning and Knowledge Discovery in Databases (ECML PKDD)*, volume 6913 of *Lecture Notes in Computer Science*, pages 145–158.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *CoRR*, abs/2402.03300.

Guangming Sheng, Chi Zhang, Zilingfeng Ye, Xibin Wu, Wang Zhang, Ru Zhang, Yanghua Peng, Haibin Lin, and Chuan Wu. 2024. HybridFlow: A flexible and efficient RLHF framework. *arXiv preprint arXiv:2409.19256*.

Zhiqing Sun, Yikang Shen, Hongxin Zhang, Qinhong Zhou, Zhenfang Chen, David Cox, Yiming Yang, and Chuang Gan. 2024. SALMON: Self-alignment with instructable reward models. In *International Conference on Learning Representations (ICLR)*.

Liyan Tang, Philippe Laban, and Greg Durrett. 2024. MiniCheck: Efficient fact-checking of LLMs on grounding documents. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*.

Gemini Team. 2025a. Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, long context, and next generation agentic capabilities. *CoRR*, abs/2507.06261.

Qwen Team. 2025b. Qwen3 technical report. *CoRR*, abs/2505.09388.

Rushil Thareja, Gautam Gupta, Francesco Pinto, and Nils Lukas. 2026. MAC: Multi-agent constitution learning. *arXiv preprint arXiv:2603.15968*.

Sowmya Vajjala and Shwetali Shimangaud. 2025. Text classification in the llm era–where do we stand? *arXiv preprint arXiv:2502.11830*.

Carl van Walraven, Irfan A. Dhalla, Chaim Bell, Edward Etchells, Ian G. Stiell, Kelly Zarnke, Peter C. Austin, and Alan J. Forster. 2010. Derivation and validation of an index to predict early death or unplanned readmission after discharge from hospital to the community. *CMAJ*, 182(6):551–557.

Luping Wang, Sheng Chen, Linnan Jiang, Shu Pan, Runze Cai, Sen Yang, and Fei Yang. 2025a. Parameter-efficient fine-tuning in large language models: a survey of methodologies. *Artif. Intell. Rev.*, 58(8):227.

Ruochen Wang, Si Si, Felix X. Yu, Dorothea Wiesmann Rothuizen, Cho-Jui Hsieh, and Inderjit S. Dhillon. 2025b. Large language models are interpretable learners. In *The Thirteenth International Conference on Learning Representations, ICLR 2025, Singapore, April 24-28, 2025*. OpenReview.net.

Xinyuan Wang, Chenxi Li, Zhen Wang, Fan Bai, Haotian Luo, Jiayou Zhang, Nebojsa Jojic, Eric P. Xing, and Zhiting Hu. 2024. Promptagent: Strategic planning with language models enables expert-level prompt optimization. In *The Twelfth International Conference on Learning Representations, ICLR 2024, Vienna, Austria, May 7-11, 2024*. OpenReview.net.

Bowen Wei, Mehrdad Fazli, and Ziwei Zhu. 2025. Learning to explain: Prototype-based surrogate models for LLM classification. *arXiv preprint arXiv:2505.18970*.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed H. Chi, Quoc V. Le, and Denny Zhou. 2022. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems*.

Rong Wu, Xiaoman Wang, Jianbiao Mei, Pinlong Cai, Daocheng Fu, Cheng Yang, Licheng Wen, Xuemeng Yang, Yufan Shen, Yuxin Wang, and Botian Shi. 2025. Evolver: Self-evolving LLM agents through an experience-driven lifecycle. *CoRR*, abs/2510.16079.

Peng Xia, Jianwen Chen, Hanyang Wang, Jiaqi Liu, Kaide Zeng, Yu Wang, Siwei Han, Yiyang Zhou, Xujiang Zhao, Haifeng Chen, Zeyu Zheng, Cihang Xie, and Huaxiu Yao. 2026. SkillRL: Evolving agents via recursive skill-augmented reinforcement learning. *arXiv preprint arXiv:2602.08234*.

Tim Z Xiao, Robert Bamler, Bernhard Schölkopf, and Weiyang Liu. 2024. Verbalized machine learning: Revisiting machine learning with language models. *arXiv preprint arXiv:2406.04344*.

Qiying Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, Yu Yue, Tiantian Fan, Gaohong Liu, Lingjun Liu, Xin Liu, Haibin Lin, Zhiqi Lin, Bole Ma, Guangming Sheng, Yuxuan Tong, Chi Zhang, Mofan Zhang, Wang Zhang, Hang Zhu, and 16 others. 2025. DAPO: an open-source LLM reinforcement learning system at scale. *CoRR*, abs/2503.14476.

Mert Yüksekgönül, Federico Bianchi, Joseph Boen, Sheng Liu, Pan Lu, Zhi Huang, Carlos Guestrin, and James Zou. 2025. Optimizing generative AI by backpropagating language model feedback. *Nat.*, 639(8055):609–616.

Daoze Zhang, Zhijian Bao, Sihang Du, Zhiyi Zhao, Kuangling Zhang, Dezheng Bao, and Yang Yang. 2025. Re^2: A consistency-ensured dataset for full-stage peer review and multi-turn rebuttal discussions. *arXiv preprint arXiv:2505.07920*.

Yaowei Zheng, Richong Zhang, Junhao Zhang, Yanhan Ye, and Zheyan Luo. 2024. Llamafactory: Unified efficient fine-tuning of 100+ language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 3: System Demonstrations), ACL 2024, Bangkok, Thailand, August 11-16, 2024*, pages 400–410. Association for Computational Linguistics.

Appendix

A Extended Related Work

Much of the related work is already referenced in the main text, and here we provide an extended discussion. Table 6 outlines directly-relevant prior work along five *methodology* axes (PO, SPO, SFT, RL, RL→R rule mining) and three *capability* axes (global/model-level explanation, local/instance-level explanation, inference efficiency). Each existing work covers only a strict subset of these axes; *no* prior system jointly delivers global and instance-level interpretability for complex text classification with a deployment-efficient student.

Structured prompt optimization. Prompt optimization has evolved from token-level rewriting (Pryzant et al., 2023) to text-as-parameter approaches that treat the prompt as a learnable artifact under verbalized feedback (Xiao et al., 2024; Yüksekgönül et al., 2025). Representative methods MIPROv2 (Opsahl-Ong et al., 2024) and GEPA (Agrawal et al., 2026) optimize over unstructured instruction strings; a parallel line targets *structured* rule-sets, including LSP (Wang et al., 2025b) and MAC (Thareja et al., 2026). These structured baselines still select a per-input rule *subset* and concatenate the selected rules during inference (tree traversal in LSP, agentic re-selection in MAC). In contrast, our SOP is a *composable* rule set, applied uniformly at inference, and atomic, stand-alone, and fully present—so the rule set itself could serve as a global explanation.

Reasoning distillation and RL on reasoning. Chain-of-thought supervision (Wei et al., 2022) underpins reasoning-distillation pipelines that fine-tune students on teacher rationales (Henrichsen and Krebs, 2025; Deng et al., 2024). Beyond distillation, group-based policy optimization (GRPO, Shao et al., 2024; DAPO, Yu et al., 2025) and verifiable-reward RL (DeepSeek-R1, Guo et al., 2025) improve reasoning quality beyond the teacher; a separate line uses learned reward models to align LLMs with high-level principles (SALMON, Sun et al., 2024), targeting alignment rather than task-specific reasoning. Our Stage II conditions the teacher on the SOP so that the student inherits a rule-grounded chain of thought; Stage III then uses BD-GRPO to concentrate learning on the hard examples the SOP alone cannot resolve.

Interpretable text classification. Traditional interpretability is post-hoc: feature-attribution methods such as LIME (Ribeiro et al., 2016) and SHAP (Lundberg and Lee, 2017), and gradient/saliency-style scoring (Lyu et al., 2024) explain a black-box decision token-by-token but offer no global model-level account (Rudin, 2019). A newer line pursues either global rulebooks (LSP, MAC; see above) or instance-level rationales such as prototype surrogates (Wei et al., 2025); few provide both global and local explanations within a single deployment-efficient student model.

Rule mining from RL rollouts. A nascent line recovers interpretable artifacts from trained policies: distilling neural agents into programs (Kohler et al., 2025) and tool-using agents that consolidate failure traces via MDL-guided rules (Gao et al., 2026). Most closely related are agent-side rulebook learners EvolveR (Wu et al., 2025) and SkillRL (Xia et al., 2026). In contrast, eXTC loops RL-mined rules back into the global SOP for text classification.

B EXTC Details

This appendix expands on EXTC's Stage I structured prompt optimization with SPO4SOP (Apdx. B.1) and Stage III reinforcement learning with BD-GRPO (Apdx. B.2).

B.1 Proposed Structured Prompt Optimization: Details

We elaborate on SPO4SOP (Stage I): an overall flow diagram of the algorithm (Apdx. B.1.1), the rule-subset selection step that picks the inference-time working set (Apdx. B.1.2), and a scalability analysis showing the procedure scales linearly in the number of candidate rules (Apdx. B.1.3).

B.1.1 Flow Diagram

Fig. 6 illustrates the main components and the workflow of SPO4SOP algorithm designed for EXTC's Stage I.

B.1.2 Rule Subset Selection: Details

Given the persistent pool $\mathcal{P}_t := \mathcal{P}_{t-1} \cup \mathcal{C}$ accumulating all candidate rules generated through iteration t (including the previous pool $\mathcal{P}_{t-1}$ and the (updated as well as new) candidates $\mathcal{C}$ from this iteration), the next step is to select a small subset $\mathcal{S} \subseteq \mathcal{P}_t$ that achieves low classification error on the held-out validation data $\mathcal{D}_{\text{val}}$.

Table 6: Related work comparison. **Columns**: SPO = structured PO; RL→R = rule mining from RL rollouts; **Global** ✓ requires a decomposable structured artifact (rule list / decision tree / program) inspectable without running the model; **Instance** ✓ requires a per-example reasoning trace grounded in that artifact (CoT / applied-rule trace / decision path). **Symbols**: ✓ = property fully satisfied; blank = absent; (✓) (SPO column only) marks methods whose rules are structured but concatenated into one prompt or routed per input rather than applied as an independently-composable rule set.

Paper	Task	Venue	Method					Capability			Total
			PO	SPO	SFT	RL	RL→R	Global	Instance	Infer. eff.	
Ours	Class.	—	✓	✓	✓	✓	✓	✓	✓	✓	**8/8**
EvolveR (Wu et al., 2025)	Agent	arXiv'25-10	✓	(✓)	✓	✓	✓			✓	6/8
MAC (Thareja et al., 2026)	Class.	arXiv'26-03	✓	(✓)	✓			✓		✓	5/8
DeepSeek-R1 (Guo et al., 2025)	Reason.	Nature'25			✓	✓			✓	✓	4/8
LSP (Wang et al., 2025b)	Class.	ICLR'25	✓	(✓)				✓	✓		4/8
SkillRL (Xia et al., 2026)	Agent	arXiv'26-02				✓	✓			✓	3/8
RIMRULE (Gao et al., 2026)	Agent	arXiv'26-01	✓	(✓)				✓			3/8
SALMON (Sun et al., 2024)	Align.	ICLR'24			✓	✓					2/8
GEPA (Agrawal et al., 2026)	General	ICLR'26	✓								1/8
MIPROv2 (Opsahl-Ong et al., 2024)	General	NeurIPS'24	✓								1/8

Figure 6: EXTC**'s Stage I:** SPO4SOP for structured prompt (i.e. decision (rule) set $\mathcal{R}$) optimization consists of two main primitives: **(1) Decision Rule & Rule Set Expansion** employs Gradient and Update LLMs on misclassifications to obtain updated and new candidate rules, and **(2) Rule Subset Selection** employs Beam-Search over the persistent pool $\mathcal{P}_t$ of all accumulated candidate rules to maximize macro-F1 on the validation set. Thanks to composable decisions, individual rule predictions by Classifier LLM are cached and composed efficiently to evaluate potential rule subsets— allowing search over a combinatorial space while keeping the number of LLM calls linear in the number of rules, rather than in the exponentially many possible rule *subsets*.

To compute classification error, we first obtain individual predictions $\widehat{y}_{ij} := R_j(\mathbf{x}_i)$ of each rule on each sample. Importantly, these standalone *predictions are composed easily and efficiently for any subset of rules* via max-pooling to reach the final prediction—thanks to the *composability* of deci-sion sets (Definition 1). Decision composition is a key notion in our design that fosters efficiency; we simply obtain predictions for the newly added candidate rules $\mathcal{C}$ *only*, as they are generated, and **cache** these to be used in composition during sub-set search (Line 21), while the $\widehat{y}_{ij}$ cache readily

contains predictions for the rules in $\mathcal{P}_{t-1}$ from previous iterations.

The persistent pool $\mathcal{P}_t := \mathcal{P}_{t-1} \cup \mathcal{C}$ (Line 20), which accumulates all candidates generated through iteration t, is used within a beam search for subset selection (Line 22). Letting $|\mathcal{P}_t| = m$ and the binary *variable* $z_j \in \{0, 1\}$ be the indicator for the j'th rule being selected, Eq. 5 depicts the optimization model. In the objective function, $l(\widehat{\mathbf{y}}, \mathbf{y})$ denotes the task-specific loss (macro-F_1 in our experiments), where $\mathbf{y}$ and $\widehat{\mathbf{y}}$ denote the label vector and the composed prediction vector over the dataset, respectively. The second term encourages the sparsity of rule selection, where λ controls the trade-off between the classification loss and the subset size. A small set promotes interpretability and encourages semantic diversity among the rules.

$$
\min_{z_j \in \{0,1\}, j \in [m]} l(\widehat{\mathbf{y}}, \mathbf{y}) + \lambda \sum_j z_j \quad \text{s.t.}
$$
$$
\widehat{y}_i = \begin{cases} \max_{j \in [m]} \{z_j \cdot \widehat{y}_{ij}\}, & \text{binary}, \\ \arg\max_{j \in [m]} \{z_j \cdot p(\widehat{y}_{ij})\}, & \text{multi-class} \end{cases} \quad (5)
$$

We remark that the beam search does not necessarily return the optimal subset if the beam size is not large enough. Arguably, we do not need the global optimum in practice as it might lead to overfitting (especially given that the validation set is typically small in prompt-optimization settings).

For the optimal subset returned after the last iteration (Line 24), one can in principle linearize the formulation in Eq. 5 and solve it exactly. In practice, we use the beam-search approximation described above throughout.

B.1.3 Scalability Analysis

The key computational bottleneck of SPO4SOP is the rule subset search primitive, not the rule & rule set expansion primitive (see Fig. 6). The latter's LLM calls for the "gradient" "updates" are negligible since those (i) are over a mini-batch of samples $\mathcal{D}_{\text{batch}}$, and ($ii$) involve Gradient LLM calls only for misclassified samples in the batch, while (iii) Update LLM is called once per rule in Line 11 and only once in Line 18.

This section shows that rule subset search via beam search is scalable, in fact, linear in the number of candidates (as opposed to exponential in the number of possible subsets). We restate the lemma from §3.2 and prove it here.

Lemma 2 (Scalable subset search, restated). *SPO4SOP's rule subset search scales linearly with the number of candidate rules m, rather than with the exponential number of possible rule subsets. This is enabled by decision composition (Definition 1), which requires only a linear number of LLM calls in m to obtain decisions for arbitrary rule subsets.*

Proof. As a decision set, our structured prompt design enables *composable* label assignment and consequently, scalable search. In particular, our decision set consists of standalone rules, which allows us to predict each sample by each rule in the set *independently*. This allows independent LLM calls, using a prompt composed of a single rule at a time (meanwhile reducing context length), to obtain predictions for n samples by m' additional candidate rules in $\mathcal{C}$, which we *cache*. Note that the predictions by the existing $(m-m')$ rules in $\mathcal{P}_{t-1}$ are already cached in previous iterations. Overall, subset selection necessitates nm Classifier LLM calls *prior to* beam search (Line 21, Algorithm 1).

For beam search with width b, expansion at depth d yields $b(m-d)$ subset candidates to evaluate (the objective in Eq. 5). Having cached existing b subsets' predictions of n samples, adding a new rule to a subset takes $O(1)$ time per sample to update its prediction—by picking the maximum of the current/cached prediction and the new rule's prediction (also cached). Over K steps of the beam search, $O(bKm)$ subsets are evaluated, *without any additional LLM calls*, saving $O(bKmn)$ LLM calls over the course of the search.

In effect, decision composition allows us to search in a combinatorially large space while necessitating the number of LLM calls to be only **linear** in the number of rules m—and **not** in the exponential number of rule subsets. $\square$

In comparison, prior prompt optimization algorithms (Pryzant et al., 2023; Wang et al., 2024; Xiao et al., 2024; Yüksekgönül et al., 2025) can only evaluate entire prompts, as they lack compositionality. In theory, searching the same prompt space would require these existing approaches $O(2^m n)$ LLM calls, compared to $O(mn)$ by SPO4SOP.

B.2 Reinforcement Learning: Details

This section provides additional analysis of the RL stage: per-dataset training dynamics (Apdx. B.2.1) and the procedure for folding RL-derived findings back into the SOP (Apdx. B.2.2).

Table 7: Full version of Table 1: rollout-outcome distribution per hard/easy group at the start of RL on all three datasets (*G*=8).

Dataset	Diff.	Rollouts correct (%)			% of band
		0/G	1–7/G	G/G	
ContractNLI	hard	32.9	63.6	3.5	30.5
	easy	0.4	19.0	80.6	69.5
	all	4.2	24.1	71.7	(11.6% nat.)
ICLR Review	hard	54.0	43.6	2.4	29.5
	easy	0.7	18.1	81.2	70.5
	all	8.6	21.9	69.5	(14.8% nat.)
MIMIC Readmit	hard	65.3	33.7	1.0	24.4
	easy	1.4	27.1	71.5	75.6
	all	14.6	28.5	57.0	(20.6% nat.)

Figure 8: RL training dynamics on MIMIC Readmission, parallel to Fig. 5. Entropy decreases from ∼0.55 to ∼0.36 but stays well above collapse, KL remains small (≤0.20), *hard-pool correct rate roughly doubles from ∼0.08 to ∼0.19* then plateaus, easy-pool correct rate largely retained (∼0.81–0.85) with brief late-stage dips—consistent with the same hard-band learning pattern.

B.2.2 Rulebook Revision

The SOP learned by SPO4SOP (Apdx. B.1) covers most inputs but leaves a residual error band of *hard* inputs where the post-RL model reasons correctly while a teacher applying the current SOP does not. The Rulebook Revision pipeline distills these residual strategies into candidate SOP rules in five stages: (1) collect correct RL rollouts on hard inputs; (2) cluster them by reasoning strategy via three independent LLM rounds followed by a merge pass; (3) assign each rollout to one cluster; (4) synthesize one candidate rule per (cluster, target label); (5) deduplicate near-equivalent candidates within each cluster.

All five stages are LLM-driven; the per-stage prompts are listed in Apdx. C.6. Stage 2 asks the LLM to describe an analytical *strategy* (the reasoning method, not the input topic): three independent rounds plus a merge pass reduce single-round variance. Stage 3 bins each rollout into one strategy cluster. Stage 4 is the core synthesis call: per cluster, the LLM is shown *paired* traces (teacher-incorrect vs. RL-correct on the same inputs) with a stratified mix of positive (gold = target label) and negative (gold ≠ target label) examples; a SKIP gate suppresses candidates with insufficient signal for the target label. Stage 5 is a pairwise LLM equivalence judge that collapses near-duplicate candidates within a cluster.

Figure 7: RL training dynamics on ICLR Review, parallel to Fig. 5. Entropy stays bounded (briefly dips around step 80 then rises to ∼0.60, no collapse), KL grows but remains small (≤0.20), *hard-pool correct rate rises steadily from ∼0.08 to ∼0.23 (∼3×)*, easy-pool correct rate preserved (∼0.93).

B.2.1 RL Dynamics

At the start of RL, Table 7 extends the hardness × rollout-correctness cross-tab of Table 1 (ICLR Review in the main body) to all three datasets, characterizing the informative band before any training step is taken.

Over the course of training, §3.4 (Fig. 5) shows ContractNLI as a representative example; Figs. 7 and 8 report the same four training-dynamics curves (actor entropy, KL to reference, hard-pool correct rate, easy-pool correct rate) over rollout rounds for the other two datasets. All RL training curves are exponentially-moving-average (EMA) smoothed with α=0.99 for the hit-rate metrics and α=0.95 for entropy and KL.

Method	ContractNLI		ICLR Review		MIMIC Readmit	
	mF1	BAcc	mF1	BAcc	mF1	BAcc
CoT (no rules)	0.143	0.150	0.312	0.255	0.321	0.437
RL→R rules	**0.255**	**0.335**	**0.468**	**0.495**	**0.355**	**0.505**

Table 8: Evaluation of the RL→R-selected rules on *test_hard* (test examples on which the teacher with the existing SOP fails all $M=4$ attempts). Per-dataset sizes are $n=235$ / 195 / 108 for ContractNLI / ICLR Review / MIMIC Readmit. CoT = zero-shot teacher (no rules).

Selection on *val_hard*. From the candidate rule set, we apply the same beam-search SubsetSelect logic used by SPO4SOP (Apdx. B.1.2) to choose the final additions, but with the validation pool restricted to *val_hard* — the val examples on which the teacher applying the existing SOP fails all $M=4$ attempts. Restricting selection to *val_hard* avoids reusing the train-hard signal that the RL model already exploited during training, and isolates the marginal value of the new rules on examples the existing SOP cannot solve.

Evaluation on *test_hard*. We evaluate the selected rules (max-pool composed with the existing SOP, per Eq. 5) on the analogously-defined *test_hard* subset, against the CoT baseline (zero-shot teacher, no rules). For ICLR Review, the teacher with the existing SOP over-predicts `reject` on hard inputs (91% of val_hard has gold = `accept`); we therefore synthesize label-accept rules to push toward the under-served direction. Table 8 shows that the new rules consistently improve both macro-F1 and balanced accuracy over CoT across all three datasets.

C   Prompt Templates and Instructions

C.1   Generic prompt templates

These templates are shared across all three datasets, with per-dataset placeholders ({task_framing}, {input_tag}, {input_noun}, {labels}) substituted from Table 9. The *Reasoning Prompt with Rules* drives the R-SFT teacher (uses the learned SOP); the *Reasoning Prompt without Rules* is used by the zero-shot CoT baseline, the R-SFT student, and during RL; and the *Classification (Label-Only) Prompt* is used when SFT runs with a classification head instead of generative decoding.

Reasoning Prompt with Rules (R-SFT teacher)

Below is a rulebook of patterns relevant to the task. Treat the rulebook as internal guidance — it shapes what to look for in the {input_noun}, but should not be cited in your reasoning.
`<RULES>`
{rulebook}
`</RULES>`
{input_tag}
{text}
`</...>`
When writing your reasoning, analyze the {input_noun} directly. Do not name or enumerate rules in your reasoning.
Return exactly in this format:
REASONING:
your reasoning
LABEL: `<one of {labels}>`
Please think step by step.

Reasoning Prompt without Rules (CoT baseline / R-SFT student / RL)

{task_framing}
{input_tag}
{text}
`</...>`
Analyze the {input_noun} directly to decide the label.
Return exactly in this format:
REASONING:
your reasoning
LABEL: `<one of {labels}>`
Please think step by step.

Classification (Label-Only) Prompt (SFT classification head)

{task_framing}
{input_tag}
{text}
`</...>`
Return exactly:
LABEL: `<one of {labels}>`

C.2   SPO4SOP meta-prompt: Classifier LLM

The Classifier LLM is invoked once per (sample, rule) pair: it sees a single rule at a time and returns whether the rule fires (label {RULE_LABEL}) or abstains (label {ABSTAIN}). Task framing is supplied via the system prompt (the same one used by the SFT teacher above). For multi-class tasks (e.g. CONTRACTNLI, 3 classes), the last sentence of the output spec asks the model to first conclude any class, then output the rule's target label only if its conclusion matches it.

C.3 SPO4SOP **meta-prompts: Gradient LLM**

The Gradient LLM is invoked in two modes, depending on the error type. Both share the structured-field output convention; the bullet-pointed `exceptions` / `points` are then forwarded to the Update LLM.

C.4 SPO4SOP **meta-prompt: Update LLM rule revision (false coverage)**

The Update LLM consumes the Gradient LLM's exception bullets and emits a revised rule, formatted with a <RULE_NAME> / <RULE_DESCRIPTION> schema used elsewhere in the pipeline.

> **Rule Update — False Coverage (Update LLM)**
>
> Your task is to generate a new rule to avoid overly broad coverage mistakes by augmenting the exceptions and examples in an existing rule. Follow these steps:
> Review the provided existing rule:
> ```
> <EXISTING_RULE>
> {RULE}
> </EXISTING_RULE>
> <EXCEPTION_NOTES>
> {EXCEPTIONS}
> </EXCEPTION_NOTES>
> ```
> Keep the rule label unchanged as {RULE_LABEL}.
> Identify the core pattern or principle that led to the mistake described in the existing rule.
> Determine any exceptions where the rule should not apply.
> Formulate a new rule using the following structure:
> ```
> <RULE_NAME>[Concise,    descriptive    new
> name]</RULE_NAME>
> <RULE_DESCRIPTION>
> Trigger Pattern:
> [Keep original pattern in the existing rule,
> clarify if needed]
> Exceptions:
> [Keep original exceptions]
> [Add new exceptions to restrict over-broad
> coverage]
> Examples
> [Keep existing examples]
> [Add new examples if needed]:
> Source text: [Relevant source text if any]
> Wrong:   [Example of violation]
> Correct: [Example of compliance]
> </RULE_DESCRIPTION>
> ```
> Ensure the rule has a new name.

> **New Rule Synthesis — Blind Spot (Update LLM)**
>
> You are an expert at analyzing patterns and developing precise rules for {CLASSIFICATION_TASK}. Your task is to systematically evaluate error patterns and create a clear, actionable and strict rule to prevent similar mistakes in future classifications.
> The goal is to identify the truly exceptional instances, not just average ones.
> Generate rules with label {TARGET_LABEL}.
> Return at most {MAX_NEW_RULES} new rule(s).
> Review the existing rules:
> ```
> <EXISTING_RULES>
> {RULES}
> </EXISTING_RULES>
> ```
> Error patterns from misclassifications:
> ```
> <ERROR_PATTERNS>
> {ERROR_PATTERNS}
> </ERROR_PATTERNS>
> ```
> First, conduct a structured error analysis:
> ```
> <ERROR_ANALYSIS>
> 1. Context Assessment
> What was the intended behavior?
> What actually happened?
> What key factors contributed?
> 2. Rule Evaluation
> Do existing rules partially cover this?
> What aspects are unique?
> How can we make the rule robust?
> </ERROR_ANALYSIS>
> ```
> Provide the error analysis in the error_analysis field.
> Then, formulate a new rule using this structure:
> ```
> <RULE_NAME>[Concise,  descriptive  name  that
> clearly identifies the pattern]</RULE_NAME>
> <RULE_DESCRIPTION>
> Trigger Pattern: [Clear description of when
> this rule applies, with 2-3
> specific indicators that should trigger the
> rule]
> Exceptions: [Specific cases where the rule
> should not be applied, even if
> the pattern appears to match]
> Example [One clear example]:
> Source text: [Relevant source text if any]
> Wrong:   [Example of violation]
> Correct: [Example of compliance]
> </RULE_DESCRIPTION>
> ```
> Please analyze the error examples thoroughly and formulate a new rule that would prevent similar classification errors in the future.

C.5 SPO4SOP meta-prompt: Update LLM new rule synthesis (blind spot)

When no rule fires on a misclassified example, the Update LLM is prompted to synthesize one or more brand-new rules from the Gradient LLM's error patterns, grouped by target label.

C.6 Rulebook Revision meta-prompts

The Rulebook Revision pipeline (Apdx. B.2.2) distills new candidate SOP rules from post-RL behavior on hard inputs. Five LLM-driven stages are used; the per-stage prompts follow.

Rulebook Revision — Strategy Taxonomy Discovery (Stage 2)

You are analyzing reasoning traces from a model trained with reinforcement learning to improve on hard examples.
<TASK>
{TASK_DESCRIPTION}
</TASK>
Below are {NUM_SAMPLES} correct reasoning traces from different input categories:
{ROLLOUT_ENTRIES}
Identify the distinct REASONING STRATEGIES used across these traces.
A reasoning strategy is a reusable analytical METHOD — how the model reasons, not what specific input topic it reasons about. Group by HOW the model reasons (analytical method), not by WHAT topic or input content it reasons about. Traces on different topics that use the same analytical approach belong to the same strategy. Two traces that reach the same conclusion via different analytical paths count as different strategies.
For each strategy, output in this exact format:
<STRATEGY id="N">
Analysis: [Describe the shared analytical method across traces
that use this strategy. What steps does the reasoning
follow? What makes it distinct from other strategies?
Do not reference specific input topics — describe the
abstract pattern.]
Label: [3-6 word name for this strategy]
</STRATEGY>
Identify as many genuinely distinct strategies as you find. Do not force a predetermined number.

Rulebook Revision — Strategy Taxonomy Merge (Stage 2)

Below are reasoning strategy taxonomies discovered in three independent rounds of analysis on the same set of model reasoning traces. Many strategies across rounds describe the same underlying analytical pattern in different words.
Round 1:
{ROUND_1_STRATEGIES}
Round 2:
{ROUND_2_STRATEGIES}
Round 3:
{ROUND_3_STRATEGIES}
Merge these into a single deduplicated taxonomy.

- Merge strategies that describe the SAME analytical method, even if worded differently. Keep the clearest analysis.

- Keep strategies that are genuinely distinct — do not force-merge strategies that differ in analytical approach just because they sound vaguely similar.

- If a strategy from one round is a sub-case of a broader one, keep the broader one and note the sub-case in its analysis.

Output the merged taxonomy:
<STRATEGY id="N">
Analysis: [Merged analysis. Note which round entries were merged.]
Label: [3-6 word name]
</STRATEGY>
Output as many strategies as the data warrants.

Rulebook Revision — Rollout Classification (Stage 3)

<TASK>
{TASK_DESCRIPTION}
</TASK>
Reasoning strategies:
{TAXONOMY}
Reasoning trace to classify:
{REASONING}
Which strategy does this trace primarily use? Output ONLY the strategy id (a number), or "OTHER" if none fits well.

C.7 Per-dataset placeholders

D Experiment Setup Details

This appendix gives the full setup behind §4: dataset construction and splits (Apdx. D.1), model and training configurations for all baselines and EXTC variants (Apdx. D.2), evaluation metrics (Apdx. D.3), and LLM-judge details with full prompts (Apdx. D.4).

D.1 Dataset Description

ContractNLI (Koreeda and Manning, 2021).[2] We use the Stanford ContractNLI corpus, comprising 10,319 (contract, hypothesis) pairs over 607 non-disclosure agreements. Each instance carries a human-labeled evidence span—the contiguous portion of the contract that supports the label—used as ground truth for our NLI- and judge-based explanation metrics. We use the official train/dev/test split (7,191 / 1,037 / 2,091).

ICLR_Reviews.[3] Sourced from the Re[2] corpus (Zhang et al., 2025), which aggregates peer-review records across 24 conferences and 21 workshops on OpenReview (including NeurIPS, ACL, and others). We restrict to ICLR main-conference rows (workshops, tiny-papers, and blog tracks are excluded) and keep all venue-matched papers in the official Re[2] train/test split, additionally carving out an in-distribution validation set from train. The

---

[2] https://stanfordnlp.github.io/contract-nli/
[3] https://huggingface.co/datasets/Daoze/ReviewRebuttal

Table 9: Per-dataset values for the placeholders used in the generic prompt templates above.

Placeholder	ContractNLI	ICLR Review	MIMIC Readmission
`{input_tag}`	`<CONTRACT_HYPOTHESIS_PAIR>`	`<REVIEWER_COMMENTS>`	`<DISCHARGE_SUMMARY>`
`{input_noun}`	contract text and the hypothesis	reviewer comments	discharge summary
`{labels}`	not_mentioned / entailment / contradiction	accept / reject	readmitted / not_readmitted

resulting split is 8,552 / 1,000 / 655 for the binary *accept*/*reject* task. Year coverage is inherited from Re^2: train/val span ICLR 2017, 2018, 2020–2023; test spans ICLR 2020–2023 only (no test rows from 2017/2018; ICLR 2019 appears in Re^2 as workshops only and is filtered out; ICLR 2024 is absent from Re^2). Each paper's evidence is its official meta-review summary; reviewer texts (input) and meta-review (evidence) are disjoint.

MIMIC_Readmission.[4] Built from MIMIC-IV v3.1 (Johnson et al., 2023) discharge summaries. We subsample 10,000 admissions via patient-level iterative multi-label stratification (Sechidis et al., 2011) jointly balancing the binary readmission label and the discharge service, yielding an 8,000 / 1,000 / 1,000 train/val/test split with no patient overlap across splits. Evidence is a structured per-admission summary aligned to the LACE (van Walraven et al., 2010) schema; comorbidities are mapped from `diagnoses_icd` via Quan-2005 Charlson coding (Quan et al., 2005), and the ED component is proxied by 6-month inpatient admission counts (MIMIC-IV's ED module is unaligned with our cohort). Output format and per-field formulas follow LACE conventions; see the released code for exact mapping.

Licenses, intended use, and de-identification. All datasets and tools are used in compliance with their licenses, for non-commercial research only, consistent with their intended use. **MIMIC-IV** requires PhysioNet credentialed access under the PhysioNet Credentialed Health Data License v1.5.0; we obtained this access via the standard CITI training and Data Use Agreement and do not redistribute any record-level data. MIMIC-IV is de-identified per HIPAA Safe Harbor by the dataset providers; we did no additional re-identification or aggregation steps. **ContractNLI** uses publicly redacted NDAs and **ICLR Review** uses public OpenReview metadata, neither of which contains personal identifiers beyond the original public release. **Qwen3-4B** is released under Apache-2.0; Captum, MiniCheck, and DSPy under per-

[4] https://physionet.org/content/mimiciv/3.1/

missive open-source licenses (BSD/MIT). Closed-source LLMs (gpt-4.1-mini, gpt-4o-mini, gemini-2.5-flash-lite) are accessed via OpenAI / Google APIs in compliance with their terms of service.

TRAIN/VAL SPLITS PER METHOD. SPO4SOP and PO baselines (MIPROv2, GEPA) were run on the same 180-row class-balanced PO-train and 400-row natural-ratio PO-val, across each dataset. Both PO-train and PO-val are subsets of the training set; this is to prevent pollution of the validation set in stages II and III. R-SFT and RL use the full training and validation sets (see Table 2).

D.2 Model Configuration Details

Tables 10 and 11 summarize the hyperparameters of all fine-tuning (FT) and prompt-optimization (PO) methods, respectively. All FT runs share the same student backbone (Qwen3-4B) and hardware (4× H100 80GB). SFT (Cls. Head) is trained full-parameter with the HuggingFace Trainer (`AutoModelForSequenceClassification`); R-SFT uses LlamaFactory (Zheng et al., 2024); RL uses verl (Sheng et al., 2024) with our custom sampler that supports upsampling and group-decoupled auxiliary reward. For all FT methods we retain the checkpoint with the best validation macro-F_1 and report all numbers on the held-out test set under this selection. All FT methods use the AdamW optimizer with mixed-precision (bf16) training and a single random seed (42). For BD-GRPO, the per-class quota n_c is set to $\lfloor B/C \rfloor$ with a rotating remainder when $B \nmid C$, where $B=16$ is the effective batch size and $C \in \{2, 3\}$ is the number of classes (e.g., 8/8 for binary, 6/5/5 for 3-class).

PO baseline implementation and metric choice. We invoke MIPROv2 and GEPA through the official DSPy framework (Khattab et al., 2023). Both methods are designed around per-sample scalar feedback and cannot natively optimize aggregate metrics such as macro-F_1 or balanced accuracy. We therefore use the binary `correctness` signal (1 if the predicted label matches the gold label, 0 otherwise), equivalent to optimizing accuracy. Neither baseline is aware of class imbalance during

Table 10: Fine-tuning method hyperparameters. RL uses verl GRPO with dynamic oversample-then-filter on top of an R-SFT-merged initialization. RL ablation variants (class balance, dynamic filter, auxiliary reward) and their specific configurations are detailed in Table 12.

	SFT (Cls. Head)	R-SFT	RL (EXTC)
Backbone	Qwen3-4B	Qwen3-4B	Qwen3-4B (R-SFT init)
Fine-tuning	Full-parameter	LoRA $r=64$, $\alpha=128$	Full-parameter
LoRA target	—	all linear (q/k/v/o + MLP)	—
Epochs / Steps	4 epochs	2 epochs	260 steps
Learning rate	5e−6 (10% warmup)	2e−4 → 2e−5 (cos)	1e−6 (10% warmup)
Eff. batch	32	32	16
Max input len.	8192	8192	8192
Max output len.	—	—	1024

Table 11: Prompt-optimization method hyperparameters. All PO methods use the same 180/400 PO-train/PO-val subset (Apdx. D.1); CoT requires no optimization.

	CoT	MIPROv2	GEPA	SPO4SOP
Task model	gpt-4.1-mini	gpt-4.1-mini	gpt-4.1-mini	gpt-4.1-mini
temperature	0	0	0	0
Optimizer model	—	gpt-5.4-mini	gpt-5.4-mini	gpt-5.4-mini
temperature	—	1	1	1
reasoning	—	low	low	low
Train / Val	—	180 / 400	180 / 400	180 / 400
Budget	—	auto=medium	auto=heavy	$T=6$, batch=30, beam=15
Subset constraint	—	—	—	$K=8$, $\lambda=1.0$
Selection	—	Bayesian	Pareto + Reflection	Reflection + Beam

prompt search, partially explaining their weaker performance on the most label-imbalanced dataset, MIMIC Readmission, reported in Table 4.

Cls-head SFT saliency extraction. For the Cls-head SFT baseline (Qwen3-4B with a classification head, no native reasoning), we generate a token-level pseudo-explanation post-hoc with Captum's `LayerGradientXActivation` (Kokhlikyan et al., 2020) on the input-embedding layer, targeting the predicted-class logit. This attribution gives a signed, magnitude-aware contribution per token, isolating the input tokens that pull the model toward its prediction—the natural candidates for an evidence-like span set. Per-token scores are summed over the hidden dimension and ReLU-clamped (keeping only tokens that support the predicted label); high-saliency spans are then picked by greedy non-maximum suppression over $W=10$-token windows until 400 tokens are accumulated. Selected spans are decoded back to text, yielding the pseudo-reasoning string scored by the NLI and LLM-judge metrics.

D.3 Metrics

Classification performance metrics. Let C be the number of classes and let recall_c, precision_c, $F_{1,c}$ denote the per-class recall, precision, and F_1.

We report:

$$\text{macro-}F_1 = \frac{1}{C} \sum_{c=1}^{C} F_{1,c},$$
$$\text{BAcc} = \frac{1}{C} \sum_{c=1}^{C} \text{recall}_c.$$

Both are unweighted means over classes, robust to label imbalance.

Predictions that fail to parse into a valid label (e.g., format violations, missing LABEL: field) are counted as wrong for the gold class, so an unparseable output contributes one false negative to its true class and zero true positives anywhere. Parse-failure rates are below 1% across all reported runs.

Explanation quality metrics. For each test example we evaluate the model's reasoning trace $\mathbf{r}$ against the dataset-provided evidence $\mathbf{x}_{\text{ev}}$ with two complementary metrics:

- *NLI score*: per-sentence entailment with $\mathbf{x}_{\text{ev}}$ as the premise and each sentence of $\mathbf{r}$ as the hypothesis, scored by MiniCheck-Flan-T5-Large (Tang et al., 2024). We average the per-sentence entailment probability over sentences in $\mathbf{r}$.
- *LLM-judge score*: a G-Eval-style 1–5 Likert rating (Liu et al., 2023) of how well $\mathbf{r}$ is grounded in $\mathbf{x}_{\text{ev}}$, returned by gemini-2.5-flash-lite.

For all metrics higher is better. NLI and LLM-judge are computed only on examples for which evidence is available; coverage is 100% for

Table 12: RL ablation variant hyperparameters, matching the rows of Table 5 (performance). [†] RL runs on ContractNLI override the entropy coefficient to 0.001 for all variants to encourage exploration; ICLR Review and MIMIC use the defaults shown. [‡] B-GRPO is allotted $3\times$ more optimizer steps because, lacking dynamic filtering, each of its steps consumes the same nominal rollout budget but yields a much noisier (mostly zero-advantage) gradient; the longer schedule gives it the wall-clock budget needed to peak (see Fig. 4).

	B-GRPO	D-GRPO	BD-GRPO (III)	BD-GRPO+aux
Init	R-SFT merged	R-SFT merged	R-SFT merged	R-SFT merged
Fine-tuning	Full-param	Full-param	Full-param	Full-param
Learning rate	1e−6	1e−6	1e−6	1e−6
LR warmup	10%	10%	10%	10%
KL coef	0.001	0.001	0.001	0.001
Rollout temp.	1.0	1.0	1.0	1.0
Eff. batch	16	16	16	16
Rollouts (n)	8	8	8	8
Entropy coef[†]	0	0	0	0
Training steps[‡]	780	260	260	260
Clip (low / high)	0.2 / 0.2	0.2 / 0.28	0.2 / 0.28	0.2 / 0.28
Upsampling batch size	—	$6\times$ batch	$6\times$ batch	$6\times$ batch
Class-balanced batch	✓	✗	✓	✓
Aux reward	—	—	—	LLM-judge ($\mathbf{x} \to \mathbf{r}$), $\lambda{=}0.2$

ContractNLI / ICLR_Reviews and $\sim$95% for MIMIC_Readmission (admissions without LACE-derived evidence are excluded).

D.4 LLM-judge details

Two G-Eval-style LLM-judges appear in our pipeline with distinct roles. **(i) Evaluation judge (Groundedness):** scores reasoning $\mathbf{r}$ against the held-out evidence span $\mathbf{x}_{ev}$; powers the explanation-quality metric reported in our results tables. **(ii) Auxiliary reward judge (Faithfulness):** scores reasoning $\mathbf{r}$ against the model input $\mathbf{x}$ (not $\mathbf{x}_{ev}$) as a dense secondary reward during RL training in BD-GRPO + aux ablation (Table 12). We describe each in turn below, then list the per-dataset prompt substitutions shared by both judges in Table 13 at the end of this section.

Evaluation judge: model. We use gemini-2.5-flash-lite (Team, 2025a) accessed through the Google Enterprise Agent Platform (formerly Google Vertex AI), which exposes per-token log-probabilities required for G-Eval-style probability-weighted scoring. gemini-2.5-flash-lite is from a different model family than the task classifier (gpt-4.1-mini) and the student LLM (Qwen3-4B), which could avoid the same-family preference bias of LLM judges (Panickssery et al., 2024).

Evaluation judge: scoring. We extract a continuous score from the judge's output as the expected value $s = \sum_{i=1}^{5} i \cdot p(i)$ over the renormalized top-k token-level probabilities of $\{1,2,3,4,5\}$ at the answer position. The same expected-value extraction is reused by the auxiliary judge below.

Evaluation judge: prompt. The Groundedness prompt template (shared across the three datasets up to two task-specific phrases substituted via PYTHON .format()) is:

Auxiliary judge: motivation and model. We use gpt-4o-mini (OpenAI, 2024) with a G-Eval-style *Faithfulness* rubric (Liu et al., 2023) on the input–reasoning pair $(\mathbf{x}, \mathbf{r})$, *not* the evidence–reasoning pair $(\mathbf{x}_{\text{ev}}, \mathbf{r})$: $\mathbf{x}_{\text{ev}}$ is by construction a near-sufficient determinant of the label (e.g., the ICLR Review meta-review summary is strongly related to the final acceptance decision). Rewarding alignment with $\mathbf{x}_{\text{ev}}$ would leak label-revealing text unavailable to baselines, whereas $\mathbf{x}$ is already the model's inference-time context, so faithfulness to $\mathbf{x}$ is leak-free. The auxiliary judge reuses the same expected-value extraction as the evaluation judge.

Auxiliary judge: prompt. The Faithfulness prompt is shared across the three datasets up to two placeholders, input and task_description:

Auxiliary judge: call cost. With train batch $B{=}16$ prompts per step, rollout group size $G{=}8$, and $T{=}260$ training steps per run, the auxiliary judge is called $B \cdot G \cdot T = 16 \cdot 8 \cdot 260 = 33{,}280$ times per run. Across the three +aux runs (ContractNLI / ICLR Review / MIMIC), this totals $\sim$100k gpt-4o-mini calls.

Auxiliary judge: group-decoupled normalization in BD-GRPO. A naive addition of the auxiliary reward to the binary correctness reward $R_i^{\text{cor}} \in \{-1, +1\}$ would dilute the per-group sparsity that the BD-GRPO oversample-then-filter step explicitly preserves. BD-GRPO drops any rollout group whose correctness reward has $\text{std}(\{R_j^{\text{cor}}\}_{j=1}^{G}) = 0$ because that group carries no contrastive learning signal; pre-mixing a dense

1–5 auxiliary score into the reward would silently let the filter keep groups that have no correctness signal at all. To avoid this we follow the GDPO group-reward-decoupled formulation (Liu et al., 2026): the auxiliary judge is invoked *after* the BD-GRPO filter (so only correctness-signal-bearing groups are scored, halving API cost vs. pre-filter scoring), and the two reward streams are z-scored independently within each surviving group before being summed into a single advantage:

$$\hat{A}_i^{\bullet} = \frac{R_i^{\bullet} - \mathrm{mean}(\{R_j^{\bullet}\}_{j=1}^{G})}{\mathrm{std}(\{R_j^{\bullet}\}_{j=1}^{G}) + \varepsilon}, \quad \bullet \in \{\mathrm{cor}, \mathrm{aux}\},$$

$$\hat{A}_i = \hat{A}_i^{\mathrm{cor}} + \lambda \cdot \hat{A}_i^{\mathrm{aux}}, \qquad \lambda = 0.2.$$

Here mean and std are computed over the $G=8$ rollouts of the same prompt that survive the BD-GRPO filter; rollouts inapplicable to the auxiliary judge prompt (empty reasoning or empty input) receive $\hat{A}_i^{\mathrm{aux}}=0$ and pass through unchanged. Because the two advantages are z-scored independently, the auxiliary contribution stays in the same unit-variance scale as the correctness advantage regardless of how the raw 1–5 Faithfulness scores cluster, and the $\lambda=0.2$ weight keeps its magnitude at roughly one-fifth of the main signal. This is small enough that BD-GRPO's filter decision and the overall optimization direction remain driven by correctness, while still giving the model a smooth, dense secondary signal that shapes which correct rollouts (and which incorrect-but-faithful rollouts) are pushed up or down.

Per-dataset substitutions (both judges). The dataset-specific phrases substituted via PYTHON `.format()` into both prompt templates are listed in Table 13. All other prompt content is identical across the three datasets.

E Additional Experiment Results

This appendix presents results complementing §4: the SPO4SOP validation trajectory across iterations, showing rule-quality progression on all three datasets, and additional qualitative case studies on ICLR Review and ContractNLI (Apdx. E.2).

E.1 SPO4SOP Validation Trajectory

Fig. 9 shows val macro-F_1 over SPO4SOP iterations on all three datasets. Because each iteration's subset search ranges over the entire accumulated rule pool and ranks candidates by validation macro-F_1, the previously selected subset always remains a feasible candidate; the trajectory is therefore non-

Table 13: Per-dataset substitutions for both judge prompt templates. `task_description` is shared between the evaluation judge (Groundedness) and the auxiliary judge (Faithfulness); `evidence_phrase` appears only in the evaluation-judge template; `input` appears only in the auxiliary-judge template.

Dataset	Substitutions
ContractNLI	`task_description`: "decides whether the contract entails, contradicts, or does not mention the hypothesis"
`evidence_phrase`: "the contract clause excerpt"
`input`: "the contract and hypothesis"
ICLR Review	`task_description`: "predicts whether the paper should be accepted or rejected"
`evidence_phrase`: "the meta-review summary"
`input`: "the reviewer comments"
MIMIC Readmission	`task_description`: "predicts whether the patient would be readmitted within 30 days"
`evidence_phrase`: "the patient evidence summary"
`input`: "the discharge summary"

Figure 9: Val macro-F_1 across SPO4SOP iterations, per dataset.

decreasing, up to small fluctuations induced by the beam-search approximation.

E.2 Additional Case Studies

Beyond the MIMIC Readmission teaser (Fig. 1), Figs. 10 and 11 illustrate the same global-rule / local-reasoning interplay on the other two datasets. Each figure pairs an excerpt of a learned SOP rule with a real test case and side-by-side reasoning traces from zero-shot CoT and EXTC.

ICLR Review (Fig. 10). Panel (a) shows Rule 1 from the learned SOP (full rule in Table 19): predict `reject` when reviewer comments contain rejection cues such as "limited novelty" or "missing comparisons", *with the exception* that no reviewer explicitly recommends rejection and the raised con-

cerns are fixable or exploratory. Panel (b) presents a test case where three reviewers raise concerns about "limited novelty" and missing comparisons but none recommends outright rejection, and the criticisms remain fixable. In (b) right, EXTC correctly invokes the rule's exception—identifying the absence of an explicit reject signal and the fixable nature of the concerns—and predicts `accept`. In contrast, (b) left shows zero-shot CoT latching onto the surface critique phrases ("limited novelty," "missing comparisons") and mispredicting `reject`, without weighing that the aggregate reviewer signal is mixed-to-positive.

ContractNLI (Fig. 11). Panel (a) shows Rule 5 from the learned SOP (full rule in Table 18): predict `contradiction` when a contract's cleanup clause requires the receiving party to return or destroy *all* Confidential Information but the hypothesis claims the party may retain some of it, *with the exception* that the contract expressly allows retention of specified categories (archival, legal, backup, etc.). Panel (b) presents a test case where the contract requires "recipient shall return all Confidential Information (including any copies thereof) or certify the destruction thereof"—an all-encompassing return/destroy obligation that contradicts the hypothesis "Receiving Party may retain some Confidential Information." In (b) right, EXTC recognises the rule's trigger pattern (return...or certify destruction of *all* CI) and correctly outputs `contradiction`. In contrast, (b) left shows zero-shot CoT noting the strict return/destroy language but then misjudging the contract as "silent on retention," incorrectly outputting `not_mentioned`.

In both cases the failure mode mirrors the MIMIC example in §4.4: zero-shot CoT over-fires on a surface trigger or under-fires by missing an applicable rule, while EXTC invokes the relevant rule together with its exception. As in MIMIC, EXTC produces its reasoning *without* the SOP in-context at inference time, indicating that the rules have been internalised through distillation and preserved through RL.

F   SPO4SOP **Learned Rules**

F.1   **ContractNLI (5 rules)**

Tables 14–18 list the five rules learned by SPO4SOP for ContractNLI.

F.2   **ICLR Review (2 rules)**

Tables 19 and 20 list the two rules learned by SPO4SOP for ICLR Review.

F.3   **MIMIC Readmission (4 rules)**

Tables 21, 22, 23, and 24 list the four rules learned by SPO4SOP for MIMIC Readmission.

G   PO Baseline Optimized Prompts

For completeness, we include the optimized instruction prompts produced by the MIPROv2 and GEPA baselines, extracted from each method's checkpoint after running on the same 180-row class-balanced train subset (cf. §4.2). Unlike SPO4SOP's modular rule sets, both baselines emit a single monolithic instruction string per dataset.

G.1   **MIPROv2**

Tables 25, 26, and 27 give the MIPROv2-optimized instruction prompts for ContractNLI, ICLR Review, and MIMIC Readmission.

G.2   **GEPA**

Tables 28, 29, and 30 give the GEPA-optimized instruction prompts for ContractNLI, ICLR Review, and MIMIC Readmission.

(a) Example rule from the SOP (excerpt):	[Global Explanation]

Trigger Pattern: Predict `reject` when reviewer comments contain rejection cues (limited novelty / missing comparisons). . . .
Exceptions: no reviewer explicitly recommends rejection and the criticisms are fixable / exploratory. . . .

(b) ICLR Review (excerpt). *Reviewer 1:* "novelty is *limited*; missing comparisons to Chen et al. (2018), nn-RNN, unitary-RNNs." *Reviewer 2:* "interesting exploration of non-normal RNN initialization; plots small; missing reference to Henaff (2016)." *Reviewer 3:* "*method is promising* and paper well written, but comparison with prior work missing."

Zero-shot CoT reasoning:		EXTC **(RL) reasoning:** [Local Explanation]
"Several missing comparisons (Chen 2018, Henaff 2016, nn-RNN) and limited novelty weaken the claim; the paper is not yet ready for acceptance." *Predicted:* `reject` ✗	**V.S.**	"Critiques cite limited novelty / missing comparisons, but no reviewer explicitly rejects and concerns are fixable — net mixed-to-positive." *Predicted:* `accept` (✓)

Figure 10: EXTC **at a glance on ICLR Review. (a)** a rule excerpt from our *learned* rulebook (full rule in Apdx. F, Rule 1); **(b)** on a test case: Zero-shot CoT overfires on the surface critique phrases ("limited novelty," "missing comparisons"), whereas EXTC correctly invokes the rule's *exception* (no explicit reject + fixable concerns).

(a) Example rule from the SOP (excerpt):	[Global Explanation]

Trigger Pattern: Predict `contradiction` when the cleanup clause requires return. . . or destroy all Confidential Information and the hypothesis claims the party may retain some. . . .
Exceptions: Do not apply if the contract allows retention of specified categories (archival / legal / backup). . . .

(b) ContractNLI test case. *Hypothesis:* "Receiving Party may *retain some* Confidential Information even after the return or destruction of Confidential Information." *Contract:* "Recipient shall return all Confidential Information (including any copies thereof) *or certify the destruction* thereof."

Zero-shot CoT reasoning:		EXTC **(RL) reasoning:** [Local Explanation]
"Recipient must return or destroy all CI on request, but the contract is silent on retention afterwards — neither entails nor contradicts." *Predicted:* `not_mentioned` ✗	**V.S.**	"Cleanup clause requires return. . . or certify destruction of all CI — an all-encompassing obligation that contradicts 'may retain some'." *Predicted:* `contradiction` (✓)

Figure 11: EXTC **at a glance on ContractNLI. (a)** a rule excerpt from our *learned* rulebook (full rule in Apdx. F, Rule 5); **(b)** on a test case: Zero-shot CoT reads the cleanup clause but wrongly calls the contract "silent" on retention, whereas EXTC applies Rule 5 (return/destroy-all contradicts "may retain some").

ContractNLI Rule 1 (fires → entailment): Paraphrased NDA Duty or Definition Still Entails

Trigger Pattern: Apply label 1 when the hypothesis is a semantic paraphrase of an express contractual duty or definition, even if the wording is different. Look for 2–3 indicators such as:
– the contract uses different but equivalent legal phrasing, e.g. "oral or written form" = verbally conveyed;
– party-role equivalents like "Recipient" / "Receiving Party";
– broader wording that clearly covers the same fact, such as "existence and nature of this Agreement" covering disclosure that the agreement was agreed or negotiated.
Exceptions: Do not apply this rule if:
– the contract merely discusses a related topic but does not clearly cover the hypothesis;
– the hypothesis requires a stronger or different obligation than the source text;
– the contract language is only tangentially related and not a true semantic match.
Example.
Source text: "Recipient agrees to keep the existence and nature of this Agreement confidential."
Wrong: Label 0 (NotMentioned) for "The Receiving Party shall not disclose the fact that the Agreement was agreed or negotiated."
Correct: Label 1 (Entailment) because confidentiality of the agreement's existence and nature supports nondisclosure of the fact it was negotiated.

Table 14: ContractNLI learned rule 1 (SPO4SOP output).

ContractNLI Rule 2 (fires → contradiction): Broad Confidentiality Scope Does Not Imply Granted Rights

Trigger Pattern: Apply label 2 when the hypothesis makes an exclusive or universal claim about the scope of Confidential Information, but the contract defines Confidential Information more broadly or allows confidentiality to arise without express marking/identification. Common indicators include:
– the hypothesis says Confidential Information "only includes" a narrow category, while the contract lists additional categories such as business, financial, legal, operational, customer, marketing, proprietary, or trade secret information;
– the hypothesis says all Confidential Information must be expressly identified or marked, but the contract covers information that is confidential by nature, known or reasonably known to be confidential, orally identified, or otherwise covered without marking;
– the contract uses broad scope language such as "including, without limitation," "any information," "all information and documents," or an expansive list that clearly exceeds the hypothesis's narrow limit.

Exceptions:
– Do not apply this rule when the hypothesis is about whether the agreement grants a right, license, privilege, or affirmative entitlement to Confidential Information. Broad confidentiality restrictions do not by themselves contradict a statement that no such right is granted; if the contract is silent on granting rights, use NotMentioned.
– Do not apply if the contract merely gives examples that do not clearly expand the scope beyond the hypothesis.
– Do not apply if the text is genuinely silent on the scope issue and does not include broader definitional language or non-marking mechanisms.
– Do not apply if the hypothesis is phrased as a possibility, limitation, or example rather than an exclusivity or universality claim.
– Do not infer contradiction from confidentiality duties alone (e.g., nondisclosure, return, or use restrictions) when the hypothesis concerns the absence of an express grant of rights.

Examples.
Source text: "Confidential Information means any information and documents disclosed by a party, including, without limitation, financial, business, legal, technical, operational, and customer information."
Wrong: Label 0 for "Confidential Information shall only include technical information."
Correct: Label 2, because the contract expressly includes many non-technical categories and therefore contradicts the exclusive technical-only limitation.
Source text: "Receiving Party shall not disclose or use any Confidential Information and shall return all documents containing Confidential Information upon request."
Wrong: Label 2 for "Agreement shall not grant Receiving Party any right to Confidential Information."
Correct: Label 0, because the agreement does not expressly grant any right; it is silent on the specific rights issue.

Table 15: ContractNLI learned rule 2 (SPO4SOP output).

ContractNLI Rule 3 (fires → contradiction): Explicit No-Record Or No-Copy Ban Contradicts Any Claimed Copy Permission

Trigger Pattern: Apply label 2 when the hypothesis asserts that the Receiving Party may copy, duplicate, reproduce, photograph, videotape, record, or preserve some Confidential Information, but the contract expressly prohibits any such activity. Common indicators include:
– phrases like "shall not photograph," "shall not videotape," "shall not make any record of," "shall not copy," "shall not reproduce," or "shall not preserve" Confidential Information;
– an absolute prohibition on creating or retaining records, images, duplicates, or reproductions of Confidential Information;
– broad anti-recording language that covers all forms of reproduction, even if the hypothesis describes only a limited or conditional copy right.

Exceptions: Do not apply this rule if:
– the contract expressly allows copies for a stated purpose, archival use, legal compliance, or with consent;
– the contract only restricts disclosure but does not restrict copying, recording, or preservation;
– the hypothesis concerns retention after return/destruction rather than the act of copying itself;
– the text is silent or ambiguous about recording/copying rights.

Example.
Source text: "Visitor shall not photograph, videotape, or otherwise make any record of or preserve any Confidential Information."
Wrong: Label 0 for "The Visitor may create a copy of some Confidential Information in some circumstances."
Correct: Label 2, because the contract expressly forbids making records or preserving Confidential Information, which directly contradicts any asserted right to copy it.

Table 16: ContractNLI learned rule 3 (SPO4SOP output).

ContractNLI Rule 4 (fires → contradiction): Broad "Authorized Persons" or Similar Internal-Carveout Exceptions Prevent Blanket Third-Party Ban Contradictions

Trigger Pattern: Apply label 2 only when the hypothesis says the Receiving Party may disclose/share Confidential Information with third parties, and the contract truly imposes a blanket ban on third-party disclosure. Use this rule when the contract bars disclosure to any third party in absolute terms, or only allows disclosure through a narrow written-authorization carveout, while the hypothesis claims a general right to share with outsiders.

Exceptions: Do not apply label 2 if the contract:

1. Expressly permits disclosure to a defined third-party category or representative group, including broad terms like "Authorized Persons," consultants, agents, contractors, professional advisors, legal/financial advisors, or accountants.

2. Restricts disclosure to third parties "except as expressly permitted" or otherwise contains an internal carveout that makes the ban non-absolute.

3. Allows disclosure with the prior written consent or other written consent of the Disclosing Party, and the hypothesis is consistent with that consent-based permission.

4. Is merely silent, vague, or ambiguous about third-party disclosure rather than expressly prohibiting it.

5. Uses a broad permitted-recipient definition that can reasonably encompass the hypothesis's examples (e.g., consultants, agents, professional advisors), even if not listed verbatim.

Examples.

Source text: "Receiving Party shall not divulge Confidential Information to any third party for any purpose unless expressly authorized in writing by Disclosing Party."

Wrong: Label 0 for "The Receiving Party may share some Confidential Information with consultants, agents, and professional advisors."

Correct: Label 2, because the contract prohibits third-party disclosure unless written authorization is given, and it does not create a general consultant/agent/advisor exception.

Source text: "Section 3(c) prohibits disclosure to third parties except as expressly permitted under Paragraph 4. Paragraph 4 authorizes disclosure to legal advisors, financial advisors, and accountants. Disclosure may also be made with the prior written consent of the Disclosing Party."

Wrong: Label 2 for "The Receiving Party may disclose Confidential Information to some third parties."

Correct: Label 1, because the contract expressly allows disclosure to certain third-party representatives and by prior written consent.

Source text: "The Receiving Party shall not disclose Confidential Information to any third party, except to the Receiving Party's own Authorized Persons on a need-to-know basis. 'Authorized Persons' means any person or entity authorized to access the Confidential Information for the Purpose and bound by confidentiality obligations at least as protective as this Agreement."

Wrong: Label 2 for "The Receiving Party may share Confidential Information with consultants, agents, and professional advisors."

Correct: Label 1, because the agreement contains an express third-party exception for broadly defined Authorized Persons, which can include those categories.

Table 17: ContractNLI learned rule 4 (SPO4SOP output).

ContractNLI Rule 5 (fires → contradiction): Return/Destroy Clauses Do Not Imply a Right to Make Copies

Trigger Pattern: Apply label 2 when the hypothesis claims the Receiving Party may retain, keep, possess, or make/use copies of Confidential Information after return, destruction, or termination, but the contract requires one or more of the following:
– return all confidential or proprietary materials upon request or termination;
– destroy all such materials or copies;
– not keep copies, duplicates, or retained versions of the information;
– surrender or return all documents/copies without any retention right.
Use this rule when the clause shows a full return/destruction framework and the hypothesis tries to derive a right to retain or possess copies from language that only addresses returning/destroying existing copies.

Exceptions: Do not apply this rule if:
1. The contract expressly allows retention of specific archival, legal, regulatory, or backup copies.
2. The contract is only about return/destruction of existing materials and is silent on post-termination retention; if the hypothesis is about retaining copies, that may be NotMentioned unless retention is prohibited.
3. The hypothesis is about the right to create copies in some circumstances, rather than to keep existing copies after termination; that is a different topic.
4. The contract never addresses copies at all, and the only relevant issue is general copying permission.
5. The hypothesis concerns a different subject unrelated to post-termination possession, return, destruction, or copy retention.

Examples.
Source text: "Upon request or termination, Receiving Party shall return all Information and destroy all materials containing Information and shall not keep copies or duplicates thereof."
Wrong: Label 0 for "The Receiving Party may retain some Confidential Information even after return or destruction."
Correct: Label 2, because the contract expressly requires return/destruction and forbids keeping copies or duplicates, which conflicts with any post-return retention right.
Source text: "Upon termination, Recipient shall promptly return or destroy all Confidential Information and all copies thereof."
Wrong: Label 2 for "Recipient is permitted to make copies of Confidential Information for use during the term."
Correct: Label 0, because the clause only requires returning or destroying existing copies after termination; it does not address whether copying is allowed in the first place.

Table 18: ContractNLI learned rule 5 (SPO4SOP output).

ICLR Review Rule 1 (fires → reject): Positive-leaning Mixed Reviews Override Critique

Trigger Pattern: Apply this rule when reviewer comments contain both praise and criticism, but the model is tempted to predict rejection just because it sees negative phrases. Typical rejection cues include:
– explicit reject / lean reject / cannot recommend acceptance / not strong enough / not the right venue,
– criticism of novelty, contribution size, positioning, applicability, baselines, clarity, or rigor,
– post-rebuttal remarks that remain skeptical.

Exceptions: Do not apply this rule if any of the following hold:
1. One or more reviewers explicitly recommend acceptance, marginal-accept, or clearly revise upward after rebuttal.
2. The overall discussion is mixed-to-positive: substantive praise for novelty, usefulness, clarity, significance, strong results, or impact outweighs the concerns.
3. The criticisms are mainly fixable or exploratory issues (extra ablations, more comparisons, clarification, code, presentation, sensitivity analysis) rather than fatal methodological flaws.
4. Positive language is substantive endorsement of the paper's contribution, not mere politeness.
5. A single rejection-leaning review should not dominate if other reviewers are positive or acceptance-leaning, especially when the negative review itself is mixed and ends with openness to revision.

Examples.
Source text: "The idea is interesting and the paper is well written, but the contribution feels incremental, the experiments are insufficient, and I still cannot recommend acceptance."
Wrong: Predict label 1 because of "interesting" and "well written."
Correct: Predict label 0 because the final stance and substantive critiques are rejection-leaning.
Source text: "Overall, I think this is a good paper and I recommend acceptance. There are some concerns about ablations and presentation, but they seem fixable."
Wrong: Predict label 0 because of the concerns and criticism.
Correct: Predict label 1 because the review explicitly recommends acceptance and the negatives are minor.
Source text: "The method is promising and the results are strong. I have concerns about missing comparisons and would like more analysis, but I revised my assessment from marginal-reject to marginal-accept."
Wrong: Predict label 0 because of the earlier skepticism.
Correct: Predict label 1 because the final recommendation is acceptance-leaning and the concerns are not decisive.
Source text: "I enjoyed reading this paper. The idea is natural, useful, and has interesting potential applications. I would be willing to upgrade my review if points 2 and 3 are addressed."
Wrong: Predict label 0 because of the concerns about methodology and missing ablations.
Correct: Predict label 1 because the review is substantively positive and explicitly open to upgrading.
Source text: "This is a valuable and novel benchmark; the results are promising and competitively strong. Although one reviewer is more critical, the overall set of reviews is positive and the remaining concerns are mostly about clarification and extra comparisons."
Wrong: Predict label 0 because of the critical review and requests for more analysis.
Correct: Predict label 1 because the aggregate signal is acceptance-leaning and the issues are not fatal.

Table 19: ICLR Review learned rule 1 (SPO4SOP output).

ICLR Review Rule 2 (fires → reject): Reject Only When Negative Signal Dominates, Not When Positives Outweigh Cautions

Trigger Pattern: Apply this rule when the review set has some positive or acceptance-leaning language, but the overall consensus is still clearly rejection-leaning. Typical cues:
– one reviewer is favorable while others explicitly reject or remain strongly unconvinced,
– multiple reviews say the paper is only a minor extension, lacks novelty, or has weak justification/experiments,
– criticisms focus on core merit: novelty, validity, robustness, theoretical support, or impact,
– the aggregate tone is mixed-to-negative overall, not merely cautious.

Exceptions: Do not apply this rule if:
1. Two or more reviewers explicitly recommend acceptance, or clearly lean acceptance, and the negative comments are secondary.
2. The unfavorable review is an outlier while the other reviews are broadly positive or supportive.
3. The main issues are requests for more ablations, baselines, sensitivity tests, clearer framing, or related-work discussion, without questioning the paper's central merit.
4. Reviews contain explicit praise such as "novel," "promising," "interesting," "useful," "state of the art," or "good contribution," and these positives are echoed by multiple reviewers.
5. Mixed reviews still conclude with practical value or endorsement of the approach, especially when comments emphasize presentation/coverage limitations rather than fatal flaws.

Examples.
Source text: "Reviewer 1: good writing, but the gains are not convincing. Reviewer 2: this is a minor extension with weak experiments. Reviewer 3: promising, but I still recommend rejection due to low novelty."
Wrong: Predict label 1 because one reviewer used positive language.
Correct: Predict label 0 because the strongest and majority signal is rejection-leaning.
Source text: "Reviewer 1: the idea is novel and useful, but I need more ablations. Reviewer 2: promising results and a nice theoretical foundation; lean reject only because of missing comparisons. Reviewer 3: innovative approach with good potential. Reviewer 4: nice contribution, state-of-the-art performance, and a variety of datasets."
Wrong: Predict label 0 because some reviewers mention concerns and one leans reject.
Correct: Predict label 1 because multiple reviewers are clearly positive and the concerns are secondary.

Table 20: ICLR Review learned rule 2 (SPO4SOP output).

MIMIC Readmission Rule 1 (fires → readmitted): Unresolved Diagnostic Workup Only When Pending Result Could Change Immediate Management

Trigger Pattern: Apply label 1 when discharge happens before a clinically important diagnostic/treatment pathway is truly finished, especially when the summary shows:
1. Pending pathology, cytology, biopsy, molecular testing, or other results that may change near-term management.
2. Active concern for malignancy or another serious disease based on imaging, tumor markers, specialist concern, or uncertain diagnosis.
3. Explicit near-term specialty follow-up for reassessment, staging, or treatment planning within days to a few weeks.

Exceptions: Do not apply label 1 for:
1. Routine post-procedure or post-op pathology when the main inpatient problem has been treated, the patient is clinically stable, and follow-up is routine outpatient review.
2. Diagnosis already established during admission with only a confirmatory pending test or part of standard cancer follow-up, with outpatient oncology/neurosurgery already arranged.
3. Routine monitoring labs or pending tests (e.g., viral load, HIV, standard infection workup, echo/cath results, repeat echo) with no major diagnostic uncertainty and no immediate management change expected.
4. Chronic/known disease managed long-term when the acute hospitalization issue is resolved, even if outpatient specialty follow-up continues.
5. Routine/non-urgent surveillance or elective outpatient treatment, or when the patient is stable for discharge without urgent reassessment; also when the admission was complicated by treated issues (acute systolic HF/AKI/bridging anticoagulation/low EF) but the discharge plan is stable outpatient management.

Examples.
Source text: "Pleural effusion drained; cytology/pathology pending; imaging concerning for malignancy / lymphadenopathy; oncology follow-up in 2 weeks; discharged home stable."
Wrong: Predict label 0 because the acute symptoms improved and the patient went home.
Correct: Predict label 1 because the underlying disease is not resolved and near-term reassessment may lead to further hospitalization or intervention.
Source text: "Post-op recovery after colectomy; pathology pending; ambulating, tolerating diet, pain controlled; routine surgical follow-up planned; discharged home in stable condition."
Wrong: Predict label 1 because any pending pathology means high readmission risk.
Correct: Predict label 0 because this is routine post-operative pathology after a completed treatment, not an unresolved high-risk diagnostic workup.
Source text: "Known metastatic brain lesion resected; post-op imaging reassuring; final pathology pending; routine brain tumor clinic follow-up; discharged home with services."
Wrong: Predict label 1 because pathology is still pending.
Correct: Predict label 0 because the lesion was already known, surgery was completed, and the pending pathology is routine post-op confirmation, not an unfinished urgent diagnostic pathway.
Source text: "APML confirmed on marrow cytology with t(15;17); completed inpatient idarubicin, continued ATRA; pending PCR translocation test; stable for discharge with heme/onc follow-up."
Wrong: Predict label 1 because a cancer-related lab is pending.
Correct: Predict label 0 because the diagnosis was already established and the pending test is routine outpatient follow-up.

Table 21: MIMIC Readmission learned rule 1 (SPO4SOP output).

MIMIC Readmission Rule 2 (fires → readmitted): Complicated Postoperative Discharge With Foley or Unresolved Recovery Milestone

Trigger Pattern: Apply label 1 when the discharge summary shows a recent major surgery plus unresolved short-term postoperative complications that still require active management after discharge. Strong indicators include:
– failed voiding trial, urinary retention, high post-void residuals, or discharge with an indwelling Foley catheter,
– need for catheter-related prophylaxis, device care, or planned early catheter removal follow-up,
– persistent postoperative issues such as wound drainage, infection concern, ileus, uncontrolled pain, or significant anemia requiring close follow-up.

Exceptions: Do not apply this rule for routine postoperative discharges with no unresolved complication, no device dependence, and no early follow-up for a specific recovery problem.

Example.
Source text: "Total abdominal hysterectomy with sling/cystoscopy complicated by urinary retention; failed voiding trial, discharged home with Foley catheter, nitrofurantoin prophylaxis, and follow-up for catheter removal."
Wrong: Predict label 0 because the patient was discharged home and described as stable.
Correct: Predict label 1 because the postoperative course was not resolved and Foley/device dependence with early follow-up creates high 30-day return risk.

Table 22: MIMIC Readmission learned rule 2 (SPO4SOP output).

MIMIC Readmission Rule 3 (fires → readmitted): High-Risk Obstetric Discharge With Persistent Preterm-Birth Threat

Trigger Pattern: Apply label 1 when a pregnant patient is discharged after a threatened preterm labor / cervical insufficiency admission and the pregnancy remains high risk and unresolved. Strong indicators include:
– cervical shortening, funneling, or dilation despite treatment,
– need for magnesium sulfate, cerclage-related management, bedrest/pelvic rest, progesterone change, or NICU counseling,
– high-risk features such as twin gestation, prior preterm birth, breech presentation, or planned imminent steroids/close follow-up.
Exceptions: Do not apply label 1 for routine uncomplicated obstetric admissions with no cervical change, no threatened preterm labor, and no ongoing high-risk pregnancy issue.
Example.
Source text: "23-week pregnancy with short cervix, funneling to cerclage, 1 cm dilation, modified bedrest and pelvic rest, progesterone changed, NICU consulted, betamethasone planned soon."
Wrong: Predict label 0 because there was no infection or active labor at discharge.
Correct: Predict label 1: imminent preterm delivery in this high-risk pregnancy is the dominant near-term driver of readmission, even without current infection or active labor.

Table 23: MIMIC Readmission learned rule 3 (SPO4SOP output).

MIMIC Readmission Rule 4 (fires → readmitted): Decompensated Cirrhosis Only — Exclude Malignant Ascites, Hospice Decline, and In-Hospital Transfer

Trigger Pattern: Apply label 1 when discharge occurs after severe decompensation of chronic liver disease/cirrhosis with ongoing near-term risk. Strong indicators include:
– advanced cirrhosis/liver failure with hepatic encephalopathy, portal-hypertensive ascites, hyponatremia, variceal/other liver-related bleeding, AKI/HRS physiology, or transfusion-requiring anemia
– recurrent hepatic decompensation or very high severity markers (e.g., high MELD, repeated admissions, medication nonadherence triggering the event)
– discharge with ongoing need for close lab monitoring, diuretics/lactulose adjustment, repeat paracentesis, or active liver-management follow-up
Exceptions: Do not apply label 1 if:
1. The ascites/instability is due to malignancy, terminal cancer, or general functional decline rather than cirrhosis/liver failure.
2. There is no clear evidence of cirrhosis/portal hypertension/hepatic encephalopathy/MELD-based liver failure.
3. A single paracentesis or supportive treatment is for malignant ascites and not recurrent cirrhotic decompensation.
4. The acute issue is treated and improving, and the remaining plan is mainly palliative/hospice/disposition planning rather than ongoing cirrhosis instability.
5. The case is not a completed discharge after stabilization, but instead an in-hospital transfer to another facility/higher level of care (e.g., transplant evaluation) for ongoing inpatient management. Do not label 1 solely because of severe labs/ascites if the transition is transfer-driven rather than a standard discharge home.
6. The chronic liver disease is clearly compensated or follow-up is routine without ongoing instability.
Examples.
Source text: "Advanced alcoholic cirrhosis with hepatic encephalopathy from lactulose nonadherence, acute on chronic severe anemia requiring 2 units PRBCs, large ascites requiring therapeutic paracentesis, hyponatremia, MELD 30, discharged after partial improvement with close follow-up."
Wrong: Predict label 0 because the patient was clinically improved at discharge.
Correct: Predict label 1 because this is a highly decompensated chronic illness with persistent near-term risk of recurrence and readmission.
Source text: "Metastatic breast and pancreatic cancer with worsening malignant ascites, diarrhea, dehydration, hypotension, and hypoxemia; paracentesis performed; symptoms improved; discharge planning focused on rehab then hospice."
Wrong: Predict label 1 because there is ascites, paracentesis, and severe medical instability.
Correct: Predict label 0 because this is malignancy-related decline with malignant ascites and palliative disposition, not decompensated cirrhosis/liver failure.
Source text: "Alcoholic cirrhosis with ascites, encephalopathy, hyponatremia, and very high bilirubin/INR; C. diff and UTI treated with improvement; transferred to tertiary center for transplant evaluation and ongoing inpatient management."
Wrong: Predict label 1 because of the severe liver labs, ascites, and encephalopathy.
Correct: Predict label 0 because this is an in-hospital transfer for higher-level care/transplant evaluation, not a standard discharge after stabilization with outpatient readmission risk.

Table 24: MIMIC Readmission learned rule 4 (SPO4SOP output).

MIPROv2 optimized prompt for ContractNLI

You are a contract analyst performing 3-way natural language inference on NDA clauses.
Label 'not_mentioned' (0): the contract is silent on the hypothesis.
Label 'entailment' (1): the contract entails the hypothesis.
Label 'contradiction' (2): the contract contradicts the hypothesis.
Important:
– Do not judge whether the clause is desirable or compliant in general.
– Only decide whether the contract text entails, contradicts, or stays silent on the hypothesis.
Output your final label as an integer: 0 for 'not_mentioned', 1 for 'entailment', 2 for 'contradiction'.

Table 25: MIPROv2-optimized instruction prompt for ContractNLI.

MIPROv2 optimized prompt for ICLR Review

You are a meta-reviewer aggregating multiple reviewer comments for a conference paper and deciding whether the paper should be accepted.
Task:
– Read the full reviewer comments only.
– Infer the reviewers' collective recommendation from the comments, not from the paper itself.
– Decide whether the overall sentiment implies 'accept' or 'reject'.
Guidelines:
– Base your decision on the balance of strengths vs. weaknesses in the reviews.
– Give strong weight to explicit recommendation language such as "accept," "weak accept," "reject," "weak reject," "recommend accept," or "cannot recommend acceptance."
– Accepted papers are typically described as novel, clear, technically sound, and backed by strong experiments.
– Rejected papers are typically described as incremental, unclear, methodologically weak, insufficiently validated, or lacking convincing experiments/baselines/ablations.
– If reviewers mention rebuttals or polite author replies, do not treat them as evidence of acceptance unless the reviews clearly change their recommendation.
– Judge the collective implication of all reviews together, even if individual reviews disagree.
Output requirements:
– First provide brief reasoning that cites the most relevant review evidence.
– Then output the final binary label as an integer:
'0' = reject
'1' = accept

Table 26: MIPROv2-optimized instruction prompt for ICLR Review.

MIPROv2 optimized prompt for MIMIC Readmission

You are a clinical reviewer tasked with predicting 30-day hospital readmission risk from a single discharge summary.

Your job:
– Read the discharge summary carefully.
– Decide whether the patient is likely to be readmitted within 30 days of discharge.
– Use only the information present in the discharge summary. Do not use outside knowledge, assumptions, or patient history not explicitly stated.
– The majority of cases are not readmitted, so prefer '0' unless the text contains clear evidence of high risk.

Label meanings:
– '0' = 'not_readmitted'
– '1' = 'readmitted'

What to look for:
Signs of higher readmission risk:
– unresolved or worsening medical problems at discharge
– postoperative complications, infections, wound issues, bleeding, respiratory failure, sepsis, or organ dysfunction
– repeated admissions, return visits, or transfer to higher levels of care
– significant frailty, bedbound status, malnutrition, or unstable vitals/labs
– complex multimorbidity with heavy follow-up needs, rehabilitation, wound vacs, oxygen, IV antibiotics, or frequent monitoring
– discharge to rehab/extended care because the patient is not stable enough for home
– discharge instructions that imply ongoing active disease rather than recovery
Signs of lower readmission risk:
– uncomplicated recovery
– stable vital signs and labs
– pain controlled, tolerating diet, ambulating, voiding, and medically stable
– discharge home with routine follow-up and no major unresolved issues
– no evidence of active infection, complication, or persistent instability

Reasoning guidance:
– Base your decision on the overall clinical picture, giving most weight to the HPI, hospital course, results, discharge condition, and discharge disposition/instructions.
– If the summary shows clear recovery and stable discharge, output '0'.
– If the summary shows major complications, ongoing infection, unstable condition, or significant post-discharge medical needs, output '1'.
– Provide a brief reasoning trace that cites relevant evidence from the note, then output the final integer label.

Output format:
– First give 'Reasoning: . . . '
– Then give 'Label: 0' or 'Label: 1'

Table 27: MIPROv2-optimized instruction prompt for MIMIC Readmission.

GEPA optimized prompt for ContractNLI

You are a legal contract NLI classifier for NDA-style agreements.
Task: Given a contract excerpt and a hypothesis, decide whether the contract text:
– 'not_mentioned' (0): is silent on the hypothesis,
– 'entailment' (1): clearly states or logically guarantees the hypothesis,
– 'contradiction' (2): clearly states the opposite of the hypothesis.
Important rules:
– Use only the contract text. Do not use outside legal knowledge.
– Do not judge whether a clause is good practice, standard, fair, or compliant.
– Focus only on whether the contract text itself entails, contradicts, or says nothing about the hypothesis.
– Be strict: if the contract does not clearly address the exact issue, label it 'not_mentioned'.
– Do not infer broad meaning from general confidentiality language unless the text directly supports the exact hypothesis.
– General confidentiality duties do NOT automatically imply other restrictions, permissions, exceptions, or rights.
– If the contract contains an explicit exception, carve-out, permission, prohibition, or definition that directly matches the hypothesis, use that.
– If the hypothesis uses generic NDA roles, map them to the contract's actual parties:
Receiving Party = Recipient / RECIPIENT / Contractor / Supplier / similar
Disclosing Party = Company / PROVIDER / JHU / Owner / similar
How to decide:
1. entailment *(1)*
– The contract expressly says the hypothesis is true, or
– The contract's wording makes the hypothesis unavoidable.
– Example: "Recipient may disclose Confidential Information if required by law" entails a lawful-disclosure exception.
– Example: "Information received from a third party not under an obligation of confidentiality" entails a third-party-source carve-out.
2. contradiction *(2)*
– The contract expressly says the opposite of the hypothesis.
– Example: if the hypothesis says "Recipient may disclose to third parties," but the contract says "Recipient shall not disclose to any third party except as authorized," that is contradiction.
– Example: if the hypothesis says "Confidential Information includes publicly available information," but the contract says publicly available information is excluded, that is contradiction.
3. not_mentioned *(0)*
– The contract is silent or only discusses related but not identical matters.
– Do not infer unrelated provisions.
– A clause saying information is confidential, must not be disclosed, or may be shared only with authorized persons does not by itself entail: non-solicitation, non-compete, no-hire, assignment, rights/grant of license, ownership transfer, arbitration, venue, or other separate obligations unless explicitly stated.
– If the contract does not explicitly grant rights or licenses, do not assume a hypothesis about rights being granted or not granted unless the text clearly says so.
NDA-specific guidance:
– Common NDA clauses include: definitions of Confidential Information, exclusions for public domain, prior knowledge, independent development, third-party sources, permitted use restrictions, permitted disclosure to employees/representatives/advisors, compelled disclosure by law or court order, return/destruction of materials, term/duration, no license / no rights clauses, governing law / venue.
– Third-party-source language matters only if the clause explicitly says information from another source is excluded or allowed.
– Public-domain exclusions matter only if the clause actually states the information is public or becomes public.
– Independent-development exclusions matter only if the contract says the information was developed independently.
– If a clause says information is confidential "in any form," do NOT automatically infer that oral/verbal communications are included unless the text clearly covers them. For example, "in any form" alone does not necessarily entail "verbally conveyed information" unless the contract explicitly includes oral, verbal, spoken, or non-written information.
– If the definition requires information to be "designated as confidential," "indicated as confidential," or similar, then the label depends on that requirement.
– If the contract says confidential information may be shared with employees/representatives who have a need to know and are bound by the agreement, that entails limited internal sharing only under those conditions.
– If the contract says disclosure is allowed when required by law or court order, that entails a compelled-disclosure exception.
– If the contract says nothing about a specific topic, do not infer it from the general purpose of the NDA.
Strictness reminders:
– Prefer 'not_mentioned' unless the contract text clearly and directly supports entailment or contradiction.
– Do not upgrade a general phrase into a specific legal proposition.
– Do not use common drafting patterns as if they were present unless the text actually contains them.
– If the hypothesis is more specific than the text, label 'not_mentioned'.
Input format: You will receive a contract excerpt under a 'Contract:' heading and a hypothesis under a 'Hypothesis:' heading.
Output format: Return only the final integer label: '0' for not_mentioned, '1' for entailment, '2' for contradiction. Do not provide reasoning, explanation, or any extra text.

Table 28: GEPA-optimized instruction prompt for ContractNLI.

GEPA optimized prompt for ICLR Review

You are a meta-review labeler for conference paper reviews.

Your task: Given ONLY the reviewer comments for a paper, infer whether the collective review outcome is closer to acceptance or rejection.

Output labels: 'accept' → output '1'; 'reject' → output '0'.

Input format you will receive:
– A block of text containing one or more reviewer entries.
– Each reviewer may have fields like 'summary_of_the_paper', 'main_review', 'strengths', 'weaknesses', 'summary_of_the_review', or an update after rebuttal.
– Use only the reviewer text; do not rely on any paper content outside the reviews.

Decision rules:
1. Base your decision on the collective implication of the reviews, not on isolated positive or negative sentences.
2. Do not count polite tone, gratitude, or soft language as evidence of acceptance.
3. If a reviewer mentions rebuttal or author response, only treat it as positive if the reviewer explicitly says their rating increased, their concerns were addressed, or they now support acceptance.
4. If the reviews are mixed but the overall implication is clearly "acceptable with revisions", "would not oppose acceptance", "inclined to accept", "worth accepting", or a score was raised toward acceptance, label 'accept'.
5. If the reviews collectively emphasize substantial problems, especially any of the following, label 'reject':
– limited novelty / incremental contribution
– weak, incomplete, or unconvincing experiments
– only one domain/task, especially a narrow synthetic/toy/artificial setup, with no broader validation
– poor or missing baselines/comparisons
– unclear generalization or narrow applicability
– insufficient rigor, unclear analysis, or missing motivation that prevents publication readiness
6. Positive remarks such as "well written", "interesting", "important problem", or "technically sound" are not enough for 'accept' if major concerns remain.
7. If a reviewer explicitly recommends rejection, treat that as a strong negative signal unless other reviews clearly and explicitly support acceptance overall.
8. If most reviewers are constructive and overall supportive, accept.
9. If the main objections are about presentation/clarity only, but the results and novelty are otherwise strong and reviewers lean positive, accept.
10. If the main objections are about novelty, scope, applicability, missing experiments, missing comparisons, or weak validation, reject even when the paper is described positively in other respects.

Useful aggregation strategy:
– Pay special attention to final recommendation language and score changes.
– Weigh explicit statements like "recommend accept", "inclined to accept", "happy to increase the rating", "not ready for publication", or "do not recommend acceptance" more than detailed minor comments.
– If the reviews contain a positive trajectory after rebuttal, that is a strong accept signal only when the reviewer explicitly says so.
– If the reviews repeatedly say the method is novel/promising but also say it lacks sufficient validation, is too narrow, or is not ready for publication, the decision should usually be 'reject'.
– In borderline cases, prefer 'reject' when major weaknesses remain unresolved.

Output requirements: Return only a single integer ('1' for accept, '0' for reject). Do not include any explanation, reasoning, or extra text.

Table 29: GEPA-optimized instruction prompt for ICLR Review.

GEPA optimized prompt for MIMIC Readmission

You are a clinical reviewer classifying 30-day hospital readmission risk from discharge summaries.
Task: Read only the discharge summary text provided. Decide whether the patient is likely to be readmitted to the hospital within 30 days after discharge. Output exactly one integer: 0 = not_readmitted; 1 = readmitted.
Core rule: Default to 0. Only choose 1 when the discharge summary itself strongly suggests a substantial near-term likelihood of rehospitalization.
What counts as strong evidence for 1:
– The patient is discharged with an ongoing unstable or unresolved acute illness.
– Symptoms or objective findings are still worsening, refractory, or not controlled at discharge.
– A complication of the admission is still active and likely to require imminent inpatient care.
– The note explicitly suggests planned return, anticipated readmission, inability to stabilize, or failure of outpatient management.
– Recurrent decompensation is clearly active in this admission and the discharge condition remains poor.
– There is clear ongoing danger of near-term failure of outpatient treatment.
– The summary says the patient is still clinically unstable, not improving, or only partially treated.
– Positive blood cultures / bacteremia that are not fully resolved at discharge, especially when speciation is still pending, source control is incomplete, or treatment is being continued but the infection is not clearly cured.
– Incomplete source control for serious infection, especially when ongoing drainage, repeat procedures, or persistent collections are still expected.
– Ongoing hemodynamic instability, need for ICU-level support, or repeated desaturations close to discharge.
– Discharge with a clearly unresolved major acute problem and no convincing stabilization.
What usually still counts as 0:
– Stable discharge to home, rehab, SNF, or extended care facility.
– Stable vital signs, improving symptoms, controlled pain, tolerating diet, breathing comfortably, ambulatory, alert, interactive, or otherwise "stable for discharge."
– Routine postoperative care, even after major surgery, if the course is uncomplicated and the patient is stable.
– Serious diagnoses alone do NOT imply readmission risk.
– Chronic or complex comorbidities alone do NOT imply readmission risk.
– Discharge with services, oxygen, walker, brace, anticoagulation, antibiotics, drains, or follow-up appointments does NOT by itself mean 1.
– Hospice / comfort-focused discharge generally points to 0 unless the summary explicitly predicts imminent return.
– Discharge on oral antibiotics after a clearly improving infection is usually 0 if the note shows the infection is controlled and the patient is stable.
– A drain left in place can still be 0 if the patient is otherwise stable, the collection has been adequately drained, and outpatient follow-up is the plan.
Important nuance:
– Do NOT label 1 just because the patient has cancer, metastatic disease, stroke, pulmonary embolism, fracture, surgery, heart failure, atrial fibrillation, CKD, dementia, diabetes, or other serious diagnoses.
– Do NOT label 1 just because the patient is medically complex, elderly, frail, disabled, or needs rehab / nursing care.
– Do NOT label 1 just because the discharge plan includes chemotherapy, port placement, outpatient biopsy, specialist follow-up, repeat imaging, lab monitoring, or drain care.
– Do NOT label 1 just because anticoagulation is prescribed or temporarily held/restarted.
– Do NOT label 1 just because there are residual deficits, if the summary says the patient is otherwise stable and discharge-ready.
– Do NOT label 1 just because the patient needs home oxygen, BiPAP, antibiotics, or routine follow-up, unless the note clearly shows persistent instability.
– Do NOT label 1 for "poor prognosis" alone if the patient is actually stable for discharge and no near-term rehospitalization is suggested.
How to interpret common discharge situations:
– Post-op orthopedic / spine / trauma admissions: label 0 if the procedure was uncomplicated, neuro exam is intact/stable, pain is controlled, wound is fine, and the patient is discharged in a stable state.
– Stroke / neurologic admissions: label 0 if the patient is stable/improving, even if residual deficits remain, unless the note clearly indicates ongoing instability or imminent return.
– Cancer admissions: label 0 if the patient is stable, discharged home or to rehab, and the plan is outpatient oncology workup or treatment.
– GI bleed / anemia / infection: label 0 if bleeding is controlled, infection treated, labs/vitals stabilized, and no active deterioration remains.
– PE / anticoagulation: label 0 if the PE is treated and the patient is stable for discharge.
– Discharge to rehab, extended care, or SNF: still usually 0 if clinically stable.
– Infection with drains or IV antibiotics: label 0 if source control is achieved, the patient is improving, and the note does not indicate persistent uncontrolled infection.
– However, label 1 if there is persistent or inadequately controlled infection, ongoing fevers/worsening sepsis, or unresolved bacteremia/positive cultures with unclear cure at discharge.
Strategy:
1. Check the discharge condition and overall course first.
2. Look for explicit instability, deterioration, or expected near-term return.
3. If the summary says stable, improved, controlled, hemodynamically stable, breathing comfortably, alert, or ready for discharge, choose 0.
4. If the summary says unresolved acute problems are still active and likely to rebound quickly, choose 1.
5. Give extra weight to unresolved bacteremia, persistent sepsis, pending speciation with positive blood cultures, incomplete source control, and explicit concern that outpatient management may fail.
6. When in doubt, choose 0.
Output format: Return only the integer label. Do not explain your answer. Do not output any extra text.

Table 30: GEPA-optimized instruction prompt for MIMIC Readmission.